

FCC Test Report (2.4GHz WLAN)

Report No.: RFBEMI-WTW-P21070601

FCC ID: XHHBNRV1100-A

Test Model: BNRV1100

Received Date: 2020/11/2

Test Date: 2021/9/3 ~ 2021/9/29

Issued Date: 2021/10/28

Applicant: Nook Digital LLC

Address: 33 E 17th Street, New York, NY 10003 United States Of America

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan

**FCC Registration /
Designation Number:** 723255 / TW2022



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	4
1 Certificate of Conformity.....	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty	6
2.2 Modification Record	6
3 General Information.....	7
3.1 General Description of EUT (2.4GHz WLAN)	7
3.2 Description of Test Modes	9
3.2.1 Test Mode Applicability and Tested Channel Detail	10
3.3 Duty Cycle of Test Signal	12
3.4 Description of Support Units	13
3.4.1 Configuration of System under Test	13
3.5 General Description of Applied Standards and References	14
4 Test Types and Results	15
4.1 Radiated Emission and Bandedge Measurement.....	15
4.1.1 Limits of Radiated Emission and Bandedge Measurement	15
4.1.2 Test Instruments	16
4.1.3 Test Procedures.....	19
4.1.4 Deviation from Test Standard	19
4.1.5 Test Setup.....	20
4.1.6 EUT Operating Conditions.....	21
4.1.7 Test Results (Mode 1).....	22
4.1.8 Test Results (Mode 2).....	36
4.2 Conducted Emission Measurement	38
4.2.1 Limits of Conducted Emission Measurement	38
4.2.2 Test Instruments	38
4.2.3 Test Procedures.....	39
4.2.4 Deviation from Test Standard	39
4.2.5 Test Setup.....	39
4.2.6 EUT Operating Conditions.....	39
4.2.7 Test Results	40
4.3 6dB Bandwidth Measurement	42
4.3.1 Limits of 6dB Bandwidth Measurement	42
4.3.2 Test Setup.....	42
4.3.3 Test Instruments	42
4.3.4 Test Procedure	42
4.3.5 Deviation from Test Standard	42
4.3.6 EUT Operating Conditions.....	42
4.3.7 Test Result.....	43
4.4 Conducted Output Power Measurement.....	45
4.4.1 Limits of Conducted Output Power Measurement	45
4.4.2 Test Setup.....	45
4.4.3 Test Instruments	45
4.4.4 Test Procedures.....	45
4.4.5 Deviation from Test Standard	45
4.4.6 EUT Operating Conditions.....	45
4.4.7 Test Results	46
4.5 Power Spectral Density Measurement.....	48
4.5.1 Limits of Power Spectral Density Measurement	48
4.5.2 Test Setup.....	48
4.5.3 Test Instruments	48
4.5.4 Test Procedure	48
4.5.5 Deviation from Test Standard	48

4.5.6 EUT Operating Condition	48
4.5.7 Test Results	49
4.6 Conducted Out of Band Emission Measurement	51
4.6.1 Limits of Conducted Out of Band Emission Measurement.....	51
4.6.2 Test Setup.....	51
4.6.3 Test Instruments	51
4.6.4 Test Procedure	51
4.6.5 Deviation from Test Standard	51
4.6.6 EUT Operating Condition	51
4.6.7 Test Results	51
5 Pictures of Test Arrangements.....	56
Annex A - Band-Edge Measurement.....	57
Appendix – Information of the Testing Laboratories	61

Release Control Record

Issue No.	Description	Date Issued
RFBEMI-WTW-P21070601	Original release.	2021/10/28

1 Certificate of Conformity

Product: EBOOK READER

Brand: Nook

Test Model: BNRV1100

Sample Status: Engineering sample

Applicant: Nook Digital LLC

Test Date: 2021/9/3 ~ 2021/9/29

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)
ANSI C63.10: 2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : Evy Chen, **Date:** 2021/10/28
Evy Chen / Specialist

Approved by : Clark Lin, **Date:** 2021/10/28
Clark Lin / Technical Manager

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	Pass	Meet the requirement of limit. Minimum passing margin is -9.83 dB at 0.15781 MHz.
15.205 / 15.209 / 15.247(d)	Radiated Emissions and Band Edge Measurement	Pass	Meet the requirement of limit. Minimum passing margin is -0.2 dB at 2390.00 MHz, 2483.50 MHz.
15.247(d)	Antenna Port Emission	Pass	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	Pass	Meet the requirement of limit.
15.247(b)	Conducted power	Pass	Meet the requirement of limit.
15.247(e)	Power Spectral Density	Pass	Meet the requirement of limit.
15.203	Antenna Requirement	Pass	No antenna connector is used.

Note:

- For 2.4 GHz band compliance with rule 15.247(d) of the band-edge items, the test plots were recorded in Annex A.
- Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) ($\pm$)
Conducted Emissions at mains ports	150kHz ~ 30MHz	1.9 dB
Conducted emissions	-	2.5 dB
Radiated Emissions up to 1 GHz	9kHz ~ 30MHz	3.1 dB
	30MHz ~ 1GHz	5.1 dB
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	5.1 dB
	18GHz ~ 40GHz	5.3 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT (2.4GHz WLAN)

Product	EBOOK READER
Brand	Nook
Test Model	BNRV1100
Status of EUT	Engineering sample
Power Supply Rating	DC 5V from USB interface or DC 3.7V from battery
Modulation Type	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
Modulation Technology	DSSS, OFDM
Transfer Rate	802.11b: up to 11 Mbps 802.11g: up to 54 Mbps 802.11n: up to 150 Mbps
Operating Frequency	2.412 ~ 2.462 GHz
Number of Channel	802.11b, 802.11g, 802.11n (HT20): 11 802.11n (HT40): 7
Output Power	120.226 mW
Antenna Type	Refer to Note
Antenna Connector	Refer to Note
Accessory Device	Refer to note
Cable Supplied	USB Cable X1 (Shielded, 1.0m)

Note:

1. There are WLAN and Bluetooth technology used for the EUT.
2. Simultaneously transmission condition.

Condition	Technology	
1	WLAN (2.4GHz)	Bluetooth

Note: The emission of the simultaneous operation has been evaluated and no non-compliance was found.

3. The EUT could be supplied with USB cable and following different models could be chosen as following table:

No.	Brand	Model	Signal Line
1	Yih Fone	SH-0430	Shielded : Y , 1.0m , Core: N/A
2	Yih Fone	SH-0507	Shielded : Y , 1.0m , Core: N/A

4. The EUT could be supplied with eMMC as following table:

Brand	Model
KINGSTON	EMMC32G-TX29-GA8A

5. The EUT could be supplied with a rechargeable battery as the following table:

Brand Name	Model No.	Spec.
EVE Energy CO., LTD	PR-284983N	3.7V ,1500mAH ,5.25Wh

6. The antenna provided to the EUT, please refer to the following table:

RF Chain NO.	Brand	Model	Antenna Net Gain (dBi)	Frequency Range (GHz)	Antenna Type	Connector Type
0	Walsin Technology Corporation	RFECA3216060AAT	2	2.4~2.4835	CERAMIC ANTENNA	none

7. The EUT was pre-tested under the following modes:

Radiated Emission test	
Test Mode	Description
Mode A	Battery mode
Mode B	USB Adapter mode
Note: From the above modes, the worst case was found in Mode B . Therefore only the test data of the mode was recorded in this report.	
AC Power Conducted Emission test	
Test Mode	Description
Mode A	USB Adapter mode
Mode B	Laptop mode
Note: From the above modes, the worst case was found in Mode A . Therefore only the test data of the mode was recorded in this report.	

8. The EUT incorporates a SISO function:

2.4GHz Band		
MODULATION MODE	TX & RX CONFIGURATION	
802.11b	1TX	1RX
802.11g	1TX	1RX
802.11n (HT20)	1TX	1RX
802.11n (HT40)	1TX	1RX

9. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

10. The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

3.2 Description of Test Modes

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437		

7 channels are provided for 802.11n (HT40)

Channel	Frequency	Channel	Frequency
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT Configure Mode	Applicable To				Description
	RE $\geq$ 1G	RE<1G	PLC	APCM	
1	√	√	√	√	USB Cable No. 1
2	-	√	-	-	USB Cable No. 2

Where **RE $\geq$ 1G**: Radiated Emission above 1GHz & Bandedge Measurement

RE<1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

Note: The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **X-plane**.

Radiated Emission Test (Above 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	13.5

Radiated Emission Test (Below 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	11	DSSS	DBPSK	1

Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	11	DSSS	DBPSK	1

Antenna Port Conducted Measurement:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.


Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	13.5

Test Condition:

Applicable To	Environmental Conditions	Input Power (System)	Tested By
RE $\geq$ 1G	25deg. C, 65%RH	120Vac, 60Hz	Tom Yang
RE<1G	25deg. C, 70%RH	120Vac, 60Hz	Tom Yang
PLC	25deg. C, 60%RH	120Vac, 60Hz	Tom Yang
APCM	25deg. C, 60%RH	120Vac, 60Hz	Jim Hung

3.3 Duty Cycle of Test Signal

Duty cycle of test signal is 100 %, duty factor is not required.




3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	USB Adapter	ASUS	EXA1205UA	NA	NA	Provided by Lab

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	USB Type A To USB Type C Cable	1	1	Yes	0	Supplied by client

3.4.1 Configuration of System under Test



3.5 General Description of Applied Standards and References

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards and references:

Test Standard:

FCC Part 15, Subpart C (15.247)

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

References Test Guidance:

KDB 558074 D01 15.247 Meas Guidance v05r02

All test items have been performed as a reference to the above KDB test guidance.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Note:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 Test Instruments

For Radiated Emission and Bandedge test (Mode 1):

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver R&S	ESR3	102528	2021/3/2	2022/3/1
Spectrum Analyzer KEYSIGHT	N9030B	MY57141948	2021/5/21	2022/5/20
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Boresight Antenna Tower & Turn Table Max-Full	MF-7802BS	MF780208530	NA	NA
Pre_Amplifier EMCI	EMC001340	980142	2021/5/24	2022/5/23
LOOP ANTENNA Electro-Metrics	EM-6879	264	2021/3/5	2022/3/4
RF Coaxial Cable JYEBO	5D-FB	LOOPCAB-001	2021/1/7	2022/1/6
RF Coaxial Cable JYEBO	5D-FB	LOOPCAB-002	2021/1/7	2022/1/6
Pre_Amplifier EMCI	EMC330N	980538	2021/4/26	2022/4/25
Bilog Antenna Schwarzbeck	VULB 9168	9168-0842	2020/11/3	2021/11/2
RF Coaxial Cable COMMATE/PEWC	8D	966-5-1	2021/4/26	2022/4/25
RF Coaxial Cable COMMATE/PEWC	8D	966-5-2	2021/4/26	2022/4/25
RF Coaxial Cable COMMATE/PEWC	8D	966-5-3	2021/4/26	2022/4/25
Fixed attenuator Mini-Circuits	UNAT-5+	PAD-ATT5-02	2021/1/11	2022/1/10
Broad-Band Horn Antenna Schwarzbeck	BBHA 9120D	9120D-1819	2020/11/22	2021/11/21
Pre_Amplifier EMCI	EMC12630SE	980509	2021/4/26	2022/4/25
RF Coaxial Cable EMCI	EMC104-SM-SM-1500	180503	2021/4/26	2022/4/25
RF Coaxial Cable EMCI	EMC104-SM-SM-2000	180501	2021/4/26	2022/4/25
RF Coaxial Cable EMCI	EMC104-SM-SM-6000	180506	2021/4/26	2022/4/25
Pre_Amplifier EMCI	EMC184045SE	980387	2021/1/11	2022/1/10
Horn Antenna Schwarzbeck	BBHA 9170	BBHA9170519	2020/11/22	2021/11/21
RF Cable-Frequency range: 1-40GHz EMCI	EMC102-KM-KM-1200	160924	2021/1/11	2022/1/10
RF cable (40GHz) EMCI	EMC-KM-KM-4000	200214	2021/3/10	2022/3/9

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in 966 Chamber No. 5.
3. Tested Date: 2021/9/3 ~ 2021/9/24

For Radiated Emission (Mode 2):

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver Agilent	N9038A	MY50010156	2021/7/22	2022/7/21
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Antenna Tower & Turn Table Max-Full	MF-7802	MF780208406	NA	NA
Pre_Amplifier EMCI	EMC001340	980142	2021/5/24	2022/5/23
LOOP ANTENNA Electro-Metrics	EM-6879	264	2021/3/5	2022/3/4
RF Coaxial Cable JYEBO	5D-FB	LOOPCAB-001	2021/1/7	2022/1/6
RF Coaxial Cable JYEBO	5D-FB	LOOPCAB-002	2021/1/7	2022/1/6
Pre_Amplifier Mini-Circuits	ZFL-1000VH2	QA0838008	2020/10/20	2021/10/19
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-361	2020/11/5	2021/11/4
RF Coaxial Cable COMMATE/PEWC	8D	966-3-1	2021/3/16	2022/3/15
RF Coaxial Cable COMMATE/PEWC	8D	966-3-2	2021/3/16	2022/3/15
RF Coaxial Cable COMMATE/PEWC	8D	966-3-3	2021/3/16	2022/3/15
Fixed attenuator Mini-Circuits	UNAT-5+	PAD-3m-3-01	2021/9/23	2022/9/22

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in 966 Chamber No. 3.
3. Tested Date: 2021/9/29

For other test items:

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Spectrum Analyzer R&S	FSV40	101516	2021/3/8	2022/3/7
Power Meter Anritsu	ML2495A	1529002	2021/6/21	2022/6/20
Pulse Power Sensor Anritsu	MA2411B	1339443	2021/5/31	2022/5/30
Attenuator WOKEN	MDCS18N-10	MDCS18N-10-01	2021/4/13	2022/4/12
Software	ADT_RF Test Software V6.6.5.4	NA	NA	NA

- NOTE:**
1. The test was performed in Oven room 2.
 2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 3. Tested Date: 2021/9/23

4.1.3 Test Procedures

For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard


No deviation.

4.1.5 Test Setup


For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

- Placed the EUT on the testing table.
- Controlling software (RUN_WI-FI.TXT) has been activated to set the EUT under transmission condition continuously at specific channel frequency.

4.1.7 Test Results (Mode 1)

Above 1GHz Data:

RF Mode	TX 802.11b	Channel	CH 1 : 2412 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2387.26	58.5 PK	74.0	-15.5	1.19 H	210	61.2	-2.7
2	2387.26	48.1 AV	54.0	-5.9	1.19 H	210	50.8	-2.7
3	*2412.00	106.3 PK			1.19 H	210	109.0	-2.7
4	*2412.00	103.9 AV			1.19 H	210	106.6	-2.7
5	4824.00	53.5 PK	74.0	-20.5	1.11 H	227	51.7	1.8
6	4824.00	51.7 AV	54.0	-2.3	1.11 H	227	49.9	1.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2386.15	56.1 PK	74.0	-17.9	3.75 V	276	58.8	-2.7
2	2386.15	45.7 AV	54.0	-8.3	3.75 V	276	48.4	-2.7
3	*2412.00	103.3 PK			3.75 V	276	106.0	-2.7
4	*2412.00	100.7 AV			3.75 V	276	103.4	-2.7
5	4824.00	54.7 PK	74.0	-19.3	1.31 V	206	52.9	1.8
6	4824.00	53.5 AV	54.0	-0.5	1.31 V	206	51.7	1.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11b	Channel	CH 6 : 2437 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	53.5 PK	74.0	-20.5	1.15 H	212	56.2	-2.7
2	2390.00	42.3 AV	54.0	-11.7	1.15 H	212	45.0	-2.7
3	*2437.00	106.8 PK			1.15 H	212	109.5	-2.7
4	*2437.00	104.7 AV			1.15 H	212	107.4	-2.7
5	2483.50	55.1 PK	74.0	-18.9	1.15 H	212	57.9	-2.8
6	2483.50	43.7 AV	54.0	-10.3	1.15 H	212	46.5	-2.8
7	4874.00	53.7 PK	74.0	-20.3	1.16 H	230	52.0	1.7
8	4874.00	51.8 AV	54.0	-2.2	1.16 H	230	50.1	1.7
9	7311.00	50.8 PK	74.0	-23.2	1.24 H	198	43.6	7.2
10	7311.00	45.7 AV	54.0	-8.3	1.24 H	198	38.5	7.2

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	53.4 PK	74.0	-20.6	3.22 V	296	56.1	-2.7
2	2390.00	42.1 AV	54.0	-11.9	3.22 V	296	44.8	-2.7
3	*2437.00	105.1 PK			3.22 V	296	107.8	-2.7
4	*2437.00	101.0 AV			3.22 V	296	103.7	-2.7
5	2483.50	54.8 PK	74.0	-19.2	3.22 V	296	57.6	-2.8
6	2483.50	43.5 AV	54.0	-10.5	3.22 V	296	46.3	-2.8
7	4874.00	54.5 PK	74.0	-19.5	1.26 V	222	52.8	1.7
8	4874.00	53.5 AV	54.0	-0.5	1.26 V	222	51.8	1.7
9	7311.00	50.2 PK	74.0	-23.8	1.54 V	154	43.0	7.2
10	7311.00	44.9 AV	54.0	-9.1	1.54 V	154	37.7	7.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11b	Channel	CH 11 : 2462 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	106.8 PK			1.14 H	212	109.6	-2.8
2	*2462.00	104.6 AV			1.14 H	212	107.4	-2.8
3	2483.50	61.9 PK	74.0	-12.1	1.14 H	212	64.7	-2.8
4	2483.50	52.2 AV	54.0	-1.8	1.14 H	212	55.0	-2.8
5	4924.00	53.6 PK	74.0	-20.4	1.14 H	220	51.8	1.8
6	4924.00	51.4 AV	54.0	-2.6	1.14 H	220	49.6	1.8
7	7386.00	51.3 PK	74.0	-22.7	1.22 H	205	43.9	7.4
8	7386.00	46.1 AV	54.0	-7.9	1.22 H	205	38.7	7.4
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	105.5 PK			3.17 V	306	108.3	-2.8
2	*2462.00	101.2 AV			3.17 V	306	104.0	-2.8
3	2484.50	59.8 PK	74.0	-14.2	3.17 V	306	62.6	-2.8
4	2484.50	51.6 AV	54.0	-2.4	3.17 V	306	54.4	-2.8
5	4924.00	54.8 PK	74.0	-19.2	1.29 V	218	53.0	1.8
6	4924.00	53.6 AV	54.0	-0.4	1.29 V	218	51.8	1.8
7	7386.00	50.0 PK	74.0	-24.0	1.53 V	141	42.6	7.4
8	7386.00	44.5 AV	54.0	-9.5	1.53 V	141	37.1	7.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11g	Channel	CH 1 : 2412 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	67.6 PK	74.0	-6.4	1.18 H	212	70.3	-2.7
2	2390.00	53.5 AV	54.0	-0.5	1.18 H	212	56.2	-2.7
3	*2412.00	106.6 PK			1.18 H	212	109.3	-2.7
4	*2412.00	97.5 AV			1.18 H	212	100.2	-2.7
5	4824.00	42.4 PK	74.0	-31.6	1.07 H	214	40.6	1.8
6	4824.00	31.2 AV	54.0	-22.8	1.07 H	214	29.4	1.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	65.2 PK	74.0	-8.8	3.84 V	320	67.9	-2.7
2	2390.00	53.0 AV	54.0	-1.0	3.84 V	320	55.7	-2.7
3	*2412.00	105.7 PK			3.84 V	320	108.4	-2.7
4	*2412.00	96.1 AV			3.84 V	320	98.8	-2.7
5	4824.00	44.5 PK	74.0	-29.5	1.11 V	237	42.7	1.8
6	4824.00	32.7 AV	54.0	-21.3	1.11 V	237	30.9	1.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11g	Channel	CH 6 : 2437 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	61.7 PK	74.0	-12.3	1.16 H	211	64.4	-2.7
2	2390.00	48.7 AV	54.0	-5.3	1.16 H	211	51.4	-2.7
3	*2437.00	109.9 PK			1.16 H	211	112.6	-2.7
4	*2437.00	100.5 AV			1.16 H	211	103.2	-2.7
5	2483.50	67.0 PK	74.0	-7.0	1.16 H	211	69.8	-2.8
6	2483.50	53.7 AV	54.0	-0.3	1.16 H	211	56.5	-2.8
7	4874.00	45.8 PK	74.0	-28.2	1.09 H	223	44.1	1.7
8	4874.00	34.2 AV	54.0	-19.8	1.09 H	223	32.5	1.7
9	7311.00	56.1 PK	74.0	-17.9	1.26 H	195	48.9	7.2
10	7311.00	45.3 AV	54.0	-8.7	1.26 H	195	38.1	7.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	60.1 PK	74.0	-13.9	3.59 V	331	62.8	-2.7
2	2390.00	48.1 AV	54.0	-5.9	3.59 V	331	50.8	-2.7
3	*2437.00	108.1 PK			3.59 V	331	110.8	-2.7
4	*2437.00	99.3 AV			3.59 V	331	102.0	-2.7
5	2483.50	64.1 PK	74.0	-9.9	3.59 V	331	66.9	-2.8
6	2483.50	51.9 AV	54.0	-2.1	3.59 V	331	54.7	-2.8
7	4874.00	47.9 PK	74.0	-26.1	1.10 V	230	46.2	1.7
8	4874.00	36.9 AV	54.0	-17.1	1.10 V	230	35.2	1.7
9	7311.00	56.9 PK	74.0	-17.1	1.04 V	137	49.7	7.2
10	7311.00	44.1 AV	54.0	-9.9	1.04 V	137	36.9	7.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11g	Channel	CH 11 : 2462 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	105.4 PK			1.11 H	211	108.2	-2.8
2	*2462.00	96.3 AV			1.11 H	211	99.1	-2.8
3	2483.50	70.0 PK	74.0	-4.0	1.11 H	211	72.8	-2.8
4	2483.50	53.6 AV	54.0	-0.4	1.11 H	211	56.4	-2.8
5	4924.00	42.6 PK	74.0	-31.4	1.07 H	215	40.8	1.8
6	4924.00	31.1 AV	54.0	-22.9	1.07 H	215	29.3	1.8
7	7386.00	51.4 PK	74.0	-22.6	1.31 H	185	44.0	7.4
8	7386.00	40.5 AV	54.0	-13.5	1.31 H	185	33.1	7.4
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	105.7 PK			3.62 V	318	108.5	-2.8
2	*2462.00	96.7 AV			3.62 V	318	99.5	-2.8
3	2483.50	66.6 PK	74.0	-7.4	3.62 V	318	69.4	-2.8
4	2483.50	51.3 AV	54.0	-2.7	3.62 V	318	54.1	-2.8
5	4924.00	44.8 PK	74.0	-29.2	1.10 V	240	43.0	1.8
6	4924.00	33.1 AV	54.0	-20.9	1.10 V	240	31.3	1.8
7	7386.00	52.1 PK	74.0	-21.9	1.09 V	149	44.7	7.4
8	7386.00	39.7 AV	54.0	-14.3	1.09 V	149	32.3	7.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11n (HT20)	Channel	CH 1 : 2412 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	69.2 PK	74.0	-4.8	1.17 H	211	71.9	-2.7
2	2390.00	53.5 AV	54.0	-0.5	1.17 H	211	56.2	-2.7
3	*2412.00	105.4 PK			1.17 H	211	108.1	-2.7
4	*2412.00	96.1 AV			1.17 H	211	98.8	-2.7
5	4824.00	42.8 PK	74.0	-31.2	1.05 H	228	41.0	1.8
6	4824.00	31.4 AV	54.0	-22.6	1.05 H	228	29.6	1.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	64.6 PK	74.0	-9.4	3.66 V	300	67.3	-2.7
2	2390.00	50.9 AV	54.0	-3.1	3.66 V	300	53.6	-2.7
3	*2412.00	105.5 PK			3.66 V	300	108.2	-2.7
4	*2412.00	95.6 AV			3.66 V	300	98.3	-2.7
5	4824.00	44.8 PK	74.0	-29.2	1.13 V	248	43.0	1.8
6	4824.00	33.2 AV	54.0	-20.8	1.13 V	248	31.4	1.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11n (HT20)	Channel	CH 6 : 2437 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	61.6 PK	74.0	-12.4	1.16 H	212	64.3	-2.7
2	2390.00	48.5 AV	54.0	-5.5	1.16 H	212	51.2	-2.7
3	*2437.00	110.4 PK			1.16 H	212	113.1	-2.7
4	*2437.00	100.8 AV			1.16 H	212	103.5	-2.7
5	2483.50	66.8 PK	74.0	-7.2	1.16 H	212	69.6	-2.8
6	2483.50	53.7 AV	54.0	-0.3	1.16 H	212	56.5	-2.8
7	4874.00	45.4 PK	74.0	-28.6	1.07 H	235	43.7	1.7
8	4874.00	33.8 AV	54.0	-20.2	1.07 H	235	32.1	1.7
9	7311.00	56.7 PK	74.0	-17.3	1.28 H	204	49.5	7.2
10	7311.00	45.7 AV	54.0	-8.3	1.28 H	204	38.5	7.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	60.1 PK	74.0	-13.9	3.65 V	322	62.8	-2.7
2	2390.00	48.0 AV	54.0	-6.0	3.65 V	322	50.7	-2.7
3	*2437.00	108.0 PK			3.65 V	322	110.7	-2.7
4	*2437.00	99.3 AV			3.65 V	322	102.0	-2.7
5	2483.50	64.4 PK	74.0	-9.6	3.65 V	322	67.2	-2.8
6	2483.50	52.0 AV	54.0	-2.0	3.65 V	322	54.8	-2.8
7	4874.00	48.0 PK	74.0	-26.0	1.06 V	229	46.3	1.7
8	4874.00	36.8 AV	54.0	-17.2	1.06 V	229	35.1	1.7
9	7311.00	57.2 PK	74.0	-16.8	1.03 V	125	50.0	7.2
10	7311.00	44.6 AV	54.0	-9.4	1.03 V	125	37.4	7.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11n (HT20)	Channel	CH 11 : 2462 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	105.9 PK			1.17 H	212	108.7	-2.8
2	*2462.00	95.6 AV			1.17 H	212	98.4	-2.8
3	2483.50	70.2 PK	74.0	-3.8	1.17 H	212	73.0	-2.8
4	2483.50	53.6 AV	54.0	-0.4	1.17 H	212	56.4	-2.8
5	4924.00	42.7 PK	74.0	-31.3	1.03 H	217	40.9	1.8
6	4924.00	31.1 AV	54.0	-22.9	1.03 H	217	29.3	1.8
7	7386.00	51.0 PK	74.0	-23.0	1.36 H	184	43.6	7.4
8	7386.00	40.2 AV	54.0	-13.8	1.36 H	184	32.8	7.4
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	102.2 PK			3.63 V	282	105.0	-2.8
2	*2462.00	93.1 AV			3.63 V	282	95.9	-2.8
3	2483.50	69.9 PK	74.0	-4.1	3.63 V	282	72.7	-2.8
4	2483.50	52.2 AV	54.0	-1.8	3.63 V	282	55.0	-2.8
5	4924.00	45.5 PK	74.0	-28.5	1.11 V	243	43.7	1.8
6	4924.00	33.6 AV	54.0	-20.4	1.11 V	243	31.8	1.8
7	7386.00	52.1 PK	74.0	-21.9	1.15 V	141	44.7	7.4
8	7386.00	39.4 AV	54.0	-14.6	1.15 V	141	32.0	7.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11n (HT40)	Channel	CH 3 : 2422 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2386.00	67.1 PK	74.0	-6.9	1.35 H	228	69.8	-2.7
2	2386.00	52.9 AV	54.0	-1.1	1.35 H	228	55.6	-2.7
3	2390.00	63.8 PK	74.0	-10.2	1.35 H	228	66.5	-2.7
4	2390.00	53.8 AV	54.0	-0.2	1.35 H	228	56.5	-2.7
5	*2422.00	101.3 PK			1.35 H	228	104.0	-2.7
6	*2422.00	91.7 AV			1.35 H	228	94.4	-2.7
7	4844.00	42.5 PK	74.0	-31.5	1.02 H	209	40.7	1.8
8	4844.00	30.9 AV	54.0	-23.1	1.02 H	209	29.1	1.8
9	7266.00	48.8 PK	74.0	-25.2	1.36 H	177	41.5	7.3
10	7266.00	36.5 AV	54.0	-17.5	1.36 H	177	29.2	7.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2388.30	66.3 PK	74.0	-7.7	3.71 V	288	69.0	-2.7
2	2388.30	50.6 AV	54.0	-3.4	3.71 V	288	53.3	-2.7
3	2390.00	62.7 PK	74.0	-11.3	3.71 V	288	65.4	-2.7
4	2390.00	51.5 AV	54.0	-2.5	3.71 V	288	54.2	-2.7
5	*2422.00	100.5 PK			3.71 V	288	103.2	-2.7
6	*2422.00	90.7 AV			3.71 V	288	93.4	-2.7
7	4844.00	43.9 PK	74.0	-30.1	1.14 V	230	42.1	1.8
8	4844.00	31.6 AV	54.0	-22.4	1.14 V	230	29.8	1.8
9	7266.00	47.9 PK	74.0	-26.1	1.08 V	150	40.6	7.3
10	7266.00	36.2 AV	54.0	-17.8	1.08 V	150	28.9	7.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11n (HT40)	Channel	CH 6 : 2437 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	63.5 PK	74.0	-10.5	1.32 H	227	66.2	-2.7
2	2390.00	50.5 AV	54.0	-3.5	1.32 H	227	53.2	-2.7
3	*2437.00	102.4 PK			1.32 H	227	105.1	-2.7
4	*2437.00	92.5 AV			1.32 H	227	95.2	-2.7
5	2483.50	68.2 PK	74.0	-5.8	1.32 H	227	71.0	-2.8
6	2483.50	53.8 AV	54.0	-0.2	1.32 H	227	56.6	-2.8
7	4874.00	43.0 PK	74.0	-31.0	1.00 H	202	41.3	1.7
8	4874.00	31.4 AV	54.0	-22.6	1.00 H	202	29.7	1.7
9	7311.00	48.5 PK	74.0	-25.5	1.35 H	190	41.3	7.2
10	7311.00	36.1 AV	54.0	-17.9	1.35 H	190	28.9	7.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	63.4 PK	74.0	-10.6	3.73 V	280	66.1	-2.7
2	2390.00	48.6 AV	54.0	-5.4	3.73 V	280	51.3	-2.7
3	*2437.00	100.5 PK			3.73 V	280	103.2	-2.7
4	*2437.00	91.2 AV			3.73 V	280	93.9	-2.7
5	2483.50	65.2 PK	74.0	-8.8	3.73 V	280	68.0	-2.8
6	2483.50	50.5 AV	54.0	-3.5	3.73 V	280	53.3	-2.8
7	4874.00	43.5 PK	74.0	-30.5	1.10 V	227	41.8	1.7
8	4874.00	31.2 AV	54.0	-22.8	1.10 V	227	29.5	1.7
9	7311.00	47.4 PK	74.0	-26.6	1.10 V	140	40.2	7.2
10	7311.00	35.8 AV	54.0	-18.2	1.10 V	140	28.6	7.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11n (HT40)	Channel	CH 9 : 2452 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2452.00	100.2 PK			1.09 H	228	102.9	-2.7
2	*2452.00	90.1 AV			1.09 H	228	92.8	-2.7
3	2483.50	68.1 PK	74.0	-5.9	1.09 H	228	70.9	-2.8
4	2483.50	53.5 AV	54.0	-0.5	1.09 H	228	56.3	-2.8
5	4904.00	42.2 PK	74.0	-31.8	1.00 H	207	40.5	1.7
6	4904.00	30.9 AV	54.0	-23.1	1.00 H	207	29.2	1.7
7	7356.00	48.7 PK	74.0	-25.3	1.34 H	195	41.4	7.3
8	7356.00	36.0 AV	54.0	-18.0	1.34 H	195	28.7	7.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2452.00	96.5 PK			3.45 V	285	99.2	-2.7
2	*2452.00	88.5 AV			3.45 V	285	91.2	-2.7
3	2483.50	65.7 PK	74.0	-8.3	3.45 V	285	68.5	-2.8
4	2483.50	50.5 AV	54.0	-3.5	3.45 V	285	53.3	-2.8
5	2486.00	66.5 PK	74.0	-7.5	3.45 V	285	69.3	-2.8
6	2486.00	49.1 AV	54.0	-4.9	3.45 V	285	51.9	-2.8
7	4904.00	43.8 PK	74.0	-30.2	1.11 V	227	42.1	1.7
8	4904.00	31.5 AV	54.0	-22.5	1.11 V	227	29.8	1.7
9	7356.00	47.6 PK	74.0	-26.4	1.07 V	146	40.3	7.3
10	7356.00	35.8 AV	54.0	-18.2	1.07 V	146	28.5	7.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.


Below 1GHz Data:

RF Mode	TX 802.11b	Channel	CH 11 : 2462 MHz
Frequency Range	9kHz ~ 1GHz	Detector Function	Quasi-Peak (QP)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	39.53	20.0 QP	40.0	-20.0	2.00 H	95	33.3	-13.3
2	75.06	27.2 QP	40.0	-12.8	2.00 H	168	43.4	-16.2
3	141.60	25.4 QP	43.5	-18.1	2.00 H	280	38.4	-13.0
4	393.57	19.4 QP	46.0	-26.6	1.00 H	24	29.4	-10.0
5	607.13	25.3 QP	46.0	-20.7	2.00 H	205	30.4	-5.1
6	791.99	40.0 QP	46.0	-6.0	1.00 H	8	42.5	-2.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




RF Mode	TX 802.11b	Channel	CH 11 : 2462 MHz
Frequency Range	9kHz ~ 1GHz	Detector Function	Quasi-Peak (QP)

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	39.60	36.1 QP	40.0	-3.9	1.00 V	223	49.4	-13.3
2	75.79	29.4 QP	40.0	-10.6	1.00 V	207	45.9	-16.5
3	149.70	18.5 QP	43.5	-25.0	1.00 V	360	31.1	-12.6
4	449.98	27.8 QP	46.0	-18.2	1.00 V	198	36.1	-8.3
5	714.13	35.3 QP	46.0	-10.7	2.00 V	91	39.0	-3.7
6	792.02	33.7 QP	46.0	-12.3	2.00 V	316	36.2	-2.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




4.1.8 Test Results (Mode 2)

RF Mode	TX 802.11b	Channel	CH 11 : 2462 MHz
Frequency Range	9kHz ~ 1GHz	Detector Function	Quasi-Peak (QP)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	32.11	35.8 QP	40.0	-4.2	1.50 H	329	45.1	-9.3
2	46.55	33.2 QP	40.0	-6.8	1.50 H	302	41.4	-8.2
3	196.27	26.3 QP	43.5	-17.2	1.00 H	253	36.9	-10.6
4	451.34	28.9 QP	46.0	-17.1	2.00 H	6	30.9	-2.0
5	549.43	29.3 QP	46.0	-16.7	1.00 H	308	29.5	-0.2
6	792.08	42.7 QP	46.0	-3.3	1.00 H	240	37.8	4.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




RF Mode	TX 802.11b	Channel	CH 11 : 2462 MHz
Frequency Range	9kHz ~ 1GHz	Detector Function	Quasi-Peak (QP)

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	40.78	29.4 QP	40.0	-10.6	1.00 V	145	37.9	-8.5
2	114.58	36.3 QP	43.5	-7.2	1.00 V	109	46.6	-10.3
3	281.88	23.6 QP	46.0	-22.4	2.00 V	92	30.8	-7.2
4	464.84	27.9 QP	46.0	-18.1	1.00 V	109	29.7	-1.8
5	650.95	31.6 QP	46.0	-14.4	2.00 V	196	29.3	2.3
6	792.13	37.7 QP	46.0	-8.3	2.00 V	79	32.8	4.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver R&S	ESCS 30	847124/029	2020/10/20	2021/10/19
LISN R&S	ESH3-Z5	848773/004	2020/10/27	2021/10/26
LISN R & S	ESH3-Z5	835239/001	2021/3/26	2022/3/25
50 ohms Terminator	50	3	2020/10/26	2021/10/25
RF Coaxial Cable JYEBO	5D-FB	COCCAB-001	2020/9/26	2021/9/25
Fixed attenuator STI	STI02-2200-10	005	2021/8/27	2022/8/26
Software BVADT	BVADT_Cond_V7.3.7.4	NA	NA	NA

Note:

1. The calibration interval of the above test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Conduction 1.
- 3 Tested Date: 2021/9/7

4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

4.2.4 Deviation from Test Standard

No deviation.

4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Conditions

Same as 4.1.6.


4.2.7 Test Results

RF Mode	TX 802.11b	Channel	CH 11 : 2462 MHz
Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15781	9.97	43.47	35.78	53.44	45.75	65.58	55.58	-12.14	-9.83
2	0.23594	10.01	38.14	31.12	48.15	41.13	62.24	52.24	-14.09	-11.11
3	0.55234	10.04	34.31	23.16	44.35	33.20	56.00	46.00	-11.65	-12.80
4	1.69922	10.10	25.94	16.11	36.04	26.21	56.00	46.00	-19.96	-19.79
5	4.33984	10.28	17.07	5.07	27.35	15.35	56.00	46.00	-28.65	-30.65
6	15.11719	11.10	21.61	13.76	32.71	24.86	60.00	50.00	-27.29	-25.14

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




RF Mode	TX 802.11b	Channel	CH 11 : 2462 MHz
Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15391	9.95	45.00	33.90	54.95	43.85	65.79	55.79	-10.84	-11.94
2	0.23203	10.00	38.94	29.22	48.94	39.22	62.38	52.38	-13.44	-13.16
3	0.30625	10.01	28.62	14.01	38.63	24.02	60.07	50.07	-21.44	-26.05
4	0.54063	10.03	28.92	22.75	38.95	32.78	56.00	46.00	-17.05	-13.22
5	2.08594	10.13	23.98	14.16	34.11	24.29	56.00	46.00	-21.89	-21.71
6	14.80078	10.88	19.52	13.04	30.40	23.92	60.00	50.00	-29.60	-26.08

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




4.3 6dB Bandwidth Measurement

4.3.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure

- Set resolution bandwidth (RBW) = 100kHz
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.3.5 Deviation from Test Standard

No deviation.

4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 Test Result

802.11b

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2412	10.11	0.5	Pass
6	2437	10.1	0.5	Pass
11	2462	10.1	0.5	Pass

802.11g

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2412	16.59	0.5	Pass
6	2437	16.59	0.5	Pass
11	2462	16.59	0.5	Pass

802.11n (HT20)


Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2412	17.76	0.5	Pass
6	2437	17.75	0.5	Pass
11	2462	17.75	0.5	Pass

802.11n (HT40)


Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
3	2422	36.49	0.5	Pass
6	2437	36.55	0.5	Pass
9	2452	36.54	0.5	Pass

Spectrum Plot of Worst Value


802.11b / CH11




802.11g / CH11



802.11n (HT20) / CH11



802.11n (HT40) / CH3




4.4 Conducted Output Power Measurement

4.4.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

4.4.2 Test Setup



4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.4 Test Procedures

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

4.4.5 Deviation from Test Standard

No deviation.

4.4.6 EUT Operating Conditions

Same as Item 4.3.6.

4.4.7 Test Results

FOR PEAK POWER

802.11b

Chan.	Chan. Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass / Fail
1	2412	20.845	13.19	30	Pass
6	2437	23.227	13.66	30	Pass
11	2462	24.322	13.86	30	Pass

802.11g

Chan.	Chan. Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass / Fail
1	2412	116.95	20.68	30	Pass
6	2437	118.577	20.74	30	Pass
11	2462	117.49	20.70	30	Pass

802.11n (HT20)

Chan.	Chan. Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass / Fail
1	2412	115.611	20.63	30	Pass
6	2437	118.85	20.75	30	Pass
11	2462	116.95	20.68	30	Pass

802.11n (HT40)

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass/Fail
3	2422	115.08	20.61	30	Pass
6	2437	120.226	20.80	30	Pass
9	2452	118.85	20.75	30	Pass

FOR AVERAGE POWER

802.11b

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)
1	2412	13.521	11.31
6	2437	14.962	11.75
11	2462	15.668	11.95

802.11g

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)
1	2412	14.622	11.65
6	2437	14.894	11.73
11	2462	14.757	11.69

802.11n (HT20)

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)
1	2412	14.521	11.62
6	2437	15.031	11.77
11	2462	14.723	11.68

802.11n (HT40)


Channel	Frequency (MHz)	Average Power (mW)	Average Power (dBm)
3	2422	14.454	11.60
6	2437	14.962	11.75
9	2452	14.757	11.69

4.5 Power Spectral Density Measurement

4.5.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8dBm in any 3 kHz.

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 Test Procedure

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq 3 \times \text{RBW}$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.

4.5.5 Deviation from Test Standard

No deviation.

4.5.6 EUT Operating Condition

Same as Item 4.3.6

4.5.7 Test Results

802.11b

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Pass / Fail
1	2412	-19.11	8.00	Pass
6	2437	-18.87	8.00	Pass
11	2462	-18.80	8.00	Pass

802.11g

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Pass / Fail
1	2412	-17.53	8.00	Pass
6	2437	-17.30	8.00	Pass
11	2462	-17.36	8.00	Pass

802.11n (HT20)


Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Pass / Fail
1	2412	-17.01	8.00	Pass
6	2437	-16.88	8.00	Pass
11	2462	-16.66	8.00	Pass

802.11n (HT40)


Channel	Freq. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
3	2422	-18.66	8	Pass
6	2437	-17.31	8	Pass
9	2452	-16.91	8	Pass

Spectrum Plot of Worst Value


802.11b / CH11




802.11g / CH6



802.11n (HT20) / CH11



802.11n (HT40) / CH9




4.6 Conducted Out of Band Emission Measurement

4.6.1 Limits of Conducted Out of Band Emission Measurement

Below 20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 Test Setup



4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.6.4 Test Procedure

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

4.6.5 Deviation from Test Standard

No deviation.

4.6.6 EUT Operating Condition


Same as Item 4.3.6

4.6.7 Test Results


The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.

802.11b


CH 1




CH 6




CH 11



CH 1 Band edge





CH 11 Band edge





802.11g



CH 1




CH 6




CH 11



CH 1 Band edge





CH 11 Band edge





802.11n (HT20)



CH 1




CH 6




CH 11



CH 1 Band edge




CH 11 Band edge




802.11n (HT40)


CH 3




CH 6




CH 9



CH 3 Band edge




CH 9 Band edge





5 Pictures of Test Arrangements


Please refer to the attached file (Test Setup Photo).

Annex A - Band-Edge Measurement









Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---