

FCC PART 15.247

TEST REPORT

For

SHUOYING INDUSTRIAL(SHENZHEN)CO.,LTD

NO.1 Shuoying Rd.,Hebei Industry Area,Dalang,Longhua Town,Baoan,Shenzhen,China

FCC ID: XJN-PA7810X

Report Type: Original Report	Product Type: Mobile Internet Devices
Test Engineer:	Leon Chen
Report Number:	R2DG140605002-00B
Report Date:	2014-06-24
Reviewed By:	Sula Huang RF Engineer
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan). This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
DESCRIPTION OF TEST CONFIGURATION	5
EUT EXERCISE SOFTWARE	5
EQUIPMENT MODIFICATIONS	5
SUPPORT EQUIPMENT LIST AND DETAILS	5
EXTERNAL CABLE.....	5
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS	7
FCC §15.247 (i) & §2.1093 – RF EXPOSURE	8
APPLICABLE STANDARD	8
FCC §15.203 - ANTENNA REQUIREMENT.....	9
APPLICABLE STANDARD	9
ANTENNA CONNECTOR CONSTRUCTION	9
FCC §15.207 – AC LINE CONDUCTED EMISSIONS.....	10
MEASUREMENT UNCERTAINTY	10
EUT SETUP.....	10
EMI TEST RECEIVER SETUP.....	11
TEST PROCEDURE	11
CORRECTED AMPLITUDE & MARGIN CALCULATION	11
TEST EQUIPMENT LIST AND DETAILS.....	12
TEST RESULTS SUMMARY	12
TEST DATA	12
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	15
APPLICABLE STANDARD	15
MEASUREMENT UNCERTAINTY	15
EUT SETUP.....	15
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	16
TEST PROCEDURE	16
TEST EQUIPMENT LIST AND DETAILS.....	17
CORRECTED AMPLITUDE & MARGIN CALCULATION	17
TEST RESULTS SUMMARY	17
TEST DATA	17
FCC §15.247(a) (1) - CHANNEL SEPARATION TEST	26
APPLICABLE STANDARD	26
TEST EQUIPMENT LIST AND DETAILS.....	26
TEST PROCEDURE	26
TEST DATA	26
FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING	32

APPLICABLE STANDARD	32
TEST PROCEDURE	32
TEST EQUIPMENT LIST AND DETAILS.....	32
TEST DATA	32
FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST	38
APPLICABLE STANDARD	38
TEST PROCEDURE	38
TEST EQUIPMENT LIST AND DETAILS.....	38
TEST DATA	38
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....	42
APPLICABLE STANDARD	42
TEST PROCEDURE	42
TEST EQUIPMENT LIST AND DETAILS.....	42
TEST DATA	42
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	58
APPLICABLE STANDARD	58
TEST PROCEDURE	58
TEST EQUIPMENT LIST AND DETAILS.....	58
TEST DATA	58
FCC §15.247(d) - BAND EDGES TESTING	64
APPLICABLE STANDARD	64
TEST PROCEDURE	64
TEST EQUIPMENT LIST AND DETAILS.....	64
TEST DATA	64

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *SHUOYING INDUSTRIAL(SHENZHEN)CO.,LTD.*'s product, model number: *PA7810(FCC ID: XJN-PA7810X)* (the "EUT") in this report was a *Mobile Internet Devices*, which was measured approximately: 20.0cm (L) x 13.5 cm (W) x 1.0 cm(H), rated input voltage: DC 3.7 V rechargeable Li-ion battery or DC 5.0V charging from adapter.

Adapter information: SPPS
Model Name: I.T.E adapter
Model: SA/12PA/05FUS050200
Input: AC 100-240V, 50/60Hz, 0.5A
Output: DC 5.0V, 2A

** All measurement and test data in this report was gathered from production sample serial number: 140605002. (Assigned by BACL.Dongguan). The EUT was received on 2014-06-05.*

Objective

This report is prepared on behalf of *SHUOYING INDUSTRIAL(SHENZHEN)CO.,LTD.* in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communications Commission's rules

The tests were performed in order to determine the Bluetooth BDR and EDR mode of EUT compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part15C JBP submissions with FCC ID: XJN-PA7810X.
FCC Part15C DTS submissions with FCC ID: XJN-PA7810X.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 02, 2012. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode.

EUT Exercise Software

The software “RF Test Tool” embedded in the EUT was used, which was provided by manufacturer. The maximum power was set by default configuration.

Test Software Version		RF Test Tool v4.8		
Test Frequency		2402MHz	2441MHz	2480MHz
Power Level Setting	GFSK	0	0	0
	$\pi/4$ DQPSK	0	0	0
	8DPSK	0	0	0

Equipment Modifications

No modification was made to the EUT.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
SAMSUNG	LCD Monitor	S22C330H	ZXDCHTHD10149K
/	Earphone	N/A	N/A

External Cable

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
Earphone	no	no	1.1	EUT	Earphone
USB	yes	no	0.8	Adapter	EUT
HDMI	yes	no	1.0	HDMI Port of LCD Monitor	EUT

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §1.1307 (b) (1) & §2.1093	RF EXPOSURE	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Emissions	Compliance
§15.247 (a)(1)	20 dB Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band Edges	Compliance

FCC §15.247 (i) & §2.1093 – RF EXPOSURE

Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v05r02:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Measurement Result

The maximum conducted (average) output power = -2.11 dBm (0.62 mW) at 2480 MHz
 $[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$
 $= 0.62/5 \cdot (\sqrt{2.48}) = 0.20 < 3.0$

So the stand-alone SAR evaluation is not necessary.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
 - b. Antenna must use a unique type of connector to attach to the EUT.
- Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Antenna Connector Construction

The EUT has one integral antenna arrangement for BT, and the antenna gain is 2.54 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC §15.207 – AC LINE CONDUCTED EMISSIONS

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cispr} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cispr} of Table 1, then:


- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Dongguan) is 3.46 dB (150 kHz to 30 MHz).

Table 1 – Values of U_{cispr}

Measurement	U_{cispr}
Conducted disturbance at mains port using AMN (150 kHz to 30 MHz)	3.4 dB

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.207 Class B limits.

The spacing between the peripherals was 10 cm.

The adapter of EUT was connected to a 120 VAC/60 Hz power source

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter of EUT was connected to the outlet of the first LISN and the other support equipments were connected to the outlet of the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

V_C (cord. Reading): corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN

C_f : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2013-11-20	2014-11-19
R&S	Two-line V-network	ENV216	3560.6550.12	2014-01-22	2015-01-21
R&S	L.I.S.N	ESH3-Z5	100113	N/A	N/A
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

3.1 dB at **0.563041 MHz** in the **Line** conducted mode


Test Data**Environmental Conditions**

Temperature:	28.4 °C
Relative Humidity:	60%
ATM Pressure:	99.6 kPa

The testing was performed by Leon Chen on 2014-06-10.

Test mode: Transmitting


AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.511698	51.9	9.000	L1	10.4	4.1	56.0	Compliance
0.563041	52.9	9.000	L1	10.4	3.1*	56.0	Compliance
0.585926	52.5	9.000	L1	10.5	3.5	56.0	Compliance
0.629488	51.9	9.000	L1	10.5	4.1	56.0	Compliance
2.930016	50.3	9.000	L1	10.6	5.7	56.0	Compliance
4.029873	51.0	9.000	L1	10.7	5.0	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.519918	40.1	9.000	L1	10.4	5.9	46.0	Compliance
0.572086	41.1	9.000	L1	10.4	4.9	46.0	Compliance
2.930016	37.4	9.000	L1	10.6	8.6	46.0	Compliance
3.691692	32.6	9.000	L1	10.7	13.4	46.0	Compliance
4.029873	35.1	9.000	L1	10.7	10.9	46.0	Compliance
4.879149	35.3	9.000	L1	10.7	10.7	46.0	Compliance

*Within measurement uncertainty!

AC120 V, 60 Hz, Neutral:

Frequency (MHz)	QuasiPeak (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)	Comment
0.528270	51.9	9.000	N	10.4	4.1	56.0	Compliance
0.590613	52.8	9.000	N	10.5	3.2*	56.0	Compliance
0.634524	52.0	9.000	N	10.6	4.0	56.0	Compliance
0.655073	51.3	9.000	N	10.6	4.7	56.0	Compliance
3.781003	52.9	9.000	N	10.8	3.1*	56.0	Compliance
4.295123	51.5	9.000	N	10.8	4.5	56.0	Compliance

Frequency (MHz)	Average (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)	Comment
0.322331	42.6	9.000	N	11.1	7.1	49.6	Compliance
0.519918	39.1	9.000	N	10.4	6.9	46.0	Compliance
0.590613	40.7	9.000	N	10.5	5.3	46.0	Compliance
3.000901	34.8	9.000	N	10.7	11.2	46.0	Compliance
3.122873	38.4	9.000	N	10.7	7.6	46.0	Compliance
4.127365	38.7	9.000	N	10.8	7.3	46.0	Compliance

*Within measurement uncertainty!

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cispr} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cispr} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is:

30M~200MHz: 5.0 dB

200M~1GHz: 6.2 dB

1G~6GHz: 4.45 dB


6G~18GHz: 5.23 dB


Table 1 – Values of U_{cispr}

Measurement	U_{cispr}
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB

EUT Setup

Below 1GHz:



Above 1GHz:

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.4-2003. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The adapter of EUT was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz - 1 GHz, peak and average detection modes for frequencies above 1 GHz.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2014-05-09	2015-05-08
Sunol Sciences	Antenna	JB3	A060611-1	2011-09-06	2014-09-05
HP	Amplifier	8447E	2434A02181	2013-09-06	2014-09-05
R&S	Spectrum Analyzer	FSEM	DE31388	2014-05-09	2015-05-08
ETS LINDGREN	Horn Antenna	3115	000 527 35	2012-09-06	2015-09-05
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2014-02-19	2015-02-18
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2013-06-16	2014-06-15

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, and section 15.205, 15.209 and 15.247, with the worst margin reading of:

13.99 dB at 281.6 MHz in the **Horizontal** polarization of EDR Mode (8DPSK)

Test Data

Environmental Conditions

Temperature:	28.4 °C
Relative Humidity:	60%
ATM Pressure:	99.6 kPa

The testing was performed by Leon Chen on 2014-06-10.

Mode: Transmitting

BDR Mode (GFSK):


EDR Mode (GFSK)									
Frequency	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	FCC 15.247	
(MHz)	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)				Limit (dBμV/m)	Margin (dB)
Low Channel: 2402 MHz									
2402	86.97	PK	H	25.65	4.42	27.32	89.72	N/A	N/A
2402	76.68	AV	H	25.65	4.42	27.32	79.43	N/A	N/A
2402	90.37	PK	V	25.65	4.42	27.32	93.12	N/A	N/A
2402	80.02	AV	V	25.65	4.42	27.32	82.77	N/A	N/A
2390	38.13	PK	V	25.61	4.39	27.32	40.81	74.00	33.19
2390	26.25	AV	V	25.61	4.39	27.32	28.93	54.00	25.07
4804	31.05	PK	V	30.59	5.98	27.41	40.21	74.00	33.79
4804	18.68	AV	V	30.59	5.98	27.41	27.84	54.00	26.16
7206	31.32	PK	V	34.09	7.45	25.91	46.95	74.00	27.05
7206	18.82	AV	V	34.09	7.45	25.91	34.45	54.00	19.55
9608	28.69	PK	V	35.96	8.80	27.55	45.90	74.00	28.10
9608	17.46	AV	V	35.96	8.80	27.55	34.67	54.00	19.33
7525	30.81	PK	V	34.82	7.61	26.20	47.04	74.00	26.96
7525	17.9	AV	V	34.82	7.61	26.20	34.13	54.00	19.87
281.6	37.61	QP	H	13.77	2.04	21.51	31.91	46.00	14.09
240.9	36.92	QP	H	12.22	1.86	21.48	29.52	46.00	16.48
Middle Channel: 2441 MHz									
2441	84.4	PK	H	25.75	4.4	27.34	87.21	N/A	N/A
2441	74.09	AV	H	25.75	4.4	27.34	76.9	N/A	N/A
2441	89.69	PK	V	25.75	4.4	27.34	92.5	N/A	N/A
2441	79.32	AV	V	25.75	4.4	27.34	82.13	N/A	N/A
4882	31.26	PK	V	30.79	6.08	27.42	40.71	74.00	33.29
4882	18.78	AV	V	30.79	6.08	27.42	28.23	54.00	25.77
7323	31.88	PK	V	34.38	7.51	25.88	47.89	74.00	26.11
7323	18.9	AV	V	34.38	7.51	25.88	34.91	54.00	19.09
9764	28.97	PK	V	36.33	8.83	27.20	46.93	74.00	27.07
9764	18.03	AV	V	36.33	8.83	27.20	35.99	54.00	18.01
7525	31.16	PK	V	34.82	7.61	26.20	47.39	74.00	26.61
7525	18.84	AV	V	34.82	7.61	26.20	35.07	54.00	18.93
281.6	37.26	QP	H	13.77	2.04	21.51	31.56	46.00	14.44
240.9	36.67	QP	H	12.22	1.86	21.48	29.27	46.00	16.73
High Channel: 2480 MHz									
2480	84.08	PK	H	25.85	4.48	27.36	87.05	N/A	N/A
2480	73.75	AV	H	25.85	4.48	27.36	76.72	N/A	N/A
2480	87.15	PK	V	25.85	4.48	27.36	90.12	N/A	N/A
2480	76.83	AV	V	25.85	4.48	27.36	79.80	N/A	N/A
2483.5	38.04	PK	V	25.86	4.49	27.36	41.03	74.00	32.97
2483.5	26.18	AV	V	25.86	4.49	27.36	29.17	54.00	24.83
4960	30.55	PK	V	31.00	5.90	27.43	40.02	74.00	33.98
4960	18.58	AV	V	31.00	5.90	27.43	28.05	54.00	25.95
7440	31.21	PK	V	34.66	7.58	25.97	47.48	74.00	26.52
7440	19.06	AV	V	34.66	7.58	25.97	35.33	54.00	18.67
9920	29.16	PK	V	36.71	8.87	26.66	48.08	74.00	25.92
9920	18.07	AV	V	36.71	8.87	26.66	36.99	54.00	17.01
7525	30.87	PK	V	34.82	7.61	26.20	47.10	74.00	26.90
7525	17.26	AV	V	34.82	7.61	26.20	33.49	54.00	20.51
281.6	37.59	QP	H	13.77	2.04	21.51	31.89	46.00	14.11
240.9	36.62	QP	H	12.22	1.86	21.48	29.22	46.00	16.78

EDR Mode ($\pi/4$ -DQPSK):


Frequency	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	FCC 15.247	
(MHz)	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)				Limit (dBμV/m)	Margin (dB)
Low Channel: 2402 MHz									
2402	86.94	PK	H	25.65	4.42	27.32	89.69	N/A	N/A
2402	75.1	AV	H	25.65	4.42	27.32	77.85	N/A	N/A
2402	91.11	PK	V	25.65	4.42	27.32	93.86	N/A	N/A
2402	79.18	AV	V	25.65	4.42	27.32	81.93	N/A	N/A
2390	37.28	PK	V	25.61	4.39	27.32	39.96	74.00	34.04
2390	25.86	AV	V	25.61	4.39	27.32	28.54	54.00	25.46
4804	30.71	PK	V	30.59	5.98	27.41	39.87	74.00	34.13
4804	18.69	AV	V	30.59	5.98	27.41	27.85	54.00	26.15
7206	30.55	PK	V	34.09	7.45	25.91	46.18	74.00	27.82
7206	19.07	AV	V	34.09	7.45	25.91	34.70	54.00	19.30
9608	29.66	PK	V	35.96	8.80	27.55	46.87	74.00	27.13
9608	16.83	AV	V	35.96	8.80	27.55	34.04	54.00	19.96
7525	31.05	PK	V	34.82	7.61	26.20	47.28	74.00	26.72
7525	17.93	AV	V	34.82	7.61	26.20	34.16	54.00	19.84
281.6	37.57	QP	H	13.77	2.04	21.51	31.87	46.00	14.13
240.9	36.93	QP	H	12.22	1.86	21.48	29.53	46.00	16.47
Middle Channel: 2441 MHz									
2441	84.7	PK	H	25.75	4.4	27.34	87.51	N/A	N/A
2441	74.87	AV	H	25.75	4.4	27.34	77.68	N/A	N/A
2441	90.59	PK	V	25.75	4.4	27.34	93.4	N/A	N/A
2441	77.63	AV	V	25.75	4.4	27.34	80.44	N/A	N/A
4882	31.33	PK	V	30.79	6.08	27.42	40.78	74.00	33.22
4882	18.9	AV	V	30.79	6.08	27.42	28.35	54.00	25.65
7323	31.24	PK	V	34.38	7.51	25.88	47.25	74.00	26.75
7323	19.37	AV	V	34.38	7.51	25.88	35.38	54.00	18.62
9764	29.12	PK	V	36.33	8.83	27.20	47.08	74.00	26.92
9764	17.03	AV	V	36.33	8.83	27.20	34.99	54.00	19.01
7525	31.18	PK	V	34.82	7.61	26.20	47.41	74.00	26.59
7525	18.09	AV	V	34.82	7.61	26.20	34.32	54.00	19.68
281.6	37.42	QP	H	13.77	2.04	21.51	31.72	46.00	14.28
240.9	36.79	QP	H	12.22	1.86	21.48	29.39	46.00	16.61
High Channel: 2480 MHz									
2480	83.87	PK	H	25.85	4.48	27.36	86.84	N/A	N/A
2480	71.93	AV	H	25.85	4.48	27.36	74.9	N/A	N/A
2480	87.54	PK	V	25.85	4.48	27.36	90.51	N/A	N/A
2480	75.61	AV	V	25.85	4.48	27.36	78.58	N/A	N/A
2483.5	38.48	PK	V	25.86	4.49	27.36	41.47	74.00	32.53
2483.5	26.05	AV	V	25.86	4.49	27.36	29.04	54.00	24.96
4960	30.04	PK	V	31.00	5.90	27.43	39.51	74.00	34.49
4960	18.16	AV	V	31.00	5.90	27.43	27.63	54.00	26.37
7440	31.29	PK	V	34.66	7.58	25.97	47.56	74.00	26.44
7440	19.29	AV	V	34.66	7.58	25.97	35.56	54.00	18.44
9920	28.56	PK	V	36.71	8.87	26.66	47.48	74.00	26.52
9920	17.17	AV	V	36.71	8.87	26.66	36.09	54.00	17.91
7525	30.56	PK	V	34.82	7.61	26.20	46.79	74.00	27.21
7525	18.76	AV	V	34.82	7.61	26.20	34.99	54.00	19.01
281.6	37.62	QP	H	13.77	2.04	21.51	31.92	46.00	14.08
240.9	36.71	QP	H	12.22	1.86	21.48	29.31	46.00	16.69

EDR Mode (8DPSK):

EDR Mode (dBFS):									
Frequency	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	FCC 15.247	
(MHz)	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)				Limit (dBμV/m)	Margin (dB)
Low Channel: 2402 MHz									
2402	87.43	PK	H	25.65	4.42	27.32	90.18	N/A	N/A
2402	74.83	AV	H	25.65	4.42	27.32	77.58	N/A	N/A
2402	91.75	PK	V	25.65	4.42	27.32	94.5	N/A	N/A
2402	79.31	AV	V	25.65	4.42	27.32	82.06	N/A	N/A
2390	37.48	PK	V	25.61	4.39	27.32	40.16	74.00	33.84
2390	25.95	AV	V	25.61	4.39	27.32	28.63	54.00	25.37
4804	30.76	PK	V	30.59	5.98	27.41	39.92	74.00	34.08
4804	18.76	AV	V	30.59	5.98	27.41	27.92	54.00	26.08
7206	32.21	PK	V	34.09	7.45	25.91	47.84	74.00	26.16
7206	19.89	AV	V	34.09	7.45	25.91	35.52	54.00	18.48
9608	29.39	PK	V	35.96	8.80	27.55	46.60	74.00	27.40
9608	18.37	AV	V	35.96	8.80	27.55	35.58	54.00	18.42
7525	31.06	PK	V	34.82	7.61	26.20	47.29	74.00	26.71
7525	18.16	AV	V	34.82	7.61	26.20	34.39	54.00	19.61
281.6	37.59	QP	H	13.77	2.04	21.51	31.89	46.00	14.11
240.9	36.7	QP	H	12.22	1.86	21.48	29.30	46.00	16.70
Middle Channel: 2441 MHz									
2441	85.86	PK	H	25.75	4.4	27.34	88.67	N/A	N/A
2441	72.63	AV	H	25.75	4.4	27.34	75.44	N/A	N/A
2441	90.06	PK	V	25.75	4.4	27.34	92.87	N/A	N/A
2441	76.54	AV	V	25.75	4.4	27.34	79.35	N/A	N/A
4882	30.45	PK	V	30.79	6.08	27.42	39.90	74.00	34.10
4882	18.77	AV	V	30.79	6.08	27.42	28.22	54.00	25.78
7323	31.98	PK	V	34.38	7.51	25.88	47.99	74.00	26.01
7323	19.37	AV	V	34.38	7.51	25.88	35.38	54.00	18.62
9764	28.8	PK	V	36.33	8.83	27.20	46.76	74.00	27.24
9764	17.85	AV	V	36.33	8.83	27.20	35.81	54.00	18.19
7525	31.63	PK	V	34.82	7.61	26.20	47.86	74.00	26.14
7525	18.89	AV	V	34.82	7.61	26.20	35.12	54.00	18.88
281.6	37.71	QP	H	13.77	2.04	21.51	32.01	46.00	13.99
240.9	36.54	QP	H	12.22	1.86	21.48	29.14	46.00	16.86
High Channel: 2480 MHz									
2480	84.6	PK	H	25.85	4.48	27.36	87.57	N/A	N/A
2480	71.95	AV	H	25.85	4.48	27.36	74.92	N/A	N/A
2480	88.31	PK	V	25.85	4.48	27.36	91.28	N/A	N/A
2480	75.6	AV	V	25.85	4.48	27.36	78.57	N/A	N/A
2483.5	38.25	PK	V	25.86	4.49	27.36	41.24	74.00	32.76
2483.5	26.01	AV	V	25.86	4.49	27.36	29.00	54.00	25.00
4960	30.43	PK	V	31.00	5.90	27.43	39.90	74.00	34.10
4960	18.36	AV	V	31.00	5.90	27.43	27.83	54.00	26.17
7440	31.23	PK	V	34.66	7.58	25.97	47.50	74.00	26.50
7440	19.09	AV	V	34.66	7.58	25.97	35.36	54.00	18.64
9920	29.55	PK	V	36.71	8.87	26.66	48.47	74.00	25.53
9920	18.06	AV	V	36.71	8.87	26.66	36.98	54.00	17.02
7525	31.59	PK	V	34.82	7.61	26.20	47.82	74.00	26.18
7525	18.37	AV	V	34.82	7.61	26.20	34.60	54.00	19.40
281.6	37.52	QP	H	13.77	2.04	21.51	31.82	46.00	14.18
240.9	36.83	QP	H	12.22	1.86	21.48	29.43	46.00	16.57


Conducted Spurious Emissions at Antenna Port*BDR Mode (GFSK):***Low Channel**

Date: 10.JUN.2014 10:10:10


Middle Channel

Date: 10.JUN.2014 10:06:46


High Channel

EDR Mode (($\pi/4$ -DQPSK):


Low Channel




Middle Channel




High Channel



Low Channel



High Channel



FCC §15.247(a) (1) - CHANNEL SEPARATION TEST**Applicable Standard**

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.50 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2014-05-09	2015-05-08

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

1. Set the EUT in transmitting mode, spectrum Bandwidth was set at 30 kHz, maxhold the channel.
2. Set the adjacent channel of the EUT maxhold another trace
3. Measure the channel separation.

Test Data**Environmental Conditions**

Temperature:	28.4 °C
Relative Humidity:	60%
ATM Pressure:	99.6 kPa

The testing was performed by Leon Chen on 2014-06-10.


Test Result: Compliance.

Please refer to following tables and plots


Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)	Result
BDR Mode (GFSK)	Low	2402	1.002	0.69	Pass
	Adjacent	2403			
	Middle	2441	1.002	0.70	Pass
	Adjacent	2442			
	High	2480	1.002	0.70	Pass
	Adjacent	2479			
EDR Mode ($\pi/4$ -DQPSK)	Low	2402	1.002	0.84	Pass
	Adjacent	2403			
	Middle	2441	1.002	0.84	Pass
	Adjacent	2442			
	High	2480	1.002	0.84	Pass
	Adjacent	2479			
EDR Mode (8DPSK)	Low	2402	1.002	0.83	Pass
	Adjacent	2403			
	Middle	2441	1.002	0.83	Pass
	Adjacent	2442			
	High	2480	1.002	0.83	Pass
	Adjacent	2479			


BDR Mode (GFSK):



Middle Channel




High Channel




EDR Mode ($\pi/4$ -DQPSK):

Low Channel



Middle Channel



Delta 1 [T1]

Ref Lvl 0.05 dB RBW 30 kHz RF Att 20 dB

13.5 dBm 1.00200401 MHz SWT 6 ms Unit dBm

4 dB Offset

▼1 [T1] -5.07 dBm

▲1 [T1] 0.05 dB

2.47894088 GHz


1.00200401 MHz


1MAX

Center 2.4795 GHz 200 kHz/ Span 2 MHz

Date: 10.JUN.2014 09:40:57

Low Channel





FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2014-05-09	2015-05-08

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	28.4 °C
Relative Humidity:	60%
ATM Pressure:	99.6 kPa

The testing was performed by Leon Chen on 2014-06-10.

Test Result: Compliance.


Please refer to following tables and plots

Mode	Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
BDR Mode (GFSK)	Low	2402	1.042
	Middle	2441	1.050
	High	2480	1.050
EDR Mode ($\pi/4$ -DQPSK)	Low	2402	1.263
	Middle	2441	1.259
	High	2480	1.263
EDR Mode (8DPSK)	Low	2402	1.242
	Middle	2441	1.242
	High	2480	1.251


BDR Mode (GFSK):



Middle Channel




High Channel




EDR Mode ($\pi/4$ -DQPSK):


Low Channel



Middle Channel




High Channel




EDR Mode (8DPSK):


Low Channel



Middle Channel



High Channel



FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST**Applicable Standard**

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the Max-Hold function record the Quantity of the channel.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2014-05-09	2015-05-08

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	28.4 °C
Relative Humidity:	60%
ATM Pressure:	99.6 kPa

The testing was performed by Leon Chen on 2014-06-10.

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting

BDR Mode (GFSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥ 15


Number of Hopping Channels



EDR Mode ($\pi/4$ -DQPSK):


Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥ 15

Number of Hopping Channels



EDR Mode (8DPSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥ 15

Number of Hopping Channels

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)**Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT was worked in channel hopping; Spectrum SPAN was set as 0. Sweep was set as 0.4 * channel no. (s), the quantity of pulse was get from single sweep. In addition, the time of single pulses was tested.

Dwell Time= time slot length * hope rate/ number of hopping channels * 31.6s
Hop rate=1600/s

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2014-05-09	2015-05-08

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	28.4 °C
Relative Humidity:	60%
ATM Pressure:	99.6 kPa

The testing was performed by Leon Chen on 2014-06-10.


Test Result: Compliance.

Please refer to following tables and plots


Test Mode: Transmitting

BDR Mode (GFSK):

Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
DH1	Low	0.455	0.146	0.4	Pass
	Middle	0.455	0.146	0.4	Pass
	High	0.453	0.145	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/2/79) $\times$ 31.6 s				
DH3	Low	1.719	0.275	0.4	Pass
	Middle	1.725	0.276	0.4	Pass
	High	1.719	0.275	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/4/79) $\times$ 31.6 s				
DH5	Low	2.998	0.320	0.4	Pass
	Middle	2.978	0.318	0.4	Pass
	High	2.998	0.320	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/6/79) $\times$ 31.6 s				


DH1: Low Channel

DH1: Middle Channel




Date: 10.JUN.2014 11:04:14

DH1: High Channel




Date: 10.JUN.2014 11:17:51

DH3: Low Channel



DH3: Middle Channel



Date: 10.JUN.2014 11:23:19

Ref Lvl 13.5 dBm

Delta 1 [T1] -0.86 dB 2.997876 ms

RBW 1 MHz RF Att 20 dB

VBW 3 MHz

SWT 5 ms Unit dBm

4 dB Offset

▼1 [T1] -61.22 dBm

▲1 [T1] -85.450902 μs



-0.86 dB

2.997876 ms

TR


Center 2.402 GHz 500 μs/

Date: 10.JUN.2014 11:33:16


DH5: Middle Channel**DH5: High Channel**

EDR Mode ($\pi/4$ -DQPSK):


Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
DH1	Low	0.461	0.148	0.4	Pass
	Middle	0.461	0.148	0.4	Pass
	High	0.459	0.147	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/2/79) $\times$ 31.6 s				
DH3	Low	1.719	0.275	0.4	Pass
	Middle	1.725	0.276	0.4	Pass
	High	1.725	0.276	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/4/79) $\times$ 31.6 s				
DH5	Low	2.998	0.320	0.4	Pass
	Middle	2.998	0.320	0.4	Pass
	High	2.988	0.319	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/6/79) $\times$ 31.6 s				

DH1: Low Channel


DH1: Middle Channel




DH1: High Channel




DH3: Low Channel




DH3: Middle Channel





DH3: High Channel




DH5: Low Channel




DH5: Middle Channel**DH5: High Channel**

EDR Mode (8DPSK):


Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
DH1	Low	0.465	0.149	0.4	Pass
	Middle	0.457	0.146	0.4	Pass
	High	0.457	0.146	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/2/79) $\times$ 31.6 s				
DH3	Low	1.725	0.276	0.4	Pass
	Middle	1.719	0.275	0.4	Pass
	High	1.726	0.276	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/4/79) $\times$ 31.6 s				
DH5	Low	2.978	0.318	0.4	Pass
	Middle	2.978	0.318	0.4	Pass
	High	3.008	0.321	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/6/79) $\times$ 31.6 s				

DH1: Low Channel


DH1: Middle Channel




DH1: High Channel



DH3: Low Channel



DH3: Middle Channel



Ref Lvl 13.5 dBm
 Delta 1 [T1] 3.12 dB
 RBW 1 MHz
 VBW 3 MHz
 SWT 3 ms
 Unit dBm
 4 dB Offset
 1.725331 ms
 -63.23 dBm
 -65.410822 μs
 3.12 dB
 1.725331 ms
 TR
 Center 2.48 GHz
 300 μs/

Date: 10.JUN.2014 11:22:45

Ref Lvl 13.5 dBm

Delta 1 [T1] 0.01 dB

RBW 1 MHz

VBW 3 MHz

SWT 5 ms

Unit dBm

4 dB Offset

▼1 [T1] -68.01 dBm

▲1 [T1] -75.430862 μs

0.01 dB


2.977836 ms

TR


Center 2.402 GHz

500 μs

Date: 10.JUN.2014 11:30:49

DH5: Middle Channel

Date: 10.JUN.2014 11:31:13

DH5: High Channel

Date: 10.JUN.2014 11:31:39

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
3. Add a correction factor to the display.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2014-05-09	2015-05-08

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	28.4 °C
Relative Humidity:	60%
ATM Pressure:	99.6 kPa


The testing was performed by Leon Chen on 2014-06-10.

Test Result: Compliance.


Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	Peak Output Power (dBm)	Limit (dBm)
BDR Mode (GFSK)	Low	2402	-4.40	30
	Middle	2441	-4.36	30
	High	2480	-3.62	30
EDR Mode ($\pi/4$ -DQPSK)	Low	2402	-3.75	30
	Middle	2441	-3.72	30
	High	2480	-2.99	30
EDR Mode (8DPSK)	Low	2402	-3.11	30
	Middle	2441	-2.99	30
	High	2480	-2.21	30


Note: The data above was tested in conducted mode.

BDR Mode (GFSK):

Output Power, Middle Channel




Output Power, High Channel




EDR Mode ($\pi/4$ -DQPSK):

Output Power, Low Channel




Date: 10.JUN.2014 09:08:29

Output Power, Middle Channel




Date: 10.JUN.2014 09:08:05

Output Power, High Channel




EDR Mode (8DPSK):


Output Power, Low Channel



Output Power, Middle Channel



Output Power, High Channel



FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2014-05-09	2015-05-08

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data


Environmental Conditions

Temperature:	28.4 °C
Relative Humidity:	60%
ATM Pressure:	99.6 kPa

The testing was performed by Leon Chen on 2014-06-10.


Test Result: Compliance
BDR Mode (GFSK):

Band Edge, Left Side



Date: 10.JUN.2014 09:59:36


Band Edge, Right Side




Date: 10.JUN.2014 09:58:22

EDR Mode (π 4-DQPSK):

Band Edge, Left Side




Band Edge, Right Side




EDR Mode (8DPSK):

Band Edge, Left Side



Band Edge, Right Side



***** END OF REPORT *****