



CETECOM ICT Services is now

CTC | **advanced**
member of RWTÜV group

TEST REPORT

Test report no.: 1-1633/16-01-06-B



Deutsche
Akkreditierungsstelle
D-PL-12076-01-01

Testing laboratory

CTC advanced GmbH

Untertuerkheimer Strasse 6 – 10
66117 Saarbruecken / Germany
Phone: + 49 681 5 98 - 0
Fax: + 49 681 5 98 - 9075
Internet: <http://www.ctcadvanced.com>
e-mail: mail@ctcadvanced.com

Accredited Testing Laboratory:

The testing laboratory (area of testing) is accredited according to DIN EN ISO/IEC 17025 (2005) by the Deutsche Akkreditierungsstelle GmbH (DAKKS). The accreditation is valid for the scope of testing procedures as stated in the accreditation certificate with the registration number: D-PL-12076-01-01.

Applicant

Ingenico Group

9 Avenue de la Gare Rovaltain
26958 Valence Cedex 9 / FRANCE
Phone: -/-
Fax: -/-
Contact: Jean-Baptiste Palisse
e-mail: jean-baptiste.palisse@ingenico.com
Phone: +33 4 75 84 21 74

Manufacturer

Flextronics Technology (M) Sdn. Bhd

Plot D26, Jalan DPB/4 Kawasan Zon Perindustrian
Bebas, PTP
81560 Gelang Patah, Johor / MALAYSIA

Test standard/s

47 CFR Part 15	Title 47 of the Code of Federal Regulations; Chapter I; Part 15 - Radio frequency devices
RSS - 247 Issue 2	Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence - Exempt Local Area Network (LE-LAN) Devices
RSS - Gen Issue 4	Spectrum Management and Telecommunications Radio Standards Specifications - General Requirements and Information for the Certification of Radio Apparatus

For further applied test standards please refer to section 3 of this test report.

Test Item

Kind of test item:	Communication dongle
Model name:	Xtra module
FCC ID:	XKB-M7002WIBT
IC:	2586D-M7002WIBT
Frequency:	DTS band 2400 MHz to 2483.5 MHz
Technology tested:	WLAN (DSSS/b-mode; OFDM/g-,n HT20 & 40-mode)
Antenna:	Integrated flex antenna
Power supply:	110 V AC & 5 V DC by mains adapter / battery
Temperature range:	0°C to +50°C



This test report is electronically signed and valid without handwriting signature. For verification of the electronic signature, the public keys can be requested at the testing laboratory.

Test report authorized:


cn=Stefan Boes, o=CTC advanced GmbH,
ou=BOE-161129,
email=Stefan.Boes@ctcadvanced.com, c=DE
2017.07.06 10:11:57 +02'00'

Stefan Böes
Lab Manager
Radio Communications & EMC

Test performed:


cn=Mihail Dorongovskij, o=CTC advanced
GmbH, ou=DOR-281116,
email=Mihail.Dorongovskij@ctcadvanced.co
m, c=DE
2017.07.06 10:09:18 +02'00'

Mihail Dorongovskij
Testing Manager
Radio Communications & EMC

1 Table of contents

1	Table of contents.....	2
2	General information	3
2.1	Notes and disclaimer	3
2.2	Application details	3
2.3	Test laboratories sub-contracted	3
3	Test standard/s and references.....	4
4	Test environment	5
5	Test item	5
5.1	General description.....	5
5.2	Additional information	5
6	Description of the test setup	6
6.1	Shielded semi anechoic chamber	7
6.2	Shielded fully anechoic chamber	8
6.3	Radiated measurements > 18 GHz	9
6.4	AC conducted	10
6.5	Conducted measurements with peak power meter & spectrum analyzer.....	11
7	Sequence of testing	12
7.1	Sequence of testing radiated spurious 9 kHz to 30 MHz	12
7.2	Sequence of testing radiated spurious 30 MHz to 1 GHz	13
7.3	Sequence of testing radiated spurious 1 GHz to 18 GHz	14
7.4	Sequence of testing radiated spurious above 18 GHz	15
8	Measurement uncertainty.....	16
9	Summary of measurement results	17
10	Additional comments.....	18
11	Measurement results	19
11.1	Antenna gain.....	19
11.2	Identify worst case data rate.....	20
11.3	Maximum output power	21
11.4	Duty cycle	23
11.5	Peak power spectral density	24
11.6	6 dB DTS bandwidth	38
11.7	Occupied bandwidth – 99% emission bandwidth	52
11.8	Occupied bandwidth – 20 dB bandwidth	66
11.9	Band edge compliance conducted.....	79
11.10	Spurious emissions conducted	85
11.11	Spurious emissions radiated below 30 MHz	111
11.12	Spurious emissions radiated 30 MHz to 1 GHz	118
11.13	Spurious emissions radiated above 1 GHz	129
11.14	Spurious emissions conducted below 30 MHz (AC conducted).....	142
12	Observations	145
Annex A	Document history	145
Annex B	Further information.....	145
Annex C	Accreditation Certificate	146

2 General information

2.1 Notes and disclaimer

The test results of this test report relate exclusively to the test item specified in this test report. CTC advanced GmbH does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item.

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CTC advanced GmbH.

The testing service provided by CTC advanced GmbH has been rendered under the current "General Terms and Conditions for CTC advanced GmbH".

CTC advanced GmbH will not be liable for any loss or damage resulting from false, inaccurate, inappropriate or incomplete product information provided by the customer.

Under no circumstances does the CTC advanced GmbH test report include any endorsement or warranty regarding the functionality, quality or performance of any other product or service provided.

Under no circumstances does the CTC advanced GmbH test report include or imply any product or service warranties from CTC advanced GmbH, including, without limitation, any implied warranties of merchantability, fitness for purpose, or non-infringement, all of which are expressly disclaimed by CTC advanced GmbH.

All rights and remedies regarding vendor's products and services for which CTC advanced GmbH has prepared this test report shall be provided by the party offering such products or services and not by CTC advanced GmbH. In no case this test report can be considered as a Letter of Approval.

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

This test report replaces the test report with the number 1-1633/16-01-06-A and dated 2017-07-04

2.2 Application details

Date of receipt of order:	2016-06-06
Date of receipt of test item:	2017-03-01
Start of test:	2017-03-01
End of test:	2017-06-16
Person(s) present during the test:	-/-

2.3 Test laboratories sub-contracted

None

3 Test standard/s and references

Test standard	Date	Description
47 CFR Part 15	-/-	Title 47 of the Code of Federal Regulations; Chapter I; Part 15 - Radio frequency devices
RSS - 247 Issue 2	February 2017	Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSs) and Licence - Exempt Local Area Network (LE-LAN) Devices
RSS - Gen Issue 4	November 2014	Spectrum Management and Telecommunications Radio Standards Specifications - General Requirements and Information for the Certification of Radio Apparatus

Guidance	Version	Description
DTS: KDB 558074 D01	v03r05	Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247
ANSI C63.4-2014	-/-	American national standard for methods of measurement of radio-noise emissions from low-voltage electrical and electronic equipment in the range of 9 kHz to 40 GHz
ANSI C63.10-2013	-/-	American national standard of procedures for compliance testing of unlicensed wireless devices

4 Test environment

Temperature	:	T _{nom} T _{max} T _{min}	+22 °C during room temperature tests No tests under extreme temperature conditions required. No tests under extreme temperature conditions required.
Relative humidity content	:		55 %
Barometric pressure	:		1021 hpa
Power supply	:	V _{nom} V _{max} V _{min}	110 V AC & 5 V DC by mains adapter / battery No tests under extreme voltage conditions required. No tests under extreme voltage conditions required.

5 Test item

5.1 General description

Kind of test item	:	Communication dongle
Type identification	:	Xtra module
HMN	:	-/-
PMN	:	XTRA module
HVIN	:	XTRA module MODU/7002 WiFi/BT
FVIN	:	-/-
S/N serial number	:	Radiated module: 162013413091023800001537 Conducted module: 162003413091023800001467 Main part: 161793413031023700001364
HW hardware status	:	01
SW software status	:	OS 034010 / HTB 0072
Frequency band	:	DTS band 2400 MHz to 2483.5 MHz (lowest channel 2412 MHz; highest channel 2462 MHz)
Type of radio transmission	:	DSSS, OFDM
Use of frequency spectrum	:	
Type of modulation	:	(D)BPSK, (D)QPSK, 16 – QAM, 64 – QAM
Number of channels	:	11 (20 MHz); 9 (40 MHz)
Antenna	:	Integrated flex antenna
Power supply	:	115 V AC & 5 V DC by mains adapter / battery
Temperature range	:	0°C to +50°C

5.2 Additional information

The content of the following annexes is defined in the QA. It may be that not all of the listed annexes are necessary for this report, thus some values in between may be missing.

Test setup- and EUT-photos are included in test report:

1-1633/16-01-01_AnnexA
 1-1633/16-01-01_AnnexB
 1-1633/16-01-01_AnnexD

6 Description of the test setup

Typically, the calibrations of the test apparatus are commissioned to and performed by an accredited calibration laboratory. The calibration intervals are determined in accordance with the DIN EN ISO/IEC 17025. In addition to the external calibrations, the laboratory executes comparison measurements with other calibrated test systems or effective verifications. Weekly chamber inspections and range calibrations are performed. Where possible, RF generating and signaling equipment as well as measuring receivers and analyzers are connected to an external high-precision 10 MHz reference (GPS-based or rubidium frequency standard).


In order to simplify the identification of the equipment used at some special tests, some items of test equipment and ancillaries can be provided with an identifier or number in the equipment list below (Lab/Item).

Agenda: Kind of Calibration

k	calibration / calibrated	EK	limited calibration
ne	not required (k, ev, izw, zw not required)	zw	cyclical maintenance (external cyclical maintenance)
ev	periodic self verification	izw	internal cyclical maintenance
Ve	long-term stability recognized	g	blocked for accredited testing
vk!	Attention: extended calibration interval		
NK!	Attention: not calibrated	*)	next calibration ordered / currently in progress

6.1 Shielded semi anechoic chamber

The radiated measurements are performed in vertical and horizontal plane in the frequency range from 9 kHz to 1 GHz in semi-anechoic chambers. The EUT is positioned on a non-conductive support with a height of 0.80 m above a conductive ground plane that covers the whole chamber. The receiving antennas are conform to specifications ANSI C63. These antennas can be moved over the height range between 1.0 m and 4.0 m in order to search for maximum field strength emitted from EUT. The measurement distances between EUT and receiving antennas are indicated in the test setups for the various frequency ranges. For each measurement, the EUT is rotated in all three axes until the maximum field strength is received. The wanted and unwanted emissions are received by spectrum analyzers where the detector modes and resolution bandwidths over various frequency ranges are set according to requirement ANSI C63.



Measurement distance: tri-log antenna 10 meter

$$FS = UR + CL + AF$$

(FS-field strength; UR-voltage at the receiver; CL-loss of the cable; AF-antenna factor)


Example calculation:

$$FS [dB\mu V/m] = 12.35 [dB\mu V/m] + 1.90 [dB] + 16.80 [dB/m] = 31.05 [dB\mu V/m] (35.69 \mu V/m)$$

Equipment table:

No.	Lab / Item	Equipment	Type	Manufacturer	Serial No.	INV. No.	Kind of Calibration	Last Calibration	Next Calibration
1	A	Switch-Unit	3488A	HP	2719A14505	300000368	ev	-/-	-/-
2	A	Meßkabine 1	HF-Absorberhalle	MWB AG 300023	101042	300000551	ne	-/-	-/-
3	A	EMI Test Receiver	ESCI 3	R&S	100083	300003312	k	01.02.2017	31.01.2018
4	A	Analyzer-Reference-System (Harmonics and Flicker)	ARS 16/1	SPS	A3509 07/0 0205	300003314	Ve	02.02.2016	02.02.2018
5	A	Antenna Tower	Model 2175	ETS-Lindgren	64762	300003745	izw	-/-	-/-
6	A	Positioning Controller	Model 2090	ETS-Lindgren	64672	300003746	izw	-/-	-/-
7	A	Turntable Interface-Box	Model 105637	ETS-Lindgren	44583	300003747	izw	-/-	-/-
8	A	TRILOG Broadband Test-Antenna 30 MHz - 3 GHz	VULB9163	Schwarzbeck	295	300003787	k	25.04.2016	25.04.2018

6.2 Shielded fully anechoic chamber



Measurement distance: tri-log antenna and horn antenna 3 meter; loop antenna 3 meter

FS = UR + CA + AF

(FS-field strength; UR-voltage at the receiver; CA-loss of the signal path; AF-antenna factor)

Example calculation:


FS [dBμV/m] = 40.0 [dBμV/m] + (-35.8) [dB] + 32.9 [dB/m] = 37.1 [dBμV/m] (71.61 μV/m)

Equipment table:

No.	Lab / Item	Equipment	Type	Manufacturer	Serial No.	INV. No.	Kind of Calibration	Last Calibration	Next Calibration
1	C	Active Loop Antenna 10 kHz to 30 MHz	6502	EMCO/2	8905-2342	300000256	k	24.06.2015	24.06.2017
2	A	Double-Ridged Waveguide Horn Antenna 1-18.0GHz	3115	EMCO	9709-5290	300000212	k	13.08.2015	13.08.2017
3	A	Highpass Filter	WHK1.1/15G-10SS	Wainwright	37	400000148	ne	-/-	-/-
4	A	Highpass Filter	WHKX7.0/18G-8SS	Wainwright	18	300003789	ne	-/-	-/-
5	A	Band Reject Filter	WRCG2400/2483-2375/2505-50/10SS	Wainwright	26	300003792	ne	-/-	-/-
6	A, B	TRILOG Broadband Test-Antenna 30 MHz - 3 GHz	VULB9163	Schwarzbeck	371	300003854	vIKI!	29.10.2014	29.10.2017
7	A, B	Broadband Amplifier 0.5-18 GHz	CBLU5184540	CERNEX	22051	300004483	ev	-/-	-/-
8	A, B, C	4U RF Switch Platform	L4491A	Agilent Technologies	MY50000032	300004510	ne	-/-	-/-
9	A, B, C	Messrechner und Monitor	Intel Core i3 3220/3,3 GHz, Prozessor	Huber & Suhner	2V2403033A54 21	300004591	ne	-/-	-/-
10	A, B, C	NEXO EMV-Software	BAT EMC V3.16.0.49	EMCO	Batch no. 14844	300004682	ne	-/-	-/-
11	A, B, C	Anechoic chamber	ESH3-Z5	TDK	893045/004	300003726	ne	-/-	-/-
12	A, B, C	EMI Test Receiver 9kHz-26,5GHz	ESR26	R&S	101376	300005063	vIKI!	13.09.2016	13.03.2018

6.3 Radiated measurements > 18 GHz

Radiated measurements > 18 GHz



Measurement distance: horn antenna 50 cm

$$FS = U_R + CA + AF$$

(FS-field strength; U_R -voltage at the receiver; CA-loss signal path & distance correction; AF-antenna factor)


Example calculation:

$$FS \text{ [dB}\mu\text{V/m]} = 40.0 \text{ [dB}\mu\text{V/m]} + (-60.1) \text{ [dB]} + 36.74 \text{ [dB/m]} = 16.64 \text{ [dB}\mu\text{V/m]} \text{ (6.79 } \mu\text{V/m)}$$

Equipment table:

No.	Lab / Item	Equipment	Type	Manufacturer	Serial No.	INV. No.	Kind of Calibration	Last Calibration	Next Calibration
1	A	Std. Gain Horn Antenna 18.0 to 26.5 GHz	638	Narda	-/-	300000486	k	10.09.2015	10.09.2017
2	A	Signal Analyzer 40 GHz	FSV40	R&S	101042	300004517	k	27.01.2017	26.01.2018
3	A	Microwave System Amplifier, 0.5-26.5 GHz	83017A	HP	00419	300002268	ev	-/-	-/-
4	A	RF-Cable	ST18/SMAM/SMAM/48	Huber & Suhner	Batch no. 600918	400001182	ev	-/-	-/-
5	A	RF-Cable	ST18/SMAM/SMAM/48	Huber & Suhner	Batch no. 127377	400001183	ev	-/-	-/-
6	A	DC-Blocker 0.1-40 GHz	8141A	Inmet	-/-	400001185	ev	-/-	-/-

6.4 AC conducted



$$FS = UR + CF + VC$$

(FS-field strength; UR-voltage at the receiver; CR-loss of the cable and filter; VC-correction factor of the ISN)

Example calculation:


$$FS [dB\mu V/m] = 37.62 [dB\mu V/m] + 9.90 [dB] + 0.23 [dB] = 47.75 [dB\mu V/m] \quad (244.06 \mu V/m)$$

Equipment table:

No.	Lab / Item	Equipment	Type	Manufacturer	Serial No.	INV. No.	Kind of Calibration	Last Calibration	Next Calibration
1	A	Two-line V-Network (LISN) 9 kHz to 30 MHz	ESH3-Z5	R&S	893045/004	300000584	k	31.01.2017	30.01.2018
2	A	RF-Filter-section	85420E	HP	3427A00162	300002214	k	27.11.2006	-/-
3	A	EM-Injection Clamp AC-Spannungsquelle variabel	FCC-203i	emv	232	300000626	ev	18.05.2001	-/-
4	A	Spannungsquelle variabel	MV2616-V	EM-Test	0397-12	300003259	k	11.12.2015	11.12.2017
5	A	Hochpass 150 kHz	EZ-25	R&S	100010	300003798	ev	08.04.2008	-/-
6	A	MXE EMI Receiver 20 Hz to 26,5 GHz	N9038A	Agilent Technologies	MY51210197	300004405	k	16.08.2016	16.08.2017

6.5 Conducted measurements with peak power meter & spectrum analyzer

Conducted measurements normal conditions



$$OP = AV + CA$$

(OP-output power; AV-analyzer value; CA-loss signal path)

Example calculation:

$$OP \text{ [dBm]} = 6.0 \text{ [dBm]} + 11.7 \text{ [dB]} = 17.7 \text{ [dBm]} (58.88 \text{ mW})$$

Equipment table:

No.	Lab / Item	Equipment	Type	Manufacturer	Serial No.	INV. No.	Kind of Calibration	Last Calibration	Next Calibration
1	A, B	Switch / Control Unit	3488A	HP	2719A15013	300000151	ne	-/-	-/-
2	A, B	PC-WLAN Tester	Intel Core i3 3220/3,3 GHz, Prozessor	R&S	2V2403033A4523	300004589	ne	-/-	-/-
3	A, B	Teststand	Teststand Custom Sequence Editor	National Instruments GmbH	2V2403033A4523	300004590	ne	-/-	-/-
4	A	Power Sensor	NRP-Z81	R&S	100010	300003780	k	26.01.2017	25.01.2019
5	A, B	PowerSplitter/Combiner 150-6000MHz N-Type	ZB3PD-63-N+	Mini-Circuits	100010	400000451	ev	-/-	-/-
6	A, B	RF-Cable	ST18/SMAM/SMAM/60	Huber & Suhner	Batch no. 606844	400001181	ev	-/-	-/-
7	A, B	Coax Attenuator 10 dB 2W 0-40 GHz	MCL BW-K10-2W44+	Mini Circuits	Batch no. 606844	400001186	ev	-/-	-/-
8	B	DC-Blocker 0.1-40 GHz	8141A	Inmet	Batch no. 127377	400001185	ev	-/-	-/-
9	B	Signal Analyzer 40 GHz	FSV40	R&S	101042	300004517	k	27.01.2017	26.01.2018

7 Sequence of testing

7.1 Sequence of testing radiated spurious 9 kHz to 30 MHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a 2-axis positioner with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed directly on the turn table.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

Premeasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 1.5 m.
- At each turntable position the analyzer sweeps with positive-peak detector to find the maximum of all emissions.

Final measurement

- Identified emissions during the premeasurement are maximized by the software by rotating the turntable from 0° to 360°. In case of the 2-axis positioner is used the elevation axis is also rotated from 0° to 360°.
- The final measurement is done in the position (turntable and elevation) causing the highest emissions with quasi-peak (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. A plot with the graph of the premeasurement and the limit is stored.

7.2 Sequence of testing radiated spurious 30 MHz to 1 GHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 10 m or 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

Premeasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 m to 3 m.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement

- The final measurement is performed for at least six highest peaks according to the requirements of the ANSI C63.4.
- Based on antenna and turntable positions at which the peak values are measured the software maximize the peaks by changing turntable position $\pm 45^\circ$ and antenna height between 1 and 4 m.
- The final measurement is done with quasi-peak detector (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement with marked maximum final results and the limit is stored.

7.3 Sequence of testing radiated spurious 1 GHz to 18 GHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a 2-axis positioner with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed directly on the turn table.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

Premeasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height is 1.5 m.
- At each turntable position and antenna polarization the analyzer sweeps with positive peak detector to find the maximum of all emissions.

Final measurement

- The final measurement is performed for at least six highest peaks according to the requirements of the ANSI C63.4.
- Based on antenna and turntable positions at which the peak values are measured the software maximizes the peaks by rotating the turntable from 0° to 360°. This measurement is repeated for different EUT-table positions (0° to 150° in 30°-steps) and for both antenna polarizations.
- The final measurement is done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and RMS detector (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement with marked maximum final results and the limit is stored.

7.4 Sequence of testing radiated spurious above 18 GHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet.
- The measurement distance is as appropriate (e.g. 0.5 m).
- The EUT is set into operation.

Premeasurement

- The test antenna is handheld and moved carefully over the EUT to cover the EUT's whole sphere and different polarizations of the antenna.

Final measurement

- The final measurement is performed at the position and antenna orientation causing the highest emissions with Peak and RMS detector (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement and the limit is stored.

8 Measurement uncertainty

Measurement uncertainty	
Test case	Uncertainty
Antenna gain	± 3 dB
Power spectral density	± 1.5 dB
DTS bandwidth	± 100 kHz (depends on the used RBW)
Occupied bandwidth	± 100 kHz (depends on the used RBW)
Maximum output power	± 1.5 dB
Detailed spurious emissions @ the band edge - conducted	± 1.5 dB
Band edge compliance radiated	± 3 dB
Spurious emissions conducted	± 3 dB
Spurious emissions radiated below 30 MHz	± 3 dB
Spurious emissions radiated 30 MHz to 1 GHz	± 3 dB
Spurious emissions radiated 1 GHz to 12.75 GHz	± 3.7 dB
Spurious emissions radiated above 12.75 GHz	± 4.5 dB
Spurious emissions conducted below 30 MHz (AC conducted)	± 2.6 dB

9 Summary of measurement results

☒	No deviations from the technical specifications were ascertained
☐	There were deviations from the technical specifications ascertained
☐	This test report is only a partial test report. The content and verdict of the performed test cases are listed below.

TC Identifier	Description	Verdict	Date	Remark
RF-Testing	CFR Part 15 RSS - 247, Issue 2	See table!	2017-07-06	-/-

Test specification clause	Test case	Guideline	Temperature conditions	Power source voltages	Mode	C	NC	NA	NP	Remark
§15.247(b)(4) RSS - 247 / 5.4 (4)	Antenna gain	-/-	Nominal	Nominal	DSSS	-/-				-/-
RSS - 247 / 6.0	Duty cycle	-/-	Nominal	Nominal	DSSS OFDM	-/-				-/-
§15.247(e) RSS - 247 / 5.2 (2)	Power spectral density	KDB 558074 DTS clause: 10.2	Nominal	Nominal	DSSS OFDM	☒	☐	☐	☐	-/-
§15.247(a)(2) RSS - 247 / 5.2 (1)	DTS bandwidth	KDB 558074 DTS clause: 8.1	Nominal	Nominal	DSSS OFDM	☒	☐	☐	☐	-/-
RSS Gen clause 4.6.1	Occupied bandwidth	-/-	Nominal	Nominal	DSSS OFDM	☒	☐	☐	☐	-/-
§15.247(b)(3) RSS - 247 / 5.4 (4)	Maximum output power	KDB 558074 DTS clause: 9.1.2	Nominal	Nominal	DSSS OFDM	☒	☐	☐	☐	-/-
§15.247(d) RSS - 247 / 5.5	Detailed spurious emissions @ the band edge - conducted	-/-	Nominal	Nominal	DSSS OFDM	☒	☐	☐	☐	-/-
§15.205 RSS - 247 / 5.5 RSS - Gen	Band edge compliance conducted and radiated	KDB 558074 DTS clause: 13.3.2 and clause 12.2.2	Nominal	Nominal	DSSS OFDM	☒	☐	☐	☐	-/-
§15.247(d) RSS - 247 / 5.5	TX spurious emissions conducted	KDB 558074 DTS clause: 11.1 & 11.2 11.3	Nominal	Nominal	DSSS OFDM	☒	☐	☐	☐	-/-
§15.209(a) RSS-Gen	TX spurious emissions radiated below 30 MHz	-/-	Nominal	Nominal	DSSS OFDM	☒	☐	☐	☐	-/-
§15.247(d) RSS - 247 / 5.5 RSS-Gen	TX spurious emissions radiated 30 MHz to 1 GHz	-/-	Nominal	Nominal	DSSS OFDM	☒	☐	☐	☐	-/-
§15.247(d) RSS - 247 / 5.5 RSS-Gen	TX spurious emissions radiated above 1 GHz	-/-	Nominal	Nominal	DSSS OFDM	☒	☐	☐	☐	-/-
§15.109 RSS-Gen	RX spurious emissions radiated 30 MHz to 1 GHz	-/-	Nominal	Nominal	RX / idle	☒	☐	☐	☐	-/-
§15.109 RSS-Gen	RX spurious emissions radiated above 1 GHz	-/-	Nominal	Nominal	RX / idle	☒	☐	☐	☐	-/-
§15.107(a) §15.207	Conducted emissions < 30 MHz	-/-	Nominal	Nominal	DSSS OFDM	☒	☐	☐	☐	-/-

Note: C = Compliant; NC = Not compliant; NA = Not applicable; NP = Not performed

10 Additional comments

Reference documents: Customer Questionnaire_XTRA module_CETECOM.docx
 ICO-OPE-03994 Wifi_labtool_Radio_agreement_procedure.pdf

Special test descriptions: Used power settings for all tests:

Channel	1	2	3	4	5	6	7	8	9	10	11
11b	15	15	15	15	15	15	15	15	15	15	15
11g	12	15	16	16	16	16	16	16	16	14	10
11n-20	11	15	15	15	15	15	15	15	15	14	10
11n-40			9	11	12	13	13	12	8		

Configuration descriptions: None

Test mode: ☐ No test mode available.
 lperf was used to ping another device with the largest support packet size

☒ Special software is used.
 EUT is transmitting pseudo random data by itself

Antennas and transmit operating modes:

- ☒ Operating mode 1 (single antenna)
- Equipment with 1 antenna,
 - Equipment with 2 diversity antennas operating in switched diversity mode by which at any moment in time only 1 antenna is used,
 - Smart antenna system with 2 or more transmit/receive chains, but operating in a mode where only 1 transmit/receive chain is used)
- ☐ Operating mode 2 (multiple antennas, no beamforming)
- Equipment operating in this mode contains a smart antenna system using two or more transmit/receive chains simultaneously but without beamforming.
- ☐ Operating mode 3 (multiple antennas, with beamforming)
- Equipment operating in this mode contains a smart antenna system using two or more transmit/receive chains simultaneously with beamforming.
 In addition to the antenna assembly gain (G), the beamforming gain (Y) may have to be taken into account when performing the measurements.

11 Measurement results

11.1 Antenna gain

Measurement:

The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module. For normal WLAN devices, the DSSS mode is used.

Measurement parameters:

Measurement parameter	
Detector:	Peak
Sweep time:	Auto
Resolution bandwidth:	3 MHz
Video bandwidth:	3 MHz
Trace mode:	Max hold
Test setup:	See sub clause 6.2 – B (radiated) See sub clause 6.5 – B (conducted)
Measurement uncertainty:	See sub clause 8

Limits:

FCC	IC
6 dBi / > 6 dBi output power and power density reduction required	

Results:

T _{nom}	V _{nom}	lowest channel 2412 MHz	middle channel 2437 MHz	highest channel 2462 MHz
Conducted power [dBm] Measured with DSSS modulation		14.3	14.0	14.5
Radiated power [dBm] Measured with DSSS modulation		15.6	16.0	16.9
Gain [dBi] Calculated		1.3	2.0	2.4

11.2 Identify worst case data rate

Measurement:

All modes of the module will be measured with an average power meter or spectrum analyzer to identify the maximum transmission power.

In further tests only the identified worst case modulation scheme or bandwidth will be measured and this mode is used as representative mode for all other modulation schemes.

Additional the band edge compliance test will be performed in the lowest and highest modulation scheme.

Measurement parameters:

Measurement parameter	
Detector:	Peak
Sweep time:	Auto
Resolution bandwidth:	3 MHz
Video bandwidth:	3 MHz
Trace mode:	Max hold
Test setup:	See sub clause 6.5 – A
Measurement uncertainty:	-/-

Results:

Modulation	Modulation scheme / bandwidth
DSSS / b – mode	1 Mbit/s
OFDM / g – mode	6 Mbit/s
OFDM / n HT20 – mode	MCS0
OFDM / n HT40 – mode	MCS0

11.3 Maximum output power

Description:

Measurement of the maximum output power conducted and radiated. The measurements are performed using the data rate producing the highest conducted output power.

Measurement:

Measurement parameter	
According to DTS clause: 9.1.2	
Peak power meter	
Test setup:	See sub clause 6.5 – A
Measurement uncertainty	See sub clause 8

Limits:

FCC	IC
Conducted: 1.0 W – Antenna gain with max. 6 dBi	

Results:

	Maximum Output Power [dBm]						
Frequency	2412 MHz	2417 MHz	2422 MHz	2437 MHz	2457 MHz	2462 MHz	
Output power conducted DSSS / b – mode	16.3			16.1		16.5	
Output power conducted OFDM / g – mode	21.6	20.9	20.9	23.4	22.9	19.8	
Output power conducted OFDM / n HT20 – mode	20.4	20.6		22.9	22.7	19.2	
Frequency	2422 MHz	2427 MHz	2432 MHz	2437 MHz	2442 MHz	2447 MHz	2452 MHz
Output power conducted OFDM / n HT40 – mode	19.5	20.6	21.0	21.0	20.9	21.0	16.7

11.4 Duty cycle

Measurement:

Measurement parameters:

Measurement parameter	
Detector:	Peak
Sweep time:	Depends on the signal see plot
Resolution bandwidth:	10 MHz
Video bandwidth:	10 MHz
Trace mode:	Max hold
Test setup:	See sub clause 6.5 - B
Measurement uncertainty:	See sub clause 8

Limits:

FCC	IC
-/-	

Results:

T _{nom}	V _{nom}	lowest channel 2412 MHz	middle channel 2437 MHz	highest channel 2462 MHz
DSSS / b – mode		100 % / 0.0 dB	100 % / 0.0 dB	100 % / 0.0 dB
OFDM / g – mode		100 % / 0.0 dB	100 % / 0.0 dB	100 % / 0.0 dB
OFDM / n HT20 – mode		100 % / 0.0 dB	100 % / 0.0 dB	100 % / 0.0 dB
T _{nom}	V _{nom}	lowest channel 2422 MHz	middle channel 2437 MHz	highest channel 2452 MHz
OFDM / n HT40 – mode		100 % / 0.0 dB	100 % / 0.0 dB	100 % / 0.0 dB

11.5 Peak power spectral density

Description:

Measurement of the power spectral density of a digital modulated system. The measurement is repeated for both modulations at the lowest, middle and highest channel.

Measurement:

Measurement parameter	
According to DTS clause: 10.2	
Detector:	Positive Peak
Sweep time:	Auto
Resolution bandwidth:	100 kHz
Video bandwidth:	300 kHz
Span:	30 MHz
Trace mode:	Max hold (allow trace to fully stabilize)
Test setup:	See sub clause 6.5 - B
Measurement uncertainty	See sub clause 8

Limits:


FCC	IC
8 dBm / 3kHz (conducted)	

Results:


Modulation	Peak power spectral density [dBm]						
Frequency	2412 MHz	2417 MHz	2422 MHz	2437 MHz	2457 MHz	2462 MHz	
Output power conducted DSSS / b – mode	3.3			3.0		3.4	
Output power conducted OFDM / g – mode	-3.2	-2.8	-3.7	-0.1	-0.9	-3.2	
Output power conducted OFDM / n HT20 – mode	-4.0	-3.2		-0.8	-0.6	-5.2	
Frequency	2422 MHz	2427 MHz	2432 MHz	2437 MHz	2442 MHz	2447 MHz	2452 MHz
Output power conducted OFDM / n HT40 – mode	-7.3	-5.7	-6.7	-4.3	-7.2	-7.0	-11.0

Plots: DSSS / b – mode


Plot 1: Channel 1



Plot 2: Channel 6




Plot 3: Channel 11



Date: 12.JUN.2017 10:37:02


Plots: OFDM / g – mode

Plot 1: Channel 1




Date: 16.JUN.2017 13:13:42

Plot 2: Channel 2




Date: 02.03.2017 15:12:25


Plot 3: Channel 3




Plot 4: Channel 6



Plot 5: Channel 10




Plot 6: Channel 11




Plots: OFDM / n HT20 – mode


Plot 1: Channel 1




Plot 2: Channel 2




Plot 3: Channel 6



Plot 4: Channel 10




Plot 5: Channel 11




Date: 16.JUN.2017 13:45:12

Plots: OFDM / n HT40 – mode


Plot 1: Channel 3




Plot 2: Channel 4




Plot 3: Channel 5



Plot 4: Channel 6




Plot 5: Channel 7




Date: 2.MAR.2017 17:17:50

Plot 6: Channel 8



Date: 2.MAR.2017 17:30:32

Plot 7: Channel 9



Date: 16.JUN.2017 14:10:50

11.6 6 dB DTS bandwidth

Description:

Measurement of the 6 dB bandwidth of the modulated signal.

Measurement:

Measurement parameter	
According to DTS clause: 8.1	
Detector:	Peak
Sweep time:	Auto
Resolution bandwidth:	100 kHz
Video bandwidth:	500 kHz
Span:	30 MHz / 50 MHz
Trace mode:	Single count with 200 counts
Test setup:	See sub clause 6.5 - B
Measurement uncertainty	See sub clause 8

Limits:


FCC	IC
Systems using digital modulation techniques may operate in the 2400–2483.5 MHz band. The minimum 6 dB bandwidth shall be at least 500 kHz.	

Results:


	6 dB DTS bandwidth [kHz]						
Frequency	2412 MHz	2417 MHz	2422 MHz	2437 MHz	2457 MHz	2462 MHz	
Output power conducted DSSS / b – mode	10049			10052			10046
Output power conducted OFDM / g – mode	16549	16543	16549	16561	16564		16543
Output power conducted OFDM / n HT20 – mode	17803	17818		17794	17800		17659
Frequency	2422 MHz	2427 MHz	2432 MHz	2437 MHz	2442 MHz	2447 MHz	2452 MHz
Output power conducted OFDM / n HT40 – mode	36519	36554	36560	36548	36554	36512	36548

Plots: DSSS / b – mode


Plot 1: Channel 1



Plot 2: Channel 6




Plot 3: Channel 11




Plots: OFDM / g – mode


Plot 1: Channel 1




Plot 2: Channel 2




Plot 3: Channel 3




Plot 4: Channel 6



Plot 5: Channel 10




Plot 6: Channel 11




Plots: OFDM / n HT20 – mode


Plot 1: Channel 1




Plot 2: Channel 2




Plot 3: Channel 6



Plot 4: Channel 10




Plot 5: Channel 11




Date: 16.JUN.2017 13:43:05

Plots: OFDM / n HT40 – mode


Plot 1: Channel 3




Plot 2: Channel 4




Plot 3: Channel 5




Plot 4: Channel 6




Plot 5: Channel 7



Plot 6: Channel 8



Plot 7: Channel 9



Date: 16.JUN.2017 14:07:56

11.7 Occupied bandwidth – 99% emission bandwidth

Description:

Measurement of the 99% bandwidth of the modulated signal acc. RSS-GEN.

Measurement:

Measurement parameter	
Detector:	Peak
Sweep time:	Auto
Resolution bandwidth:	300 kHz
Video bandwidth:	1 MHz
Span:	30 MHz / 50 MHz
Measurement procedure:	Measurement of the 99% bandwidth using the integration function of the analyzer
Trace mode:	Single count with 200 counts
Test setup:	See sub clause 6.5 - B
Measurement uncertainty	See sub clause 8

Usage:


-/-	IC
OBW is necessary for Emission Designator	

Results:


Modulation	99% bandwidth [kHz]						
Frequency	2412 MHz	2417 MHz	2422 MHz	2437 MHz	2457 MHz	2462 MHz	
Output power conducted DSSS / b – mode	13625			13601			13607
Output power conducted OFDM / g – mode	16738	16942	16975	16873	16864		16750
Output power conducted OFDM / n HT20 – mode	17878	18037		17926	17926		17896
Frequency	2422 MHz	2427 MHz	2432 MHz	2437 MHz	2442 MHz	2447 MHz	2452 MHz
Output power conducted OFDM / n HT40 – mode	36842	36860	36956	36932	36932	36938	36842

Plots: DSSS / b – mode


Plot 1: Channel 1



Plot 2: Channel 6




Plot 3: Channel 11




Plots: OFDM / g – mode


Plot 1: Channel 1




Plot 2: Channel 2




Plot 3: Channel 3




Plot 4: Channel 6



Plot 5: Channel 10




Plot 6: Channel 11




Plots: OFDM / n HT20 – mode


Plot 1: Channel 1




Plot 2: Channel 2




Plot 3: Channel 6



Plot 4: Channel 10




Plot 5: Channel 11




Date: 16.JUN.2017 13:43:21

Plots: OFDM / n HT40 – mode


Plot 1: Channel 3




Plot 2: Channel 4




Plot 3: Channel 5




Plot 4: Channel 6




Plot 5: Channel 7



Plot 6: Channel 8



Plot 7: Channel 9



Date: 16.JUN.2017 14:08:10

11.8 Occupied bandwidth – 20 dB bandwidth

Description:

Measurement of the 20 dB bandwidth of the modulated carrier.

Measurement:

Measurement parameter	
Detector:	Peak
Sweep time:	Auto
Resolution bandwidth:	100 kHz
Video bandwidth:	500 kHz
Span:	30 MHz / 50 MHz
Trace mode:	Single count with min. 200 counts
Test setup:	See sub clause 6.5 - B
Measurement uncertainty	See sub clause 8

Usage:


-/-	IC
Within the used band!	

Results:


Modulation	20 dB bandwidth [MHz]						
Frequency	2412 MHz	2417 MHz	2422 MHz	2437 MHz	2457 MHz	2462 MHz	
Output power conducted DSSS / b – mode	15.206			15.206		15.194	
Output power conducted OFDM / g – mode	18.361	18.826	18.781	18.457	18.421	18.322	
Output power conducted OFDM / n HT20 – mode	19.138	19.453		18.841	19.309	19.237	
Frequency	2422 MHz	2427 MHz	2432 MHz	2437 MHz	2442 MHz	2447 MHz	2452 MHz
Output power conducted OFDM / n HT40 – mode	38.294	38.330	38.426	38.342	38.438	38.498	38.390

Plots: DSSS / b – mode


Plot 1: Channel 1



Plot 2: Channel 6




Plot 3: Channel 11




Date: 12.JUN.2017 10:35:04

Plots: OFDM / g – mode


Plot 1: Channel 1




Plot 2: Channel 2




Plot 3: Channel 3




Plot 4: Channel 6



Plot 5: Channel 10




Plot 6: Channel 11




Plots: OFDM / n HT20 – mode


Plot 1: Channel 1




Plot 2: Channel 2




Plot 3: Channel 6



Plot 4: Channel 10




Plot 5: Channel 11




Date: 16.JUN.2017 13:43:13

Plots: OFDM / n HT40 – mode


Plot 1: Channel 3




Plot 2: Channel 4




Plot 3: Channel 5




Plot 4: Channel 6




Plot 5: Channel 7



Plot 6: Channel 8



Plot 7: Channel 9



Date: 16.JUN.2017 14:08:02

11.9 Band edge compliance conducted

Description:

Measurement of the radiated band edge compliance with a conducted test setup.

Measurement:

Measurement parameter for measurements	
According to DTS clause: 13.3.2 and clause 12.2.2	
Detector:	RMS
Sweep time:	Auto
Resolution bandwidth:	100 kHz
Video bandwidth:	300 kHz
Span:	Lower band edge: 2388 MHz to 2390 MHz (2 MHz) Upper band edge: 2483.5 MHz to 2485.5 MHz (2 MHz)
Trace mode:	Trace average with 200 counts
Test setup:	See sub clause 6.5 - B
Measurement uncertainty	See sub clause 8

Limits:


FCC	IC
-41.26 dBm	

Results:


Scenario Modulation	Band edge compliance [dBm] (included antenna gain)			
	DSSS / b – mode	OFDM / g – mode	OFDM / n HT20 – mode	OFDM / n HT40 – mode
Max. lower band edge power	-48.6	-45.0	-45.0	-45.8
Max. upper band edge power	-46.0	-47.1	-46.5	-49.4

Plots: DSSS / b – mode

Plot 1: Lower band edge




Plot 2: Upper band edge




Plots: OFDM / g – mode

Plot 1: Lower band edge




Plot 2: Upper band edge




Plots: OFDM / n HT20 – mode

Plot 1: Lower band edge




Plot 2: Upper band edge




Plots: OFDM / n HT40 – mode

Plot 1: Lower band edge



Plot 2: Upper band edge



11.10 Spurious emissions conducted

Description:

Measurement of the conducted spurious emissions in transmit mode. The measurement is performed at channel 1, 6 and 11. The measurement is repeated for all modulations.

Measurement:

Measurement parameter	
Detector:	Peak
Sweep time:	Auto
Resolution bandwidth:	100 kHz
Video bandwidth:	500 kHz
Span:	9 kHz to 25 GHz
Trace mode:	Max Hold
Test setup:	See sub clause 6.5 - B
Measurement uncertainty	See sub clause 8

Limits:

FCC	IC
In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required	

Results: DSSS / b – mode

TX Spurious Emissions Conducted					
DSSS / b – mode					
f [MHz]		amplitude of emission [dBm]	limit max. allowed emission power	actual attenuation below frequency of operation [dB]	results
2412		3.4	30 dBm		Operating frequency
All detected emissions are below the -20 dBc & -30 dBc criteria.			-20 dBc (peak) -30 dBc (average)		compliant
2437		3.2	30 dBm		Operating frequency
All detected emissions are below the -20 dBc & -30 dBc criteria.			-20 dBc (peak) -30 dBc (average)		compliant
2462		3.5	30 dBm		Operating frequency
All detected emissions are below the -20 dBc & -30 dBc criteria.			-20 dBc (peak) -30 dBc (average)		compliant

Results: OFDM / g – mode

TX Spurious Emissions Conducted					
OFDM / g – mode					
f [MHz]		amplitude of emission [dBm]	limit max. allowed emission power	actual attenuation below frequency of operation [dB]	results
2412		-3.3	30 dBm		Operating frequency
All detected emissions are below the -20 dBc criteria.			-20 dBc (peak) -30 dBc (average)		compliant
2417		-4.2	30 dBm		Operating frequency
All detected emissions are below the -20 dBc criteria.			-20 dBc (peak) -30 dBc (average)		compliant
2422		-4.2	30 dBm		Operating frequency
All detected emissions are below the -20 dBc criteria.			-20 dBc (peak) -30 dBc (average)		compliant
2437		-6.3	30 dBm		Operating frequency
All detected emissions are below the -20 dBc criteria.			-20 dBc (peak) -30 dBc (average)		compliant
2457		-1.0	30 dBm		Operating frequency
All detected emissions are below the -20 dBc criteria.			-20 dBc (peak) -30 dBc (average)		compliant
2462		-5.7			Operating frequency
All detected emissions are below the -20 dBc criteria.			-20 dBc (peak) -30 dBc (average)		compliant

Results: OFDM / n HT20 – mode


TX Spurious Emissions Conducted					
OFDM / n HT20 – mode					
f [MHz]		amplitude of emission [dBm]	limit max. allowed emission power	actual attenuation below frequency of operation [dB]	results
2412		-4.4	30 dBm		Operating frequency
All detected emissions are below the -20 dBc criteria.			-20 dBc (peak) -30 dBc (average)		compliant
2417		-4.4	30 dBm		Operating frequency
All detected emissions are below the -20 dBc criteria.			-20 dBc (peak) -30 dBc (average)		compliant
2437		-1.0	30 dBm		Operating frequency
All detected emissions are below the -20 dBc criteria.			-20 dBc (peak) -30 dBc (average)		compliant
2457		-1.9	30 dBm		Operating frequency
All detected emissions are below the -20 dBc criteria.			-20 dBc (peak) -30 dBc (average)		compliant
2462		-6.3	30 dBm		Operating frequency
All detected emissions are below the -20 dBc criteria.			-20 dBc (peak) -30 dBc (average)		compliant

Results: OFDM / n HT40 – mode

TX Spurious Emissions Conducted					
OFDM / n HT40 – mode					
f [MHz]		amplitude of emission [dBm]	limit max. allowed emission power	actual attenuation below frequency of operation [dB]	results
2422		-9.6	30 dBm		Operating frequency
All detected emissions are below the -20 dBc criteria.			-20 dBc (peak) -30 dBc (average)		compliant
2427		-8.4	30 dBm		Operating frequency
All detected emissions are below the -20 dBc criteria.			-20 dBc (peak) -30 dBc (average)		compliant
2432		-6.8	30 dBm		Operating frequency
All detected emissions are below the -20 dBc criteria.			-20 dBc (peak) -30 dBc (average)		compliant
2437		-4.2	30 dBm		Operating frequency
All detected emissions are below the -20 dBc criteria.			-20 dBc (peak) -30 dBc (average)		compliant
2442		-7.0	30 dBm		Operating frequency
All detected emissions are below the -20 dBc criteria.			-20 dBc (peak) -30 dBc (average)		compliant
2447		-7.4	30 dBm		Operating frequency
All detected emissions are below the -20 dBc criteria.			-20 dBc (peak) -30 dBc (average)		compliant
2452		-11.8	30 dBm		Operating frequency
All detected emissions are below the -20 dBc criteria.			-20 dBc (peak) -30 dBc (average)		compliant


Plots: OFDM / b – mode

Plot 1: Channel 1, up to 25 GHz




The peak at the beginning of the plot is the LO from the SA.

Plot 2: Channel 1, zoomed carrier




Plot 3: Channel 6, up to 25 GHz




The peak at the beginning of the plot is the LO from the SA.

Plot 4: Channel 6, zoomed carrier




Plot 5: Channel 11, up to 25 GHz




The peak at the beginning of the plot is the LO from the SA.

Plot 6: Channel 11, zoomed carrier




Plots: OFDM / g – mode

Plot 1: Channel 1, up to 25 GHz




The peak at the beginning of the plot is the LO from the SA.

Plot 2: Channel 1, zoomed carrier




Plot 3: Channel 2, up to 25 GHz




The peak at the beginning of the plot is the LO from the SA.

Plot 4: Channel 2, zoomed carrier




Plot 5: Channel 3, up to 25 GHz




The peak at the beginning of the plot is the LO from the SA.

Plot 6: Channel 3, zoomed carrier




Plot 7: Channel 6, up to 25 GHz




The peak at the beginning of the plot is the LO from the SA.

Plot 8: Channel 6, zoomed carrier




Date: 16.JUN.2017 15:03:41

Plot 9: Channel 10, up to 25 GHz




The peak at the beginning of the plot is the LO from the SA.

Plot 10: Channel 10, zoomed carrier




Date: 16.JUN.2017 14:20:22

Plot 11: Channel 11, up to 25 GHz




The peak at the beginning of the plot is the LO from the SA.

Plot 12: Channel 11, zoomed carrier




Plots: OFDM / n HT 20 – mode

Plot 1: Channel 1, up to 25 GHz




The peak at the beginning of the plot is the LO from the SA.

Plot 2: Channel 1, zoomed carrier




Plot 3: Channel 2, up to 25 GHz




The peak at the beginning of the plot is the LO from the SA.

Plot 4: Channel 2, zoomed carrier




Plot 5: Channel 6, up to 25 GHz




The peak at the beginning of the plot is the LO from the SA.

Plot 6: Channel 6, zoomed carrier




Date: 16.JUN.2017 14:31:53

Plot 7: Channel 10, up to 25 GHz




The peak at the beginning of the plot is the LO from the SA.

Plot 8: Channel 10, zoomed carrier




Plot 9: Channel 11, up to 25 GHz



The peak at the beginning of the plot is the LO from the SA.


Plot 10: Channel 11, zoomed carrier



Date: 16.JUN.2017 13:45:24


Plots: OFDM / n HT 40 – mode

Plot 1: Channel 3, up to 25 GHz




The peak at the beginning of the plot is the LO from the SA.

Plot 2: Channel 3, zoomed carrier




Plot 3: Channel 4, up to 25 GHz




The peak at the beginning of the plot is the LO from the SA.

Plot 4: Channel 4, zoomed carrier




Plot 5: Channel 5, up to 25 GHz




The peak at the beginning of the plot is the LO from the SA.

Plot 6: Channel 5, zoomed carrier




Plot 7: Channel 6, up to 25 GHz




The peak at the beginning of the plot is the LO from the SA.

Plot 8: Channel 6, zoomed carrier




Date: 2.MAR.2017 17:09:27

Plot 9: Channel 7, up to 25 GHz




The peak at the beginning of the plot is the LO from the SA.

Plot 10: Channel 7, zoomed carrier




Date: 2.MAR.2017 17:18:02

Plot 11: Channel 8, up to 25 GHz




The peak at the beginning of the plot is the LO from the SA.

Plot 12: Channel 8, zoomed carrier




Plot 13: Channel 9, up to 25 GHz



The peak at the beginning of the plot is the LO from the SA.

Plot 14: Channel 9, zoomed carrier



Date: 16.JUN.2017 14:11:02

11.11 Spurious emissions radiated below 30 MHz

Description:

Measurement of the radiated spurious emissions in transmit mode below 30 MHz. The EUT is set to channel 6. This measurement is representative for all channels and modes. If peaks are found channel 1 and channel 11 will be measured too. The measurement is performed with the data rate producing the highest output power. The limits are recalculated to a measurement distance of 3 m with 40 dB/decade according CFR Part 2.

Measurement:

Measurement parameter	
Detector:	Peak / Quasi Peak
Sweep time:	Auto
Resolution bandwidth:	F < 150 kHz: 200 Hz F > 150 kHz: 9 kHz
Video bandwidth:	F < 150 kHz: 1 kHz F > 150 kHz: 100 kHz
Span:	9 kHz to 30 MHz
Trace mode:	Max Hold
Measured modulation	☒ DSSS b – mode ☒ OFDM g – mode ☐ OFDM n HT20 – mode ☒ OFDM n HT40 – mode
Test setup:	See sub clause 6.2 - C
Measurement uncertainty	See sub clause 8

Limits:


FCC		IC
Frequency (MHz)	Field Strength (dBμV/m)	Measurement distance
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30

Results:


TX Spurious Emissions Radiated < 30 MHz [dBμV/m]		
F [MHz]	Detector	Level [dBμV/m]
All detected peaks are more than 20 dB below the limit.		

Plots: DSSS


Plot 1: 9 kHz to 30 MHz, low channel



Plot 2: 9 kHz to 30 MHz, mid channel




Plot 3: 9 kHz to 30 MHz, high channel




Plots: OFDM (20 MHz bandwidth)


Plot 1: 9 kHz to 30 MHz, low channel



Plot 2: 9 kHz to 30 MHz, mid channel




Plot 3: 9 kHz to 30 MHz, high channel




Plots: OFDM (40 MHz bandwidth)


Plot 1: 9 kHz to 30 MHz, low channel



Plot 2: 9 kHz to 30 MHz, mid channel



Plot 3: 9 kHz to 30 MHz, high channel



11.12 Spurious emissions radiated 30 MHz to 1 GHz

Description:

Measurement of the radiated spurious emissions and cabinet radiations below 1 GHz.

Measurement:

Measurement parameter	
Detector:	Peak / Quasi Peak
Sweep time:	Auto
Resolution bandwidth:	120 kHz
Video bandwidth:	3 x RBW
Span:	30 MHz to 1 GHz
Trace mode:	Max Hold
Measured modulation	☒ DSSS b – mode ☒ OFDM g – mode ☐ OFDM n HT20 – mode ☒ OFDM n HT40 – mode ☒ RX / Idle – mode
Test setup:	See sub clause 6.1 A
Measurement uncertainty	See sub clause 8


The modulation with the highest output power was used to perform the transmitter spurious emissions. If spurious were detected a re-measurement was performed on the detected frequency with each modulation.

Limits:

FCC		IC
In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).		
Frequency (MHz)	Field Strength (dBμV/m)	Measurement distance
30 - 88	30.0	10
88 – 216	33.5	10
216 – 960	36.0	10


Plot: DSSS

Plot 1: 30 MHz to 1 GHz, vertical & horizontal polarization, low channel




Final results:

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
38.945550	20.99	30.00	9.01	1000.0	120.000	172.0	V	275.0	13.1
74.576550	26.39	30.00	3.61	1000.0	120.000	203.0	V	279.0	8.9
98.474400	26.57	33.50	6.93	1000.0	120.000	100.0	V	15.0	11.7
250.001700	28.28	36.00	7.72	1000.0	120.000	272.0	H	300.0	13.4
500.007150	31.93	36.00	4.07	1000.0	120.000	100.0	V	330.0	18.7
924.976500	29.65	36.00	6.35	1000.0	120.000	100.0	H	15.0	24.3
959.985600	29.79	36.00	6.21	1000.0	120.000	103.0	V	230.0	24.5

Plot 2: 30 MHz to 1 GHz, vertical & horizontal polarization, mid channel**Final results:**


Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
35.035650	10.39	30.00	19.61	1000.0	120.000	177.0	H	204.0	12.7
41.543700	9.82	30.00	20.18	1000.0	120.000	177.0	H	252.0	13.3
48.399000	22.75	30.00	7.25	1000.0	120.000	185.0	V	94.0	13.7
50.441700	27.67	30.00	2.33	1000.0	120.000	101.0	V	161.0	13.7
52.136100	9.53	30.00	20.47	1000.0	120.000	178.0	H	252.0	13.5
57.724050	8.44	30.00	21.56	1000.0	120.000	185.0	H	252.0	12.4
750.016350	29.41	36.00	6.59	1000.0	120.000	98.0	H	265.0	22.7

Plot 3: 30 MHz to 1 GHz, vertical & horizontal polarization, high channel**Final results:**

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
45.785100	21.00	30.00	9.00	1000.0	120.000	101.0	V	106.0	13.6
48.444450	23.14	30.00	6.86	1000.0	120.000	101.0	V	70.0	13.7
50.446350	24.80	30.00	5.20	1000.0	120.000	101.0	V	309.0	13.7
50.863350	10.45	30.00	19.55	1000.0	120.000	178.0	H	16.0	13.6
101.915250	20.85	33.50	12.65	1000.0	120.000	101.0	V	309.0	11.9
925.006650	29.90	36.00	6.10	1000.0	120.000	98.0	H	342.0	24.3


Plot: OFDM (20 MHz bandwidth)

Plot 1: 30 MHz to 1 GHz, vertical & horizontal polarization, low channel




Final results:

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
34.629600	25.21	30.00	4.79	1000.0	120.000	170.0	V	-8.0	12.6
49.034250	23.15	30.00	6.85	1000.0	120.000	100.0	V	-10.0	13.7
50.446650	28.17	30.00	1.83	1000.0	120.000	101.0	V	82.0	13.7
101.902500	25.00	33.50	8.50	1000.0	120.000	170.0	V	81.0	11.9
566.655150	27.69	36.00	8.31	1000.0	120.000	100.0	H	80.0	19.8
699.994350	28.17	36.00	7.83	1000.0	120.000	101.0	H	262.0	21.5

Plot 2: 30 MHz to 1 GHz, vertical & horizontal polarization, mid channel**Final results:**


Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
30.409200	8.37	30.00	21.63	1000.0	120.000	100.0	H	10.0	11.9
34.985550	23.25	30.00	6.75	1000.0	120.000	101.0	V	-10.0	12.7
48.467250	26.58	30.00	3.42	1000.0	120.000	100.0	V	190.0	13.7
50.437050	28.34	30.00	1.66	1000.0	120.000	101.0	V	190.0	13.7
101.898750	24.00	33.50	9.50	1000.0	120.000	101.0	V	-8.0	11.9
959.996250	27.94	36.00	8.06	1000.0	120.000	170.0	V	261.0	24.5

Plot 3: 30 MHz to 1 GHz, vertical & horizontal polarization, high channel**Final results:**

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
34.627650	25.70	30.00	4.30	1000.0	120.000	100.0	V	100.0	12.6
49.022550	24.10	30.00	5.90	1000.0	120.000	100.0	V	-10.0	13.7
50.446200	29.19	30.00	0.81	1000.0	120.000	101.0	V	-8.0	13.7
101.889150	24.36	33.50	9.14	1000.0	120.000	101.0	V	10.0	11.9
566.689500	27.40	36.00	8.60	1000.0	120.000	101.0	H	260.0	19.8
699.999900	27.16	36.00	8.84	1000.0	120.000	98.0	H	170.0	21.5


Plot: OFDM (40 MHz bandwidth)

Plot 1: 30 MHz to 1 GHz, vertical & horizontal polarization, low channel




Final results:

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
34.640850	26.67	30.00	3.33	1000.0	120.000	101.0	V	261.0	12.6
48.467400	22.69	30.00	7.31	1000.0	120.000	101.0	V	-8.0	13.7
49.806900	22.46	30.00	7.54	1000.0	120.000	101.0	V	190.0	13.7
50.439150	29.68	30.00	0.32	1000.0	120.000	100.0	V	80.0	13.7
500.025150	29.53	36.00	6.47	1000.0	120.000	98.0	V	-10.0	18.7
575.024100	26.25	36.00	9.75	1000.0	120.000	101.0	H	190.0	20.0

Plot 2: 30 MHz to 1 GHz, vertical & horizontal polarization, mid channel**Final results:**


Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
34.655700	24.62	30.00	5.38	1000.0	120.000	100.0	V	262.0	12.6
49.572600	11.64	30.00	18.36	1000.0	120.000	98.0	H	280.0	13.7
50.447700	28.25	30.00	1.75	1000.0	120.000	101.0	V	10.0	13.7
101.885250	24.12	33.50	9.38	1000.0	120.000	100.0	V	-8.0	11.9
574.992900	27.23	36.00	8.77	1000.0	120.000	98.0	H	260.0	20.0
750.030600	29.20	36.00	6.80	1000.0	120.000	98.0	H	260.0	22.7

Plot 3: 30 MHz to 1 GHz, vertical & horizontal polarization, high channel**Final results:**

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
34.621950	26.51	30.00	3.49	1000.0	120.000	102.0	V	170.0	12.6
48.429600	21.47	30.00	8.53	1000.0	120.000	101.0	V	-8.0	13.7
49.039200	23.78	30.00	6.22	1000.0	120.000	101.0	V	-8.0	13.7
50.440050	26.75	30.00	3.25	1000.0	120.000	101.0	V	-8.0	13.7
575.012400	28.02	36.00	7.98	1000.0	120.000	100.0	H	10.0	20.0
875.038650	28.22	36.00	7.78	1000.0	120.000	98.0	H	261.0	23.9

Plot: RX / Idle mode

Plot 1: 30 MHz to 1 GHz, vertical & horizontal polarization



Final results:

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
30.630650	23.93	30.00	6.07	1000.0	120.000	103.0	V	307.0	11.9
98.431950	10.27	33.50	23.23	1000.0	120.000	101.0	V	-8.0	11.7
101.893300	12.13	33.50	21.37	1000.0	120.000	104.0	V	36.0	11.9
105.278900	15.63	33.50	17.87	1000.0	120.000	102.0	V	125.0	11.6
250.007800	31.51	36.00	4.49	1000.0	120.000	98.0	V	80.0	13.4
500.008650	32.07	36.00	3.93	1000.0	120.000	100.0	H	128.0	18.7
750.021100	26.89	36.00	9.11	1000.0	120.000	203.0	H	126.0	22.7
959.982900	31.91	36.00	4.09	1000.0	120.000	103.0	H	35.0	24.5

11.13 Spurious emissions radiated above 1 GHz

Description:

Measurement of the radiated spurious emissions above 1 GHz in transmit mode and receiver / idle mode.

Measurement:

Measurement parameter	
Detector:	Peak / RMS
Sweep time:	Auto
Resolution bandwidth:	1 MHz
Video bandwidth:	3 x RBW
Span:	1 GHz to 26 GHz
Trace mode:	Max Hold
Measured modulation	☒ DSSS b – mode ☒ OFDM g – mode ☐ OFDM n HT20 – mode ☒ OFDM n HT40 – mode ☒ RX / Idle – mode
Test setup:	See sub clause 6.2 A (1 GHz - 18 GHz) See sub clause 6.3 A (18 GHz - 26 GHz)
Measurement uncertainty	See sub clause 8

Limits:

FCC		IC
In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).		
Frequency (MHz)	Field Strength (dBμV/m)	Measurement distance
Above 960	54.0	3

Results: DSSS

TX Spurious Emissions Radiated [dBµV/m]								
2412 MHz			2437 MHz			2462 MHz		
F [MHz]	Detector	Level [dBµV/m]	F [MHz]	Detector	Level [dBµV/m]	F [MHz]	Detector	Level [dBµV/m]
1025	Peak	45.4	1025	Peak	45.4	1025	Peak	45.4
	AVG	41.7		AVG	41.7		AVG	41.7
1075	Peak	41.3	1075	Peak	41.3	1075	Peak	41.3
	AVG	39.0		AVG	39.0		AVG	39.0
1440	Peak	41.5	1440	Peak	41.5	1440	Peak	41.5
	AVG	39.2		AVG	39.2		AVG	39.2
1475	Peak	43.3	1475	Peak	43.3	1475	Peak	43.3
	AVG	41.0		AVG	41.0		AVG	41.0
1500	Peak	45.2	1500	Peak	45.2	1500	Peak	45.2
	AVG	41.5		AVG	41.5		AVG	41.5
4824	Peak	53.9	4874	Peak	54.0	4924	Peak	56.0
	AVG	48.0		AVG	49.0		AVG	51.8

Results: OFDM (20 MHz bandwidth)

TX Spurious Emissions Radiated [dBµV/m]								
2412 MHz			2437 MHz			2462 MHz		
F [MHz]	Detector	Level [dBµV/m]	F [MHz]	Detector	Level [dBµV/m]	F [MHz]	Detector	Level [dBµV/m]
1025	Peak	45.4	1025	Peak	45.4	1025	Peak	45.4
	AVG	41.7		AVG	41.7		AVG	41.7
1075	Peak	41.3	1075	Peak	41.3	1075	Peak	41.3
	AVG	39.0		AVG	39.0		AVG	39.0
1440	Peak	41.5	1440	Peak	41.5	1440	Peak	41.5
	AVG	39.2		AVG	39.2		AVG	39.2
1475	Peak	43.3	1475	Peak	43.3	1475	Peak	43.3
	AVG	41.0		AVG	41.0		AVG	41.0
1500	Peak	45.2	1500	Peak	45.2	1500	Peak	45.2
	AVG	41.5		AVG	41.5		AVG	41.5
1625	Peak	41.5	1625	Peak	41.5	4924	Peak	55.5
	AVG	39.2		AVG	39.2		AVG	43.1

Results: OFDM (40 MHz bandwidth)


TX Spurious Emissions Radiated [dBµV/m]								
2422 MHz			2437 MHz			2452 MHz		
F [MHz]	Detector	Level [dBµV/m]	F [MHz]	Detector	Level [dBµV/m]	F [MHz]	Detector	Level [dBµV/m]
1025	Peak	45.4	1025	Peak	45.4	1025	Peak	45.4
	AVG	41.7		AVG	41.7		AVG	41.7
1075	Peak	41.3	1075	Peak	41.3	1075	Peak	41.3
	AVG	39.0		AVG	39.0		AVG	39.0
1440	Peak	41.5	1440	Peak	41.5	1440	Peak	41.5
	AVG	39.2		AVG	39.2		AVG	39.2
1475	Peak	43.3	1475	Peak	43.3	1475	Peak	43.3
	AVG	41.0		AVG	41.0		AVG	41.0
1500	Peak	45.2	1500	Peak	45.2	1500	Peak	45.2
	AVG	41.5		AVG	41.5		AVG	41.5
1625	Peak	41.5	1625	Peak	41.5	1625	Peak	41.5
	AVG	39.2		AVG	39.2		AVG	39.2

Results: RX / idle – mode

TX Spurious Emissions Radiated [dBµV/m]		
F [MHz]	Detector	Level [dBµV/m]
1025	Peak	45.4
	AVG	41.7
1075	Peak	41.3
	AVG	39.0
1440	Peak	41.5
	AVG	39.2
1475	Peak	43.3
	AVG	41.0
1500	Peak	45.2
	AVG	41.5
1625	Peak	41.5
	AVG	39.2


Plots: DSSS

Plot 1: Lowest channel, 1 GHz to 18 GHz, vertical & horizontal polarization




The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 2: Lowest channel, 18 GHz to 26 GHz, vertical & horizontal polarization




Plot 3: Middle channel, 1 GHz to 18 GHz, vertical & horizontal polarization




The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 4: Middle channel, 18 GHz to 26 GHz, vertical & horizontal polarization




Plot 5: Highest channel, 1 GHz to 18 GHz, vertical & horizontal polarization




The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 6: Highest channel, 18 GHz to 26 GHz, vertical & horizontal polarization




Plots: OFDM (20 MHz bandwidth)

Plot 1: Lowest channel, 1 GHz to 18 GHz, vertical & horizontal polarization




The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 2: Lowest channel, 18 GHz to 26 GHz, vertical & horizontal polarization




Plot 3: Middle channel, 1 GHz to 18 GHz, vertical & horizontal polarization




The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 4: Middle channel, 18 GHz to 26 GHz, vertical & horizontal polarization




Plot 5: Highest channel, 1 GHz to 18 GHz, vertical & horizontal polarization




The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 6: Highest channel, 18 GHz to 26 GHz, vertical & horizontal polarization




Plots: OFDM (40 MHz bandwidth)

Plot 1: Lowest channel, 1 GHz to 18 GHz, vertical & horizontal polarization




The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 2: Lowest channel, 18 GHz to 26 GHz, vertical & horizontal polarization




Plot 3: Middle channel, 1 GHz to 18 GHz, vertical & horizontal polarization




The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 4: Middle channel, 18 GHz to 26 GHz, vertical & horizontal polarization




Plot 5: Highest channel, 1 GHz to 18 GHz, vertical & horizontal polarization




The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 6: Highest channel, 18 GHz to 26 GHz, vertical & horizontal polarization




Plots: RX / idle mode

Plot 1: 1 GHz to 18 GHz, vertical & horizontal polarization



Plot 2: 18 GHz to 26 GHz, vertical & horizontal polarization



11.14 Spurious emissions conducted below 30 MHz (AC conducted)

Description:

Measurement of the conducted spurious emissions in transmit mode below 30 MHz. The EUT is set to single channel mode and the transmit channel is channel 39. This measurement is representative for all channels and modes. If critical peaks are found channel 00 and channel 78 will be measured too. The measurement is performed in the mode with the highest output power. Both power lines, phase and neutral line, are measured. Found peaks are remeasured with average and quasi peak detection to show compliance to the limits.

Measurement parameters	
Detector	Peak - Quasi peak / average
Sweep time	Auto
Resolution bandwidth	F < 150 kHz: 200 Hz F > 150 kHz: 9 kHz
Video bandwidth	F < 150 kHz: 1 kHz F > 150 kHz: 100 kHz
Span	9 kHz to 30 MHz
Trace mode	Max hold
Test setup	See sub clause 6.4 A
Measurement uncertainty	See sub clause 8


Limits:

FCC		IC
TX spurious emissions conducted < 30 MHz		
Frequency (MHz)	Quasi-peak (dB μ V/m)	Average (dB μ V/m)
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30.0	60	50

*Decreases with the logarithm of the frequency


Results:

Spurious emissions conducted < 30 MHz [dB μ V/m]		
F [MHz]	Detector	Level [dB μ V/m]
Please look at the table below the plots.		

Plots:**Plot 1:** 150 kHz to 30 MHz, phase line

Frequency	Quasi peak level	Margin quasi peak	Limit QP	Average level	Margin average	Limit AV
MHz	dBµV	dB	dBµV	dBµV	dB	dBµV
0.299393	47.99	12.27	60.260	46.15	5.58	51.732
0.327725	49.37	10.14	59.509	47.90	3.02	50.922
0.356991	42.63	16.16	58.798	39.87	10.21	50.086
0.985915	37.63	18.37	56.000	33.20	12.80	46.000
1.254999	40.39	15.61	56.000	35.95	10.05	46.000
1.694230	39.81	16.19	56.000	31.53	14.47	46.000
4.151188	38.79	17.21	56.000	31.23	14.77	46.000
4.501152	38.98	17.02	56.000	31.50	14.50	46.000
6.566714	38.28	21.72	60.000	29.78	20.22	50.000
7.757761	38.76	21.24	60.000	30.71	19.29	50.000
8.831049	39.06	20.94	60.000	31.59	18.41	50.000
13.560992	49.52	10.48	60.000	45.56	4.44	50.000

Plot 2: 150 kHz to 30 MHz, neutral line



Frequency	Quasi peak level	Margin quasi peak	Limit QP	Average level	Margin average	Limit AV
MHz	dBµV	dB	dBµV	dBµV	dB	dBµV
0.150943	50.42	15.52	65.948	35.17	20.80	55.973
0.300348	47.34	12.90	60.233	45.21	6.49	51.704
0.330373	48.60	10.84	59.442	47.37	3.47	50.846
0.358009	42.33	16.44	58.775	39.54	10.52	50.057
1.407011	40.41	15.59	56.000	35.06	10.94	46.000
4.201598	39.03	16.97	56.000	31.51	14.49	46.000
4.259312	39.12	16.88	56.000	31.11	14.89	46.000
4.371142	39.32	16.68	56.000	30.87	15.13	46.000
6.030377	38.93	21.07	60.000	29.73	20.27	50.000
7.017914	39.08	20.92	60.000	29.90	20.10	50.000
8.756431	39.32	20.68	60.000	31.32	18.68	50.000
13.560036	49.44	10.56	60.000	45.53	4.47	50.000

12 Observations

No observations except those reported with the single test cases have been made.

Annex A Document history

Version	Applied changes	Date of release
	Initial release	2017-06-20
A	EUT photo changed	2017-07-04
B	FCC-ID, IC number, PMN and HVIN changed	2017-07-06

Annex B Further information

Glossary

AVG	-	Average
DUT	-	Device under test
EMC	-	Electromagnetic Compatibility
EN	-	European Standard
EUT	-	Equipment under test
ETSI	-	European Telecommunications Standard Institute
FCC	-	Federal Communication Commission
FCC ID	-	Company Identifier at FCC
HW	-	Hardware
IC	-	Industry Canada
Inv. No.	-	Inventory number
N/A	-	Not applicable
PP	-	Positive peak
QP	-	Quasi peak
S/N	-	Serial number
SW	-	Software
PMN	-	Product marketing name
HMN	-	Host marketing name
HVIN	-	Hardware version identification number
FVIN	-	Firmware version identification number
OBW		Occupied Bandwidth
OC		Operating Channel
OCW		Operating Channel Bandwidth
OOB		Out Of Band

Annex C Accreditation Certificate

first page

last page



Deutsche Akkreditierungsstelle GmbH

Beliehung gemäß § 8 Absatz 1 AkkStelleG i.V.m. § 1 Absatz 1 AkkStelleGBV
Unterzeichnerin der Multilateralen Abkommen
von EA, ILAC und IAF zur gegenseitigen Anerkennung

Akkreditierung



Die Deutsche Akkreditierungsstelle GmbH bestätigt hiermit, dass das Prüflaboratorium

CTC advanced GmbH
Untertürkheimer Straße 6-10, 66117 Saarbrücken

die Kompetenz nach DIN EN ISO/IEC 17025:2005 besitzt, Prüfungen in folgenden Bereichen durchzuführen:

Funk
Mobilfunk (GSM / DCS) + OTA
Elektromagnetische Verträglichkeit (EMV)
Produktsicherheit
SAR / EMF
Umwelt
Smart Card Technology
Bluetooth®
Automotive
Wi-Fi-Services
Kanaadische Anforderungen
US-Anforderungen
Akustik
Near Field Communication (NFC)

Die Akkreditierungsurkunde gilt nur in Verbindung mit dem Bescheid vom 25.11.2016 mit der Akkreditierungsnummer D-PL-12076-01 und ist gültig bis 17.01.2018. Sie besteht aus diesem Deckblatt, der Rückseite des Deckblatts und der folgenden Anlage mit insgesamt 63 Seiten.

Registrierungsnummer der Urkunde: D-PL-12076-01-01

Frankfurt, 25.11.2016

Stelle Minister auf der Rückseite

Im Auftrag Dipl.-Ing. Ralf Eigner
Abteilungsleiter

Deutsche Akkreditierungsstelle GmbH

Standort Berlin
Spittelmarkt 10
10117 Berlin

Standort Frankfurt am Main
Europa-Allee 52
60327 Frankfurt am Main

Standort Braunschweig
Bundesallee 100
38116 Braunschweig

Die auszugsweise Veröffentlichung der Akkreditierungsurkunde bedarf der vorherigen schriftlichen Zustimmung der Deutsche Akkreditierungsstelle GmbH (DAKKS). Ausgenommen davon ist die separate Weiterverbreitung des Deckblattes durch die umseitig genannte Konformitätsbewertungsstelle in unveränderter Form.

Es darf nicht der Anschein erweckt werden, dass sich die Akkreditierung auch auf Bereiche erstreckt, die über den durch die DAKKS bestätigten Akkreditierungsbereich hinausgehen.

Die Akkreditierung erfolgte gemäß des Gesetzes über die Akkreditierungsstelle (AkkStelleG) vom 31. Juli 2009 (BGBl. I S. 2625) sowie der Verordnung (EG) Nr. 765/2008 des Europäischen Parlaments und des Rates vom 9. Juli 2008 über die Vorschriften für die Akkreditierung und Marktüberwachung im Zusammenhang mit der Vermarktung von Produkten (Abt. L 218 vom 9. Juli 2008, S. 30). Die DAKKS ist Unterzeichnerin der Multilateralen Abkommen zur gegenseitigen Anerkennung der European co-operation for Accreditation (EA), des International Accreditation Forum (IAF) und der International Laboratory Accreditation Cooperation (ILAC). Die Unterzeichner dieser Abkommen erkennen ihre Akkreditierungen gegenseitig an.

Der aktuelle Stand der Mitgliedschaft kann folgenden Webseiten entnommen werden:
EA: www.european-accreditation.org
ILAC: www.ilac.org
IAF: www.iaf.nu

Note:

The current certificate including annex can be received on request.