

TEST REPORT

Applicant: FCC: INGENICO

IC: Ingenico

FCC: 9 Avenue de la gare - Rovaltain TGV, BP25156, Valence Cedex

Address: 9,26958 ,France

IC: 9 avenue de la gare Rovaltain TGV, Valence 26958, France

Product Name: Payment Terminals

FCC ID: XKB-SXXCLWIBT

IC: 2586D-SXXCLWIBT

AXIUM SX7000 CL/Eth/4G/WiFi/BT,

HVIN: AXIUM SX5000 CL/Eth/4G/WiFi/BT,

AXIUM SX7000 CL/Eth/WiFi/BT, AXIUM SX5000 CL/Eth/WiFi/BT

47 CFR Part 15, Subpart C(15.247)

RSS-247 Issue 3, August 2023

Standard(s): RSS-Gen, Issue 5, February 2021 Amendment 2

ANSI C63.10-2013

KDB 558074 D01 15.247 Meas Guidance v05r02

Report Number: 2402W92356E-RF-00C

Report Date: 2024/12/20

The above device has been tested and found compliant with the requirement of the relative standards by Bay Area Compliance Laboratories Corp. (Dongguan).

Reviewed By: Pedro Yun

Title: Project Engineer

Approved By: Ivan Cao

Title: EMC Manager

Bay Area Compliance Laboratories Corp. (Dongguan)

No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China

Tel: +86-769-86858888

Fax: +86-769-86858891

www.baclcorp.com.cn

Note: The information marked ▲ is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report cannot be reproduced except in full, without prior written approval of the Company. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0. This report may contain data that are not covered by the accreditation scope and shall be marked with ★. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government. Each test item follows the test standard(s) without deviation.

CONTENTS

DOCUMENT REVISION HISTORY	4
1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
1.2 ACCESSORY INFORMATION.....	5
1.3 ANTENNA INFORMATION DETAIL▲.....	6
1.4 EQUIPMENT MODIFICATIONS	6
2. SUMMARY OF TEST RESULTS	7
3. DESCRIPTION OF TEST CONFIGURATION	8
3.1 OPERATION FREQUENCY DETAIL.....	8
3.2 EUT OPERATION CONDITION.....	8
3.3 SUPPORT EQUIPMENT LIST AND DETAILS	9
3.4 SUPPORT CABLE LIST AND DETAILS	9
3.5 BLOCK DIAGRAM OF TEST SETUP	10
3.6 TEST FACILITY.....	14
3.7 MEASUREMENT UNCERTAINTY	14
4. REQUIREMENTS AND TEST PROCEDURES	15
4.1 AC LINE CONDUCTED EMISSIONS.....	15
4.1.1 Applicable Standard.....	15
4.1.2 EUT Setup.....	17
4.1.3 EMI Test Receiver Setup	17
4.1.4 Test Procedure	18
4.1.5 Corrected Amplitude & Margin Calculation.....	18
4.1.6 Test Result	18
4.2 RADIATION SPURIOUS EMISSIONS.....	19
4.2.1 Applicable Standard.....	19
4.2.2 EUT Setup.....	19
4.2.3 EMI Test Receiver & Spectrum Analyzer Setup	21
4.2.4 Test Procedure	21
4.2.5 Corrected Amplitude & Margin Calculation.....	22
4.2.6 Test Result	22
4.3 MINIMUM 6 DB EMISSION BANDWIDTH	23
4.3.1 Applicable Standard.....	23
4.3.2 EUT Setup.....	23
4.3.3 Test Procedure	23
4.3.4 Test Result	23
4.4 99% OCCUPIED BANDWIDTH.....	24
4.4.1 Applicable Standard.....	24
4.4.2 EUT Setup.....	24
4.4.3 Test Procedure	25
4.4.4 Test Result	25
4.5 MAXIMUM CONDUCTED OUTPUT POWER.....	26
4.5.1 Applicable Standard.....	26

4.5.2 EUT Setup.....	26
4.5.3 Test Procedure	26
4.5.4 Test Result	26
4.6 MAXIMUM POWER SPECTRAL DENSITY	27
4.6.1 Applicable Standard.....	27
4.6.2 EUT Setup.....	27
4.6.3 Test Procedure	27
4.6.4 Test Result	27
4.7 100 KHz BANDWIDTH OF FREQUENCY BAND EDGE.....	28
4.7.1 Applicable Standard.....	28
4.7.2 EUT Setup.....	28
4.7.3 Test Procedure	28
4.7.4 Test Result	28
4.8 DUTY CYCLE	29
4.8.1 EUT Setup.....	29
4.8.2 Test Procedure	29
4.8.3 Judgment.....	29
4.9 ANTENNA REQUIREMENT.....	30
4.9.1 Applicable Standard.....	30
4.9.2 Judgment.....	30
5. Test DATA AND RESULTS.....	31
5.1 AC LINE CONDUCTED EMISSIONS	31
5.2 RADIATION SPURIOUS EMISSIONS	40
5.3 6dB EMISSION BANDWIDTH.....	74
5.4 99% OCCUPIED BANDWIDTH.....	77
5.5 MAXIMUM CONDUCTED OUTPUT POWER.....	80
5.6 POWER SPECTRAL DENSITY	83
5.7 100 KHz BANDWIDTH OF FREQUENCY BAND EDGE.....	86
5.8 DUTY CYCLE	88
EXHIBIT A - EUT PHOTOGRAPHS.....	90
EXHIBIT B - TEST SETUP PHOTOGRAPHS	91

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	2402W92356E-RF-00C	Original Report	2024/12/20

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	Payment Terminals
EUT Model:	AXIUM SX7000
Multiple Model:	AXIUM SX5000
Operation Frequency:	2412-2462MHz (802.11b/g/n ht20) 2422-2452MHz(802.11n ht40)
Maximum Peak Output Power (Conducted):	22.94dBm
Maximum Average Output Power (Conducted):	16.13dBm
Modulation Type:	802.11b:DSSS-DBPSK, DQPSK, CCK 802.11g/n: OFDM-BPSK, QPSK, 16QAM, 64QAM
Rated Input Voltage:	DC 9V-45V
Serial Number:	For RF Conducted Test: 2QUD-5 (Configuration 1#) 2QUD-10 (Configuration 2#) 2QUD-7 (Configuration 3#) 2QUD-9 (Configuration 4#) For AC line conducted emissions and Radiated Spurious Emissions Below 1G Tests: 2QUD-1 (Configuration 1#) 2QUD-3 (Configuration 2#) 2QUD-2 (Configuration 3#) 2QUD-4 (Configuration 4#) For Radiated Spurious Emissions Above 1G Test: 2QUD-6 (Configuration 1#) 2QUD-3 (Configuration 2#) 2QUD-8 (Configuration 3#) 2QUD-4 (Configuration 4#)
EUT Received Date:	2024/8/29
EUT Received Status:	Good

Note: The multiple models are electrically identical with the test model. Please refer to the declaration letter for more detail, which was provided by manufacturer.

Configurations:

Configuration	HVIN	Configuration Description
1#	AXIUM SX7000 CL/Eth/4G/WiFi/BT	With Smartcard reader, With LTE.
2#	AXIUM SX5000 CL/Eth/4G/WiFi/BT	Without Smartcard reader, With LTE.
3#	AXIUM SX7000 CL/Eth/WiFi/BT	With Smartcard reader, Without LTE.
4#	AXIUM SX5000 CL/Eth/WiFi/BT	Without Smartcard reader, Without LTE.

1.2 Accessory Information

Accessory Description	Manufacturer	Model	Parameters
/	/	/	/

1.3 Antenna Information Detail ▲

Antenna Manufacturer	Antenna Type	input impedance (Ohm)	Frequency Range	Antenna Gain
Ingenico	PIFA	50	2.4~2.5GHz	0.90 dBi
The design of compliance with §15.203:				
☒ Unit uses a permanently attached antenna.				
☐ Unit uses a unique coupling to the intentional radiator.				
☐ Unit was professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.				

1.4 Equipment Modifications

No modifications are made to the EUT during all test items.

2. SUMMARY OF TEST RESULTS

Standard(s) Section	Test Items	Result
§15.207(a) RSS-Gen Clause 8.8	AC Line Conducted Emissions	Compliant
§15.205, §15.209, §15.247(d) RSS-Gen Clause 8.10	Spurious Emissions	Compliant
§15.247 (a)(2) RSS-247 Clause 5.2 a)	Minimum 6 dB Bandwidth	Compliant
RSS-Gen Clause 6.7	99% Occupied Bandwidth	Compliant
§15.247(b)(3) RSS-247 Clause 5.4 d)	Maximum Conducted Output Power	Compliant
§15.247(d) RSS-247 Clause 5.5	100 kHz Bandwidth Of Frequency Band Edge	Compliant
§15.247(e) RSS-247 Clause 5.2 b)	Power Spectral Density	Compliant
FCC §15.203 RSS-Gen Clause 6.8	Antenna Requirement	Compliant
Note 1: For AC line conducted emissions, the maximum output power mode and channel was tested. Note 2: For Radiated Spurious Emissions 9kHz~ 1GHz and 18-25GHz, the maximum output power mode and channel was tested.		

3. DESCRIPTION OF TEST CONFIGURATION

3.1 Operation Frequency Detail

For 802.11b/g/n ht20:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For 802.11n ht40:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	7	2442
4	2427	8	2447
5	2432	9	2452
6	2437	/	/

Note: The above frequencies in bold were performed the test.

3.2 EUT Operation Condition

The EUT was configured for testing in Engineering Mode, which was provided by the manufacturer. The EUT configuration as below:

EUT Exercise Software:		CMD		
The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer▲:				
Test Modes	Data Rate	Power Level Setting		
		Lowest Channel	Middle Channel	Highest Channel
802.11b	1Mbps	15	15	15
802.11g	6Mbps	18	18	18
802.11n ht20	MCS0	17	17	17
802.11n ht40	MCS0	16	16	16
The above are the worst-case data rates, which are determined for each mode based upon investigations by measuring the peak power and PSD across all data rates, bandwidths, and modulations.				

3.3 Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
ZIONCOM	Router	MB-R210-00	R16Y06M271022
Lenovo	Laptop 1	G510	EMZBPC21103006
Lenovo	Laptop 2	E450	PF-OMRADG
DELL	Monitor	P2721Q	CN-0XJ46C-FCC00-135-A97L-A03
Adam	LTE Antenna 1	Unknown	SXANTENNA1
Adam	LTE Antenna 2	Unknown	SXANTENNA2
Unknown	I/O Load	Unknown	I/O Load-SX7000
Unknown	RJ11 Load	Unknown	RJ11 Load-SX7000
SANDisk	U-Disk	16G	BL201026115 B
Phihong	Adapter(12V)	PSM36W-120L6IN	192050627
CLC	Earphone	Blackview5.0	EMZBEP21103001W


3.4 Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
DC Cable	No	No	1	Adapter(12V)	EUT
RJ45 Cable	No	No	10	Router	EUT
DC Cable	No	No	2	I/O Load	EUT
RJ11 Cable	No	No	3	RJ11 Load	EUT
USB Cable	No	No	1	Laptop 1/2	EUT
HDMI Cable	Yes	No	1.2	Monitor	EUT
Earphone	No	No	0.8	Earphone	EUT
Signal cable	No	No	1	LTE Antenna 1	EUT
Signal cable	No	No	1	LTE Antenna 2	EUT


3.5 Block Diagram of Test Setup

AC line conducted emissions:

Configuration 1#& Configuration 2#:




Configuration 3#& Configuration 4#:




Spurious Emissions:

Below 1GHz:


Configuration 1#:




Configuration 2#:



Configuration 3#:




Configuration 4#:




Above 1GHz:

Configuration 1#& Configuration 2#:



Configuration 3#& Configuration 4#:



3.6 Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 829273, the FCC Designation No. : CN5044.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

3.7 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	9kHz~30MHz: 3.3dB, 30MHz~200MHz: 4.55 dB, 200MHz~1GHz: 5.92 dB, 1GHz~6GHz: 4.98 dB, 6GHz~18GHz: 5.89 dB, 18GHz~26.5GHz:5.47 dB, 26.5GHz~40GHz:5.63 dB
Unwanted Emissions, conducted	±2.47 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.11 dB (150 kHz to 30 MHz)

4. REQUIREMENTS AND TEST PROCEDURES

4.1 AC Line Conducted Emissions

4.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:

(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

RSS-Gen Clause 8.8

Unless stated otherwise in the applicable RSS, for radio apparatus that are designed to be connected to the public utility AC power network, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the range 150 kHz to 30 MHz shall not exceed the limits in table 4, as measured using a 50 μ H / 50 Ω line impedance stabilization network. This requirement applies for the radio frequency voltage measured between each power line and the ground terminal of each AC power-line mains cable of the EUT.

For an EUT that connects to the AC power lines indirectly, through another device, the requirement for compliance with the limits in table 4 shall apply at the terminals of the AC power-line mains cable of a representative support device, while it provides power to the EUT. The lower limit applies at the boundary between the frequency ranges. The device used to power the EUT shall be representative of typical applications.

Table 4 – AC power-line conducted emissions limits

Frequency (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 ¹	56 to 46 ¹
0.5 – 5	56	46
5 – 30	60	50


Note 1: The level decreases linearly with the logarithm of the frequency.

For an EUT with a permanent or detachable antenna operating between 150 kHz and 30 MHz, the AC power-line conducted emissions must be measured using the following configurations:

(a) Perform the AC power-line conducted emissions test with the antenna connected to determine compliance with the limits of table 4 outside the transmitter's fundamental emission band.

(b) Retest with a dummy load instead of the antenna to determine compliance with the limits of table 4 within the transmitter's fundamental emission band. For a detachable antenna, remove the antenna and connect a suitable dummy load to the antenna connector. For a permanent antenna, remove the antenna and terminate the RF output with a dummy load or network that simulates the antenna in the fundamental frequency band.

4.1.2 EUT Setup



The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207, RSS-Gen limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

4.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

4.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

4.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

4.1.6 Test Result

Please refer to section 5.1.

4.2 Radiation Spurious Emissions

4.2.1 Applicable Standard

FCC §15.247 (d);


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).



RSS-247 Clause 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required

4.2.2 EUT Setup

9kHz~30MHz:



30MHz~1GHz:**Above 1GHz:**

The radiated emissions were performed in the 3 meters distance, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247,RSS-247,RSS-Gen limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

For 9kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

4.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9 kHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9kHz-1000MHz:

Frequency Range	Measurement	RBW	Video B/W	IF B/W	Detector
9 kHz – 150 kHz	QP/AV	300Hz	1 kHz	200 Hz	QP/AV
150 kHz – 30 MHz	QP/AV	10 kHz	30 kHz	9 kHz	QP/AV
30MHz – 1000 MHz	PK	100 kHz	300 kHz	/	PK
	QP	/	/	120kHz	QP

1GHz- 25GHz:

Pre-scan:

Measurement	Detector	Duty cycle	RBW	Video B/W
PK	PK	Any	1MHz	3 MHz
Ave.	PK	>98%	1MHz	5kHz
		<98%	1MHz	1/T, not less than 5kHz

Final measurement for emission identified during the pre-scan:

Measurement	Detector	Duty cycle	RBW	Video B/W
PK	PK	Any	1MHz	3 MHz
Ave.	PK	>98%	1MHz	10 Hz
		<98%	1MHz	1/T

Note: T is minimum transmission duration

4.2.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 9 kHz-1 GHz except 9 – 90 kHz, 110 – 490 kHz, employing an average detector, peak and Average detection modes for frequencies above 1 GHz.

If the maximized peak measured value is under the QP/Average limit by more than 6dB, then it is unnecessary to perform an QP/Average measurement.

All emissions under the average limit and under the noise floor have not recorded in the report.

4.2.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = Antenna Factor + Cable Loss- Amplifier Gain

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

For the spurious emission below 30MHz, the limit was convert from dBμA/m to dBμV/m by adding 51.5 dB.

4.2.6 Test Result

Please refer to section 5.2.

4.3 Minimum 6 dB Emission Bandwidth

4.3.1 Applicable Standard


FCC §15.247 (a)(2)

Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

RSS-247 Clause 5.2 a

The minimum 6 dB bandwidth shall be 500 kHz.

4.3.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, which was provided by manufacturer. The insert loss of this RF cable/attenuator was offset into the setting of test equipment.

4.3.3 Test Procedure

According to ANSI C63.10-2013 Section 11.8

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW) $\geq 3 \times \text{RBW}$.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

4.3.4 Test Result

Please refer to section 5.3.

4.4 99% Occupied Bandwidth

4.4.1 Applicable Standard

RSS-Gen Clause 6.7

The occupied bandwidth or the “99% emission bandwidth” is defined as the frequency range between two points, one above and the other below the carrier frequency, within which 99% of the total transmitted power of the fundamental transmitted emission is contained. The occupied bandwidth shall be reported for all equipment in addition to the specified bandwidth required in the applicable RSSs. In some cases, the “x dB bandwidth” is required, which is defined as the frequency range between two points, one at the lowest frequency below and one at the highest frequency above the carrier frequency, at which the maximum power level of the transmitted emission is attenuated x dB below the maximum in-band power level of the modulated signal, where the two points are on the outskirts of the in-band emission.

The following conditions shall be observed for measuring the occupied bandwidth and x dB bandwidth: The transmitter shall be operated at its maximum carrier power measured under normal test conditions. The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.

The detector of the spectrum analyzer shall be set to “Sample”. However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or “Max Hold”) may be necessary to determine the occupied / x dB bandwidth if the device is not transmitting continuously.


The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / x dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value.

Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.

For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).

4.4.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, which was provided by manufacturer. The insert loss of this RF cable/attenuator was offset into the setting of test equipment.

4.4.3 Test Procedure

According to ANSI C63.10-2013 Section 6.9.3

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2.
- d) Step a) through step c) might require iteration to adjust within the specified range.
- e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- h) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

4.4.4 Test Result

Please refer to section 5.4.

4.5 Maximum Conducted Output Power

4.5.1 Applicable Standard


FCC §15.247 (b)(3)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

RSS-247 Clause 5.4 d

For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e).

4.5.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, which was provided by manufacturer. The insert loss of this RF cable/attenuator was offset into the setting of test equipment.

4.5.3 Test Procedure

According to ANSI C63.10-2013 Section 11.9.1.3

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

- Set the EUT in transmitting mode.
- Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
- Add a correction factor to the display.
- Set the power meter to test peak output power, record the result.

According to ANSI C63.10-2013 Section 11.9.2.3.2

Method AVGPM-G is a measurement using a gated RF average power meter.

Alternatively, measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

4.5.4 Test Result

Please refer to section 5.5.

4.6 Maximum Power Spectral Density

4.6.1 Applicable Standard


FCC §15.247 (e)

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

RSS-247 Clause 5.2 b

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of section 5.4(d), (i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power).

4.6.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, which was provided by manufacturer. The insert loss of this RF cable/attenuator was offset into the setting of test equipment.

4.6.3 Test Procedure

According to ANSI C63.10-2013 Section 11.10.2

The following procedure shall be used if maximum peak conducted output power was used to determine compliance:

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.
- If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.

4.6.4 Test Result

Please refer to section 5.6.

4.7 100 kHz Bandwidth of Frequency Band Edge

4.7.1 Applicable Standard


FCC §15.247 (d);

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

RSS-247 Clause 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required

4.7.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, which was provided by manufacturer. The insert loss of this RF cable/attenuator was offset into the setting of test equipment.

4.7.3 Test Procedure

According to ANSI C63.10-2013 Section 11.11

- Set the center frequency and span to encompass frequency range to be measured.
- Set the RBW = 100 kHz.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.


Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

4.7.4 Test Result

Please refer to section 5.7.

4.8 Duty Cycle

4.8.1 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, which was provided by manufacturer. The insert loss of this RF cable/attenuator was offset into the setting of test equipment.

4.8.2 Test Procedure

According to ANSI C63.10-2013 Section 11.6

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
- 3) Set $VBW \geq RBW$. Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)

4.8.3 Judgment

Report Only. Please refer to section 5.8.

4.9 Antenna Requirement

4.9.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

RSS-Gen Clause 6.8

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below). When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

4.9.2 Judgment

Compliant. Please refer to the Antenna Information detail in Section 1.3.

5. Test DATA AND RESULTS

5.1 AC Line Conducted Emissions

Serial Number:	2QUD-1, 2QUD-3, 2QUD-2, 2QUD-4	Test Date:	2024/9/14~2024/10/24
Test Site:	CE	Test Mode:	Transmitting
Tester:	Yukin Qiu	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.3~26.6	Relative Humidity: (%)	43~69	ATM Pressure: (kPa)	99.8~101.2
----------------------	-----------	------------------------------	-------	------------------------	------------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101614	2024/9/5	2025/9/4
MICRO-COAX	Coaxial Cable	C-NJNJ-50	C-0200-01	2024/9/5	2025/9/4
R&S	EMI Test Receiver	ESCI	100035	2024/8/26	2025/8/25
Audix	Test Software	E3	191218 V9	N/A	N/A

** Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Configuration 1#:

Project No.: 2402W92356E-RF
Port: Line
Test Mode: Transmitting
Note: 802.11g High Channel

Serial No.: 2QUD-1
Tester: Yukin Qiu




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.152	29.88	10.75	40.63	65.89	25.26	QP
2	0.152	19.61	10.75	30.36	55.89	25.53	Average
3	0.167	28.87	10.78	39.65	65.11	25.46	QP
4	0.167	20.43	10.78	31.21	55.11	23.90	Average
5	0.176	27.61	10.80	38.41	64.66	26.25	QP
6	0.176	18.93	10.80	29.73	54.66	24.93	Average
7	0.209	27.02	10.85	37.87	63.25	25.38	QP
8	0.209	20.42	10.85	31.27	53.25	21.98	Average
9	0.369	37.11	10.83	47.94	58.53	10.59	QP
10	0.369	30.98	10.83	41.81	48.53	6.72	Average
11	18.782	21.73	10.87	32.60	60.00	27.40	QP
12	18.782	17.00	10.87	27.87	50.00	22.13	Average

Project No.: 2402W92356E-RF
Port: neutral
Test Mode: Transmitting
Note: 802.11g High Channel

Serial No.: 2QUD-1
Tester: Yukin Qiu

Date: 2024-09-18



No.	Frequency (MHz)	Reading (dBUV)	Factor (dB)	Result (dBUV)	Limit (dBUV)	Margin (dB)	Detector
1	0.151	29.55	10.85	40.40	65.95	25.55	QP
2	0.151	18.57	10.85	29.42	55.95	26.53	Average
3	0.170	28.06	10.85	38.91	64.94	26.03	QP
4	0.170	19.78	10.85	30.63	54.94	24.31	Average
5	0.190	27.42	10.85	38.27	64.05	25.78	QP
6	0.190	19.62	10.85	30.47	54.05	23.58	Average
7	0.204	26.52	10.85	37.37	63.43	26.06	QP
8	0.204	19.23	10.85	30.08	53.43	23.35	Average
9	0.369	36.60	10.77	47.37	58.52	11.15	QP
10	0.369	30.46	10.77	41.23	48.52	7.29	Average
11	17.969	23.63	10.86	34.49	60.00	25.51	QP
12	17.969	18.46	10.86	29.32	50.00	20.68	Average


Spot Check:

Configuration 2#:

Project No.: 2402W92356E-RF
Port: Line
Test Mode: Transmitting
Note: 802.11g High Channel

Serial No.: 2QUD-3
Tester: Yukin Qiu

Date: 2024-10-24




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.155	30.58	10.76	41.34	65.72	24.38	QP
2	0.155	20.10	10.76	30.86	55.72	24.86	Average
3	0.174	28.80	10.80	39.60	64.76	25.16	QP
4	0.174	19.98	10.80	30.78	54.76	23.98	Average
5	0.207	25.94	10.85	36.79	63.33	26.54	QP
6	0.207	18.39	10.85	29.24	53.33	24.09	Average
7	0.330	29.29	10.83	40.12	59.45	19.33	QP
8	0.330	25.57	10.83	36.40	49.45	13.05	Average
9	0.352	31.66	10.83	42.49	58.91	16.42	QP
10	0.352	27.03	10.83	37.86	48.91	11.05	Average
11	0.374	36.56	10.83	47.39	58.42	11.03	QP
12	0.374	32.80	10.83	43.63	48.42	4.79	Average

Project No.: 2402W92356E-RF
Port: neutral
Test Mode: Transmitting
Note: 802.11g High Channel

Serial No.: 2QUD-3
Tester: Yukin Qiu

Date: 2024-10-24




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.159	29.50	10.85	40.35	65.54	25.19	QP
2	0.159	19.38	10.85	30.23	55.54	25.31	Average
3	0.191	28.04	10.85	38.89	64.01	25.12	QP
4	0.191	20.65	10.85	31.50	54.01	22.51	Average
5	0.233	25.02	10.83	35.85	62.34	26.49	QP
6	0.233	16.28	10.83	27.11	52.34	25.23	Average
7	0.326	28.97	10.79	39.76	59.55	19.79	QP
8	0.326	22.42	10.79	33.21	49.55	16.34	Average
9	0.346	35.02	10.78	45.80	59.06	13.26	QP
10	0.346	25.48	10.78	36.26	49.06	12.80	Average
11	0.368	36.97	10.77	47.74	58.55	10.81	QP
12	0.368	31.09	10.77	41.86	48.55	6.69	Average

Configuration 3#:

Project No.: 2402W92356E-RF
Port: Line
Test Mode: Transmitting
Note: 802.11g mode High channel

Serial No.: 2QUD-2
Tester: Yukin Qiu




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.152	31.14	10.75	41.89	65.90	24.01	QP
2	0.152	20.45	10.75	31.20	55.90	24.70	Average
3	0.161	29.85	10.77	40.62	65.42	24.80	QP
4	0.161	21.76	10.77	32.53	55.42	22.89	Average
5	0.173	28.51	10.80	39.31	64.82	25.51	QP
6	0.173	19.60	10.80	30.40	54.82	24.42	Average
7	0.189	27.46	10.83	38.29	64.08	25.79	QP
8	0.189	19.86	10.83	30.69	54.08	23.39	Average
9	0.369	37.09	10.83	47.92	58.53	10.61	QP
10	0.369	31.30	10.83	42.13	48.53	6.40	Average
11	18.242	23.91	10.86	34.77	60.00	25.23	QP
12	18.242	18.76	10.86	29.62	50.00	20.38	Average

Project No.: 2402W92356E-RF
Port: neutral
Test Mode: Transmitting
Note: 802.11g mode High channel

Serial No.: 2QUD-2
Tester: Yukin Qiu

Date: 2024-09-14




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.155	29.60	10.85	40.45	65.75	25.30	QP
2	0.155	20.46	10.85	31.31	55.75	24.44	Average
3	0.165	28.31	10.85	39.16	65.20	26.04	QP
4	0.165	20.43	10.85	31.28	55.20	23.92	Average
5	0.178	28.10	10.85	38.95	64.59	25.64	QP
6	0.178	19.90	10.85	30.75	54.59	23.84	Average
7	0.184	27.06	10.85	37.91	64.31	26.40	QP
8	0.184	21.00	10.85	31.85	54.31	22.46	Average
9	0.373	36.97	10.77	47.74	58.44	10.70	QP
10	0.373	29.65	10.77	40.42	48.44	8.02	Average
11	18.203	22.97	10.86	33.83	60.00	26.17	QP
12	18.203	18.07	10.86	28.93	50.00	21.07	Average

Configuration 4#:

Project No.: 2402W92356E-RF
Port: Line
Test Mode: Transmitting
Note: 802.11g mode High channel

Serial No.: 2QUD-4
Tester: Yukin Qiu

Date: 2024-10-24




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.153	28.56	10.76	39.32	65.86	26.54	QP
2	0.153	18.17	10.76	28.93	55.86	26.93	Average
3	0.185	25.56	10.82	36.38	64.26	27.88	QP
4	0.185	16.58	10.82	27.40	54.26	26.86	Average
5	0.331	29.12	10.83	39.95	59.42	19.47	QP
6	0.331	21.26	10.83	32.09	49.42	17.33	Average
7	0.368	36.33	10.83	47.16	58.54	11.38	QP
8	0.368	25.83	10.83	36.66	48.54	11.88	Average
9	13.419	26.81	10.83	37.64	60.00	22.36	QP
10	13.419	23.72	10.83	34.55	50.00	15.45	Average
11	17.082	27.23	10.87	38.10	60.00	21.90	QP
12	17.082	23.04	10.87	33.91	50.00	16.09	Average

Project No.: 2402W92356E-RF
Port: neutral
Test Mode: Transmitting
Note: 802.11g mode High channel

Serial No.: 2QUD-4
Tester: Yukin Qiu

Date: 2024-10-24



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.159	27.58	10.85	38.43	65.51	27.08	QP
2	0.159	18.56	10.85	29.41	55.51	26.10	Average
3	0.334	29.87	10.79	40.66	59.35	18.69	QP
4	0.334	23.87	10.79	34.66	49.35	14.69	Average
5	0.373	36.95	10.77	47.72	58.44	10.72	QP
6	0.373	32.61	10.77	43.38	48.44	5.06	Average
7	0.379	35.29	10.78	46.07	58.29	12.22	QP
8	0.379	28.87	10.78	39.65	48.29	8.64	Average
9	13.357	26.28	10.86	37.14	60.00	22.86	QP
10	13.357	23.30	10.86	34.16	50.00	15.84	Average
11	16.901	26.39	10.87	37.26	60.00	22.74	QP
12	16.901	22.15	10.87	33.02	50.00	16.98	Average

5.2 Radiation Spurious Emissions

1) 9kHz - 1GHz

Serial Number:	2QUD-1, 2QUD-2, 2QUD-3, 2QUD-4	Test Date:	2024/9/12~2024/10/24
Test Site:	Chamber A	Test Mode:	Transmitting
Tester:	Jayce Wang, Alan Xie	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.6~27.2	Relative Humidity: (%)	26~35	ATM Pressure: (kPa)	100.9~101.2
----------------------	-----------	---------------------------	-------	---------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
EMCO	Passive Loop Antenna	6512	9706-1206	2023/10/25	2026/10/24
Sunol Sciences	Hybrid Antenna	JB3	A060611-3	2024/1/12	2027/1/11
Wilson	Coaxial Attenuator	859936	F-08-EM014	2024/1/12	2027/1/11
Unknown	Coaxial Cable	C-NJNJ-50	C-0075-01	2024/7/1	2025/6/30
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-01	2024/7/1	2025/6/30
Unknown	Coaxial Cable	C-NJNJ-50	C-1400-01	2024/7/1	2025/6/30
Sonoma	Amplifier	310N	372193	2024/8/16	2025/8/15
R&S	EMI Test Receiver	ESR3	102453	2024/8/26	2025/8/25
Audix	Test Software	E3	191218 V9	N/A	N/A
Sunol Sciences	Hybrid Antenna	JB3	A060611-2	2024/4/16	2027/4/15
Narda	Coaxial Attenuator	757C-6dB	34010	2024/4/16	2027/4/15

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Please refer to the below table and plots.


9kHz~30MHz

Three antenna orientations (parallel, perpendicular, and ground-parallel) was measured,
the worst orientations was below:

Configuration 1#:

Project No.: 2402W92356E-RF
Polarization: Parallel
Test Mode: Transmitting
Note: 802.11g High Channel

Serial No.: 2QUD-1
Tester: Jayce Wang




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	0.0208	13.30	48.81	62.11	121.23	59.12	Peak
2	0.0230	15.72	48.33	64.05	120.39	56.34	Peak
3	0.0438	16.93	44.36	61.29	114.77	53.48	Peak
4	0.0468	18.93	43.92	62.85	114.20	51.35	Peak
5	0.0485	15.09	43.67	58.76	113.89	55.13	Peak
6	0.1221	19.94	33.74	53.68	105.87	52.19	Peak

Project No.: 2402W92356E-RF
Polarization: Parallel
Test Mode: Transmitting
Note: 802.11g High Channel

Serial No.: 2QUD-1
Tester: Jayce Wang

Date: 2024-09-12




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	4.2920	32.73	6.64	39.37	69.54	30.17	Peak
2	4.4300	35.04	6.46	41.50	69.54	28.04	Peak
3	4.7460	34.26	6.04	40.30	69.54	29.24	Peak
4	5.1390	33.53	5.61	39.14	69.54	30.40	Peak
5	17.9440	33.14	3.79	36.93	69.54	32.61	Peak
6	29.3709	36.12	3.39	39.51	69.54	30.03	Peak

Spot Check:

Configuration 2#:

Project No.: 2402W92356E-RF
Polarization: Parallel
Test Mode: Transmitting
Note: 802.11g High Channel

Serial No.: 2QUD-3
Tester: Jayce Wang




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.0108	4.03	51.34	55.37	126.91	71.54	Peak
2	0.0186	6.57	49.36	55.93	122.22	66.29	Peak
3	0.0213	7.32	48.72	56.04	121.05	65.01	Peak
4	0.0502	5.25	43.41	48.66	113.60	64.94	Peak
5	0.0640	8.48	41.15	49.63	111.48	61.85	Peak
6	0.0757	5.55	39.14	44.69	110.02	65.33	Peak

Project No.: 2402W92356E-RF
Polarization: Parallel
Test Mode: Transmitting
Note: 802.11g High Channel

Serial No.: 2QUD-3
Tester: Jayce Wang

Date: 2024-10-24




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	4.8224	36.37	5.93	42.30	69.54	27.24	Peak
2	4.9519	37.68	5.76	43.44	69.54	26.10	Peak
3	5.4186	31.09	5.42	36.51	69.54	33.03	Peak
4	15.7180	35.39	3.60	38.99	69.54	30.55	Peak
5	16.3120	38.25	3.63	41.88	69.54	27.66	Peak
6	17.1090	35.28	3.77	39.05	69.54	30.49	Peak

Configuration 3#:

Project No.: 2402W92356E-RF
Polarization: Parallel
Test Mode: Transmitting
Note: 802.11g High channel

Serial No.: 2QUD-2
Tester: Alan Xie




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.018	7.60	49.43	57.03	122.35	65.32	Peak
2	0.021	7.54	48.72	56.26	121.05	64.79	Peak
3	0.050	6.79	43.41	50.20	113.60	63.40	Peak
4	0.064	8.43	41.15	49.58	111.48	61.90	Peak
5	0.076	5.92	39.12	45.04	110.01	64.97	Peak
6	0.118	12.27	33.98	46.25	106.16	59.91	Peak

Project No.: 2402W92356E-RF
Polarization: Parallel
Test Mode: Transmitting
Note: 802.11g High channel

Serial No.: 2QUD-2
Tester: Alan Xie

Date: 2024-09-12




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.317	19.94	23.21	43.15	97.59	54.44	Peak
2	0.800	19.54	19.68	39.22	69.45	30.23	Peak
3	4.549	39.39	6.29	45.68	69.54	23.86	Peak
4	11.996	21.63	3.88	25.51	69.54	44.03	Peak
5	16.750	43.65	3.73	47.38	69.54	22.16	Peak
6	23.888	28.85	3.77	32.62	69.54	36.92	Peak

Configuration 4#:

Project No.: 2402W92356E-RF
Polarization: Parallel
Test Mode: Transmitting
Note: 802.11g High channel

Serial No.: 2QUD-4
Tester: Jayce Wang




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.023	8.27	48.31	56.58	120.33	63.75	Peak
2	0.046	10.67	43.98	54.65	114.28	59.63	Peak
3	0.050	6.81	43.39	50.20	113.57	63.37	Peak
4	0.064	8.55	41.15	49.70	111.48	61.78	Peak
5	0.076	6.27	39.17	45.44	110.04	64.60	Peak
6	0.127	11.41	33.44	44.85	105.50	60.65	Peak

Project No.: 2402W92356E-RF
Polarization: Parallel
Test Mode: Transmitting
Note: 802.11g High channel

Serial No.: 2QUD-4
Tester: Jayce Wang

Date: 2024-10-24




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	4.952	37.53	5.76	43.29	69.54	26.25	Peak
2	5.194	35.40	5.58	40.98	69.54	28.56	Peak
3	15.388	35.64	3.65	39.29	69.54	30.25	Peak
4	16.839	37.82	3.75	41.57	69.54	27.97	Peak
5	18.426	39.61	3.62	43.23	69.54	26.31	Peak
6	19.224	39.48	3.38	42.86	69.54	26.68	Peak

30MHz-1GHz

Configuration 1#:

Project No.: 2402W92356E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11g High Channel

Serial No.: 2QUD-1
Tester: Jayce Wang




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.00	36.67	-3.51	33.16	40.00	6.84	Peak
2	58.13	49.56	-16.91	32.65	40.00	7.35	Peak
3	142.52	46.65	-10.76	35.89	43.50	7.61	Peak
4	222.06	52.68	-11.08	41.60	46.00	4.40	Peak
5	250.19	48.32	-11.17	37.15	46.00	8.85	Peak
6	371.44	47.51	-7.82	39.69	46.00	6.31	QP

Project No.: 2402W92356E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11g High Channel

Serial No.: 2QUD-1
Tester: Jayce Wang

Date: 2024-09-12




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	36.79	44.39	-8.01	36.38	40.00	3.62	QP
2	43.58	47.30	-12.34	34.96	40.00	5.04	QP
3	58.13	53.20	-16.91	36.29	40.00	3.71	QP
4	65.89	48.81	-16.21	32.60	40.00	7.40	QP
5	85.29	51.20	-16.53	34.67	40.00	5.33	QP
6	101.78	50.50	-12.96	37.54	43.50	5.96	QP

Spot Check:

Configuration 2#:

Project No.: 2402W92356E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11g High Channel

Serial No.: 2QUD-3
Tester: Jayce Wang




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	148.34	46.60	-11.40	35.20	43.50	8.30	Peak
2	192.96	48.55	-11.99	36.56	43.50	6.94	Peak
3	222.06	46.46	-10.96	35.50	46.00	10.50	Peak
4	296.75	48.81	-9.41	39.40	46.00	6.60	Peak
5	371.44	45.68	-7.47	38.21	46.00	7.79	Peak
6	532.46	38.28	-3.79	34.49	46.00	11.51	Peak

Project No.: 2402W92356E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11g High Channel

Serial No.: 2QUD-3
Tester: Jayce Wang

Date: 2024-10-24




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	52.31	48.80	-16.57	32.23	40.00	7.77	QP
2	148.34	46.11	-11.40	34.71	43.50	8.79	Peak
3	222.06	47.11	-10.96	36.15	46.00	9.85	Peak
4	371.44	44.60	-7.47	37.13	46.00	8.87	Peak
5	483.96	40.81	-4.61	36.20	46.00	9.80	Peak
6	531.49	39.55	-3.81	35.74	46.00	10.26	Peak

Configuration 3#:

Project No.: 2402W92356E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11g High channel

Serial No.: 2QUD-2
Tester: Alan Xie




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	110.51	44.27	-11.09	33.18	43.50	10.32	Peak
2	145.43	46.50	-11.01	35.49	43.50	8.01	Peak
3	194.90	48.01	-11.82	36.19	43.50	7.31	Peak
4	250.19	50.21	-11.17	39.04	46.00	6.96	Peak
5	332.64	45.61	-8.41	37.20	46.00	8.80	Peak
6	714.82	37.54	-0.54	37.00	46.00	9.00	Peak

Project No.: 2402W92356E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11g High channel

Serial No.: 2QUD-2
Tester: Alan Xie

Date: 2024-09-12




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.00	39.96	-3.51	36.45	40.00	3.55	QP
2	35.82	43.74	-7.35	36.39	40.00	3.61	QP
3	45.52	46.03	-13.54	32.49	40.00	7.51	QP
4	80.44	48.21	-16.56	31.65	40.00	8.35	QP
5	194.90	46.18	-11.82	34.36	43.50	9.14	Peak
6	797.27	35.40	1.33	36.73	46.00	9.27	Peak

Configuration 4#:

Project No.: 2402W92356E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11g High channel


Serial No.: 2QUD-4
Tester: Jayce Wang



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	148.34	46.83	-11.40	35.43	43.50	8.07	Peak
2	222.06	49.25	-10.96	38.29	46.00	7.71	Peak
3	296.75	47.60	-9.41	38.19	46.00	7.81	QP
4	371.44	47.20	-7.47	39.73	46.00	6.27	Peak
5	389.87	44.47	-6.96	37.51	46.00	8.49	Peak
6	816.67	35.35	1.89	37.24	46.00	8.76	Peak

Project No.: 2402W92356E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11g High channel

Serial No.: 2QUD-4
Tester: Jayce Wang



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	52.31	49.67	-16.57	33.10	40.00	6.90	Peak
2	148.34	43.75	-11.40	32.35	43.50	11.15	Peak
3	222.06	48.93	-10.96	37.97	46.00	8.03	Peak
4	296.75	46.09	-9.41	36.68	46.00	9.32	Peak
5	371.44	46.42	-7.47	38.95	46.00	7.05	Peak
6	531.49	41.42	-3.81	37.61	46.00	8.39	Peak

2) 1-25GHz:

Serial Number:	2QUD-6,2QUD-3, 2QUD-8, 2QUD-4	Test Date:	2024/9/12~2024/11/16
Test Site:	Chamber B	Test Mode:	Transmitting
Tester:	Nat Zhou	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24.4~26.3	Relative Humidity: (%)	52~62	ATM Pressure: (kPa)	100.9~101.1
----------------------	-----------	---------------------------	-------	------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
ETS-Lindgren	Horn Antenna	3115	000 527 35	2023/9/7	2026/9/6
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-02 1304	2023/2/22	2026/2/21
Xinhang Macrowave	Coaxial Cable	XH750A-N/J-SMA/J-10M	20231117004 #0001	2023/11/17	2024/11/16
Xinhang Macrowave	Coaxial Cable	XH360A-2.92/J-2.92/J-6M-A	20231208001 #0001	2023/12/11	2024/12/10
AH	Preamplifier	PAM-0118P	469	2024/4/15	2025/4/15
AH	Preamplifier	PAM-1840VH	191	2024/9/5	2025/9/4
R&S	Spectrum Analyzer	FSV40	101944	2024/9/6	2025/9/5
Audix	Test Software	E3	191218 V9	N/A	N/A
E-Microwave	Band Rejection Filter	OBSF-2400-2483.5-S	OE01601525	2024/2/21	2025/2/20
Micro-tronics	High Pass Filter	HPM50111	G217	2023/12/1	2024/11/30

** Statement of Traceability: Bay Area Compliance Laboratories Corp.(Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:

Configuration 1#::

802.11b

Frequency	Reading	Detector	Polar	Factor	Corrected Amplitude	Limit	Margin
MHz	dBμV	PK/QP/AV	H/V	dB/m	dBμV/m	dBμV/m	dB
Low Channel				2412	MHz		
2390.00	27.23	PK	H	28.57	55.80	74.00	18.20
2390.00	16.94	AV	H	28.57	45.51	54.00	8.49
2390.00	28.17	PK	V	28.57	56.74	74.00	17.26
2390.00	16.64	AV	V	28.57	45.21	54.00	8.79
4824.00	63.20	PK	H	-10.09	53.11	74.00	20.89
4824.00	61.51	AV	H	-10.09	51.42	54.00	2.58
4824.00	62.38	PK	V	-10.09	52.29	74.00	21.71
4824.00	60.41	AV	V	-10.09	50.32	54.00	3.68
7236.00	49.59	PK	H	-5.38	44.21	74.00	29.79
7236.00	38.71	AV	H	-5.38	33.33	54.00	20.67
7236.00	50.41	PK	V	-5.38	45.03	74.00	28.97
7236.00	39.34	AV	V	-5.38	33.96	54.00	20.04
Middle Channel				2437	MHz		
4874.00	62.49	PK	H	-10.02	52.47	74.00	21.53
4874.00	60.52	AV	H	-10.02	50.50	54.00	3.50
4874.00	61.59	PK	V	-10.02	51.57	74.00	22.43
4874.00	58.81	AV	V	-10.02	48.79	54.00	5.21
7311.00	49.57	PK	H	-5.05	44.52	74.00	29.48
7311.00	38.66	AV	H	-5.05	33.61	54.00	20.39
7311.00	49.88	PK	V	-5.05	44.83	74.00	29.17
7311.00	38.82	AV	V	-5.05	33.77	54.00	20.23
High Channel				2462	MHz		
2483.50	27.86	PK	H	28.95	56.81	74.00	17.19
2483.50	16.87	AV	H	28.95	45.82	54.00	8.18
2483.50	27.83	PK	V	28.95	56.78	74.00	17.22
2483.50	16.73	AV	V	28.95	45.68	54.00	8.32
4924.00	62.39	PK	H	-9.99	52.40	74.00	21.60
4924.00	60.11	AV	H	-9.99	50.12	54.00	3.88
4924.00	60.19	PK	V	-9.99	50.20	74.00	23.80
4924.00	57.73	AV	V	-9.99	47.74	54.00	6.26
7386.00	49.63	PK	H	-4.74	44.89	74.00	29.11
7386.00	38.53	AV	H	-4.74	33.79	54.00	20.21
7386.00	49.71	PK	V	-4.74	44.97	74.00	29.03
7386.00	38.57	AV	V	-4.74	33.83	54.00	20.17

802.11g

Frequency	Reading	Detector	Polar	Factor	Corrected Amplitude	Limit	Margin
MHz	dBμV	PK/QP/AV	H/V	dB/m	dBμV/m	dBμV/m	dB
Low Channel				2412	MHz		
2390.00	34.92	PK	H	28.57	63.49	74.00	10.51
2390.00	21.66	AV	H	28.57	50.23	54.00	3.77
2390.00	36.72	PK	V	28.57	65.29	74.00	8.71
2390.00	22.30	AV	V	28.57	50.87	54.00	3.13
4824.00	61.49	PK	H	-10.09	51.40	74.00	22.60
4824.00	51.62	AV	H	-10.09	41.53	54.00	12.47
4824.00	58.78	PK	V	-10.09	48.69	74.00	25.31
4824.00	48.36	AV	V	-10.09	38.27	54.00	15.73
7236.00	48.59	PK	H	-5.38	43.21	74.00	30.79
7236.00	38.20	AV	H	-5.38	32.82	54.00	21.18
7236.00	49.64	PK	V	-5.38	44.26	74.00	29.74
7236.00	39.32	AV	V	-5.38	33.94	54.00	20.06
Middle Channel				2437	MHz		
4874.00	57.21	PK	H	-10.02	47.19	74.00	26.81
4874.00	47.33	AV	H	-10.02	37.31	54.00	16.69
4874.00	55.57	PK	V	-10.02	45.55	74.00	28.45
4874.00	46.62	AV	V	-10.02	36.60	54.00	17.40
7311.00	48.81	PK	H	-5.05	43.76	74.00	30.24
7311.00	38.69	AV	H	-5.05	33.64	54.00	20.36
7311.00	49.43	PK	V	-5.05	44.38	74.00	29.62
7311.00	39.52	AV	V	-5.05	34.47	54.00	19.53
High Channel				2462	MHz		
2483.50	33.62	PK	H	28.95	62.57	74.00	11.43
2483.50	19.18	AV	H	28.95	48.13	54.00	5.87
2483.50	36.14	PK	V	28.95	65.09	74.00	8.91
2483.50	19.93	AV	V	28.95	48.88	54.00	5.12
4924.00	56.72	PK	H	-9.99	46.73	74.00	27.27
4924.00	46.84	AV	H	-9.99	36.85	54.00	17.15
4924.00	55.24	PK	V	-9.99	45.25	74.00	28.75
4924.00	46.17	AV	V	-9.99	36.18	54.00	17.82
7386.00	49.46	PK	H	-4.74	44.72	74.00	29.28
7386.00	38.81	AV	H	-4.74	34.07	54.00	19.93
7386.00	49.57	PK	V	-4.74	44.83	74.00	29.17
7386.00	39.46	AV	V	-4.74	34.72	54.00	19.28

802.11n20

Frequency	Reading	Detector	Polar	Factor	Corrected Amplitude	Limit	Margin
MHz	dBμV	PK/QP/AV	H/V	dB/m	dBμV/m	dBμV/m	dB
Low Channel				2412	MHz		
2390.00	35.14	PK	H	28.57	63.71	74.00	10.29
2390.00	21.21	AV	H	28.57	49.78	54.00	4.22
2390.00	35.91	PK	V	28.57	64.48	74.00	9.52
2390.00	21.80	AV	V	28.57	50.37	54.00	3.63
4824.00	60.29	PK	H	-10.09	50.20	74.00	23.80
4824.00	50.18	AV	H	-10.09	40.09	54.00	13.91
4824.00	57.75	PK	V	-10.09	47.66	74.00	26.34
4824.00	47.24	AV	V	-10.09	37.15	54.00	16.85
7236.00	48.99	PK	H	-5.38	43.61	74.00	30.39
7236.00	38.09	AV	H	-5.38	32.71	54.00	21.29
7236.00	48.69	PK	V	-5.38	43.31	74.00	30.69
7236.00	38.46	AV	V	-5.38	33.08	54.00	20.92
Middle Channel				2437	MHz		
4874.00	56.78	PK	H	-10.02	46.76	74.00	27.24
4874.00	46.81	AV	H	-10.02	36.79	54.00	17.21
4874.00	54.68	PK	V	-10.02	44.66	74.00	29.34
4874.00	45.28	AV	V	-10.02	35.26	54.00	18.74
7311.00	49.20	PK	H	-5.05	44.15	74.00	29.85
7311.00	38.64	AV	H	-5.05	33.59	54.00	20.41
7311.00	49.36	PK	V	-5.05	44.31	74.00	29.69
7311.00	38.77	AV	V	-5.05	33.72	54.00	20.28
High Channel				2462	MHz		
2483.50	33.18	PK	H	28.95	62.13	74.00	11.87
2483.50	18.03	AV	H	28.95	46.98	54.00	7.02
2483.50	33.95	PK	V	28.95	62.90	74.00	11.10
2483.50	18.83	AV	V	28.95	47.78	54.00	6.22
4924.00	56.45	PK	H	-9.99	46.46	74.00	27.54
4924.00	45.41	AV	H	-9.99	35.42	54.00	18.58
4924.00	53.67	PK	V	-9.99	43.68	74.00	30.32
4924.00	44.40	AV	V	-9.99	34.41	54.00	19.59
7386.00	49.61	PK	H	-4.74	44.87	74.00	29.13
7386.00	39.31	AV	H	-4.74	34.57	54.00	19.43
7386.00	49.30	PK	V	-4.74	44.56	74.00	29.44
7386.00	38.79	AV	V	-4.74	34.05	54.00	19.95

802.11n40

Frequency	Reading	Detector	Polar	Factor	Corrected Amplitude	Limit	Margin
MHz	dBμV	PK/QP/AV	H/V	dB/m	dBμV/m	dBμV/m	dB
Low Channel				2422	MHz		
2390.00	35.51	PK	H	28.57	64.08	74.00	9.92
2390.00	21.54	AV	H	28.57	50.11	54.00	3.89
2390.00	36.51	PK	V	28.57	65.08	74.00	8.92
2390.00	22.52	AV	V	28.57	51.09	54.00	2.91
4844.00	52.25	PK	H	-10.05	42.20	74.00	31.80
4844.00	43.12	AV	H	-10.05	33.07	54.00	20.93
4844.00	51.31	PK	V	-10.05	41.26	74.00	32.74
4844.00	41.30	AV	V	-10.05	31.25	54.00	22.75
7266.00	49.12	PK	H	-5.25	43.87	74.00	30.13
7266.00	38.73	AV	H	-5.25	33.48	54.00	20.52
7266.00	49.26	PK	V	-5.25	44.01	74.00	29.99
7266.00	39.13	AV	V	-5.25	33.88	54.00	20.12
Middle Channel				2437	MHz		
4874.00	51.14	PK	H	-10.02	41.12	74.00	32.88
4874.00	41.38	AV	H	-10.02	31.36	54.00	22.64
4874.00	50.73	PK	V	-10.02	40.71	74.00	33.29
4874.00	40.80	AV	V	-10.02	30.78	54.00	23.22
7311.00	49.41	PK	H	-5.05	44.36	74.00	29.64
7311.00	39.29	AV	H	-5.05	34.24	54.00	19.76
7311.00	49.38	PK	V	-5.05	44.33	74.00	29.67
7311.00	39.32	AV	V	-5.05	34.27	54.00	19.73
High Channel				2452	MHz		
2483.50	32.18	PK	H	28.95	61.13	74.00	12.87
2483.50	17.94	AV	H	28.95	46.89	54.00	7.11
2483.50	32.97	PK	V	28.95	61.92	74.00	12.08
2483.50	18.44	AV	V	28.95	47.39	54.00	6.61
4904.00	50.34	PK	H	-9.99	40.35	74.00	33.65
4904.00	40.37	AV	H	-9.99	30.38	54.00	23.62
4904.00	50.58	PK	V	-9.99	40.59	74.00	33.41
4904.00	39.40	AV	V	-9.99	29.41	54.00	24.59
7356.00	50.40	PK	H	-4.87	45.53	74.00	28.47
7356.00	39.29	AV	H	-4.87	34.42	54.00	19.58
7356.00	49.65	PK	V	-4.87	44.78	74.00	29.22
7356.00	39.23	AV	V	-4.87	34.36	54.00	19.64

Spot Check:**Note: Worst mode was test**

Configuration 2#:

802.11b

Frequency	Reading	Detector	Polar	Factor	Corrected Amplitude	Limit	Margin
MHz	dBμV	PK/QP/AV	H/V	dB/m	dBμV/m	dBμV/m	dB
Low Channel				2412	MHz		
2390.00	28.30	PK	H	28.57	56.87	74.00	17.13
2390.00	17.76	AV	H	28.57	46.33	54.00	7.67
2390.00	29.52	PK	V	28.57	58.09	74.00	15.91
2390.00	17.87	AV	V	28.57	46.44	54.00	7.56
4824.00	59.24	PK	H	-10.09	49.15	74.00	24.85
4824.00	56.48	AV	H	-10.09	46.39	54.00	7.61
4824.00	61.66	PK	V	-10.09	51.57	74.00	22.43
4824.00	59.75	AV	V	-10.09	49.66	54.00	4.34
7236.00	49.60	PK	H	-5.38	44.22	74.00	29.78
7236.00	39.50	AV	H	-5.38	34.12	54.00	19.88
7236.00	49.36	PK	V	-5.38	43.98	74.00	30.02
7236.00	38.91	AV	V	-5.38	33.53	54.00	20.47
Middle Channel				2437	MHz		
4874.00	59.44	PK	H	-10.02	49.42	74.00	24.58
4874.00	56.68	AV	H	-10.02	46.66	54.00	7.34
4874.00	61.56	PK	V	-10.02	51.54	74.00	22.46
4874.00	59.55	AV	V	-10.02	49.53	54.00	4.47
7311.00	49.60	PK	H	-5.05	44.55	74.00	29.45
7311.00	39.33	AV	H	-5.05	34.28	54.00	19.72
7311.00	49.66	PK	V	-5.05	44.61	74.00	29.39
7311.00	38.50	AV	V	-5.05	33.45	54.00	20.55
High Channel				2462	MHz		
2483.50	28.74	PK	H	28.95	57.69	74.00	16.31
2483.50	18.28	AV	H	28.95	47.23	54.00	6.77
2483.50	28.96	PK	V	28.95	57.91	74.00	16.09
2483.50	18.15	AV	V	28.95	47.10	54.00	6.90
4924.00	59.74	PK	H	-9.99	49.75	74.00	24.25
4924.00	56.51	AV	H	-9.99	46.52	54.00	7.48
4924.00	61.61	PK	V	-9.99	51.62	74.00	22.38
4924.00	59.29	AV	V	-9.99	49.30	54.00	4.70
7386.00	49.69	PK	H	-4.74	44.95	74.00	29.05
7386.00	39.39	AV	H	-4.74	34.65	54.00	19.35
7386.00	49.38	PK	V	-4.74	44.64	74.00	29.36
7386.00	38.41	AV	V	-4.74	33.67	54.00	20.33

Configuration 3#:

802.11b





Frequency	Reading	Detector	Polar	Factor	Corrected Amplitude	Limit	Margin
MHz	dBμV	PK/QP/AV	H/V	dB/m	dBμV/m	dBμV/m	dB
Low Channel				2412	MHz		
2390.00	29.35	PK	H	28.57	57.92	74.00	16.08
2390.00	17.71	AV	H	28.57	46.28	54.00	7.72
2390.00	28.70	PK	V	28.57	57.27	74.00	16.73
2390.00	17.81	AV	V	28.57	46.38	54.00	7.62
4824.00	63.25	PK	H	-10.09	53.16	74.00	20.84
4824.00	61.57	AV	H	-10.09	51.48	54.00	2.52
4824.00	62.34	PK	V	-10.09	52.25	74.00	21.75
4824.00	60.54	AV	V	-10.09	50.45	54.00	3.55
7236.00	49.51	PK	H	-5.38	44.13	74.00	29.87
7236.00	38.79	AV	H	-5.38	33.41	54.00	20.59
7236.00	50.57	PK	V	-5.38	45.19	74.00	28.81
7236.00	39.11	AV	V	-5.38	33.73	54.00	20.27
Middle Channel				2437	MHz		
4874.00	62.45	PK	H	-10.02	52.43	74.00	21.57
4874.00	60.68	AV	H	-10.02	50.66	54.00	3.34
4874.00	61.55	PK	V	-10.02	51.53	74.00	22.47
4874.00	58.96	AV	V	-10.02	48.94	54.00	5.06
7311.00	49.53	PK	H	-5.05	44.48	74.00	29.52
7311.00	38.67	AV	H	-5.05	33.62	54.00	20.38
7311.00	49.82	PK	V	-5.05	44.77	74.00	29.23
7311.00	38.88	AV	V	-5.05	33.83	54.00	20.17
High Channel				2462	MHz		
2483.50	28.20	PK	H	28.95	57.15	74.00	16.85
2483.50	17.74	AV	H	28.95	46.69	54.00	7.31
2483.50	28.84	PK	V	28.95	57.79	74.00	16.21
2483.50	17.69	AV	V	28.95	46.64	54.00	7.36
4924.00	62.33	PK	H	-9.99	52.34	74.00	21.66
4924.00	60.08	AV	H	-9.99	50.09	54.00	3.91
4924.00	60.16	PK	V	-9.99	50.17	74.00	23.83
4924.00	57.77	AV	V	-9.99	47.78	54.00	6.22
7386.00	49.48	PK	H	-4.74	44.74	74.00	29.26
7386.00	38.56	AV	H	-4.74	33.82	54.00	20.18
7386.00	49.61	PK	V	-4.74	44.87	74.00	29.13
7386.00	38.75	AV	V	-4.74	34.01	54.00	19.99

Configuration 4#:

802.11b

Frequency	Reading	Detector	Polar	Factor	Corrected Amplitude	Limit	Margin
MHz	dBμV	PK/QP/AV	H/V	dB/m	dBμV/m	dBμV/m	dB
Low Channel				2412	MHz		
2390.00	28.33	PK	H	28.57	56.90	74.00	17.10
2390.00	16.49	AV	H	28.57	45.06	54.00	8.94
2390.00	27.74	PK	V	28.57	56.31	74.00	17.69
2390.00	16.35	AV	V	28.57	44.92	54.00	9.08
4824.00	60.57	PK	H	-10.09	50.48	74.00	23.52
4824.00	58.79	AV	H	-10.09	48.70	54.00	5.30
4824.00	62.47	PK	V	-10.09	52.38	74.00	21.62
4824.00	60.23	AV	V	-10.09	50.14	54.00	3.86
7236.00	48.49	PK	H	-5.38	43.11	74.00	30.89
7236.00	37.16	AV	H	-5.38	31.78	54.00	22.22
7236.00	49.03	PK	V	-5.38	43.65	74.00	30.35
7236.00	37.32	AV	V	-5.38	31.94	54.00	22.06
Middle Channel				2437	MHz		
4874.00	59.89	PK	H	-10.02	49.87	74.00	24.13
4874.00	57.36	AV	H	-10.02	47.34	54.00	6.66
4874.00	61.23	PK	V	-10.02	51.21	74.00	22.79
4874.00	59.21	AV	V	-10.02	49.19	54.00	4.81
7311.00	49.65	PK	H	-5.05	44.60	74.00	29.40
7311.00	37.82	AV	H	-5.05	32.77	54.00	21.23
7311.00	48.77	PK	V	-5.05	43.72	74.00	30.28
7311.00	37.16	AV	V	-5.05	32.11	54.00	21.89
High Channel				2462	MHz		
2483.50	28.74	PK	H	28.95	57.69	74.00	16.31
2483.50	16.49	AV	H	28.95	45.44	54.00	8.56
2483.50	28.52	PK	V	28.95	57.47	74.00	16.53
2483.50	16.43	AV	V	28.95	45.38	54.00	8.62
4924.00	60.22	PK	H	-9.99	50.23	74.00	23.77
4924.00	58.04	AV	H	-9.99	48.05	54.00	5.95
4924.00	61.43	PK	V	-9.99	51.44	74.00	22.56
4924.00	59.48	AV	V	-9.99	49.49	54.00	4.51
7386.00	48.87	PK	H	-4.74	44.13	74.00	29.87
7386.00	37.36	AV	H	-4.74	32.62	54.00	21.38
7386.00	48.19	PK	V	-4.74	43.45	74.00	30.55
7386.00	37.36	AV	V	-4.74	32.62	54.00	21.38

Worst Channel Test plots:
Configuration 1#:
1-18GHz:


802.11b, Low Channel, Horizontal**802.11b, Low Channel, Vertical**

802.11g, Low Channel, Horizontal

Project No.: 2402W92356E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11g Low Channel 2412MHz

Serial No.: 2QUD-6
Tester: Nat Zhou

Date: 2024-09-12




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4824.00	61.49	-10.09	51.40	74.00	22.60	Peak
2	4824.00	51.62	-10.09	41.53	54.00	12.47	Average

802.11g, Low Channel, Vertical

Project No.: 2402W92356E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11g Low Channel 2412MHz

Serial No.: 2QUD-6
Tester: Nat Zhou

Date: 2024-09-12




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4824.00	58.78	-10.09	48.69	74.00	25.31	Peak
2	4824.00	48.36	-10.09	38.27	54.00	15.73	Average

Project No.: 2402W92356E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11g Low Channel 2412MHz

Serial No.: 2QUD-6
Tester: Nat Zhou

Date: 2024-11-16




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	7236.00	48.59	-5.38	43.21	74.00	30.79	Peak
2	7236.00	38.20	-5.38	32.82	54.00	21.18	Average
3	17997.60	46.51	8.12	54.63	74.00	19.37	Peak
4	17997.60	36.85	8.12	44.97	54.00	9.03	Average

Project No.: 2402W92356E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11g Low Channel 2412MHz

Serial No.: 2QUD-6
Tester: Nat Zhou

Date: 2024-11-16




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	7236.00	49.64	-5.38	44.26	74.00	29.74	Peak
2	7236.00	39.32	-5.38	33.94	54.00	20.06	Average
3	17985.60	47.05	8.03	55.08	74.00	18.92	Peak
4	17985.60	37.07	8.03	45.10	54.00	8.90	Average

802. 11n20, Low Channel, Horizontal

Project No.: 2402W92356E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11n20 Low Channel 2412MHz


Serial No.: 2QU0-6
Tester: Nat Zhou



802. 11n20, Low Channel, Vertical


Project No.: 2402W92356E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11n20 Low Channel 2412MHz

Serial No.: 2QU0-6
Tester: Nat Zhou




Project No.: 2402W92356E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11n20 Low Channel 2412MHz

Serial No.: 2QU0-6
Tester: Nat Zhou



Project No.: 2402W92356E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11n20 Low Channel 2412MHz


Serial No.: 2QU0-6
Tester: Nat Zhou



802.11n40, High Channel, Horizontal


Project No.: 2402W92356E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11n40 High Channel 2452MHz

Serial No.: 2QUD-6
Tester: Nat Zhou

**802.11n40, High Channel, Vertical**


Project No.: 2402W92356E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11n40 High Channel 2452MHz

Serial No.: 2QUD-6
Tester: Nat Zhou




Project No.: 2402W92356E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11n40 High Channel 2452MHz

Serial No.: 2QUD-6
Tester: Nat Zhou



Project No.: 2402W92356E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11n40 High Channel 2452MHz

Serial No.: 2QUD-6
Tester: Nat Zhou




18-25GHz:

No Emission was detected in the range 18-25GHz, test was performed on the mode and channel which with the maximum power.

802.11g, High Channel, Horizontal

Project No.: 2402W92356E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11g High Channel 2462MHz

Serial No.: ZQUD-6
Tester: Nat Zhou




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	24958.00	43.96	9.55	53.51	74.00	20.49	Peak
2	24958.00	38.10	9.55	47.65	54.00	6.35	Average





802.11g, High Channel, Vertical

Project No.: 2402W92356E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11g High Channel 2462MHz


Serial No.: ZQUD-6
Tester: Nat Zhou




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	23395.60	44.94	8.71	53.65	74.00	20.35	Peak
2	23395.60	38.95	8.71	47.66	54.00	6.34	Average

Bandedge:**802.11b, Low Channel, Bandedge, Horizontal****802.11b, Low Channel, Bandedge, Vertical****802.11b, High Channel, Bandedge, Horizontal****802.11b, High Channel, Bandedge, Vertical**


802.11g, Low Channel, Bandedge, Horizontal




802.11g, Low Channel, Bandedge, Vertical



802.11g, High Channel, Bandedge, Horizontal




802.11g, High Channel, Bandedge, Vertical



**802.11n20, Low Channel, Bandedge,
Horizontal**

Project No.: 2402W92356E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11n20 Low Channel 2412MHz

Serial No.: 2QUD-6
Tester: Nat Zhou




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2390.00	35.14	28.57	63.71	74.00	10.29	Peak
2	2390.00	21.21	28.57	49.78	54.00	4.22	Average

**802.11n20, Low Channel, Bandedge,
Vertical**

Project No.: 2402W92356E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11n20 Low Channel 2412MHz

Serial No.: 2QUD-6
Tester: Nat Zhou




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2390.00	35.91	28.57	64.48	74.00	9.52	Peak
2	2390.00	21.80	28.57	50.37	54.00	3.63	Average

**802.11n20, High Channel, Bandedge,
Horizontal**

Project No.: 2402W92356E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11n20 High Channel 2462MHz

Serial No.: 2QUD-6
Tester: Nat Zhou




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2483.50	33.18	28.95	62.13	74.00	11.87	Peak
2	2483.50	18.03	28.95	46.98	54.00	7.02	Average

**802.11n20, High Channel, Bandedge,
Vertical**

Project No.: 2402W92356E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11n20 High Channel 2462MHz

Serial No.: 2QUD-6
Tester: Nat Zhou




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2483.50	33.95	28.95	62.90	74.00	11.10	Peak
2	2483.50	18.83	28.95	47.78	54.00	6.22	Average

**802. 11n40, Low Channel, Bandedge,
Horizontal**

Project No.: 2402W92356E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11n40 Low Channel 2422MHz

Serial No.: 2QUD-6
Tester: Nat Zhou




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2390.00	35.51	28.57	64.08	74.00	9.92	Peak
2	2390.00	21.54	28.57	50.11	54.00	3.89	Average

**802. 11n40, Low Channel, Bandedge,
Vertical**

Project No.: 2402W92356E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11n40 Low Channel 2422MHz

Serial No.: 2QUD-6
Tester: Nat Zhou




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2390.00	36.51	28.57	65.08	74.00	8.92	Peak
2	2390.00	22.52	28.57	51.09	54.00	2.91	Average

**802. 11n40, High Channel, Bandedge,
Horizontal**

Project No.: 2402W92356E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11n40 High Channel 2452MHz

Serial No.: 2QUD-6
Tester: Nat Zhou




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2483.50	32.18	28.95	61.13	74.00	12.87	Peak
2	2483.50	17.94	28.95	46.89	54.00	7.11	Average

**802. 11n40, High Channel, Bandedge,
Vertical**

Project No.: 2402W92356E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11n40 High Channel 2452MHz

Serial No.: 2QUD-6
Tester: Nat Zhou



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2483.50	32.97	28.95	61.92	74.00	12.08	Peak
2	2483.50	18.44	28.95	47.39	54.00	6.61	Average

5.3 6dB Emission Bandwidth

Test Information:

Serial No.:	2QUD-5	Test Date:	2024/09/19~2024/11/13
Test Site:	RF	Test Mode:	Transmitting
Tester:	Roy Xiao, Jeff Wei	Test Result:	Pass

Environmental Conditions:

Temperature: (°C):	25.4~26.1	Relative Humidity: (%)	52~54	ATM Pressure: (kPa)	100.2~101.2
-----------------------	-----------	------------------------------	-------	------------------------	-------------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Narda	Coaxial Attenuator	773-10	F-08-EM511	2024/06/07	2025/06/06
R&S	Spectrum Analyzer	FSV40	101589	2024/09/05	2025/09/04

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:


Mode	Test Frequency (MHz)	Result (MHz)	Limit (MHz)	Verdict
802.11b	2412	8.609	≥0.5	Pass
	2437	8.128	≥0.5	Pass
	2462	8.609	≥0.5	Pass
802.11g	2412	15.776	≥0.5	Pass
	2437	15.175	≥0.5	Pass
	2462	15.215	≥0.5	Pass
802.11n20	2412	16.376	≥0.5	Pass
	2437	15.175	≥0.5	Pass
	2462	15.776	≥0.5	Pass
802.11n40	2422	30.190	≥0.5	Pass
	2437	32.753	≥0.5	Pass
	2452	35.235	≥0.5	Pass

802.11b_2412MHz




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 19.SEP.2024 23:32:46

802.11b_2437MHz




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 19.SEP.2024 23:36:21

802.11b_2462MHz




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 19.SEP.2024 23:40:48

802.11g_2412MHz




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 19.SEP.2024 23:43:47

802.11g_2437MHz




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 19.SEP.2024 23:46:41

802.11g_2462MHz




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 19.SEP.2024 23:49:13

802.11n20_2412MHz




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 19.SEP.2024 23:51:58

802.11n20_2437MHz




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 19.SEP.2024 23:54:42

802.11n20_2462MHz




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 19.SEP.2024 23:56:45

802.11n40_2422MHz




ProjectNo.:2402W92356E-RF Tester:Jeff Wei
Date: 13.NOV.2024 11:06:29

802.11n40_2437MHz



ProjectNo.:2402W92356E-RF Tester:Jeff Wei
Date: 13.NOV.2024 11:08:12

802.11n40_2452MHz



ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 00:04:24

5.4 99% Occupied Bandwidth**Test Information:**

Serial No.:	2QUD-5	Test Date:	2024/09/19~2024/09/20
Test Site:	RF	Test Mode:	Transmitting
Tester:	Roy Xiao	Test Result:	/

Environmental Conditions:

Temperature: (°C):	26.1~26.2	Relative Humidity: (%)	41~43	ATM Pressure: (kPa)	100.1~100.2
-------------------------------	-----------	---------------------------------------	-------	--------------------------------	-------------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Narda	Coaxial Attenuator	773-10	F-08-EM511	2024/06/07	2025/06/06
R&S	Spectrum Analyzer	FSV40	101589	2024/09/05	2025/09/04

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Mode	Test Frequency (MHz)	99% OBW (MHz)
802.11b	2412	12.840
	2437	12.520
	2462	12.840
802.11g	2412	16.560
	2437	16.360
	2462	16.520
802.11n20	2412	17.640
	2437	17.520
	2462	17.640
802.11n40	2422	36.080
	2437	35.600
	2452	36.160


802.11b_2412MHz



ProjectNo.:2402W92356E-RF Tester:Roy Xiao

Date: 19.SEP.2024 23:13:02


802.11b_2437MHz



ProjectNo.:2402W92356E-RF Tester:Roy Xiao

Date: 19.SEP.2024 23:16:37


802.11b_2462MHz



ProjectNo.:2402W92356E-RF Tester:Roy Xiao

Date: 19.SEP.2024 23:41:05


802.11g_2412MHz



ProjectNo.:2402W92356E-RF Tester:Roy Xiao

Date: 19.SEP.2024 23:44:05


802.11g_2437MHz



ProjectNo.:2402W92356E-RF Tester:Roy Xiao

Date: 19.SEP.2024 23:46:58


802.11g_2462MHz



ProjectNo.:2402W92356E-RF Tester:Roy Xiao


Date: 19.SEP.2024 23:49:30

802.11n20_2412MHz




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 19.SEP.2024 23:52:16

802.11n20_2437MHz




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 19.SEP.2024 23:54:59

802.11n20_2462MHz




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 19.SEP.2024 23:57:02

802.11n40_2422MHz




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 19.SEP.2024 23:59:30

802.11n40_2437MHz



ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 00:02:16

802.11n40_2452MHz



ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 00:04:37

5.5 Maximum Conducted Output Power

Test Information:

Serial No.:	2QUD-5, 2QUD-10, 2QUD-7, 2QUD-9	Test Date:	2024/09/19~2024/12/19
Test Site:	RF	Test Mode:	Transmitting
Tester:	Roy Xiao, Jeff Wei, Jojo Zhou	Test Result:	Pass

Environmental Conditions:

Temperature: (°C):	20.8~26.2	Relative Humidity: (%)	33~51	ATM Pressure: (kPa)	100.1~102.5
-----------------------	-----------	------------------------------	-------	------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Narda	Coaxial Attenuator	773-10	F-08-EM511	2024/06/07	2025/06/06
Anritsu	Microwave Peak Power Sensor	MA24418A	12618	2024/09/04	2025/09/03
Eastsheep	Coaxial Attenuator	5W-N-JK-6G-10dB	F-08-EM504	2024/6/7	2025/6/6

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Configuration 1#:

Mode	Test Frequency (MHz)	Peak Output Power (dBm)	Average Output Power (dBm)	Limit (dBm)	Verdict
802.11b	2412	15.56	13.01	30	Pass
	2437	15.73	13.26	30	Pass
	2462	16.21	13.41	30	Pass
802.11g	2412	22.81	15.66	30	Pass
	2437	22.92	15.91	30	Pass
	2462	22.94	16.13	30	Pass
802.11n20	2412	21.55	15.01	30	Pass
	2437	21.91	15.06	30	Pass
	2462	21.97	15.23	30	Pass
802.11n40	2422	21.06	13.99	30	Pass
	2437	21.23	14.21	30	Pass
	2452	21.24	13.93	30	Pass
Max.EIRP		23.84		36	Pass

Spot Check:
Configuration 2#:

Mode	Test Frequency (MHz)	Peak Output Power(dBm)	Average Output Power(dBm)	Limit (dBm)	Verdict
802.11b	2412	15.48	12.72	30	Pass
	2437	15.53	13.08	30	Pass
	2462	16.04	13.15	30	Pass
802.11g	2412	22.70	15.46	30	Pass
	2437	22.80	15.78	30	Pass
	2462	22.91	15.90	30	Pass
802.11n20	2412	21.41	14.42	30	Pass
	2437	21.74	14.73	30	Pass
	2462	21.88	14.98	30	Pass
802.11n40	2422	20.91	13.72	30	Pass
	2437	21.12	13.97	30	Pass
	2452	21.13	13.18	30	Pass
Max.EIRP		23.81		36	Pass

Configuration 3#:

Mode	Test Frequency (MHz)	Peak Output Power(dBm)	Average Output Power(dBm)	Limit (dBm)	Verdict
802.11b	2412	15.33	12.92	30	Pass
	2437	15.44	12.85	30	Pass
	2462	15.99	13.22	30	Pass
802.11g	2412	22.74	15.47	30	Pass
	2437	22.85	15.65	30	Pass
	2462	22.79	15.88	30	Pass
802.11n20	2412	21.44	14.84	30	Pass
	2437	21.70	14.90	30	Pass
	2462	21.85	15.07	30	Pass
802.11n40	2422	20.98	13.75	30	Pass
	2437	21.17	13.93	30	Pass
	2452	21.22	13.75	30	Pass
Max.EIRP		23.75		36	Pass

Configuration 4#:

Mode	Test Frequency (MHz)	Peak Output Power (dBm)	Average Output Power (dBm)	Limit (dBm)	Verdict
802.11b	2412	15.18	12.78	30	Pass
	2437	15.47	12.94	30	Pass
	2462	15.99	13.22	30	Pass
802.11g	2412	22.47	15.32	30	Pass
	2437	22.52	15.58	30	Pass
	2462	22.66	15.70	30	Pass
802.11n20	2412	21.38	14.98	30	Pass
	2437	21.47	15.01	30	Pass
	2462	21.63	15.13	30	Pass
802.11n40	2422	20.59	13.63	30	Pass
	2437	21.07	13.84	30	Pass
	2452	20.95	13.48	30	Pass
Max.EIRP		23.56		36	Pass

Note: The test data of the two models are almost the same.

5.6 Power Spectral Density

Test Information:

Serial No.:	2QUD-5	Test Date:	2024/09/19~2024/11/13
Test Site:	RF	Test Mode:	Transmitting
Tester:	Roy Xiao, Jeff Wei	Test Result:	Pass

Environmental Conditions:

Temperature: (°C):	25.4~26.1	Relative Humidity: (%)	52~54	ATM Pressure: (kPa)	100.2~101.2
-----------------------	-----------	------------------------------	-------	------------------------	-------------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Narda	Coaxial Attenuator	773-10	F-08-EM511	2024/06/07	2025/06/06
R&S	Spectrum Analyzer	FSV40	101589	2024/09/05	2025/09/04

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:


Mode	Test Frequency (MHz)	Result (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
802.11b	2412	-8.59	8	Pass
	2437	-7.61	8	Pass
	2462	-8.42	8	Pass
802.11g	2412	-6.80	8	Pass
	2437	-7.00	8	Pass
	2462	-7.52	8	Pass
802.11n20	2412	-8.20	8	Pass
	2437	-8.14	8	Pass
	2462	-8.41	8	Pass
802.11n40	2422	-12.60	8	Pass
	2437	-11.94	8	Pass
	2452	-12.18	8	Pass

802.11b_2412MHz




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 19.SEP.2024 23:34:53

802.11b_2437MHz




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 19.SEP.2024 23:37:13

802.11b_2462MHz




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 19.SEP.2024 23:42:04

802.11g_2412MHz




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 19.SEP.2024 23:45:19

802.11g_2437MHz




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 19.SEP.2024 23:47:50

802.11g_2462MHz




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 19.SEP.2024 23:50:41

802.11n20_2412MHz




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 19.SEP.2024 23:53:30

802.11n20_2437MHz




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 19.SEP.2024 23:55:52

802.11n20_2462MHz




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 19.SEP.2024 23:58:14

802.11n40_2422MHz




ProjectNo.:2402W92356E-RF Tester:Jeff Wei
Date: 13.NOV.2024 11:07:35

802.11n40_2437MHz



ProjectNo.:2402W92356E-RF Tester:Jeff Wei
Date: 13.NOV.2024 11:09:25

802.11n40_2452MHz



ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 00:06:30

5.7 100 kHz Bandwidth of Frequency Band Edge

Test Information:

Serial No.:	2QUD-5	Test Date:	2024/09/19~2024/09/20
Test Site:	RF	Test Mode:	Transmitting
Tester:	Roy Xiao	Test Result:	Pass

Environmental Conditions:



Temperature: (°C):	26.1~26.2	Relative Humidity: (%)	41~43	ATM Pressure: (kPa)	100.1~100.2
-----------------------	-----------	------------------------------	-------	------------------------	-------------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Narda	Coaxial Attenuator	773-10	F-08-EM511	2024/06/07	2025/06/06
R&S	Spectrum Analyzer	FSV40	101589	2024/09/05	2025/09/04

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:




802.11g_2412MHz



ProjectNo.:2402W92356E-RF Tester:Roy Xiao

Date: 19.SEP.2024 23:44:40


802.11g_2462MHz



ProjectNo.:2402W92356E-RF Tester:Roy Xiao

Date: 19.SEP.2024 23:50:04


802.11n20_2412MHz



ProjectNo.:2402W92356E-RF Tester:Roy Xiao

Date: 19.SEP.2024 23:52:50


802.11n20_2462MHz



ProjectNo.:2402W92356E-RF Tester:Roy Xiao

Date: 19.SEP.2024 23:57:36


802.11n40_2422MHz



ProjectNo.:2402W92356E-RF Tester:Roy Xiao

Date: 20.SEP.2024 00:00:05

802.11n40_2452MHz



ProjectNo.:2402W92356E-RF Tester:Roy Xiao

Date: 20.SEP.2024 00:05:13

5.8 Duty Cycle

Test Information:

Serial No.:	2QUD-5	Test Date:	2024/09/19
Test Site:	RF	Test Mode:	Transmitting
Tester:	Roy Xiao	Test Result:	/

Environmental Conditions:

Temperature: (°C):	26.2	Relative Humidity: (%)	41	ATM Pressure: (kPa)	100.1
-------------------------------	------	---------------------------------------	----	--------------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Narda	Coaxial Attenuator	773-10	F-08-EM511	2024/06/07	2025/06/06
R&S	Spectrum Analyzer	FSV40	101589	2024/09/05	2025/09/04


* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Mode	Test Frequency (MHz)	Ton (ms)	Ton+Toff (ms)	Duty Cycle (%)	1/Ton (Hz)	VBW Setting (kHz)
802.11b	2437	8.368	8.415	99.44	/	0.010
802.11g	2437	1.391	1.437	96.80	719	1
802.11n20	2437	0.648	0.692	93.64	1543	2
802.11n40	2437	1.299	1.344	96.65	770	1


Duty Cycle = Ton/(Ton+Toff)*100%

802.11b_2437MHz




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 19_SEP,2024 23:26:31

802.11g_2437MHz




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 19_SEP,2024 23:28:10

802.11n20_2437MHz



ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 19_SEP,2024 23:30:25

802.11n40_2437MHz



ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 19_SEP,2024 23:31:37

EXHIBIT A - EUT PHOTOGRAPHS

Please refer to the attachment 2402W92356E-RF-EXP EUT EXTERNAL PHOTOGRAPHS and 2402W92356E-RF-INP EUT INTERNAL PHOTOGRAPHS.

EXHIBIT B - TEST SETUP PHOTOGRAPHS

Please refer to the attachment 2402W92356E-RF-00C-TSP TEST SETUP PHOTOGRAPHS.

******* END OF REPORT *******