

TEST REPORT

Applicant: FCC: INGENICO

IC: Ingenico

FCC: 9 Avenue de la gare - Rovaltain TGV, BP25156, Valence Cedex

Address: 9,26958 ,France

IC: 9 avenue de la gare Rovaltain TGV, Valence 26958, France

Product Name: Payment Terminals

FCC ID: XKB-SXXCLWIBT

IC: 2586D-SXXCLWIBT

AXIUM SX7000 CL/Eth/4G/WiFi/BT,

HVIN: AXIUM SX5000 CL/Eth/4G/WiFi/BT,

AXIUM SX7000 CL/Eth/WiFi/BT, AXIUM SX5000 CL/Eth/WiFi/BT

47 CFR Part 15, Subpart C(15.247)

RSS-247 Issue 3, August 2023

Standard(s): RSS-Gen, Issue 5, February 2021 Amendment 2

ANSI C63.10-2013

KDB 558074 D01 15.247 Meas Guidance v05r02

Report Number: 2402W92356E-RF-00A

Report Date: 2024/12/20

The above device has been tested and found compliant with the requirement of the relative standards by Bay Area Compliance Laboratories Corp. (Dongguan).

Reviewed By: Pedro Yun

Title: **Project Engineer**

Approved By: Ivan Cao

Title: **EMC Manager**

Bay Area Compliance Laboratories Corp. (Dongguan)
No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China

Tel: +86-769-86858888

Fax: +86-769-86858891

www.baclcorp.com.cn

Note: The information marked ▲ is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report cannot be reproduced except in full, without prior written approval of the Company. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0. This report may contain data that are not covered by the accreditation scope and shall be marked with ★. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government. Each test item follows the test standard(s) without deviation.

CONTENTS

CONTENTS	2
DOCUMENT REVISION HISTORY	4
1. GENERAL INFORMATION	5
1.1 GENERAL DESCRIPTION OF EQUIPMENT UNDER TEST	5
1.2 ACCESSORY INFORMATION	5
1.3 ANTENNA INFORMATION DETAIL▲	6
1.4 EQUIPMENT MODIFICATIONS	6
2. SUMMARY OF TEST RESULTS	7
3. DESCRIPTION OF TEST CONFIGURATION	8
3.1 OPERATION FREQUENCY DETAIL	8
3.2 EUT OPERATION CONDITION	8
3.3 SUPPORT EQUIPMENT LIST AND DETAILS	8
3.4 SUPPORT CABLE LIST AND DETAILS	9
3.5 BLOCK DIAGRAM OF TEST SETUP	9
3.6 TEST FACILITY	14
3.7 MEASUREMENT UNCERTAINTY	14
4. REQUIREMENTS AND TEST PROCEDURES	15
4.1 AC LINE CONDUCTED EMISSIONS	15
4.1.1 Applicable Standard	15
4.1.2 EUT Setup	17
4.1.3 EMI Test Receiver Setup	17
4.1.4 Test Procedure	18
4.1.5 Corrected Amplitude & Margin Calculation	18
4.1.6 Test Result	18
4.2 RADIATED SPURIOUS EMISSIONS	19
4.2.1 Applicable Standard	19
4.2.2 EUT Setup	19
4.2.3 EMI Test Receiver & Spectrum Analyzer Setup	21
4.2.4 Test Procedure	21
4.2.5 Corrected Result & Margin Calculation	22
4.2.6 Test Result	22
4.3 20 dB EMISSION BANDWIDTH	23
4.3.1 Applicable Standard	23
4.3.2 EUT Setup	23
4.3.3 Test Procedure	24
4.3.4 Test Result	24
4.4 99% OCCUPIED BANDWIDTH:	25
4.4.1 Applicable Standard	25
4.4.2 EUT Setup	25
4.4.3 Test Procedure	26
4.4.4 Test Result	26
4.5 CHANNEL SEPARATION	27

4.5.1 Applicable Standard	27
4.5.2 EUT Setup	27
4.5.3 Test Procedure	27
4.5.4 Test Result	27
4.6 NUMBER OF HOPPING FREQUENCY	28
4.6.1 Applicable Standard	28
4.6.2 EUT Setup	28
4.6.3 Test Procedure	28
4.6.4 Test Result	28
4.7 TIME OF OCCUPANCY(DWELL TIME)	29
4.7.1 Applicable Standard	29
4.7.2 EUT Setup	29
4.7.3 Test Procedure	29
4.7.4 Test Result	30
4.8 MAXIMUM CONDUCTED OUTPUT POWER	31
4.8.1 Applicable Standard	31
4.8.2 EUT Setup	31
4.8.3 Test Procedure	31
4.8.4 Test Result	32
4.9 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	33
4.9.1 Applicable Standard	33
4.9.2 EUT Setup	33
4.9.3 Test Procedure	33
4.9.4 Test Result	34
4.10 ANTENNA REQUIREMENT	35
4.10.1 Applicable Standard	35
4.10.2 Judgment	35
5. TEST DATA AND RESULTS	36
5.1 AC LINE CONDUCTED EMISSIONS	36
5.2 RADIATED SPURIOUS EMISSIONS	45
5.3 20 dB EMISSION BANDWIDTH	70
5.4 99% OCCUPIED BANDWIDTH	73
5.5 CHANNEL SEPARATION	76
5.6 NUMBER OF HOPPING FREQUENCY	78
5.7 TIME OF OCCUPANCY (DWELL TIME)	80
5.8 MAXIMUM CONDUCTED OUTPUT POWER	83
5.9 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	94
EXHIBIT A - EUT PHOTOGRAPHS	97
EXHIBIT B - TEST SETUP PHOTOGRAPHS	98

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	2402W92356E-RF-00A	Original Report	2024/12/20

1. GENERAL INFORMATION

1.1 General Description of Equipment under Test

EUT Name:	Payment Terminals
EUT Model:	AXIUM SX7000
Multiple Model:	AXIUM SX5000
Operation Frequency:	2402-2480 MHz
Maximum Peak Output Power (Conducted):	6.71dBm
Modulation Type:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Rated Input Voltage:	DC 9V-45V
Serial Number:	For RF Conducted Test: 2QUD-5 (Configuration 1#) 2QUD-10 (Configuration 2#) 2QUD-7 (Configuration 3#) 2QUD-9 (Configuration 4#) For AC line conducted emissions and Radiated Spurious Emissions Below 1G Tests: 2QUD-1 (Configuration 1#) 2QUD-3 (Configuration 2#) 2QUD-2 (Configuration 3#) 2QUD-4 (Configuration 4#) For Radiated Spurious Emissions Above 1G Test: 2QUD-6 (Configuration 1#) 2QUD-3 (Configuration 2#) 2QUD-8 (Configuration 3#) 2QUD-4 (Configuration 4#)
EUT Received Date:	2024/8/29
EUT Received Status:	Good

Note: The multiple models are electrically identical with the test model. Please refer to the declaration letter for more detail, which was provided by manufacturer.

Configurations:

Configuration	HVIN	Configuration Description
1#	AXIUM SX7000 CL/Eth/4G/WiFi/BT	With Smartcard reader, With LTE.
2#	AXIUM SX5000 CL/Eth/4G/WiFi/BT	Without Smartcard reader, With LTE.
3#	AXIUM SX7000 CL/Eth/WiFi/BT	With Smartcard reader, Without LTE.
4#	AXIUM SX5000 CL/Eth/WiFi/BT	Without Smartcard reader, Without LTE.

1.2 Accessory Information

Accessory Description	Manufacturer	Model	Parameters
/	/	/	/

1.3 Antenna Information Detail ▲

Antenna Manufacturer	Antenna Type	input impedance (Ohm)	Frequency Range	Antenna Gain
Ingenico	PIFA	50	2.4~2.5GHz	0.90 dBi
The design of compliance with §15.203:				
☒ Unit uses a permanently attached antenna.				
☐ Unit uses a unique coupling to the intentional radiator.				
☐ Unit was professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.				

1.4 Equipment Modifications

No modifications are made to the EUT during all test items.

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.207(a) RSS-Gen Clause 8.8	AC Line Conducted Emissions	Compliant
FCC §15.205, §15.209, §15.247(d) RSS-Gen Clause 8.10	Radiated Spurious Emissions	Compliant
FCC §15.247(a)(1) RSS-247 Clause 5.1 b)	20 dB Emission Bandwidth	Compliant
RSS-Gen Clause 6.7	99% Occupied Bandwidth	Compliant
FCC §15.247(a)(1) RSS-247 Clause 5.1 b)	Channel Separation	Compliant
FCC §15.247(a)(1)(iii) RSS-247 Clause 5.1 d)	Number Of Hopping Frequency	Compliant
FCC §15.247(a)(1)(iii) RSS-247 Clause 5.1 d)	Time Of Occupancy (dwell time)	Compliant
FCC §15.247(b)(1) RSS-247 Clause 5.4 b)	Maximum Conducted Output Power	Compliant
FCC §15.247(d) RSS-247 Clause 5.5	100 kHz Bandwidth Of Frequency Band Edge	Compliant
FCC §15.203 RSS-Gen Clause 6.8	Antenna Requirement	Compliant
Note 1: For AC line conducted emissions, the maximum output power mode and channel was tested. Note 2: For Radiated Spurious Emissions 9kHz~ 1GHz and 18-25GHz, the maximum output power mode and channel was tested.		

3. DESCRIPTION OF TEST CONFIGURATION

3.1 Operation Frequency Detail

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	40	2442
1	2404	41	2443
...	...	...	...
...	...	...	...
...	...	78	2480
39	2441	/	/

Note: The above frequencies in bold were performed the test.

3.2 EUT Operation Condition

The EUT was configured for testing in Engineering Mode, which was provided by the manufacturer. The EUT configuration as below:

EUT Exercise Software:	CMD		
The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer▲:			
Test Modes	Power Level Setting		
	Lowest Channel	Middle Channel	Highest Channel
GFSK	Default	Default	Default
$\pi/4$ -DQPSK	Default	Default	Default
8DPSK	Default	Default	Default

3.3 Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
ZIONCOM	Router	MB-R210-00	R16Y06M271022
Lenovo	Laptop 1	G510	EMZBPC21103006
Lenovo	Laptop 2	E450	PF-OMRADG
DELL	Monitor	P2721Q	CN-0XJ46C-FCC00-135-A97L-A03
Adam	LTE Antenna 1	Unknown	SXANTENNA1
Adam	LTE Antenna 2	Unknown	SXANTENNA2
Unknown	I/O Load	Unknown	I/O Load-SX7000
Unknown	RJ11 Load	Unknown	RJ11 Load-SX7000
SANDisk	U-Disk	16G	BL201026115 B
Phihong	Adapter(12V)	PSM36W-120L6IN	192050627
CLC	Earphone	Blackview5.0	EMZBEP21103001W


3.4 Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
DC Cable	No	No	1	Adapter(12V)	EUT
RJ45 Cable	No	No	10	Router	EUT
DC Cable	No	No	2	I/O Load	EUT
RJ11 Cable	No	No	3	RJ11 Load	EUT
USB Cable	No	No	1	Laptop 1/2	EUT
HDMI Cable	Yes	No	1.2	Monitor	EUT
Earphone	No	No	0.8	Earphone	EUT
Signal cable	No	No	1	LTE Antenna 1	EUT
Signal cable	No	No	1	LTE Antenna 2	EUT


3.5 Block Diagram of Test Setup

AC line conducted emissions:

Configuration 1#& Configuration 2#:




Configuration 3#& Configuration 4#:




Spurious Emissions:

Below 1GHz:


Configuration 1#:




Configuration 2#:



Configuration 3#:




Configuration 4#:




Above 1GHz:

Configuration 1#& Configuration 2#:



Configuration 3#& Configuration 4#:



3.6 Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 829273, the FCC Designation No. : CN5044.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

3.7 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	9kHz~30MHz: 3.3dB, 30MHz~200MHz: 4.55 dB, 200MHz~1GHz: 5.92 dB, 1GHz~6GHz: 4.98 dB, 6GHz~18GHz: 5.89 dB, 18GHz~26.5GHz:5.47 dB, 26.5GHz~40GHz:5.63 dB
Unwanted Emissions, conducted	±2.47 dB
Temperature	±1℃
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.11 dB (150 kHz to 30 MHz)

4. REQUIREMENTS AND TEST PROCEDURES

4.1 AC Line Conducted Emissions

4.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:

(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

RSS-Gen Clause 8.8

Unless stated otherwise in the applicable RSS, for radio apparatus that are designed to be connected to the public utility AC power network, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the range 150 kHz to 30 MHz shall not exceed the limits in table 4, as measured using a 50 μ H / 50 Ω line impedance stabilization network. This requirement applies for the radio frequency voltage measured between each power line and the ground terminal of each AC power-line mains cable of the EUT. For an EUT that connects to the AC power lines indirectly, through another device, the requirement for compliance with the limits in table 4 shall apply at the terminals of the AC power-line mains cable of a representative support device, while it provides power to the EUT. The lower limit applies at the boundary between the frequency ranges. The device used to power the EUT shall be representative of typical applications.

Table 4 – AC power-line conducted emissions limits


Frequency (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 ¹	56 to 46 ¹
0.5 – 5	56	46
5 – 30	60	50

Note 1: The level decreases linearly with the logarithm of the frequency.

For an EUT with a permanent or detachable antenna operating between 150 kHz and 30 MHz, the AC power-line conducted emissions must be measured using the following configurations:

- (a) Perform the AC power-line conducted emissions test with the antenna connected to determine compliance with the limits of table 4 outside the transmitter's fundamental emission band.
- (b) Retest with a dummy load instead of the antenna to determine compliance with the limits of table 4 within the transmitter's fundamental emission band. For a detachable antenna, remove the antenna and connect a suitable dummy load to the antenna connector. For a permanent antenna, remove the antenna and terminate the RF output with a dummy load or network that simulates the antenna in the fundamental frequency band.

4.1.2 EUT Setup



The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207, RSS-Gen limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

4.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

4.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

4.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

4.1.6 Test Result

Please refer to section 5.1.

4.2 Radiated Spurious Emissions

4.2.1 Applicable Standard

FCC §15.247 (d);


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).



RSS-247 Clause 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required

4.2.2 EUT Setup

9kHz~30MHz:



30MHz~1GHz:**Above 1GHz:**

The radiated emissions were performed in the 3 meters distance, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, FCC 15.247 limits & RSS-247, RSS-Gen limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

For 9kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

4.2.3 EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9kHz-1000MHz:

Frequency Range	Measurement	RBW	Video B/W	IF B/W	Detector
9 kHz – 150 kHz	QP/AV	200 Hz	1 kHz	200 Hz	QP/AV
150 kHz – 30 MHz	QP/AV	9 kHz	30 kHz	9 kHz	QP/AV
30 MHz – 1000 MHz	PK	100 kHz	300 kHz	/	PK
	QP	/	/	120 kHz	QP

1GHz- 25GHz:

Pre-scan:

Measurement	RBW	Video B/W	Detector
PK	1MHz	3 MHz	PK
Ave.	1MHz	5kHz	PK

Final measurement for emission identified during the pre-scan:

Measurement	RBW	Video B/W	Detector
PK	1MHz	3 MHz	PK
Ave.	1MHz	10 Hz	PK

4.2.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 9 kHz-1 GHz except 9-90 kHz, 110-490 kHz, employing an average detector, peak and Average detection modes for frequencies above 1 GHz.

If the maximized peak measured value is under the QP/Average limit by more than 6dB, then it is unnecessary to perform an QP/Average measurement.

All emissions under the average limit and under the noise floor have not recorded in the report.

4.2.5 Corrected Result & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = Antenna Factor + Cable Loss - Amplifier Gain

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

For the spurious emission below 30MHz, the limit was convert from dBμA/m to dBμV/m by adding 51.5 dB.

4.2.6 Test Result

Please refer to section 5.2.

4.3 20 dB Emission Bandwidth

4.3.1 Applicable Standard


FCC §15.247 (a)(1)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

RSS-247 Clause 5.1 b)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

4.3.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, which was provided by manufacturer. The insert loss of this RF cable/attenuator was offset into the setting of test equipment.

4.3.3 Test Procedure

According to ANSI C63.10-2013 Section 6.9.2

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW}/\text{RBW})]$ below the reference level. Specific guidance is given in 4.1.5.2
- d) Steps a) through c) might require iteration to adjust within the specified tolerances.
- e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.
- f) Set detection mode to peak and trace mode to max hold.
- g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).
- h) Determine the “-xx dB down amplitude” using $[(\text{reference value}) - \text{xx}]$. Alternatively, this calculation may be made by using the marker-delta function of the instrument.
- i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).
- j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “-xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.
- k) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

4.3.4 Test Result

Please refer to section 5.3.

4.4 99% Occupied Bandwidth:

4.4.1 Applicable Standard

RSS-Gen Clause 6.7

The occupied bandwidth or the “99% emission bandwidth” is defined as the frequency range between two points, one above and the other below the carrier frequency, within which 99% of the total transmitted power of the fundamental transmitted emission is contained. The occupied bandwidth shall be reported for all equipment in addition to the specified bandwidth required in the applicable RSSs. In some cases, the “x dB bandwidth” is required, which is defined as the frequency range between two points, one at the lowest frequency below and one at the highest frequency above the carrier frequency, at which the maximum power level of the transmitted emission is attenuated x dB below the maximum in-band power level of the modulated signal, where the two points are on the outskirts of the in-band emission.

The following conditions shall be observed for measuring the occupied bandwidth and x dB bandwidth: The transmitter shall be operated at its maximum carrier power measured under normal test conditions. The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.

The detector of the spectrum analyzer shall be set to “Sample”. However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or “Max Hold”) may be necessary to determine the occupied / x dB bandwidth if the device is not transmitting continuously.


The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / x dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value.

Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.

For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).

4.4.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, which was provided by manufacturer. The insert loss of this RF cable/attenuator was offset into the setting of test equipment.

4.4.3 Test Procedure

According to ANSI C63.10-2013 Section 6.9.3

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW}/\text{RBW})]$ below the reference level. Specific guidance is given in 4.1.5.2.
- d) Step a) through step c) might require iteration to adjust within the specified range.
- e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- h) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

4.4.4 Test Result

Please refer to section 5.4.

4.5 Channel Separation

4.5.1 Applicable Standard


FCC §15.247 (a)(1)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

RSS-247 Clause 5.1 b)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.50 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

4.5.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, which was provided by manufacturer. The insert loss of this RF cable/attenuator was offset into the setting of test equipment.

4.5.3 Test Procedure

According to ANSI C63.10-2013 Section 7.8.2

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: Wide enough to capture the peaks of two adjacent channels.
- b) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- c) Video (or average) bandwidth (VBW) $\geq$ RBW.
- d) Sweep: Auto.
- e) Detector function: Peak.
- f) Trace: Max hold.
- g) Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels. Compliance of an EUT with the appropriate regulatory limit shall be determined. A plot of the data shall be included in the test report.

4.5.4 Test Result

Please refer to section 5.5.

4.6 Number Of Hopping Frequency

4.6.1 Applicable Standard


FCC §15.247 (a)(1)(iii)

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

RSS-247 Clause 5.1 d)

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

4.6.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, which was provided by manufacturer. The insert loss of this RF cable/attenuator was offset into the setting of test equipment.

4.6.3 Test Procedure

According to ANSI C63.10-2013 Section 7.8.3

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- b) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- c) VBW $\geq$ RBW.
- d) Sweep: Auto.
- e) Detector function: Peak.
- f) Trace: Max hold.
- g) Allow the trace to stabilize

It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies. Compliance of an EUT with the appropriate regulatory limit shall be determined for the number of hopping channels. A plot of the data shall be included in the test report.

4.6.4 Test Result

Please refer to section 5.6.

4.7 Time Of Occupancy(Dwell Time)


4.7.1 Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

RSS-247 Clause 5.1 d)

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

4.7.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, which was provided by manufacturer. The insert loss of this RF cable/attenuator was offset into the setting of test equipment.

4.7.3 Test Procedure

According to ANSI C63.10-2013 Section 7.8.4

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: Zero span, centered on a hopping channel.
- b) RBW shall be $\leq$ channel spacing and where possible RBW should be set $\gg 1 / T$, where T is the expected dwell time per channel.
- c) Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
- d) Detector function: Peak.
- e) Trace: Max hold.

Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

Repeat the measurement using a longer sweep time to determine the number of hops over the period specified in the requirements. The sweep time shall be equal to, or less than, the period specified in the requirements. Determine the number of hops over the sweep time and calculate the total number of hops in the period specified in the requirements, using the following equation:

$$\text{(Number of hops in the period specified in the requirements)} = \text{(number of hops on spectrum analyzer)} \times \text{(period specified in the requirements / analyzer sweep time)}$$

The average time of occupancy is calculated from the transmit time per hop multiplied by the number of hops in the period specified in the requirements. If the number of hops in a specific time varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation.

The measured transmit time and time between hops shall be consistent with the values described in the operational description for the EUT.

4.7.4 Test Result

Please refer to section 5.7.

4.8 Maximum Conducted Output Power

4.8.1 Applicable Standard


FCC §15.247 (b)(1)

For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts

According to RSS-247 Clause 5.4 b)

For FHSs operating in the band 2400–2483.5 MHz, the maximum peak conducted output power shall not exceed 1.0 W if the hopset uses 75 or more hopping channels; the maximum peak conducted output power shall not exceed 0.125 W if the hopset uses less than 75 hopping channels. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e).

4.8.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, which was provided by manufacturer. The insert loss of this RF cable/attenuator was offset into the setting of test equipment.

4.8.3 Test Procedure

According to ANSI C63.10-2013 Section 7.8.5

This is an RF-conducted test to evaluate maximum peak output power. Use a direct connection between the antenna port of the unlicensed wireless device and the spectrum analyzer, through suitable attenuation. Offset the Insertion loss of the RF cable, DC Block/ Attenuator into the spectrum analyzer. The hopping shall be disabled for this test:

- a) Use the following spectrum analyzer settings:
 - 1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
 - 2) RBW > 20 dB bandwidth of the emission being measured.
 - 3) VBW $\geq$ RBW.
 - 4) Sweep: Auto.
 - 5) Detector function: Peak.
 - 6) Trace: Max hold.
- b) Allow trace to stabilize.
- c) Use the marker-to-peak function to set the marker to the peak of the emission.
- d) The indicated level is the peak output power, after any corrections for external attenuators and cables.
- e) A plot of the test results and setup description shall be included in the test report.

NOTE—A peak responding power meter may be used, where the power meter and sensor system video bandwidth is greater than the occupied bandwidth of the unlicensed wireless device, rather than a spectrum analyzer.

4.8.4 Test Result

Please refer to section 5.8.

4.9 100 kHz Bandwidth Of Frequency Band Edge

4.9.1 Applicable Standard


FCC §15.247 (d);

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to RSS-247 Clause 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

4.9.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, which was provided by manufacturer. The insert loss of this RF cable/attenuator was offset into the setting of test equipment.

4.9.3 Test Procedure

According to ANSI C63.10-2013 Section 7.8.6

For band-edge measurements, use the band-edge procedure in 6.10. Band-edge measurements shall be tested both on single channels, and with the EUT hopping.

- Set the center frequency and span to encompass frequency range to be measured.
- Set the RBW = 100 kHz.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.

h) Use the peak marker function to determine the maximum amplitude level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements. Report the three highest emissions relative to the limit.

4.9.4 Test Result

Please refer to section 5.9.

4.10 Antenna Requirement

4.10.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

RSS-Gen §6.8

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

4.10.2 Judgment

Compliant. Please refer to the Antenna Information detail in Section 1.3.

5. TEST DATA AND RESULTS

5.1 AC Line Conducted Emissions

Serial Number:	2QUD-1, 2QUD-3, 2QUD-2, 2QUD-4	Test Date:	2024/9/14~2024/9/25
Test Site:	CE	Test Mode:	Transmitting
Tester:	Yukin Qiu	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.9~26.6	Relative Humidity: (%)	58~69	ATM Pressure: (kPa)	99.8~100.5
----------------------	-----------	------------------------------	-------	------------------------	------------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101614	2024/9/5	2025/9/4
MICRO-COAX	Coaxial Cable	C-NJNJ-50	C-0200-01	2024/9/5	2025/9/4
R&S	EMI Test Receiver	ESCI	100035	2024/8/26	2025/8/25
Audix	Test Software	E3	191218 V9	N/A	N/A

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Configuration 1#:

Project No.: 2402W92356E-RF
Port: Line
Test Mode: Transmitting
Note: BDR Middle Channel


Serial No.: 2QUD-1
Tester: Yukin Qiu



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.152	30.65	10.75	41.40	65.91	24.51	QP
2	0.152	20.62	10.75	31.37	55.91	24.54	Average
3	0.177	28.72	10.80	39.52	64.65	25.13	QP
4	0.177	20.35	10.80	31.15	54.65	23.50	Average
5	0.193	27.59	10.84	38.43	63.90	25.47	QP
6	0.193	20.13	10.84	30.97	53.90	22.93	Average
7	0.206	27.31	10.85	38.16	63.35	25.19	QP
8	0.206	20.34	10.85	31.19	53.35	22.16	Average
9	0.372	36.97	10.83	47.80	58.45	10.65	QP
10	0.372	29.73	10.83	40.56	48.45	7.89	Average
11	18.343	23.59	10.86	34.45	60.00	25.55	QP
12	18.343	18.68	10.86	29.54	50.00	20.46	Average

Project No.: 2402W92356E-RF
Port: neutral
Test Mode: Transmitting
Note: BDR Middle Channel

Serial No.: 2QUD-1
Tester: Yukin Qiu



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.154	30.32	10.85	41.17	65.76	24.59	QP
2	0.154	19.42	10.85	30.27	55.76	25.49	Average
3	0.165	29.35	10.85	40.20	65.20	25.00	QP
4	0.165	19.70	10.85	30.55	55.20	24.65	Average
5	0.188	27.27	10.85	38.12	64.14	26.02	QP
6	0.188	19.66	10.85	30.51	54.14	23.63	Average
7	0.333	29.93	10.79	40.72	59.37	18.65	QP
8	0.333	22.64	10.79	33.43	49.37	15.94	Average
9	0.368	36.76	10.77	47.53	58.54	11.01	QP
10	0.368	30.51	10.77	41.28	48.54	7.26	Average
11	18.130	24.19	10.86	35.05	60.00	24.95	QP
12	18.130	19.34	10.86	30.20	50.00	19.80	Average


Spot Check:

Configuration 2#:

Project No.: 2402W92356E-RF
Port: Line
Test Mode: Transmitting
Note: BDR Middle Channel

Serial No.: 2QUD-3
Tester: Yukin Qiu

Date: 2024-09-25




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.156	29.70	10.76	40.46	65.66	25.20	QP
2	0.156	20.73	10.76	31.49	55.66	24.17	Average
3	0.164	29.99	10.78	40.77	65.27	24.50	QP
4	0.164	22.18	10.78	32.96	55.27	22.31	Average
5	0.190	28.81	10.83	39.64	64.03	24.39	QP
6	0.190	22.16	10.83	32.99	54.03	21.04	Average
7	0.370	37.33	10.83	48.16	58.51	10.35	QP
8	0.370	30.31	10.83	41.14	48.51	7.37	Average
9	13.418	28.39	10.83	39.22	60.00	20.78	QP
10	13.418	25.21	10.83	36.04	50.00	13.96	Average
11	21.663	33.37	10.87	44.24	60.00	15.76	QP
12	21.663	27.19	10.87	38.06	50.00	11.94	Average

Project No.: 2402W92356E-RF
Port: neutral
Test Mode: Transmitting
Note: BDR Middle Channel

Serial No.: 2QUD-3
Tester: Yukin Qiu

Date: 2024-09-25




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.154	29.85	10.85	40.70	65.80	25.10	QP
2	0.154	20.04	10.85	30.89	55.80	24.91	Average
3	0.177	27.95	10.85	38.80	64.64	25.84	QP
4	0.177	20.38	10.85	31.23	54.64	23.41	Average
5	0.188	27.72	10.85	38.57	64.11	25.54	QP
6	0.188	20.90	10.85	31.75	54.11	22.36	Average
7	0.198	26.03	10.85	36.88	63.69	26.81	QP
8	0.198	18.71	10.85	29.56	53.69	24.13	Average
9	0.369	37.02	10.77	47.79	58.53	10.74	QP
10	0.369	33.48	10.77	44.25	48.53	4.28	Average
11	19.707	34.72	10.87	45.59	60.00	14.41	QP
12	19.707	27.57	10.87	38.44	50.00	11.56	Average

Configuration 3#:

Project No.: 2402W92356E-RF
Port: Line
Test Mode: Transmitting
Note: BDR Middle Channel

Serial No.: 2QUD-2
Tester: Yukin Qiu




No.	Frequency (MHz)	Reading (dBUV)	Factor (dB)	Result (dBUV)	Limit (dBUV)	Margin (dB)	Detector
1	0.160	30.75	10.77	41.52	65.47	23.95	QP
2	0.160	19.77	10.77	30.54	55.47	24.93	Average
3	0.165	30.01	10.78	40.79	65.22	24.43	QP
4	0.165	20.31	10.78	31.09	55.22	24.13	Average
5	0.176	29.09	10.80	39.89	64.70	24.81	QP
6	0.176	19.60	10.80	30.40	54.70	24.30	Average
7	0.215	26.69	10.85	37.54	63.01	25.47	QP
8	0.215	19.69	10.85	30.54	53.01	22.47	Average
9	0.367	36.99	10.83	47.82	58.56	10.74	QP
10	0.367	30.64	10.83	41.47	48.56	7.09	Average
11	18.140	23.75	10.86	34.61	60.00	25.39	QP
12	18.140	18.86	10.86	29.72	50.00	20.28	Average

Project No.: 2402W92356E-RF
Port: neutral
Test Mode: Transmitting
Note: BDR Middle Channel

Serial No.: 2QUD-2
Tester: Yukin Qiu

Date: 2024-09-14




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.157	37.93	10.85	48.78	65.63	16.85	QP
2	0.157	21.93	10.85	32.78	55.63	22.85	Average
3	0.372	37.10	10.77	47.87	58.47	10.60	QP
4	0.372	31.10	10.77	41.87	48.47	6.60	Average
5	0.643	22.87	10.74	33.61	56.00	22.39	QP
6	0.643	12.87	10.74	23.61	46.00	22.39	Average
7	1.037	20.49	10.85	31.34	56.00	24.66	QP
8	1.037	10.49	10.85	21.34	46.00	24.66	Average
9	3.906	20.78	10.86	31.64	56.00	24.36	QP
10	3.906	10.37	10.86	21.23	46.00	24.77	Average
11	18.225	24.47	10.86	35.33	60.00	24.67	QP
12	18.225	18.47	10.86	29.33	50.00	20.67	Average

Configuration 4#:

Project No.: 2402W92356E-RF
Port: Line
Test Mode: Transmitting
Note: BDR Middle Channel

Serial No.: 2QUD-4
Tester: Yukin Qiu




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.157	29.53	10.76	40.29	65.62	25.33	QP
2	0.157	20.34	10.76	31.10	55.62	24.52	Average
3	0.164	29.15	10.78	39.93	65.25	25.32	QP
4	0.164	20.34	10.78	31.12	55.25	24.13	Average
5	0.180	28.19	10.81	39.00	64.49	25.49	QP
6	0.180	19.56	10.81	30.37	54.49	24.12	Average
7	0.201	27.19	10.85	38.04	63.57	25.53	QP
8	0.201	18.94	10.85	29.79	53.57	23.78	Average
9	0.370	37.35	10.83	48.18	58.50	10.32	QP
10	0.370	31.09	10.83	41.92	48.50	6.58	Average
11	19.707	33.40	10.87	44.27	60.00	15.73	QP
12	19.707	25.74	10.87	36.61	50.00	13.39	Average

Project No.: 2402W92356E-RF
Port: neutral
Test Mode: Transmitting
Note: BDR Middle Channel

Serial No.: 2QUD-4
Tester: Yukin Qiu

Date: 2024-09-25



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.150	29.41	10.85	40.26	65.98	25.72	QP
2	0.150	19.80	10.85	30.65	55.98	25.33	Average
3	0.176	27.75	10.85	38.60	64.69	26.09	QP
4	0.176	18.90	10.85	29.75	54.69	24.94	Average
5	0.189	27.71	10.85	38.56	64.10	25.54	QP
6	0.189	20.67	10.85	31.52	54.10	22.58	Average
7	0.228	25.89	10.83	36.72	62.52	25.80	QP
8	0.228	17.86	10.83	28.69	52.52	23.83	Average
9	0.369	37.00	10.77	47.77	58.52	10.75	QP
10	0.369	31.02	10.77	41.79	48.52	6.73	Average
11	20.258	36.07	10.87	46.94	60.00	13.06	QP
12	20.258	27.64	10.87	38.51	50.00	11.49	Average

5.2 Radiated Spurious Emissions

1) 9kHz - 1GHz

Serial Number:	2QUD-1, 2QUD-3, 2QUD-2, 2QUD-4	Test Date:	2024/9/12~2024/10/24
Test Site:	Chamber A	Test Mode:	Transmitting
Tester:	Jayce Wang, Alan Xie	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.6~27.2	Relative Humidity: (%)	26~35	ATM Pressure: (kPa)	100.9~101.2
----------------------	-----------	---------------------------	-------	---------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
EMCO	Passive Loop Antenna	6512	9706-1206	2023/10/25	2026/10/24
Sunol Sciences	Hybrid Antenna	JB3	A060611-3	2024/1/12	2027/1/11
Wilson	Coaxial Attenuator	859936	F-08-EM014	2024/1/12	2027/1/11
Unknown	Coaxial Cable	C-NJNJ-50	C-0075-01	2024/7/1	2025/6/30
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-01	2024/7/1	2025/6/30
Unknown	Coaxial Cable	C-NJNJ-50	C-1400-01	2024/7/1	2025/6/30
Sonoma	Amplifier	310N	372193	2024/8/16	2025/8/15
R&S	EMI Test Receiver	ESR3	102453	2024/8/26	2025/8/25
Audix	Test Software	E3	191218 V9	N/A	N/A
Sunol Sciences	Hybrid Antenna	JB3	A060611-2	2024/4/16	2027/4/15
Narda	Coaxial Attenuator	757C-6dB	34010	2024/4/16	2027/4/15

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Please refer to the below table and plots.

9kHz~30MHz

Three antenna orientations (parallel, perpendicular, and ground parallel) was measured, the worst orientations was below:

Configuration 1#:

Project No.: 2402W92356E-RF


Serial No.: 2QUD-1

Polarization: Parallel

Tester: Jayce Wang

Test Mode: Transmitting

Note: BDR Middle Channel




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.022	12.20	48.52	60.72	120.71	59.99	Peak
2	0.044	10.29	44.28	54.57	114.66	60.09	Peak
3	0.050	7.05	43.41	50.46	113.60	63.14	Peak
4	0.064	9.31	41.15	50.46	111.48	61.02	Peak
5	0.117	10.80	34.02	44.82	106.21	61.39	Peak
6	0.121	17.17	33.80	50.97	105.93	54.96	Peak

Project No.: 2402W92356E-RF
Polarization: Parallel
Test Mode: Transmitting
Note: BDR Middle Channel

Serial No.: 2QUD-1
Tester: Jayce Wang

Date: 2024-09-12




No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Result (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector
1	0.611	30.53	21.74	52.27	71.85	19.58	Peak
2	4.478	41.99	6.40	48.39	69.54	21.15	Peak
3	4.926	39.69	5.79	45.48	69.54	24.06	Peak
4	13.408	47.71	3.90	51.61	69.54	17.93	Peak
5	14.063	47.21	4.15	51.36	69.54	18.18	Peak
6	18.426	49.26	3.62	52.88	69.54	16.66	Peak

Spot Check:
Configuration 2#:

Project No.: 2402W92356E-RF
Polarization: Parallel
Test Mode: Transmitting
Note: BDR Middle Channel

Serial No.: 2QUD-3
Tester: Jayce Wang




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.015	5.10	50.15	55.25	123.81	68.56	Peak
2	0.019	4.84	49.32	54.16	122.15	67.99	Peak
3	0.021	7.61	48.75	56.36	121.11	64.75	Peak
4	0.024	4.84	48.08	52.92	119.97	67.05	Peak
5	0.050	6.68	43.41	50.09	113.60	63.51	Peak
6	0.064	8.44	41.15	49.59	111.48	61.89	Peak

Project No.: 2402W92356E-RF
Polarization: Parallel
Test Mode: Transmitting
Note: BDR Middle Channel

Serial No.: 2QUD-3
Tester: Jayce Wang

Date: 2024-10-24




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	4.384	33.47	6.52	39.99	69.54	29.55	Peak
2	4.797	38.26	5.97	44.23	69.54	25.31	Peak
3	4.952	39.88	5.76	45.64	69.54	23.90	Peak
4	5.221	39.49	5.55	45.04	69.54	24.50	Peak
5	15.885	36.57	3.58	40.15	69.54	29.39	Peak
6	16.750	35.91	3.73	39.64	69.54	29.90	Peak

Configuration 3#:

Project No.: 2402W92356E-RF
Polarization: Parallel
Test Mode: Transmitting
Note: BDR Middle channel

Serial No.: 2QUD-2
Tester: Alan Xie




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.015	7.28	50.15	57.43	123.81	66.38	Peak
2	0.021	7.78	48.75	56.53	121.11	64.58	Peak
3	0.050	6.92	43.41	50.33	113.60	63.27	Peak
4	0.064	9.18	41.15	50.33	111.48	61.15	Peak
5	0.076	6.17	39.12	45.29	110.01	64.72	Peak
6	0.119	14.69	33.94	48.63	106.11	57.48	Peak

Project No.: 2402W92356E-RF
Polarization: Parallel
Test Mode: Transmitting
Note: BDR Middle channel

Serial No.: 2QUD-2
Tester: Alan Xie

Date: 2024-09-12




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.334	22.57	23.14	45.71	97.13	51.42	Peak
2	0.521	19.46	22.49	41.95	73.26	31.31	Peak
3	0.804	18.91	19.60	38.51	69.40	30.89	Peak
4	4.430	37.79	6.46	44.25	69.54	25.29	Peak
5	16.928	44.09	3.77	47.86	69.54	21.68	Peak
6	23.762	30.79	3.76	34.55	69.54	34.99	Peak

Configuration 4#:

Project No.: 2402W92356E-RF
Polarization: Parallel
Test Mode: Transmitting
Note: BDR Middle channel

Serial No.: 2QUD-4
Tester: Alan Xie




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.016	9.36	50.12	59.48	123.73	64.25	Peak
2	0.019	6.88	49.36	56.24	122.22	65.98	Peak
3	0.021	7.68	48.75	56.43	121.11	64.68	Peak
4	0.035	5.89	45.87	51.76	116.77	65.01	Peak
5	0.050	6.51	43.41	49.92	113.60	63.68	Peak
6	0.064	9.64	41.15	50.79	111.48	60.69	Peak

Project No.: 2402W92356E-RF
Polarization: Parallel
Test Mode: Transmitting
Note: BDR Middle channel

Serial No.: 2QUD-4
Tester: Alan Xie

Date: 2024-09-12




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	1.535	25.85	13.22	39.07	63.67	24.60	Peak
2	4.797	37.92	5.97	43.89	69.54	25.65	Peak
3	5.085	39.23	5.64	44.87	69.54	24.67	Peak
4	15.226	35.14	3.66	38.80	69.54	30.74	Peak
5	16.226	38.17	3.61	41.78	69.54	27.76	Peak
6	17.109	35.80	3.77	39.57	69.54	29.97	Peak

30MHz-1GHz

Configuration 1#:

Project No.: 2402W92356E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: BDR Middle Channel

Serial No.: 2QUD-1
Tester: Jayce Wang




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	141.55	46.79	-10.66	36.13	43.50	7.37	Peak
2	192.96	44.67	-11.93	32.74	43.50	10.76	Peak
3	222.06	49.77	-11.08	38.69	46.00	7.31	Peak
4	250.19	48.35	-11.17	37.18	46.00	8.82	Peak
5	296.75	45.34	-9.41	35.93	46.00	10.07	Peak
6	371.44	47.61	-7.82	39.79	46.00	6.21	QP

Project No.: 2402W92356E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: BDR Middle Channel

Serial No.: 2QUD-1
Tester: Jayce Wang

Date: 2024-09-12




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	36.79	44.79	-8.01	36.78	40.00	3.22	QP
2	43.58	47.30	-12.34	34.96	40.00	5.04	QP
3	51.34	52.60	-16.56	36.04	40.00	3.96	QP
4	65.89	50.31	-16.21	34.10	40.00	5.90	QP
5	80.44	51.19	-16.56	34.63	40.00	5.37	QP
6	97.90	51.29	-14.02	37.27	43.50	6.23	Peak
7	371.44	48.41	-7.82	40.59	46.00	5.41	QP

Spot Check:

Configuration 2#:

Project No.: 2402W92356E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: BDR Middle Channel

Serial No.: 2QUD-3
Tester: Jayce Wang




No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Result (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector
1	145.43	46.71	-11.16	35.55	43.50	7.95	Peak
2	222.06	46.77	-10.96	35.81	46.00	10.19	Peak
3	296.75	48.95	-9.41	39.54	46.00	6.46	Peak
4	371.44	46.81	-7.47	39.34	46.00	6.66	Peak
5	389.87	41.03	-6.96	34.07	46.00	11.93	Peak
6	482.99	37.72	-4.63	33.09	46.00	12.91	Peak

Project No.: 2402W92356E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: BDR Middle Channel

Serial No.: 2QUD-3
Tester: Jayce Wang

Date: 2024-10-24




No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Result (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector
1	51.34	49.19	-16.51	32.68	40.00	7.32	QP
2	222.06	48.73	-10.96	37.77	46.00	8.23	Peak
3	296.75	43.94	-9.41	34.53	46.00	11.47	Peak
4	371.44	44.10	-7.47	36.63	46.00	9.37	Peak
5	519.85	38.66	-3.99	34.67	46.00	11.33	Peak
6	531.49	40.62	-3.81	36.81	46.00	9.19	Peak

Configuration 3#:

Project No.: 2402W92356E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: BDR Middle channel


Serial No.: 2QUD-2
Tester: Alan Xie



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	80.44	48.27	-16.56	31.71	40.00	8.29	Peak
2	143.49	46.61	-10.83	35.78	43.50	7.72	Peak
3	194.90	48.95	-11.82	37.13	43.50	6.37	Peak
4	250.19	49.54	-11.17	38.37	46.00	7.63	Peak
5	714.82	38.27	-0.54	37.73	46.00	8.27	Peak
6	800.18	37.96	1.40	39.36	46.00	6.64	Peak

Project No.: 2402W92356E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: BDR Middle channel

Serial No.: 2QUD-2
Tester: Alan Xie




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.00	40.06	-3.51	36.55	40.00	3.45	QP
2	35.82	43.69	-7.35	36.34	40.00	3.66	QP
3	43.58	46.18	-12.34	33.84	40.00	6.16	QP
4	80.44	48.39	-16.56	31.83	40.00	8.17	QP
5	250.19	47.80	-11.17	36.63	46.00	9.37	Peak
6	798.24	37.07	1.35	38.42	46.00	7.58	Peak

Configuration 4#:

Project No.: 2402W92356E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: BDR Middle channel

Serial No.: 2QUD-4
Tester: Alan Xie




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	129.91	43.15	-9.99	33.16	43.50	10.34	Peak
2	259.89	44.22	-10.73	33.49	46.00	12.51	Peak
3	324.88	42.33	-8.43	33.90	46.00	12.10	Peak
4	389.87	45.89	-6.96	38.93	46.00	7.07	Peak
5	631.40	34.45	-1.71	32.74	46.00	13.26	Peak
6	975.75	31.17	4.68	35.85	54.00	18.15	Peak

Project No.: 2402W92356E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: BDR Middle channel

Serial No.: 2QUD-4
Tester: Alan Xie

Date: 2024-09-12



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	146.40	47.64	-11.24	36.40	43.50	7.10	Peak
2	194.90	48.50	-11.77	36.73	43.50	6.77	QP
3	259.89	48.24	-10.73	37.51	46.00	8.49	Peak
4	324.88	44.53	-8.43	36.10	46.00	9.90	Peak
5	975.75	33.76	4.68	38.44	54.00	15.56	Peak
6	999.03	33.37	4.96	38.33	54.00	15.67	Peak

2) 1-25GHz:

Serial Number:	2QUD-6,2QUD-3, 2QUD-8, 2QUD-4	Test Date:	2024/9/11~2024/11/16
Test Site:	Chamber B	Test Mode:	Transmitting
Tester:	Colin Yang, Nat Zhou	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24.4~26.3	Relative Humidity: (%)	46~62	ATM Pressure: (kPa)	100.2~101.2
----------------------	-----------	---------------------------	-------	---------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
ETS-Lindgren	Horn Antenna	3115	000 527 35	2023/9/7	2026/9/6
R&S	Spectrum Analyzer	FSV40	101944	2024/9/6	2025/9/5
Xinhang Macrowave	Coaxial Cable	XH750A-N/J-SMA/J-10M	20231117004 #0001	2023/11/17	2024/11/16
Audix	Test Software	E3	191218 (V9)	N/A	N/A
AH	Preamplifier	PAM-0118P	469	2024/4/15	2025/4/15
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-02 1304	2023/2/22	2026/2/21
AH	Preamplifier	PAM-1840VH	191	2024/9/5	2025/9/4
E-Microwave	Band Rejection Filter	OBSF-2400-2483.5-S	OE01601525	2024/2/21	2025/2/20
Micro-tronics	High Pass Filter	HPM50111	G217	2023/12/1	2024/11/30
Xinhang Macrowave	Coaxial Cable	XH360A-2.92/J-2.92/J-6M-A	20231208001 #0001	2023/12/11	2024/12/10

* Statement of Traceability: Bay Area Compliance Laboratories Corp.(Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

The maximum output power mode was tested.

Configuration 1#:

BDR Mode(GFSK):

Frequency	Reading	Detector	Polar	Factor	Corrected Amplitude	Limit	Margin
MHz	dBμV	PK/QP/AV	H/V	dB/m	dBμV/m	dBμV/m	dB
Low Channel				2402	MHz		
2390.00	28.94	PK	H	28.57	57.51	74.00	16.49
2390.00	17.86	AV	H	28.57	46.43	54.00	7.57
2390.00	29.02	PK	V	28.57	57.59	74.00	16.41
2390.00	17.64	AV	V	28.57	46.21	54.00	7.79
4804.00	49.12	PK	H	-10.12	39.00	74.00	35.00
4804.00	37.62	AV	H	-10.12	27.50	54.00	26.50
4804.00	49.29	PK	V	-10.12	39.17	74.00	34.83
4804.00	37.26	AV	V	-10.12	27.14	54.00	26.86
7206.00	48.62	PK	H	-5.52	43.10	74.00	30.90
7206.00	36.49	AV	H	-5.52	30.97	54.00	23.03
7206.00	48.58	PK	V	-5.52	43.06	74.00	30.94
7206.00	36.73	AV	V	-5.52	31.21	54.00	22.79
Middle Channel				2441	MHz		
4882.00	49.59	PK	H	-10	39.59	74.00	34.41
4882.00	37.38	AV	H	-10	27.38	54.00	26.62
4882.00	49.03	PK	V	-10	39.03	74.00	34.97
4882.00	37.16	AV	V	-10	27.16	54.00	26.84
7323.00	48.76	PK	H	-5.01	43.75	74.00	30.25
7323.00	36.49	AV	H	-5.01	31.48	54.00	22.52
7323.00	49.24	PK	V	-5.01	44.23	74.00	29.77
7323.00	37.58	AV	V	-5.01	32.57	54.00	21.43
High Channel				2480	MHz		
2483.50	28.37	PK	H	28.95	57.32	74.00	16.68
2483.50	17.27	AV	H	28.95	46.22	54.00	7.78
2483.50	29.45	PK	V	28.95	58.40	74.00	15.60
2483.50	17.51	AV	V	28.95	46.46	54.00	7.54
4960.00	49.56	PK	H	-9.98	39.58	74.00	34.42
4960.00	37.62	AV	H	-9.98	27.64	54.00	26.36
4960.00	49.74	PK	V	-9.98	39.76	74.00	34.24
4960.00	37.19	AV	V	-9.98	27.21	54.00	26.79
7440.00	49.21	PK	H	-4.51	44.70	74.00	29.30
7440.00	37.52	AV	H	-4.51	33.01	54.00	20.99
7440.00	50.40	PK	V	-4.51	45.89	74.00	28.11
7440.00	38.16	AV	V	-4.51	33.65	54.00	20.35

Spot Check:

Configuration 2#:

BDR Mode(GFSK):

Frequency	Reading	Detector	Polar	Factor	Corrected Amplitude	Limit	Margin
MHz	dBμV	PK/QP/AV	H/V	dB/m	dBμV/m	dBμV/m	dB
Low Channel				2402	MHz		
2390.00	29.28	PK	H	28.57	57.85	74.00	16.15
2390.00	18.66	AV	H	28.57	47.23	54.00	6.77
2390.00	28.45	PK	V	28.57	57.02	74.00	16.98
2390.00	18.53	AV	V	28.57	47.10	54.00	6.90
4804.00	49.77	PK	H	-10.12	39.65	74.00	34.35
4804.00	39.68	AV	H	-10.12	29.56	54.00	24.44
4804.00	50.33	PK	V	-10.12	40.21	74.00	33.79
4804.00	39.69	AV	V	-10.12	29.57	54.00	24.43
7206.00	50.78	PK	H	-5.52	45.26	74.00	28.74
7206.00	40.26	AV	H	-5.52	34.74	54.00	19.26
7206.00	51.37	PK	V	-5.52	45.85	74.00	28.15
7206.00	40.14	AV	V	-5.52	34.62	54.00	19.38
Middle Channel				2441	MHz		
4882.00	49.79	PK	H	-10	39.79	74.00	34.21
4882.00	39.59	AV	H	-10	29.59	54.00	24.41
4882.00	50.00	PK	V	-10	40.00	74.00	34.00
4882.00	39.67	AV	V	-10	29.67	54.00	24.33
7323.00	50.84	PK	H	-5.01	45.83	74.00	28.17
7323.00	40.12	AV	H	-5.01	35.11	54.00	18.89
7323.00	51.10	PK	V	-5.01	46.09	74.00	27.91
7323.00	40.18	AV	V	-5.01	35.17	54.00	18.83
High Channel				2480	MHz		
2483.50	29.77	PK	H	28.95	58.72	74.00	15.28
2483.50	17.99	AV	H	28.95	46.94	54.00	7.06
2483.50	28.67	PK	V	28.95	57.62	74.00	16.38
2483.50	18.20	AV	V	28.95	47.15	54.00	6.85
4960.00	49.96	PK	H	-9.98	39.98	74.00	34.02
4960.00	39.52	AV	H	-9.98	29.54	54.00	24.46
4960.00	50.09	PK	V	-9.98	40.11	74.00	33.89
4960.00	39.99	AV	V	-9.98	30.01	54.00	23.99
7440.00	50.93	PK	H	-4.51	46.42	74.00	27.58
7440.00	40.19	AV	H	-4.51	35.68	54.00	18.32
7440.00	51.15	PK	V	-4.51	46.64	74.00	27.36
7440.00	40.38	AV	V	-4.51	35.87	54.00	18.13

Configuration 3#:

BDR Mode(GFSK):





Frequency	Reading	Detector	Polar	Factor	Corrected Amplitude	Limit	Margin
MHz	dBμV	PK/QP/AV	H/V	dB/m	dBμV/m	dBμV/m	dB
Low Channel				2402	MHz		
2390.00	29.12	PK	H	28.57	57.69	74.00	16.31
2390.00	17.67	AV	H	28.57	46.24	54.00	7.76
2390.00	28.73	PK	V	28.57	57.30	74.00	16.70
2390.00	17.56	AV	V	28.57	46.13	54.00	7.87
4804.00	49.46	PK	H	-10.12	39.34	74.00	34.66
4804.00	39.35	AV	H	-10.12	29.23	54.00	24.77
4804.00	50.05	PK	V	-10.12	39.93	74.00	34.07
4804.00	39.97	AV	V	-10.12	29.85	54.00	24.15
7206.00	49.16	PK	H	-5.52	43.64	74.00	30.36
7206.00	38.61	AV	H	-5.52	33.09	54.00	20.91
7206.00	49.11	PK	V	-5.52	43.59	74.00	30.41
7206.00	38.54	AV	V	-5.52	33.02	54.00	20.98
Middle Channel				2441	MHz		
4882.00	49.37	PK	H	-10	39.37	74.00	34.63
4882.00	39.23	AV	H	-10	29.23	54.00	24.77
4882.00	50.48	PK	V	-10	40.48	74.00	33.52
4882.00	39.78	AV	V	-10	29.78	54.00	24.22
7323.00	49.36	PK	H	-5.01	44.35	74.00	29.65
7323.00	39.14	AV	H	-5.01	34.13	54.00	19.87
7323.00	49.42	PK	V	-5.01	44.41	74.00	29.59
7323.00	39.21	AV	V	-5.01	34.20	54.00	19.80
High Channel				2480	MHz		
2483.50	28.81	PK	H	28.95	57.76	74.00	16.24
2483.50	17.64	AV	H	28.95	46.59	54.00	7.41
2483.50	29.80	PK	V	28.95	58.75	74.00	15.25
2483.50	17.54	AV	V	28.95	46.49	54.00	7.51
4960.00	49.29	PK	H	-9.98	39.31	74.00	34.69
4960.00	38.43	AV	H	-9.98	28.45	54.00	25.55
4960.00	50.99	PK	V	-9.98	41.01	74.00	32.99
4960.00	40.83	AV	V	-9.98	30.85	54.00	23.15
7440.00	49.54	PK	H	-4.51	45.03	74.00	28.97
7440.00	39.11	AV	H	-4.51	34.60	54.00	19.40
7440.00	49.90	PK	V	-4.51	45.39	74.00	28.61
7440.00	39.64	AV	V	-4.51	35.13	54.00	18.87

Configuration 4#:

BDR Mode(GFSK):

Frequency	Reading	Detector	Polar	Factor	Corrected Amplitude	Limit	Margin
MHz	dBμV	PK/QP/AV	H/V	dB/m	dBμV/m	dBμV/m	dB
Low Channel				2402	MHz		
2390.00	29.05	PK	H	28.57	57.62	74.00	16.38
2390.00	16.45	AV	H	28.57	45.02	54.00	8.98
2390.00	28.16	PK	V	28.57	56.73	74.00	17.27
2390.00	16.29	AV	V	28.57	44.86	54.00	9.14
4804.00	48.25	PK	H	-10.12	38.13	74.00	35.87
4804.00	36.69	AV	H	-10.12	26.57	54.00	27.43
4804.00	48.19	PK	V	-10.12	38.07	74.00	35.93
4804.00	36.53	AV	V	-10.12	26.41	54.00	27.59
7206.00	48.51	PK	H	-5.52	42.99	74.00	31.01
7206.00	37.38	AV	H	-5.52	31.86	54.00	22.14
7206.00	48.22	PK	V	-5.52	42.70	74.00	31.30
7206.00	37.59	AV	V	-5.52	32.07	54.00	21.93
Middle Channel				2441	MHz		
4882.00	48.15	PK	H	-10	38.15	74.00	35.85
4882.00	36.75	AV	H	-10	26.75	54.00	27.25
4882.00	48.62	PK	V	-10	38.62	74.00	35.38
4882.00	36.67	AV	V	-10	26.67	54.00	27.33
7323.00	48.82	PK	H	-5.01	43.81	74.00	30.19
7323.00	37.78	AV	H	-5.01	32.77	54.00	21.23
7323.00	48.01	PK	V	-5.01	43.00	74.00	31.00
7323.00	37.13	AV	V	-5.01	32.12	54.00	21.88
High Channel				2480	MHz		
2483.50	28.20	PK	H	28.95	57.15	74.00	16.85
2483.50	16.22	AV	H	28.95	45.17	54.00	8.83
2483.50	28.97	PK	V	28.95	57.92	74.00	16.08
2483.50	16.63	AV	V	28.95	45.58	54.00	8.42
4960.00	48.84	PK	H	-9.98	38.86	74.00	35.14
4960.00	36.61	AV	H	-9.98	26.63	54.00	27.37
4960.00	48.49	PK	V	-9.98	38.51	74.00	35.49
4960.00	37.18	AV	V	-9.98	27.20	54.00	26.80
7440.00	48.26	PK	H	-4.51	43.75	74.00	30.25
7440.00	37.12	AV	H	-4.51	32.61	54.00	21.39
7440.00	49.11	PK	V	-4.51	44.60	74.00	29.40
7440.00	38.36	AV	V	-4.51	33.85	54.00	20.15

Worst Channel Test plots:
Configuration 1#:
1-18GHz:

BDR, High Channel, Horizontal**BDR, High Channel, Vertical**

18-25GHz:


No Emission was detected in the range 18-25GHz, test was performed on the mode and channel which with the maximum power.

BDR, Middle Channel, Horizontal

Project No.: 2402W92356E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: BDR middle channel 2441MHz

Serial No.: 20UD-6
Tester: Colin Yang

Date: 2024-09-12




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	24949.60	43.89	9.55	53.44	74.00	20.56	Peak
2	24949.60	32.35	9.55	41.90	54.00	12.10	Average

BDR, Middle Channel, Vertical





Project No.: 2402W92356E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: BDR middle channel 2441MHz

Serial No.: 20UD-6
Tester: Colin Yang

Date: 2024-09-12



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	24853.00	44.03	9.44	53.47	74.00	20.53	Peak
2	24853.00	32.64	9.44	42.08	54.00	11.92	Average

Bandedge:**BDR, Low Channel, Bandedge, Horizontal****BDR, Low Channel, Bandedge, Vertical****BDR, High Channel, Bandedge, Horizontal****BDR, High Channel, Bandedge, Vertical**

5.3 20 dB Emission Bandwidth

Test Information:

Serial No.:	2QUD-5	Test Date:	2024/09/20
Test Site:	RF	Test Mode:	Transmitting
Tester:	Roy Xiao	Test Result:	/

Environmental Conditions:

Temperature: (°C):	26	Relative Humidity: (%)	41	ATM Pressure: (kPa)	100.2
-----------------------	----	------------------------------	----	------------------------	-------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Narda	Coaxial Attenuator	773-10	F-08-EM511	2024/06/07	2025/06/06
R&S	Spectrum Analyzer	FSV40	101589	2024/09/05	2025/09/04

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:


Mode	Channel	Result (MHz)
DH1	Low	0.778
	Middle	0.775
	High	0.778
2DH1	Low	1.216
	Middle	1.213
	High	1.216
3DH1	Low	1.219
	Middle	1.219
	High	1.222

DH1_Low




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 00:13:06

DH1_Middle




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 21:04:11

DH1_High




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 21:07:16

2DH1_Low




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 21:13:36

2DH1_Middle




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 21:16:59

2DH1_High




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 21:19:26

3DH1_Low




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 21:23:34

3DH1_Middle



ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 21:27:03

3DH1_High



ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 21:29:59

5.4 99% Occupied Bandwidth

Test Information:

Serial No.:	2QUD-5	Test Date:	2024/09/20
Test Site:	RF	Test Mode:	Transmitting
Tester:	Roy Xiao	Test Result:	/

Environmental Conditions:

Temperature: (°C):	26	Relative Humidity: (%)	41	ATM Pressure: (kPa)	100.2
-----------------------	----	------------------------------	----	------------------------	-------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Narda	Coaxial Attenuator	773-10	F-08-EM511	2024/06/07	2025/06/06
R&S	Spectrum Analyzer	FSV40	101589	2024/09/05	2025/09/04

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:


Mode	Channel	99% OBW (MHz)
DH1	Low	0.720
	Middle	0.723
	High	0.723
2DH1	Low	1.134
	Middle	1.134
	High	1.137
3DH1	Low	1.125
	Middle	1.125
	High	1.125

DH1_Low




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 00:14:10

DH1_Middle




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 21:04:21

DH1_High




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 21:09:06

2DH1_Low




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 21:14:36

2DH1_Middle




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 21:17:10

2DH1_High



ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 21:20:16


3DH1_Low



ProjectNo.:2402W92356E-RF Tester:Roy Xiao

Date: 20.5EP.2024 21:24:34


3DH1_Middle



ProjectNo.:2402W92356E-RF Tester:Roy Xiao

Date: 20.5EP.2024 21:27:15

3DH1_High



ProjectNo.:2402W92356E-RF Tester:Roy Xiao

Date: 20.5EP.2024 21:30:52

5.5 Channel Separation

Test Information:

Serial No.:	2QUD-5	Test Date:	2024/11/12
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jeff Wei	Test Result:	Pass

Environmental Conditions:

Temperature: (°C):	26.8	Relative Humidity: (%)	44	ATM Pressure: (kPa)	100.5
-----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Coaxial Attenuator	10dB	F-08-EM512	2024/06/13	2025/06/12
R&S	Spectrum Analyzer	FSV40	101589	2024/09/05	2025/09/04

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data:

Mode	Channel	Result (MHz)	Limit (MHz)	Verdict
DH1	Low	1.001	0.815	Pass
	Middle	1.001	0.815	Pass
	High	1.004	0.815	Pass

Note:


1. Only GFSK mode result is reported since EDR ($\pi/4$ -DQPSK, 8DPSK) has the exact same channel plan.
2. The limit is maximum 20dB bandwidth*2/3.

DH1_Low




ProjectNo.:2402W92356E-RF Tester:Jeff Wei
Date: 12.NOV.2024 21:22:48

DH1_Middle



ProjectNo.:2402W92356E-RF Tester:Jeff Wei
Date: 12.NOV.2024 21:36:23

DH1_High



ProjectNo.:2402W92356E-RF Tester:Jeff Wei
Date: 12.NOV.2024 21:25:13

5.6 Number of Hopping Frequency

Test Information:

Serial No.:	2QUD-5	Test Date:	2024/09/20
Test Site:	RF	Test Mode:	Transmitting
Tester:	Roy Xiao	Test Result:	Pass

Environmental Conditions:

Temperature: (°C):	26	Relative Humidity: (%)	41	ATM Pressure: (kPa)	100.2
-------------------------------	----	---------------------------------------	----	--------------------------------	-------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Narda	Coaxial Attenuator	773-10	F-08-EM511	2024/06/07	2025/06/06
R&S	Spectrum Analyzer	FSV40	101589	2024/09/05	2025/09/04

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:


Mode	Channel	Result	Limit	Verdict
DH1	Hopping	79	15	Pass
2DH1	Hopping	79	15	Pass
3DH1	Hopping	79	15	Pass

DH1_Hopping




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 21:41:55

2DH1_Hopping



ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 21:45:42

3DH1_Hopping



ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 21:54:54

5.7 Time of Occupancy (dwell time)**Test Information:**

Serial No.:	2QUD-5	Test Date:	2024/09/20
Test Site:	RF	Test Mode:	Transmitting
Tester:	Roy Xiao	Test Result:	Pass

Environmental Conditions:

Temperature: (°C):	26	Relative Humidity: (%)	41	ATM Pressure: (kPa)	100.2
-------------------------------	----	---------------------------------------	----	--------------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Narda	Coaxial Attenuator	773-10	F-08-EM511	2024/06/07	2025/06/06
R&S	Spectrum Analyzer	FSV40	101589	2024/09/05	2025/09/04

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data:

Mode	Channel	Pulse width (ms)	Dwell time (s)	Limit (s)	Verdict
DH1	Hopping	0.390	0.125	0.400	Pass
DH3	Hopping	1.649	0.264	0.400	Pass
DH5	Hopping	2.908	0.310	0.400	Pass
2DH1	Hopping	0.390	0.125	0.400	Pass
2DH3	Hopping	1.652	0.264	0.400	Pass
2DH5	Hopping	2.908	0.310	0.400	Pass
3DH1	Hopping	0.395	0.126	0.400	Pass
3DH3	Hopping	1.655	0.265	0.400	Pass
3DH5	Hopping	2.908	0.310	0.400	Pass

Note:


DH1:Dwell time=Pulse width (ms) × (1600/2/79) ×31.6 s
DH3:Dwell time=Pulse width (ms) × (1600/4/79) ×31.6 s
DH5:Dwell time=Pulse width (ms) × (1600/6/79) ×31.6 s
2DH1: Dwell time=Pulse width (ms) × (1600/2/79) ×31.6 s
2DH3: Dwell time=Pulse width (ms) × (1600/4/79) ×31.6 s
2DH5: Dwell time=Pulse width (ms) × (1600/6/79) ×31.6 s
3DH1: Dwell time=Pulse width (ms) × (1600/2/79) ×31.6 s
3DH3: Dwell time=Pulse width (ms) × (1600/4/79) ×31.6 s
3DH5: Dwell time=Pulse width (ms) × (1600/6/79) ×31.6 s

DH3_Hopping




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 21:59:40

2DH1_Hopping




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 22:25:58

2DH5_Hopping




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 22:36:55

3DH1_Hopping




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.5EP.2024 22:14:42

3DH3_Hopping



ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.5EP.2024 22:44:21

3DH5_Hopping



ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.5EP.2024 22:53:31

5.8 Maximum Conducted Output Power

Test Information:

Serial No.:	2QUD-5, 2QUD-10, 2QUD-7, 2QUD-9	Test Date:	2024/09/20~2024/12/19
Test Site:	RF	Test Mode:	Transmitting
Tester:	Roy Xiao, ,Jojo Zhou, Jeff Wei, Tower Qing	Test Result:	Pass

Environmental Conditions:

Temperature: (°C):	20.8~26	Relative Humidity: (%)	33~52	ATM Pressure: (kPa)	100.2~102.5
-----------------------	---------	------------------------------	-------	------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Narda	Coaxial Attenuator	773-10	F-08- EM511	2024/06/07	2025/06/06
R&S	Spectrum Analyzer	FSV40	101589	2024/09/05	2025/09/04
R&S	Coaxial Attenuator	10dB	F-08- EM512	2024/6/13	2025/6/12
R&S	Spectrum Analyzer	FSV40	101461	2024/9/5	2025/9/4
Eastsheep	Coaxial Attenuator	5W-N-JK- 6G-10dB	F-08- EM503	2024/6/7	2025/6/6

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Configuration 1#:

Mode	Channel	Result (dBm)	Limit (dBm)	Verdict
DH1	Low	5.54	21.00	Pass
	Middle	6.71	21.00	Pass
	High	5.63	21.00	Pass
2DH1	Low	4.45	21.00	Pass
	Middle	5.90	21.00	Pass
	High	4.92	21.00	Pass
3DH1	Low	4.56	21.00	Pass
	Middle	6.02	21.00	Pass
	High	5.02	21.00	Pass
Max.EIRP		7.61	36.00	Pass

Spot Check:

Configuration 2#:

Mode	Channel	Result (dBm)	Limit (dBm)	Verdict
DH1	Low	4.95	21.00	Pass
	Middle	6.48	21.00	Pass
	High	5.45	21.00	Pass
2DH1	Low	4.24	21.00	Pass
	Middle	5.69	21.00	Pass
	High	4.77	21.00	Pass
3DH1	Low	4.36	21.00	Pass
	Middle	5.79	21.00	Pass
	High	4.87	21.00	Pass
Max.EIRP		7.38	36.00	Pass

Configuration 3#:

Mode	Channel	Result (dBm)	Limit (dBm)	Verdict
DH1	Low	5.35	21.00	Pass
	Middle	6.68	21.00	Pass
	High	5.28	21.00	Pass
2DH1	Low	4.03	21.00	Pass
	Middle	5.67	21.00	Pass
	High	4.7	21.00	Pass
3DH1	Low	4.13	21.00	Pass
	Middle	5.84	21.00	Pass
	High	4.96	21.00	Pass
Max.EIRP		7.58	36.00	Pass

Configuration 4#:


Mode	Channel	Result (dBm)	Limit (dBm)	Verdict
DH1	Low	5.35	21.00	Pass
	Middle	6.64	21.00	Pass
	High	5.49	21.00	Pass
2DH1	Low	4.13	21.00	Pass
	Middle	5.67	21.00	Pass
	High	4.85	21.00	Pass
3DH1	Low	4.47	21.00	Pass
	Middle	5.95	21.00	Pass
	High	4.82	21.00	Pass
Max.EIRP		7.54	36.00	Pass

Note:

The test data of the two models are almost the same.


Configuration 1#:

DH1_Low




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 00:27:32

DH1_Middle




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 21:04:46

DH1_High




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 21:08:36

2DH1_Low




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 21:15:05

2DH1_Middle




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 21:17:42

2DH1_High




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 21:20:32

3DH1_Low




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.5EP.2024 21:29:06

3DH1_Middle



ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.5EP.2024 21:27:33


3DH1_High




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.5EP.2024 21:31:22

Configuration 2#:


DH1_Low




DH1_Middle




DH1_High




2DH1_Low




2DH1_Middle



2DH1_High




3DH1_Low




ProjectNo.:2402W92356E Testor:Jeff Wei
Date: 13.NOV.2024 14:54:02

3DH1_Middle



ProjectNo.:2402W92356E Testor:Jeff Wei
Date: 13.NOV.2024 14:44:46


3DH1_High



ProjectNo.:2402W92356E Testor:Jeff Wei
Date: 13.NOV.2024 14:41:13


Configuration 3#:

DH1_Low




ProjectNo.:2402W92356E-RF Tester:Jojo Zhou
Date: 11.DEC.2024 10:20:57

DH1_Middle




ProjectNo.:2402W92356E-RF Tester:Jojo Zhou
Date: 11.DEC.2024 10:27:14

DH1_High




ProjectNo.:2402W92356E-RF Tester:Tower Qing
Date: 19.DEC.2024 17:35:07

2DH1_Low




ProjectNo.:2402W92356E-RF Tester:Tower Qing
Date: 19.DEC.2024 17:42:02

2DH1_Middle




ProjectNo.:2402W92356E-RF Tester:Tower Qing
Date: 19.DEC.2024 17:45:43

2DH1_High




ProjectNo.:2402W92356E-RF Tester:Tower Qing
Date: 19.DEC.2024 17:46:53

3DH1_Low




ProjectNo.:2402W92356 Tester:Tower Qing
Date: 19.DEC.2024 17:50:59

3DH1_Middle



ProjectNo.:2402W92356 Tester:Tower Qing
Date: 19.DEC.2024 17:52:52


3DH1_High



ProjectNo.:2402W92356 Tester:Tower Qing
Date: 19.DEC.2024 17:53:37


Configuration 4#:

DH1_Low




ProjectNo.:2402W92356E-RF Tester:Jojo Zhou
Date: 11.DEC.2024 11:34:02

DH1_Middle




ProjectNo.:2402W92356E-RF Tester:Jojo Zhou
Date: 11.DEC.2024 11:36:53

DH1_High




ProjectNo.:2402W92356E-RF Tester:Tower Qing
Date: 19.DEC.2024 17:58:13

2DH1_Low




ProjectNo.:2402W92356E-RF Tester:Tower Qing
Date: 19.DEC.2024 18:01:34

2DH1_Middle




ProjectNo.:2402W92356E-RF Tester:Tower Qing
Date: 19.DEC.2024 18:02:28

2DH1_High




ProjectNo.:2402W92356E-RF Tester:Tower Qing
Date: 19.DEC.2024 18:03:23

3DH1_Low




ProjectNo.:2402W92356 Tester:Tower Qing
Date: 19.DEC.2024 18:06:24

3DH1_Middle



ProjectNo.:2402W92356 Tester:Tower Qing
Date: 19.DEC.2024 18:07:19

3DH1_High



ProjectNo.:2402W92356 Tester:Tower Qing
Date: 19.DEC.2024 18:09:14

5.9 100 kHz Bandwidth of Frequency Band Edge**Test Information:**

Serial No.:	2QUD-5	Test Date:	2024/09/20
Test Site:	RF	Test Mode:	Transmitting
Tester:	Roy Xiao	Test Result:	Pass

Environmental Conditions:

Temperature: (°C):	26	Relative Humidity: (%)	41	ATM Pressure: (kPa)	100.2
-------------------------------	----	---------------------------------------	----	--------------------------------	-------


Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Narda	Coaxial Attenuator	773-10	F-08-EM511	2024/06/07	2025/06/06
R&S	Spectrum Analyzer	FSV40	101589	2024/09/05	2025/09/04

** Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*


Test Data:

DH1_Low




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 00:13:56

DH1_High




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 21:07:54

DH1_Hopping_Lower




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 21:37:58

DH1_Hopping_Upper




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 21:40:17

2DH1_Low




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 21:14:24

2DH1_High




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 21:20:06

2DH1_Hopping_Lower




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 21:43:30

2DH1_Hopping_Upper




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 21:44:23

3DH1_Low




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 21:24:21

3DH1_High




ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 21:30:39

3DH1_Hopping_Lower



ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 21:47:40

3DH1_Hopping_Upper



ProjectNo.:2402W92356E-RF Tester:Roy Xiao
Date: 20.SEP.2024 21:48:26

EXHIBIT A - EUT PHOTOGRAPHS

Please refer to the attachment 2402W92356E-RF-EXP EUT EXTERNAL PHOTOGRAPHS and 2402W92356E-RF-INP EUT INTERNAL PHOTOGRAPHS.

EXHIBIT B - TEST SETUP PHOTOGRAPHS

Please refer to the attachment 2402W92356E-RF-00A-TSP TEST SETUP PHOTOGRAPHS.

******* END OF REPORT *******