

TEST REPORT

Applicant: FCC: INGENICO
IC: Ingenico
FCC: 9 Avenue de la gare - Rovaltain TGV, BP25156, Valence Cedex
Address: 9,26958 ,France
IC: 9 avenue de la gare Rovaltain TGV, Valence 26958, France

Product Name: Payment Terminals

FCC ID: XKB-SXXCLWIBT

IC: 2586D-SXXCLWIBT

HVIN: AXIUM SX7000 CL/Eth/4G/WiFi/BT,
AXIUM SX5000 CL/Eth/4G/WiFi/BT,
AXIUM SX7000 CL/Eth/WiFi/BT, AXIUM SX5000 CL/Eth/WiFi/BT
47 CFR Part 15, Subpart C(15.225)
Standard(s): ANSI C63.10-2013
RSS-210 Issue 11, June 25, 2024
RSS-Gen, Issue 5, February 2021 Amendment 2

Report Number: 2402W92356E-RF-00F

Report Date: 2025/1/15

The above device has been tested and found compliant with the requirement of the relative standards by Bay Area Compliance Laboratories Corp. (Dongguan).



Reviewed By: Pedro Yun
Title: **Project Engineer**



Approved By: Ivan Cao
Title: **EMC Manager**

Bay Area Compliance Laboratories Corp. (Dongguan)
No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China

Tel: +86-769-86858888

Fax: +86-769-86858891

www.baclcorp.com.cn

Note: The information marked ▲ is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report cannot be reproduced except in full, without prior written approval of the Company. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0. This report may contain data that are not covered by the accreditation scope and shall be marked with ★ This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government. Each test item follows the test standard(s) without deviation.

CONTENTS

DOCUMENT REVISION HISTORY	4
1. GENERAL INFORMATION	5
1.1 GENERAL DESCRIPTION OF EQUIPMENT UNDER TEST	5
1.2 ACCESSORY INFORMATION	5
1.3 ANTENNA INFORMATION DETAIL▲	5
1.4 EQUIPMENT MODIFICATIONS	5
2. SUMMARY OF TEST RESULTS	6
3. DESCRIPTION OF TEST CONFIGURATION	7
3.1 EUT OPERATION CONDITION	7
3.2 EUT EXERCISE SOFTWARE	7
3.3 SUPPORT EQUIPMENT LIST AND DETAILS	7
3.4 SUPPORT CABLE LIST AND DETAILS	7
3.5 BLOCK DIAGRAM OF TEST SETUP	8
3.6 TEST FACILITY	11
3.7 MEASUREMENT UNCERTAINTY	11
4. REQUIREMENTS AND TEST RESULTS	12
4.1 AC LINE CONDUCTED EMISSIONS	12
4.1.1 Applicable Standard	12
4.1.2 EUT Setup	14
4.1.3 EMI Test Receiver Setup	14
4.1.4 Test Procedure	15
4.1.5 Corrected Amplitude & Margin Calculation	15
4.1.6 Test Data	16
4.2 RADIATED SPURIOUS EMISSIONS	25
4.2.1 Applicable Standard	25
4.2.2 EUT Setup	25
4.2.3 EMI Test Receiver & Spectrum Analyzer Setup	26
4.2.4 Test Procedure	27
4.2.5 Corrected Result & Margin Calculation	27
4.2.6 Test Data	28
4.3 20 dB EMISSION BANDWIDTH	81
4.3.1 Applicable Standard	81
4.3.2 EUT Setup	81
4.3.3 Test Procedure	81
4.3.4 Test Data	83
4.3 99% OCCUPIED BANDWIDTH:	84
4.3.1 Applicable Standard	84
4.3.2 EUT Setup	85
4.3.3 Test Procedure	85
4.3.4 Test Data And Result	86
4.5 FREQUENCY STABILITY	87

4.5.1 Applicable Standard	87
4.5.2 EUT Setup	87
4.5.3 Test Procedure	87
4.5.4 Test Result	89
4.6 ANTENNA REQUIREMENT	90
4.6.1 Applicable Standard	90
4.6.2 Judgment	90
EXHIBIT A - EUT PHOTOGRAPHS	91
EXHIBIT B - TEST SETUP PHOTOGRAPHS	92

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	2402W92356E-RF-00F	Original Report	2025/1/15

1. GENERAL INFORMATION

1.1 General Description of Equipment under Test

EUT Name:	Payment Terminals
EUT Model:	AXIUM SX7000
Multiple Model:	AXIUM SX5000
Operation Frequency:	13.56 MHz
Modulation Type:	ASK
Rated Input Voltage:	DC 9V-45V
Serial Number:	For RF Test: 2QUD-5 (Configuration 1#) For AC line conducted emissions and Radiated Spurious Emissions Below 1G Tests: 2QUD-1 (Configuration 1#) 2QUD-3 (Configuration 2#) 2QUD-2 (Configuration 3#) 2QUD-4 (Configuration 4#)
EUT Received Date:	2024/8/29
EUT Received Status:	Good
Note: The multiple models are electrically identical with the test model. Please refer to the declaration letter for more detail, which was provided by manufacturer.	

Configurations:

Configuration	HVIN	Configuration Description
1#	AXIUM SX7000 CL/Eth/4G/WiFi/BT	With Smartcard reader, With LTE.
2#	AXIUM SX5000 CL/Eth/4G/WiFi/BT	Without Smartcard reader, With LTE.
3#	AXIUM SX7000 CL/Eth/WiFi/BT	With Smartcard reader, Without LTE.
4#	AXIUM SX5000 CL/Eth/WiFi/BT	Without Smartcard reader, Without LTE.

1.2 Accessory Information

Accessory Description	Manufacturer	Model	Parameters
/	/	/	/

1.3 Antenna Information Detail ▲

Antenna Manufacturer	Antenna Type	input impedance (Ohm)	Frequency Range	Antenna Gain
Ingenico	Loop	50	13.56MHz	Unknown
The design of compliance with §15.203:				
☒ Unit uses a permanently attached antenna.				
☐ Unit uses a unique coupling to the intentional radiator.				
☐ Unit was professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.				

1.4 Equipment Modifications

No modifications are made to the EUT during all test items.

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC§15.207 (a) RSS-Gen Clause 8.8	AC Line Conducted Emissions	Compliant
§15.225 §15.209; §15.205 RSS-Gen Clause 8.9 RSS-210 Annex B.6 (a)	Radiated Spurious Emissions	Compliant
§15.225(e) RSS-210 Annex B.6 (b)	Frequency Stability	Compliant
§15.215(c)	20 dB Bandwidth	Compliant
RSS-Gen Clause 6.7	99% Occupied Bandwidth	Compliant
FCC§15.203 RSS-Gen Clause 6.8	Antenna Requirement	Compliant

3. DESCRIPTION OF TEST CONFIGURATION

3.1 EUT Operation Condition

The system was configured for testing in Engineering Mode, which was provided by the manufacturer.

3.2 EUT Exercise Software

Software “Authenticate Test.apk” was used during test.


3.3 Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
ZIONCOM	Router	MB-R210-00	R16Y06M271022
Lenovo	Laptop 1	G510	EMZBPC21103006
Lenovo	Laptop 2	E450	PF-OMRADG
DELL	Monitor	P2721Q	CN-0XJ46C-FCC00-135-A97L-A03
Adam	LTE Antenna 1	Unknown	SXANTENNA1
Adam	LTE Antenna 2	Unknown	SXANTENNA2
Unknown	I/O Load	Unknown	I/O Load-SX7000
Unknown	RJ11 Load	Unknown	RJ11 Load-SX7000
SANDisk	U-Disk	16G	BL201026115 B
Phihong	Adapter(12V)	PSM36W-120L6IN	192050627
CLC	Earphone	Blackview5.0	EMZBEP21103001W
Unknown	NFC Card	EINOLDA	EMZBNC21103001
Unknown	Antenna	Unknown	Unknown
R&S	Wideband Radio Communication Tester	CMW500	149216


3.4 Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
DC Cable	No	No	1	Adapter(12V)	EUT
RJ45 Cable	No	No	10	Router	EUT
DC Cable	No	No	2	I/O Load	EUT
RJ11 Cable	No	No	3	RJ11 Load	EUT
USB Cable	No	No	1	Laptop	EUT
HDMI Cable	Yes	No	1.2	Monitor	EUT
Earphone	No	No	0.8	Earphone	EUT
Signal cable	No	No	1	LTE Antenna 1	EUT
Signal cable	No	No	1	LTE Antenna 2	EUT
Signal Cable	no	no	1.0	Antenna	CMW500


AC power line conducted emissions:
Configuration 1#& Configuration 2#:




Radiated Spurious Emissions:
Configuration 1#& Configuration 2#:



Configuration 3#& Configuration 4#:



5G Wifi&WWAN&NFC transmit simultaneously:



3.6 Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 829273, the FCC Designation No. : CN5044.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

3.7 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	9kHz~30MHz: 3.3dB, 30MHz~200MHz: 4.55 dB, 200MHz~1GHz: 5.92 dB, 1GHz~6GHz: 4.98 dB, 6GHz~18GHz: 5.89 dB, 18GHz~26.5GHz:5.47 dB, 26.5GHz~40GHz:5.63 dB
Unwanted Emissions, conducted	±2.47 dB
Temperature	±1℃
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.11 dB (150 kHz to 30 MHz)

4. REQUIREMENTS AND TEST RESULTS

4.1 AC Line Conducted Emissions

4.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:

(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

RSS-Gen Clause 8.8

Unless stated otherwise in the applicable RSS, for radio apparatus that are designed to be connected to the public utility AC power network, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the range 150 kHz to 30 MHz shall not exceed the limits in table 4, as measured using a 50 μ H / 50 Ω line impedance stabilization network. This requirement applies for the radio frequency voltage measured between each power line and the ground terminal of each AC power-line mains cable of the EUT. For an EUT that connects to the AC power lines indirectly, through another device, the requirement for compliance with the limits in table 4 shall apply at the terminals of the AC power-line mains cable of a representative support device, while it provides power to the EUT. The lower limit applies at the boundary between the frequency ranges. The device used to power the EUT shall be representative of typical applications.

Table 4 – AC power-line conducted emissions limits


Frequency (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 ¹	56 to 46 ¹
0.5 – 5	56	46
5 – 30	60	50

Note 1: The level decreases linearly with the logarithm of the frequency.

For an EUT with a permanent or detachable antenna operating between 150 kHz and 30 MHz, the AC power-line conducted emissions must be measured using the following configurations:

- (a) Perform the AC power-line conducted emissions test with the antenna connected to determine compliance with the limits of table 4 outside the transmitter's fundamental emission band.
- (b) Retest with a dummy load instead of the antenna to determine compliance with the limits of table 4 within the transmitter's fundamental emission band. For a detachable antenna, remove the antenna and connect a suitable dummy load to the antenna connector. For a permanent antenna, remove the antenna and terminate the RF output with a dummy load or network that simulates the antenna in the fundamental frequency band.

4.1.2 EUT Setup



The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207, RSS-Gen limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

4.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

4.1.4 Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

According FCC publication number 174176, for a device with a permanent antenna operating at or below 30 MHz, the measurements done with a suitable dummy load, in lieu of the permanent antenna under the following conditions: (1) perform the AC line conducted tests with the permanent antenna to determine compliance with the Section 15.207 limits outside the transmitter’s fundamental emission band; (2) retest with a dummy load in lieu of the permanent antenna to determine compliance with the Section 15.207 limits within the transmitter’s fundamental emission band.

4.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

4.1.6 Test Data

Serial Number:	2QUD-1,2QUD-3,2QUD-2,2QUD-4	Test Date:	2024/9/14~2024/10/24
Test Site:	CE	Test Mode:	Transmitting
Tester:	Yukin Qiu	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.3~26.6	Relative Humidity: (%)	43~69	ATM Pressure: (kPa)	99.8~101.2
----------------------	-----------	------------------------------	-------	------------------------	------------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101614	2024/9/5	2025/9/4
MICRO-COAX	Coaxial Cable	C-NJNJ-50	C-0200-01	2024/9/5	2025/9/4
R&S	EMI Test Receiver	ESCI	100035	2024/8/26	2025/8/25
Audix	Test Software	E3	191218 V9	N/A	N/A

** Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Configuration 1#:

Project No.: 2402W92356E-RF
Port: Line
Test Mode: Transmitting
Note: NFC

Serial No.: 2QUD-1
Tester: Yukin Qiu




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	0.150	31.63	10.75	42.38	66.00	23.62	QP
2	0.150	21.38	10.75	32.13	56.00	23.87	Average
3	0.165	29.56	10.78	40.34	65.18	24.84	QP
4	0.165	20.39	10.78	31.17	55.18	24.01	Average
5	0.193	26.25	10.84	37.09	63.92	26.83	QP
6	0.193	15.11	10.84	25.95	53.92	27.97	Average
7	0.368	36.62	10.83	47.45	58.55	11.10	QP
8	0.368	29.45	10.83	40.28	48.55	8.27	Average
9	3.792	17.46	10.77	28.23	56.00	27.77	QP
10	3.792	11.13	10.77	21.90	46.00	24.10	Average
11	13.561	45.76	10.83	56.59	60.00	3.41	QP
12	13.561	22.66	10.83	33.49	50.00	16.51	Average

Project No.: 2402W92356E-RF
Port: neutral
Test Mode: Transmitting
Note: NFC

Serial No.: 2QUD-1
Tester: Yukin Qiu

Date: 2024-09-18




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.160	30.22	10.85	41.07	65.45	24.38	QP
2	0.160	19.64	10.85	30.49	55.45	24.96	Average
3	0.164	29.90	10.85	40.75	65.28	24.53	QP
4	0.164	19.57	10.85	30.42	55.28	24.86	Average
5	0.182	27.73	10.85	38.58	64.41	25.83	QP
6	0.182	17.67	10.85	28.52	54.41	25.89	Average
7	0.372	36.12	10.77	46.89	58.46	11.57	QP
8	0.372	29.83	10.77	40.60	48.46	7.86	Average
9	13.561	45.46	10.86	56.32	60.00	3.68	QP
10	13.561	32.30	10.86	43.16	50.00	6.84	Average
11	18.197	24.06	10.86	34.92	60.00	25.08	QP
12	18.197	19.18	10.86	30.04	50.00	19.96	Average

**Spot Check:
Configuration 2#:**

Project No.: 2402W92356E-RF
Port: Line
Test Mode: Transmitting
Note:

Serial No.: 2QUD-3
Tester: Yukin Qiu




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.157	30.93	10.76	41.69	65.63	23.94	QP
2	0.157	19.79	10.76	30.55	55.63	25.08	Average
3	0.174	29.06	10.80	39.86	64.77	24.91	QP
4	0.174	18.50	10.80	29.30	54.77	25.47	Average
5	0.293	24.47	10.82	35.29	60.45	25.16	QP
6	0.293	15.21	10.82	26.03	50.45	24.42	Average
7	0.325	28.68	10.83	39.51	59.57	20.06	QP
8	0.325	23.88	10.83	34.71	49.57	14.86	Average
9	0.370	36.32	10.83	47.15	58.51	11.36	QP
10	0.370	31.90	10.83	42.73	48.51	5.78	Average
11	13.559	40.03	10.83	50.86	60.00	9.14	QP
12	13.559	29.75	10.83	40.58	50.00	9.42	Average

Project No.: 2402W92356E-RF
Port: neutral
Test Mode: Transmitting
Note:

Serial No.: 2QUD-3
Tester: Yukin Qiu

Date: 2024-10-24




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.162	30.72	10.85	41.57	65.37	23.80	QP
2	0.162	20.91	10.85	31.76	55.37	23.61	Average
3	0.187	27.64	10.85	38.49	64.15	25.66	QP
4	0.187	16.89	10.85	27.74	54.15	26.41	Average
5	0.305	26.30	10.79	37.09	60.12	23.03	QP
6	0.305	20.96	10.79	31.75	50.12	18.37	Average
7	0.323	28.67	10.78	39.45	59.62	20.17	QP
8	0.323	23.01	10.78	33.79	49.62	15.83	Average
9	0.366	36.64	10.77	47.41	58.58	11.17	QP
10	0.366	30.99	10.77	41.76	48.58	6.82	Average
11	13.560	39.57	10.86	50.43	60.00	9.57	QP
12	13.560	34.92	10.86	45.78	50.00	4.22	Average

Configuration 3#:

Project No.: 2402W92356E-RF
Port: Line
Test Mode: Transmitting
Note: NFC

Serial No.: 2QUD-2
Tester: Yukin Qiu




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.150	31.96	10.75	42.71	65.98	23.27	QP
2	0.150	20.71	10.75	31.46	55.98	24.52	Average
3	0.159	30.89	10.77	41.66	65.52	23.86	QP
4	0.159	19.65	10.77	30.42	55.52	25.10	Average
5	0.180	28.10	10.81	38.91	64.49	25.58	QP
6	0.180	17.32	10.81	28.13	54.49	26.36	Average
7	0.375	35.95	10.84	46.79	58.38	11.59	QP
8	0.375	29.69	10.84	40.53	48.38	7.85	Average
9	18.246	45.65	10.86	56.51	60.00	3.49	QP
10	18.246	19.79	10.86	30.65	50.00	19.35	Average
11	23.739	24.79	10.87	35.66	60.00	24.34	QP
12	23.739	17.78	10.87	28.65	50.00	21.35	Average

Project No.: 2402W92356E-RF
Port: neutral
Test Mode: Transmitting
Note: NFC

Serial No.: 2QUD-2
Tester: Yukin Qiu

Date: 2024-09-14




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.160	30.35	10.85	41.20	65.47	24.27	QP
2	0.160	20.47	10.85	31.32	55.47	24.15	Average
3	0.178	28.62	10.85	39.47	64.56	25.09	QP
4	0.178	18.53	10.85	29.38	54.56	25.18	Average
5	0.200	26.25	10.85	37.10	63.62	26.52	QP
6	0.200	14.12	10.85	24.97	53.62	28.65	Average
7	0.239	22.58	10.83	33.41	62.14	28.73	QP
8	0.239	12.45	10.83	23.28	52.14	28.86	Average
9	0.366	37.03	10.77	47.80	58.59	10.79	QP
10	0.366	29.57	10.77	40.34	48.59	8.25	Average
11	13.560	43.89	10.86	54.75	60.00	5.25	QP
12	13.560	33.50	10.86	44.36	50.00	5.64	Average

Configuration 4#:

Project No.: 2402W92356E-RF
Port: Line
Test Mode: Transmitting
Note:

Serial No.: 2QUD-4
Tester: Yukin Qiu




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.153	30.20	10.76	40.96	65.85	24.89	QP
2	0.153	19.92	10.76	30.68	55.85	25.17	Average
3	0.187	26.86	10.82	37.68	64.16	26.48	QP
4	0.187	17.60	10.82	28.42	54.16	25.74	Average
5	0.206	24.90	10.85	35.75	63.37	27.62	QP
6	0.206	13.78	10.85	24.63	53.37	28.74	Average
7	0.333	28.93	10.83	39.76	59.38	19.62	QP
8	0.333	22.52	10.83	33.35	49.38	16.03	Average
9	0.369	36.40	10.83	47.23	58.53	11.30	QP
10	0.369	29.18	10.83	40.01	48.53	8.52	Average
11	13.561	43.09	10.83	53.92	60.00	6.08	QP
12	13.561	25.14	10.83	35.97	50.00	14.03	Average

Project No.: 2402W92356E-RF
Port: neutral
Test Mode: Transmitting
Note:

Serial No.: 2QUD-4
Tester: Yukin Qiu

Date: 2024-10-24



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.159	29.76	10.85	40.61	65.54	24.93	QP
2	0.159	20.28	10.85	31.13	55.54	24.41	Average
3	0.182	27.00	10.85	37.85	64.38	26.53	QP
4	0.182	18.19	10.85	29.04	54.38	25.34	Average
5	0.204	25.99	10.85	36.84	63.46	26.62	QP
6	0.204	14.65	10.85	25.50	53.46	27.96	Average
7	0.328	22.10	10.79	32.89	49.49	16.60	Average
8	0.338	28.95	10.78	39.73	59.24	19.51	QP
9	0.369	36.96	10.77	47.73	58.53	10.80	QP
10	0.369	29.43	10.77	40.20	48.53	8.33	Average
11	13.561	37.54	10.86	48.40	60.00	11.60	QP
12	13.561	22.15	10.86	33.01	50.00	16.99	Average

4.2 Radiated Spurious Emissions

4.2.1 Applicable Standard

FCC Part 15.225

- (a) The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.
- (b) Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.
- (c) Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.
- (d) The field strength of any emissions appearing outside of the 13.110–14.010 MHz band shall not exceed the general radiated emission limits in §15.209.


RSS-210 B.6(a)


- (a) the field strength of any emission shall not exceed the following limits:

- (i) 15.848 mV/m (84 dB μ V/m) at 30 m, within the band 13.553-13.567 MHz
- (ii) 334 μ V/m (50.5 dB μ V/m) at 30 m, within the bands 13.410-13.553 MHz and 13.567-13.710 MHz
- (iii) 106 μ V/m (40.5 dB μ V/m) at 30 m, within the bands 13.110-13.410 MHz and 13.710-14.010 MHz
- (iv) RSS-Gen general field strength limits for frequencies outside the band 13.110-14.010 MHz

4.2.2 EUT Setup

9kHz~30MHz:



30MHz~1GHz:

The radiated emission tests were performed in the 3-meter chamber test site, using the setup accordance with the ANSI C63.10-2013.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

For 9kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

4.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9 kHz to 1 GHz.

During the radiated emission test, the EMI test Receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
9 kHz – 150 kHz	200 Hz	1 kHz	200 Hz	QP/AV
150 kHz – 30 MHz	9 kHz	30 kHz	9 kHz	QP/AV
30 MHz – 1000 MHz	100 kHz	300 kHz	/	PK
	/	/	120 kHz	QP

If the maximized peak measured value complies with the limit, then it is unnecessary to perform an QP measurement

4.2.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 9 kHz-1 GHz except 9-90 kHz, 110-490 kHz, employing an average detector.

All emissions under the average limit and under the noise floor have not recorded in the report.

4.2.5 Corrected Result & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = Antenna Factor + Cable Loss - Amplifier Gain

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

The limit of Magnetic field strength for 9 kHz-30MHz in RSS-Gen requirement was converted to E-Filed by add 51,5dB, which was identical with FCC Limits.

4.2.6 Test Data

Serial Number:	2QUD-1, 2QUD-2, 2QUD-3, 2QUD-4	Test Date:	2024/10/10~2025/1/14
Test Site:	Chamber A	Test Mode:	Transmitting
Tester:	Jayce Wang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	21.6~26.4	Relative Humidity: (%)	29~37	ATM Pressure: (kPa)	101.4~101.5
----------------------	-----------	---------------------------	-------	---------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
EMCO	Passive Loop Antenna	6512	9706-1206	2023/10/25	2026/10/24
Sunol Sciences	Hybrid Antenna	JB3	A060611-2	2024/4/16	2027/4/15
Narda	Coaxial Attenuator	757C-6dB	34010	2024/4/16	2027/4/15
Unknown	Coaxial Cable	C-NJNJ-50	C-0075-01	2024/7/1	2025/6/30
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-01	2024/7/1	2025/6/30
Unknown	Coaxial Cable	C-NJNJ-50	C-1400-01	2024/7/1	2025/6/30
Sonoma	Amplifier	310N	372193	2024/8/16	2025/8/15
R&S	EMI Test Receiver	ESR3	102453	2024/8/26	2025/8/25
Audix	Test Software	E3	191218 V9	N/A	N/A
Sinoscite	Band Rejection Filter	BSF824-862MS	1438001	2024/6/7	2025/6/6
R&S	Wideband Radio Communication Tester	CMW500	149216	2024/9/5	2025/9/4

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:


Please refer to the below table and plots.

1) 9kHz~30MHz

Configuration 1#:

Project No.: 2402W92356E-RF
Polarization: Parallel
Test Mode: Transmitting
Note:


Serial No.: 2QUD-1
Tester: Jayce Wang



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.016	4.83	50.12	54.95	123.73	68.78	Peak
2	0.018	4.15	49.40	53.55	122.29	68.74	Peak
3	0.021	3.54	48.69	52.23	120.99	68.76	Peak
4	0.031	1.49	46.51	48.00	117.70	69.70	Peak
5	0.050	2.70	43.41	46.11	113.60	67.49	Peak
6	0.064	4.86	41.15	46.01	111.48	65.47	Peak

Project No.: 2402W92356E-RF
Polarization: Parallel
Test Mode: Transmitting
Note:

Serial No.: 2QUD-1
Tester: Jayce Wang




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	4.797	42.87	5.97	48.84	69.54	20.70	Peak
2	5.031	43.76	5.67	49.43	69.54	20.11	Peak
3	5.194	46.20	5.58	51.78	69.54	17.76	Peak
4	5.390	43.95	5.44	49.39	69.54	20.15	Peak
5	18.232	38.51	3.69	42.20	69.54	27.34	Peak
6	29.371	37.01	3.39	40.40	69.54	29.14	Peak

Project No.: 2402W92356E-RF
Polarization: Parallel
Test Mode: Transmitting
Note:

Serial No.: 2QUD-1
Tester: Jayce Wang

Date: 2024-10-11




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	13.348	54.13	3.88	58.01	80.51	22.50	Peak
2	13.454	55.48	3.93	59.41	90.47	31.06	Peak
3	13.475	54.33	3.94	58.27	90.47	32.20	Peak
4	13.558	70.07	3.98	74.05	124.00	49.95	Peak
5	13.665	54.49	4.03	58.52	90.47	31.95	Peak
6	13.772	52.51	4.07	56.58	80.51	23.93	Peak

Project No.: 2402W92356E-RF
Polarization: Perpendicular
Test Mode: Transmitting
Note:

Serial No.: 2QUD-1
Tester: Jayce Wang

Date: 2024-10-11




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.015	8.90	50.15	59.05	123.81	64.76	Peak
2	0.018	8.35	49.40	57.75	122.29	64.54	Peak
3	0.021	9.26	48.77	58.03	121.17	63.14	Peak
4	0.031	5.62	46.51	52.13	117.70	65.57	Peak
5	0.044	7.54	44.36	51.90	114.77	62.87	Peak
6	0.064	10.49	41.15	51.64	111.48	59.84	Peak

Project No.: 2402W92356E-RF
Polarization: Perpendicular
Test Mode: Transmitting
Note:

Serial No.: 2QUD-1
Tester: Jayce Wang

Date: 2024-10-11




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	4.822	42.50	5.93	48.43	69.54	21.11	Peak
2	5.221	45.54	5.55	51.09	69.54	18.45	Peak
3	5.390	45.22	5.44	50.66	69.54	18.88	Peak
4	7.062	33.02	4.99	38.01	69.54	31.53	Peak
5	17.755	32.09	3.79	35.88	69.54	33.66	Peak
6	27.127	39.41	3.47	42.88	69.54	26.66	Peak

Project No.: 2402W92356E-RF
Polarization: Perpendicular
Test Mode: Transmitting
Note:

Serial No.: 2QUD-1
Tester: Jayce Wang

Date: 2024-10-11




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	13.348	61.13	3.88	65.01	80.51	15.50	Peak
2	13.454	62.12	3.93	66.05	90.47	24.42	Peak
3	13.475	60.83	3.94	64.77	90.47	25.70	Peak
4	13.560	76.23	3.98	80.21	124.00	43.79	Peak
5	13.666	60.12	4.03	64.15	90.47	26.32	Peak
6	13.772	57.55	4.07	61.62	80.51	18.89	Peak

Project No.: 2402W92356E-RF
Polarization: Ground-parallel
Test Mode: Transmitting
Note:

Serial No.: 2QUD-1
Tester: Jayce Wang

Date: 2024-10-11




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.016	8.69	50.12	58.81	123.73	64.92	Peak
2	0.018	8.79	49.47	58.26	122.42	64.16	Peak
3	0.021	9.90	48.75	58.65	121.11	62.46	Peak
4	0.042	7.68	44.65	52.33	115.17	62.84	Peak
5	0.046	7.87	44.04	51.91	114.36	62.45	Peak
6	0.050	7.60	43.41	51.01	113.60	62.59	Peak

Project No.: 2402W92356E-RF
Polarization: Ground-parallel
Test Mode: Transmitting
Note:

Serial No.: 2QUD-1
Tester: Jayce Wang

Date: 2024-10-11




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	5.031	40.04	5.67	45.71	69.54	23.83	Peak
2	5.221	41.33	5.55	46.88	69.54	22.66	Peak
3	7.062	30.73	4.99	35.72	69.54	33.82	Peak
4	16.055	33.44	3.58	37.02	69.54	32.52	Peak
5	27.127	31.98	3.47	35.45	69.54	34.09	Peak
6	29.371	32.75	3.39	36.14	69.54	33.40	Peak

Project No.: 2402W92356E-RF
Polarization: Ground-parallel
Test Mode: Transmitting
Note:

Serial No.: 2QUD-1
Tester: Jayce Wang

Date: 2024-10-11




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	13.348	56.85	3.88	60.73	80.51	19.78	Peak
2	13.454	58.39	3.93	62.32	90.47	28.15	Peak
3	13.477	55.63	3.94	59.57	90.47	30.90	Peak
4	13.560	72.26	3.98	76.24	124.00	47.76	Peak
5	13.666	56.68	4.03	60.71	90.47	29.76	Peak
6	13.772	53.59	4.07	57.66	80.51	22.85	Peak

Spot Check:**Configuration 2#:**

Project No.: 2402W92356E-RF
Polarization: Parallel
Test Mode: Transmitting
Note:

Serial No.: 2QUD-3
Tester: Jayce Wang




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.015	5.18	50.15	55.33	123.81	68.48	Peak
2	0.019	3.53	49.25	52.78	122.02	69.24	Peak
3	0.021	4.00	48.75	52.75	121.11	68.36	Peak
4	0.050	3.16	43.39	46.55	113.57	67.02	Peak
5	0.064	6.28	41.15	47.43	111.48	64.05	Peak
6	0.076	3.32	39.17	42.49	110.04	67.55	Peak

Project No.: 2402W92356E-RF
Polarization: Parallel
Test Mode: Transmitting
Note:

Serial No.: 2QUD-3
Tester: Jayce Wang

Date: 2024-10-10




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	5.005	42.56	5.70	48.26	69.54	21.28	Peak
2	5.249	43.94	5.53	49.47	69.54	20.07	Peak
3	5.390	44.12	5.44	49.56	69.54	19.98	Peak
4	15.226	35.19	3.66	38.85	69.54	30.69	Peak
5	18.328	38.09	3.66	41.75	69.54	27.79	Peak
6	29.371	37.75	3.39	41.14	69.54	28.40	Peak

Project No.: 2402W92356E-RF
Polarization: Parallel
Test Mode: Transmitting
Note:

Serial No.: 2QUD-3
Tester: Jayce Wang


Date: 2024-10-10



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	13.348	52.85	3.88	56.73	80.51	23.78	Peak
2	13.454	54.20	3.93	58.13	90.47	32.34	Peak
3	13.475	53.31	3.94	57.25	90.47	33.22	Peak
4	13.560	74.48	3.98	78.46	124.00	45.54	Peak
5	13.665	53.52	4.03	57.55	90.47	32.92	Peak
6	13.772	51.86	4.07	55.93	80.51	24.58	Peak

Project No.: 2402W92356E-RF
Polarization: Perpendicular
Test Mode: Transmitting
Note:


Serial No.: 2QUD-3
Tester: Jayce Wang



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.016	9.20	50.12	59.32	123.73	64.41	Peak
2	0.018	8.58	49.47	58.05	122.42	64.37	Peak
3	0.021	9.98	48.75	58.73	121.11	62.38	Peak
4	0.042	7.90	44.65	52.55	115.17	62.62	Peak
5	0.047	8.29	43.88	52.17	114.15	61.98	Peak
6	0.064	10.46	41.15	51.61	111.48	59.87	Peak

Project No.: 2402W92356E-RF
Polarization: Perpendicular
Test Mode: Transmitting
Note:

Serial No.: 2QUD-3
Tester: Jayce Wang




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.592	27.28	21.94	49.22	72.13	22.91	Peak
2	0.624	24.68	21.58	46.26	71.66	25.40	Peak
3	5.166	41.32	5.59	46.91	69.54	22.63	Peak
4	5.390	43.21	5.44	48.65	69.54	20.89	Peak
5	27.127	37.59	3.47	41.06	69.54	28.48	Peak
6	29.371	36.21	3.39	39.60	69.54	29.94	Peak

Project No.: 2402W92356E-RF
Polarization: Perpendicular
Test Mode: Transmitting
Note:

Serial No.: 2QUD-3
Tester: Jayce Wang

Date: 2024-10-11




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	13.348	60.10	3.88	63.98	80.51	16.53	Peak
2	13.454	61.56	3.93	65.49	90.47	24.98	Peak
3	13.469	60.05	3.94	63.99	90.47	26.48	Peak
4	13.560	76.53	3.98	80.51	124.00	43.49	Peak
5	13.665	59.95	4.03	63.98	90.47	26.49	Peak
6	13.772	57.15	4.07	61.22	80.51	19.29	Peak

Project No.: 2402W92356E-RF
Polarization: Ground-parallel
Test Mode: Transmitting
Note:

Serial No.: 2QUD-3
Tester: Jayce Wang

Date: 2024-10-11




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.015	7.53	50.15	57.68	123.81	66.13	Peak
2	0.019	6.93	49.29	56.22	122.09	65.87	Peak
3	0.021	7.03	48.72	55.75	121.05	65.30	Peak
4	0.050	6.69	43.41	50.10	113.60	63.50	Peak
5	0.064	9.34	41.15	50.49	111.48	60.99	Peak
6	0.076	6.14	39.17	45.31	110.04	64.73	Peak

Project No.: 2402W92356E-RF
Polarization: Ground-parallel
Test Mode: Transmitting
Note:

Serial No.: 2QUD-3
Tester: Jayce Wang

Date: 2024-10-11




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	4.672	41.32	6.13	47.45	69.54	22.09	Peak
2	4.822	44.47	5.93	50.40	69.54	19.14	Peak
3	4.952	44.09	5.76	49.85	69.54	19.69	Peak
4	5.362	41.75	5.46	47.21	69.54	22.33	Peak
5	16.573	32.58	3.68	36.26	69.54	33.28	Peak
6	29.371	31.61	3.39	35.00	69.54	34.54	Peak

Project No.: 2402W92356E-RF
Polarization: Ground-parallel
Test Mode: Transmitting
Note:

Serial No.: 2QUD-3
Tester: Jayce Wang

Date: 2024-10-11




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	13.348	54.67	3.88	58.55	80.51	21.96	Peak
2	13.454	55.98	3.93	59.91	90.47	30.56	Peak
3	13.468	54.52	3.94	58.46	90.47	32.01	Peak
4	13.560	72.55	3.98	76.53	124.00	47.47	Peak
5	13.665	54.50	4.03	58.53	90.47	31.94	Peak
6	13.772	51.94	4.07	56.01	80.51	24.50	Peak

Configuration 3#

Project No.: 2402W92356E-RF
Polarization: Parallel
Test Mode: Transmitting
Note:

Serial No.: 2QUD-2
Tester: Jayce Wang




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.015	8.14	50.15	58.29	123.81	65.52	Peak
2	0.019	6.42	49.36	55.78	122.22	66.44	Peak
3	0.021	8.77	48.75	57.52	121.11	63.59	Peak
4	0.035	6.40	45.82	52.22	116.70	64.48	Peak
5	0.050	6.76	43.41	50.17	113.60	63.43	Peak
6	0.064	9.59	41.15	50.74	111.48	60.74	Peak

Project No.: 2402W92356E-RF
Polarization: Parallel
Test Mode: Transmitting
Note:

Serial No.: 2QUD-2
Tester: Jayce Wang

Date: 2024-10-10




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	4.797	43.71	5.97	49.68	69.54	19.86	Peak
2	5.031	44.12	5.67	49.79	69.54	19.75	Peak
3	5.362	45.50	5.46	50.96	69.54	18.58	Peak
4	14.213	39.96	4.08	44.04	69.54	25.50	Peak
5	18.328	37.72	3.66	41.38	69.54	28.16	Peak
6	29.371	36.67	3.39	40.06	69.54	29.48	Peak

Project No.: 2402W92356E-RF
Polarization: Parallel
Test Mode: Transmitting
Note:

Serial No.: 2QUD-2
Tester: Jayce Wang


Date: 2024-10-10



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	13.348	53.56	3.88	57.44	80.51	23.07	Peak
2	13.454	54.43	3.93	58.36	90.47	32.11	Peak
3	13.475	53.22	3.94	57.16	90.47	33.31	Peak
4	13.560	69.09	3.98	73.07	124.00	50.93	Peak
5	13.665	52.74	4.03	56.77	90.47	33.70	Peak
6	13.772	50.01	4.07	54.08	80.51	26.43	Peak

Project No.: 2402W92356E-RF
Polarization: Perpendicular
Test Mode: Transmitting
Note:

Serial No.: 2QUD-2
Tester: Jayce Wang




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.015	9.21	50.15	59.36	123.81	64.45	Peak
2	0.019	8.49	49.36	57.85	122.22	64.37	Peak
3	0.021	9.01	48.75	57.76	121.11	63.35	Peak
4	0.050	8.02	43.41	51.43	113.60	62.17	Peak
5	0.064	10.30	41.15	51.45	111.48	60.03	Peak
6	0.076	8.05	39.17	47.22	110.04	62.82	Peak

Project No.: 2402W92356E-RF
Polarization: Perpendicular
Test Mode: Transmitting
Note:

Serial No.: 2QUD-2
Tester: Jayce Wang


Date: 2024-10-11



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	4.797	39.50	5.97	45.47	69.54	24.07	Peak
2	5.362	43.41	5.46	48.87	69.54	20.67	Peak
3	7.062	32.79	4.99	37.78	69.54	31.76	Peak
4	18.328	32.29	3.66	35.95	69.54	33.59	Peak
5	27.127	35.34	3.47	38.81	69.54	30.73	Peak
6	29.371	35.66	3.39	39.05	69.54	30.49	Peak

Project No.: 2402W92356E-RF
Polarization: Perpendicular
Test Mode: Transmitting
Note:

Serial No.: 2QUD-2
Tester: Jayce Wang




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	13.348	61.17	3.88	65.05	80.51	15.46	Peak
2	13.454	61.94	3.93	65.87	90.47	24.60	Peak
3	13.475	60.78	3.94	64.72	90.47	25.75	Peak
4	13.560	76.27	3.98	80.25	124.00	43.75	Peak
5	13.666	59.98	4.03	64.01	90.47	26.46	Peak
6	13.772	57.42	4.07	61.49	80.51	19.02	Peak

Project No.: 2402W92356E-RF
Polarization: Ground-parallel
Test Mode: Transmitting
Note:

Serial No.: 2QUD-2
Tester: Jayce Wang


Date: 2024-10-11



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.016	4.04	50.12	54.16	123.73	69.57	Peak
2	0.021	5.24	48.75	53.99	121.11	67.12	Peak
3	0.031	1.95	46.54	48.49	117.74	69.25	Peak
4	0.050	3.06	43.39	46.45	113.57	67.12	Peak
5	0.064	4.84	41.15	45.99	111.48	65.49	Peak
6	0.076	2.41	39.17	41.58	110.04	68.46	Peak

Project No.: 2402W92356E-RF
Polarization: Ground-parallel
Test Mode: Transmitting
Note:

Serial No.: 2QUD-2
Tester: Jayce Wang




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	4.822	45.14	5.93	51.07	69.54	18.47	Peak
2	5.249	43.07	5.53	48.60	69.54	20.94	Peak
3	8.062	29.47	4.33	33.80	69.54	35.74	Peak
4	16.140	34.09	3.59	37.68	69.54	31.86	Peak
5	18.622	31.26	3.54	34.80	69.54	34.74	Peak
6	29.371	33.06	3.39	36.45	69.54	33.09	Peak

Project No.: 2402W92356E-RF
Polarization: Ground-parallel
Test Mode: Transmitting
Note:

Serial No.: 2QUD-2
Tester: Jayce Wang

Date: 2024-10-11




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	13.348	52.32	3.88	56.20	80.51	24.31	Peak
2	13.454	53.85	3.93	57.78	90.47	32.69	Peak
3	13.469	52.31	3.94	56.25	90.47	34.22	Peak
4	13.560	68.08	3.98	72.06	124.00	51.94	Peak
5	13.666	52.36	4.03	56.39	90.47	34.08	Peak
6	13.772	49.90	4.07	53.97	80.51	26.54	Peak

Configuration 4#:

Project No.: 2402W92356E-RF
Polarization: Parallel
Test Mode: Transmitting
Note:

Serial No.: 2QUD-4
Tester: Jayce Wang




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.016	7.62	50.12	57.74	123.73	65.99	Peak
2	0.021	8.84	48.77	57.61	121.17	63.56	Peak
3	0.023	9.04	48.33	57.37	120.39	63.02	Peak
4	0.043	9.47	44.49	53.96	114.94	60.98	Peak
5	0.047	15.24	43.94	59.18	114.23	55.05	Peak
6	0.064	9.88	41.15	51.03	111.48	60.45	Peak

Project No.: 2402W92356E-RF
Polarization: Parallel
Test Mode: Transmitting
Note:

Serial No.: 2QUD-4
Tester: Jayce Wang

Date: 2024-10-24




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	4.384	42.15	6.52	48.67	69.54	20.87	Peak
2	4.721	44.34	6.07	50.41	69.54	19.13	Peak
3	5.031	48.82	5.67	54.49	69.54	15.05	Peak
4	15.388	36.46	3.65	40.11	69.54	29.43	Peak
5	16.661	35.68	3.70	39.38	69.54	30.16	Peak
6	27.127	31.91	3.47	35.38	69.54	34.16	Peak

Project No.: 2402W92356E-RF
Polarization: Parallel
Test Mode: Transmitting
Note:

Serial No.: 2QUD-4
Tester: Jayce Wang

Date: 2024-10-24




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	13.348	58.16	3.88	62.04	80.51	18.47	Peak
2	13.480	57.03	3.94	60.97	90.47	29.50	Peak
3	13.495	56.81	3.95	60.76	90.47	29.71	Peak
4	13.560	78.00	3.98	81.98	124.00	42.02	Peak
5	13.624	55.98	4.01	59.99	90.47	30.48	Peak
6	13.772	55.91	4.07	59.98	80.51	20.53	Peak

Project No.: 2402W92356E-RF
Polarization: Perpendicular
Test Mode: Transmitting
Note:

Serial No.: 2QUD-4
Tester: Jayce Wang

Date: 2024-10-24




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.013	7.66	50.91	58.57	125.65	67.08	Peak
2	0.017	6.10	49.72	55.82	122.91	67.09	Peak
3	0.019	6.49	49.36	55.85	122.22	66.37	Peak
4	0.050	4.18	43.41	47.59	113.60	66.01	Peak
5	0.064	6.59	41.15	47.74	111.48	63.74	Peak
6	0.076	4.41	39.17	43.58	110.04	66.46	Peak

Project No.: 2402W92356E-RF
Polarization: Perpendicular
Test Mode: Transmitting
Note:

Serial No.: 2QUD-4
Tester: Jayce Wang

Date: 2024-10-24




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	4.672	47.39	6.13	53.52	69.54	16.02	Peak
2	4.822	49.07	5.93	55.00	69.54	14.54	Peak
3	5.221	48.42	5.55	53.97	69.54	15.57	Peak
4	16.312	35.57	3.63	39.20	69.54	30.34	Peak
5	17.849	40.11	3.78	43.89	69.54	25.65	Peak
6	27.127	36.52	3.47	39.99	69.54	29.55	Peak

Project No.: 2402W92356E-RF
Polarization: Perpendicular
Test Mode: Transmitting
Note:

Serial No.: 2QUD-4
Tester: Jayce Wang

Date: 2024-10-24




No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Result (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector
1	13.348	56.37	3.88	60.25	80.51	20.26	Peak
2	13.454	58.19	3.93	62.12	90.47	28.35	Peak
3	13.560	73.63	3.98	77.61	124.00	46.39	Peak
4	13.644	56.96	4.01	60.97	90.47	29.50	Peak
5	13.665	57.89	4.03	61.92	90.47	28.55	Peak
6	13.772	55.97	4.07	60.04	80.51	20.47	Peak

Project No.: 2402W92356E-RF
Polarization: Ground-parallel
Test Mode: Transmitting
Note:

Serial No.: 2QUD-4
Tester: Jayce Wang

Date: 2024-10-25




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.016	7.30	50.12	57.42	123.73	66.31	Peak
2	0.018	6.93	49.40	56.33	122.29	65.96	Peak
3	0.021	8.05	48.75	56.80	121.11	64.31	Peak
4	0.042	7.04	44.59	51.63	115.08	63.45	Peak
5	0.050	7.51	43.39	50.90	113.57	62.67	Peak
6	0.064	10.15	41.15	51.30	111.48	60.18	Peak

Project No.: 2402W92356E-RF
Polarization: Ground-parallel
Test Mode: Transmitting
Note:

Serial No.: 2QUD-4
Tester: Jayce Wang

Date: 2024-10-25




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	4.647	46.89	6.17	53.06	69.54	16.48	Peak
2	4.822	49.82	5.93	55.75	69.54	13.79	Peak
3	4.952	49.57	5.76	55.33	69.54	14.21	Peak
4	5.221	47.73	5.55	53.28	69.54	16.26	Peak
5	16.226	40.85	3.61	44.46	69.54	25.08	Peak
6	18.820	33.35	3.45	36.80	69.54	32.74	Peak

Project No.: 2402W92356E-RF
Polarization: Ground-parallel
Test Mode: Transmitting
Note:

Serial No.: 2QUD-4
Tester: Jayce Wang

Date: 2024-10-25




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	13.348	52.82	3.88	56.70	80.51	23.81	Peak
2	13.458	53.82	3.93	57.75	90.47	32.72	Peak
3	13.468	52.66	3.94	56.60	90.47	33.87	Peak
4	13.560	70.48	3.98	74.46	124.00	49.54	Peak
5	13.666	53.69	4.03	57.72	90.47	32.75	Peak
6	13.772	52.31	4.07	56.38	80.51	24.13	Peak

5G Wifi is transmitted simultaneously with WWAN and NFC (Configuration 1#):
802.11ac80_U-NII-3 middle channel 5775MHz+GSM 850(GPRS) 848.8MHz +NFC was tested:

Project No.: 2402W92356E-RF
Polarization: Parallel
Test Mode: Transmitting
: RBW:300Hz,VBW:1kHz

Serial No.: 2QUD-1
Tester: Jayce Wang




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	0.042	27.90	44.69	72.59	115.23	42.64	Peak
2	0.059	43.08	42.03	85.11	112.24	27.13	Peak
3	0.061	43.32	41.71	85.03	111.95	26.92	Peak
4	0.083	28.05	37.73	65.78	109.19	43.41	Peak
5	0.117	31.69	34.03	65.72	106.23	40.51	Peak
6	0.121	32.11	33.79	65.90	105.92	40.02	Peak

Project No.: 2402W92356E-RF
Polarization: Parallel
Test Mode: Transmitting
: RBW:10kHz,VBW:30kHz

Serial No.: 2QUD-1
Tester: Jayce Wang

Date: 2025-01-14




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.180	35.21	30.38	65.59	102.52	36.93	Peak
2	0.302	30.57	23.26	53.83	98.01	44.18	Peak
3	4.822	39.48	5.93	45.41	69.54	24.13	Peak
4	5.139	39.74	5.61	45.35	69.54	24.19	Peak
5	6.056	41.87	5.04	46.91	69.54	22.63	Peak
6	27.271	43.98	3.49	47.47	69.54	22.07	Peak

Project No.: 2402W92356E-RF
Polarization: Perpendicular
Test Mode: Transmitting
: RBW:300Hz,VBW:1kHz

Serial No.: 2QUD-1
Tester: Jayce Wang

Date: 2025-01-14




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.042	20.58	44.69	65.27	115.23	49.96	Peak
2	0.059	39.91	42.01	81.92	112.22	30.30	Peak
3	0.061	40.19	41.71	81.90	111.95	30.05	Peak
4	0.083	23.98	37.73	61.71	109.19	47.48	Peak
5	0.117	28.88	34.02	62.90	106.21	43.31	Peak
6	0.121	29.08	33.80	62.88	105.93	43.05	Peak

Project No.: 2402W92356E-RF
Polarization: Perpendicular
Test Mode: Transmitting
RBW: 10kHz, VBW: 30kHz

Serial No.: 2QUD-1
Tester: Jayce Wang

Date: 2025-01-14




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.178	30.85	30.50	61.35	102.61	41.26	Peak
2	0.255	25.13	25.95	51.08	99.48	48.40	Peak
3	5.249	46.51	5.53	52.04	69.54	17.50	Peak
4	5.836	47.52	5.15	52.67	69.54	16.87	Peak
5	27.127	40.23	3.47	43.70	69.54	25.84	Peak
6	28.755	40.37	3.47	43.84	69.54	25.70	Peak

Project No.: 2402W92356E-RF
Polarization: Ground-parallel
Test Mode: Transmitting
: RBW:300Hz,VBW:1kHz

Serial No.: 2QUD-1
Tester: Jayce Wang

Date: 2025-01-14




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.042	31.21	44.69	75.90	115.23	39.33	Peak
2	0.059	35.09	42.01	77.10	112.22	35.12	Peak
3	0.061	35.23	41.71	76.94	111.95	35.01	Peak
4	0.083	22.07	37.73	59.80	109.19	49.39	Peak
5	0.118	22.99	34.01	57.00	106.20	49.20	Peak
6	0.121	23.31	33.79	57.10	105.92	48.82	Peak

Project No.: 2402W92356E-RF
Polarization: Ground-parallel
Test Mode: Transmitting
RBW: 10kHz, VBW: 30kHz

Serial No.: 2QUD-1
Tester: Jayce Wang

Date: 2025-01-14




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.177	27.22	30.55	57.77	102.66	44.89	Peak
2	5.139	44.40	5.61	50.01	69.54	19.53	Peak
3	5.305	44.63	5.50	50.13	69.54	19.41	Peak
4	6.186	43.78	5.04	48.82	69.54	20.72	Peak
5	18.328	37.91	3.66	41.57	69.54	27.97	Peak
6	27.271	39.48	3.49	42.97	69.54	26.57	Peak

2) 30MHz-1GHz**Configuration 1#:**

Project No.: 2402W92356E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note:

Serial No.: 2QUD-1
Tester: Jayce Wang




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	46.49	46.20	-14.26	31.94	40.00	8.06	QP
2	138.64	44.78	-10.63	34.15	43.50	9.35	Peak
3	148.34	48.73	-11.40	37.33	43.50	6.17	Peak
4	222.06	47.25	-10.96	36.29	46.00	9.71	Peak
5	371.44	45.08	-7.47	37.61	46.00	8.39	Peak
6	966.05	31.71	4.58	36.29	54.00	17.71	Peak

Project No.: 2402W92356E-RF
Polarization: Vertical
Test Mode: Transmitting
Note:

Serial No.: 2QUD-1
Tester: Jayce Wang

Date: 2024-10-10




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.00	37.10	-3.71	33.39	40.00	6.61	Peak
2	144.46	47.83	-11.09	36.74	43.50	6.76	Peak
3	172.59	45.60	-11.88	33.72	43.50	9.78	Peak
4	222.06	48.67	-10.96	37.71	46.00	8.29	Peak
5	296.75	48.50	-9.41	39.09	46.00	6.91	Peak
6	371.44	46.72	-7.47	39.25	46.00	6.75	Peak

**Spot Check:
Configuration 2#:**

Project No.: 2402W92356E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note:

Serial No.: 2QUD-3
Tester: Jayce Wang




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	142.52	47.55	-10.93	36.62	43.50	6.88	Peak
2	194.90	48.69	-11.77	36.92	43.50	6.58	Peak
3	250.19	48.29	-11.27	37.02	46.00	8.98	Peak
4	259.89	48.97	-10.73	38.24	46.00	7.76	Peak
5	324.88	47.60	-8.43	39.17	46.00	6.83	Peak
6	389.87	46.71	-6.96	39.75	46.00	6.25	Peak

Project No.: 2402W92356E-RF
Polarization: Vertical
Test Mode: Transmitting
Note:

Serial No.: 2QUD-3
Tester: Jayce Wang

Date: 2024-10-10




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	46.49	48.23	-14.26	33.97	40.00	6.03	Peak
2	53.28	50.21	-16.63	33.58	40.00	6.42	QP
3	389.87	45.65	-6.96	38.69	46.00	7.31	Peak
4	484.93	39.97	-4.60	35.37	46.00	10.63	Peak
5	532.46	40.97	-3.79	37.18	46.00	8.82	Peak
6	975.75	31.28	4.68	35.96	54.00	18.04	Peak

Configuration 3#:

Project No.: 2402W92356E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note:

Serial No.: 2QUD-2
Tester: Jayce Wang




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	145.43	47.60	-11.01	36.59	43.50	6.91	Peak
2	176.47	46.33	-12.19	34.14	43.50	9.36	Peak
3	222.06	49.43	-11.08	38.35	46.00	7.65	Peak
4	266.68	45.83	-10.50	35.33	46.00	10.67	Peak
5	296.75	48.37	-9.41	38.96	46.00	7.04	Peak
6	371.44	47.29	-7.82	39.47	46.00	6.53	Peak

Project No.: 2402W92356E-RF
Polarization: Vertical
Test Mode: Transmitting
Note:

Serial No.: 2QUD-2
Tester: Jayce Wang

Date: 2024-10-10




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	39.70	43.80	-10.00	33.80	40.00	6.20	QP
2	148.34	46.81	-11.28	35.53	43.50	7.97	Peak
3	222.06	46.20	-11.08	35.12	46.00	10.88	Peak
4	371.44	42.89	-7.82	35.07	46.00	10.93	Peak
5	484.93	39.74	-4.50	35.24	46.00	10.76	Peak
6	531.49	40.23	-3.90	36.33	46.00	9.67	Peak

Configuration 4#:

Project No.: 2402W92356E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note:

Serial No.: 2QUD-4
Tester: Jayce Wang




No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Result (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector
1	142.52	46.24	-10.93	35.31	43.50	8.19	Peak
2	148.34	46.76	-11.40	35.36	43.50	8.14	Peak
3	222.06	49.93	-10.96	38.97	46.00	7.03	Peak
4	296.75	48.64	-9.41	39.23	46.00	6.77	Peak
5	371.44	46.52	-7.47	39.05	46.00	6.95	Peak
6	389.87	46.95	-6.96	39.99	46.00	6.01	Peak

Project No.: 2402W92356E-RF
Polarization: Vertical
Test Mode: Transmitting
Note:

Serial No.: 2QUD-4
Tester: Jayce Wang

Date: 2024-10-24




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	53.28	47.81	-16.63	31.18	40.00	8.82	QP
2	222.06	51.10	-10.96	40.14	46.00	5.86	QP
3	371.44	47.00	-7.47	39.53	46.00	6.47	Peak
4	389.87	47.30	-6.96	40.34	46.00	5.66	QP
5	519.85	39.45	-3.99	35.46	46.00	10.54	Peak
6	532.46	39.69	-3.79	35.90	46.00	10.10	Peak

5G Wifi is transmitted simultaneously with WWAN and NFC(Configuration 1#):
802.11ac80_U-NII-3 middle channel 5775MHz+GSM 850(GPRS) 848.8MHz+NFC was tested:

Project No.: 2402W92356E-RF
Polarization: Horizontal
Test Mode: Transmitting


Serial No.: 2QUD-1
Tester: Jayce Wang



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	147.37	46.88	-11.19	35.69	43.50	7.81	Peak
2	191.99	46.19	-12.00	34.19	43.50	9.31	Peak
3	206.54	45.36	-11.36	34.00	43.50	9.50	Peak
4	222.06	47.77	-11.08	36.69	46.00	9.31	Peak
5	296.75	47.57	-9.41	38.16	46.00	7.84	Peak
6	372.41	48.51	-7.79	40.72	46.00	5.28	Peak

Project No.: 2402W92356E-RF
Polarization: Vertical
Test Mode: Transmitting
:

Serial No.: 2QUD-1
Tester: Jayce Wang



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	54.25	48.32	-16.62	31.70	40.00	8.30	QP
2	148.34	44.71	-11.28	33.43	43.50	10.07	Peak
3	222.06	49.85	-11.08	38.77	46.00	7.23	Peak
4	371.44	42.79	-7.82	34.97	46.00	11.03	Peak
5	483.96	37.93	-4.51	33.42	46.00	12.58	Peak
6	530.52	39.54	-3.91	35.63	46.00	10.37	Peak


4.3 20 dB Emission Bandwidth

4.3.1 Applicable Standard

FCC §15.215

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §15.217 through § 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of band operation.

4.3.2 EUT Setup



4.3.3 Test Procedure

According to ANSI C63.10-2013 Section 6.9.2

- The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.
- The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement.
- Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2
- Steps a) through c) might require iteration to adjust within the specified tolerances.
- The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target

“-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.

f) Set detection mode to peak and trace mode to max hold.

g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).

h) Determine the “-xx dB down amplitude” using [(reference value) - xx]. Alternatively, this calculation may be made by using the marker-delta function of the instrument.

i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).

j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “-xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.

k) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

4.3.4 Test Data

Serial Number:	2QUD-1	Test Date:	2024/9/11
Test Site:	Chamber A	Test Mode:	Transmitting
Tester:	Jayce Wang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	27	Relative Humidity: (%)	34	ATM Pressure: (kPa)	100.2
----------------------	----	---------------------------	----	---------------------------	-------


Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
EMCO	Passive Loop Antenna	6512	9706-1206	2023/10/25	2026/10/24
Narda	Coaxial Attenuator	757C-6dB	34010	2024/4/16	2027/4/15
Unknown	Coaxial Cable	C-NJNJ-50	C-0075-01	2024/7/1	2025/6/30
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-01	2024/7/1	2025/6/30
Unknown	Coaxial Cable	C-NJNJ-50	C-1400-01	2024/7/1	2025/6/30
Sonoma	Amplifier	310N	372193	2024/8/16	2025/8/15
R&S	EMI Test Receiver	ESR3	102453	2024/8/26	2025/8/25

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Test Frequency (MHz)	20 dB Emission Bandwidth (kHz)
13.56	0.759



4.3 99% Occupied Bandwidth:

4.3.1 Applicable Standard

RSS-Gen Clause 6.7

The occupied bandwidth or the “99% emission bandwidth” is defined as the frequency range between two points, one above and the other below the carrier frequency, within which 99% of the total transmitted power of the fundamental transmitted emission is contained. The occupied bandwidth shall be reported for all equipment in addition to the specified bandwidth required in the applicable RSSs. In some cases, the “x dB bandwidth” is required, which is defined as the frequency range between two points, one at the lowest frequency below and one at the highest frequency above the carrier frequency, at which the maximum power level of the transmitted emission is attenuated x dB below the maximum in-band power level of the modulated signal, where the two points are on the outskirts of the in-band emission.

The following conditions shall be observed for measuring the occupied bandwidth and x dB bandwidth: The transmitter shall be operated at its maximum carrier power measured under normal test conditions. The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.

The detector of the spectrum analyzer shall be set to “Sample”. However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or “Max Hold”) may be necessary to determine the occupied / x dB bandwidth if the device is not transmitting continuously.


The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / x dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value.

Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.

For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).

4.3.2 EUT Setup



4.3.3 Test Procedure

According to ANSI C63.10-2013 Section 6.9.3

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement.
- Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW}/\text{RBW})]$ below the reference level. Specific guidance is given in 4.1.5.2.
- Step a) through step c) might require iteration to adjust within the specified range.
- Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

4.3.4 Test Data And Result

Serial Number:	2QUD-1	Test Date:	2024/9/11
Test Site:	Chamber A	Test Mode:	Transmitting
Tester:	Jayce Wang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	27	Relative Humidity: (%)	34	ATM Pressure: (kPa)	100.2
----------------------	----	---------------------------	----	---------------------------	-------


Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
EMCO	Passive Loop Antenna	6512	9706-1206	2023/10/25	2026/10/24
Narda	Coaxial Attenuator	757C-6dB	34010	2024/4/16	2027/4/15
Unknown	Coaxial Cable	C-NJNJ-50	C-0075-01	2024/7/1	2025/6/30
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-01	2024/7/1	2025/6/30
Unknown	Coaxial Cable	C-NJNJ-50	C-1400-01	2024/7/1	2025/6/30
Sonoma	Amplifier	310N	372193	2024/8/16	2025/8/15
R&S	EMI Test Receiver	ESR3	102453	2024/8/26	2025/8/25

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Test Frequency (MHz)	99% Occupied Bandwidth (kHz)
13.56	0.669



4.5 Frequency Stability

4.5.1 Applicable Standard


FCC Part 15.225:

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency over a temperature variation of -20 degrees to $+50$ degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

RSS-210 B.6:

(b) the carrier frequency stability shall not exceed ± 100 ppm

4.5.2 EUT Setup



4.5.3 Test Procedure

According to ANSI C63.10-2013 Section 6.8

Frequency stability with respect to ambient temperature

a) Supply the EUT with a nominal ac voltage or install a new or fully charged battery in the EUT. If possible, a dummy load shall be connected to the EUT because an antenna near the metallic walls of an environmental test chamber could affect the output frequency of the EUT. If the EUT is equipped with a permanently attached, adjustable-length antenna, then the EUT shall be placed in the center of the chamber with the antenna adjusted to the shortest length possible. Turn ON the EUT and tune it to one of the number of frequencies shown in 5.6.

b) Couple the unlicensed wireless device output to the measuring instrument by connecting an antenna to the measuring instrument with a suitable length of coaxial cable and placing the measuring antenna near the EUT (e.g., 15 cm away), or by connecting a dummy load to the measuring instrument, through an attenuator if necessary.

NOTE—An instrument that has an adequate level of accuracy as specified by the procuring or regulatory agency is the recommended measuring instrument.

c) Adjust the location of the measurement antenna and the controls on the measurement instrument to obtain a suitable signal level (i.e., a level that will not overload the measurement instrument but is strong enough to allow measurement of the operating or fundamental frequency of the EUT).

d) Turn the EUT OFF and place it inside the environmental temperature chamber. For devices that have oscillator heaters, energize only the heater circuit.

- e) Set the temperature control on the chamber to the highest specified in the regulatory requirements for the type of device and allow the oscillator heater and the chamber temperature to stabilize.
- f) While maintaining a constant temperature inside the environmental chamber, turn the EUT ON and record the operating frequency at startup, and at 2 minutes, 5 minutes, and 10 minutes after the EUT is energized. Four measurements in total are made.
- g) Measure the frequency at each of frequencies specified in 5.6.
- h) Switch OFF the EUT but do not switch OFF the oscillator heater.
- i) Lower the chamber temperature by not more than 10 °C, and allow the temperature inside the chamber to stabilize.
- j) Repeat step f) through step i) down to the lowest specified temperature.

Frequency stability when varying supply voltage

Unless otherwise specified, these tests shall be made at ambient room temperature (+15 °C to +25 °C). An antenna shall be connected to the antenna output terminals of the EUT if possible. If the EUT is equipped with or uses an adjustable-length antenna, then it shall be fully extended.

- a) Supply the EUT with nominal voltage or install a new or fully charged battery in the EUT. Turn ON the EUT and couple its output to a frequency counter or other frequency-measuring instrument.
NOTE—An instrument that has an adequate level of accuracy as specified by the procuring or regulatory agency is the recommended measuring instrument.
- b) Tune the EUT to one of the number of frequencies required in 5.6. Adjust the location of the measurement antenna and the controls on the measurement instrument to obtain a suitable signal level (i.e., a level that will not overload the measurement instrument but is strong enough to allow measurement of the operating or fundamental frequency of the EUT).
- c) Measure the frequency at each of the frequencies specified in 5.6.
- d) Repeat the above procedure at 85% and 115% of the nominal supply voltage as described in 5.13.

4.5.4 Test Result

Serial Number:	2QUD-5	Test Date:	2024/9/11
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jayce Wang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	27	Relative Humidity: (%)	34	ATM Pressure: (kPa)	100.2
----------------------	----	---------------------------	----	---------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Narda	Coaxial Attenuator	757C-6dB	34010	2024/4/16	2027/4/15
R&S	EMI Test Receiver	ESR3	102453	2024/8/26	2025/8/25
BACL	TEMP&HUMI Test Chamber	BTH-150-40	30173	2024/9/6	2025/9/5
All-sun	Clamp Meter	EM305A	8348897	2024/8/16	2025/8/15
TDK-Lambda	DC Power Supply	Z+60-14	F-08-EM038-1	N/A	N/A

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

$f_o = 13.56 \text{ MHz}$				
Temperature	Voltage	Measured frequency	Frequency Error	Limit
°C	V _{dc}	MHz	Hz	Hz
-30	12.0	13.55984	-160	±1356
-20		13.55986	-140	±1356
-10		13.55983	-170	±1356
0		13.55985	-150	±1356
10		13.55988	-120	±1356
20		13.55983	-170	±1356
30		13.55980	-200	±1356
40		13.55982	-180	±1356
50		13.55984	-160	±1356
20	9.0	13.55986	-140	±1356
20	45.0	13.55983	-170	±1356

Note: the voltage range was declared by manufacturer▲.

4.6 Antenna Requirement

4.6.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

RSS-Gen §6.8

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

4.6.2 Judgment

Please refer to the Antenna Information detail in Section 1.3.

EXHIBIT A - EUT PHOTOGRAPHS

Please refer to the attachment 2402W92356E-RF-EXP EUT external photographs and 2402W92356E-RF-INP EUT internal photographs.

EXHIBIT B - TEST SETUP PHOTOGRAPHS

Please refer to the attachment 2402W92356E-RF-00F-TSP test setup photographs.

******* END OF REPORT *******