

SAR Test exclusion documentation according to CFR 47 §1.1307

Report identification number: 1-3734/21-01-07 Exemption / MPE (FCC)

contains the module with the following certification numbers	
FCC ID	XKB-XTRAWIC

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Document authorised:



cn=Thomas Vogler, o=CTC advanced
GmbH, ou=VOG-211118,
email=thomas.vogler@ctcadvanced.com,
c=DE
2022.09.26 14:31:17 +02'00'

Thomas Vogler
Lab Manager
Radio Communications & EMC



cn=Marco Scigliano, o=CTC advanced
GmbH, ou=SCI-211118,
email=marco.scigliano@ctcadvanced.co
m, c=DE
2022.09.26 14:29:21 +02'00'

Marco Scigliano
Testing Manager
Radio Communications & EMC

EUT technologies:

Technologies:	Max. meas. cond. AVG Power	Antenna gain	Max. EIRP for RF exposure	Max. ERP for RF exposure
WLAN ¹⁾ 2450 MHz	15.2 dBm	6.6 dBi	21.8 dBm	19.65 dBm (=92.26mW)
WLAN ²⁾ 5000 MHz	11.6 dBm	7.2 dBi	18.8 dBm	16.65 dBm (=46.24mW)

¹⁾ Test result taken from CTC advanced GmbH report 1-3734/21-01-06.

²⁾ Test result taken from CTC advanced GmbH report 1-3734/21-01-05.

Declared minimum safety distance: 20cm

According the manual a safety distance of 20cm shall be applied between the user (and/or bystanders) to the EUT antenna whilst active transmitting.

SAR-Based Exemption following 47 CFR 1.1307 amendment:

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P_{th} (mW). This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula (B.2).

$$P_{th}(mW) = \begin{cases} ERP_{20cm} \left(\frac{d}{20cm}\right)^x & d \leq 20cm \\ ERP_{20cm} & 20cm \leq d \leq 40cm \end{cases} \quad (B.2)$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20cm} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and ERP_{20cm} is per Formula (B.1).

$$P_{th}(mW) = ERP_{20cm}(mW) = \begin{cases} ERP_{20cm} \left(\frac{d}{20cm}\right)^x & d \leq 20cm \\ ERP_{20cm} & 20cm \leq d \leq 40cm \end{cases} \quad (B.1)$$

Technology	Transmitter frequency (MHz)	Max. decl. ERP (mW)	Threshold ERP		Minimal Safety (mm)	Verdict
			(mW)	(dBm)		
WLAN	2450	92.26	3060.00	34.8	200	EXCEMPTED
WLAN	5000	46.24	3060.00	34.8	200	EXCEMPTED