

FCC 47 CFR PART 15 SUBPART C

Product Type : WiFi Repeater
Applicant : BaudTec Corporation
Address : 12F,NO,181,Sec.1.TatungRd.,His-chih City,Taipei county,Taiwan,
221
Trade Name : Baudtec
Model Number : RE300B1-2T2R, WRE-6001
FCC ID : XKR-RE300B1
Test Specification : FCC 47 CFR PART 15 SUBPART C: Oct., 2013
ANSI C63.4:2009
Receive Date : Sep. 05, 2014
Test Period : Sep. 11~Sep.18, 2014
Issue Date : Oct. 30, 2014

Issue by

A Test Lab Techno Corp.
No. 140-1, Changan Street, Bade City,
Taoyuan County 334, Taiwan R.O.C.
Tel : +886-3-2710188 / Fax : +886-3-2710190



Taiwan Accreditation Foundation accreditation number: 1330

Note: This report shall not be reproduced except in full, without the written approval of A Test Lab Techno Corp. This document may be altered or revised by A Test Lab Techno Corp. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, or any government agencies. The test results in the report only apply to the tested sample.

Revision History

Rev.	Issue Date	Revisions	Revised By
00	Sep. 19, 2014	Initial Issue	
01	Oct. 22, 2014	Update report information	Nico Peng
02	Oct. 27, 2014	Revised report information	Nico Peng
03	Oct. 28, 2014	Revised report information	Nico Peng
04	Oct. 30, 2014	Revised report information	Nico Peng

Verification of Compliance

Issued Date: 10/30/2014

Product Type : WiFi Repeater
Applicant : BaudTec Corporation
Address : 12F,NO,181,Sec.1.TatungRd.,His-chih City,Taipei
county,Taiwan, 221
Trade Name : Baudtec
Model Number : RE300B1-2T2R, WRE-6001
FCC ID : XKR-RE300B1
EUT Rated Voltage : AC100V~240V
Test Voltage : 120 Vac / 60 Hz
Applicable Standard : FCC 47 CFR PART 15 SUBPART C: Oct., 2013
ANSI C63.4:2009
Test Result : Complied
Performing Lab. : A Test Lab Techno Corp.
No. 140-1, Changan Street, Bade City,
Taoyuan County 334, Taiwan R.O.C.
Tel : +886-3-2710188 / Fax : +886-3-2710190
Taiwan Accreditation Foundation accreditation number: 1330
<http://www.atl-lab.com.tw/e-index.htm>



The above equipment was tested by A Test Lab Techno Corp. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4: 2009 and the energy emitted by the sample tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247 .

The test results of this report relate only to the tested sample identified in this report.

Approved By

: Fly Lu
(Fly Lu)

Reviewed By

(Testing Engineer)

: Eric Ou Yang
(Eric Ou Yang)

TABLE OF CONTENTS

1	General Information	6
2	EUT Description	7
3	Test Methodology	8
3.1.	Mode of Operation	8
3.2.	EUT Exercise Software	8
3.3.	Configuration of Test System Details	9
3.4.	Test Site Environment	10
4	Conducted Emission Measurement	10
4.1.	Limit	10
4.2.	Test Instruments	10
4.3.	Test Setup	11
4.4.	Test Procedure	11
4.5.	Test Result	12
5	Radiated Emission Measurement	14
5.1.	Limit	14
5.2.	Test Instruments	14
5.3.	Setup	15
5.4.	Test Procedure	16
5.5.	Test Result	18
6	Maximum Conducted Output Power Measurement	25
6.1.	Limit	25
6.2.	Test Setup	25
6.3.	Test Instruments	25
6.4.	Test Procedure	25
6.5.	Test Result	26
7	6dB RF Bandwidth and 99 % Occupied Bandwidth Measurement	29
7.1.	Limit	29
7.2.	Test Setup	29
7.3.	Test Instruments	29
7.4.	Test Procedure	29
7.5.	Test Result	30
7.6.	Test Graphs	32
8	Maximum Power Density Measurement	44
8.1.	Limit	44
8.2.	Test Setup	44
8.3.	Test Instruments	44
8.4.	Test Procedure	44
8.5.	Test Result	45
8.6.	Test Graphs	47

9	Out of Band Conducted Emissions Measurement	53
9.1.	Limit	53
9.2.	Test Setup.....	53
9.3.	Test Instruments	53
9.4.	Test Procedure	53
9.5.	Test Graphs	54
10	Band Edges Measurement	72
10.1.	Limit	72
10.2.	Test Setup.....	72
10.3.	Test Instruments	72
10.4.	Test Procedure	73
10.5.	Test Result.....	74
11	Antenna Measurement.....	78
11.1.	Limit	78
11.2.	Antenna Connector Construction	78

1 General Information

1.1 Summary of Test Result

Standard	Item	Result	Remark
15.247			
15.207	AC Power Conducted Emission	PASS	-----
-----	99 % Occupied Bandwidth	PASS	-----
Standard	Item	Result	Remark
15.247			
15.247(d)	Transmitter Radiated Emissions	PASS	-----
15.247(b)(3)	Max. Output Power	PASS	-----
15.247(a)(2)	6dB RF Bandwidth	PASS	-----
15.247(e)	Power Spectral Density	PASS	-----
15.247(d)	Out of Band Conducted Spurious Emission	PASS	-----
15.247(d)	Band Edge Measurement	PASS	-----
15.203	Antenna Requirement	PASS	-----

The test results of this report relate only to the tested sample(s) identified in this report. Manufacturer or whom it may concern should recognize the pass or fail of the test result.

1.2 Measurement Uncertainty

Test Item	Frequency Range		Uncertainty (dB)
Conducted Emission	9kHz ~ 30MHz		± 2.02
Radiated Emission	30MHz ~ 1000MHz	Horizontal	± 3.98
		Vertical	± 3.62
	1000MHz ~ 18000MHz	Horizontal	± 3.11
		Vertical	± 3.07
	18000MHz ~ 40000MHz	Horizontal	± 3.66
		Vertical	± 3.54

2 EUT Description

Product Type	WiFi Repeater			
Trade Name	Baudtec			
Model No.	RE300B1-2T2R, WRE-6001 * There model numbers differ from each other in selling region.			
Applicant	BaudTec Corporation 12F,NO,181,Sec.1.TatungRd.,His-chih City,Taipei county,Taiwan, 221			
Manufacturer	BaudTec Corporation 12F,NO,181,Sec.1.TatungRd.,His-chih City,Taipei county,Taiwan, 221			
FCC ID	XKR-RE300B1			
Frequency Range	IEEE 802.11b / 802.11g / 802.11n 2.4GHz 20MHz: 2412 ~ 2462 MHz IEEE 802.11n 2.4GHz 40MHz: 2422 ~ 2452 MHz			
Modulation Type	IEEE 802.11b:DSSS IEEE 802.11g:DSSS + OFDM IEEE 802.11n 2.4GHz 20MHz: OFDM IEEE 802.11n 2.4GHz 40MHz: OFDM			
Antenna Used	Item	Antenna Port	Type	Max Gain
	1	ANT-1	FCB Antenna	2.73 dBi
	2	ANT-2	FCB Antenna	3.67 dBi
Antenna Delivery	IEEE 802.11b/g :1TX + 1RX IEEE 802.11n :2*TX + 2*RX			
RF Output Power	IEEE 802.11b: 0.0566 W / 17.53 dBm IEEE 802.11g: 0.1884 W / 22.75 dBm IEEE 802.11n 2.4GHz 20MHz: 0.2569 W / 24.10 dBm IEEE 802.11n 2.4GHz 40MHz: 0.2904 W / 24.63 dBm			
99 % Occupied Bandwidth	IEEE 802.11b: 15.02 MHz IEEE 802.11g: 16.81 MHz IEEE 802.11n 2.4GHz 20MHz: 17.99 MHz IEEE 802.11n 2.4GHz 40MHz: 36.60 MHz			

3 Test Methodology

3.1. Mode of Operation

Decision of Test ATL has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was shown in this test report and defined as:

Test Mode
Mode 1: Normal Operation Mode
Mode 2: IEEE 802.11b Link Mode
Mode 3: IEEE 802.11g Link Mode
Mode 4: IEEE 802.11n 2.4GHz 20MHz Link Mode
Mode 5: IEEE 802.11n 2.4GHz 40MHz Link Mode

Software used to control the EUT for staying in continuous transmitting mode was programmed.

After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz and power line conducted emissions below 30MHz, which worst case was in normal link mode only.

IEEE 802.11b mode: (ANT-1)

Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 1Mbps data rate and cyclic delay diversity were chosen for full testing.

IEEE 802.11g mode: (ANT-1)

Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 6Mbps data rate and cyclic delay diversity were chosen for full testing.

IEEE 802.11n 2.4GHz 20MHz mode: (ANT-1+2)

Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 13Mbps data rate were chosen for full testing.

IEEE 802.11n 2.4GHz 40MHz mode: (ANT-1+2)


Channel Low (2422MHz), Channel Mid (2437MHz) and Channel High (2452MHz) with 27Mbps data rate were chosen for full testing.

3.2. EUT Exercise Software


1. Setup the EUT shown on 3.3.
2. Turn on the power of all equipment.
3. Turn on Wi-Fi function link to AP.
4. EUT run test program.

3.3. Configuration of Test System Details

Conducted Emission



Radiated Emission



3.4. Test Site Environment

Items	Required (IEC 60068-1)	Actual
Temperature (°C)	15-35	26
Humidity (%RH)	25-75	60
Barometric pressure (mbar)	860-1060	950

4 Conducted Emission Measurement

4.1. Limit

Frequency (MHz)	Quasi-peak	Average
0.15 - 0.5	66 to 56	56 to 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50


4.2. Test Instruments

Describe	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Test Receiver	R&S	ESCI	100367	06/12/2014	(1)
LISN	R&S	ENV216	101040	03/07/2014	(1)
LISN	R&S	ENV216	101041	03/07/2014	(1)
Test Site	ATL	TE02	TE02	N.C.R.	-----

Remark: (1) Calibration period 1 year. (2) Calibration period 2 years. (3) Calibration period 3 years.

Note: N.C.R. = No Calibration Request.

4.3. Test Setup



4.4. Test Procedure


The power line conducted emission measurements were performed in a shielded enclosure. The EUT was assembled on a wooden table which is 80 centimeters high, was placed 40 centimeters from the back wall and at least 1 meter from the sidewall.

Power was fed to the EUT from the public utility power grid through a line filter and EMCO Model 3162/2 SH Line Impedance Stabilization Networks (LISN). The LISN housing, measuring instrumentation case, ground plane, etc., were electrically bonded together at the same RF potential. The Spectrum analyzer was connected to the AC line through an isolation transformer. The 50-ohm output of the LISN was connected to the spectrum analyzer directly. Conducted emission levels were in the CISPR quasi-peak detection mode. The analyzer's 6 dB bandwidth was set to 9 KHz. No post-detector video filter was used.

The spectrum was scanned from 150 KHz to 30 MHz. The physical arrangement of the test system and associated cabling was varied (within the scope of arrangements likely to be encountered in actual use) to determine the effect on the unit's emanations in amplitude and frequency. All spurious emission frequencies were observed. The highest emission amplitudes relative to the appropriate limit were measured and have been recorded in paragraph 4.1.

4.5. Test Result

Standard:	FCC Part 15C	Line:	L1
Test item:	Conducted Emission	Power:	AC 120V/60Hz
Model Number:	RE300B1-2T2R	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	1	Date:	09/12/2014
		Test By:	Eric Ou Yang
Description:			




No.	Frequency (MHz)	QP reading (dBuV)	AVG reading (dBuV)	Correction factor (dB)	QP result (dBuV)	AVG result (dBuV)	QP limit (dBuV)	AVG limit (dBuV)	QP margin (dB)	AVG margin (dB)	Remark
1	1.6700	15.44	3.59	9.68	25.12	13.27	56.00	46.00	-30.88	-32.73	Pass
2	1.7340	15.67	5.24	9.68	25.35	14.92	56.00	46.00	-30.65	-31.08	Pass
3	1.8300	17.69	6.15	9.68	27.37	15.83	56.00	46.00	-28.63	-30.17	Pass
4	20.2580	17.24	12.30	10.25	27.49	22.55	60.00	50.00	-32.51	-27.45	Pass
5	21.6620	18.19	12.58	10.26	28.45	22.84	60.00	50.00	-31.55	-27.16	Pass
6	23.1300	19.74	13.45	10.27	30.01	23.72	60.00	50.00	-29.99	-26.28	Pass

Note: 1. Result (dBuV) = Correction factor (dB) + Reading(dBuV).

2. Correction factor (dB) = Cable loss (dB) + L.I.S.N. factor (dB).

Standard:	FCC Part 15C	Line:	N
Test item:	Conducted Emission	Power:	AC 120V/60Hz
Model Number:	RE300B1-2T2R	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	1	Date:	09/12/2014
		Test By:	Eric Ou Yang
Description:			



No.	Frequency (MHz)	QP reading (dBuV)	AVG reading (dBuV)	Correction factor (dB)	QP result (dBuV)	AVG result (dBuV)	QP limit (dBuV)	AVG limit (dBuV)	QP margin (dB)	AVG margin (dB)	Remark
1	0.1500	28.59	10.05	9.59	38.18	19.64	66.00	56.00	-27.82	-36.36	Pass
2	1.7820	21.52	15.57	9.69	31.21	25.26	56.00	46.00	-24.79	-20.74	Pass
3	1.8660	25.55	17.16	9.69	35.24	26.85	56.00	46.00	-20.76	-19.15	Pass
4	1.9180	26.60	15.24	9.70	36.30	24.94	56.00	46.00	-19.70	-21.06	Pass
5	21.6620	25.81	19.96	10.27	36.08	30.23	60.00	50.00	-23.92	-19.77	Pass
6	23.1300	26.11	19.34	10.28	36.39	29.62	60.00	50.00	-23.61	-20.38	Pass

Note: 1. Result (dBuV) = Correction factor (dB) + Reading(dBuV).

2. Correction factor (dB) = Cable loss (dB) + L.I.S.N. factor (dB).

5 Radiated Emission Measurement

5.1. Limit

According to §15.209(a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$ at meter)	Measurement Distance (meters)
0.009 – 0.490	2400 / F (kHz)	300
0.490 – 1.705	24000 / F (kHz)	30
1.705 – 30.0	30	30
30 - 88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

5.2. Test Instruments


3 Meter Chamber					
Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
RF Pre-selector	Agilent	N9039A	MY46520256	01/10/2014	(1)
Spectrum Analyzer	Agilent	E4446A	MY46180578	01/10/2014	(1)
Pre Amplifier	Agilent	8449B	3008A02237	02/21/2014	(1)
Pre Amplifier	Agilent	8447D	2944A10961	02/21/2014	(1)
Broadband Antenna (30MHz~1GHz)	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	9163-270	07/22/2014	(1)
Horn Antenna (1~18GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA9120D	9120D-550	06/11/2014	(1)
Horn Antenna (18~40GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA9170	9170-320	07/02/2014	(1)
Loop Antenna	COM-POWER CORPORATION	AL-130	121014	08/14/2012	(3)
Test Site	ATL	TE01	888001	08/28/2014	(1)

Remark: (1) Calibration period 1 year. (2) Calibration period 2 years. (3) Calibration period 3 years.


Note: N.C.R. = No Calibration Request.

5.3. Setup

Below 1GHz



Above 1GHz



5.4. Test Procedure

Final radiation measurements were made on a three-meter, Semi Anechoic Chamber. The EUT system was placed on a nonconductive turntable which is 0.8 meters height, top surface 1.0 x 1.5 meter. The spectrum was examined from 250 MHz to 2.5 GHz in order to cover the whole spectrum below 10th harmonic which could generate from the EUT. During the test, EUT was set to transmit continuously & Measurements spectrum range from 9 kHz to 26.5 GHz is investigated.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, and then the video bandwidth is set to 1 MHz for peak measurements and 10 Hz for average measurements.

A nonconductive material surrounded the EUT to supporting the EUT for standing on three orthogonal planes. At each condition, the EUT was rotated 360 degrees, and the antenna was raised and lowered from one to four meters to find the maximum emission levels. Measurements were taken using both horizontal and vertical antenna polarization.

SCHWARZBECK MESS-ELEKTRONIK Biconilog Antenna (mode VULB9163) at 3 Meter and the SCHWARZBECK Double Ridged Guide Antenna (model BBHA9120D&9170) was used in frequencies 1 – 26.5 GHz at a distance of 1 meter. All test results were extrapolated to equivalent signal at 3 meters utilizing an inverse linear distance extrapolation Factor (20dB/decade).

For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

Appropriate preamplifiers were used for improving sensitivity and precautions were taken to avoid overloading or desensitizing the spectrum analyzer. No post – detector video filters were used in the test.

The spectrum analyzer's 6 dB bandwidth was set to 1 MHz, and the analyzer was operated in the peak detection mode, for frequencies both below and up 1 GHz. The average levels were obtained by subtracting the duty cycle correction factor from the peak readings.

The following procedures were used to convert the emission levels measured in decibels referenced to 1 microvolt (dBuV) into field intensity in micro volts per meter (uV/m).

The actual field intensity in decibels referenced to 1 microvolt in to field intensity in micro volts per meter (dBuV/m).

The actual field intensity in referenced to 1 microvolt per meter (dBuV/m) is determined by algebraically adding the measured reading in dBuV, the antenna factor (dB), and cable loss (dB) and Subtracting the gain of preamplifier (dB) is auto calculate in spectrum analyzer.

(1) $\text{Amplitude (dBuV/m)} = \text{FI (dBuV)} + \text{AF (dBuV)} + \text{CL (dBuV)} - \text{Gain (dB)}$

FI= Reading of the field intensity.

AF= Antenna factor.

CL= Cable loss.

P.S Amplitude is auto calculate in spectrum analyzer.

(2) $\text{Actual Amplitude (dBuV/m)} = \text{Amplitude (dBuV)} - \text{Dis(dB)}$

The FCC specified emission limits were calculated according the EUT operating frequency and by following linear interpolation equations:

(a) For fundamental frequency : Transmitter Output < +30dBm

(b) For spurious frequency : Spurious emission limits = fundamental emission limit /10

Data of measurement within this frequency range without mark in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

5.5. Test Result

Below 1GHz

Standard:		FCC Part 15C		Test Distance:		3m	
Test item:		Radiated Emission		Power:		AC 120V/60Hz	
Model Number:		RE300B1-2T2R		Temp.(℃)/Hum.(%RH):		26(℃)/60%RH	
Mode:		1		Date:		09/10/2014	
				Test By:		Eric Ou Yang	
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
111.0000	44.37	-15.17	29.20	43.50	-14.30	QP	H
200.0000	39.84	-14.39	25.45	43.50	-18.05	QP	H
258.0000	39.10	-11.84	27.26	46.00	-18.74	QP	H
400.0000	30.81	-8.20	22.61	46.00	-23.39	QP	H
500.0000	30.31	-6.29	24.02	46.00	-21.98	QP	H
750.0000	35.27	-1.16	34.11	46.00	-11.89	QP	H
179.0000	42.32	-13.03	29.29	43.50	-14.21	QP	V
259.0000	34.64	-11.81	22.83	46.00	-23.17	QP	V
400.0000	32.27	-8.20	24.07	46.00	-21.93	QP	V
500.0000	36.34	-6.29	30.05	46.00	-15.95	QP	V
750.0000	32.05	-1.16	30.89	46.00	-15.11	QP	V
900.0000	27.47	1.71	29.18	46.00	-16.82	QP	V

Note: No emission found between lowest internal used/generated frequency to 30MHz (9kHz~30MHz).

Above 1GHz

Standard:	FCC Part 15C		Test Distance:	3m			
Test item:	Radiated Emission		Power:	AC 120V/60Hz			
Model Number:	RE300B1-2T2R		Temp.(°C)/Hum.(%RH):	26(°C)/60%RH			
Mode:	2		Date:	09/11/2014			
Frequency:	2412MHz		Test By:	Eric Ou Yang			
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3002.000	36.50	-0.20	36.30	74.00	-37.70	peak	H
4824.000	44.29	5.03	49.32	74.00	-24.68	peak	H
6670.000	34.67	9.95	44.62	74.00	-29.38	peak	H
3009.000	37.45	-0.17	37.28	74.00	-36.72	peak	V
4824.000	44.87	5.03	49.90	74.00	-24.10	peak	V
6677.000	33.76	9.97	43.73	74.00	-30.27	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	RE300B1-2T2R			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	2			Date:	09/11/2014		
Frequency:	2437MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3030.000	37.03	-0.11	36.92	74.00	-37.08	peak	H
4874.000	42.89	5.16	48.05	74.00	-25.95	peak	H
6670.000	33.36	9.95	43.31	74.00	-30.69	peak	H
3009.000	36.91	-0.17	36.74	74.00	-37.26	peak	V
4874.000	44.38	5.16	49.54	74.00	-24.46	peak	V
6691.000	33.67	10.01	43.68	74.00	-30.32	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	RE300B1-2T2R			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	2			Date:	09/11/2014		
Frequency:	2462MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3009.000	37.18	-0.17	37.01	74.00	-36.99	peak	H
4924.000	41.24	5.29	46.53	74.00	-27.47	peak	H
6726.000	33.54	10.10	43.64	74.00	-30.36	peak	H
3009.000	36.15	-0.17	35.98	74.00	-38.02	peak	V
4924.000	49.59	5.29	54.88	74.00	-19.12	peak	V
4924.000	46.34	5.29	51.63	54.00	-2.37	AVG	V
6698.000	33.18	10.03	43.21	74.00	-30.79	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	RE300B1-2T2R			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	3			Date:	09/11/2014		
Frequency:	2412MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3058.000	36.77	-0.04	36.73	74.00	-37.27	peak	H
4824.000	40.89	5.03	45.92	74.00	-28.08	peak	H
6670.000	33.17	9.95	43.12	74.00	-30.88	peak	H
3023.000	37.26	-0.14	37.12	74.00	-36.88	peak	V
4824.000	43.57	5.03	48.60	74.00	-25.40	peak	V
6698.000	33.43	10.03	43.46	74.00	-30.54	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	RE300B1-2T2R			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	3			Date:	09/11/2014		
Frequency:	2437MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3002.000	36.43	-0.20	36.23	74.00	-37.77	peak	H
4874.000	39.61	5.16	44.77	74.00	-29.23	peak	H
6698.000	33.82	10.03	43.85	74.00	-30.15	peak	H
3030.000	36.71	-0.11	36.60	74.00	-37.40	peak	V
4874.000	43.63	5.16	48.79	74.00	-25.21	peak	V
6705.000	33.53	10.05	43.58	74.00	-30.42	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	RE300B1-2T2R			Temp.(℃)/Hum.(%RH):	26(℃)/60%RH		
Mode:	3			Date:	09/11/2014		
Frequency:	2462MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3023.000	36.88	-0.14	36.74	74.00	-37.26	peak	H
4924.000	38.47	5.29	43.76	74.00	-30.24	peak	H
6691.000	34.02	10.01	44.03	74.00	-29.97	peak	H
3030.000	36.46	-0.11	36.35	74.00	-37.65	peak	V
4924.000	44.01	5.29	49.30	74.00	-24.70	peak	V
6691.000	34.41	10.01	44.42	74.00	-29.58	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	RE300B1-2T2R			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	4			Date:	09/11/2014		
Frequency:	2412MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3051.000	37.77	-0.06	37.71	74.00	-36.29	peak	H
4570.000	34.70	4.38	39.08	74.00	-34.92	peak	H
6649.000	34.02	9.90	43.92	74.00	-30.08	peak	H
3002.000	37.02	-0.20	36.82	74.00	-37.18	peak	V
4563.000	35.12	4.36	39.48	74.00	-34.52	peak	V
6705.000	33.54	10.05	43.59	74.00	-30.41	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	RE300B1-2T2R			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	4			Date:	09/11/2014		
Frequency:	2437MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3058.000	37.11	-0.04	37.07	74.00	-36.93	peak	H
4591.000	34.58	4.43	39.01	74.00	-34.99	peak	H
6719.000	33.30	10.09	43.39	74.00	-30.61	peak	H
3002.000	37.77	-0.20	37.57	74.00	-36.43	peak	V
4605.000	36.01	4.47	40.48	74.00	-33.52	peak	V
6705.000	34.29	10.05	44.34	74.00	-29.66	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	RE300B1-2T2R			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	4			Date:	09/11/2014		
Frequency:	2462MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3009.000	36.66	-0.17	36.49	74.00	-37.51	peak	H
4577.000	34.07	4.39	38.46	74.00	-35.54	peak	H
6698.000	33.72	10.03	43.75	74.00	-30.25	peak	H
2953.000	36.72	-0.32	36.40	74.00	-37.60	peak	V
4570.000	34.87	4.38	39.25	74.00	-34.75	peak	V
6691.000	34.16	10.01	44.17	74.00	-29.83	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	RE300B1-2T2R			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	5			Date:	09/11/2014		
Frequency:	2422MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3051.000	36.98	-0.06	36.92	74.00	-37.08	peak	H
4598.000	35.29	4.45	39.74	74.00	-34.26	peak	H
6698.000	33.99	10.03	44.02	74.00	-29.98	peak	H
3037.000	36.71	-0.10	36.61	74.00	-37.39	peak	V
4570.000	34.48	4.38	38.86	74.00	-35.14	peak	V
6698.000	33.00	10.03	43.03	74.00	-30.97	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	RE300B1-2T2R			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	5			Date:	09/11/2014		
Frequency:	2437MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3037.000	37.65	-0.10	37.55	74.00	-36.45	peak	H
4570.000	33.95	4.38	38.33	74.00	-35.67	peak	H
6719.000	33.00	10.09	43.09	74.00	-30.91	peak	H
2995.000	37.10	-0.22	36.88	74.00	-37.12	peak	V
4577.000	35.44	4.39	39.83	74.00	-34.17	peak	V
6677.000	33.01	9.97	42.98	74.00	-31.02	peak	V


Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	RE300B1-2T2R			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	5			Date:	09/11/2014		
Frequency:	2452MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3030.000	38.24	-0.11	38.13	74.00	-35.87	peak	H
4577.000	33.83	4.39	38.22	74.00	-35.78	peak	H
6705.000	32.85	10.05	42.90	74.00	-31.10	peak	H
3023.000	37.30	-0.14	37.16	74.00	-36.84	peak	V
4570.000	34.15	4.38	38.53	74.00	-35.47	peak	V
6719.000	33.71	10.09	43.80	74.00	-30.20	peak	V

6 Maximum Conducted Output Power Measurement

6.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm.

6.2. Test Setup



6.3. Test Instruments

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Power Sensor	Anritsu	MA2411B	1126022	08/21/2014	(1)
Power Meter	Anritsu	ML2495A	1135009	08/21/2014	(1)
Test Site	ATL	TE05	TE05	N.C.R.	-----

Remark: (1) Calibration period 1 year. (2) Calibration period 2 years. (3) Calibration period 3 years.

Note: N.C.R. = No Calibration Request.

6.4. Test Procedure

The tests below are run with the EUT's transmitter set at high power in TX mode. The EUT is needed to force selection of output power level and channel number. While testing, EUT was set to transmit continuously. Remove the Subjective device's antenna and connect the RF output port to power sensor. The maximum peak output power shall not exceed 1 watt.

Use a direct connection between the antenna port of transmitter and the power sensor, for prevent the power sensor input attenuation 40-50 dB. Set the RBW Bandwidth of the emission or use a channel power meter mode.

For antennas with gains of 6 dBi or less, maximum allowed transmitter output is 1 watt (+30 dBm). For antennas with gains greater than 6 dBi, transmitter output level must be decreased by an amount equal to (GAIN - 6)/3 dBm.

The antenna port of the EUT was connected to the input of a power sensor. Power was read directly and cable loss correction was added to the reading to obtain power at the EUT antenna terminals.

6.5. Test Result

Model Number	RE300B1-2T2R									
Test Item	Maximum Conducted Output Power									
Test Mode	Mode 2: IEEE 802.11b Link Mode									
Date of Test	09/12/2014					Test Site		TE05		
Frequency (MHz)	Data Rate	ANT-1				ANT-2				Limit (dBm)
		Average Power		Peak Power		Average Power		Peak Power		
		(dBm)	(W)	(dBm)	(W)	(dBm)	(W)	(dBm)	(W)	
2412	1M	15.20	0.0331	17.53	0.0566	15.19	0.0330	17.52	0.0565	< 30
2437		15.15	0.0327	17.35	0.0543	15.11	0.0324	17.50	0.0562	< 30
2462		15.19	0.0330	17.41	0.0551	15.08	0.0322	17.40	0.0550	< 30
2437	2M	15.12	0.0325	17.31	0.0538	15.00	0.0316	17.23	0.0528	< 30
2437	5.5M	15.09	0.0323	17.26	0.0532	15.01	0.0317	17.29	0.0536	< 30
2437	11M	15.10	0.0324	17.29	0.0536	15.08	0.0322	17.26	0.0532	< 30

Model Number	RE300B1-2T2R									
Test Item	Maximum Conducted Output Power									
Test Mode	Mode 3: IEEE 802.11g Link Mode									
Date of Test	09/12/2014					Test Site		TE05		
Frequency (MHz)	Data Rate	ANT-1				ANT-2				Limit (dBm)
		Average Power		Peak Power		Average Power		Peak Power		
		(dBm)	(W)	(dBm)	(W)	(dBm)	(W)	(dBm)	(W)	
2412	6M	14.14	0.0259	22.24	0.1675	14.51	0.0282	22.14	0.1637	< 30
2437		14.39	0.0275	22.44	0.1754	14.32	0.0270	21.97	0.1574	< 30
2462		14.58	0.0287	22.75	0.1884	14.22	0.0264	21.87	0.1538	< 30
2437	9M	14.36	0.0273	22.44	0.1752	14.27	0.0267	21.97	0.1573	< 30
2437	12M	14.30	0.0269	22.42	0.1744	14.26	0.0267	21.91	0.1554	< 30
2437	18M	14.29	0.0269	22.37	0.1727	14.28	0.0268	21.96	0.1570	< 30
2437	24M	14.28	0.0268	22.40	0.1738	14.25	0.0266	21.87	0.1538	< 30
2437	36M	14.35	0.0272	22.39	0.1732	14.24	0.0265	21.91	0.1551	< 30
2437	48M	14.33	0.0271	22.35	0.1719	14.30	0.0269	21.89	0.1544	< 30
2437	54M	14.31	0.0270	22.36	0.1722	14.31	0.0270	21.93	0.1559	< 30

Model Number	RE300B1-2T2R									
Test Item	Maximum Conducted Output Power									
Test Mode	Mode 4: IEEE 802.11n 2.4GHz 20MHz Link Mode									
Date of Test	09/12/2014					Test Site		TE05		
Frequency (MHz)	Data Rate	ANT-1				ANT-2				Limit (dBm)
		Average Power		Peak Power		Average Power		Peak Power		
		(dBm)	(W)	(dBm)	(W)	(dBm)	(W)	(dBm)	(W)	
2412	13M	12.02	0.0159	21.21	0.1321	11.98	0.0158	20.88	0.1225	< 30
2437		12.06	0.0161	21.28	0.1343	11.90	0.0155	20.87	0.1222	< 30
2462		12.20	0.0166	21.51	0.1416	11.85	0.0153	20.62	0.1153	< 30
2437	26M	12.01	0.0159	21.19	0.1315	11.88	0.0154	20.87	0.1221	< 30
2437	39M	11.97	0.0157	21.19	0.1315	11.87	0.0154	20.77	0.1194	< 30
2437	52M	11.99	0.0158	21.26	0.1335	11.81	0.0152	20.85	0.1216	< 30
2437	78M	12.00	0.0159	21.23	0.1328	11.83	0.0153	20.82	0.1209	< 30
2437	104M	12.03	0.0160	21.19	0.1315	11.85	0.0153	20.83	0.1211	< 30
2437	117M	12.02	0.0159	21.26	0.1336	11.89	0.0155	20.86	0.1219	< 30
2437	130M	11.99	0.0158	21.20	0.1318	11.81	0.0152	20.84	0.1214	< 30
Frequency (MHz)	Data Rate	ANT-1+2								Limit (dBm)
		Average Power				Peak Power				
		(dBm)		(W)		(dBm)		(W)		
2412	13M	15.01		0.0317		24.06		0.2546		< 30
2437		14.99		0.0316		24.09		0.2565		< 30
2462		15.04		0.0319		24.10		0.2569		< 30
2437	26M	14.96		0.0313		24.04		0.2536		< 30
2437	39M	14.93		0.0311		24.00		0.2509		< 30
2437	52M	14.91		0.0310		24.07		0.2551		< 30
2437	78M	14.93		0.0311		24.04		0.2537		< 30
2437	104M	14.95		0.0313		24.02		0.2525		< 30
2437	117M	14.97		0.0314		24.07		0.2555		< 30
2437	130M	14.91		0.0310		24.03		0.2532		< 30

Model Number	RE300B1-2T2R									
Test Item	Maximum Conducted Output Power									
Test Mode	Mode 5: IEEE 802.11n 2.4GHz 40MHz Link Mode									
Date of Test	09/12/2014					Test Site		TE05		
Frequency (MHz)	Data Rate	ANT-1				ANT-2				Limit (dBm)
		Average Power		Peak Power		Average Power		Peak Power		
		(dBm)	(W)	(dBm)	(W)	(dBm)	(W)	(dBm)	(W)	
2422	27M	11.01	0.0126	20.92	0.1236	11.43	0.0139	21.23	0.1327	< 30
2437		11.51	0.0142	21.36	0.1368	11.41	0.0138	21.31	0.1352	< 30
2452		11.83	0.0152	21.81	0.1517	11.45	0.0140	21.42	0.1387	< 30
2437	54M	11.42	0.0139	21.27	0.1339	11.38	0.0137	21.26	0.1337	< 30
2437	81M	11.44	0.0139	21.29	0.1345	11.31	0.0135	21.24	0.1330	< 30
2437	108M	11.44	0.0139	21.34	0.1361	11.36	0.0137	21.29	0.1347	< 30
2437	162M	11.47	0.0140	21.32	0.1356	11.32	0.0136	21.27	0.1340	< 30
2437	216M	11.43	0.0139	21.29	0.1346	11.35	0.0136	21.30	0.1348	< 30
2437	243M	11.41	0.0139	21.33	0.1357	11.39	0.0138	21.31	0.1351	< 30
2437	270M	11.40	0.0138	21.30	0.1348	11.33	0.0136	21.21	0.1321	< 30
Frequency (MHz)	Data Rate	ANT-1+2								Limit (dBm)
		Average Power				Peak Power				
		(dBm)		(W)		(dBm)		(W)		
2422	27M	14.24		0.0265		24.09		0.2563		< 30
2437		14.47		0.0280		24.35		0.2720		< 30
2452		14.65		0.0292		24.63		0.2904		< 30
2437	54M	14.41		0.0276		24.27		0.2676		< 30
2437	81M	14.39		0.0275		24.27		0.2675		< 30
2437	108M	14.41		0.0276		24.33		0.2708		< 30
2437	162M	14.41		0.0276		24.31		0.2696		< 30
2437	216M	14.40		0.0275		24.30		0.2694		< 30
2437	243M	14.41		0.0276		24.33		0.2708		< 30
2437	270M	14.38		0.0274		24.26		0.2669		< 30


7 6dB RF Bandwidth and 99 % Occupied Bandwidth Measurement

7.1. Limit

6dB RF Bandwidth: Systems using digital modulation techniques may operate in the 2400–2483.5 MHz bands. The minimum 6 dB band-width shall be at least 500 kHz.

99 % Occupied Bandwidth: N/A

7.2. Test Setup



7.3. Test Instruments

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Spectrum Analyzer	Agilent	E4445A	MY45300744	12/19/2012	(2)
Test Site	ATL	TE05	TE05	N.C.R.	-----

dRemark: (1) Calibration period 1 year. (2) Calibration period 2 years. (3) Calibration period 3 years.

Note: N.C.R. = No Calibration Request.

7.4. Test Procedure

The EUT was setup to ANSI C63.4, 2009; tested to DTS test procedure of KDB558074D01 for compliance to FCC 47CFR 15.247 requirements.

6dB RF Bandwidth: The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RES BW was set to 100 kHz. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A peak output reading was taken, a DISPLAY line was drawn 6 dB lower than peak level. The 6 dB bandwidth was determined from where the channel output spectrum intersected the display line.

The test was performed at 3 channels (Channel low, middle, high)

99 % Occupied Bandwidth: The transmitter shall be operated at its maximum carrier power measured under normal test conditions.

The video bandwidth shall be set to 3 times the resolution bandwidth. Video averaging is not permitted. Where practical, a sampling detector shall be used since a peak or, peak hold, may produce a wider bandwidth than actual.

The trace data points are recovered and are directly summed in linear terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points. This frequency is recorded.

7.5. Test Result

Model Number	RE300B1-2T2R		
Test Item	6dB RF Bandwidth and 99 % Occupied Bandwidth		
Test Mode	Mode 2: IEEE 802.11b Link Mode		
Date of Test	09/15/2014		Test Site TE05
Frequency (MHz)	6dB RF Bandwidth (MHz)	99 % Occupied Bandwidth (MHz)	6dB RF Bandwidth Limit (MHz)
2412	10.034	15.0029	> 0.500
2437	10.082	15.0106	> 0.500
2462	10.060	15.0232	> 0.500

Model Number	RE300B1-2T2R		
Test Item	6dB RF Bandwidth and 99 % Occupied Bandwidth		
Test Mode	Mode 3: IEEE 802.11g Link Mode		
Date of Test	09/15/2014		Test Site TE05
Frequency (MHz)	6dB RF Bandwidth (MHz)	99 % Occupied Bandwidth (MHz)	6dB RF Bandwidth Limit (MHz)
2412	16.435	16.7800	> 0.500
2437	16.408	16.7907	> 0.500
2462	16.433	16.8153	> 0.500




Model Number	RE300B1-2T2R					
Test Item	6dB RF Bandwidth and 99 % Occupied Bandwidth					
Test Mode	Mode 4: IEEE 802.11n 2.4GHz 20MHz Link Mode					
Date of Test	09/15/2014				Test Site	TE05
Frequency (MHz)	6dB RF Bandwidth (MHz)		99 % Occupied Bandwidth (MHz)		6dB RF Bandwidth Limit (MHz)	
	ANT-1	ANT-2	ANT-1	ANT-2		
2412	17.614	17.627	17.9315	17.8806	> 0.500	
2437	17.620	17.634	17.8994	17.8559	> 0.500	
2462	17.669	17.596	17.9957	17.8598	> 0.500	

Model Number	RE300B1-2T2R				
Test Item	6dB RF Bandwidth and 99 % Occupied Bandwidth				
Test Mode	Mode 5: IEEE 802.11n 2.4GHz 40MHz Link Mode				
Date of Test	09/15/2014			Test Site	TE05
Frequency (MHz)	6dB RF Bandwidth (MHz)		99 % Occupied Bandwidth (MHz)		6dB RF Bandwidth Limit (MHz)
	ANT-1	ANT-2	ANT-1	ANT-2	
2422	35.789	35.791	36.4751	36.5484	> 0.500
2437	35.463	33.951	36.4660	36.4331	> 0.500
2452	35.674	35.598	36.6069	36.4433	> 0.500

7.6. Test Graphs


6dB RF Bandwidth

Mode 2: IEEE 802.11b Link Mode


2412	 Agilent R T Ch Freq 2.412 GHz Trig Free Occupied Bandwidth Ref 20 dBm #Atten 20 dB #Peak Log 10 dB/ Offst 11.5 dB Center 2.412 GHz Span 30 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 4 ms (401 pts) Occupied Bandwidth 14.9988 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB Transmit Freq Error 21.440 kHz x dB Bandwidth 10.034 MHz Freq/Channel Center Freq 2.41200000 GHz Start Freq 2.39700000 GHz Stop Freq 2.42700000 GHz CF Step 3.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off
2437	 Agilent R T Ch Freq 2.437 GHz Trig Free Occupied Bandwidth Ref 20 dBm #Atten 20 dB #Peak Log 10 dB/ Offst 11.5 dB Center 2.437 GHz Span 30 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 4 ms (401 pts) Occupied Bandwidth 14.9539 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB Transmit Freq Error 9.312 kHz x dB Bandwidth 10.082 MHz Freq/Channel Center Freq 2.43700000 GHz Start Freq 2.42200000 GHz Stop Freq 2.45200000 GHz CF Step 3.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off
2462	 Agilent R T Ch Freq 2.462 GHz Trig Free Occupied Bandwidth Ref 20 dBm #Atten 20 dB #Peak Log 10 dB/ Offst 11.5 dB Center 2.462 GHz Span 30 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 4 ms (401 pts) Occupied Bandwidth 15.0063 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB Transmit Freq Error 2.658 kHz x dB Bandwidth 10.060 MHz Freq/Channel Center Freq 2.46200000 GHz Start Freq 2.44700000 GHz Stop Freq 2.47700000 GHz CF Step 3.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off

Mode 3: IEEE 802.11g Link Mode


2412



2437




2462




Mode 4: IEEE 802.11n 2.4GHz 20MHz Link Mode – ANT1


2412



2437




2462




Mode 4: IEEE 802.11n 2.4GHz 20MHz Link Mode – ANT2


2412



2437




2462




Mode 5: IEEE 802.11n 2.4GHz 40MHz Link Mode- ANT1


2422



2437






2452



Mode 5: IEEE 802.11n 2.4GHz 40MHz Link Mode-- ANT2	
2422	Agilent R T Ch Freq 2.422 GHz Trig Free Occupied Bandwidth Ref 20 dBm #Atten 20 dB #Peak Log 10 dB/Offset 11.5 dB Center 2.422 GHz Span 50 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 5.18 ms (401 pts) Occupied Bandwidth 35.9669 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB Transmit Freq Error 30.709 kHz x dB Bandwidth 35.791 MHz Freq/Channel Center Freq 2.4220000 GHz Start Freq 2.3970000 GHz Stop Freq 2.4470000 GHz CF Step 5.0000000 MHz Auto Man Freq Offset 0.0000000 Hz Signal Track On Off
2437	Agilent R T Ch Freq 2.437 GHz Trig Free Occupied Bandwidth Ref 20 dBm #Atten 20 dB #Peak Log 10 dB/Offset 11.5 dB Center 2.437 GHz Span 50 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 5.18 ms (401 pts) Occupied Bandwidth 35.8938 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB Transmit Freq Error 63.357 kHz x dB Bandwidth 33.951 MHz Freq/Channel Center Freq 2.4370000 GHz Start Freq 2.4120000 GHz Stop Freq 2.4620000 GHz CF Step 5.0000000 MHz Auto Man Freq Offset 0.0000000 Hz Signal Track On Off
2452	Agilent R T Ch Freq 2.452 GHz Trig Free Occupied Bandwidth Ref 20 dBm #Atten 20 dB #Peak Log 10 dB/Offset 11.5 dB Center 2.452 GHz Span 50 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 5.18 ms (401 pts) Occupied Bandwidth 36.0198 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB Transmit Freq Error 6.159 kHz x dB Bandwidth 35.598 MHz Freq/Channel Center Freq 2.4520000 GHz Start Freq 2.4270000 GHz Stop Freq 2.4770000 GHz CF Step 5.0000000 MHz Auto Man Freq Offset 0.0000000 Hz Signal Track On Off


99 % Occupied Bandwidth

Mode 2: IEEE 802.11b Link Mode


2412	 Agilent R T Ch Freq 2.412 GHz Trig Free Occupied Bandwidth Ref 20 dBm #Atten 20 dB #Samp Log 10 dB/ Offst 11.5 dB Center 2.412 GHz Span 30 MHz #Res BW 300 kHz #VBW 1 MHz Sweep 4 ms (401 pts) Occupied Bandwidth 15.0029 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB Transmit Freq Error 9.131 kHz x dB Bandwidth 10.152 MHz* Freq/Channel Center Freq 2.41200000 GHz Start Freq 2.39700000 GHz Stop Freq 2.42700000 GHz CF Step 3.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off
2437	 Agilent R T Ch Freq 2.437 GHz Trig Free Occupied Bandwidth Ref 20 dBm #Atten 20 dB #Samp Log 10 dB/ Offst 11.5 dB Center 2.437 GHz Span 30 MHz #Res BW 300 kHz #VBW 1 MHz Sweep 4 ms (401 pts) Occupied Bandwidth 15.0106 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB Transmit Freq Error 6.908 kHz x dB Bandwidth 10.129 MHz* Freq/Channel Center Freq 2.43700000 GHz Start Freq 2.42200000 GHz Stop Freq 2.45200000 GHz CF Step 3.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off
2462	 Agilent R T Ch Freq 2.462 GHz Trig Free Occupied Bandwidth Ref 20 dBm #Atten 20 dB #Samp Log 10 dB/ Offst 11.5 dB Center 2.462 GHz Span 30 MHz #Res BW 300 kHz #VBW 1 MHz Sweep 4 ms (401 pts) Occupied Bandwidth 15.0232 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB Transmit Freq Error -6.397 kHz x dB Bandwidth 10.087 MHz* Freq/Channel Center Freq 2.46200000 GHz Start Freq 2.44700000 GHz Stop Freq 2.47700000 GHz CF Step 3.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off

Mode 3: IEEE 802.11g Link Mode


2412



2437




2462




Mode 4: IEEE 802.11n 2.4GHz 20MHz Link Mode –ANT1


2412



2437




2462




Mode 4: IEEE 802.11n 2.4GHz 20MHz Link Mode –ANT2


2412



2437




2462




Mode 5: IEEE 802.11n 2.4GHz 40MHz Link Mode – ANT1


2422



2437




2452




Mode 5: IEEE 802.11n 2.4GHz 40MHz Link Mode – ANT2


2422



2437



2452




8 Maximum Power Density Measurement

8.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

8.2. Test Setup



8.3. Test Instruments

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Spectrum Analyzer	Agilent	E4445A	MY45300744	12/19/2012	(2)
Test Site	ATL	TE05	TE05	N.C.R.	-----

Remark: (1) Calibration period 1 year. (2) Calibration period 2 years. (3) Calibration period 3 years.

Note: N.C.R. = No Calibration Request.

8.4. Test Procedure

The EUT was setup to ANSI C63.4, 2009; tested to DTS test procedure of KDB558074D01 for compliance to FCC 47CFR 15.247 requirements.

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

8.5. Test Result

Model Number	RE300B1-2T2R		
Test Item	Maximum Power Density		
Test Mode	Mode 2: IEEE 802.11b Link Mode		
Date of Test	09/15/2014	Test Site	TE05
Frequency (MHz)	Reading (dBm/3KHz)		Limit (dBm)
2412	-9.78		< 8
2437	-8.64		< 8
2462	-8.68		< 8

Model Number	RE300B1-2T2R		
Test Item	Maximum Power Density		
Test Mode	Mode 3: IEEE 802.11g Link Mode		
Date of Test	09/15/2014	Test Site	TE05
Frequency (MHz)	Reading (dBm/3KHz)		Limit (dBm)
2412	-12.44		< 8
2437	-12.49		< 8
2462	-12.22		< 8

Model Number	RE300B1-2T2R		
Test Item	Maximum Power Density		
Test Mode	Mode 4: IEEE 802.11n 2.4GHz 20MHz Link Mode		
Date of Test	09/15/2014	Test Site	TE05
Frequency (MHz)	Reading (dBm/3KHz)		
	ANT-1	ANT-2	ANT1 + 2
2412	-13.55	-14.13	-10.82
2437	-13.91	-13.39	-10.63
2462	-13.35	-14.16	-10.73


Model Number	RE300B1-2T2R			
Test Item	Maximum Power Density			
Test Mode	Mode 5: IEEE 802.11n 2.4GHz 40MHz Link Mode			
Date of Test	09/15/2014	Test Site	TE05	
Frequency (MHz)	Reading (dBm/3KHz)			Limit (dBm)
	ANT-1	ANT-2	ANT1 + 2	
2422	-17.35	-17.24	-14.28	< 8
2437	-15.93	-15.29	-12.59	< 8
2452	-15.71	-14.68	-12.15	< 8

8.6. Test Graphs


Mode 2: IEEE 802.11b Link Mode	
2412	Agilent R T Ref 20 dBm #Atten 20 dB Mkr1 2.41146 GHz -9.78 dBm Peak Log 10 dB/Offst 11.5 dB DI 8.0 dBm M1 S2 S3 FC AA Center 2.412 GHz Span 16.5 MHz #Res BW 3 kHz #VBW 10 kHz Sweep 1.887 s (401 pts) Freq/Channel Center Freq 2.41200000 GHz Start Freq 2.40375000 GHz Stop Freq 2.42025000 GHz CF Step 1.65000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off
2437	Agilent R T Ref 20 dBm #Atten 20 dB Mkr1 2.43601 GHz -8.636 dBm Peak Log 10 dB/Offst 11.5 dB DI 8.0 dBm M1 S2 S3 FC AA Center 2.437 GHz Span 16.5 MHz #Res BW 3 kHz #VBW 10 kHz Sweep 1.887 s (401 pts) Freq/Channel Center Freq 2.43700000 GHz Start Freq 2.42875000 GHz Stop Freq 2.44525000 GHz CF Step 1.65000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off
2462	Agilent R T Ref 20 dBm #Atten 20 dB Mkr1 2.46720 GHz -8.683 dBm Peak Log 10 dB/Offst 11.5 dB DI 8.0 dBm M1 S2 S3 FC AA Center 2.462 GHz Span 16.5 MHz #Res BW 3 kHz #VBW 10 kHz Sweep 1.887 s (401 pts) Freq/Channel Center Freq 2.46200000 GHz Start Freq 2.45375000 GHz Stop Freq 2.47025000 GHz CF Step 1.65000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off

Mode 3: IEEE 802.11g Link Mode


2412



2437




2462




Mode 4: IEEE 802.11n 2.4GHz 20MHz Link Mode – ANT1


2412



2437




2462




Mode 4: IEEE 802.11n 2.4GHz 20MHz Link Mode – ANT2


2412



2437




2462




Mode 5: IEEE 802.11n 2.4GHz 40MHz Link Mode – ANT1


2422



2437




2452




Mode 5: IEEE 802.11n 2.4GHz 40MHz Link Mode – ANT2


2422



2437



2452




9 Out of Band Conducted Emissions Measurement

9.1. Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

9.2. Test Setup



9.3. Test Instruments

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Spectrum Analyzer	Agilent	E4445A	MY45300744	12/19/2012	(2)
Spectrum Analyzer	Agilent	E4408B	MY45107753	07/24/2014	(1)
Test Site	ATL	TE05	TE05	N.C.R.	-----

Remark: (1) Calibration period 1 year. (2) Calibration period 2 years. (3) Calibration period 3 years.

Note: N.C.R. = No Calibration Request.

9.4. Test Procedure

In any 100 kHz bandwidth outside the EUT pass band, the RF power produced by the modulation products of the spreading sequence, the information sequence, and the carrier frequency shall be at least 20 dB below that of the maximum in-band 100 kHz emission, antenna output of the EUT was coupled directly to spectrum analyzer; if an external attenuator and/or cable was used, these losses are compensated for with the analyzer OFFSET function. All other types of emissions from the EUT shall meet the general limits for radiated frequencies outside the pass band. The test was performed at 3 channels.


9.5. Test Graphs

Reference level


Mode 2: IEEE 802.11b Link Mode	
2412	
2437	
2462	

Mode 3: IEEE 802.11g Link Mode


2412



2437




2462




Mode 4: IEEE 802.11n 2.4GHz 20MHz Link Mode – ANT1


2412



2437




2462




Mode 4: IEEE 802.11n 2.4GHz 20MHz Link Mode – ANT2


2412



2437




2462




Mode 5: IEEE 802.11n 2.4GHz 40MHz Link Mode – ANT1


2422



2437




2452




Mode 5: IEEE 802.11n 2.4GHz 40MHz Link Mode – ANT2


2422



2437




2452




Out of Band Conducted Emissions

Mode 2: IEEE 802.11b Link Mode


2412



2437




2462




Mode 3: IEEE 802.11g Link Mode


2412



2437




2462




Mode 4: IEEE 802.11n 2.4GHz 20MHz Link Mode – ANT1


2412



2437




2462




Mode 4: IEEE 802.11n 2.4GHz 20MHz Link Mode – ANT2


2412



2437




2462




Mode 5: IEEE 802.11n 2.4GHz 40MHz Link Mode – ANT1


2422



2437




2452




Mode 5: IEEE 802.11n 2.4GHz 40MHz Link Mode – ANT2


2422



2437




2452




Conducted Band Edge

Mode 2: IEEE 802.11b Link Mode

2412




2462




Mode 3: IEEE 802.11g Link Mode

2412




2462




Mode 4: IEEE 802.11n 2.4GHz 20MHz Link Mode – ANT1

2412




2462




Mode 4: IEEE 802.11n 2.4GHz 20MHz Link Mode – ANT2

2412




2462




Mode 5: IEEE 802.11n 2.4GHz 40MHz Link Mode – ANT1

2422




2452




Mode 5: IEEE 802.11n 2.4GHz 40MHz Link Mode – ANT2

2422



2452




10 Band Edges Measurement

10.1.Limit

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

10.2.Test Setup



10.3.Test Instruments

3 Meter Chamber					
Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
RF Pre-selector	Agilent	N9039A	MY46520256	01/10/2014	(1)
Spectrum Analyzer	Agilent	E4446A	MY46180578	01/10/2014	(1)
Pre Amplifier	Agilent	8449B	3008A02237	02/21/2014	(1)
Pre Amplifier	Agilent	8447D	2944A10961	02/21/2014	(1)
Horn Antenna (1~18GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA9120D	9120D-550	06/11/2014	(1)
Test Site	ATL	TE01	888001	08/28/2014	(1)

Remark: (1) Calibration period 1 year. (2) Calibration period 2 years. (3) Calibration period 3 years.

Note: N.C.R. = No Calibration Request.

10.4. Test Procedure

The EUT was setup to ANSI C63.4, 2009; tested to DTS test procedure of KDB558074D01 for compliance to FCC 47CFR 15.247 requirements.

The emissions on the harmonics frequencies, the limits, and the margin of compliance are presented. These tests were made when the transmitter was in full radiated power. The additional test was performed to show compliance with the requirement at the band-edge frequency 2483.5 MHz and up to 2500 MHz and at 2390.0 MHz.

The transmitter was configured with the worst case antenna and setup to transmit at the highest channel. Then the field strength was measured at 2483.5 MHz.

The transmitter was then configured with the worst case antenna and setup to transmit at the lowest channel. Then the field strength was measured at 2390.0 MHz. These tests were performed at 4 different bit rates.

For measurements the resolution bandwidth is set to 1 MHz, and then the video bandwidth is set to 1 MHz for peak measurements and 10 Hz for average measurements.

10.5. Test Result

Standard:		FCC Part 15C		Test Distance:		3m	
Test item:		Radiated Emission		Power:		AC 120V/60Hz	
Model Number:		RE300B1-2T2R		Temp.(°C)/Hum.(%RH):		26(°C)/60%RH	
Mode:		2		Date:		09/10/2014	
Frequency:		2412 MHz		Test By:		Eric Ou Yang	
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2388.210	52.84	-1.96	50.88	74.00	-23.12	2388.210	H
2390.000	51.77	-1.94	49.83	74.00	-24.17	2390.000	H
2387.990	51.30	-1.96	49.34	74.00	-24.66	2387.990	V
2390.000	48.74	-1.94	46.80	74.00	-27.20	2390.000	V

Standard:		FCC Part 15C		Test Distance:		3m	
Test item:		Radiated Emission		Power:		AC 120V/60Hz	
Model Number:		RE300B1-2T2R		Temp.(°C)/Hum.(%RH):		26(°C)/60%RH	
Mode:		2		Date:		09/10/2014	
Frequency:		2462 MHz		Test By:		Eric Ou Yang	
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2483.500	50.10	-1.52	48.58	74.00	-25.42	2483.500	H
2487.680	52.44	-1.50	50.94	74.00	-23.06	2487.680	H
2483.500	48.32	-1.52	46.80	74.00	-27.20	2483.500	V
2490.240	51.57	-1.48	50.09	74.00	-23.91	2490.240	V

Standard:		FCC Part 15C		Test Distance:		3m	
Test item:		Radiated Emission		Power:		AC 120V/60Hz	
Model Number:		RE300B1-2T2R		Temp.(°C)/Hum.(%RH):		26(°C)/60%RH	
Mode:		3		Date:		09/10/2014	
Frequency:		2412 MHz		Test By:		Eric Ou Yang	
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2387.990	65.72	-1.96	63.76	74.00	-10.24	peak	H
2387.990	50.36	-1.96	48.40	54.00	-5.60	AVG	H
2390.000	66.57	-1.94	64.63	74.00	-9.37	peak	H
2390.000	52.77	-1.94	50.83	54.00	-3.17	AVG	H
2388.320	60.30	-1.96	58.34	74.00	-15.66	peak	V
2388.320	44.94	-1.96	42.98	54.00	-11.02	AVG	V
2390.000	58.29	-1.94	56.35	74.00	-17.65	peak	V
2390.000	47.27	-1.94	45.33	54.00	-8.67	AVG	V

Standard:		FCC Part 15C		Test Distance:		3m	
Test item:		Radiated Emission		Power:		AC 120V/60Hz	
Model Number:		RE300B1-2T2R		Temp.(°C)/Hum.(%RH):		26(°C)/60%RH	
Mode:		3		Date:		09/10/2014	
Frequency:		2462 MHz		Test By:		Eric Ou Yang	
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2483.500	62.35	-1.52	60.83	74.00	-13.17	peak	H
2483.500	51.47	-1.52	49.95	54.00	-4.05	AVG	H
2483.680	65.87	-1.52	64.35	74.00	-9.65	peak	H
2483.680	51.34	-1.52	49.82	54.00	-4.18	AVG	H
2483.500	56.52	-1.52	55.00	74.00	-19.00	peak	V
2483.500	44.79	-1.52	43.27	54.00	-10.73	AVG	V
2485.200	58.46	-1.51	56.95	74.00	-17.05	peak	V
2485.200	43.41	-1.51	41.90	54.00	-12.10	AVG	V

Standard:	FCC Part 15C	Test Distance:	3m				
Test item:	Radiated Emission	Power:	AC 120V/60Hz				
Model Number:	RE300B1-2T2R	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH				
Mode:	4	Date:	09/10/2014				
Frequency:	2412 MHz	Test By:	Eric Ou Yang				
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2389.200	64.81	-1.96	62.85	74.00	-11.15	peak	H
2389.200	49.15	-1.96	47.19	54.00	-6.81	AVG	H
2390.000	63.70	-1.94	61.76	74.00	-12.24	peak	H
2390.000	50.23	-1.94	48.29	54.00	-5.71	AVG	H
2388.980	56.71	-1.96	54.75	74.00	-19.25	peak	V
2388.980	43.29	-1.96	41.33	54.00	-12.67	AVG	V
2390.000	58.52	-1.94	56.58	74.00	-17.42	peak	V
2390.000	44.88	-1.94	42.94	54.00	-11.06	AVG	V

Standard:	FCC Part 15C	Test Distance:	3m				
Test item:	Radiated Emission	Power:	AC 120V/60Hz				
Model Number:	RE300B1-2T2R	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH				
Mode:	4	Date:	09/10/2014				
Frequency:	2462 MHz	Test By:	Eric Ou Yang				
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2483.500	62.62	-1.52	61.10	74.00	-12.90	peak	H
2483.500	49.10	-1.52	47.58	54.00	-6.42	AVG	H
2483.680	64.25	-1.52	62.73	74.00	-11.27	peak	H
2483.680	49.31	-1.52	47.79	54.00	-6.21	AVG	H
2483.500	56.57	-1.52	55.05	74.00	-18.95	peak	V
2483.500	45.12	-1.52	43.60	54.00	-10.40	AVG	V
2484.320	58.46	-1.51	56.95	74.00	-17.05	peak	V
2484.320	43.59	-1.51	42.08	54.00	-11.92	AVG	V

Standard:	FCC Part 15C	Test Distance:	3m				
Test item:	Radiated Emission	Power:	AC 120V/60Hz				
Model Number:	RE300B1-2T2R	Temp.(℃)/Hum.(%RH):	26(℃)/60%RH				
Mode:	5	Date:	09/10/2014				
Frequency:	2422 MHz	Test By:	Eric Ou Yang				
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2386.800	66.83	-1.96	64.87	74.00	-9.13	peak	H
2386.800	50.43	-1.96	48.47	54.00	-5.53	AVG	H
2390.000	65.60	-1.94	63.66	74.00	-10.34	peak	H
2390.000	52.06	-1.94	50.12	54.00	-3.88	AVG	H
2386.440	60.53	-1.97	58.56	74.00	-15.44	peak	V
2386.440	45.02	-1.97	43.05	54.00	-10.95	AVG	V
2390.000	57.75	-1.94	55.81	74.00	-18.19	peak	V
2390.000	46.62	-1.94	44.68	54.00	-9.32	AVG	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	RE300B1-2T2R			Temp.(℃)/Hum.(%RH):	26(℃)/60%RH		
Mode:	5			Date:	09/10/2014		
Frequency:	2452 MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2483.500	62.65	-1.52	61.13	74.00	-12.87	peak	H
2483.500	50.86	-1.52	49.34	54.00	-4.66	AVG	H
2483.800	64.18	-1.52	62.66	74.00	-11.34	peak	H
2483.800	51.00	-1.52	49.48	54.00	-4.52	AVG	H
2483.500	56.36	-1.52	54.84	74.00	-19.16	peak	V
2483.500	45.52	-1.52	44.00	54.00	-10.00	AVG	V
2485.100	58.17	-1.51	56.66	74.00	-17.34	peak	V
2485.100	44.22	-1.51	42.71	54.00	-11.29	AVG	V

11 Antenna Measurement

11.1.Limit

For intentional device, according to 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And According to 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

11.2.Antenna Connector Construction

The antenna used in this product is PCB Antenna. And the maximum Gain of those antenna are
ANT-1 :2.73 dBi / ANT-2 :3.67 dBi