



April 29, 2016

TUV SUD BABT
Octagon House, Concorde Way
Segensworth Rd N, Fareham
PO15 5RL

Attention: Director of Certification

RE: Analysis of RF Exposure for Portable and Mobile use per KDB 447498 D01 Mobile Portable RF Exposure v05r02 and RSS-102 Issue 5 March 2015.

FCC ID: XM5-SMG2SMT

1. Limits

Limits for General Population/Uncontrolled Exposure (Title 47 Subpart J §2.1091 and KDB 447498 D01 referring to limits under §1.1310)

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Electric Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time (minutes)
0.3 - 1.34	614	1.63	*(100)	30
1.34 - 30	824/f	2.19/f	*(180/f ²)	30
30 - 300	27.5	0.073	0.2	30
300 - 1500	-	-	f/1500	30
1500 - 100,000	-	-	1.0	30

f = frequency in MHz

**Plane-wave equivalent power density*



2. Mobile MPE Calculation Summary using a 20cm separation distance:

Mode (Worst Case)	Output Power	Power Density (mW/cm ²)
Mobile Satellite Service	2.93 watt	0.3696
WLAN	0.0794 watt	0.0354

3. Simultaneous Transmission MPE:

Transmitter type	MPE (mW/cm ²)	FCC Limit (mW/cm ²)	FCC MPE ratio (MPE/Limit)
Mobile Satellite Service	0.3696	1	0.3696
WLAN	0.0354	1	0.0354
Sum of the ratios (should be <1.0)			0.405



4. *Mobile MPE Calculation using a 100cm separation distance (Mobile Satellite Service):*

Using Power Density formula:

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to isotropic

R = distance to the center of radiation of the antenna


Maximum peak output power at antenna input terminal:	34.67	(dBm)
Maximum peak output power at antenna input terminal:	2930.89	(mW)
Antenna gain(typical):	12	(dBi)
Maximum antenna gain:	15.849	(numeric)
Prediction distance:	100	(cm)
Source Based Time Average Duty Cycle:	100	(%)
Prediction frequency:	1643.482	(MHz)
FCC MPE limit for uncontrolled exposure at prediction frequency:	1.0	(mW/cm ²)
Power density at prediction frequency:	0.3696	(mW/cm ²)
Power density at prediction frequency:	3.696	(W/m ²)
FCC Margin of Compliance:	-4.32	(dB)



5. Mobile MPE Calculation using a 20cm separation distance (WLAN):

Maximum peak output power at antenna input terminal:	19.0	(dBm)
Maximum peak output power at antenna input terminal:	79.43	(mW)
Antenna gain(typical):	3.5	(dBi)
Maximum antenna gain:	2.239	(numeric)
Prediction distance:	20	(cm)
Source Based Time Average Duty Cycle:	100	(%)
Prediction frequency:	2412	(MHz)
FCC MPE limit for uncontrolled exposure at prediction frequency:	1.000	(mW/cm ²)
Power density at prediction frequency:	0.03538	(mW/cm ²)
Power density at prediction frequency:	0.354	(W/m ²)
FCC Margin of Compliance:	-14.51	(dB)

Sincerely,


Alex Chang

Name

Authorized Signatory

Title: Senior EMC/Wireless Test Engineer