



RF TEST REPORT

Applicant	Quectel Wireless Solutions Co., Ltd
FCC ID	XMR201909EG95NAX
Product	LTE Module
Brand	Quectel
Model	EG95-NAX
Report No.	R1907A0407-R2
Issue Date	November 19, 2019

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC CFR47 Part 2 (2018)/ FCC CFR 47 Part 24E (2018)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Performed by: Peng Tao

Approved by: Kai Xu

TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000



TABLE OF CONTENT

1. Test Laboratory	4
1.1. Notes of the test report	4
1.2. Testing Location	4
2. General Description of Equipment under Test	5
2.1. Applicant and Manufacturer Information	5
2.2. General information	5
3. Applied Standards	6
4. Test Configuration	7
5. Test Case Results	8
5.1. RF Power Output and Effective Radiated Power	8
5.2. Occupied Bandwidth	16
5.3. Band Edge Compliance	25
5.4. Peak-to-Average Power Ratio (PAPR)	34
5.5. Frequency Stability	36
5.6. Spurious Emissions at Antenna Terminals	39
5.7. Radiates Spurious Emission	46
6. Main Test Instruments	51

Summary of measurement results

No.	Test Case	Clause in FCC rules	Verdict
1	RF power output and Effective Radiated Power	2.1046 24.232(c)	PASS
2	Occupied Bandwidth	2.1049	PASS
3	Band Edge Compliance	2.1051 /24.238(a)	PASS
4	Peak-to-Average Power Ratio	24.232/KDB 971168 D01(5.7)	PASS
5	Frequency Stability	2.1055 / 24.235	PASS
6	Spurious Emissions at Antenna Terminals	2.1051 / 24.238(a)	PASS
7	Radiates Spurious Emission	2.1053 / 24.238(a)	PASS
Note: PASS: The EUT complies with the essential requirements in the standard. FAIL: The EUT does not comply with the essential requirements in the standard.			
Date of Testing: October 22, 2019 ~ November 9, 2019			



1. Test Laboratory

1.1. Notes of the test report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2. Testing Location

Company: TA Technology (Shanghai) Co., Ltd.
Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <http://www.ta-shanghai.com>
E-mail: xukai@ta-shanghai.com

2. General Description of Equipment under Test

2.1. Applicant and Manufacturer Information

Applicant	Quectel Wireless Solutions Co., Ltd
Applicant address	Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, China 200233
Manufacturer	Quectel Wireless Solutions Co., Ltd
Manufacturer address	Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, China 200233

2.2. General information

EUT Description			
Model	EG95-NAX		
IMEI	865026040005000		
Hardware Version	R1.0		
Software Version	EG95NAXGAR07A01M1G		
Power Supply	External Power Supply		
Antenna Type	The EUT don't have standard Antenna, The Antenna used for testing in this report is the after-market accessory (Dipole Antenna)		
Antenna Gain	4dBi		
Test Mode(s)	LTE Band 25;		
Test Modulation	(LTE)QPSK,16QAM		
LTE Category	4		
Maximum E.I.R.P	LTE Band 25:	25.24dBm	
Rated Power Supply Voltage	3.8V		
Extreme Voltage	Minimum: 3.3V Maximum: 4.3V		
Extreme Temperature	Lowest: -40°C Highest: +85°C		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	LTE Band 25	1850 ~ 1915	1930 ~ 1995
Note: 1. The information of the EUT is declared by the manufacturer.			

3. Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

Test standards:

FCC CFR 47 Part 24E (2018)

ANSI C63.26 (2015)

Reference standard:

FCC CFR47 Part 2 (2018)

KDB 971168 D01 Power Meas License Digital Systems v03r01

4. Test Configuration

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes. EUT stand-up position (Z axis), lie-down position (X, Y axis). Receiver antenna polarization (horizontal and vertical), the worst emission was found in position (X axis, vertical polarization) and the worst case was recorded.

All mode and data rates and positions and RB size and modulations were investigated.

Subsequently, only the worst case emissions are reported.

The following testing in LTE is set based on the maximum RF Output Power.

Test modes are chosen to be reported as the worst case configuration below for LTE Band 25:

Test items	Bandwidth (MHz)						Modulation		RB			Test Channel		
	1.4	3	5	10	15	20	QPSK	16QAM	1	50%	100%	L	M	H
RF power output	O	O	O	O	O	O	O	O	O	O	O	O	O	O
Effective Isotropic Radiated power	O	O	O	O	O	O	O	O	O	O	O	O	O	O
Occupied Bandwidth	O	O	O	O	O	O	O	O	-	-	O	O	O	O
Band Edge Compliance	O	O	O	O	O	O	O	O	O	-	O	O	-	O
Peak-to-Average Power Ratio	O	O	O	O	O	O	O	O	-	-	O	O	O	O
Frequency Stability	-	-	-	-	O	O	O	O	-	-	O	-	O	-
Conducted Spurious Emissions	O	O	O	O	O	O	O	-	O	-	-	O	O	O
Radiates Spurious Emission	O	-	O	-	-	O	O	-	O	-	-	-	O	-
Note	1. The mark "O" means that this configuration is chosen for testing. 2. The mark "-" means that this configuration is not testing.													

5. Test Case Results

5.1.RF Power Output and Effective Radiated Power

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement


During the process of the testing, The EUT is controlled by the Base Station Simulator to ensure max power transmission and proper modulation.

The testing follows FCC KDB 971168 v03r01 Section 5.8 and ANSI C63.26 (2015).


- Connect the equipment as illustrated. Mount the equipment with the manufacturer specified antenna in a vertical orientation on a manufacturer specified mounting surface located on a non-conducting rotating platform of a RF anechoic chamber (preferred) or a standard radiation site.
- Key the transmitter, then rotate the EUT 360° azimuthally and record spectrum analyzer power level (LVL) measurements at angular increments that are sufficiently small to permit resolution of all peaks. If a standard radiation test site is used, raise and lower the test antenna to obtain a maximum reading at each angular increment. (Note: several batteries may be needed to offset the effect of battery voltage droop, which should not exceed 5% of the manufactured specified battery voltage during transmission).
- Replace the transmitter under test with a vertically polarized half-wave dipole (or an antenna whose gain is known relative to an ideal half-wave dipole). The center of the antenna should be at the same location as the center of the antenna under test.
- Connect the antenna to a signal generator with a known output power and record the path loss (in dB) as LOSS. If a standard radiation test site is used, raise and lower the test antenna to obtain a maximum reading. $LOSS = \text{Generator Output Power (dBm)} - \text{Analyzer reading (dBm)}$
- Determine the effective radiated output power at each angular position from the readings in steps b) and d) using the following equation: $ERP \text{ (dBm)} = LVL \text{ (dBm)} + LOSS \text{ (dB)}$
- The maximum ERP is the maximum value determined in the preceding step.
- When calculating ERP, in addition to knowing the antenna radiation and matching characteristics, it is necessary to know the loss values of all elements (e.g.transmission line attenuation, mismatches, filters, combiners) interposed between the point where transmitter output power is measured, and the point where power is applied to the antenna. ERP can then be calculated as follows:
 $EIRP \text{ (dBm)} = \text{Output Power (dBm)} - \text{Losses (dB)} + \text{Antenna Gain (dBi)}$
where:dBd refers to gain relative to an ideal dipole.
 $EIRP \text{ (dBm)} = ERP \text{ (dBm)} + 2.15 \text{ (dB.)}$

The RB allocation refers to section 5.1, using the maximum output power configuration.

Test Setup



The loss between RF output port of the EUT and the input port of the tester has been taken into consideration.



Limits

No specific RF power output requirements in part 2.1046.

Rule Part 24.232(c) Mobile and portable stations are limited to 2 watts EIRP.

Rule Part 24.232(e) Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.

Limit	$\leq 2 \text{ W}$ (33 dBm)
-------	-----------------------------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 0.4 \text{ dB}$ for RF power output, $k = 2$, $U = 1.19 \text{ dB}$ for EIRP.



Test Results

Band	Bandwidth (MHz)	UL Channel	RB Size	RB Position	Modulation	Power (dBm)	EIRP
LTE Band25	1.4	26047	1	#0	QPSK	23.78	25.03
LTE Band25	1.4	26047	1	#Mid	QPSK	23.87	25.12
LTE Band25	1.4	26047	1	#Max	QPSK	23.72	24.97
LTE Band25	1.4	26047	3	#0	QPSK	23.60	24.85
LTE Band25	1.4	26047	3	#Mid	QPSK	23.60	24.85
LTE Band25	1.4	26047	3	#Max	QPSK	23.60	24.85
LTE Band25	1.4	26047	6	#0	QPSK	22.61	23.86
LTE Band25	1.4	26047	1	#0	16QAM	22.53	23.78
LTE Band25	1.4	26047	1	#Mid	16QAM	22.75	24.00
LTE Band25	1.4	26047	1	#Max	16QAM	22.67	23.92
LTE Band25	1.4	26047	3	#0	16QAM	22.74	23.99
LTE Band25	1.4	26047	3	#Mid	16QAM	22.74	23.99
LTE Band25	1.4	26047	3	#Max	16QAM	22.78	24.03
LTE Band25	1.4	26047	6	#0	16QAM	21.40	22.65
LTE Band25	1.4	26365	1	#0	QPSK	23.47	24.72
LTE Band25	1.4	26365	1	#Mid	QPSK	23.71	24.96
LTE Band25	1.4	26365	1	#Max	QPSK	23.57	24.82
LTE Band25	1.4	26365	3	#0	QPSK	23.44	24.69
LTE Band25	1.4	26365	3	#Mid	QPSK	23.43	24.68
LTE Band25	1.4	26365	3	#Max	QPSK	23.54	24.79
LTE Band25	1.4	26365	6	#0	QPSK	22.72	23.97
LTE Band25	1.4	26365	1	#0	16QAM	22.71	23.96
LTE Band25	1.4	26365	1	#Mid	16QAM	22.97	24.22
LTE Band25	1.4	26365	1	#Max	16QAM	23.00	24.25
LTE Band25	1.4	26365	3	#0	16QAM	22.93	24.18
LTE Band25	1.4	26365	3	#Mid	16QAM	22.73	23.98
LTE Band25	1.4	26365	3	#Max	16QAM	22.70	23.95
LTE Band25	1.4	26365	6	#0	16QAM	21.67	22.92
LTE Band25	1.4	26683	1	#0	QPSK	23.47	24.72
LTE Band25	1.4	26683	1	#Mid	QPSK	23.46	24.71
LTE Band25	1.4	26683	1	#Max	QPSK	23.45	24.70
LTE Band25	1.4	26683	3	#0	QPSK	23.49	24.74
LTE Band25	1.4	26683	3	#Mid	QPSK	23.48	24.73
LTE Band25	1.4	26683	3	#Max	QPSK	23.48	24.73
LTE Band25	1.4	26683	6	#0	QPSK	22.62	23.87
LTE Band25	1.4	26683	1	#0	16QAM	22.12	23.37
LTE Band25	1.4	26683	1	#Mid	16QAM	22.30	23.55
LTE Band25	1.4	26683	1	#Max	16QAM	22.00	23.25
LTE Band25	1.4	26683	3	#0	16QAM	22.73	23.98



LTE Band25	1.4	26683	3	#Mid	16QAM	22.72	23.97
LTE Band25	1.4	26683	3	#Max	16QAM	22.69	23.94
LTE Band25	1.4	26683	6	#0	16QAM	21.75	23.00
LTE Band25	3	26055	1	#0	QPSK	23.55	24.80
LTE Band25	3	26055	1	#Mid	QPSK	23.58	24.83
LTE Band25	3	26055	1	#Max	QPSK	23.55	24.80
LTE Band25	3	26055	8	#0	QPSK	22.74	23.99
LTE Band25	3	26055	8	#Mid	QPSK	22.74	23.99
LTE Band25	3	26055	8	#Max	QPSK	22.69	23.94
LTE Band25	3	26055	15	#0	QPSK	22.66	23.91
LTE Band25	3	26055	1	#0	16QAM	22.72	23.97
LTE Band25	3	26055	1	#Mid	16QAM	22.59	23.84
LTE Band25	3	26055	1	#Max	16QAM	22.57	23.82
LTE Band25	3	26055	8	#0	16QAM	21.45	22.70
LTE Band25	3	26055	8	#Mid	16QAM	21.46	22.71
LTE Band25	3	26055	8	#Max	16QAM	21.53	22.78
LTE Band25	3	26055	15	#0	16QAM	21.44	22.69
LTE Band25	3	26365	1	#0	QPSK	23.62	24.87
LTE Band25	3	26365	1	#Mid	QPSK	23.64	24.89
LTE Band25	3	26365	1	#Max	QPSK	23.56	24.81
LTE Band25	3	26365	8	#0	QPSK	22.77	24.02
LTE Band25	3	26365	8	#Mid	QPSK	22.77	24.02
LTE Band25	3	26365	8	#Max	QPSK	22.68	23.93
LTE Band25	3	26365	15	#0	QPSK	22.63	23.88
LTE Band25	3	26365	1	#0	16QAM	23.17	24.42
LTE Band25	3	26365	1	#Mid	16QAM	23.34	24.59
LTE Band25	3	26365	1	#Max	16QAM	23.36	24.61
LTE Band25	3	26365	8	#0	16QAM	22.01	23.26
LTE Band25	3	26365	8	#Mid	16QAM	22.01	23.26
LTE Band25	3	26365	8	#Max	16QAM	21.92	23.17
LTE Band25	3	26365	15	#0	16QAM	21.56	22.81
LTE Band25	3	26675	1	#0	QPSK	23.51	24.76
LTE Band25	3	26675	1	#Mid	QPSK	23.85	25.10
LTE Band25	3	26675	1	#Max	QPSK	23.57	24.82
LTE Band25	3	26675	8	#0	QPSK	22.67	23.92
LTE Band25	3	26675	8	#Mid	QPSK	22.68	23.93
LTE Band25	3	26675	8	#Max	QPSK	22.86	24.11
LTE Band25	3	26675	15	#0	QPSK	22.77	24.02
LTE Band25	3	26675	1	#0	16QAM	22.28	23.53
LTE Band25	3	26675	1	#Mid	16QAM	22.44	23.69
LTE Band25	3	26675	1	#Max	16QAM	22.50	23.75
LTE Band25	3	26675	8	#0	16QAM	21.80	23.05
LTE Band25	3	26675	8	#Mid	16QAM	21.81	23.06



LTE Band25	3	26675	8	#Max	16QAM	21.94	23.19
LTE Band25	3	26675	15	#0	16QAM	21.57	22.82
LTE Band25	5	26065	1	#0	QPSK	23.50	24.75
LTE Band25	5	26065	1	#Mid	QPSK	23.61	24.86
LTE Band25	5	26065	1	#Max	QPSK	23.54	24.79
LTE Band25	5	26065	12	#0	QPSK	22.64	23.89
LTE Band25	5	26065	12	#Mid	QPSK	22.64	23.89
LTE Band25	5	26065	12	#Max	QPSK	22.68	23.93
LTE Band25	5	26065	25	#0	QPSK	22.75	24.00
LTE Band25	5	26065	1	#0	16QAM	22.65	23.90
LTE Band25	5	26065	1	#Mid	16QAM	22.60	23.85
LTE Band25	5	26065	1	#Max	16QAM	22.50	23.75
LTE Band25	5	26065	12	#0	16QAM	21.53	22.78
LTE Band25	5	26065	12	#Mid	16QAM	21.53	22.78
LTE Band25	5	26065	12	#Max	16QAM	21.50	22.75
LTE Band25	5	26065	25	#0	16QAM	21.56	22.81
LTE Band25	5	26365	1	#0	QPSK	23.60	24.85
LTE Band25	5	26365	1	#Mid	QPSK	23.65	24.90
LTE Band25	5	26365	1	#Max	QPSK	23.68	24.93
LTE Band25	5	26365	12	#0	QPSK	22.76	24.01
LTE Band25	5	26365	12	#Mid	QPSK	22.76	24.01
LTE Band25	5	26365	12	#Max	QPSK	22.75	24.00
LTE Band25	5	26365	25	#0	QPSK	22.70	23.95
LTE Band25	5	26365	1	#0	16QAM	22.78	24.03
LTE Band25	5	26365	1	#Mid	16QAM	22.85	24.10
LTE Band25	5	26365	1	#Max	16QAM	22.88	24.13
LTE Band25	5	26365	12	#0	16QAM	21.45	22.70
LTE Band25	5	26365	12	#Mid	16QAM	21.45	22.70
LTE Band25	5	26365	12	#Max	16QAM	21.24	22.49
LTE Band25	5	26365	25	#0	16QAM	21.40	22.65
LTE Band25	5	26665	1	#0	QPSK	23.57	24.82
LTE Band25	5	26665	1	#Mid	QPSK	23.82	25.07
LTE Band25	5	26665	1	#Max	QPSK	23.51	24.76
LTE Band25	5	26665	12	#0	QPSK	22.70	23.95
LTE Band25	5	26665	12	#Mid	QPSK	22.66	23.91
LTE Band25	5	26665	12	#Max	QPSK	22.72	23.97
LTE Band25	5	26665	25	#0	QPSK	22.65	23.90
LTE Band25	5	26665	1	#0	16QAM	22.85	24.10
LTE Band25	5	26665	1	#Mid	16QAM	22.75	24.00
LTE Band25	5	26665	1	#Max	16QAM	22.51	23.76
LTE Band25	5	26665	12	#0	16QAM	21.57	22.82
LTE Band25	5	26665	12	#Mid	16QAM	21.56	22.81
LTE Band25	5	26665	12	#Max	16QAM	21.70	22.95



LTE Band25	5	26665	25	#0	16QAM	21.62	22.87
LTE Band25	10	26090	1	#0	QPSK	23.65	24.90
LTE Band25	10	26090	1	#Mid	QPSK	23.76	25.01
LTE Band25	10	26090	1	#Max	QPSK	23.63	24.88
LTE Band25	10	26090	25	#0	QPSK	22.81	24.06
LTE Band25	10	26090	25	#Mid	QPSK	22.71	23.96
LTE Band25	10	26090	25	#Max	QPSK	22.80	24.05
LTE Band25	10	26090	50	#0	QPSK	22.70	23.95
LTE Band25	10	26090	1	#0	16QAM	22.83	24.08
LTE Band25	10	26090	1	#Mid	16QAM	23.47	24.72
LTE Band25	10	26090	1	#Max	16QAM	22.72	23.97
LTE Band25	10	26090	25	#0	16QAM	21.79	23.04
LTE Band25	10	26090	25	#Mid	16QAM	21.79	23.04
LTE Band25	10	26090	25	#Max	16QAM	21.80	23.05
LTE Band25	10	26090	50	#0	16QAM	21.61	22.86
LTE Band25	10	26365	1	#0	QPSK	23.83	25.08
LTE Band25	10	26365	1	#Mid	QPSK	23.99	25.24
LTE Band25	10	26365	1	#Max	QPSK	23.80	25.05
LTE Band25	10	26365	25	#0	QPSK	22.74	23.99
LTE Band25	10	26365	25	#Mid	QPSK	22.74	23.99
LTE Band25	10	26365	25	#Max	QPSK	22.82	24.07
LTE Band25	10	26365	50	#0	QPSK	22.80	24.05
LTE Band25	10	26365	1	#0	16QAM	23.50	24.75
LTE Band25	10	26365	1	#Mid	16QAM	23.34	24.59
LTE Band25	10	26365	1	#Max	16QAM	23.27	24.52
LTE Band25	10	26365	25	#0	16QAM	21.90	23.15
LTE Band25	10	26365	25	#Mid	16QAM	21.80	23.05
LTE Band25	10	26365	25	#Max	16QAM	21.96	23.21
LTE Band25	10	26365	50	#0	16QAM	21.90	23.15
LTE Band25	10	26640	1	#0	QPSK	23.51	24.76
LTE Band25	10	26640	1	#Mid	QPSK	23.56	24.81
LTE Band25	10	26640	1	#Max	QPSK	23.55	24.80
LTE Band25	10	26640	25	#0	QPSK	22.79	24.04
LTE Band25	10	26640	25	#Mid	QPSK	22.75	24.00
LTE Band25	10	26640	25	#Max	QPSK	22.69	23.94
LTE Band25	10	26640	50	#0	QPSK	22.78	24.03
LTE Band25	10	26640	1	#0	16QAM	22.66	23.91
LTE Band25	10	26640	1	#Mid	16QAM	22.61	23.86
LTE Band25	10	26640	1	#Max	16QAM	22.41	23.66
LTE Band25	10	26640	25	#0	16QAM	21.81	23.06
LTE Band25	10	26640	25	#Mid	16QAM	21.82	23.07
LTE Band25	10	26640	25	#Max	16QAM	21.66	22.91
LTE Band25	10	26640	50	#0	16QAM	21.84	23.09



LTE Band25	15	26115	1	#0	QPSK	23.63	24.88
LTE Band25	15	26115	1	#Mid	QPSK	23.78	25.03
LTE Band25	15	26115	1	#Max	QPSK	23.64	24.89
LTE Band25	15	26115	36	#0	QPSK	22.75	24.00
LTE Band25	15	26115	36	#Mid	QPSK	22.73	23.98
LTE Band25	15	26115	36	#Max	QPSK	22.70	23.95
LTE Band25	15	26115	75	#0	QPSK	22.73	23.98
LTE Band25	15	26115	1	#0	16QAM	22.89	24.14
LTE Band25	15	26115	1	#Mid	16QAM	22.67	23.92
LTE Band25	15	26115	1	#Max	16QAM	22.73	23.98
LTE Band25	15	26115	36	#0	16QAM	21.66	22.91
LTE Band25	15	26115	36	#Mid	16QAM	21.66	22.91
LTE Band25	15	26115	36	#Max	16QAM	21.64	22.89
LTE Band25	15	26115	75	#0	16QAM	21.68	22.93
LTE Band25	15	26365	1	#0	QPSK	23.69	24.94
LTE Band25	15	26365	1	#Mid	QPSK	23.70	24.95
LTE Band25	15	26365	1	#Max	QPSK	23.68	24.93
LTE Band25	15	26365	36	#0	QPSK	22.73	23.98
LTE Band25	15	26365	36	#Mid	QPSK	22.70	23.95
LTE Band25	15	26365	36	#Max	QPSK	22.80	24.05
LTE Band25	15	26365	75	#0	QPSK	22.71	23.96
LTE Band25	15	26365	1	#0	16QAM	23.23	24.48
LTE Band25	15	26365	1	#Mid	16QAM	23.16	24.41
LTE Band25	15	26365	1	#Max	16QAM	23.20	24.45
LTE Band25	15	26365	36	#0	16QAM	21.85	23.10
LTE Band25	15	26365	36	#Mid	16QAM	21.86	23.11
LTE Band25	15	26365	36	#Max	16QAM	21.95	23.20
LTE Band25	15	26365	75	#0	16QAM	21.75	23.00
LTE Band25	15	26615	1	#0	QPSK	23.62	24.87
LTE Band25	15	26615	1	#Mid	QPSK	23.53	24.78
LTE Band25	15	26615	1	#Max	QPSK	23.32	24.57
LTE Band25	15	26615	36	#0	QPSK	22.74	23.99
LTE Band25	15	26615	36	#Mid	QPSK	22.70	23.95
LTE Band25	15	26615	36	#Max	QPSK	22.62	23.87
LTE Band25	15	26615	75	#0	QPSK	22.65	23.90
LTE Band25	15	26615	1	#0	16QAM	22.30	23.55
LTE Band25	15	26615	1	#Mid	16QAM	22.29	23.54
LTE Band25	15	26615	1	#Max	16QAM	21.78	23.03
LTE Band25	15	26615	36	#0	16QAM	21.73	22.98
LTE Band25	15	26615	36	#Mid	16QAM	21.72	22.97
LTE Band25	15	26615	36	#Max	16QAM	21.44	22.69
LTE Band25	15	26615	75	#0	16QAM	21.71	22.96
LTE Band25	20	26140	1	#0	QPSK	23.39	24.64



LTE Band25	20	26140	1	#Mid	QPSK	23.88	25.13
LTE Band25	20	26140	1	#Max	QPSK	23.63	24.88
LTE Band25	20	26140	50	#0	QPSK	22.68	23.93
LTE Band25	20	26140	50	#Mid	QPSK	22.66	23.91
LTE Band25	20	26140	50	#Max	QPSK	22.66	23.91
LTE Band25	20	26140	100	#0	QPSK	22.67	23.92
LTE Band25	20	26140	1	#0	16QAM	22.89	24.14
LTE Band25	20	26140	1	#Mid	16QAM	23.35	24.60
LTE Band25	20	26140	1	#Max	16QAM	22.41	23.66
LTE Band25	20	26140	50	#0	16QAM	21.71	22.96
LTE Band25	20	26140	50	#Mid	16QAM	21.71	22.96
LTE Band25	20	26140	50	#Max	16QAM	21.70	22.95
LTE Band25	20	26140	100	#0	16QAM	21.67	22.92
LTE Band25	20	26365	1	#0	QPSK	23.55	24.80
LTE Band25	20	26365	1	#Mid	QPSK	23.81	25.06
LTE Band25	20	26365	1	#Max	QPSK	23.84	25.09
LTE Band25	20	26365	50	#0	QPSK	22.71	23.96
LTE Band25	20	26365	50	#Mid	QPSK	22.71	23.96
LTE Band25	20	26365	50	#Max	QPSK	22.85	24.10
LTE Band25	20	26365	100	#0	QPSK	22.78	24.03
LTE Band25	20	26365	1	#0	16QAM	22.37	23.62
LTE Band25	20	26365	1	#Mid	16QAM	22.37	23.62
LTE Band25	20	26365	1	#Max	16QAM	21.86	23.11
LTE Band25	20	26365	50	#0	16QAM	21.72	22.97
LTE Band25	20	26365	50	#Mid	16QAM	21.72	22.97
LTE Band25	20	26365	50	#Max	16QAM	21.86	23.11
LTE Band25	20	26365	100	#0	16QAM	21.74	22.99
LTE Band25	20	26590	1	#0	QPSK	23.67	24.92
LTE Band25	20	26590	1	#Mid	QPSK	23.83	25.08
LTE Band25	20	26590	1	#Max	QPSK	23.46	24.71
LTE Band25	20	26590	50	#0	QPSK	22.80	24.05
LTE Band25	20	26590	50	#Mid	QPSK	22.71	23.96
LTE Band25	20	26590	50	#Max	QPSK	22.57	23.82
LTE Band25	20	26590	100	#0	QPSK	22.80	24.05
LTE Band25	20	26590	1	#0	16QAM	22.79	24.04
LTE Band25	20	26590	1	#Mid	16QAM	22.91	24.16
LTE Band25	20	26590	1	#Max	16QAM	22.37	23.62
LTE Band25	20	26590	50	#0	16QAM	21.82	23.07
LTE Band25	20	26590	50	#Mid	16QAM	21.75	23.00
LTE Band25	20	26590	50	#Max	16QAM	21.59	22.84
LTE Band25	20	26590	100	#0	16QAM	21.76	23.01

5.2.Occupied Bandwidth

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The occupied bandwidth is measured using spectrum analyzer.

RBW is set to 30kHz, VBW is set to 91kHz for LTE Band 25(1.4MHz),

RBW is set to 62kHz,VBW is set to 180kHz for LTE Band 25 (3MHz),

RBW is set to 100kHz,VBW is set to 300kHz for LTE Band 25 (5MHz),


RBW is set to 200kHz,VBW is set to 620kHz for LTE Band 25(10MHz),

RBW is set to 300kHz,VBW is set to 910kHz for LTE Band 25(15MHz),

RBW is set to 430kHz,VBW is set to 1.2MHz for LTE Band 25(20MHz).

99% power and -26dBc occupied bandwidths are recorded. Spectrum analyzer plots are included on the following pages.

Test Setup



Limits

No specific occupied bandwidth requirements in part 2.1049.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 624\text{Hz}$.

Test Result


LTE Band 25					
Modulation	Bandwidth (MHz)	Channel	Frequency (MHz)	99% Power Bandwidth(MHz)	-26dBc Bandwidth(MHz)
QPSK	1.4	26047	1850.7	1.0935	1.292
		26365	1882.5	1.0992	1.299
		26683	1914.3	1.1026	1.300
	3	26055	1851.5	2.7121	2.995
		26365	1882.5	2.6987	2.989
		26675	1913.5	2.7021	3.016
	5	26065	1852.5	4.5082	4.975
		26365	1882.5	4.5254	4.956
		26665	1912.5	4.5251	4.989
	10	26090	1855	8.9705	9.762
		26365	1882.5	8.9819	9.808
		26640	1910	8.9656	9.669
	15	26115	1857.5	13.4370	14.530
		26365	1882.5	13.4490	14.580
		26615	1907.5	13.3980	14.520
	20	26140	1860	17.8730	19.220
		26365	1882.5	17.8880	19.210
		26590	1905	17.8380	19.140
16QAM	1.4	26047	1850.7	1.1017	1.273
		26365	1882.5	1.0887	1.280
		26683	1914.3	1.0983	1.300
	3	26055	1851.5	2.7049	2.990
		26365	1882.5	2.6941	2.972
		26675	1913.5	2.6994	2.974
	5	26065	1852.5	4.5258	4.928
		26365	1882.5	4.5018	4.967
		26665	1912.5	4.5247	4.984
	10	26090	1855	8.9760	9.813
		26365	1882.5	8.9984	9.814
		26640	1910	8.9683	9.741




	15	26115	1857.5	13.4280	14.430
		26365	1882.5	13.4540	14.680
		26615	1907.5	13.3590	14.330
	20	26140	1860	17.9390	19.310
		26365	1882.5	17.9000	19.230
		26590	1905	17.8660	19.230




LTE Band 25 1.4MHz QPSK CH-Low




LTE Band 25 3MHz QPSK CH-Low




LTE Band 25 1.4MHz QPSK CH-Middle




LTE Band 25 3MHz QPSK CH-Middle



LTE Band 25 1.4MHz QPSK CH-High




LTE Band 25 3MHz QPSK CH-High







LTE Band 25 5MHz QPSK CH-Low




LTE Band 25 10MHz QPSK CH-Low




LTE Band 25 5MHz QPSK CH-Middle




LTE Band 25 10MHz QPSK CH-Middle



LTE Band 25 5MHz QPSK CH-High




LTE Band 25 10MHz QPSK CH-High







LTE Band 25 15MHz QPSK CH-Low




LTE Band 25 20MHz QPSK CH-Low




LTE Band 25 15MHz QPSK CH-Middle




LTE Band 25 20MHz QPSK CH-Middle



LTE Band 25 15MHz QPSK CH-High




LTE Band 25 20MHz QPSK CH-High







LTE Band 25 1.4MHz 16QAM CH-Low




LTE Band 25 3MHz 16QAM CH-Low



LTE Band 25 1.4MHz 16QAM CH-Middle




LTE Band 25 3MHz 16QAM CH-Middle



LTE Band 25 1.4MHz 16QAM CH-High




LTE Band 25 3MHz 16QAM CH-High







LTE Band 25 5MHz 16QAM CH-Low




LTE Band 25 10MHz 16QAM CH-Low




LTE Band 25 5MHz 16QAM CH-Middle




LTE Band 25 10MHz 16QAM CH-Middle




LTE Band 25 5MHz 16QAM CH-High




LTE Band 25 10MHz 16QAM CH-High




LTE Band 25 15MHz 16QAM CH-Low




LTE Band 25 20MHz 16QAM CH-Low




LTE Band 25 15MHz 16QAM CH-Middle




LTE Band 25 20MHz 16QAM CH-Middle



LTE Band 25 15MHz 16QAM CH-High



LTE Band 25 20MHz 16QAM CH-High



5.3.Band Edge Compliance


Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The band edge of the lowest and highest channels were measured. The Average detector is used and RBW is set to 15kHz, VBW is set to 43kHz for LTE Band 25(1.4MHz), RBW is set to 30kHz,VBW is set to 91kHz for LTE Band 25 (3MHz), RBW is set to 51kHz,VBW is set to 150kHz for LTE Band 25 (5MHz), RBW is set to 100kHz,VBW is set to 300kHz for LTE Band 25(10MHz), RBW is set to 150kHz,VBW is set to 470kHz for LTE Band 25(15MHz), RBW is set to 200kHz,VBW is set to 620kHz for LTE Band 25(20MHz). Spectrum analyzer plots are included on the following pages.

Test Setup



Limits

Rule Part 24.238(a) specifies that “on any frequency outside a licensee’s frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10} (P)$ dB.”

Limit	-13 dBm
-------	---------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$, $U=0.684$ dB.



Test Result:

LTE Band 25 1.4MHz QPSK 1RB CH-Low



LTE Band 25 1.4MHz QPSK 1RB CH-High




LTE Band 25 1.4MHz QPSK 100%RB CH-Low




LTE Band 25 1.4MHz QPSK 100%RB CH-High



LTE Band 25 3MHz QPSK 1RB CH-Low



LTE Band 25 3MHz QPSK 1RB CH-High






LTE Band 25 3MHz QPSK 100%RB CH-Low




LTE Band 25 3MHz QPSK 100%RB CH-High




LTE Band 25 5MHz QPSK 1RB CH-Low



LTE Band 25 5MHz QPSK 1RB CH-High



LTE Band 25 5MHz QPSK 100%RB CH-Low




LTE Band 25 5MHz QPSK 100%RB CH-High







LTE Band 25 10MHz QPSK 1RB CH-Low



LTE Band 25 10MHz QPSK 1RB CH-High




LTE Band 25 10MHz QPSK 100%RB CH-Low




LTE Band 25 10MHz QPSK 100%RB CH-High



LTE Band 25 15MHz QPSK 1RB CH-Low




LTE Band 25 15MHz QPSK 1RB CH-High






LTE Band 25 15MHz QPSK 100%RB CH-Low




LTE Band 25 15MHz QPSK 100%RB CH-High




LTE Band 25 20MHz QPSK 1RB CH-Low



LTE Band 25 20MHz QPSK 1RB CH-High




LTE Band 25 20MHz QPSK 100%RB CH-Low



LTE Band 25 20MHz QPSK 100%RB CH-High



LTE Band 25 1.4MHz 16QAM 1RB CH-Low



LTE Band 25 1.4MHz 16QAM 1RB CH-High




LTE Band 25 1.4MHz 16QAM 100%RB CH-Low




LTE Band 25 1.4MHz 16QAM 100%RB CH-High



LTE Band 25 3MHz 16QAM 1RB CH-Low



LTE Band 25 3MHz 16QAM 1RB CH-High






LTE Band 25 3MHz 16QAM 100%RB CH-Low




LTE Band 25 3MHz 16QAM 100%RB CH-High




LTE Band 25 5MHz 16QAM 1RB CH-Low



LTE Band 25 5MHz 16QAM 1RB CH-High



LTE Band 25 5MHz 16QAM 100%RB CH-Low




LTE Band 25 5MHz 16QAM 100%RB CH-High







LTE Band 25 10MHz 16QAM 1RB CH-Low



LTE Band 25 10MHz 16QAM 1RB CH-High




LTE Band 25 10MHz 16QAM 100%RB CH-Low




LTE Band 25 10MHz 16QAM 100%RB CH-High



LTE Band 25 15MHz 16QAM 1RB CH-Low



LTE Band 25 15MHz 16QAM 1RB CH-High






LTE Band 25 15MHz 16QAM 100%RB CH-Low




LTE Band 25 15MHz 16QAM 100%RB CH-High




LTE Band 25 20MHz 16QAM 1RB CH-Low



LTE Band 25 20MHz 16QAM 1RB CH-High



LTE Band 25 20MHz 16QAM 100%RB CH-Low



LTE Band 25 20MHz 16QAM 100%RB CH-High



5.4. Peak-to-Average Power Ratio (PAPR)

Ambient condition


Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

Measure the total peak power and record as PPk. And measure the total average power and record as PAvg. Both the peak and average power levels must be expressed in the same logarithmic units (e.g., dBm). Determine the PAPR from:

$$\text{PAPR (dB)} = \text{PPk (dBm)} - \text{PAvg (dBm)}.$$

Test Setup



Limits

In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB in 24.232(d).

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 0.4$ dB.



Test Results

LTE Band 25								
Modulation	Bandwidth (MHz)	Channel	Frequency (MHz)	Peak (dBm)	Avg (dBm)	PAPR (dB)	Limit (dB)	Conclusion
QPSK	1.4	26047	1850.7	28.03	22.81	5.22	≤13	PASS
		26365	1882.5	28.12	22.91	5.21	≤13	PASS
		26683	1914.3	27.32	23.00	4.32	≤13	PASS
	3	26055	1851.5	28.13	22.83	5.30	≤13	PASS
		26365	1882.5	28.22	23.00	5.22	≤13	PASS
		26675	1913.5	27.46	23.04	4.42	≤13	PASS
	5	26065	1852.5	28.13	22.78	5.35	≤13	PASS
		26365	1882.5	28.17	22.94	5.23	≤13	PASS
		26665	1912.5	27.41	22.84	4.57	≤13	PASS
	10	26090	1855	28.24	22.91	5.33	≤13	PASS
		26365	1882.5	28.15	22.94	5.21	≤13	PASS
		26640	1910	27.55	22.78	4.77	≤13	PASS
	15	26115	1857.5	28.29	22.87	5.42	≤13	PASS
		26365	1882.5	28.29	22.90	5.39	≤13	PASS
		26615	1907.5	27.84	22.79	5.05	≤13	PASS
16QAM	1.4	26047	1850.7	27.84	21.75	6.09	≤13	PASS
		26365	1882.5	28.28	22.27	6.01	≤13	PASS
		26683	1914.3	27.33	22.02	5.31	≤13	PASS
	3	26055	1851.5	28.00	21.81	6.19	≤13	PASS
		26365	1882.5	28.12	22.07	6.05	≤13	PASS
		26675	1913.5	27.41	21.98	5.43	≤13	PASS
	5	26065	1852.5	28.03	21.82	6.21	≤13	PASS
		26365	1882.5	27.95	21.86	6.09	≤13	PASS
		26665	1912.5	27.38	21.90	5.48	≤13	PASS
	10	26090	1855	28.12	21.94	6.18	≤13	PASS
		26365	1882.5	27.99	21.88	6.11	≤13	PASS
		26640	1910	27.44	21.85	5.59	≤13	PASS
	15	26115	1857.5	28.03	21.81	6.22	≤13	PASS
		26365	1882.5	28.16	22.03	6.13	≤13	PASS
		26615	1907.5	27.67	21.85	5.82	≤13	PASS
	20	26140	1860	28.07	21.97	6.10	≤13	PASS
		26365	1882.5	28.11	22.07	6.04	≤13	PASS
		26590	1905	27.71	21.79	5.92	≤13	PASS

5.5.Frequency Stability

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

Frequency Stability (Temperature Variation)

The temperature inside the climate chamber is varied from -40°C to +85°C in 10°C step size,

(1) With all power removed, the temperature was decreased to 0°C and permitted to stabilize for three hours.

(2) Measure the carrier frequency with the test equipment in a “call mode”. These measurements should be made within 1 minute of powering up the mobile station, to prevent significant self warming.

(3) Repeat the above measurements at 10°C increments from -40°C to +85°C. Allow at least 1.5 hours at each temperature, un-powered, before making measurements.

Frequency Stability (Voltage Variation)


The frequency stability shall be measured with variation of primary supply voltage as follows:

(1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

(2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery-operating end point which shall be specified by the manufacturer.

This transceiver is specified to operate with an input voltage of between 3.3 V and 4.3 V, with a nominal voltage of 3.8V.

Test setup



Limits

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block

Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor $k = 3$, $U = 0.01\text{ppm}$.

Test Result

LTE Band 25						
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	20MHz					
Temperature	Voltage	16QAM	QPSK	16QAM	QPSK	
Normal (25℃)	Normal	4.43	3.30	0.00236	0.00921	PASS
Extreme (55℃)		4.79	10.15	0.00255	0.00540	PASS
Extreme (80℃)		8.77	12.16	0.00439	0.00650	PASS
Extreme (70℃)		2.64	3.45	0.00579	0.00183	PASS
Extreme (60℃)		15.24	7.52	0.00601	0.00400	PASS
Extreme (50℃)		16.77	2.97	0.00892	0.00158	PASS
Extreme (40℃)		12.50	9.90	0.00665	0.00527	PASS
Extreme (30℃)		5.43	2.37	0.00289	0.00126	PASS
Extreme (20℃)		3.43	3.24	0.00183	0.00064	PASS
Extreme (10℃)		5.58	11.23	0.00297	0.00853	PASS
Extreme (0℃)		11.12	4.72	0.00110	0.00236	PASS
Extreme (-10℃)		3.33	10.69	0.00177	0.00569	PASS
Extreme (-20℃)		14.48	4.13	0.00770	0.00220	PASS
Extreme (-30℃)		13.91	1.10	0.00740	0.00058	PASS
Extreme (-40℃)		5.54	12.08	0.00295	0.00643	PASS
25℃	LV	16.91	4.31	0.00899	0.00229	PASS
	HV	2.81	2.05	0.00740	0.00109	PASS

5.6. Spurious Emissions at Antenna Terminals

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement


The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The measurement is carried out using a spectrum analyzer. The spectrum analyzer scans from 9kHz to the 10th harmonic of the carrier. The peak detector is used.

RBW is set to 100kHz, VBW is set to 300kHz for 30MHz~1GHz

RBW is set to 1MHz, VBW is set to 3MHz for above 1GHz, Sweep is set to ATUO.

The modulation mode and RB allocation refer to section 5.1, using the maximum output power configuration.

Test setup



Limits

Rule Part 24.238(a) specifies that “on any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10} (P)$ dB.”

Limit	-13 dBm
-------	---------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor $k = 1.96$.


Frequency	Uncertainty
9kHz-1GHz	0.684 dB
1GHz-20GHz	1.407 dB

Test Result

Sweep the whole frequency band through the range from 9kHz to the 10th harmonic of the carrier, the emissions more than 20 dB below the limit are not reported.


The signal beyond the limit is carrier.

LTE Band 25 1.4MHz CH-Low 30MHz~1GHz




Date: 9.NOV.2019 10:45:35

LTE Band 25 1.4MHz CH-Low 1GHz~20GHz




Date: 9.NOV.2019 10:39:34

LTE Band 25 1.4MHz CH-Middle 30MHz~1GHz




Date: 9.NOV.2019 10:45:49

LTE Band 25 1.4MHz CH-Middle 1GHz~20GHz




Date: 9.NOV.2019 10:39:48

LTE Band 251.4MHz CH-High 30MHz~1GHz



Date: 9.NOV.2019 10:46:05


LTE Band 25 1.4MHz CH-High 1GHz~20GHz



Date: 9.NOV.2019 10:40:04




LTE Band 25 3MHz CH-Low 30MHz~1GHz




Date: 9.NOV.2019 10:46:28

LTE Band 25 3MHz CH-Low 1GHz~20GHz




Date: 9.NOV.2019 10:48:28

LTE Band 25 3MHz CH-Middle 30MHz~1GHz




Date: 9.NOV.2019 10:46:43

LTE Band 25 3MHz CH-Middle 1GHz~20GHz




Date: 9.NOV.2019 10:48:44

LTE Band 25 3MHz CH-High 30MHz~1GHz



Date: 9.NOV.2019 10:47:11


LTE Band 25 3MHz CH-High 1GHz~20GHz



Date: 9.NOV.2019 10:48:59




LTE Band 25 5MHz CH-Low 30MHz~1GHz




Date: 9.NOV.2019 10:47:36

LTE Band 25 5MHz CH-Low 1GHz~20GHz




Date: 9.NOV.2019 10:41:22

LTE Band 25 5MHz CH-Middle 30MHz~1GHz




Date: 9.NOV.2019 10:47:50

LTE Band 25 5MHz CH-Middle 1GHz~20GHz




Date: 9.NOV.2019 10:41:34

LTE Band 25 5MHz CH-High 30MHz~1GHz



Date: 9.NOV.2019 10:48:12


LTE Band 25 5MHz CH-High 1GHz~20GHz



Date: 9.NOV.2019 10:41:52




LTE Band 25 10MHz CH-Low 30MHz~1GHz




Date: 9.NOV.2019 10:48:41

LTE Band 25 10MHz CH-Low 1GHz~20GHz




Date: 9.NOV.2019 10:42:14

LTE Band 25 10MHz CH-Middle 30MHz~1GHz




Date: 9.NOV.2019 10:48:56

LTE Band 25 10MHz CH-Middle 1GHz~20GHz




Date: 9.NOV.2019 10:42:28

LTE Band 25 10MHz CH-High 30MHz~1GHz



Date: 9.NOV.2019 10:49:16


LTE Band 25 10MHz CH-High 1GHz~20GHz



Date: 9.NOV.2019 10:42:44




LTE Band 25 15MHz CH-Low 30MHz~1GHz




Date: 9.NOV.2019 10:49:39

LTE Band 25 15MHz CH-Low 1GHz~20GHz




Date: 9.NOV.2019 10:43:09

LTE Band 25 15MHz CH-Middle 30MHz~1GHz




Date: 9.NOV.2019 10:49:53

LTE Band 25 15MHz CH-Middle 1GHz~20GHz




Date: 9.NOV.2019 10:43:22

LTE Band 25 15MHz CH-High 30MHz~1GHz



Date: 9.NOV.2019 10:50:11


LTE Band 25 15MHz CH-High 1GHz~20GHz



Date: 9.NOV.2019 10:43:39




LTE Band 25 20MHz CH-Low 30MHz~1GHz




Date: 9.NOV.2019 10:51:46

LTE Band 25 20MHz CH-Low 1GHz~20GHz




Date: 9.NOV.2019 10:44:01

LTE Band 25 20MHz CH-Middle 30MHz~1GHz




Date: 9.NOV.2019 10:52:02

LTE Band 25 20MHz CH-Middle 1GHz~20GHz




Date: 9.NOV.2019 10:44:23

LTE Band 25 20MHz CH-High 30MHz~1GHz



Date: 9.NOV.2019 10:52:17

LTE Band 25 20MHz CH-High 1GHz~20GHz



Date: 9.NOV.2019 10:44:39

5.7. Radiates Spurious Emission

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

1. The testing follows FCC KDB 971168 v03r01 Section 5.8 and ANSI C63.26 (2015).
2. Below 1GHz: The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H). Above 1GHz: (Note: the FCC's permission to use 1.5m as an alternative per TCBC Conf call of Dec. 2, 2014.) The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).
3. A loop antenna, A log-periodic antenna or horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
4. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=200Hz,VBW=600Hz for 9kHz150kHz , RBW=10kHz, VBW=30kHz 150kHz-30MHz , RBW=100kHz,VBW=300kHz for 30MHz to 1GHz and RBW=1MHz, VBW=3MHz for above 1GHz, And the maximum value of the receiver should be recorded as (Pr).
5. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
6. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (Pcl) ,the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test.
7. The measurement results are obtained as described below:

$$\text{Power(EIRP)} = \text{PMea} - \text{PAg} - \text{Pcl} + \text{Ga}$$
The measurement results are amend as described below:


$$\text{Power(EIRP)} = \text{PMea} - \text{Pcl} + \text{Ga}$$
8. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi)

and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi}$.


The modulation mode and RB allocation refer to section 5.1, using the maximum output power configuration.

Test setup


9KHz ~ 30MHz



30MHz ~ 1GHz



Above 1GHz





Note: Area side: 2.4mX3.6m

Limits

Rule Part 24.238(a) specifies that “on any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10} (P)$ dB.”

Limit	-13 dBm
-------	---------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$, $U = 3.55$ dB.

Test Result

Sweep the whole frequency band through the range from 9kHz to the 10th harmonic of the carrier, the emissions below the noise floor will not be recorded in the report.

LTE Band 25 1.4MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3765.0	-54.03	5.10	11.05	Horizontal	-48.08	-13.00	35.08	90
3	5647.5	-49.85	5.42	12.65	Horizontal	-42.62	-13.00	29.62	45
4	7530.0	-56.47	6.70	13.85	Horizontal	-49.32	-13.00	36.32	45
5	9412.5	-45.15	7.01	14.75	Horizontal	-37.41	-13.00	24.41	0
6	11295.0	-54.25	7.48	15.95	Horizontal	-45.78	-13.00	32.78	180
7	13177.5	-55.91	7.51	16.55	Horizontal	-46.87	-13.00	33.87	135
8	15060.0	-52.63	8.24	15.35	Horizontal	-45.52	-13.00	32.52	45
9	16942.5	-50.14	8.41	14.95	Horizontal	-43.60	-13.00	30.60	270
10	18825.0	--	--	--	--	--	--	--	--

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Horizontal position.

LTE Band 25 5MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3765.0	-62.70	5.10	11.05	Horizontal	-56.75	-13.00	43.75	90
3	5647.5	-62.27	5.42	12.65	Horizontal	-55.04	-13.00	42.04	45
4	7530.0	-58.16	6.70	13.85	Horizontal	-51.01	-13.00	38.01	0
5	9412.5	-56.83	7.01	14.75	Horizontal	-49.09	-13.00	36.09	180
6	11295.0	-54.08	7.48	15.95	Horizontal	-45.61	-13.00	32.61	90
7	13177.5	-55.70	7.51	16.55	Horizontal	-46.66	-13.00	33.66	270
8	15060.0	-52.67	8.24	15.35	Horizontal	-45.56	-13.00	32.56	45
9	16942.5	-49.99	8.41	14.95	Horizontal	-43.45	-13.00	30.45	90
10	18825.0	--	--	--	--	--	--	--	--

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Horizontal position.

LTE Band 25 10MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3765.0	-56.08	5.10	11.05	Horizontal	-50.13	-13.00	37.13	270
3	5647.5	-48.93	5.42	12.65	Horizontal	-41.70	-13.00	28.70	135
4	7530.0	-58.80	6.70	13.85	Horizontal	-51.65	-13.00	38.65	315
5	9412.5	-43.85	7.01	14.75	Horizontal	-36.11	-13.00	23.11	0
6	11295.0	-55.03	7.48	15.95	Horizontal	-46.56	-13.00	33.56	90
7	13177.5	-55.53	7.51	16.55	Horizontal	-46.49	-13.00	33.49	45
8	15060.0	-53.03	8.24	15.35	Horizontal	-45.92	-13.00	32.92	180
9	16942.5	-50.51	8.41	14.95	Horizontal	-43.97	-13.00	30.97	90
10	18825.0	--	--	--	--	--	--	--	--

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Horizontal position.

6. Main Test Instruments

Name	Manufacturer	Type	Serial Number	Calibration Date	Expiration Date
Base Station Simulator	R&S	CMU200	118133	2019-05-19	2020-05-18
Base Station Simulator	R&S	CMW500	113824	2019-05-19	2020-05-18
Power Splitter	Hua Xiang	SHX-GF2-2-13	10120101	/	/
Spectrum Analyzer	Key sight	N9010A	MY50210259	2019-05-19	2020-05-18
Universal Radio Communication Tester	Key sight	E5515C	MY48367192	2019-05-19	2020-05-18
Signal Analyzer	R&S	FSV30	100815	2018-12-16	2019-12-15
Loop Antenna	SCHWARZBECK	FMZB1519	1519-047	2017-09-26	2020-09-25
Trilog Antenna	SCHWARZBECK	VUBL 9163	9163-201	2017-11-18	2020-11-17
Horn Antenna	R&S	HF907	100126	2018-07-07	2020-07-06
Horn Antenna	ETS-Lindgren	3160-09	00102643	2018-06-20	2020-06-19
Signal generator	R&S	SMB 100A	102594	2019-05-19	2020-05-18
Climatic Chamber	ESPEC	SU-242	93000506	2017-12-17	2020-12-16
Preamplifier	R&S	SCU18	102327	2019-05-19	2020-05-18
MOB COMMS DC SUPPLY	Keysight	66319D	MY43004105	2019-05-19	2020-05-18
RF Cable	Agilent	SMA 15cm	0001	2019-06-14	2019-12-13
Software	R&S	EMC32	9.26.0	/	/

*****END OF REPORT *****