# RF TEST REPORT

| | |
|---|---|
| **Applicant** | Quectel Wireless Solutions Co., Ltd |
| **FCC ID** | XMR201912BG77 |
| **Product** | LTE Cat M1 & Cat NB2 Module |
| **Brand** | Quectel |
| **Model** | BG77 |
| **Marketing** | Quectel BG77 |
| **Report No.** | R1909A0576-R8 |
| **Issue Date** | March 13, 2020 |

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC CFR47 Part 2 / FCC CFR 47 Part 90R**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Peng Tao

*Performed by: Peng Tao*

Kai Xu

*Approved by: Kai Xu*


## TA Technology (Shanghai) Co., Ltd.

*No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China*

*TEL: +86-021-50791141/2/3*

*FAX: +86-021-50791141/2/3-8000*

# TABLE OF CONTENT

1. Test Laboratory ....4
1.1. Notes of the Test Report ....4
1.2. Test facility ....4
1.3. Testing Location ....4
2. General Description of Equipment under Test ....5
2.3. Applicant and Manufacturer Information ....5
2.4. General Information ....5
3. Applied Standards ....6
4. Test Configuration ....7
5. Test Case Results ....8
5.1. RF Power Output and Effective Isotropic Radiated power ....8
5.2. Occupied Bandwidth ....11
5.3. Band Edge Compliance ....14
5.4. Peak-to-Average Power Ratio (PAPR) ....20
5.5. Frequency Stability ....22
5.6. Spurious Emissions at Antenna Terminals ....25
5.7. Radiates Spurious Emission ....29
6. Main Test Instruments ....33


*This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.*

# Summary of measurement results

| No. | Test Case | Clause in FCC rules | Verdict |
|---|---|---|---|
| 1 | RF power output and Effective Radiated Power | 2.1046/90.635 (b) | PASS |
| 2 | Occupied Bandwidth | 2.1049/ 90.209 | PASS |
| 3 | Emission Masks | 2.1051 / 90.543 | PASS |
| 4 | Peak-to-Average Power Ratio | KDB 971168 D01(5.7) | PASS |
| 5 | Frequency Stability | 90.539 (c) | PASS |
| 6 | Spurious Emissions at Antenna Terminals | 90.543 (e) | PASS |
| 7 | Radiates Spurious Emission | 90.543 (e) | PASS |
| Date of Testing: December 13, 2019 ~January 14, 2020 | | | |
| Note: PASS: The EUT complies with the essential requirements in the standard.<br>FAIL: The EUT does not comply with the essential requirements in the standard.<br>All indications of Pass/Fail in this report are opinions expressed by TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. | | | |


*This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.*

# 1. Test Laboratory

## 1.1. Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein .Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

## 1.2. Test facility

**FCC (Designation number: CN1179, Test Firm Registration Number: 446626)**

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

**A2LA (Certificate Number: 3857.01)**

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

## 1.3. Testing Location

| | |
|---|---|
| Company: | TA Technology (Shanghai) Co., Ltd. |
| Address: | No.145, Jintang Rd, Tangzhen Industry Park, Pudong |
| City: | Shanghai |
| Post code: | 201201 |
| Country: | P. R. China |
| Contact: | Xu Kai |
| Telephone: | +86-021-50791141/2/3 |
| Fax: | +86-021-50791141/2/3-8000 |
| Website: | http://www.ta-shanghai.com |
| E-mail: | xukai@ta-shanghai.com |


*This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.*

# 2. General Description of Equipment under Test

## 2.3. Applicant and Manufacturer Information

| | |
|---|---|
| Applicant | Quectel Wireless Solutions Co., Ltd |
| Applicant address | Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, China 200233 |
| Manufacturer | Quectel Wireless Solutions Co., Ltd |
| Manufacturer address | Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, China 200233 |

## 2.4. General Information

| EUT Description | | | |
|---|---|---|---|
| Model | BG77 | | |
| IMEI | 866349040016200 | | |
| Hardware Version | R1.2 | | |
| Software Version | BG77LAR02A02 | | |
| Power Supply | External Power Supply | | |
| Antenna Type | The EUT don't have standard Antenna, The Antenna used for testing in this report is the after-market accessory (Dipole Antenna) | | |
| Antenna Gain | 4.45dBi | | |
| Test Mode(s) | LTE Band 14; | | |
| Test Modulation | QPSK 16QAM; | | |
| LTE Category | M1 | | |
| Maximum E.R.P. | LTE Band 14: 22.47dBm | | |
| Rated Power Supply Voltage | 3.3V | | |
| Extreme Voltage | Minimum: 2.6V Maximum: 4.8V | | |
| Extreme Temperature | Lowest: -40°C Highest: +85°C | | |
| Operating Frequency Range(s) | Band | Tx (MHz) | Rx (MHz) |
| | LTE Band 14 | 788 ~ 798 | 758 ~ 768 |
| Note: 1. The EUT is sent from the applicant to TA and the information of the EUT is declared by the applicant. | | | |


*This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.*

# 3. Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**Test standards:**
**FCC CFR 47 Part 90R (2019)**
**ANSI C63.26 (2015)**

**Reference standard:**
**FCC 47 CFR Part 2 (2019)**
**KDB 971168 D01 Power Meas License Digital Systems v03r01**


*This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.*

# 4. Test Configuration

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes. EUT stand-up position (Z axis), lie-down position (X, Y axis). Receiver antenna polarization (horizontal and vertical), the worst emission was found in position (X axis, horizontal polarization) and the worst case was recorded.

All mode and data rates and positions were investigated.
The following testing in LTE is set based on the maximum RF Output Power.

Test modes are chosen as the worst case configuration below for LTE Band 14

| Test items | Bandwidth (MHz) | | Modulation | | RB | | | Test Channel | | |
|---|---|---|---|---|---|---|---|---|---|---|
| | 5 | 10 | QPSK | 16QAM | 1 | 50% | 100% | L | M | H |
| RF power output and Effective Isotropic Radiated power | O | O | O | O | O | O | O | O | O | O |
| Occupied Bandwidth | O | O | O | O | - | - | O | O | O | O |
| Band Edge Compliance | O | O | O | O | - | - | O | O | - | O |
| Peak-to-Average Power Ratio | O | O | O | O | - | - | O | O | O | O |
| Frequency Stability | O | O | O | O | - | - | O | O | O | O |
| Spurious Emissions at Antenna Terminals | O | O | O | - | O | - | - | O | O | O |
| Radiates Spurious Emission | O | O | O | - | O | - | - | - | O | - |
| Note | 1. The mark “O” means that this configuration is chosen for testing.<br>2. The mark “-” means that this configuration is not testing. | | | | | | | | | |


*This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.*

# 5. Test Case Results

## 5.1. RF Power Output and Effective Isotropic Radiated power

**Ambient condition**

| Temperature | Relative humidity | Pressure |
|---|---|---|
| 23°C ~25°C | 45%~50% | 101.5kPa |

**Methods of Measurement**

1. The testing follows FCC KDB 971168 v03r01 Section 5.8 and **ANSI C63.26 (2015)**.

a) Connect the equipment as illustrated. Mount the equipment with the manufacturer specified antenna in a vertical orientation on a manufacturer specified mounting surface located on a non-conducting rotating platform of a RF anechoic chamber (preferred) or a standard radiation site.

b) Key the transmitter, then rotate the EUT 360°azimuthally and record spectrum analyzer power level (LVL) measurements at angular increments that are sufficiently small to permit resolution of all peaks. If a standard radiation test site is used, raise and lower the test antenna to obtain a maximum reading at each angular increment. (Note: several batteries may be needed to offset the effect of battery voltage droop, which should not exceed 5% of the manufactured specified battery voltage during transmission).

c) Replace the transmitter under test with a vertically polarized half-wave dipole (or an antenna whose gain is known relative to an ideal half-wave dipole). The center of the antenna should be at the same location as the center of the antenna under test.

d) Connect the antenna to a signal generator with a known output power and record the path loss (in dB) as LOSS. If a standard radiation test site is used, raise and lower the test antenna to obtain a maximum reading.LOSS = Generator Output Power (dBm) – Analyzer reading (dBm)

e) Determine the effective radiated output power at each angular position from the readings in steps b) and d) using the following equation:ERP (dBm) = LVL (dBm) + LOSS (dB)

f) The maximum ERP is the maximum value determined in the preceding step.

g) When calculating ERP, in addition to knowing the antenna radiation and matching characteristics, it is necessary to know the loss values of all elements (e.g.transmission line attenuation, mismatches, filters, combiners) interposed between the point where transmitter output power is measured, and the point where power is applied to the antenna. ERP can then be calculated as follows:

EIRP (dBm) = Output Power (dBm) - Losses (dB) + Antenna Gain (dBi)

where:dBd refers to gain relative to an ideal dipole.

EIRP (dBm ) = ERP (dBm) + 2.15 (dB.)


*This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.*

**Test setup**







Note: Area side:2.4mX3.6m

The radiated emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in stand-up position (Z axis) and the worst case was recorded.

**Limits**

90.542(7) Portable stations (hand-held devices) transmitting in the 758-768 MHz band and the 788-798 MHz band are limited to 3 watts ERP.

Part 90.635 (b) the maximum output power of the transmitter for mobile stations is 100 watts.

**Measurement Uncertainty**

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor k = 2, U= 0.4 dB.


*This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.*

## Test Results

| LTE Band14 | Channel/ Frequency(MHz) | Index | RB# RBstart | Conducted Power (dBm) | | ERP (dBm) | |
|---|---|---|---|---|---|---|---|
| | | | | QPSK | 16QAM | QPSK | 16QAM |
| 5MHz | 23305/790.5 | 0 | 1#0 | 20.84 | 20.53 | 22.16 | 21.85 |
| | | 0 | 6#0 | 19.80 | 19.07 | 21.12 | 20.39 |
| | 23330/793 | 0 | 1#0 | 20.90 | 20.58 | 22.22 | 21.90 |
| | | 0 | 6#0 | 19.85 | 19.14 | 21.17 | 20.46 |
| | 23355/795.5 | 3 | 1#5 | 21.01 | 20.66 | 22.33 | 21.98 |
| | | 3 | 6#0 | 20.03 | 19.23 | 21.35 | 20.55 |
| 10MHz | 23330/793 | 0 | 1#0 | 20.70 | 21.15 | 22.02 | 22.47 |
| | | 0 | 4#0 | 20.78 | 20.09 | 22.10 | 21.41 |


*This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.*

## 5.2. Occupied Bandwidth

### Ambient condition

| Temperature | Relative humidity | Pressure |
|---|---|---|
| 23°C ~25°C | 45%~50% | 101.5kPa |

### Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The occupied bandwidth is measured using spectrum analyzer.
RBW is set to 51 kHz, VBW is set to 160 kHz for LTE Band 14 (5MHz/10MHz).
99% power and -26dBc occupied bandwidths are recorded. Spectrum analyzer plots are included on the following pages.

### Test Setup




### Limits

No specific occupied bandwidth requirements in part 2.1049.
Part 90.209 (a) Each authorization issued to a station licensed under this part will show an emission designator representing the class of emission authorized. The designator will be prefixed by a specified necessary bandwidth. This number does not necessarily indicate the bandwidth occupied by the emission at any instant. In those cases where part 2.202 of this chapter does not provide a formula for the computation of necessary bandwidth, the occupied bandwidth, as defined in part 2 of this chapter, may be used in lieu of the necessary bandwidth.

### Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k$ = 2, $U$= 624Hz.


*This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.*

## Test Result

| Mode | Bandwidth | Modulation | Channel/ Frequency(MHz) | RB | Index | Bandwidth(MHz) | |
|---|---|---|---|---|---|---|---|
| | | | | | | 99% Power | -26dBc |
| Band14 | 5MHz | QPSK | 23330/793 | 6#0 | 0 | 1.1123 | 1.327 |
| | | 16QAM | 23330/793 | 6#0 | 0 | 0.9472 | 1.248 |
| | 10MHz | QPSK | 23330/793 | 6#0 | 0 | 1.1141 | 1.327 |
| | | 16QAM | 23330/793 | 6#0 | 0 | 0.9631 | 1.173 |


*This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.*

LTE Band 14 QPSK 5MHz CH-Middle




LTE Band 14 QPSK 10MHz CH-Middle

LTE Band 14 16QAM 5MHz CH-Middle




LTE Band 14 16QAM 10MHz CH-Middle

*This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.*

## 5.3. Band Edge Compliance

### Ambient condition

| Temperature | Relative humidity | Pressure |
|---|---|---|
| 23°C ~25°C | 45%~50% | 101.5kPa |

### Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The band edge of the lowest and highest channels were measured.
The testing follows KDB 971168 v03r01 Section 6.0
1.The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The band edges of low and high channels for the highest RF powers were measured.
RBW is set to 6.8 kHz, VBW is set to 22 kHz for LTE Band 14 (769MHz~775MHz).
RBW is set to 100 kHz, VBW is set to 300 kHz for LTE Band 14 (775MHz~787.9MHz).
RBW is set to 6.8 kHz, VBW is set to 22 kHz for LTE Band 14 (799MHz~805MHz).
3. Set spectrum analyzer with RMS detector.
4. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
5. Checked that all the results comply with the emission limit line.

### Test Setup




### Limits

90.543 Emission limitations (e) For operations in the 758-768 MHz and the 788-798 MHz bands, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

(1) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than 76 + 10 log (P) dB in a 6.25 kHz band segment, for base and fixed stations.


*This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.*

(2) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than 65 + 10 log (P) dB in a 6.25 kHz band segment, for mobile and portable stations.

(3) On any frequency between 775-788 MHz, above 805 MHz, and below 758 MHz, by at least 43 + 10 log (P) dB.

(4) Compliance with the provisions of paragraphs (e)(1) and (2) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.

(5) Compliance with the provisions of paragraph (e)(3) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of 30 kHz may be employed.

(f) For operations in the 758-775 MHz and 788-805 MHz bands, all emissions including harmonics in the band 1559-1610 MHz shall be limited to −70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and −80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

**Measurement Uncertainty**

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k$ = 1.96, $U$=0.684dB.


*This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.*

## Test Result:

LTE Band 14 QPSK 5MHz 1 RB
(769MHz ~775MHz)




LTE Band 14 QPSK 10MHz 1 RB
(769MHz ~775MHz)




LTE Band 14 QPSK 5MHz 1 RB
(775MHz ~787.9MHz)




LTE Band 14 QPSK 10MHz 1 RB
(775MHz ~787.9MHz)




LTE Band 14 QPSK 5MHz 1 RB
(799MHz ~805MHz)




LTE Band 14 QPSK 10MHz 1 RB
(799MHz ~805MHz)





*This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.*

LTE Band 14 QPSK 5MHz 100%RB
(769MHz ~775MHz)




LTE Band 14 QPSK 10MHz 100%RB
(769MHz ~775MHz)

LTE Band 14 QPSK 5MHz 100%RB
(775MHz ~787.9MHz)

LTE Band 14 QPSK 10MHz 100%RB
(775MHz ~787.9MHz)




LTE Band 14 QPSK 5MHz 100%RB
(799MHz ~805MHz)




LTE Band 14 QPSK 10MHz 100%RB
(799MHz ~805MHz)





*This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.*

LTE Band 14 16QAM 5MHz 1 RB
(769MHz ~775MHz)




LTE Band 14 16QAM 10MHz 1 RB
(769MHz ~775MHz)




LTE Band 14 16QAM 5MHz 1 RB
(775MHz ~787.9MHz)




LTE Band 14 16QAM 10MHz 1 RB
(775MHz ~787.9MHz)




LTE Band 14 16QAM 5MHz 1 RB
(799MHz ~805MHz)




LTE Band 14 16QAM 10MHz 1 RB
(799MHz ~805MHz)





*This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.*

LTE Band 14 16QAM 5MHz 100%RB
(769MHz ~775MHz)




LTE Band 14 16QAM 10MHz 100%RB
(769MHz ~775MHz)




LTE Band 14 16QAM 5MHz 100%RB
(775MHz ~787.9MHz)




LTE Band 14 16QAM 10MHz 100%RB
(775MHz ~787.9MHz)




LTE Band 14 16QAM 5MHz 100%RB
(799MHz ~805MHz)




LTE Band 14 16QAM 10MHz 100%RB
(799MHz ~805MHz)





*This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.*

## 5.4. Peak-to-Average Power Ratio (PAPR)

### Ambient condition

| Temperature | Relative humidity | Pressure |
|---|---|---|
| 23°C ~25°C | 45%~50% | 101.5kPa |

### Methods of Measurement

Measure the total peak power and record as PPk. And measure the total average power and record as PAvg. Both the peak and average power levels must be expressed in the same logarithmic units (*e.g.*, dBm). Determine the PAPR from:
PAPR (dB) = PPk (dBm) - PAvg (dBm).

### Test Setup




### Limits

In measuring transmissions in this band using an average power technique, the peakto-average ratio (PAR) of the transmission may not exceed 13 dB in 24.232(d).

### Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor k = 2, U= 0.4 dB.


*This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.*

## Test Results

| Mode | Bandwidth | Modulation | Channel/ Frequency(MHz) | Peak-to-Average Power Ratio (PAPR) | | |
|---|---|---|---|---|---|---|
| | | | | Peak(dBm) | Avg(dBm) | PAPR(dB) |
| Band14 | 5MHz | QPSK | 23330/793 | 24.87 | 15.02 | 9.85 |
| | | 16QAM | 23330/793 | 24.76 | 14.57 | 10.19 |
| | 10MHz | QPSK | 23330/793 | 24.92 | 15.52 | 9.40 |
| | | 16QAM | 23330/793 | 25.33 | 16.10 | 9.23 |


*This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.*

## 5.5. Frequency Stability

### Ambient condition

| Temperature | Relative humidity | Pressure |
|---|---|---|
| 23°C ~25°C | 45%~50% | 101.5kPa |

### Method of Measurement

1. Frequency Stability (Temperature Variation)
   The temperature inside the climate chamber is varied from -40°C to +85°C in 10°C step size,
   (1) With all power removed, the temperature was decreased to 0°C and permitted to stabilize for three hours.
   (2) Measure the carrier frequency with the test equipment in a “call mode”. These measurements should be made within 1 minute of powering up the mobile station, to prevent significant self warming.
   (3) Repeat the above measurements at 10°C increments from -40°C to +85°C. Allow at least 1.5 hours at each temperature, un-powered, before making measurements.
2. Frequency Stability (Voltage Variation)
   The frequency stability shall be measured with variation of primary supply voltage as follows:
   (1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.
   (2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery-operating end point which shall be specified by the manufacturer.
   This transceiver is specified to operate with an input voltage of between 2.6 V and 4.8V, with a nominal voltage of 3.3V.

### Test setup





*This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.*

**Limits**

90.539 (c) The frequency stability of mobile, portable, and control transmitters operating in the narrowband segment must be 400 parts per billion or better when AFC is locked to the base station. When AFC is not locked to the base station, the frequency stability must be at least 1.0 ppm for 6.25 kHz, 1.5 ppm for 12.5 kHz (2 channel aggregate), and 2.5 ppm for 25 kHz (4 channel aggregate).

**Measurement Uncertainty**

The assessed measurement uncertainty to ensure 99.75％ confidence level for the normal distribution is with the coverage factor $k$ = 3,$U$= 0.01ppm.


*This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.*

## Test Result

| LTE Band 14 | | | | | | |
|---|---|---|---|---|---|---|
| Condition | | Freq.Error (Hz) | Freq.Error (Hz) | Frequency Stability（ppm） | Frequency Stability（ppm） | Verdict |
| BANDWIDTH | 10MHz | | | | | |
| Temperature | Voltage | 16QAM | QPSK | 16QAM | QPSK | |
| Normal（25℃） | Normal | 11.90 | 7.03 | 0.00633 | 0.00374 | PASS |
| Extreme（85℃） | | 17.44 | 5.25 | 0.00928 | 0.00279 | PASS |
| Extreme（80℃） | | 6.43 | 7.65 | 0.00342 | 0.00407 | PASS |
| Extreme（70℃） | | 2.88 | 11.65 | 0.00153 | 0.00620 | PASS |
| Extreme（60℃） | | 11.88 | 11.48 | 0.00632 | 0.00611 | PASS |
| Extreme（50℃） | | 16.39 | 2.41 | 0.00872 | 0.00128 | PASS |
| Extreme（40℃） | | 12.99 | 15.33 | 0.00691 | 0.00815 | PASS |
| Extreme（30℃） | | 12.66 | 16.04 | 0.00673 | 0.00853 | PASS |
| Extreme（20℃） | | 17.06 | 17.83 | 0.00907 | 0.00948 | PASS |
| Extreme（10℃） | | 2.96 | 17.66 | 0.00158 | 0.00939 | PASS |
| Extreme（0℃） | | 7.93 | 16.56 | 0.00422 | 0.00881 | PASS |
| Extreme（-10℃） | | 16.04 | 13.68 | 0.00853 | 0.00728 | PASS |
| Extreme（-20℃） | | 13.02 | 15.10 | 0.00693 | 0.00803 | PASS |
| Extreme（-30℃） | | 12.47 | 1.14 | 0.00663 | 0.00060 | PASS |
| Extreme（-40℃） | | 4.15 | 15.79 | 0.00221 | 0.00840 | PASS |
| 25℃ | LV | 1.95 | 4.55 | 0.00104 | 0.00242 | PASS |
| | HV | 16.31 | 12.09 | 0.00868 | 0.00643 | PASS |


*This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.*

## 5.6. Spurious Emissions at Antenna Terminals

### Ambient condition

| Temperature | Relative humidity | Pressure |
|---|---|---|
| 23°C ~25°C | 45%~50% | 101.5kPa |

### Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The measurement is carried out using a spectrum analyzer. The spectrum analyzer scans from 30MHz to the 10th harmonic of the carrier. The peak detector is used. Set RBW 1MHz and VBW 3MHz， Sweep is set to ATUO.

Of those disturbances below (limit – 20 dB), the mark is not required for the EUT.

### Test setup




### Limits

90.543 Emission limitations (e) For operations in the 758-768 MHz and the 788-798 MHz bands, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

(1) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than 76 + 10 log (P) dB in a 6.25 kHz band segment, for base and fixed stations.

(2) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than 65 + 10 log (P) dB in a 6.25 kHz band segment, for mobile and portable stations.

(3) On any frequency between 775-788 MHz, above 805 MHz, and below 758 MHz, by at least 43 + 10 log (P) dB.

(4) Compliance with the provisions of paragraphs (e)(1) and (2) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.


*This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.*

(5) Compliance with the provisions of paragraph (e)(3) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of 30 kHz may be employed.

(f) For operations in the 758-775 MHz and 788-805 MHz bands, all emissions including harmonics in the band 1559-1610 MHz shall be limited to −70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and −80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

**Measurement Uncertainty**

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor *k* = 1.96.

| Frequency | Uncertainty |
|---|---|
| 100kHz-1GHz | 0.684 dB |
| 1GHz-12.75GHz | 1.407 dB |


*This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.*

## Test Result

If disturbances were found more than 20dB below limit line, the mark is not required for the EUT.
The signal beyond the limit is carrier.

LTE Band 14 5MHz CH-Low 30MHz~1GHz




Date: 29.OCT.2019 17:37:42

LTE Band 14 5MHz CH-Low 1GHz~9GHz




Date: 29.OCT.2019 17:35:02

LTE Band 14 5MHz CH- Middle 30MHz~1GHz




Date: 29.OCT.2019 17:38:20

LTE Band 14 5MHz CH- Middle 1GHz~9GHz




Date: 29.OCT.2019 17:35:42

LTE Band 14 5MHz CH-High 30MHz~1GHz




Date: 29.OCT.2019 17:38:55

LTE Band 14 5MHz CH-High 1GHz~9GHz




Date: 29.OCT.2019 17:36:01


*This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.*

LTE Band 14 10MHz CH- Middle 30MHz~1GHz




Date: 29.OCT.2019 17:36:51

LTE Band 14 10MHz CH- Middle 1GHz~9GHz




Date: 29.OCT.2019 17:36:24


*This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.*

## 5.7. Radiates Spurious Emission

**Ambient condition**

| Temperature | Relative humidity | Pressure |
|---|---|---|
| 23°C ~25°C | 45%~50% | 101.5kPa |

**Method of Measurement**

1. The testing follows FCC KDB 971168 D01 v03r01 Section 5.8 and ANSI C63.26 (2015).
2. Above 30MHz: The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H). Above 1GHz: (Note: the FCC's permission to use 1.5m as an alternative per TCBC Conf call of Dec. 2, 2014.) The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).
3. A loop antenna, A log-periodic antenna or horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
4. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=200Hz,VBW=600Hz for 9kHz150kHz , RBW=10kHz, VBW=30kHz 150kHz-30MHz , RBW=100kHz,VBW=300kHz for 30MHz to 1GHz and RBW=1MHz, VBW=3MHz for above 1GHz, And the maximum value of the receiver should be recorded as (Pr).
5. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
6. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (Pcl) ,the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test.
7. The measurement results are obtained as described below:
Power(EIRP)=PMea- PAg - Pcl + Ga
The measurement results are amend as described below:
Power(EIRP)=PMea- Pcl + Ga
8. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi)


*This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.*

and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP-2.15dBi.

The modulation mode and RB allocation refer to section 5.1, using the maximum output power configuration.

**Test setup**

**9KHz ~ 30MHz**




**30MHz~~~ 1GHz**




**Above 1GHz**




Note: Area side:2.4mX3.6m


*This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.*

**Limits**

90.543 Emission limitations (e) For operations in the 758-768 MHz and the 788-798 MHz bands, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

(1) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than 76 + 10 log (P) dB in a 6.25 kHz band segment, for base and fixed stations.

(2) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than 65 + 10 log (P) dB in a 6.25 kHz band segment, for mobile and portable stations.

(3) On any frequency between 775-788 MHz, above 805 MHz, and below 758 MHz, by at least 43 + 10 log (P) dB.

(4) Compliance with the provisions of paragraphs (e)(1) and (2) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.

(5) Compliance with the provisions of paragraph (e)(3) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of 30 kHz may be employed.

(f) For operations in the 758-775 MHz and 788-805 MHz bands, all emissions including harmonics in the band 1559-1610 MHz shall be limited to −70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and −80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

**Measurement Uncertainty**

The assessed measurement uncertainty to ensure 95％ confidence level for the normal distribution is with the coverage factor $k$ = 1.96, $U$= 3.55 dB.


*This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.*

**Test Result**

Sweep the whole frequency band through the range from 9kHz to the 10th harmonic of the carrier, the emissions below the noise floor will not be recorded in the report.

LTE Band 14 QPSK 5MHz CH-Middle, RB 1

| Harmonic | Frequency (MHz) | SG (dBm) | Cable Loss (dB) | Gain (dBi) | Antenna Polarization | ERP Level (dBm) | Limit (dBm) | Margin (dB) | Azimuth (deg) |
|---|---|---|---|---|---|---|---|---|---|
| 2 | 1581.6 | -51.04 | 2.00 | 10.75 | Horizontal | -44.44 | -13.00 | 31.44 | 135 |
| 3 | 2379.0 | -44.17 | 2.51 | 11.05 | Horizontal | -37.78 | -13.00 | 24.78 | 45 |
| 4 | 3172.0 | -51.65 | 4.20 | 11.15 | Horizontal | -46.85 | -13.00 | 33.85 | 125 |
| 5 | 3965.0 | -60.28 | 5.20 | 11.15 | Horizontal | -56.48 | -13.00 | 43.48 | 180 |
| 6 | 4758.0 | -59.81 | 5.50 | 11.95 | Horizontal | -55.51 | -13.00 | 42.51 | 90 |
| 7 | 5551.0 | -61.31 | 5.70 | 13.55 | Horizontal | -55.61 | -13.00 | 42.61 | 0 |
| 8 | 6344.0 | -58.31 | 6.30 | 13.75 | Horizontal | -53.01 | -13.00 | 40.01 | 315 |
| 9 | 7137.0 | -53.95 | 6.80 | 13.85 | Horizontal | -49.05 | -13.00 | 36.05 | 45 |
| 10 | 7930.0 | -54.26 | 6.90 | 14.25 | Horizontal | -49.06 | -13.00 | 36.06 | 315 |

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.
2. The worst emission was found in the antenna is Horizontal position.

LTE Band 14 QPSK 10MHz CH-Middle, RB 1

| Harmonic | Frequency (MHz) | SG (dBm) | Cable Loss (dB) | Gain (dBi) | Antenna Polarization | ERP Level (dBm) | Limit (dBm) | Margin (dB) | Azimuth (deg) |
|---|---|---|---|---|---|---|---|---|---|
| 2 | 1577.1 | -53.53 | 2.00 | 10.75 | Horizontal | -46.93 | -40.00 | 6.93 | 180 |
| 3 | 2378.4 | -43.93 | 2.51 | 11.05 | Horizontal | -37.54 | -13.00 | 24.54 | 225 |
| 4 | 3172.0 | -50.10 | 4.20 | 11.15 | Horizontal | -45.30 | -13.00 | 32.30 | 315 |
| 5 | 3965.0 | -59.20 | 5.20 | 11.15 | Horizontal | -55.40 | -13.00 | 42.40 | 45 |
| 6 | 4758.0 | -60.00 | 5.50 | 11.95 | Horizontal | -55.70 | -13.00 | 42.70 | 0 |
| 7 | 5551.0 | -61.50 | 5.70 | 13.55 | Horizontal | -55.80 | -13.00 | 42.80 | 90 |
| 8 | 6344.0 | -58.30 | 6.30 | 13.75 | Horizontal | -53.00 | -13.00 | 40.00 | 45 |
| 9 | 7137.0 | -54.40 | 6.80 | 13.85 | Horizontal | -49.50 | -13.00 | 36.50 | 315 |
| 10 | 7930.0 | -52.60 | 6.90 | 14.25 | Horizontal | -47.40 | -13.00 | 34.40 | 135 |

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.
2. The worst emission was found in the antenna is Horizontal position.


*This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.*

# 6. Main Test Instruments

| Name | Manufacturer | Type | Serial Number | Calibration Date | Expiration Date |
|---|---|---|---|---|---|
| Base Station Simulator | R&S | CMW500 | 113645 | 2019-05-19 | 2020-05-18 |
| Power Splitter | Hua Xiang | SHX-GF2-2-13 | 10120101 | / | / |
| Spectrum Analyzer | Agilent | N9010A | MY50210259 | 2019-05-19 | 2020-05-18 |
| Universal Radio Communication Tester | Agilent | E5515C | MY48367192 | 2019-05-19 | 2020-05-18 |
| Signal Analyzer | R&S | FSV40 | 15195-01-00 | 2019-05-19 | 2020-05-18 |
| Trilog Antenna | SCHWARZBECK | VUBL 9163 | 9163-201 | 2017-11-18 | 2020-11-17 |
| Horn Antenna | R&S | HF907 | 100126 | 2018-07-07 | 2020-07-06 |
| Signal generator | R&S | SMB 100A | 102594 | 2019-05-19 | 2020-05-18 |
| Climatic Chamber | ESPEC | SU-242 | 93000506 | 2017-12-17 | 2020-12-16 |
| RF Cable | Agilent | SMA 15cm | 0001 | 2019-12-13 | 2020-6-12 |
| Software | R&S | EMC32 | 9.26.0 | / | / |

********END OF REPORT ********


*This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.*