

FCC Radio Test Report

FCC ID: XMR2020EM160RGL2

Report No. : BTL-FCCP-1-2311T077
Equipment : LTE-A Cat 16 M.2 Module
Model Name : EM160R-GL
Brand Name : Quectel
Applicant : Quectel Wireless Solutions Company Limited
Address : Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, China 200233

Radio Function : WCDMA Band V & LTE Band 5, 26

FCC Rule Part(s) : FCC CFR Title 47, Part 22, Subpart H


Date of Receipt : 2023/12/5
Date of Test : 2023/12/25 ~ 2024/1/12
Issued Date : 2024/1/30

The above equipment has been tested and found in compliance with the requirement of the above standards by BTL Inc.

Prepared by

: 
Jerry Chuang, Supervisor

Approved by

: 
Peter Chen, Manager



BTL Inc.

No.18, Ln. 171, Sec. 2, Jiuzong Rd., Neihu Dist., Taipei City 114, Taiwan

Tel: +886-2-2657-3299 Fax: +886-2-2657-3331 Web: www.newbtl.com Service mail: btl_qa@newbtl.com

Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

BTL's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

This report is the confidential property of the client. As a mutual protection to the clients, the public and ourselves, the test report shall not be reproduced, except in full, without our written approval.

BTL's laboratory quality assurance procedures are in compliance with the **ISO/IEC 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

BTL is not responsible for the sampling stage, so the results only apply to the sample as received.

The information, data and test plan are provided by manufacturer which may affect the validity of results, so it is manufacturer's responsibility to ensure that the apparatus meets the essential requirements of applied standards and in all the possible configurations as representative of its intended use.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Please note that the measurement uncertainty is provided for informational purpose only and are not use in determining the Pass/Fail results.

CONTENTS

1	SUMMARY OF TEST RESULTS	5
1.1	REFERENCE TEST GUIDANCE	6
1.2	TEST FACILITY	6
1.3	MEASUREMENT UNCERTAINTY	6
1.4	TEST ENVIRONMENT CONDITIONS	6
2	GENERAL INFORMATION	7
2.1	DESCRIPTION OF EUT	7
2.2	TEST MODES	9
2.3	BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	10
2.4	SUPPORT UNITS	10
3	EFFECTIVE RADIATED POWER MEASUREMENT	11
3.1	LIMIT	11
3.2	TEST PROCEDURE	11
3.3	DEVIATION FROM TEST STANDARD	11
3.4	TEST SETUP	11
3.5	EUT OPERATING CONDITIONS	11
3.6	TEST RESULT	11
4	RADIATED SPURIOUS EMISSIONS MEASUREMENT	12
4.1	LIMIT	12
4.2	TEST PROCEDURE	12
4.3	DEVIATION FROM TEST STANDARD	12
4.4	TEST SETUP	13
4.5	EUT OPERATING CONDITIONS	13
4.6	TEST RESULT	13
5	LIST OF MEASURING EQUIPMENTS	14
6	EUT TEST PHOTO	15
7	EUT PHOTOS	15
APPENDIX A	EFFECTIVE RADIATED POWER	16
APPENDIX B	RADIATED SPURIOUS EMISSIONS	23

REVISION HISTORY

Report No.	Version	Description	Issued Date	Note
BTL-FCCP-1-2311T077	R00	Original Report.	2024/1/30	Valid

1 SUMMARY OF TEST RESULTS

Test procedures according to the technical standards.

Standard(s) Section	Description	Test Result	Judgement	Remark
2.1046 22.913(a)(5)	Effective Radiated Power	APPENDIX A	Pass	-----
2.1053 22.917(a)	Radiated Spurious Emissions	APPENDIX B	Pass	-----

NOTE:

- (1) "N/A" denotes test is not applicable in this Test Report.
- (2) The report format version is TP.1.1.1.
- (3) This test report is issued for the RF module (FCCID: XMR2020EM160RGL2) to be incorporated to the host device (Model number: TP00157A), Product name: Notebook Computer).
Since the RF module has been certificated, after evaluation, above test items were criticized and reconfirmed in this report.
- (4) After spot check, this revision does not change original radio parameters.

1.1 REFERENCE TEST GUIDANCE

ANSI C63.26-2015
ANSI/TIA-603-E-2016
FCC KDB 971168 D01 Power Meas License Digital Systems v03r01

1.2 TEST FACILITY

The test locations stated below are under the TAF Accreditation Number 0659.

The test location(s) used to collect the test data in this report are:

No. 68-1, Ln. 169, Sec. 2, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan
(FCC DN: TW0659)

☐ C05 ☐ SR10 ☒ SR11

No. 72, Ln. 169, Sec. 2, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan
(FCC DN: TW0659)

☐ C06 ☒ CB21 ☐ CB22

1.3 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k = 2$, providing a level of confidence of approximately **95 %**.

The measurement instrumentation uncertainty considerations contained in CISPR 16-4-2. The BTL measurement uncertainty is less than the CISPR 16-4-2 U_{CISPR} requirement.

A. Radiated emissions test:

Test Site	Measurement Frequency Range	U,(dB)
CB21	0.03 GHz ~ 0.2 GHz	4.17
	0.2 GHz ~ 1 GHz	4.72
	1 GHz ~ 6 GHz	5.21
	6 GHz ~ 18 GHz	5.51
	18 GHz ~ 26 GHz	3.69
	26 GHz ~ 40 GHz	4.23

NOTE:

Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

1.4 TEST ENVIRONMENT CONDITIONS

Test Item	Environment Condition	Test Voltage	Tested by
Effective Radiated Power	23.2 °C, 45 %	AC 120V	Jerry Chuang
Radiated Spurious Emissions	Refer to data	AC 120V	Kevin Zhen

2 GENERAL INFORMATION

2.1 DESCRIPTION OF EUT

Equipment	LTE-A Cat 16 M.2 Module			
Model Name	EM160R-GL			
Brand Name	Quectel			
Model Difference	N/A			
Power Source	Supplied from host system.			
Power Rating	3.1 ~4.1Vdc, typical 3.7Vdc			
Host device information				
Equipment	Notebook Computer			
Model Name	TP00157A			
Brand Name	Lenovo			
Model Difference	N/A			
Power Source	DC voltage supplied from External Power Supply. (Lenovo/ ADL135YSDC3A)			
Power Rating	I/P: 100-240V~ 2.5A 50-60Hz O/P: 20.0VDC 6.75A 135.0W / 19.95VDC 5.0A / 15.0VDC 3.0A / 9.0VDC 3.0A / 5.0VDC 3.0A 15.0W			
WIFI+BT Module	Intel® Wi-Fi 6E AX211 / AX211D2W			
WWAN Module	Quectel / EM160R-GL			
Operation Frequency	Band	UL Frequency (MHz)	DL Frequency (MHz)	
	WCDMA V	824 ~ 849	869 ~ 894	
	LTE 5	824 ~ 849	869 ~ 894	
	LTE 26	824 ~ 849	869 ~ 894	
Maximum ERP	Band	BW (MHz)	Mode	Power (W)
	WCDMA V	-	-	0.086
	LTE 5/26	1.4	QPSK	0.096
			16QAM	0.090
			64QAM	0.069
		3	QPSK	0.098
			16QAM	0.091
			64QAM	0.071
		5	QPSK	0.099
			16QAM	0.092
			64QAM	0.071
		10	QPSK	0.100
			16QAM	0.093
			64QAM	0.073
	15	QPSK	0.102	
16QAM		0.094		
64QAM		0.074		
Test Model	EM160R-GL			
Sample Status	Engineering Sample			
EUT Modification(s)	N/A			

NOTE:

- (1) The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.

(2) Table for Filed Antenna:

Antenna	Manufacture	Parts Number	Type	Connector	Gain (dBi)	Note
Main	Luxshare-ICT	DC330023020	PIFA	I-PEX	-1.78	WCDMA Band V
					-1.78	LTE Band 5
Aux	Luxshare-ICT	DC330023030	PIFA	I-PEX	-	LTE Band 26
						RX only

Antenna	Manufacture	Parts Number	Type	Connector	Gain (dBi)	Note
Main	SPEEDWIRE	DC330023120	PIFA	I-PEX	-1.62	WCDMA Band V
					-1.56	LTE Band 5
Aux	SPEEDWIRE	DC330023130	PIFA	I-PEX	-	LTE Band 26
						RX only

- (3) The above Antenna information are derived from the antenna data sheet provided by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

2.2 TEST MODES


Test Items	Band	Test Mode	Note
Effective Radiated Power	WCDMA Band V	Refer to APPENDIX A	-
	LTE Band 5/26		
Radiated Spurious Emissions (Below 1G)	WCDMA Band V	TX Mode (CH 4182)	-
	LTE Band 5	TX Mode (CH 20525)	-
	LTE Band 26	TX Mode (CH 26865)	-
Radiated Spurious Emissions (Above 1G)	WCDMA Band V	TX Mode (CH 4132/4183/4233)	-
	LTE Band 5	TX Mode (CH 20450/20525/20600)	-
	LTE Band 26	TX Mode (CH 26865/26915/26965)	-

NOTE:

- (1) All X, Y and Z axes are evaluated, but only the worst case (X axis) is recorded.
- (2) For Radiated Spurious Emissions both QPSK, 16QAM and 64QAM are evaluated, but only the worst case (QPSK) is recorded.
- (3) LTE Band 26 (814 ~ 849 MHz) overlaps the entire frequency range of LTE Band 5 (824 ~ 849 MHz). Therefore, test data provided in this report covers Band 5 as well as Band 26.

2.3 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Equipment letters and Cable numbers refer to item numbers described in the tables of clause 2.4.



2.4 SUPPORT UNITS

Item	Equipment	Brand	Model No.	Series No.	Remarks
A	NB	HP	TPN-I119	N/A	Furnished by test lab.
B	ADP	Lenovo	ADL135YSDC3 A	N/A	Supplied by test requester.
C	USB 2.5" HDD	TOSIBA	XS700	483B60M9KQSS	Furnished by test lab.
D	27" 4K Monitor	DELL	U2720Q	CN-083VF-WSL0 0-0B7-332L	Furnished by test lab.
E	Mouse	Lenovo	SM-8823	N/A	Furnished by test lab.
F	Ear Phone	HTC	N/A	N/A	Furnished by test lab.
G	Keyboard	Bloody	KB-8	N/A	Furnished by test lab.

Item	Shielded	Ferrite Core	Length	Cable Type	Remarks
1	N/A	N/A	0.9m	Power Cord	Supplied by test requester.
2	N/A	N/A	1m	Type C to USB Cable	Furnished by test lab.
3	N/A	N/A	1.8m	HDMI	Furnished by test lab.
4	N/A	N/A	10m	RJ45 Cable	Furnished by test lab.

3 EFFECTIVE RADIATED POWER MEASUREMENT

3.1 LIMIT

The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts (38.45 dBm).

3.2 TEST PROCEDURE

The testing follows FCC KDB 971168 v03r01 Section 5.8.


- Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value " of step a. Record the power level of S.G
- $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn.}$
- ERP can be calculated form EIRP by subtracting the gain of dipole, $ERP = EIPR - 2.15\text{dBi.}$
- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.

3.3 DEVIATION FROM TEST STANDARD

No deviation.

3.4 TEST SETUP

Conducted Measurement:



3.5 EUT OPERATING CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

3.6 TEST RESULT

Please refer to the APPENDIX A.

4 RADIATED SPURIOUS EMISSIONS MEASUREMENT

4.1 LIMIT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm.

NOTE:

(1) The test result calculated as following:

Measurement Value = Reading Level + Correct Factor

Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain(if use)

Margin Level = Measurement Value - Limit Value

Calculation example:

Reading Level (dBm)		Correct Factor (dB/m)		Measurement Value (dBm)
-50.43	+	-2.11	=	-52.54

Measurement Value (dBm)		Limit Value (dBm)		Margin Level (dB)
-52.54	-	-13	=	-39.54

4.2 TEST PROCEDURE


The testing follows FCC KDB 971168 v03r01 Section 6.2.

- Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value " of step a. Record the power level of S.G
- $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn.}$
- ERP can be calculated form EIRP by subtracting the gain of dipole, $ERP = EIPR - 2.15\text{dBi.}$
- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.

4.3 DEVIATION FROM TEST STANDARD

No deviation.

4.4 TEST SETUP



4.5 EUT OPERATING CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

4.6 TEST RESULT

Please refer to the APPENDIX B.

5 LIST OF MEASURING EQUIPMENTS

Effective Radiated Power						
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated Date	Calibrated Until
1	WIRELESS COMMUNICATION TEST SET	Agilent	E5515C	GB47390193	2023/7/4	2024/7/3
2	Radio Communication Test Station	ANRITSU	MT8821C	6262044728	2023/11/22	2024/11/21

Radiated Emissions						
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated Date	Calibrated Until
1	Preamplifier	EMCI	EMC330N	980850	2023/9/6	2024/9/5
2	Preamplifier	EMCI	EMC118A45SE	980819	2023/3/7	2024/3/6
3	Pre-Amplifier	EMCI	EMC184045SE	980907	2023/9/21	2024/9/20
4	Test Cable	EMCI	EMC104-SM-1000	180809	2023/7/10	2024/7/9
5	Test Cable	EMCI	EMC104-SM-SM-3000	220322	2023/3/14	2024/3/13
6	Test Cable	EMCI	EMC104-SM-SM-7000	220324	2023/3/14	2024/3/13
7	EXA Signal Analyzer	keysight	N9020B	MY57120120	2023/2/24	2024/2/23
8	Horn Antenna	RFSPIN	DRH18-E	211202A18EN	2023/5/12	2024/5/11
9	Horn Ant	Schwarzbeck	BBHA 9170D	1136	2023/5/12	2024/5/11
10	Log-bicon Antenna	Schwarzbeck	VULB9168	1369	2023/5/9	2024/5/8
11	6dB Attenuator	EMCI	EMCI-N-6-06	AT-06001	2023/5/9	2024/5/8
12	Test Cable	EMCI	EMC101G-KM-KM-3000	220329	2023/3/14	2024/3/13
13	Test Cable	EMCI	EMC102-KM-KM-1000	220327	2023/3/14	2024/3/13
14	Measurement Software	EZ	EZ EMC (Version NB-03A1-01)	N/A	N/A	N/A
15	WIRELESS COMMUNICATION TEST SET	Agilent	E5515C	GB47390193	2023/7/4	2024/7/3
16	Radio Communication Test Station	ANRITSU	MT8821C	6262044728	2023/11/22	2024/11/21

Remark: "N/A" denotes no model name, no serial no. or no calibration specified.
All calibration period of equipment list is one year.

6 EUT TEST PHOTO

Please refer to document Appendix No.: TP-2311T077-FCCP-1 (APPENDIX-TEST PHOTOS).

7 EUT PHOTOS

Please refer to document Appendix No.: EP-2311T077-1 (APPENDIX-EUT PHOTOS).

APPENDIX A EFFECTIVE RADIATED POWER

WCDMA Band V Power:

Band	Mode	UL/DL Channel No.	Frequency(MHz)	Average power(dBm)	ERP Power (dBm)	ERP Power (W)
WCDMA Band V	Rel 99	4132/4357	826.4	23.10	19.33	0.086
		4183/4408	836.6	23.11	19.34	0.086
		4233/4458	846.6	23.04	19.27	0.085

Band	Sub-test	UL/DL Channel No.	Frequency(MHz)	Average power(dBm)	ERP Power (dBm)	ERP Power (W)
HSDPA V	1	4132/4357	826.4	21.99	18.22	0.066
		4183/4408	836.6	21.99	18.22	0.066
		4233/4458	846.6	21.90	18.13	0.065
	2	4132/4357	826.4	21.98	18.21	0.066
		4183/4408	836.6	21.97	18.20	0.066
		4233/4458	846.6	21.89	18.12	0.065
	3	4132/4357	826.4	21.48	17.71	0.059
		4183/4408	836.6	21.46	17.69	0.059
		4233/4458	846.6	21.38	17.61	0.058
	4	4132/4357	826.4	21.47	17.70	0.059
		4183/4408	836.6	21.45	17.68	0.059
		4233/4458	846.6	21.39	17.62	0.058

Band	Sub-test	UL/DL Channel No.	Frequency(MHz)	Average power(dBm)	ERP Power (dBm)	ERP Power (W)
HSUPA V	1	4132/4357	826.4	21.96	18.19	0.066
		4183/4408	836.6	21.98	18.21	0.066
		4233/4458	846.6	21.92	18.15	0.065
	2	4132/4357	826.4	19.98	16.21	0.042
		4183/4408	836.6	19.97	16.20	0.042
		4233/4458	846.6	19.92	16.15	0.041
	3	4132/4357	826.4	20.97	17.20	0.052
		4183/4408	836.6	20.96	17.19	0.052
		4233/4458	846.6	20.89	17.12	0.052
	4	4132/4357	826.4	19.99	16.22	0.042
		4183/4408	836.6	19.98	16.21	0.042
		4233/4458	846.6	19.91	16.14	0.041
	5	4132/4357	826.4	21.96	18.19	0.066
		4183/4408	836.6	21.98	18.21	0.066
		4233/4458	846.6	21.89	18.12	0.065

LTE Band 5/26 Power:

Band	BW (MHz)	Channel	Frequency (MHz)	Mode	UL RB Allocation	UL RB Offset	MPR	Average power (dBm)	ERP power (dBm)	ERP power (W)
5/26	1.4	26697	814.7	QPSK	1	0	0	23.10	19.39	0.087
					1	2	0	22.92	19.21	0.083
					1	5	0	23.04	19.33	0.086
					6	0	1	22.89	19.18	0.083
				16QAM	1	0	1	23.23	19.52	0.090
					1	2	1	23.09	19.38	0.087
					1	5	1	23.15	19.44	0.088
					6	0	2	21.87	18.16	0.065
				64QAM	1	0	1	22.11	18.40	0.069
					1	2	1	22.06	18.35	0.068
					1	5	1	22.07	18.36	0.069
					6	0	2	20.90	17.19	0.052
		26865	831.5	QPSK	1	0	0	23.54	19.83	0.096
					1	2	0	23.40	19.69	0.093
					1	5	0	23.39	19.68	0.093
					6	0	1	22.73	19.02	0.080
				16QAM	1	0	1	23.02	19.31	0.085
					1	2	1	23.00	19.29	0.085
					1	5	1	22.91	19.20	0.083
					6	0	2	21.57	17.86	0.061
				64QAM	1	0	1	22.03	18.32	0.068
					1	2	1	21.95	18.24	0.067
					1	5	1	21.94	18.23	0.067
					6	0	2	20.78	17.07	0.051
		27033	848.3	QPSK	1	0	0	23.04	19.33	0.086
					1	2	0	23.03	19.32	0.086
					1	5	0	22.83	19.12	0.082
					6	0	1	22.86	19.15	0.082
				16QAM	1	0	1	23.20	19.49	0.089
					1	2	1	23.14	19.43	0.088
					1	5	1	23.03	19.32	0.086
					6	0	2	21.83	18.12	0.065
				64QAM	1	0	1	21.61	17.90	0.062
					1	2	1	21.51	17.80	0.060
					1	5	1	21.12	17.41	0.055
					6	0	2	20.38	16.67	0.046

NOTE:

(1) EIRP = Average power + Antenna gain.

(2) ERP = EIRP - 2.15.

(3) $P(W) = 1 \text{ W} \cdot 10^{(P(\text{dBm}) / 10)} / 1000$

Band	BW (MHz)	Channel	Frequency (MHz)	Mode	UL RB Allocation	UL RB Offset	MPR	Average power (dBm)	ERP power (dBm)	ERP power (W)
5/26	3	26705	815.5	QPSK	1	0	0	23.15	19.44	0.088
					1	7	0	23.00	19.29	0.085
					1	14	0	23.11	19.40	0.087
					15	0	1	22.96	19.25	0.084
				16QAM	1	0	1	23.29	19.58	0.091
					1	7	1	23.17	19.46	0.088
					1	14	1	23.23	19.52	0.090
					15	0	2	21.93	18.22	0.066
				64QAM	1	0	1	22.18	18.47	0.070
					1	7	1	22.10	18.39	0.069
					1	14	1	22.15	18.44	0.070
					15	0	2	20.95	17.24	0.053
		26865	831.5	QPSK	1	0	0	23.62	19.91	0.098
					1	7	0	23.46	19.75	0.094
					1	14	0	23.45	19.74	0.094
					15	0	1	22.78	19.07	0.081
				16QAM	r	0	1	23.09	19.38	0.087
					1	7	1	23.06	19.35	0.086
					1	14	1	22.98	19.27	0.085
					15	0	2	21.63	17.92	0.062
				64QAM	1	0	1	22.11	18.40	0.069
					1	7	1	21.99	18.28	0.067
					1	14	1	21.99	18.28	0.067
					15	0	2	20.83	17.12	0.052
		27025	847.5	QPSK	1	0	0	23.09	19.38	0.087
					1	7	0	23.07	19.36	0.086
					1	14	0	22.88	19.17	0.083
					15	0	1	22.92	19.21	0.083
				16QAM	1	0	1	23.27	19.56	0.090
					1	7	1	23.22	19.51	0.089
					1	14	1	23.07	19.36	0.086
					15	0	2	21.89	18.18	0.066
				64QAM	1	0	1	21.66	17.95	0.062
					1	7	1	21.58	17.87	0.061
					1	14	1	21.19	17.48	0.056
					15	0	2	20.43	16.72	0.047

NOTE:

(1) EIRP = Average power + Antenna gain.

(2) ERP = EIRP - 2.15.

(3) $P(W) = 1 \text{ W} \cdot 10^{(P(\text{dBm}) / 10)} / 1000$

Band	BW (MHz)	Channel	Frequency (MHz)	Mode	UL RB Allocation	UL RB Offset	MPR	Average power (dBm)	ERP power (dBm)	ERP power (W)
5/26	5	26715	816.5	QPSK	1	0	0	23.20	19.49	0.089
					1	12	0	23.07	19.36	0.086
					1	24	0	23.18	19.47	0.089
					25	0	1	23.02	19.31	0.085
				16QAM	1	0	1	23.35	19.64	0.092
					1	12	1	23.23	19.52	0.090
					1	24	1	23.28	19.57	0.091
					25	0	2	22.00	18.29	0.067
				64QAM	1	0	1	22.25	18.54	0.071
					1	12	1	22.16	18.45	0.070
					1	24	1	22.20	18.49	0.071
					25	0	2	21.03	17.32	0.054
		26865	831.5	QPSK	1	0	0	23.67	19.96	0.099
					1	12	0	23.50	19.79	0.095
					1	24	0	23.52	19.81	0.096
					25	0	1	22.84	19.13	0.082
				16QAM	1	0	1	23.17	19.46	0.088
					1	12	1	23.10	19.39	0.087
					1	24	1	23.05	19.34	0.086
					25	0	2	21.70	17.99	0.063
				64QAM	1	0	1	22.16	18.45	0.070
					1	12	1	22.07	18.36	0.069
					1	24	1	22.06	18.35	0.068
					25	0	2	20.90	17.19	0.052
		27015	846.5	QPSK	1	0	0	23.15	19.44	0.088
					1	12	0	23.12	19.41	0.087
					1	24	0	22.95	19.24	0.084
					25	0	1	22.99	19.28	0.085
				16QAM	1	0	1	23.33	19.62	0.092
					1	12	1	23.30	19.59	0.091
					1	24	1	23.12	19.41	0.087
					25	0	2	21.97	18.26	0.067
				64QAM	1	0	1	21.71	18.00	0.063
					1	12	1	21.65	17.94	0.062
					1	24	1	21.26	17.55	0.057
					25	0	2	20.48	16.77	0.048

NOTE:

(1) EIRP = Average power + Antenna gain.

(2) ERP = EIRP - 2.15.

(3) $P(W) = 1 \text{ W} \cdot 10^{(P(\text{dBm}) / 10)} / 1000$

Band	BW (MHz)	Channel	Frequency (MHz)	Mode	UL RB Allocation	UL RB Offset	MPR	Average power (dBm)	ERP power (dBm)	ERP power (W)
5/26	10	26740	819.0	QPSK	1	0	0	23.26	19.55	0.090
					1	24	0	23.13	19.42	0.087
					1	49	0	23.25	19.54	0.090
					50	0	1	23.08	19.37	0.086
				16QAM	1	0	1	23.40	19.69	0.093
					1	24	1	23.31	19.60	0.091
					1	49	1	23.34	19.63	0.092
					50	0	2	22.06	18.35	0.068
				64QAM	1	0	1	22.32	18.61	0.073
					1	24	1	22.23	18.52	0.071
					1	49	1	22.28	18.57	0.072
					50	0	2	21.09	17.38	0.055
		26865	831.5	QPSK	1	0	0	23.73	20.02	0.100
					1	24	0	23.57	19.86	0.097
					1	49	0	23.59	19.88	0.097
					50	0	1	22.91	19.20	0.083
				16QAM	1	0	1	23.22	19.51	0.089
					1	24	1	23.16	19.45	0.088
					1	49	1	23.11	19.40	0.087
					50	0	2	21.77	18.06	0.064
				64QAM	1	0	1	22.21	18.50	0.071
					1	24	1	22.12	18.41	0.069
					1	49	1	22.12	18.41	0.069
					50	0	2	20.95	17.24	0.053
		26990	844.0	QPSK	1	0	0	23.21	19.50	0.089
					1	24	0	23.20	19.49	0.089
					1	49	0	23.01	19.30	0.085
					50	0	1	23.04	19.33	0.086
				16QAM	1	0	1	23.39	19.68	0.093
					1	24	1	23.35	19.64	0.092
					1	49	1	23.17	19.46	0.088
					50	0	2	22.05	18.34	0.068
				64QAM	1	0	1	21.79	18.08	0.064
					1	24	1	21.72	18.01	0.063
					1	49	1	21.30	17.59	0.057
					50	0	2	20.54	16.83	0.048

NOTE:

(1) EIRP = Average power + Antenna gain.

(2) ERP = EIRP - 2.15.

(3) $P(W) = 1 \text{ W} \cdot 10^{(P(\text{dBm}) / 10)} / 1000$

Band	BW (MHz)	Channel	Frequency (MHz)	Mode	UL RB Allocation	UL RB Offset	MPR	Average power (dBm)	ERP power (dBm)	ERP power (W)
5/26	15	26765	821.5	QPSK	1	0	0	23.30	19.59	0.091
					1	37	0	23.19	19.48	0.089
					1	74	0	23.33	19.62	0.092
					75	0	1	23.12	19.41	0.087
				16QAM	1	0	1	23.46	19.75	0.094
					1	37	1	23.38	19.67	0.093
					1	74	1	23.41	19.70	0.093
					75	0	2	22.13	18.42	0.070
				64QAM	1	0	1	22.38	18.67	0.074
					1	37	1	22.29	18.58	0.072
					1	74	1	22.32	18.61	0.073
					75	0	2	21.15	17.44	0.055
		26865	831.5	QPSK	1	0	0	23.79	20.08	0.102
					1	37	0	23.64	19.93	0.098
					1	74	0	23.65	19.94	0.099
					75	0	1	22.98	19.27	0.085
				16QAM	1	0	1	23.26	19.55	0.090
					1	37	1	23.21	19.50	0.089
					1	74	1	23.17	19.46	0.088
					75	0	2	21.82	18.11	0.065
				64QAM	1	0	1	22.27	18.56	0.072
					1	37	1	22.19	18.48	0.070
					1	74	1	22.17	18.46	0.070
					75	0	2	21.01	17.30	0.054
		26965	841.5	QPSK	1	0	0	23.28	19.57	0.091
					1	37	0	23.24	19.53	0.090
					1	74	0	23.06	19.35	0.086
					75	0	1	23.11	19.40	0.087
				16QAM	1	0	1	23.43	19.72	0.094
					1	37	1	23.39	19.68	0.093
					1	74	1	23.23	19.52	0.090
					75	0	2	22.12	18.41	0.069
				64QAM	1	0	1	21.86	18.15	0.065
					1	37	1	21.79	18.08	0.064
					1	74	1	21.36	17.65	0.058
					75	0	2	20.62	16.91	0.049

NOTE:


(1) EIRP = Average power + Antenna gain.

(2) ERP = EIRP - 2.15.

(3) $P(W) = 1 W \cdot 10^{(P(dBm) / 10) / 1000}$

APPENDIX B RADIATED SPURIOUS EMISSIONS

Test Mode	WCDMA Band V	Test Date	2023/12/26
Test Channel	CH4182	Polarization	Vertical
Temp	21°C	Hum.	59%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1	*	93.1793	-59.59	-3.66	-63.25	-13.00	-50.25	peak	
2		163.2457	-67.69	0.10	-67.59	-13.00	-54.59	peak	
3		230.4990	-65.39	-0.60	-65.99	-13.00	-52.99	peak	
4		357.9893	-71.71	-0.56	-72.27	-13.00	-59.27	peak	
5		447.1647	-68.58	0.72	-67.86	-13.00	-54.86	peak	
6		525.8963	-68.40	3.59	-64.81	-13.00	-51.81	peak	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	WCDMA Band V	Test Date	2023/12/26
Test Channel	CH4182	Polarization	Horizontal
Temp	21°C	Hum.	59%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBm	dB	dBm	dBm	dB		
1		36.9517	-67.37	4.30	-63.07	-13.00	-50.07	peak	
2		91.2393	-58.83	-6.13	-64.96	-13.00	-51.96	peak	
3	*	144.9773	-57.89	-3.45	-61.34	-13.00	-48.34	peak	
4		230.4343	-63.57	-5.74	-69.31	-13.00	-56.31	peak	
5		365.2967	-65.82	-0.43	-66.25	-13.00	-53.25	peak	
6		526.7047	-71.21	1.07	-70.14	-13.00	-57.14	peak	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	WCDMA Band V	Test Date	2023/12/26
Test Channel	CH4132	Polarization	Vertical
Temp	21°C	Hum.	59%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBm	dB	dBm	dBm	dB		
1	*	1652.800	-63.76	5.62	-58.14	-13.00	-45.14	peak	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	WCDMA Band V	Test Date	2023/12/26
Test Channel	CH4132	Polarization	Horizontal
Temp	21°C	Hum.	59%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1	*	1652.800	-64.05	5.53	-58.52	-13.00	-45.52	peak	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	WCDMA Band V	Test Date	2023/12/26
Test Channel	CH4182	Polarization	Vertical
Temp	21°C	Hum.	59%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBm	dB	dBm	dBm	dB		
1	*	1672.800	-63.16	5.64	-57.52	-13.00	-44.52	peak	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	WCDMA Band V	Test Date	2023/12/26
Test Channel	CH4182	Polarization	Horizontal
Temp	21°C	Hum.	59%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBm	dB	dBm	dBm	dB		
1	*	1672.800	-64.12	5.57	-58.55	-13.00	-45.55	peak	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	WCDMA Band V	Test Date	2023/12/26
Test Channel	CH4233	Polarization	Vertical
Temp	21°C	Hum.	59%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBm	dB	dBm	dBm	dB		
1	*	1693.200	-63.50	5.66	-57.84	-13.00	-44.84	peak	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	WCDMA Band V	Test Date	2023/12/26
Test Channel	CH4233	Polarization	Horizontal
Temp	21°C	Hum.	59%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1	*	1693.200	-64.14	5.62	-58.52	-13.00	-45.52	peak	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	LTE Band 5	Test Date	2023/12/26
Test Channel	CH20525	Polarization	Vertical
Temp	21°C	Hum.	59%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBm	dB	dBm	dBm	dB		
1	*	90.1400	-58.45	-3.43	-61.88	-13.00	-48.88	peak	
2		144.7833	-66.25	-0.88	-67.13	-13.00	-54.13	peak	
3		229.8200	-66.43	-0.64	-67.07	-13.00	-54.07	peak	
4		300.7593	-71.60	-1.14	-72.74	-13.00	-59.74	peak	
5		432.7440	-70.57	0.47	-70.10	-13.00	-57.10	peak	
6		525.6053	-69.68	3.57	-66.11	-13.00	-53.11	peak	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	LTE Band 5	Test Date	2023/12/26
Test Channel	CH20525	Polarization	Horizontal
Temp	21°C	Hum.	59%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBm	dB	dBm	dBm	dB		
1		91.8213	-56.82	-6.10	-62.92	-13.00	-49.92	peak	
2	*	145.5270	-59.19	-3.46	-62.65	-13.00	-49.65	peak	
3		229.7877	-62.53	-5.76	-68.29	-13.00	-55.29	peak	
4		356.7283	-68.22	-0.46	-68.68	-13.00	-55.68	peak	
5		459.6453	-71.21	0.22	-70.99	-13.00	-57.99	peak	
6		590.8862	-74.07	2.11	-71.96	-13.00	-58.96	peak	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	LTE Band 5	Test Date	2023/12/25
Test Channel	CH20450	Polarization	Vertical
Temp	21°C	Hum.	58%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBm	dB	dBm	dBm	dB		
1	*	2475.200	-56.06	7.51	-48.55	-13.00	-35.55	peak	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	LTE Band 5	Test Date	2023/12/25
Test Channel	CH20450	Polarization	Horizontal
Temp	21°C	Hum.	58%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBm	dB	dBm	dBm	dB		
1	*	2499.200	-53.22	7.20	-46.02	-13.00	-33.02	peak	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	LTE Band 5	Test Date	2023/12/25
Test Channel	CH20525	Polarization	Vertical
Temp	21°C	Hum.	58%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBm	dB	dBm	dBm	dB		
1	*	2497.600	-42.95	7.35	-35.60	-13.00	-22.60	peak	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	LTE Band 5	Test Date	2023/12/25
Test Channel	CH20525	Polarization	Horizontal
Temp	21°C	Hum.	58%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBm	dB	dBm	dBm	dB		
1	*	2497.600	-46.61	7.21	-39.40	-13.00	-26.40	peak	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	LTE Band 5	Test Date	2023/12/25
Test Channel	CH20600	Polarization	Vertical
Temp	21°C	Hum.	58%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBm	dB	dBm	dBm	dB		
1	*	2520.000	-55.79	7.48	-48.31	-13.00	-35.31	peak	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	LTE Band 5	Test Date	2023/12/25
Test Channel	CH20600	Polarization	Horizontal
Temp	21°C	Hum.	58%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBm	dB	dBm	dBm	dB		
1	*	2520.000	-57.19	7.36	-49.83	-13.00	-36.83	peak	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	LTE Band 26	Test Date	2023/12/26
Test Channel	CH26865	Polarization	Vertical
Temp	21°C	Hum.	59%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBm	dB	dBm	dBm	dB		
1	*	89.6226	-60.76	-3.44	-64.20	-13.00	-51.20	peak	
2		145.5593	-65.99	-0.84	-66.83	-13.00	-53.83	peak	
3		215.9813	-69.34	-1.60	-70.94	-13.00	-57.94	peak	
4		300.8240	-72.03	-1.14	-73.17	-13.00	-60.17	peak	
5		437.6263	-71.35	0.56	-70.79	-13.00	-57.79	peak	
6		531.1667	-72.31	3.89	-68.42	-13.00	-55.42	peak	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	LTE Band 26	Test Date	2023/12/26
Test Channel	CH26865	Polarization	Horizontal
Temp	21°C	Hum.	59%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBm	dB	dBm	dBm	dB		
1	*	94.9900	-54.41	-5.93	-60.34	-13.00	-47.34	peak	
2		145.5593	-59.21	-3.46	-62.67	-13.00	-49.67	peak	
3		207.4130	-61.53	-7.30	-68.83	-13.00	-55.83	peak	
4		282.0060	-69.70	-4.63	-74.33	-13.00	-61.33	peak	
5		459.4513	-70.57	0.22	-70.35	-13.00	-57.35	peak	
6		586.2303	-72.46	2.04	-70.42	-13.00	-57.42	peak	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	LTE Band 26	Test Date	2023/12/25
Test Channel	CH26865	Polarization	Vertical
Temp	21°C	Hum.	58%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBm	dB	dBm	dBm	dB		
1	*	2512.800	-43.08	7.42	-35.66	-13.00	-22.66	peak	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	LTE Band 26	Test Date	2023/12/25
Test Channel	CH26865	Polarization	Horizontal
Temp	21°C	Hum.	58%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBm	dB	dBm	dBm	dB		
1	*	2476.267	-53.46	7.37	-46.09	-13.00	-33.09	peak	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	LTE Band 26	Test Date	2023/12/25
Test Channel	CH26915	Polarization	Vertical
Temp	21°C	Hum.	58%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBm	dB	dBm	dBm	dB		
1	*	2491.467	-49.96	7.39	-42.57	-13.00	-29.57	peak	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	LTE Band 26	Test Date	2023/12/25
Test Channel	CH26915	Polarization	Horizontal
Temp	21°C	Hum.	58%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBm	dB	dBm	dBm	dB		
1	*	2528.000	-59.80	7.43	-52.37	-13.00	-39.37	peak	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	LTE Band 26	Test Date	2023/12/25
Test Channel	CH26965	Polarization	Vertical
Temp	21°C	Hum.	58%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBm	dB	dBm	dBm	dB		
1	*	2506.400	-52.55	7.38	-45.17	-13.00	-32.17	peak	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	LTE Band 26	Test Date	2023/12/25
Test Channel	CH26965	Polarization	Horizontal
Temp	21°C	Hum.	58%



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1	*	2506.400	-53.56	7.24	-46.32	-13.00	-33.32	peak	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

End of Test Report