



RF Exposure Evaluation Declaration

FCC ID: XMR202111EG915ULA

Application: Quectel Wireless Solutions Company Limited

Application Type: Certification

Product: LTE Module


Model No.: EG915U-LA

Brand Name: Quectel

Test Procedure(s): KDB 447498 D01v06

Test Date: October 17 ~ November 02, 2021

Reviewed By: 
Sunny Sun

Approved By: 
Robin Wu



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
2110RSU013-U4	Rev. 01	Initial Report	11-17-2021	Valid

1. GENERAL INFORMATION

1.1. Applicant

Quectel Wireless Solutions Company Limited

Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District,
Shanghai, China 200233

1.2. Manufacturer

Quectel Wireless Solutions Company Limited

Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District,
Shanghai, China 200233

1.3. Testing Facility

☒	Test Site - MRT Suzhou Laboratory
	Laboratory Location (Suzhou - Wuzhong)
	D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China
	Laboratory Location (Suzhou - SIP)
	4b Building, Liando U Valley, No.200 Xingpu Rd., Shengpu Town, Suzhou Industrial Park, China
	Laboratory Accreditations
A2LA: 3628.01	
CNAS: L10551	
FCC: CN1166	
ISED: CN0001	
VCCI: ☐ R-20025 ☐ G-20034 ☐ C-20020 ☐ T-20020	
☐ R-20141 ☐ G-20134 ☐ C-20103 ☐ T-20104	
☐	Test Site - MRT Shenzhen Laboratory
	Laboratory Location (Shenzhen)
	1G, Building A, Junxiangda Building, Zhongshanyuan Road West, Nanshan District, Shenzhen, China
	Laboratory Accreditations
	A2LA: 3628.02
	CNAS: L10551
FCC: CN1284	
ISED: CN0105	
☐	Test Site - MRT Taiwan Laboratory
	Laboratory Location (Taiwan)
	No. 38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)
	Laboratory Accreditations
	TAF: L3261-190725
FCC: 291082, TW3261	
ISED: TW3261	

1.4. Product Information

Product Name	LTE Module
Model No.	EG915U-LA
Brand Name	Quectel
Bluetooth Specification	V4.2 single mode for BR/EDR
Wi-Fi Specification	Scan function only
GSM Band	GSM 850, PCS 1900
E-UTRA Band	Band 2, 4, 5, 7, 66
Operating Temperature	-35 ~ 75 °C
Power Type	3.3 ~ 4.3Vdc, typical 3.8Vdc

Remark:

1. The information of EUT was provided by the manufacturer, and the accuracy of the information shall be the responsibility of the manufacturer.

2. RF Exposure Evaluation

2.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	f/1500	6
1500-100,000	--	--	1	30

f= Frequency in MHz

Calculation Formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2.2. Test Result of RF Exposure Evaluation

Product	LTE Module
Test Item	RF Exposure Evaluation

Test Mode	Frequency Band (MHz)	Maximum Conducted Power (dBm)	Antenna Gain (dBi)	ERP (EIRP) (dBm)	Power Density at 20cm (mW/cm ²)	Limit (mW/cm ²)
GSM850	824 ~ 849	27.00	6.00	33.00	0.3969	0.5493
PCS1900	1850 ~ 1910	23.00	10.00	33.00	0.3969	1.0000
LTE B2	1850 ~ 1910	25.70	6.30	32.00	0.3153	1.0000
LTE B4	1710 ~ 1755	25.70	6.30	32.00	0.3153	1.0000
LTE B5	824 ~ 849	25.70	6.30	32.00	0.3153	0.5493
LTE B7	2500 ~ 2570	25.70	6.30	32.00	0.3153	0.4660
LTE B66	1710 ~ 1780	25.70	6.30	32.00	0.3153	1.0000
Bluetooth	2402 ~ 2480	7.41	5.38	12.79	0.038	1.0000

WWAN Power Density / Limit	Bluetooth Power Density / Limit	Σ (Power Density / Limit)
0.3969	0.038	0.43

Note:

1. For colocation analysis, GSM900 is chosen for summation due to the highest (power density / limit) among all WWAN wireless modes.
2. Σ (Power Density / Limit): This is a summation of [(power density for each transmitter / antenna included in the simultaneous transmission) / (corresponding MPE limit)], for WWAN + Bluetooth.

The End

Appendix A – EUT Photograph

Refer to “2110RSU013-UE” file.