

FCC Radio Test Report

FCC ID: XMR202112UC200AGL

This report concerns: Original Grant

Project No. : 2110H019
Equipment : UMTS/HSPA+ Module
Brand Name : Quectel
Test Model : UC200A-GL
Series Model : N/A
Applicant : Quectel Wireless Solutions Co., Ltd
Address : Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, China 200233.
Manufacturer : Quectel Wireless Solutions Co., Ltd
Address : Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, China 200233.
Date of Receipt : Nov. 15, 2021
Date of Test : Nov. 15, 2021 ~ Nov. 22, 2021
Issued Date : Nov. 25, 2021
Report Version : R00
Test Sample : Engineering Sample No.: SH20211115157 for EUT, SH20211115156-3 for adapter.
Standard(s) : 47 CFR FCC Part 24 Subpart E
ANSI/TIA/EIA-603-E-2016
FCC KDB 971168 D01 Power Meas License Digital Systems v03r01

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

Maker Qi

Prepared by : Maker Qi

Ryan. Wang

Approved by : Ryan Wang



TESTING CERT #5123.03

Add: No. 29, Jintang Road, Tangzhen Industry Park, Pudong New Area, Shanghai 201210, China

TEL: +86-021-61765666

Web: www.newbtl.com

Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

BTL's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

The report must not be used by the client to claim product certification, approval, or endorsement by NIST, A2LA, or any agency of the U.S. Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and ourselves, the test report shall not be reproduced, except in full, without our written approval.

BTL's laboratory quality assurance procedures are in compliance with the **ISO/IEC 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

BTL is not responsible for the sampling stage, so the results only apply to the sample as received.

The information, data and test plan are provided by manufacturer which may affect the validity of results, so it is manufacturer's responsibility to ensure that the apparatus meets the essential requirements of applied standards and in all the possible configurations as representative of its intended use.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Please note that the measurement uncertainty is provided for informational purpose only and is not use in determining the Pass/Fail results.

Table of Contents	Page
REPORT ISSUED HISTORY	5
1 . SUMMARY OF TEST RESULTS	6
1.1 TEST FACILITY	7
1.2 MEASUREMENT UNCERTAINTY	7
1.3 TEST ENVIRONMENT CONDITIONS	7
2 . GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF EUT	8
2.2 DESCRIPTION OF TEST MODES AND TEST CONDITION	9
2.3 BLOCKDIAGRAMSHOWINGTHECONFIGURATIONOFSYSTEMTESTED	10
3.4 DESCRIPTION OF SUPPORT UNITS	10
3 . TEST RESULT	11
3.1 OUTPUT POWER MEASUREMENT	11
3.1.1 LIMIT	11
3.1.2 TEST PROCEDURE	11
3.1.3 TEST SETUP LAYOUT	11
3.1.4 TEST DEVIATION	11
3.1.5 TEST RESULTS	11
3.2 OCCUPIED BANDWIDTH MEASUREMENT	12
3.2.1 TEST PROCEDURE	12
3.2.2 TEST SETUP LAYOUT	12
3.2.3 TEST DEVIATION	12
3.2.4 TEST RESULTS	12
3.3 CONDUCTED EMISSIONS MEASUREMENT	13
3.3.1 LIMIT	13
3.3.2 TEST PROCEDURES	13
3.3.3 TEST SETUP LAYOUT	13
3.3.4 TEST DEVIATION	13
3.3.5 TEST RESULTS	13
3.4 RADIATED EMISSIONS MEASUREMENT	14
3.4.1 LIMIT	14
3.4.2 TEST PROCEDURES	14
3.4.3 TEST SETUP LAYOUT	15
3.4.4 TEST DEVIATION	16
3.4.5 TEST RESULTS (9KHZ TO 30MHZ)	16
3.4.6 TEST RESULTS (30MHZ TO 1000MHZ)	16
3.4.7 TEST RESULTS (ABOVE 1000MHZ)	16
3.5 BAND EDGE MEASUREMENT	17
3.5.1 LIMIT	17

Table of Contents	Page
3.5.2 TEST PROCEDURES	17
3.5.3 TEST SETUP LAYOUT	17
3.5.4 TEST DEVIATION	17
3.5.5 TEST RESULTS	17
3.6 PEAK TO AVERAGE RATIO MEASUREMENT	18
3.6.1 LIMIT	18
3.6.2 TEST PROCEDURES	18
3.6.3 TEST SETUP LAYOUT	18
3.6.4 TEST DEVIATION	18
3.6.5 TEST RESULTS	18
3.7 FREQUENCY STABILITY MEASUREMENT	19
3.7.1 LIMIT	19
3.7.2 TEST PROCEDURES	19
3.7.3 TEST SETUP LAYOUT	19
3.7.4 TEST DEVIATION	19
3.7.5 TEST RESULTS	19
4. LIST OF MEASUREMENT EQUIPMENTS	20
5. EUT TEST PHOTO	22
APPENDIX A - OUTPUT POWER	24
APPENDIX B - OCCUPIED BANDWIDTH	27
APPENDIX C - CONDUCTED EMISSIONS	31
APPENDIX D - RADIATED EMISSION (9KHZ TO 30MHZ)	34
APPENDIX E - RADIATED EMISSION (30MHZ TO 1GHZ)	35
APPENDIX F - RADIATED EMISSION (ABOVE 1GHZ)	40
APPENDIX G - BAND EDGE	45
APPENDIX H - PEAK TO AVERAGE RATIO	48
APPENDIX I - FREQUENCY STABILITY	51

REPORT ISSUED HISTORY

Report Version	Description	Issued Date
R00	Original Issue.	Nov. 25, 2021

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

FCC Part 24 Subpart E& Part 2			
Standard(s) Section	Test Item	Judgment	Remark
2.1046 & 24.232(c)	Equivalent Isotropic Radiated Power	PASS	-----
2.1049	Occupied Bandwidth	PASS	-----
2.1051 & 24.238(a)	Conducted Spurious Emissions	PASS	-----
2.1053 & 24.238(a)	Radiated Spurious Emissions	PASS	-----
24.238(a)	Band Edge Measurements	PASS	-----
24.232(d)	Peak To Average Ratio	PASS	-----
2.1055 & 24.235	Frequency Stability	PASS	-----

Note:

For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested".

1.1 TEST FACILITY

The test facilities used to collect the test data in this report is at the location of No. 29, Jintang Road, Tangzhen Industry Park, Pudong New Area, Shanghai 201210, China.

BTL's Test Firm Registration Number for FCC: 476765

BTL's Designation Number for FCC: CN1241

1.2 MEASUREMENT UNCERTAINTY

The measurement uncertainty figures shall be calculated according the methods described in the ETSI TR 100 028 and shall correspond to an expansion factor (coverage factor) $k=1.96$ or $k=2$ (which provide confidence levels of respectively 90% and 95.45% in the case where the distributions characterizing the actual measurement uncertainties are normal (Gaussian)).

Measurement Uncertainty for a Level of Confidence of 95 %, $U=2 \times U_c(y)$.

The BTL measurement uncertainty as below table:

A. Radiated Measurement :

Test Site	Method	Measurement Frequency Range	Ant. H / V	U,(dB)
SH-CB02	CISPR	9KHz ~ 30MHz	-	2.16
		30MHz ~ 200MHz	V	4.04
		30MHz ~ 200MHz	H	2.90
		200MHz ~ 1,000MHz	V	3.76
		200MHz ~ 1,000MHz	H	3.82

Test Site	Method	Measurement Frequency Range	U,(dB)
SH-CB02	CISPR	1GHz ~ 6GHz	4.40
		6GHz ~ 18GHz	4.86

Note: Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

1.3 TEST ENVIRONMENT CONDITIONS

Test Item	Temperature	Humidity	Test Voltage	Tested By
EIRP	22°C	51%	DC 3.8V	Danny Dang
Occupied Bandwidth	22°C	51%	DC 3.8V	Danny Dang
Conducted Spurious Emissions	22°C	51%	DC 3.8V	Danny Dang
Radiated Spurious Emissions	26°C	61%	DC 3.8V	Danny Dang
Band Edge	22°C	51%	DC 3.8V	Danny Dang
Peak to Average Ratio	22°C	51%	DC 3.8V	Danny Dang
Frequency Stability	Normal and Extreme			Danny Dang

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	UMTS/HSPA+ Module			
Brand Name	Quectel			
Test Model	UC200A-GL			
Series Model	N/A			
Model Difference(s)	N/A			
Software Version	UC200AGLAAR01A02M16_PAX			
Hardware Version	R1.0			
Power Source	DC Voltage supplied from AC/DC adapter(support unit)			
Power Rating	Supply voltage:3.4-4.5V, Typical supply voltage:3.8V			
Antenna Type	Dipole			
Antenna Gain	PCS 1900	1.59 dBi		
	WCDMA II			
Modulation Type	GSM	GMSK		
	GPRS	GMSK		
	EDGE	GMSK, 8PSK		
	WCDMA	UL: QPSK DL: QPSK, 16QAM		
Operation Frequency	EDGE/GSM/GPRS	1850.2MHz ~ 1909.8MHz		
	WCDMA Band II	1852.4MHz ~ 1907.6MHz		
Max. EIRP Power	GSM	GMSK	31.96	dBm
	GPRS	GMSK	31.92	dBm
	EDGE	8PSK	28.25	dBm
	WCDMA	QPSK	24.78	dBm

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. WCDMA (UL:QPSK; DL: QPSK) mode was found to be the worst case and recorded.


2.2 DESCRIPTION OF TEST MODES AND TEST CONDITION

Following channel(s) was (were) selected for the final test as listed below:

GSM MODE			
Test Item	Available Channel	Tested Channel	Mode
EIRP	512 to 810	512, 661, 810	GSM, GPRS, EDGE
Output Power	512 to 810	512, 661, 810	GSM, GPRS, EDGE
Occupied Bandwidth	512 to 810	512, 661, 810	GSM,EDGE
Conducuted Emission	512 to 810	661	GSM,EDGE
Radiated Emission	512 to 810	661	GSM
Band Edge	512 to 810	512, 810	GSM,EDGE
Peak to Average Ratio	512 to 810	512, 661, 810	GSM,EDGE
Frequency Stability	512 to 810	661	GSM

WCDMA MODE			
Test Item	Available Channel	Tested Channel	Mode
EIRP	9262 to 9538	9262, 9400, 9538	WCDMA, HSDPA,HSUPA
Output Power	9262 to 9538	9262, 9400, 9538	WCDMA, HSDPA,HSUPA
Conducted Emission	9262 to 9538	9400	WCDMA
Radiated Emission	9262 to 9538	9400	WCDMA
Band Edge	9262 to 9538	9262, 9538	WCDMA
Peak to Average Ratio	9262 to 9538	9262, 9400, 9538	WCDMA
Frequency Stability	9262 to 9538	9400	WCDMA

2.3 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.
A	CMW500	R&S	N/A	129246

Item	Cable Type	Shielded Type	Ferrite Core	Length
1	DC	NO	NO	1m

3. TEST RESULT

3.1 OUTPUT POWER MEASUREMENT

3.1.1 LIMIT

Mobile / Portable station are limited to 2 watts e.i.r.p.

3.1.2 TEST PROCEDURE

EIRP:


$EIRP = \text{Output Power} + \text{Antenan gain}$

Output Power:

The EUT was set up for the maximum power with GSM, GPRS, EDGE and WCDMA link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

3.1.3 TEST SETUP LAYOUT

Output Power Measurement



3.1.4 TEST DEVIATION

No deviation

3.1.5 TEST RESULTS


Please refer to the Appendix A.

3.2 OCCUPIED BANDWIDTH MEASUREMENT

3.2.1 TEST PROCEDURE

The EUT makes a call to the communication simulator. All measurements were done at low, middle and high operational frequency range. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth and 26dB bandwidth.

3.2.2 TEST SETUP LAYOUT



3.2.3 TEST DEVIATION

No deviation

3.2.4 TEST RESULTS

Please refer to the Appendix B.

3.3 CONDUCTED EMISSIONS MEASUREMENT


3.3.1 LIMIT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm.

3.3.2 TEST PROCEDURES

1. The testing follows FCC KDB 971168 v03r01 Section 6.0.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured. Set RBW $\geq 1\%$ EBW in the 1MHz band immediately outside and adjacent to the band edge.
4. Set spectrum analyzer with RMS detector.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.3.3 TEST SETUP LAYOUT



3.3.4 TEST DEVIATION

No deviation

3.3.5 TEST RESULTS

Please refer to the Appendix C.

3.4 RADIATED EMISSIONS MEASUREMENT

3.4.1 LIMIT


The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm.

3.4.2 TEST PROCEDURES


1. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
2. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value " of step a. Record the power level of S.G
3. $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}.$
4. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, $E.R.P \text{ power} = E.I.P.R \text{ power} - 2.15\text{dBi}.$
5. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.


3.4.3 TEST SETUP LAYOUT

Below 30MHz



30MHz to 1GHz





3.4.4 TEST DEVIATION

No deviation

3.4.5 TEST RESULTS (9KHZ TO 30MHZ)

Please refer to the Appendix D.

3.4.6 TEST RESULTS (30MHZ TO 1000MHZ)

Please refer to the Appendix E.

3.4.7 TEST RESULTS (ABOVE 1000MHZ)

Please refer to the Appendix F.

3.5 BAND EDGE MEASUREMENT


3.5.1 LIMIT

A Power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

3.5.2 TEST PROCEDURES

1. All measurements were done at low and high operational frequency range.
2. The center frequency of spectrum is the band edge frequency and span is 1.5MHz. RB of the spectrum is 3kHz and VB of the spectrum is 10kHz (GSM/EDGE).
3. The center frequency of spectrum is the band edge frequency and span is 10MHz. RB of the spectrum is 100kHz and VB of the spectrum is 300kHz (WCDMA).
4. Record the max trace plot into the test report.

3.5.3 TEST SETUP LAYOUT



3.5.4 TEST DEVIATION

No deviation

3.5.5 TEST RESULTS

Please refer to the Appendix G.

3.6 PEAK TO AVERAGE RATIO MEASUREMENT


3.6.1 LIMIT

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.6.2 TEST PROCEDURES

1. Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1%.

3.6.3 TEST SETUP LAYOUT



3.6.4 TEST DEVIATION

No deviation

3.6.5 TEST RESULTS

Please refer to the Appendix H.

3.7 FREQUENCY STABILITY MEASUREMENT


3.7.1 LIMIT

± 1.5 ppm is for base and fixed station. ± 2.5 ppm is for mobile station.

3.7.2 TEST PROCEDURES

1. Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
2. EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
3. The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the $\pm 0.5^{\circ}\text{C}$ during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.
4. The frequency error was recorded frequency error from the communication simulator.

3.7.3 TEST SETUP LAYOUT



3.7.4 TEST DEVIATION

No deviation

3.7.5 TEST RESULTS

Please refer to the Appendix I.

4. LIST OF MEASUREMENT EQUIPMENTS

Radiated Emission Measurement(9K-30M)					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Loop Antenna	EMCI	EMCI LPA600	275	May. 20, 2022
2	MXE EMI Receiver	Keysight	N9038A	MY56400088	Mar. 21, 2022
3	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
4	Wideband Radio Communication Test	R&S	CMW500	129246	Aug. 23, 2022

Radiated Emission Measurement(30M-1G)					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	TRILOG Broadband Antenna	Schwarzbeck	VULB 9160	9160-3233	Mar. 26, 2022
2	Pre-Amplifier	emci	EMC9135	980401	Mar. 20, 2022
3	MXE EMI Receiver	Keysight	N9038A	MY56400088	Mar. 21, 2022
4	Test Cable	emci	EMC104-SM-SM-7000	181020	Apr. 11, 2022
5	Test Cable	emci	EMC104-SM-SM-2500	170618	Apr. 11, 2022
6	Test Cable	emci	EMC104-SM-SM-800	170647	Apr. 11, 2022
7	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
8	Wideband Radio Communication Test	R&S	CMW500	129246	Aug. 23, 2022

Radiated Emission Measurement(1G-18G)					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA 9120D	9120D-1817	Mar. 26, 2022
2	Pre-Amplifier	emci	EMC051845SE	980725	Aug. 23, 2022
3	EXA Spectrum Analyzer	Keysight	N9010A	MY56480579	Mar. 21, 2022
4	Test Cable	emci	EMC104-SM-SM-7000	181020	Apr. 11, 2022
5	Test Cable	emci	EMC104-SM-SM-2500	170618	Apr. 11, 2022
6	Test Cable	emci	EMC104-SM-SM-800	170647	Apr. 11, 2022
7	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
8	Wideband Radio Communication Test	R&S	CMW500	129246	Aug. 23, 2022

For GSM & WCDMA

Conducted Emission & Band Edge & Occupied Bandwidth Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Wideband Radio Communication Test	R&S	CMW500	129246	Aug. 23, 2022
2	EXA Spectrum Analyzer	Keysight	N9010A	MY56480579	Mar. 21, 2022
3	Power Divider	JUK	PD-2SF-2060	N/A	N/A

Frequency Stability Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Wideband Radio Communication Test	R&S	CMW500	129246	Aug. 23, 2022
2	EXA Spectrum Analyzer	Keysight	N9010A	MY56480579	Mar. 21, 2022
3	Power Divider	JUK	PD-2SF-2060	N/A	N/A
4	Temperature And Humidity Box	Blue pand	BPHS-120B	170616454	Aug. 23, 2022



Remark: "N/A" denotes no model name, serial no. or calibration specified.

All calibration period of equipment list is one year.

5. EUT TEST PHOTO



Radiated Emissions Test Photos

30 MHz to 1000 MHz



Radiated Emissions Test Photos

Above 1 GHz



APPENDIX A - OUTPUT POWER

Output Power (dBm):

PCS1900		Burst Output Power		
		512CH	661CH	810CH
		1850.2MHz	1880MHz	1909.8MHz
GSM(GMSK)		30.11	30.37	30.35
GPRS/EDGE (GMSK)	1 Tx Slot	30.06	30.33	30.31
	2 Tx Slot	30.03	30.24	30.21
	3 Tx Slot	28.41	28.69	28.78
	4 Tx Slot	26.4	26.71	26.80
EDGE (8PSK)	1 Tx Slot	26.37	26.66	26.56
	2 Tx Slot	26.18	26.52	26.48
	3 Tx Slot	24.37	24.79	24.73
	4 Tx Slot	22.48	22.84	22.64

Modulation	Band	WCDMA Band II		
	Tx Channel	9262CH	9400CH	9538CH
	Frequency	1852.4MHz	1880MHz	1907.6MHz
QPSK	RMC 12.2K	22.89	23.10	22.90
	RMC 64K	22.88	23.06	22.78
	RMC 144K	22.50	23.17	22.77
	RMC 384K	22.40	23.19	22.56
	HSDPA Subtest-1	22.31	22.54	22.56
	HSDPA Subtest-2	22.41	22.36	22.49
	HSDPA Subtest-3	22.10	22.20	22.50
	HSDPA Subtest-4	21.93	22.14	22.44
	HSUPA Subtest-1	22.66	22.70	22.52
	HSUPA Subtest-2	22.50	22.56	22.49
	HSUPA Subtest-3	22.37	22.55	22.40
	HSUPA Subtest-4	22.20	22.48	22.32
	HSUPA Subtest-5	22.19	22.30	22.19

EIRP Power (dBm):

PCS1900		EIRP Power		
		512CH	661CH	810CH
		1850.2MHz	1880MHz	1909.8MHz
GSM(GMSK)		31.70	31.96	31.94
GPRS/EDGE (GMSK)	1 Tx Slot	31.65	31.92	31.90
	2 Tx Slot	31.62	31.83	31.80
	3 Tx Slot	30.00	30.28	30.37
	4 Tx Slot	27.99	28.30	28.39
EDGE (8PSK)	1 Tx Slot	27.96	28.25	28.15
	2 Tx Slot	27.77	28.11	28.07
	3 Tx Slot	25.96	26.38	26.32
	4 Tx Slot	24.07	24.43	24.23


Modulation	Band	WCDMA Band II		
	Tx Channel	9262CH	9400CH	9538CH
	Frequency	1852.4MHz	1880MHz	1907.6MHz
QPSK	RMC 12.2K	24.48	24.69	24.49
	RMC 64K	24.47	24.65	24.37
	RMC 144K	24.09	24.76	24.36
	RMC 384K	23.99	24.78	24.15
	HSDPA Subtest-1	23.90	24.13	24.15
	HSDPA Subtest-2	24.00	23.95	24.08
	HSDPA Subtest-3	23.69	23.79	24.09
	HSDPA Subtest-4	23.52	23.73	24.03
	HSUPA Subtest-1	24.25	24.29	24.11
	HSUPA Subtest-2	24.09	24.15	24.08
	HSUPA Subtest-3	23.96	24.14	23.99
	HSUPA Subtest-4	23.79	24.07	23.91
	HSUPA Subtest-5	23.78	23.89	23.78

APPENDIX B - OCCUPIED BANDWIDTH

PCS1900					
GSM			EDGE		
GMSK			8PSK		
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
512	1850.2	0.2413	512	1850.2	0.2404
661	1880	0.2457	661	1880	0.2420
810	1909.8	0.2437	810	1909.8	0.2426
Channel	Frequency (MHz)	26dB Bandwidth (MHz)	Channel	Frequency (MHz)	26dB Bandwidth (MHz)
512	1850.2	0.2978	512	1850.2	0.2978
661	1880	0.3099	661	1880	0.3103
810	1909.8	0.3059	810	1909.8	0.3094

Spectrum Plot

GSM -512



GSM -661




GSM -810



EDGE-512



EDGE-661




EDGE-810



WCDMA Band II					
QPSK					
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	Channel	Frequency (MHz)	26dB Bandwidth (MHz)
9262	1852.4	4.1559	9262	1852.4	4.7210
9400	1880	4.1644	9400	1880	4.7300
9538	1907.6	4.1510	9538	1907.6	4.7210



APPENDIX C - CONDUCTED EMISSIONS



WCDMA Band II			
Channel	Frequency(MHz)	Channel	Frequency(MHz)
9400	1880	9400	1880
Channel	Frequency(MHz)	-	-
9400	1880	-	-
		-	

APPENDIX D - RADIATED EMISSION (9KHZ TO 30MHZ)

Note: Below 30MHz, The measured value have enough margin over 20dB than the limit, therefore they are not reported.

APPENDIX E - RADIATED EMISSION (30MHZ TO 1GHZ)

Test Mode: PCS1900_TX Mode


Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		
		MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1	*	59.1000	-60.04	-10.07	-70.11	-13.00	-57.11	RMS	
2		153.1900	-71.92	0.24	-71.68	-13.00	-58.68	RMS	
3		425.2750	-77.64	0.78	-76.86	-13.00	-63.86	RMS	
4		690.5700	-79.88	4.10	-75.78	-13.00	-62.78	RMS	
5		757.9850	-80.69	5.73	-74.96	-13.00	-61.96	RMS	
6		901.0600	-79.33	6.40	-72.93	-13.00	-59.93	RMS	

Test Mode: PCS1900_TX Mode


Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		
		MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1		58.6150	-66.26	-6.98	-73.24	-13.00	-60.24	RMS	
2		94.5050	-68.00	-6.72	-74.72	-13.00	-61.72	RMS	
3	*	149.7950	-63.87	-2.83	-66.70	-13.00	-53.70	RMS	
4		428.1850	-73.43	0.66	-72.77	-13.00	-59.77	RMS	
5		464.0750	-74.76	1.08	-73.68	-13.00	-60.68	RMS	
6		628.9750	-79.18	4.09	-75.09	-13.00	-62.09	RMS	

Test Mode: WCDMA Band II_TX Mode


Vertical



No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Margin dB	Detector	Comment
1	*	60.0700	-61.78	-10.12	-71.90	-13.00	-58.90	RMS	
2		101.7800	-75.48	2.53	-72.95	-13.00	-59.95	RMS	
3		149.3100	-73.74	0.53	-73.21	-13.00	-60.21	RMS	
4		238.0650	-76.78	-3.35	-80.13	-13.00	-67.13	RMS	
5		468.4400	-79.43	1.09	-78.34	-13.00	-65.34	RMS	
6		748.7700	-81.04	5.72	-75.32	-13.00	-62.32	RMS	

Test Mode: WCDMA Band II_TX Mode

Horizontal




No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Margin dB	Detector	Comment
1	*	151.7350	-63.44	-2.86	-66.30	-13.00	-53.30	RMS	
2		413.1500	-73.30	0.52	-72.78	-13.00	-59.78	RMS	
3		482.0200	-76.16	1.34	-74.82	-13.00	-61.82	RMS	
4		624.1250	-78.80	4.10	-74.70	-13.00	-61.70	RMS	
5		691.5400	-77.16	4.12	-73.04	-13.00	-60.04	RMS	
6		831.7050	-79.85	6.39	-73.46	-13.00	-60.46	RMS	

APPENDIX F - RADIATED EMISSION (ABOVE 1GHZ)

Test Mode: PCS1900_TX Mode


Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		
		MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1	*	3759.950	-37.39	-4.92	-42.31	-13.00	-29.31	RMS	
2		5640.150	-47.47	-2.12	-49.59	-13.00	-36.59	RMS	

Test Mode: PCS1900_TX Mode


Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		
		MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1	*	3759.950	-40.18	-4.72	-44.90	-13.00	-31.90	RMS	
2		5640.150	-53.93	-2.04	-55.97	-13.00	-42.97	RMS	

Test Mode: WCDMA Band II_TX Mode


Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
		MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1	*	3758.250	-51.40	-4.93	-56.33	-13.00	-43.33	RMS	
2		5642.700	-57.75	-2.11	-59.86	-13.00	-46.86	RMS	


Test Mode: WCDMA Band II_TX Mode


Horizontal



No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
	MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1 *	3758.250	-55.97	-4.73	-60.70	-13.00	-47.70	RMS	

APPENDIX G - BAND EDGE






APPENDIX H - PEAK TO AVERAGE RATIO

PCS1900 Spectrum Plot



WCDMA Band II Spectrum Plot



APPENDIX I - FREQUENCY STABILITY

Test Mode:	PCS1900_CH661
------------	---------------

Temperature vs. Frequency Stability

Temperature(°C)	Frequency Error (Hz)	Frequency Error (ppm)	Limit(ppm)
-20	4.54	0.002414894	± 2.5
-10	5.49	0.002920213	
0	-2.75	-0.001462766	
10	5.06	0.002691489	
20	3.28	0.001744681	
30	5.43	0.002888298	
40	-3.15	-0.001675532	
50	4.57	0.002430851	
Max. Deviation (ppm)	5.43	0.002888298	

Voltage vs. Frequency Stability

Voltage(Volts)	Frequency Error (Hz)	Frequency Error (ppm)	Limit(ppm)
4.5	-5.70	-0.003031915	± 2.5
3.8	-6.14	-0.003265957	
3.4	-6.70	-0.003563830	
Max. Deviation (ppm)	6.70	-0.003031915	

Test Mode:	WCDMA Band II_CH9800
------------	----------------------

Temperature vs. Frequency Stability

Temperature(°C)	Frequency Error (Hz)	Frequency Error (ppm)	Limit(ppm)
-20	3.57	0.001898936	± 2.5
-10	4.29	0.002281915	
0	-2.73	0.001452128	
10	4.66	0.002478723	
20	-3.61	0.001920213	
30	-2.87	0.001526596	
40	3.54	0.001882979	
50	-4.06	0.002159574	
Max. Deviation (ppm)	4.66	0.002478723	

Voltage vs. Frequency Stability

Voltage(Volts)	Frequency Error (Hz)	Frequency Error (ppm)	Limit(ppm)
4.5	5.86	0.003117021	± 2.5
3.8	4.75	0.002526596	
3.4	5.49	0.002920213	
Max. Deviation (ppm)	5.86	0.003117021	

End of Test Report