TEST REPORT

Applicant:	Quectel Wireless Solutions Co., Ltd
Address:	Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, China 200233
Equipment Type:	Wi-Fi & BT Module
Model Name:	FC80A
Brand Name:	Quectel
FCC ID:	XMR202203FC80A
ISED Number:	10224A-202203FC80A
Test Standard:	47 CFR Part 15 Subpart C RSS-Gen Issue 5 RSS-247 Issue 2 (refer section 3.1)
Test Date:	Mar. 02, 2022 – May 25, 2022
Date of Issue:	Jun. 13, 2022

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

Tested by: Julie Zhu **Checked by:** Ye Hongji **Approved by:** Liao Jianming (Technical Director)

Revision History

Version	Issue Date	Revisions
Rev. 01	Jun. 13, 2022	Initial Issue

TABLE OF CONTENTS

1 GENERAL INFORMATION 4
1.1 Identification of the Testing Laboratory 4
1.2 Identification of the Responsible Testing Location 4
2 PRODUCT INFORMATION 5
2.1 Applicant Information 5
2.2 Manufacturer Information 5
2.3 Factory Information 5
2.4 General Description for Equipment under Test (EUT) 5
2.5 Technical Information 6
2.6 Additional Instructions 8
3 SUMMARY OF TEST RESULTS 9
3.1 Test Standards 9
3.2 Test Verdict 10
4 GENERAL TEST CONFIGURATIONS 11
4.1 Test Environments 11
4.2 Test Equipment List 11
4.3 Test Software List 11
4.4 Measurement Uncertainty 12
4.5 Description of Test Setup 12
4.6 Measurement Results Explanation Example 15
5 TEST ITEMS 16
5.1 Antenna Requirements 16
5.2 Frequency Hopping Systems 17
5.3 Number of Hopping Frequencies 19

5.4 Peak Output Power and E.I.R.P 20
5.5 Occupied Bandwidth 21
5.6 Carrier Frequency Separation 22
5.7 Time of Occupancy (Dwell time) 23
5.8 Conducted Spurious Emission & Authorized-band band-edge 25
5.9 Conducted Emission 26
5.10 Radiated Spurious Emission 27
5.11 Band Edge (Restricted-band band-edge) 29
ANNEX A TEST RESULT 30
A.1 Number of Hopping Frequency 30
A.2 Peak Output Power and E.I.R.P 31
A.3 20 dB and 99% bandwidth 34
A.4 Hopping Frequency Separation 39
A.5 Average Time of Occupancy 40
A.6 Conducted Spurious Emissions & Authorized-band band-edge 43
A.7 Conducted Emissions 50
A.8 Radiated Spurious Emission 52
A.9 Band Edge (Restricted-band band-edge) 66
ANNEX B TEST SETUP PHOTOS 70
ANNEX C EUT EXTERNAL PHOTOS 70
ANNEX D EUT INTERNAL PHOTOS 70

1 GENERAL INFORMATION

1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe West Road, Nanshan District, ShenZhen, GuangDong Province, China
Phone Number	+86 755 6685 0100

1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe West Road, Nanshan District, ShenZhen, GuangDong Province, China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196. The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 11524A.
Description	All measurement facilities used to collect the measurement data are located at Block B, 1/F, Baisha Science and Technology Park, Shahe West Road, Nanshan District, ShenZhen, GuangDong Province, China

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Quectel Wireless Solutions Co., Ltd
Address	Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, China 200233

2.2 Manufacturer Information

Manufacturer	Quectel Wireless Solutions Co., Ltd
Address	Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, China 200233

2.3 Factory Information

Factory	N/A
Address	N/A

2.4 General Description for Equipment under Test (EUT)

EUT Name	Wi-Fi & BT Module
Model Name Under Test	FC80A
Series Model Name	N/A
Description of Model name differentiation	N/A
Serial Number	FC80A20220409
Hardware Version	R1.0
Software Version	N/A
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.5 Technical Information

Network and Wireless connectivity	Bluetooth (BR+EDR+BLE) 2.4G WIFI 802.11b, 802.11g, 802.11n(HT20) 5G WIFI 802.11a, 802.11n(20/40), 802.11ac(VHT20/40/80) U-NII-1/2A/2C/3

The requirement for the following technical information of the EUT was tested in this report:

Modulation Technology	FHSS
Modulation Type	GFSK, π/4-DQPSK, 8-DPSK
Product Type	☒ Mobile ☐ Portable ☐ Fix Location
Transfer Rate	DH5: 1 Mbps 2DH5: 2 Mbps 3DH5: 3 Mbps
Frequency Range	The frequency range used is 2400 MHz to 2483.5 MHz.
Number of Channel	79 (at intervals of 1 MHz)
Tested Channel	0 (2402 MHz), 39 (2441 MHz), 78 (2480 MHz)
Antenna Type	Dipole Antenna (Model: YE0038AA)
Antenna Gain	1.0 dBi (In test items related to antenna gain, the final results reflect this figure. This value is provided by the applicant.)
Antenna Impedance	50Ω
Antenna System (MIMO Smart Antenna)	N/A

All channel was listed on the following table:

Channel number	Freq. (MHz)	Channel number	Freq. (MHz)	Channel number	Freq. (MHz)	Channel number	Freq. (MHz)
0	**2402**	21	2423	42	2444	63	2465
1	2403	22	2424	43	2445	64	2466
2	2404	23	2425	44	2446	65	2467
3	2405	24	2426	45	2447	66	2468
4	2406	25	2427	46	2448	67	2469
5	2407	26	2428	47	2449	68	2470
6	2408	27	2429	48	2450	69	2471
7	2409	28	2430	49	2451	70	2472
8	2410	29	2431	50	2452	71	2473
9	2411	30	2432	51	2453	72	2474
10	2412	31	2433	52	2454	73	2475
11	2413	32	2434	53	2455	74	2476
12	2414	33	2435	54	2456	75	2477
13	2415	34	2436	55	2457	76	2478
14	2416	35	2437	56	2458	77	2479
15	2417	36	2438	57	2459	**78**	**2480**
16	2418	37	2439	58	2460	-	-
17	2419	38	2440	59	2461	-	-
18	2420	**39**	**2441**	60	2462	-	-
19	2421	40	2442	61	2463	-	-
20	2422	41	2443	62	2464	-	-

2.6 Additional Instructions

EUT Software Settings:

Mode	☒ Special software is used. The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power level setup in software			
Test Software Version	cybluetool_setup_0.1.107.1		
Support Units (Software installation media)	Description	Manufacturer	Model
	Notebook	HP	N/A
Mode	Channel	Frequency (MHz)	Soft Set
DH5	CH0	2402	Power parameter Settings is 10
	CH39	2441	
	CH78	2480	
2DH5	CH0	2402	
	CH39	2441	
	CH78	2480	
3DH5	CH0	2402	
	CH39	2441	
	CH78	2480	

Run Software:



3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C	Miscellaneous Wireless Communications Services
2	RSS-Gen Issue 5	General Requirements for Compliance of Radio Apparatus
3	RSS-247 Issue 2	Digital Transmission Systems (DTSs), Frequency Hopping Systems(FHSs) and Licence-Exemp Local Area Network (LE-LAN) Devices
4	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
5	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules

3.2 Test Verdict

No.	Description	FCC Part No.	ISED Part No.	Channel	Test Result	Verdict	Remark
1	Antenna Requirement	15.203	RSS-247, 5.4 (f)	N/A	--	Pass	Note [1]
2	Number of Hopping Frequencies	15.247(a)	RSS-247, 5.1 (d)	Hopping Mode	ANNEX A.1	Pass	Note [2]
3	Peak Output Power and E.I.R.P	15.247(b)	RSS-247, 5.4 (b)	Low/Middle/ High	ANNEX A.2	Pass	--
4	Occupied Bandwidth	15.247(a)	RSS-247, 5.1 (a)	Low/Middle/ High	ANNEX A.3	Pass	Note [2]
5	Carrier Frequency Separation	15.247(a)	RSS-247, 5.1 (b)	Hopping Mode	ANNEX A.4	Pass	Note [2]
6	Time of Occupancy (Dwell time)	15.247(a)	RSS-247, 5.1 (d)	Hopping Mode	ANNEX A.5	Pass	Note [2]
7	Conducted Spurious Emission & Authorized-band band-edge	15.247(d)	RSS-247, 5.5	Low/Middle/ High	ANNEX A.6	Pass	Note [2]
8	Conducted Emission	15.207	RSS-GEN, 8.8	Low/Middle/ High	ANNEX A.7	Pass	Note [2]
9	Radiated Spurious Emission	15.209 15.247(d)	RSS-247, 5.5	Hopping Mode, Low/Middle/ High	ANNEX A.8	Pass	Note [2]
10	Band Edge(Restricted-band band-edge)	15.209 15.247(d)	RSS-247, 5.5	Hopping Mode, Low/Middle/ High	ANNEX A.9	Pass	Note [2]
11	Receiver Spurious Emissions	--	RSS-Gen, 7.3	--	--	N/A	Note [3]

Note [1]: Please refer to section 5.1

Note [2]: π/4-DQPSK is the EDR 2M rate mode, 8-DPSK is the EDR 3M rate mode. The consistency of test results in π/4-DQPSK and 8-DPSK is very high. So we chose 8-DPSK as a typical representative to appear on the report. Another we will show all the modes on the RF output power test item.

Note [3]: Only radio communication receivers operating in stand-alone mode within the band 30-960 MHz, as well as scanner receivers, are subject to Industry Canada requirements, so this test is not applicable.

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	45% to 55%	
Atmospheric Pressure	100 kPa to 102 kPa	
Temperature	NT (Normal Temperature)	+22℃ to +25℃
Working Voltage of the EUT	NV (Normal Voltage)	3.3 V

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	ROHDE&SCHWARZ	FSV-40	101544	2022.01.04	2023.01.03
Spectrum Analyzer	KEYSIGHT	N9020A	MY50330200	2021.06.01	2022.05.31
Signaling Unit	ROHDE&SCHWARZ	CMW500	142028	2021.06.01	2022.05.31
EMI Receiver	KEYSIGHT	N9038A	MY53220118	2021.09.13	2022.09.12
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2021.10.10	2022.10.09
LISN	SCHWARZBECK	NSLK 8127	8127-687	2021.06.08	2022.06.07
Test Antenna-Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-037	2021.04.16	2024.04.15
Test Antenna-Bi-Log(30 MHz-3 GHz)	SCHWARZBECK	VULB 9163	9163-624	2021.08.20	2024.08.19
Test Antenna-Horn(1-18 GHz)	SCHWARZBECK	BBHA 9120D	9120D-1917	2019.07.02	2022.07.01
Test Antenna-Horn (18-40 GHz)	A-INFO	LB-180400KF	J211060273	2021.07.02	2024.07.01
Anechoic Chamber	RAINFORD	9m*6m*6m	N/A	2021.09.04	2024.09.09
Anechoic Chamber	EMC Electronic Co., Ltd	20.10*11.60*7.35m	N/A	2021.08.15	2024.08.14
Shielded Enclosure	ChangNing	CN-130701	130703	--	--

4.3 Test Software List

Description	Manufacturer	Software Version	Serial No.	Applicable test Setup
BL410R	BALUN	V2.1.1.488	N/A	The section 4.5.1
BL410E	BALUN	V19.8.28.435	N/A	The section 4.5.2&4.5.3&4.5.4&4.5.5

4.4 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Parameters	Uncertainty
Occupied Channel Bandwidth	2.8%
RF output power, conducted	1.28 dB
Power Spectral Density, conducted	1.30 dB
Unwanted Emissions, conducted	1.84 dB
All emissions, radiated	5.36 dB
Temperature	0.82°C
Humidity	4.1%

4.5 Description of Test Setup

4.5.1 For Antenna Port Test

Conducted value (dBm) = Measurement value (dBm) + cable loss (dB)

For example: the measurement value is 10 dBm and the cable 0.5dBm used, then the final result of EUT: Conducted value (dBm) = 10 dBm + 0.5 dB = 10.5 dBm



(Diagram 1)

4.5.2 For AC Power Supply Port Test



(Diagram 2)

4.5.3 For Radiated Test (Below 30 MHz)



(Diagram 3)

4.5.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.5.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

4.6 Measurement Results Explanation Example

4.6.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.
The spectrum analyzer offset is derived from RF cable loss and attenuator factor.
Offset = RF cable loss + attenuator factor.

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Relevant Standards

FCC §15.203 & 15.247(b); RSS-247, 5.4 (f)
An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embedded-in antenna design is used.

Reference Documents	Item
Photo	Please refer to the EUT Photo documents.

5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 Frequency Hopping Systems

5.2.1 Relevant Standards

FCC §15.247(a) (1) (i) (ii) (iii) (iv); FCC §15.247(g); FCC §15.247(h)
Describe how the hopping sequence is generated. Provide an example of the hopping sequence channels, to demonstrate that the sequence meets the requirement specified in the definition of an FHSS system. Per the definition in Section 2.1(c), the hop set shall appear as random in the near term, shall appear as evenly distributed in the long term, and sequential hops shall be randomly distributed in both direction and magnitude of change.
Describe how each individual EUT meets the requirement that each of its hopping channels is used equally on average (e.g., that each new transmission event begins on the next channel in the hopping sequence after the final channel used in the previous transmission event).
Describe how the associated receiver(s) complies with the requirement that the input bandwidth (either RF or IF) matches the bandwidth of the transmitted signal.
Describe how the associated receiver(s) has the ability to shift frequencies in synchronization with the transmitted signals.
For short burst systems, describe how the EUT complies with the requirement that it be designed to be capable of operating as a true frequency hopping system. Specifically, the device shall comply with the equal frequency use and pseudorandom hopping sequence requirement when transmitting in short bursts, and shall be designed to comply when presented with continuous data (or information) stream.
Describe how the EUT complies with the requirement that it not have the ability to be coordinated with other FHSS systems in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitters.

5.2.2 Description of the systems

1. According to the preset procedure of the whole network, all the stations in the automatic control network synchronously change the frequency multiple times within one second, and temporarily stay on each frequency hopping channel. Periodic synchronization signaling is sent from the primary station, instructing all slaves to simultaneously change the operating frequency, then the hopping sequence is generated.
2. The hop set shall appear as random in the near term, shall appear as evenly distributed in the long term, and sequential hops shall be randomly distributed in both direction and magnitude of change.

Reference Documents	
	

3. Channels are classified into two categories, used and unused, where used channels are part of the hopping sequence and unused channels are replaced in the hopping sequence by used channels in a pseudo-random way. Make each individual EUT meets the requirement that each of its hopping channels is used equally on average.
4. The input bandwith and transmitted bandwith are both 1MHz, the associated receiver(s) complies with the requirement that the input bandwidth matches the bandwidth of the transmitted signal.
5. Connected devices communicate on the same physical channel by synchronizing with a common clock and hopping sequence.
6. EUT isn't short burst systems.
7. EUT can't have the ability to be coordinated with other FHSS systems in an effort.

5.3 Number of Hopping Frequencies

5.3.1 Limit

FCC §15.247(a) (1) (iii); RSS-247, 5.1 (d)

Frequency hopping systems operating in the 2400 MHz to 2483.5 MHz bands shall use at least 15 hopping frequencies.

5.3.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = The frequency band of operation

RBW = To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize

5.3.4 Test Result

Please refer to ANNEX A.1.

5.4 Peak Output Power and E.I.R.P

5.4.1 Test Limit

FCC § 15.247(b)

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

RSS-247, 5.4 (b)

For FHSs operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1.0 W and the e.i.r.p. shall not exceed 4 W if the hopset uses 75 or more hopping channels; the maximum peak conducted output power shall not exceed 0.125 W and the e.i.r.p. shall not exceed 0.5 W if the hopset uses less than 75 hopping channels (see Section 5.4(5) for exceptions).

5.4.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

The Module operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW > the 20 dB bandwidth of the emission being measured

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize.

5.4.4 Test Result

Please refer to ANNEX A.2.

5.5 Occupied Bandwidth

5.5.1 Limit

FCC §15.247(a); RSS-247, 5.1 (a)

Measurement of the 20dB bandwidth of the modulated signal.

5.5.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

Use the following spectrum analyzer settings:

Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel

RBW = in the range of 1% to 5% of the OBW

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

The EUT should be transmitting at its maximum data rate, Allow the trace to stabilize.

5.5.4 Test Result

Please refer to ANNEX A.3.

5.6 Carrier Frequency Separation

5.6.1 Limit

FCC §15.247(a); RSS-247, 5.1 (b)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 2/3 of the 20 dB bandwidth of the hopping channel, whichever is greater.

5.6.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.6.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW) ≥ 1% of the span

Video (or Average) Bandwidth (VBW) ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

5.6.4 Test Result

Please refer to ANNEX A.4.

5.7 Time of Occupancy (Dwell time)

5.7.1 Limit

FCC §15.247(a); RSS-247, 5.1 (d)

Frequency hopping systems in the 2400 MHz - 2483.5 MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

5.7.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.7.3 Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:
Span: Zero span, centered on a hopping channel
RBW shall be ≤ channel spacing and where possible RBW should be set >> 1 / T, where T is the expected dwell time per channel
Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel
Detector function: Peak
Trace: Max hold

Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

The average time of occupancy on any channel within the Period can be calculated with formulas:
For GFSK and 8-DPSK:
For DH1 package type
{Total of Dwell} = {Pulse Time} * (1600 / 2) / {Number of Hopping Frequency} * {Period}
{Period} = 0.4 s * {Number of Hopping Frequency}
For DH3 package type
{Total of Dwell} = {Pulse Time} * (1600 / 4) / {Number of Hopping Frequency} * {Period}
{Period} = 0.4 s * {Number of Hopping Frequency}
For DH5 package type
{Total of Dwell} = {Pulse Time} * (1600 / 6) / {Number of Hopping Frequency} * {Period}
{Period} = 0.4 s * {Number of Hopping Frequency}
For AFH Mode:
For DH1 package type
{Total of Dwell} = {Pulse Time} * (800 / 2) / {Number of Hopping Frequency} * {Period}

{Period} = 0.4 s * {Number of Hopping Frequency}
For DH3 package type
{Total of Dwell} = {Pulse Time} * (800 / 4) / {Number of Hopping Frequency} * {Period}
{Period} = 0.4 s * {Number of Hopping Frequency}
For DH5 package type
{Total of Dwell} = {Pulse Time} * (800 / 6) / {Number of Hopping Frequency} * {Period}
{Period} = 0.4 s * {Number of Hopping Frequency}

The lowest, middle and highest channels are selected to perform testing to record the dwell time of each occupation measured in this channel, which is called Pulse Time here.

5.7.4 Test Result

Please refer to ANNEX A.5.

5.8 Conducted Spurious Emission & Authorized-band band-edge

5.8.1 Limit

FCC §15.247(d); RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.8.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.8.3 Test Procedure

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.
RBW = 100 kHz
VBW = 300 kHz
Sweep = auto
Detector function = peak
Trace = max hold
Allow the trace to stabilize

5.8.4 Test Result

Please refer to ANNEX A.6.

5.9 Conducted Emission

5.9.1 Limit

FCC §15.207; RSS-GEN, 8.8

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50μH/50Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dBμV)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.9.2 Test Setup

See section 4.5.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

5.9.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.
Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.9.4 Test Result

Please refer to ANNEX A.7.

5.10 Radiated Spurious Emission

5.10.1 Limit

FCC §15.209&15.247(d); RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. Field Strength (dBμV/m) = 20*log[Field Strength (μV/m)].
2. In the emission tables above, the tighter limit applies at the band edges.
3. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
4. For above 1000 MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).

5.10.2 Test Setup

See section 4.5.3 to 4.5.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.10.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured
RBW = 1 MHz for f ≥ 1 GHz, 100 kHz for f < 1 GHz
VBW ≥ RBW
Sweep = auto
Detector function = peak
Trace = max hold
For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

5.10.4 Test Result

Please refer to ANNEX A.8.

5.11 Band Edge (Restricted-band band-edge)

5.11.1 Limit

FCC §15.209&15.247(d)

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

5.11.2 Test Setup

See section 4.5.3 to 4.5.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.11.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured
RBW = 1 MHz for f ≥ 1 GHz, 100 kHz for f < 1 GHz
VBW ≥ RBW
Sweep = auto
Detector function = peak
Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

5.11.4 Test Result

Please refer to ANNEX A.9.

ANNEX A TEST RESULT

A.1 Number of Hopping Frequency

Test Data

Test Mode	Frequency Block (MHz)	Measured Channel Numbers	Min. Limit	Verdict
GFSK	2400 - 2483.5	79	15	Pass
8-DPSK	2400 - 2483.5	79	15	Pass

Test Plots

GFSK 2.4 GHz ~ 2.4415 GHz



GFSK 2.4415 GHz ~ 2.4835 GHz



8-DPSK 2.4 GHz ~ 2.4415 GHz



8-DPSK 2.4415 GHz ~ 2.4835 GHz



A.2 Peak Output Power and E.I.R.P

Peak Power Test Data

Channel	Measured Output Peak Power						Limit		Verdict
	GFSK		π/4-DQPSK		8-DPSK		dBm	mW	
	dBm	mW	dBm	mW	dBm	mW			
Low	6.27	4.24	4.40	2.76	4.86	3.06	21	125	Pass
Middle	7.18	5.23	5.10	3.24	5.51	3.56			Pass
High	7.10	5.13	5.39	3.46	5.73	3.74			Pass

E.I.R.P Test Data (For ISED)

Channel	E.I.R.P						Limit		Verdict
	GFSK		π/4-DQPSK		8-DPSK		dBm	mW	
	dBm	mW	dBm	mW	dBm	mW			
Low	7.27	5.33	5.40	3.47	5.86	3.85	36	4000	Pass
Middle	8.18	6.58	6.10	4.07	6.51	4.48			Pass
High	8.10	6.46	6.39	4.36	6.73	4.71			Pass

Test Plots

GFSK LOW CHANNEL

GFSK MIDDLE CHANNEL

GFSK HIGH CHANNEL

π/4-DQPSK LOW CHANNEL

π/4-DQPSK MIDDLE CHANNEL

π/4-DQPSK HIGH CHANNEL

8-DPSK LOW CHANNEL

8-DPSK MIDDLE CHANNEL

8-DPSK HIGH CHANNEL

A.3 20 dB and 99% bandwidth

Test Data

GFSK		
Channel	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	1.050000	0.954340
Middle	1.050000	0.948670
High	1.050000	0.955720
π/4-DQPSK		
Channel	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	1.345000	1.196000
Middle	1.345000	1.194500
High	1.345000	1.194200
8-DPSK		
Channel	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	1.255000	1.164000
Middle	1.255000	1.165100
High	1.255000	1.166900

Test Plots

20 dB Bandwidth

GFSK LOW CHANNEL

GFSK MIDDLE CHANNEL

GFSK HIGH CHANNEL

π/4-DQPSK LOW CHANNEL

π/4-DQPSK MIDDLE CHANNEL

π/4-DQPSK HIGH CHANNEL

8-DPSK LOW CHANNEL

8-DPSK MIDDLE CHANNEL

8-DPSK HIGH CHANNEL

99% Bandwidth

GFSK LOW CHANNEL

GFSK MIDDLE CHANNEL

GFSK HIGH CHANNEL

π/4-DQPSK LOW CHANNEL

π/4-DQPSK MIDDLE CHANNEL



π/4-DQPSK HIGH CHANNEL

8-DPSK LOW CHANNEL

8-DPSK MIDDLE CHANNEL

8-DPSK HIGH CHANNEL

A.4 Hopping Frequency Separation

Test Data

Mode	Frequency separation (MHz)	2/3 of the 20 dB Bandwidth (MHz)	Verdict
GFSK	1.000	0.700	Pass
8-DPSK	1.005	0.837	Pass

Test Plots

GFSK



8-DPSK

A.5 Average Time of Occupancy

Test Data

GFSK				
DH Packet	Pulse Width (ms)	Total of Dwell (ms)	Limit (sec)	Verdict
DH 1	0.38240	122.368	0.4	Pass
DH 3	1.64100	262.560	0.4	Pass
DH 5	2.88800	308.053	0.4	Pass
8-DPSK				
DH Packet	Pulse Width (ms)	Total of Dwell (ms)	Limit (sec)	Verdict
DH 1	0.39040	124.928	0.4	Pass
DH 3	1.63400	261.440	0.4	Pass
DH 5	2.88800	308.053	0.4	Pass
AFH Mode				
DH Packet	Pulse Width (ms)	Total of Dwell (ms)	Limit (sec)	Verdict
DH 1	0.38240	61.184	0.4	Pass
DH 3	1.63400	130.720	0.4	Pass
DH 5	2.88800	154.027	0.4	Pass

Test Plots

GFSK DH1



GFSK DH3



GFSK DH5



8-DPSK DH1



8-DPSK DH3



8-DPSK DH5



AFH Mode DH1



AFH Mode DH3



AFH Mode DH5



A.6 Conducted Spurious Emissions & Authorized-band band-edge

Test Data

GFSK				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-37.34	6.11	-13.89	Pass
Middle	-37.20	7.04	-12.96	Pass
High	-37.69	6.96	-13.04	Pass
8-DPSK				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-37.43	1.70	-18.30	Pass
Middle	-37.02	2.35	-17.65	Pass
High	-37.71	2.49	-17.51	Pass

Hopping Mode				
Mode	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
GFSK	-37.02	7.28	-12.72	Pass
8-DPSK	-37.65	1.65	-18.35	Pass

Test Plots

GFSK LOW CHANNEL, CARRIER LEVEL

GFSK LOW CHANNEL, BAND EDGE

GFSK LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



GFSK LOW CHANNEL, SPURIOUS 3 GHz ~ 25 GHz

GFSK MIDDLE CHANNEL, CARRIER LEVEL

GFSK MIDDLE CHANNEL, SPURIOUS
30 MHz ~ 3 GHz



GFSK MIDDLE CHANNEL, SPURIOUS
3 GHz ~ 25 GHz

GFSK HIGH CHANNEL, CARRIER LEVEL

GFSK HIGH CHANNEL, BAND EDGE



GFSK HIGH CHANNEL, SPURIOUS
30 MHz ~ 3 GHz



GFSK HIGH CHANNEL, SPURIOUS
3 GHz ~ 25 GHz

8-DPSK LOW CHANNEL, CARRIER LEVEL

8-DPSK LOW CHANNEL, BAND EDGE

8-DPSK LOW CHANNEL, SPURIOUS
30 MHz ~ 3 GHz



8-DPSK LOW CHANNEL, SPURIOUS
3 GHz ~ 25 GHz

8-DPSK MIDDLE CHANNEL, CARRIER LEVEL

8-DPSK MIDDLE CHANNEL, SPURIOUS
30 MHz ~ 3 GHz



8-DPSK MIDDLE CHANNEL, SPURIOUS
3 GHz ~ 25 GHz

8-DPSK HIGH CHANNEL, CARRIER LEVEL

8-DPSK HIGH CHANNEL, BAND EDGE



8-DPSK HIGH CHANNEL, SPURIOUS
30 MHz ~ 3 GHz



8-DPSK HIGH CHANNEL, SPURIOUS
3 GHz ~ 25 GHz

GFSK HOPPING, CARRIER LEVEL



GFSK HOPPING BAND EDGE (LOW)

GFSK HOPPING BAND EDGE (HIGH)

GFSK Hopping Mode, SPURIOUS 30 MHz ~ 3 GHz



GFSK Hopping Mode, SPURIOUS 3GHz ~ 25 GHz

8-DPSK HOPPING, CARRIER LEVEL



8-DPSK Hopping BAND EDGE (LOW)



8-DPSK Hopping BAND EDGE (HIGH)



8-DPSK Hopping Mode, SPURIOUS 30 MHz ~ 3 GHz



8-DPSK Hopping Mode, SPURIOUS 3GHz ~ 25 GHz

A.7 Conducted Emissions

Note [1]: The EUT is working in the Normal link mode. All modes have been tested and normal link mode is worst.

Note [2]: Results (dBuV) = Original reading level of Spectrum Analyzer (dBuV) + Factor (dB)

Test Data and Plots

PHASE L



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Line	Verdict
1	0.150	54.02	11.00	66.00	-11.98	Peak	L	Pass
1**	0.150	30.07	11.00	56.00	-25.93	AV	L	Pass
2	0.172	54.84	10.98	64.86	-10.02	Peak	L	Pass
2**	0.172	29.10	10.98	54.86	-25.76	AV	L	Pass
3	0.188	53.11	10.97	64.12	-11.01	Peak	L	Pass
3**	0.188	28.45	10.97	54.12	-25.67	AV	L	Pass
4	0.342	43.24	10.89	59.15	-15.91	Peak	L	Pass
4**	0.342	26.21	10.89	49.15	-22.94	AV	L	Pass
5	0.400	40.00	10.90	57.85	-17.85	Peak	L	Pass
5**	0.400	25.91	10.90	47.85	-21.94	AV	L	Pass
6	0.702	37.80	10.83	56.00	-18.20	Peak	L	Pass
6**	0.702	25.22	10.83	46.00	-20.78	AV	L	Pass

PHASE N



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Line	Verdict
1	0.150	55.46	11.00	66.00	-10.54	Peak	N	Pass
1**	0.150	30.86	11.00	56.00	-25.14	AV	N	Pass
2	0.170	55.45	10.98	64.96	-9.51	Peak	N	Pass
2**	0.170	28.26	10.98	54.96	-26.70	AV	N	Pass
3	0.186	51.41	10.97	64.21	-12.80	Peak	N	Pass
3**	0.186	28.86	10.97	54.21	-25.35	AV	N	Pass
4	0.248	44.25	10.92	61.82	-17.57	Peak	N	Pass
4**	0.248	26.76	10.92	51.82	-25.06	AV	N	Pass
5	0.390	42.05	10.90	58.06	-16.01	Peak	N	Pass
5**	0.390	26.85	10.90	48.06	-21.21	AV	N	Pass
6	0.708	38.53	10.83	56.00	-17.47	Peak	N	Pass
6**	0.708	25.74	10.83	46.00	-20.26	AV	N	Pass

A.8 Radiated Spurious Emission

Note [1]: The symbol of "--" in the table which means not application.

Note [2]: For the test data above 1 GHz, according the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note [3]: The EUT is working in the Normal link mode below 1 GHz. All modes have been tested and DH5-Hopping mode is the worst.

Note [4]: Results (dBuV/m) = Original reading level of Spectrum Analyzer (dBuV/m) + Factor (dB)

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Test Data and Plots

30 MHz to 1 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	41.395	12.16	-26.74	30.0	-17.84	Peak	181.00	200	Horizontal	Pass
2	56.668	12.43	-27.10	30.0	-17.57	Peak	0.00	200	Horizontal	Pass
3	103.459	13.48	-27.81	33.5	-20.02	Peak	360.00	200	Horizontal	Pass
4	127.946	13.44	-31.01	33.5	-20.06	Peak	154.00	100	Horizontal	Pass
5	156.553	13.50	-31.04	33.5	-20.00	Peak	256.00	200	Horizontal	Pass
6	319.958	18.85	-24.63	36.0	-17.15	Peak	204.00	100	Horizontal	Pass

30 MHz to 1 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	50.850	17.12	-26.20	30.0	-12.88	Peak	176.00	200	Vertical	Pass
2	62.002	21.29	-28.13	30.0	-8.71	Peak	139.00	100	Vertical	Pass
3	116.066	22.36	-29.00	33.5	-11.14	Peak	235.00	100	Vertical	Pass
4	153.644	21.80	-31.25	33.5	-11.70	Peak	255.00	100	Vertical	Pass
5	210.617	15.44	-27.84	33.5	-18.06	Peak	255.00	100	Vertical	Pass
6	285.046	18.35	-25.49	36.0	-17.65	Peak	189.00	100	Vertical	Pass

Note 1: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note 2: The spurious from 18GHz-25GHz is noise only, do not show on the report.

GFSK LOW CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1351.200	41.93	-17.55	74.0	-32.07	Peak	178.00	150	Horizontal	Pass
1**	1351.200	32.01	-17.55	54.0	-21.99	AV	178.00	150	Horizontal	Pass
2	2401.800	101.34	-13.35	74.0	27.34	Peak	134.00	150	Horizontal	N/A
2**	2401.800	100.45	-13.35	54.0	46.45	AV	134.00	150	Horizontal	N/A
3	3843.750	48.08	-6.36	74.0	-25.92	Peak	95.00	150	Horizontal	Pass
3**	3843.750	46.09	-6.36	54.0	-7.91	AV	95.00	150	Horizontal	Pass
4	7133.750	52.34	0.68	74.0	-21.66	Peak	274.00	150	Horizontal	Pass
4**	7133.750	43.28	0.68	54.0	-10.72	AV	274.00	150	Horizontal	Pass
5	10717.712	48.69	-4.84	74.0	-25.31	Peak	53.00	150	Horizontal	Pass
5**	10717.712	38.97	-4.84	54.0	-15.03	AV	53.00	150	Horizontal	Pass
6	16901.437	53.37	1.49	74.0	-20.63	Peak	165.00	150	Horizontal	Pass
6**	16901.437	44.59	1.49	54.0	-9.41	AV	165.00	150	Horizontal	Pass

GFSK LOW CHANNEL 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1329.300	44.42	-17.22	74.0	-29.58	Peak	206.00	150	Vertical	Pass
1**	1329.300	34.96	-17.22	54.0	-19.04	AV	206.00	150	Vertical	Pass
2	2401.800	90.96	-13.35	74.0	16.96	Peak	230.00	150	Vertical	N/A
2**	2401.800	89.91	-13.35	54.0	35.91	AV	230.00	150	Vertical	N/A
3	4496.500	48.22	-4.19	74.0	-25.78	Peak	36.00	150	Vertical	Pass
3**	4496.500	39.32	-4.19	54.0	-14.68	AV	36.00	150	Vertical	Pass
4	7833.250	53.24	2.27	74.0	-20.76	Peak	208.00	150	Vertical	Pass
4**	7833.250	44.41	2.27	54.0	-9.59	AV	208.00	150	Vertical	Pass
5	10713.912	48.67	-4.83	74.0	-25.33	Peak	53.00	150	Vertical	Pass
5**	10713.912	39.01	-4.83	54.0	-14.99	AV	53.00	150	Vertical	Pass
6	16521.600	52.87	0.01	74.0	-21.13	Peak	66.00	150	Vertical	Pass
6**	16521.600	42.88	0.01	54.0	-11.12	AV	66.00	150	Vertical	Pass

GFSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1619.400	41.61	-17.45	74.0	-32.39	Peak	68.00	150	Horizontal	Pass
1**	1619.400	31.93	-17.45	54.0	-22.07	AV	68.00	150	Horizontal	Pass
2	2440.800	102.10	-12.32	74.0	28.10	Peak	130.00	150	Horizontal	N/A
2**	2440.800	101.19	-12.32	54.0	47.19	AV	130.00	150	Horizontal	N/A
3	3905.750	49.20	-6.52	74.0	-24.80	Peak	68.00	150	Horizontal	Pass
3**	3905.750	46.17	-6.52	54.0	-7.83	AV	68.00	150	Horizontal	Pass
4	7461.250	52.66	1.13	74.0	-21.34	Peak	201.00	150	Horizontal	Pass
4**	7461.250	43.67	1.13	54.0	-10.33	AV	201.00	150	Horizontal	Pass
5	11421.662	49.09	-4.07	74.0	-24.91	Peak	90.00	150	Horizontal	Pass
5**	11421.662	38.95	-4.07	54.0	-15.05	AV	90.00	150	Horizontal	Pass
6	17617.275	52.55	3.15	74.0	-21.45	Peak	316.00	150	Horizontal	Pass
6**	17617.275	42.70	3.15	54.0	-11.30	AV	316.00	150	Horizontal	Pass

GFSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1330.800	41.91	-17.42	74.0	-32.09	Peak	359.00	150	Vertical	Pass
1**	1330.800	32.37	-17.42	54.0	-21.63	AV	359.00	150	Vertical	Pass
2	2440.900	89.96	-12.31	74.0	15.96	Peak	141.00	150	Vertical	N/A
2**	2440.900	88.96	-12.31	54.0	34.96	AV	141.00	150	Vertical	N/A
3	5262.000	50.49	-3.77	74.0	-23.51	Peak	109.00	150	Vertical	Pass
3**	5262.000	40.24	-3.77	54.0	-13.76	AV	109.00	150	Vertical	Pass
4	7509.500	52.89	0.53	74.0	-21.11	Peak	67.00	150	Vertical	Pass
4**	7509.500	43.11	0.53	54.0	-10.89	AV	67.00	150	Vertical	Pass
5	11055.912	48.97	-5.01	74.0	-25.03	Peak	88.00	150	Vertical	Pass
5**	11055.912	38.80	-5.01	54.0	-15.20	AV	88.00	150	Vertical	Pass
6	17540.624	52.94	3.14	74.0	-21.06	Peak	197.00	150	Vertical	Pass
6**	17540.624	43.14	3.14	54.0	-10.86	AV	197.00	150	Vertical	Pass

GFSK HIGH CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1599.900	41.31	-17.75	74.0	-32.69	Peak	52.00	150	Horizontal	Pass
1**	1599.900	34.16	-17.75	54.0	-19.84	AV	52.00	150	Horizontal	Pass
2	2479.800	101.07	-13.06	74.0	27.07	Peak	131.00	150	Horizontal	N/A
2**	2479.800	99.85	-13.06	54.0	45.85	AV	131.00	150	Horizontal	N/A
3	2528.200	52.62	-12.82	74.0	-21.38	Peak	134.00	150	Horizontal	Pass
3**	2528.200	50.24	-12.82	54.0	-3.76	AV	134.00	150	Horizontal	Pass
4	7132.000	52.86	0.70	74.0	-21.14	Peak	0.00	150	Horizontal	Pass
4**	7132.000	43.25	0.70	54.0	-10.75	AV	0.00	150	Horizontal	Pass
5	10700.613	49.49	-4.79	74.0	-24.51	Peak	32.00	150	Horizontal	Pass
5**	10700.613	39.17	-4.79	54.0	-14.83	AV	32.00	150	Horizontal	Pass
6	16559.662	51.95	0.02	74.0	-22.05	Peak	360.00	150	Horizontal	Pass
6**	16559.662	41.54	0.02	54.0	-12.46	AV	360.00	150	Horizontal	Pass

GFSK HIGH CHANNEL 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1330.200	42.99	-17.34	74.0	-31.01	Peak	303.00	150	Vertical	Pass
1**	1330.200	32.41	-17.34	54.0	-21.59	AV	303.00	150	Vertical	Pass
2	2480.000	90.97	-13.08	74.0	16.97	Peak	144.00	150	Vertical	N/A
2**	2480.000	90.57	-13.08	54.0	36.57	AV	144.00	150	Vertical	N/A
3	5180.750	49.98	-2.19	74.0	-24.02	Peak	226.00	150	Vertical	Pass
3**	5180.750	41.57	-2.19	54.0	-12.43	AV	226.00	150	Vertical	Pass
4	7507.750	52.89	0.31	74.0	-21.11	Peak	226.00	150	Vertical	Pass
4**	7507.750	42.91	0.31	54.0	-11.09	AV	226.00	150	Vertical	Pass
5	11682.912	49.43	-4.29	74.0	-24.57	Peak	246.00	150	Vertical	Pass
5**	11682.912	39.45	-4.29	54.0	-14.55	AV	246.00	150	Vertical	Pass
6	16516.350	53.16	0.01	74.0	-20.84	Peak	222.00	150	Vertical	Pass
6**	16516.350	43.05	0.01	54.0	-10.95	AV	222.00	150	Vertical	Pass

8-DPSK LOW CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1599.500	42.76	-17.70	74.0	-31.24	Peak	30.00	150	Horizontal	Pass
1**	1599.500	33.55	-17.70	54.0	-20.45	AV	30.00	150	Horizontal	Pass
2	2401.900	100.12	-13.34	74.0	26.12	Peak	132.00	150	Horizontal	N/A
2**	2401.900	97.19	-13.34	54.0	43.19	AV	132.00	150	Horizontal	N/A
3	2449.800	48.20	-12.77	74.0	-25.80	Peak	137.00	150	Horizontal	Pass
3**	2449.800	48.03	-12.77	54.0	-5.97	AV	137.00	150	Horizontal	Pass
4	7455.000	52.93	1.17	74.0	-21.07	Peak	218.00	150	Horizontal	Pass
4**	7455.000	43.32	1.17	54.0	-10.68	AV	218.00	150	Horizontal	Pass
5	11452.300	48.81	-3.89	74.0	-25.19	Peak	250.00	150	Horizontal	Pass
5**	11452.300	39.57	-3.89	54.0	-14.43	AV	250.00	150	Horizontal	Pass
6	16900.650	52.99	1.51	74.0	-21.01	Peak	149.00	150	Horizontal	Pass
6**	16900.650	43.52	1.51	54.0	-10.48	AV	149.00	150	Horizontal	Pass

8-DPSK LOW CHANNEL 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1328.800	45.28	-17.15	74.0	-28.72	Peak	223.00	150	Vertical	Pass
1**	1328.800	33.13	-17.15	54.0	-20.87	AV	223.00	150	Vertical	Pass
2	2402.000	89.47	-13.34	74.0	15.47	Peak	226.00	150	Vertical	N/A
2**	2402.000	86.55	-13.34	54.0	32.55	AV	226.00	150	Vertical	N/A
3	4454.750	47.30	-4.23	74.0	-26.70	Peak	93.00	150	Vertical	Pass
3**	4454.750	42.55	-4.23	54.0	-11.45	AV	93.00	150	Vertical	Pass
4	7453.000	52.72	1.01	74.0	-21.28	Peak	240.00	150	Vertical	Pass
4**	7453.000	43.99	1.01	54.0	-10.01	AV	240.00	150	Vertical	Pass
5	11209.099	49.22	-4.08	74.0	-24.78	Peak	0.00	150	Vertical	Pass
5**	11209.099	39.24	-4.08	54.0	-14.76	AV	0.00	150	Vertical	Pass
6	16526.850	52.66	0.02	74.0	-21.34	Peak	100.00	150	Vertical	Pass
6**	16526.850	43.57	0.02	54.0	-10.43	AV	100.00	150	Vertical	Pass

8-DPSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1914.600	44.21	-16.04	74.0	-29.79	Peak	0.00	150	Horizontal	Pass
1**	1914.600	33.72	-16.04	54.0	-20.28	AV	0.00	150	Horizontal	Pass
2	2441.000	99.68	-12.31	74.0	25.68	Peak	129.00	150	Horizontal	N/A
2**	2441.000	97.21	-12.31	54.0	43.21	AV	129.00	150	Horizontal	N/A
3	3905.750	49.54	-6.52	74.0	-24.46	Peak	107.00	150	Horizontal	Pass
3**	3905.750	46.15	-6.52	54.0	-7.85	AV	107.00	150	Horizontal	Pass
4	7472.500	52.43	0.71	74.0	-21.57	Peak	233.00	150	Horizontal	Pass
4**	7472.500	43.70	0.71	54.0	-10.30	AV	233.00	150	Horizontal	Pass
5	11787.412	50.23	-3.65	74.0	-23.77	Peak	29.00	150	Horizontal	Pass
5**	11787.412	39.56	-3.65	54.0	-14.44	AV	29.00	150	Horizontal	Pass
6	17287.574	53.27	1.99	74.0	-20.73	Peak	189.00	150	Horizontal	Pass
6**	17287.574	43.35	1.99	54.0	-10.65	AV	189.00	150	Horizontal	Pass

8-DPSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1586.800	41.49	-17.43	74.0	-32.51	Peak	139.00	150	Vertical	Pass
1**	1586.800	31.73	-17.43	54.0	-22.27	AV	139.00	150	Vertical	Pass
2	2441.000	87.40	-12.31	74.0	13.40	Peak	139.00	150	Vertical	N/A
2**	2441.000	84.30	-12.31	54.0	30.30	AV	139.00	150	Vertical	N/A
3	4454.750	48.48	-4.23	74.0	-25.52	Peak	273.00	150	Vertical	Pass
3**	4454.750	40.64	-4.23	54.0	-13.36	AV	273.00	150	Vertical	Pass
4	7466.250	52.57	0.84	74.0	-21.43	Peak	175.00	150	Vertical	Pass
4**	7466.250	42.51	0.84	54.0	-11.49	AV	175.00	150	Vertical	Pass
5	10455.750	48.74	-4.59	74.0	-25.26	Peak	246.00	150	Vertical	Pass
5**	10455.750	38.40	-4.59	54.0	-15.60	AV	246.00	150	Vertical	Pass
6	16684.349	52.55	0.34	74.0	-21.45	Peak	214.00	150	Vertical	Pass
6**	16684.349	42.48	0.34	54.0	-11.52	AV	214.00	150	Vertical	Pass

8-DPSK HIGH CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1573.300	41.13	-17.56	74.0	-32.87	Peak	223.00	150	Horizontal	Pass
1**	1573.300	32.55	-17.56	54.0	-21.45	AV	223.00	150	Horizontal	Pass
2	2479.900	98.56	-13.07	74.0	24.56	Peak	129.00	150	Horizontal	N/A
2**	2479.900	95.82	-13.07	54.0	41.82	AV	129.00	150	Horizontal	N/A
3	3968.250	49.80	-6.45	74.0	-24.20	Peak	90.00	150	Horizontal	Pass
3**	3968.250	48.12	-6.45	54.0	-5.88	AV	90.00	150	Horizontal	Pass
4	6758.750	52.13	-0.94	74.0	-21.87	Peak	7.00	150	Horizontal	Pass
4**	6758.750	42.45	-0.94	54.0	-11.55	AV	7.00	150	Horizontal	Pass
5	11447.788	48.91	-3.89	74.0	-25.09	Peak	78.00	150	Horizontal	Pass
5**	11447.788	39.33	-3.89	54.0	-14.67	AV	78.00	150	Horizontal	Pass
6	17305.426	52.85	2.00	74.0	-21.15	Peak	306.00	150	Horizontal	Pass
6**	17305.426	43.54	2.00	54.0	-10.46	AV	306.00	150	Horizontal	Pass

8-DPSK HIGH CHANNEL 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1828.300	43.20	-17.19	74.0	-30.80	Peak	69.00	150	Vertical	Pass
1**	1828.300	32.82	-17.19	54.0	-21.18	AV	69.00	150	Vertical	Pass
2	2479.900	88.84	-13.07	74.0	14.84	Peak	143.00	150	Vertical	N/A
2**	2479.900	85.11	-13.07	54.0	31.11	AV	143.00	150	Vertical	N/A
3	5107.500	50.15	-2.96	74.0	-23.85	Peak	0.00	150	Vertical	Pass
3**	5107.500	40.38	-2.96	54.0	-13.62	AV	0.00	150	Vertical	Pass
4	7874.000	52.30	2.04	74.0	-21.70	Peak	151.00	150	Vertical	Pass
4**	7874.000	42.50	2.04	54.0	-11.50	AV	151.00	150	Vertical	Pass
5	11793.825	48.49	-3.59	74.0	-25.51	Peak	63.00	150	Vertical	Pass
5**	11793.825	38.42	-3.59	54.0	-15.58	AV	63.00	150	Vertical	Pass
6	17662.687	52.66	2.75	74.0	-21.34	Peak	353.00	150	Vertical	Pass
6**	17662.687	43.72	2.75	54.0	-10.28	AV	353.00	150	Vertical	Pass

A.9 Band Edge (Restricted-band band-edge)

Note [1]: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.
Note [2]: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.
Note [3]: According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.
Note [4]: The Level (dBuV/m) has been corrected by factor.

Test Data and Plots

GFSK LOW CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2390.000	56.33	1.62	74.0	-17.67	Peak	44.00	150	Horizontal	Pass
1**	2390.000	45.70	1.62	54.0	-8.30	AV	44.00	150	Horizontal	Pass
2	2345.500	58.12	2.45	74.0	-15.88	Peak	238.00	150	Horizontal	Pass
2**	2345.500	46.57	2.45	54.0	-7.43	AV	238.00	150	Horizontal	Pass

GFSK HIGH CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	56.66	1.98	74.0	-17.34	Peak	161.00	150	Horizontal	Pass
1**	2483.500	46.03	1.98	54.0	-7.97	AV	161.00	150	Horizontal	Pass
2	2493.400	57.87	1.83	74.0	-16.13	Peak	223.00	150	Horizontal	Pass
2**	2493.400	45.86	1.83	54.0	-8.14	AV	223.00	150	Horizontal	Pass

8-DPSK LOW CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2390.000	56.21	1.62	74.0	-17.79	Peak	115.00	150	Horizontal	Pass
1**	2390.000	45.58	1.62	54.0	-8.42	AV	115.00	150	Horizontal	Pass
2	2338.167	58.35	2.33	74.0	-15.65	Peak	23.00	150	Horizontal	Pass
2**	2338.167	46.14	2.33	54.0	-7.86	AV	23.00	150	Horizontal	Pass

8-DPSK HIGH CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	56.53	1.98	74.0	-17.47	Peak	307.00	150	Horizontal	Pass
1**	2483.500	46.01	1.98	54.0	-7.99	AV	307.00	150	Horizontal	Pass
2	2490.150	57.96	1.91	74.0	-16.04	Peak	132.00	150	Horizontal	Pass
2**	2490.150	46.01	1.91	54.0	-7.99	AV	132.00	150	Horizontal	Pass

ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-EC2220134-AR.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-EC2220134-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-EC2220134-AI.PDF”.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the “inspection and testing dedicated stamp” or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--