

LTE

Data List							
Test Mode	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Pol.
LTE_B2_20M_CH19100	111.0355	-53.29	-50.36	2.93	-13.00	37.36	V
	248.8444	-50.99	-49.61	1.38	-13.00	36.61	H
	886.4532	-51.03	-42.53	8.50	-13.00	29.53	H
	3782.0000	-57.67	-43.40	14.27	-13.00	30.40	V
	5673.0000	-53.72	-35.13	18.59	-13.00	22.13	V
	7564.0000	-63.50	-39.62	23.88	-13.00	26.62	V
	9455.0000	-67.49	-44.18	23.31	-13.00	31.18	H
	11346.0000	-68.66	-43.31	25.35	-13.00	30.31	V
	13237.0000	-68.10	-41.94	26.16	-13.00	28.94	V
	15128.0000	-69.39	-40.60	28.79	-13.00	27.60	V
	17019.0000	-68.62	-34.86	33.76	-13.00	21.86	V
LTE_B4_20M_CH20300	95.993	-58.00	-60.93	-2.93	-13.00	47.93	V
	155.6778	-59.38	-69.26	-9.88	-13.00	56.26	V
	879.6598	-76.65	-67.83	8.82	-13.00	54.83	H
	3470.0000	-59.54	-46.38	13.16	-13.00	33.38	H
	5207.4415	-47.88	-29.69	18.19	-13.00	16.69	V
	6940.0000	-61.73	-39.14	22.59	-13.00	26.14	H
	8675.0000	-65.28	-43.31	21.97	-13.00	30.31	V
	10410.0000	-68.22	-43.26	24.96	-13.00	30.26	V
	12145.0000	-67.92	-42.85	25.07	-13.00	29.85	V
	13880.0000	-67.88	-41.56	26.32	-13.00	28.56	H
	15615.0000	-69.12	-39.78	29.34	-13.00	26.78	H
	17350.0000	-69.20	-34.76	34.44	-13.00	21.76	V
LTE_B7_20M_CH21100	109.5798	-52.36	-49.87	2.49	-25.00	24.87	V
	250.7854	-52.43	-50.40	2.03	-25.00	25.40	H
	5052.0000	-51.97	-33.54	18.43	-25.00	8.54	V
	7578.0000	-62.93	-38.90	24.03	-25.00	13.90	V
	10104.0000	-66.28	-42.36	23.92	-25.00	17.36	V

	12630.0000	-68.73	-42.64	26.09	-25.00	17.64	V
	15156.0000	-69.18	-40.29	28.89	-25.00	15.29	V
	17682.0000	-69.74	-34.38	35.36	-25.00	9.38	H
LTE_B25_20M_CH26365	96.0118	-56.81	-59.75	-2.94	-13.00	46.75	V
	887.5229	-65.24	-56.78	8.46	-13.00	43.78	H
	3746.0000	-57.70	-43.16	14.54	-13.00	30.16	V
	5621.5243	-53.67	-34.99	18.68	-13.00	21.99	V
	7492.0000	-65.21	-40.92	24.29	-13.00	27.92	H
	9365.0000	-71.32	-48.50	22.82	-13.00	35.50	V
	11238.0000	-71.42	-47.39	24.03	-13.00	34.39	H
	13111.0000	-72.45	-46.50	25.95	-13.00	33.50	H
	14984.0000	-73.18	-44.90	28.28	-13.00	31.90	V
	16857.0000	-73.45	-40.67	32.78	-13.00	27.67	V
LTE_B30_10M_CH27710	110.514	-52.65	-49.85	2.80	-40.00	9.85	V
	252.6261	-52.55	-50.65	1.90	-40.00	10.65	H
	4610.0000	-66.84	-50.19	16.65	-40.00	10.19	V
	6915.0000	-72.64	-50.09	22.55	-40.00	10.09	H
	9220.0000	-77.04	-54.34	22.70	-40.00	14.34	V
	11525.0000	-76.74	-51.49	25.25	-40.00	11.49	V
	13830.0000	-77.68	-51.20	26.48	-40.00	11.20	V
	16135.0000	-76.92	-45.54	31.38	-40.00	5.54	H
LTE_B41_20M_CH41490	250.3002	-51.75	-49.87	1.88	-25.00	24.87	H
	879.6598	-50.82	-42.00	8.82	-25.00	17.00	H
	5342.4685	-51.99	-33.08	18.91	-25.00	8.08	V
	8016.0000	-72.54	-50.09	22.45	-25.00	25.09	H
	10688.0000	-73.61	-49.28	24.33	-25.00	24.28	H
	13360.0000	-74.95	-48.67	26.28	-25.00	23.67	V
	16032.0000	-75.88	-44.59	31.29	-25.00	19.59	V
LTE_B66_20M_CH132572	111.0355	-52.89	-49.96	2.93	-13.00	36.96	V
	252.2411	-52.33	-50.31	2.02	-13.00	37.31	H
	3522.0000	-58.49	-45.29	13.20	-13.00	32.29	V
	5283.0000	-47.82	-29.06	18.76	-13.00	16.06	V

	7044.0000	-62.79	-41.20	21.59	-13.00	28.20	V
	8805.0000	-67.53	-45.15	22.38	-13.00	32.15	H
	10566.0000	-68.80	-43.51	25.29	-13.00	30.51	V
	12327.0000	-69.03	-44.20	24.83	-13.00	31.20	H
	14088.0000	-68.97	-42.70	26.27	-13.00	29.70	V
	15849.0000	-69.43	-38.59	30.84	-13.00	25.59	V
	17610.0000	-69.58	-34.68	34.90	-13.00	21.68	V

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

(3)V=Vertical,H= Horizontal