

RF Exposure Evaluation Report

APPLICANT : Quectel Wireless Solutions Co., Ltd.
EQUIPMENT : Smart Module
BRAND NAME : Quectel
MODEL NAME : SC696S-NA
FCC ID : XMR2023SC696SNA
STANDARD : 47 CFR Part 2.1091
FCC KDB 447498 D01 v06

The product evaluation date was started from Sep. 22, 2023 and completed on Sep. 22, 2023. We, Sporton International Inc. (Kunshan), would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and FCC KDB 447498 D01 v06, and pass the limit. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.



Approved by: Si Zhang

Sporton International Inc. (Kunshan)

***No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China***



Table of Contents

1. ADMINISTRATION DATA	4
1.1. Testing Laboratory	4
2. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	5
3. MAXIMUM RF AVERAGE OUTPUT TUNE UP POWER AMONG PRODUCTION UNITS	6
4. RF EXPOSURE LIMIT INTRODUCTION	8
5. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION	9
5.1. Standalone Power Density Calculation	9
5.2. Collocated Power Density Calculation.....	10



Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA311713-01	Rev. 01	Initial issue of report.	Oct. 19, 2023



1. Administration Data

1.1. Testing Laboratory

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Testing Laboratory			
Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	SAR01-KS	CN1257	314309

Applicant	
Company Name	Quectel Wireless Solutions Co., Ltd.
Address	Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, 200233,China

Manufacturer	
Company Name	Quectel Wireless Solutions Co., Ltd.
Address	Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, 200233,China

2. Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT Type	Smart Module
Brand Name	Quectel
Model Name	SC696S-NA
FCC ID	XMR2023SC696SNA
Wireless Technology and Frequency Range	LTE Band 2 : 1850 MHz ~ 1910 MHz LTE Band 4 : 1710 MHz ~ 1755 MHz LTE Band 5 : 824 MHz ~ 849 MHz LTE Band 7: 2500 MHz ~ 2570 MHz LTE Band 12 : 699 MHz ~ 716 MHz LTE Band 13 : 777 MHz ~ 787 MHz LTE Band 14: 788 MHz ~ 798 MHz LTE Band 17: 704 MHz ~ 716 MHz LTE Band 25 : 1850 MHz ~ 1915 MHz LTE Band 26 : 814 MHz ~ 849 MHz LTE Band 66 : 1710 MHz ~ 1780 MHz LTE Band 41: 2496 MHz ~ 2690 MHz LTE Band 71: 663 MHz ~ 698 MHz WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz WLAN 5.2GHz Band: 5180 MHz ~ 5240 MHz WLAN 5.3GHz Band: 5260 MHz ~ 5320 MHz WLAN 5.5GHz Band: 5500 MHz ~ 5720 MHz WLAN 5.8GHz Band: 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Mode	LTE: QPSK, 16QAM WLAN 2.4GHz 802.11b/g/n HT20/HT40 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE
Antenna Gain	WLAN2.4GHz/Bluetooth: 0.47 dBi WLAN5.2GHz: -0.67 dBi WLAN5.3GHz: -0.19 dBi WLAN5.5GHz: 1.28 dBi WLAN5.8GHz: 1.10 dBi
Antenna Type	WWAN: Fixed External Antenna WLAN/Bluetooth: Folded Dipole Antenna
HW Version	R1.0
SW Version	SC696SNANAR60A02
EUT Stage	Identical Prototype

Remark:

- The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Comments and Explanations:

- The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.
- The maximum RF output tune up power, antenna gain also the safe distance used for evaluate RF exposure were declared by manufacturer.

3. Maximum RF average output tune up power among production units

<LTE>

Mode		Maximum Average power(dBm)
LTE	Band 2	25.0
	Band 4	25.0
	Band 5	25.0
	Band 7	25.0
	Band 12	25.0
	Band 13	25.0
	Band 14	25.0
	Band 17	25.0
	Band 25	25.0
	Band 26	25.0
	Band 41	25.0
	Band 66	25.0
	Band 71	25.0

<2.4GHz WLAN >

Mode		Maximum Average Power (dBm)
2.4GHz	802.11b	17.00
	802.11g	17.00
	802.11n-HT20	16.00
	802.11n-HT40	16.00

<Bluetooth>

Mode		Maximum Average power(dBm)
Bluetooth	BR/EDR	10.00
	LE	3.00

<5GHz WLAN >

	Mode	Maximum Average Power (dBm)
5.2GHz	802.11a	17.00
	802.11n-HT20	17.00
	802.11n-HT40	17.00
	802.11ac-VHT20	16.00
	802.11ac-VHT40	16.00
	802.11ac-VHT80	16.00
5.3GHz	802.11a	17.00
	802.11n-HT20	17.00
	802.11n-HT40	17.00
	802.11ac-VHT20	16.00
	802.11ac-VHT40	16.00
	802.11ac-VHT80	16.00
5.5GHz	802.11a	17.00
	802.11n-HT20	17.00
	802.11n-HT40	17.00
	802.11ac-VHT20	16.00
	802.11ac-VHT40	15.00
	802.11ac-VHT80	15.00
5.8GHz	802.11a	17.00
	802.11n-HT20	17.00
	802.11n-HT40	17.00
	802.11ac-VHT20	16.00
	802.11ac-VHT40	15.00
	802.11ac-VHT80	15.00

4. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna



5. Radio Frequency Radiation Exposure Evaluation

5.1. Standalone Power Density Calculation

Band	Frequency (MHz)	Maximum Power (dBm)	MPE evaluation distance (cm)	FCC ERP/EIRP Limit (W)	IC ERP/EIRP Limit (W)	FCC MPE Limit (mW)/cm ²	IC MPE Limit (W)/m ²	FCC/IC MPE Limit (mW)/cm ²	FCC/IC MPE Result / FCC/IC MPE Limit Ratio	Ant Gain to meet FCC MPE limit (dBi)	Ant Gain to meet FCC ERP/EIRP limit (dBi)	Max Gain to meet FCC ERP/EIRP and MPE limit (dBi)	Ant Gain to meet IC MPE limit (dBi)	Ant Gain to meet IC ERP/EIRP limit (dBi)	Max Gain to meet IC ERP/EIRP and MPE limit (dBi)	Max Gain to consider same Frequency	Max gain allowed (dBi)
LTE Band 2	1850.0	25.00	20.00	2.000	2.000	1.000	4.476	0.448	0.887	12.0	8.0	8.0	8.5	8.0	8.0	8.0	8.0
LTE Band 4	1710.0	25.00	20.00	1.000	1.000	1.000	4.242	0.424	0.469	12.0	5.0	5.0	8.2	5.0	5.0	5.0	5.0
LTE Band 5	824.0	25.00	20.00	7.000	11.500	0.549	2.576	0.258	0.828	9.4	13.4	9.4	6.1	15.6	6.1	5.3	5.3
LTE Band 7	2500.0	25.00	20.00	2.000	2.000	1.000	5.499	0.550	0.722	12.0	8.0	8.0	9.4	8.0	8.0	8.0	8.0
LTE Band 12	699.0	25.00	20.00	3.000	3.000	0.466	2.302	0.230	0.927	8.6	9.7	8.6	5.6	9.7	5.6	5.3	5.3
LTE Band 13	777.0	25.00	20.00	3.000	3.000	0.518	2.474	0.247	0.862	9.1	9.7	9.1	5.9	9.7	5.9	5.3	5.3
LTE Band 14	788.0	25.00	20.00	3.000	3.000	0.525	2.498	0.250	0.854	9.2	9.7	9.2	5.9	9.7	5.9	5.3	5.3
LTE Band 17	704.0	25.00	20.00	3.000	3.000	0.469	2.313	0.231	0.922	8.7	9.7	8.7	5.6	9.7	5.6	5.3	5.3
LTE Band 25	1850.0	25.00	20.00	2.000	2.000	1.000	4.476	0.448	0.887	12.0	8.0	8.0	8.5	8.0	8.0	8.0	8.0
LTE Band 26	814.0	25.00	20.00	7.000	11.500	0.543	2.554	0.255	0.835	9.3	13.4	9.3	6.0	15.6	6.0	5.3	5.3
LTE Band 41	2496.0	25.00	20.00	2.000	2.000	1.000	5.493	0.549	0.723	12.0	8.0	8.0	9.4	8.0	8.0	8.0	8.0
LTE Band 66	1710.0	25.00	20.00	1.000	1.000	1.000	4.242	0.424	0.469	12.0	5.0	5.0	8.2	5.0	5.0	5.0	5.0
LTE Band 71	663.0	25.00	20.00	3.000	3.000	0.442	2.220	0.222	0.961	8.4	9.7	8.4	5.4	9.7	5.4	5.3	5.3

Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Average EIRP (mW)	Power Density at 20cm (mW/cm ²)	Limit (mW/cm ²)	Power Density / Limit
Bluetooth	2402.0	0.47	10.00	10.470	11.143	0.002	1.000	0.002
2.4GHz WLAN	2412.0	0.47	17.00	17.470	55.847	0.011	1.000	0.011
5.2GHz WLAN	5180.0	-0.67	17.00	16.330	42.954	0.009	1.000	0.009
5.3GHz WLAN	5260.0	-0.19	17.00	16.810	47.973	0.010	1.000	0.010
5.5GHz WLAN	5500.0	1.28	17.00	18.280	67.298	0.013	1.000	0.013
5.8GHz WLAN	5745.0	1.10	17.00	18.100	64.565	0.013	1.000	0.013

Note:

1. For conservativeness, the lowest frequency of each band is used to determine the MPE limit of that band.
2. Chose the maximum power to do MPE analysis.

**5.2. Collocated Power Density Calculation**

WWAN Power Density / Limit	Bluetooth Power Density / Limit	Σ (Power Density / Limit) of WWAN + Bluetooth
0.961	0.002	0.963
WWAN Power Density / Limit	WLAN 2.4GHz Power Density / Limit	Σ (Power Density / Limit) of WWAN + WLAN 2.4GHz
0.961	0.011	0.972
WWAN Power Density / Limit	WLAN 5GHz Power Density / Limit	Σ (Power Density / Limit) of WWAN + WLAN 5GHz
0.961	0.013	0.974

Note:

1. For colocation analysis, LTE Band 71 is chosen for summation due to the highest (power density/limit) among all WWAN wireless modes.
2. Σ (Power Density / Limit): This is a summation of [(power density for each transmitter/antenna included in the simultaneous transmission)/ (corresponding MPE limit)], for WWAN + Bluetooth or WLAN2.4GHz or WLAN5GHz.
3. Considering all transmitter of the EIRP performance listed in the table above, the aggregated (power density /limit) is smaller than 1, and MPE of 2 collocated transmitters is compliant.

Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.

-----THE END-----