

GSM

Data List							
Test Mode	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Pol.
GSM_GSM850_CH190	110.5625	-64.54	-71.89	-7.35	-13.00	58.89	V
	481.8486	-54.79	-64.47	-9.68	-13.00	51.47	H
	1648.0000	-55.05	-40.38	14.67	-13.00	27.38	V
	2472.0000	-70.25	-48.77	21.48	-13.00	35.77	V
	3296.0000	-65.47	-52.59	12.88	-13.00	39.59	V
	4120.0000	-68.90	-53.15	15.75	-13.00	40.15	V
	4944.0000	-72.41	-55.74	16.67	-13.00	42.74	H
	5768.0000	-72.34	-53.04	19.30	-13.00	40.04	H
	6592.0000	-72.95	-51.89	21.06	-13.00	38.89	H
	7416.0000	-72.91	-49.49	23.42	-13.00	36.49	H
	8240.0000	-78.32	-56.67	21.65	-13.00	43.67	H
GSM_PCS1900_CH661	74.6222	-44.64	-67.53	-22.89	-13.00	54.53	H
	252.7716	-61.67	-71.06	-9.39	-13.00	58.06	H
	483.1097	-51.28	-62.03	-10.75	-13.00	49.03	V
	2451.7259	-59.70	-49.62	10.08	-13.00	36.62	V
	3760.0000	-71.10	-56.83	14.27	-13.00	43.83	V
	5640.0000	-72.37	-53.33	19.04	-13.00	40.33	H
	7520.0000	-73.31	-49.43	23.88	-13.00	36.43	H
	9400.0000	-78.08	-54.49	23.59	-13.00	41.49	V
	11280.0000	-77.91	-52.98	24.93	-13.00	39.98	V
	13160.0000	-74.79	-48.68	26.11	-13.00	35.68	V
	15040.0000	-80.06	-51.69	28.37	-13.00	38.69	V
	16920.0000	-80.36	-47.08	33.28	-13.00	34.08	V

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

(3)V=Vertical,H= Horizontal

LTE

Data List							
Test Mode	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Pol.
LTE_B2_20M_CH18900	111.0355	-61.05	-58.12	2.93	-13.00	45.12	V
	882.5713	-59.55	-50.87	8.68	-13.00	37.87	H
	3742.0000	-70.70	-56.24	14.46	-13.00	43.24	V
	5613.0000	-68.30	-49.29	19.01	-13.00	36.29	V
	7484.0000	-72.23	-48.61	23.62	-13.00	35.61	V
	9355.0000	-78.88	-56.17	22.71	-13.00	43.17	V
	11226.0000	-79.76	-55.20	24.56	-13.00	42.20	V
	13097.0000	-80.36	-54.15	26.21	-13.00	41.15	V
	14968.0000	-80.24	-51.99	28.25	-13.00	38.99	V
	16839.0000	-79.37	-46.67	32.70	-13.00	33.67	V
LTE_B4_20M_CH20050	112.006	-78.39	-75.58	2.81	-13.00	62.58	V
	482.2461	-65.73	-67.47	-1.74	-13.00	54.47	V
	3422.0000	-63.36	-50.35	13.01	-13.00	37.35	V
	5133.0000	-67.03	-49.05	17.98	-13.00	36.05	V
	6844.0000	-73.09	-51.12	21.97	-13.00	38.12	H
	8555.0000	-77.65	-55.49	22.16	-13.00	42.49	H
	10266.0000	-79.30	-54.47	24.83	-13.00	41.47	V
	11977.0000	-80.04	-54.45	25.59	-13.00	41.45	V
	13688.0000	-80.37	-54.23	26.14	-13.00	41.23	H
	15399.0000	-79.81	-50.87	28.94	-13.00	37.87	V
	17110.0000	-80.70	-47.21	33.49	-13.00	34.21	V
LTE_B5_10M_CH20600	111.5208	-61.26	-58.26	3.00	-13.00	45.26	V
	252.2411	-60.77	-58.75	2.02	-13.00	45.75	H
	1678.0000	-70.29	-54.47	15.82	-13.00	41.47	H
	2517.0000	-70.08	-47.95	22.13	-13.00	34.95	H
	3356.0000	-70.98	-57.92	13.06	-13.00	44.92	V
	4195.0000	-71.88	-56.52	15.36	-13.00	43.52	V
	5034.0000	-72.23	-54.36	17.87	-13.00	41.36	H

	5873.0000	-72.55	-53.14	19.41	-13.00	40.14	H
	6712.0000	-72.89	-51.70	21.19	-13.00	38.70	H
	7551.0000	-73.45	-49.65	23.80	-13.00	36.65	H
	8390.0000	-78.21	-55.53	22.68	-13.00	42.53	V
LTE_B7_20M_CH21100	111.0355	-61.27	-58.34	2.93	-25.00	33.34	V
	250.7854	-60.80	-58.77	2.03	-25.00	33.77	H
	879.1746	-59.45	-50.60	8.85	-25.00	25.60	H
	5052.0000	-58.18	-39.75	18.43	-25.00	14.75	V
	7578.0000	-70.37	-46.34	24.03	-25.00	21.34	V
	10104.0000	-73.58	-49.66	23.92	-25.00	24.66	V
	12630.0000	-77.57	-51.48	26.09	-25.00	26.48	V
	15156.0000	-79.86	-51.13	28.73	-25.00	26.13	H
	17682.0000	-80.03	-44.67	35.36	-25.00	19.67	H
LTE_B66_20M_CH132572	111.5208	-61.25	-58.25	3.00	-13.00	45.25	V
	252.2411	-60.33	-58.31	2.02	-13.00	45.31	H
	884.9975	-59.43	-50.86	8.57	-13.00	37.86	H
	3522.0000	-64.20	-51.00	13.20	-13.00	38.00	V
	5283.0000	-71.59	-52.83	18.76	-13.00	39.83	V
	7044.0000	-73.54	-51.46	22.08	-13.00	38.46	H
	8805.0000	-76.08	-53.82	22.26	-13.00	40.82	V
	10566.0000	-78.69	-53.40	25.29	-13.00	40.40	V
	12327.0000	-79.22	-54.39	24.83	-13.00	41.39	H
	14088.0000	-79.00	-52.73	26.27	-13.00	39.73	V
	15849.0000	-79.56	-48.72	30.84	-13.00	35.72	V
	17610.0000	-79.16	-44.13	35.03	-13.00	31.13	H

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

(3)V=Vertical,H= Horizontal