

NR SA

Data List							
Test Mode	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Pol.
NR_n5_20_CH167300	961.6658	-58.95	-51.11	7.84	-13.00	38.11	V
	1673.0000	-70.23	-54.60	15.63	-13.00	41.60	H
	2509.5000	-69.93	-48.16	21.77	-13.00	35.16	H
	3346.0000	-70.52	-57.58	12.94	-13.00	44.58	V
	4182.5000	-71.69	-56.05	15.64	-13.00	43.05	H
	5019.0000	-72.39	-55.18	17.21	-13.00	42.18	V
	5855.5000	-72.24	-52.45	19.79	-13.00	39.45	H
	6692.0000	-72.66	-51.61	21.05	-13.00	38.61	H
	7528.5000	-73.15	-49.35	23.80	-13.00	36.35	V
	8365.0000	-78.06	-55.66	22.40	-13.00	42.66	V
NR_n12_15_CH141500	875.2926	-58.95	-50.75	8.20	-13.00	37.75	H
	1415.0000	-71.62	-56.47	15.15	-13.00	43.47	V
	2122.5000	-70.74	-50.25	20.49	-13.00	37.25	H
	2830.0000	-70.27	-47.51	22.76	-13.00	34.51	H
	3537.5000	-71.07	-57.76	13.31	-13.00	44.76	V
	4245.0000	-71.61	-55.85	15.76	-13.00	42.85	H
	4952.5000	-72.11	-55.15	16.96	-13.00	42.15	H
	5660.0000	-72.11	-53.31	18.80	-13.00	40.31	H
	6367.5000	-71.81	-51.43	20.38	-13.00	38.43	H
	7075.0000	-73.35	-51.08	22.27	-13.00	38.08	H
NR_n77_100_CH656000	112.006	-74.04	-71.23	2.81	-13.00	58.23	V
	879.1746	-78.51	-69.66	8.85	-13.00	56.66	H
	3354.971	-60.65	-36.31	24.34	-13.00	23.31	V
	4232.0464	-67.33	-40.98	26.35	-13.00	27.98	V
	7582.0000	-73.16	-49.22	23.94	-13.00	36.22	H
	11373.0000	-78.85	-53.36	25.49	-13.00	40.36	V
	15164.0000	-79.97	-51.04	28.93	-13.00	38.04	V

NR_n41_100_CH518598	251.2706	-60.98	-58.81	2.17	-25.00	33.81	H
	884.5123	-58.89	-50.30	8.59	-25.00	25.30	H
	5090.0000	-73.15	-55.25	17.90	-25.00	30.25	V
	7635.0000	-73.48	-49.06	24.42	-25.00	24.06	H
	10180.0000	-84.41	-59.77	24.64	-25.00	34.77	V
	12725.0000	-83.87	-57.21	26.66	-25.00	32.21	V
	15270.0000	-86.16	-57.23	28.93	-25.00	32.23	V
	17815.0000	-88.47	-53.64	34.83	-25.00	28.64	H

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

(3)V=Vertical,H= Horizontal