

GSM

Data List							
Test Mode	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Pol.
GSM_GSM 850_CH190	111.1931	-53.92	-61.10	-7.18	-13.00	48.10	V
	623.8152	-57.21	-65.47	-8.26	-13.00	52.47	V
	1673.3347	-60.19	-44.56	15.63	-13.00	31.56	H
	2508.0000	-77.91	-56.19	21.72	-13.00	43.19	H
	3344.0000	-70.66	-57.87	12.79	-13.00	44.87	H
	4180.0000	-71.89	-55.80	16.09	-13.00	42.80	H
	5016.0000	-72.30	-55.07	17.23	-13.00	42.07	V
	5852.0000	-72.10	-52.38	19.72	-13.00	39.38	H
	6688.0000	-72.68	-51.50	21.18	-13.00	38.50	H
	7524.0000	-73.32	-49.55	23.77	-13.00	36.55	H
	8360.0000	-78.24	-55.84	22.40	-13.00	42.84	H

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

(3)V=Vertical,H= Horizontal

WCDMA

Data List							
Test Mode	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Pol.
WCDMA_Band IV_5M_CH1413	111.5208	-71.35	-68.35	3.00	-13.00	55.35	V
	884.5123	-78.45	-69.86	8.59	-13.00	56.86	H
	3506.0000	-70.47	-56.88	13.59	-13.00	43.88	V
	5259.0000	-72.28	-53.87	18.41	-13.00	40.87	H
	7012.0000	-73.42	-52.29	21.13	-13.00	39.29	H
	8765.0000	-76.72	-54.26	22.46	-13.00	41.26	H
	10518.0000	-78.99	-53.88	25.11	-13.00	40.88	V
	12271.0000	-79.16	-54.07	25.09	-13.00	41.07	V
	14024.0000	-79.43	-53.14	26.29	-13.00	40.14	V
	15777.0000	-79.76	-49.22	30.54	-13.00	36.22	V
	17530.0000	-79.40	-44.89	34.51	-13.00	31.89	H

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

(3)V=Vertical,H= Horizontal

LTE

Data List							
Test Mode	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Pol.
LTE_B2_20M_CH19100	111.5208	-71.13	-68.13	3.00	-13.00	55.13	V
	3782.0000	-69.91	-55.64	14.27	-13.00	42.64	V
	5673.0000	-72.15	-53.46	18.69	-13.00	40.46	H
	7564.0000	-73.06	-49.18	23.88	-13.00	36.18	V
	9455.0000	-79.11	-55.45	23.66	-13.00	42.45	V
	11346.0000	-79.56	-54.21	25.35	-13.00	41.21	V
	13237.0000	-79.83	-53.67	26.16	-13.00	40.67	V
	15128.0000	-80.39	-51.60	28.79	-13.00	38.60	V
	17019.0000	-80.78	-47.02	33.76	-13.00	34.02	V
CA_5B_5M+3M_CH20510_20549	111.0355	-60.76	-57.83	2.93	-13.00	44.83	V
	251.2706	-60.77	-58.60	2.17	-13.00	45.60	H
	1670.0000	-70.50	-55.03	15.47	-13.00	42.03	H
	2505.0000	-69.92	-48.33	21.59	-13.00	35.33	H
	3340.0000	-70.92	-57.98	12.94	-13.00	44.98	H
	4175.0000	-71.41	-55.91	15.50	-13.00	42.91	H
	5010.0000	-72.44	-54.72	17.72	-13.00	41.72	V
	5845.0000	-72.29	-52.51	19.78	-13.00	39.51	H
	6680.0000	-72.68	-51.83	20.85	-13.00	38.83	H
	7515.0000	-73.22	-49.52	23.70	-13.00	36.52	H
	8350.0000	-77.99	-55.74	22.25	-13.00	42.74	H

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

(3)V=Vertical,H= Horizontal