

LTE

Data List							
Test Mode	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Pol.
LTE_B2_20M_CH19100	111.5208	-60.54	-57.54	3.00	-13.00	44.54	V
	251.7559	-60.87	-58.69	2.18	-13.00	45.69	H
	3782.0000	-70.17	-55.90	14.27	-13.00	42.90	V
	5673.0000	-72.47	-53.78	18.69	-13.00	40.78	H
	7564.0000	-72.19	-48.31	23.88	-13.00	35.31	V
	9455.0000	-79.14	-55.48	23.66	-13.00	42.48	V
	11346.0000	-79.57	-54.22	25.35	-13.00	41.22	V
	13237.0000	-79.98	-53.82	26.16	-13.00	40.82	V
	15128.0000	-80.49	-51.70	28.79	-13.00	38.70	V
	17019.0000	-80.68	-46.92	33.76	-13.00	33.92	V
LTE_B4_20M_CH20300	107.6388	-67.14	-65.19	1.95	-13.00	52.19	V
	148.8844	-58.01	-68.37	-10.36	-13.00	55.37	V
	477.8789	-68.79	-69.45	-0.66	-13.00	56.45	H
	3472.0000	-59.50	-46.32	13.18	-13.00	33.32	H
	5208.0000	-72.27	-54.05	18.22	-13.00	41.05	V
	6944.0000	-72.58	-50.53	22.05	-13.00	37.53	H
	8680.0000	-76.23	-54.26	21.97	-13.00	41.26	V
	10416.0000	-79.54	-54.52	25.02	-13.00	41.52	V
	12152.0000	-79.14	-54.07	25.07	-13.00	41.07	V
	13888.0000	-80.08	-53.60	26.48	-13.00	40.60	V
	15624.0000	-80.22	-50.57	29.65	-13.00	37.57	V
	17360.0000	-80.29	-45.77	34.52	-13.00	32.77	V
LTE_B5_10M_CH20600	110.5503	-60.78	-57.97	2.81	-13.00	44.97	V
	250.7854	-60.57	-58.54	2.03	-13.00	45.54	H
	1678.0000	-70.38	-54.56	15.82	-13.00	41.56	H
	2517.0000	-70.01	-47.88	22.13	-13.00	34.88	H
	3356.0000	-71.01	-57.95	13.06	-13.00	44.95	V
	4195.0000	-71.97	-56.52	15.45	-13.00	43.52	H

	5034.0000	-72.40	-54.41	17.99	-13.00	41.41	V
	5873.0000	-72.34	-52.93	19.41	-13.00	39.93	H
	6712.0000	-72.99	-51.80	21.19	-13.00	38.80	H
	7551.0000	-73.34	-49.54	23.80	-13.00	36.54	H
	8390.0000	-77.78	-55.10	22.68	-13.00	42.10	V
LTE_B7_20M_CH20850	111.5208	-60.94	-57.94	3.00	-25.00	32.94	V
	251.7559	-60.61	-58.43	2.18	-25.00	33.43	H
	881.1156	-59.24	-50.49	8.75	-25.00	25.49	H
	5002.0000	-72.63	-54.90	17.73	-25.00	29.90	V
	7503.0000	-72.77	-49.20	23.57	-25.00	24.20	V
	10004.0000	-71.56	-46.75	24.81	-25.00	21.75	V
	12505.0000	-79.06	-53.57	25.49	-25.00	28.57	V
	15006.0000	-80.00	-51.66	28.34	-25.00	26.66	V
	17507.0000	-79.35	-44.95	34.40	-25.00	19.95	V
LTE_B66_20M_CH132322	112.4912	-60.63	-58.03	2.60	-13.00	45.03	V
	250.7854	-60.73	-58.70	2.03	-13.00	45.70	H
	3472.0000	-59.17	-46.06	13.11	-13.00	33.06	V
	5208.0000	-72.62	-54.25	18.37	-13.00	41.25	H
	6944.0000	-72.79	-50.74	22.05	-13.00	37.74	H
	8680.0000	-72.52	-50.55	21.97	-13.00	37.55	V
	10416.0000	-78.90	-53.92	24.98	-13.00	40.92	V
	12152.0000	-78.89	-53.81	25.08	-13.00	40.81	V
	13888.0000	-79.63	-53.16	26.47	-13.00	40.16	V
	15624.0000	-79.98	-50.34	29.64	-13.00	37.34	V
	17360.0000	-79.62	-45.16	34.46	-13.00	32.16	V

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

(3)V=Vertical,H= Horizontal