



Report No.: SUCR260400030906

Page: 1 of 716

TEST REPORT

Application No.: SUCR2604000309MO
FCC ID: XMR2026FME172Q
Applicant: Quectel Wireless Solutions Co., Ltd.
Address of Applicant: No. 8 Waipojing Road, Sijing Town, Songjiang District, Shanghai 201601, China
Manufacturer: Quectel Wireless Solutions Co., Ltd.
Address of Manufacturer: No. 8 Waipojing Road, Sijing Town, Songjiang District, Shanghai 201601, China
Equipment Under Test (EUT):
EUT Name: Wi-Fi & Bluetooth Module
Model No.: FME172Q
Trade Mark: QUECTEL
Standard(s) : 47 CFR Part 15, Subpart E 15.407
Date of Receipt: 2026-04-03
Date of Test: 2026-06-09 to 2026-07-20
Date of Issue: 2026-07-20


Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Revision Record			
Version	Description	Date	Remark
00	Original	2026-07-20	/

Authorized for issue by:				
Prepared By				
		Nature_Shen/Project Engineer		
Approved By				
		Cedar Cheng /Reviewer		

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart E 15.407	N/A	47 CFR Part 15, Subpart C 15.203	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Radiated Emissions (Below 1GHz)	47 CFR Part 15, Subpart E 15.407	ANSI C63.10 (2020) Section 6.4,6.5	47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)	Pass
Radiated Emissions (Above 1GHz)		ANSI C63.10 (2020) Section 6.6 & 12.7	47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)	Pass
Radiated Emissions which fall in the restricted bands		ANSI C63.10 (2020) Section 6.10.5 & 12.7.2	47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)	Pass
In-Band Emissions		ANSI C63.10 (2020) Section 12.6	47 CFR Part 15, Subpart E 15.407 (b)	Pass
Contention Based Protocol		KDB 987594 D02 Section II.I.	47 CFR Part 15, Subpart E 15.407 (d)(6)	Pass
Duty Cycle		ANSI C63.10 (2020) Section 12.2	ANSI C63.10 (2020) Section 12.2	Pass
99% Bandwidth		ANSI C63.10 (2020) Section 12.5.3	ANSI C63.10 (2020) Section 12.5.3	Pass
26dB Emission Bandwidth		ANSI C63.10 (2020) Section 12.5.2	47 CFR Part 15, Subpart E 15.407 (a)	Pass
Maximum Conducted Output Power		ANSI C63.10 (2020) Section 12.4	47 CFR Part 15, Subpart E 15.407 (a)	Pass
Power Spectral Density		ANSI C63.10 (2020) Section 12.6	47 CFR Part 15, Subpart E 15.407 (a)	Pass

3 Contents

	Page
1 COVER PAGE	1
2 Test Summary	3
3 Contents.....	4
4 General Information.....	5
4.1 Details of E.U.T.	5
4.2 Environment Parameter	5
4.3 Description of Support Units	5
4.4 Measurement Uncertainty & Decision Rule	6
4.5 Test Location	7
4.6 Test Facility	7
4.7 Deviation from Standards.....	7
4.8 Abnormalities from Standard Conditions.....	7
5 Equipment List	8
6 Radio Spectrum Technical Requirement.....	10
6.1 Antenna Requirement	10
7 Radio Spectrum Matter Test Results	11
7.1 Radiated Emissions (Below 1GHz)	11
7.2 Radiated Emissions (Above 1GHz).....	15
7.3 Radiated Emissions which fall in the restricted bands	152
7.4 In-Band Emissions	202
7.5 Contention Based Protocol.....	204
7.6 Duty Cycle	205
7.7 99% Bandwidth	206
7.8 26dB Emission Bandwidth.....	207
7.9 Maximum Conducted Output Power	208
7.10 Power Spectral Density	210
8 Test Setup Photo	212
9 EUT Constructional Details (EUT Photos).....	212
10 Appendix.....	213

4 General Information

4.1 Details of E.U.T.

Software Version:	NA
Hardware Version:	R1.0
SN:	E1Y26A94M00005
Power supply:	3.3V
Antenna Type:	Dipole Antenna
FCC Classification:	6GHz Low Power Indoor Client (6XD)
Antenna Gain*:	5925 MHz to 7125 MHz: 1.60dBi(Ant0); 1.60dBi(Ant1);(Provided by the manufacturer)
IEEE 802.11 WLAN Mode Supported:	☒ 802.11a/ax(HE20)/be(HE20): (20 MHz channel bandwidth) ☒ 802.11ax(HE40) /be(HE40): (40 MHz channel bandwidth) ☒ 802.11ax(HE80)/be(HE80): (80 MHz channel bandwidth) ☒ 802.11ax(HE160)/be(HE160) (160 MHz channel bandwidth) ☒ 802.11be(HE320) (320 MHz channel bandwidth)
Operation Frequency:	5925 MHz ~ 6425 MHz 6425 MHz ~ 6525 MHz 6525 MHz ~ 6875 MHz 6875 MHz ~ 7125 MHz
Modulation Type:	802.11a: OFDM (BPSK, QPSK, 16QAM, 64QAM); 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024-QAM); 802.11be: OFDMA with enhancements (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024-QAM, 4096-QAM)
Note: 1. For 802.11ax/be modes, all test items were evaluated only for 802.11be under the operating condition with higher output power.	

4.2 Environment Parameter

Environment Parameter	Selected Values During Tests	
Relative Humidity	Ambient	
Value	Temperature(°C)	Voltage(V)
NTNV	25	3.3
Note: NV:Normal Voltage LV:Low Extreme Test Voltage HV:High Extreme Test Voltage NT:Normal Temperature LT:Low Extreme Test Temperature HT:High Extreme Test Temperature		

4.3 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Computer	Lenovo	T14	2YK6GR
Mouse	Lenovo	3D optical Mouse	N/A
Router	Smavwave Technology Co.,Ltd	SRT 421	RT421X02211300001

4.4 Measurement Uncertainty & Decision Rule

No.	Item	Measurement Uncertainty
1	Radio Frequency	$\pm 7.25 \times 10^{-8}$
2	Duty cycle	$\pm 0.37\%$
3	Occupied Bandwidth	$\pm 3\%$
4	Conduction emission	$\pm 3.0\text{dB}$ (150kHz to 30MHz)
5	RF conducted power	$\pm 0.75\text{dB}$
6	RF power density	$\pm 2.84\text{dB}$
7	Conducted Spurious emissions	$\pm 0.75\text{dB}$
8	RF Radiated power	$\pm 1.56\text{dB}$ (9KHz-30MHz)
		$\pm 4.80\text{dB}$ (30MHz-1GHz)
		$\pm 4.80\text{dB}$ (1GHz-18GHz)
		$\pm 4.80\text{dB}$ (18GHz-40GHz)
9	Temperature test	$\pm 1^\circ\text{C}$
10	Humidity test	$\pm 3\%$
11	Supply voltages	$\pm 1\%$
12	Time	$\pm 3\%$
Remark: The U_{lab} (lab Uncertainty) is less than $U_{\text{CISPR/ETSI}}$ (CISPR/ETSI Uncertainty), so the test results – compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit; – non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.		

4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu)
Pilot Free Trade Zone

No tests were sub-contracted.

Note:

1.SGS is not responsible for wrong test results due to incorrect information (e.g., max. internal working frequency, antenna gain, cable loss, etc) is provided by the applicant. (If applicable).

2.SGS is not responsible for the authenticity, integrity and the validity of the conclusion based on results of the data provided by applicant. (If applicable).

3. Sample source: sent by customer.

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 6336.01)**

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.is accredited by the American Association for Laboratory Accreditation (A2LA).

- **FCC (Designation Number: CN1312)**

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd. has been recognized as an accredited testing laboratory. Test Firm Registration Number:717327

- **ISED (CAB Identifier: CN0120)**

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd. has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory.

Company Number: 27594

4.7 Deviation from Standards

None

4.8 Abnormalities from Standard Conditions

None

5 Equipment List

Item	Equipment	Manufacturer	Model	Inventory No	Cal Date	Cal. Due Date
RF Conducted Test						
1	Signal Analyzer	ROHDE&SCHWARZ	FSW43	SUWI-01-02-04	1/14/2026	1/13/2027
2	Signal Analyzer	KEYSIGHT	N9020A	SUWI-01-02-15	11/21/2025	11/20/2026
3	MXG Vector signal genitor	KEYSIGHT	N5182B	SUWI-01-38-01	1/14/2026	1/13/2027
4	Signal Generator	ROHDE&SCHWARZ	SMW200A	SUWI-01-07-08	1/14/2026	1/13/2027
5	Signal Generator	ROHDE&SCHWARZ	SMW100A	SUWI-01-08-01	1/14/2026	1/13/2027
6	MXG Vector Signal Generator	ROHDE&SCHWARZ	SMR20	SUWI-01-33-01	11/21/2025	11/20/2026
7	Wideband Radio Communication Tester	ROHDE&SCHWARZ	CMW500	SUWI-01-16-13	4/22/2026	4/21/2027
8	Wideband Radio Communication Test Station	Anritsu	MT8000A	SUWI-01-34-02	11/21/2025	11/20/2026
9	Wideband Radio Communication Tester	Anritsu	MT8821C	SUWI-01-26-03	11/21/2025	11/20/2026
10	Power meter	Anritsu	ML2495A	SUWI-01-31-01	11/21/2025	11/20/2026
11	Pulse power sensor	Anritsu	MA2411B	SUWI-01-32-01	11/21/2025	11/20/2026
12	DC Power Supply	HYELEC	HY3005B	SUWI-01-18-01	1/14/2026	1/13/2027
13	Temperature and humidity meter	MingGao	TH101B	SUWI-01-01-07	2/11/2026	2/10/2027
14	Temperature Chamber	GIANT FORCE	ICT-017-40-SP-SD	SUWI-01-13-02	5/7/2026	5/6/2027
15	Measurement Software	TST	TST 272 V2.02	SUWI-03-55-03	NCR	NCR
16	RF Control unit	TST	TSCB3023R2	SUWI-02-20-01	NCR	NCR
17	RFCables	Tonscend	NA	SUWI-01-03-01	1/15/2026	1/14/2027
RF Radiated Test						
1	Semi-Anechoic Chamber	Brilliant-emc	N/A	SUWI-04-02-01	6/9/2026	6/8/2029
2	Signal Analyzer	ROHDE&SCHWARZ	FSW43	SUWI-01-02-04	1/14/2026	1/13/2027
3	Signal Analyzer	KEYSIGHT	N9020A	SUWI-01-02-07	11/20/2025	11/19/2026
4	Test receiver	ROHDE&SCHWARZ	ESR7	SUWI-01-10-01	1/14/2026	1/13/2027
5	Signal Generator	ROHDE&SCHWARZ	SMW100A	SUWI-01-18-01	1/14/2026	1/13/2027
6	Receiving antenna	SCHWRZBECK MESS-ELEKTRONIK	VULB 9168	SUWI-01-11-04	11/29/2025	11/28/2027
7	Receiving antenna	SCHWRZBECK MESS-ELEKTRONIK	BBHA 9120D	SUWI-01-11-02	5/7/2025	5/6/2027
8	Receiving antenna	SCHWRZBECK MESS-ELEKTRONIK	BBHA 9170	SUWI-01-11-03	5/7/2025	5/6/2027
9	Active Loop Antenna	SCHWRZBECK MESS-ELEKTRONIK	FMZB 1519B	SUWI-01-21-01	5/7/2025	5/6/2027
10	Amplifier	Tonscend	TAP9K3G40	SUWI-01-14-01	1/14/2026	1/13/2027
11	Amplifier	Tonscend	TAP01018050	SUWI-01-14-02	1/14/2026	1/13/2027

12	Amplifier	Tonscend	TAP18040048	SUWI-01-14-03	1/14/2026	1/13/2027
13	Wideband Radio Communication Tester	Anritsu	MT8820C	SUWI-01-26-01	8/25/2025	8/24/2026
14	Wideband Radio Communication Tester	Anritsu	MT8821C	SUWI-01-26-03	8/25/2025	8/24/2026
15	Wideband Radio Communication Tester	ROHDE&SCHWARZ	CMW500	SUWI-01-16-09	8/26/2025	8/25/2026
16	Radio Communication Analyzer	StarPoint	SP9500E	SUWI-01-28-06	11/21/2025	11/20/2026
17	Signal Generator	ROHDE&SCHWARZ	SMB100A	SUWI-01-08-01	1/14/2026	1/13/2027
18	DC Power Supply	HYELEC	HY3005B	SUWI-01-18-01	1/14/2026	1/13/2027
19	Temperature and humidity meter	MingGao	TH101B	SUWI-01-01-05	2/11/2026	2/10/2027
20	Measurement Software	Tonscend	JS32-RE 4.0.0.0	SUWI-02-09-06	NCR	NCR
21	RF Control unit	Tonscend	JS0806-1	SUWI-02-20-01	NCR	NCR
22	RFCables	Tonscend	NA	SUWI-01-03-02	NCR	NCR

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203

6.1.2 6.1.2 Conclusion

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna are Dipole Antenna and no consideration of replacement. The best case gain of the 5925 MHz to 7125 MHz:

Operation Frequency	ANT0 Gain (dBi)	ANT1 Gain (dBi)	Directional gain For Power (dBi)	Directional gain For PSD (dBi)	Power Limit Reduction (dBm)	PSD Limit Reduction (dBm)
5925 MHz to 7125 MHz	1.6	1.6	1.6	4.61	0	0

7 Radio Spectrum Matter Test Results

7.1 Radiated Emissions (Below 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)

Test Method: ANSI C63.10 (2020) Section 6.4,6.5

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 24 °C


Humidity: 43 % RH

Atmospheric Pressure: 1001 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	11	TX mode (U-NII-5) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Pre-scan	12	TX mode (U-NII-6) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Pre-scan	13	TX mode (U-NII-7) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Pre-scan	14	TX mode (U-NII-8) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.

7.1.3 Test Setup Diagram



7.1.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8m above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3m or 10m away from the interference-receiving antenna, which was mounted on the variable-height antenna tower.
- c. The antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1m to 4m (for the test frequency of below 30MHz, the antenna was tuned to heights 1m) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. At frequencies below 1GHz, measurements may be performed at a distance different to specified in the regulations.

Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor+ Aux Factor (if applicable)

The aux factor needs to be added when measurements are performed at a distance other than the limit distance provided.


EX. Below 30MHz, Aux Factor = 40 dB/decade of distance, the aux factor is $40\log(3/300) = -80\text{dB}$ (for 3m test distance).

EX. Above 30MHz, Aux Factor = 20 dB/decade of distance, the aux factor is $20\log(10/3) = 10.46\text{dB}$ (for 10m test distance).

2. Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

3. The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the worst-case test curve is displayed.


Test Mode: 11; Polarity: Horizontal



Final Data List

NO.	Frequency [MHz]	Reading [dBμV]	Factor [dB]	AF [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Polarity
1	31.455	51.21	-42.30	18.39	27.30	40.00	12.70	Horizontal
2	75.3475	50.23	-41.72	16.32	24.83	40.00	15.17	Horizontal
3	143.975	45.03	-40.89	19.21	23.34	43.50	20.16	Horizontal
4	324.88	44.63	-39.79	19.67	24.51	46.00	21.49	Horizontal
5	674.8075	34.12	-37.76	26.72	23.08	46.00	22.92	Horizontal
6	992.4825	32.67	-35.70	30.38	27.35	54.00	26.65	Horizontal

Test Mode: 11; Polarity: Vertical



Final Data List								
NO.	Frequency [MHz]	Reading [dBμV]	Factor [dB]	AF [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Polarity
1	32.6675	51.41	-42.29	18.37	27.49	40.00	12.51	Vertical
2	69.5275	51.15	-41.84	17.39	26.71	40.00	13.29	Vertical
3	96.6875	51.22	-41.43	14.06	23.85	43.50	19.65	Vertical
4	173.075	40.13	-40.66	18.59	18.06	43.50	25.44	Vertical
5	334.58	41.18	-39.77	20.58	22.00	46.00	24.00	Vertical
6	969.6875	33.46	-35.59	29.68	27.55	54.00	26.45	Vertical

7.2 Radiated Emissions (Above 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)

Test Method: ANSI C63.10 (2020) Section 6.6 & 12.7

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

*(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(4) For transmitters operating in the 5.725-5.85 GHz band:

(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Remark:

1. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

2. Above 18GHz, measurements may be performed at a distance shorter than that specified in the regulations

Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor+ Aux Factor (if applicable)

The aux factor needs to be added when measurements are performed at a distance other than the limit distance provided.

EX. Above 18GHz, Aux Factor = 20 dB/decade of distance, the aux factor is $20\log(1/3) = -9.54\text{dB}$ (for 1m test distance).

7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 24 °C


Humidity: 43 % RH

Atmospheric Pressure: 1001 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	11	TX mode (U-NII-5) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	12	TX mode (U-NII-6) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	13	TX mode (U-NII-7) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	14	TX mode (U-NII-8) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.

7.2.3 Test Setup Diagram




7.2.4 Measurement Procedure and Data

- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:


1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 1GHz to 40GHz, The points marked on below plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
4. The disturbance above 18GHz were very low and the below harmonics were the highest point could be found when testing, so only the below harmonics had been displayed.
5. For devices with multiple operating modes, measurements on the middle channel is used to determine the worst-case mode(s). Only the worst case mode with the highest output power and the mode with the highest output power spectral density for each modulation family (e.g., OFDM and direct sequence spread spectrum) is recorded in the test report.
6. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.
7. For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle<98%) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.

11a_TX_CH_001_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7995.5	43.56	36.30	-18.10	61.76	88.30	26.54	Horizontal
2	8850.6667	52.89	37.24	-43.17	46.96	88.30	41.34	Horizontal
3	10300.666	48.95	39.01	-41.36	46.60	88.30	41.70	Horizontal
4	11464	48.33	39.45	-39.78	48.01	74.00	25.99	Horizontal
5	14343	46.34	40.27	-38.60	48.01	88.30	40.29	Horizontal
6	17998.666	42.30	44.79	-36.78	50.31	74.00	23.69	Horizontal
7	17916	33.59	44.30	-36.95	40.94	54.00	13.06	Horizontal

11a_TX_CH_001_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7907	43.18	36.32	-17.77	61.73	88.30	26.57	Vertical
2	8753.6667	52.81	37.13	-43.57	46.36	88.30	41.94	Vertical
3	10331	48.12	39.03	-41.27	45.88	88.30	42.42	Vertical
4	12464.333	46.79	39.12	-39.52	46.39	74.00	27.61	Vertical
5	14812.333	43.46	40.22	-37.79	45.89	88.30	42.41	Vertical
6	17917	43.81	44.30	-36.95	51.17	74.00	22.83	Vertical
7	17923.333	33.77	44.34	-36.93	41.18	54.00	12.82	Vertical

11a_TX_CH_045_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7909	43.14	36.32	-17.77	61.68	88.30	26.62	Horizontal
2	8860.6667	52.37	37.25	-43.14	46.48	88.30	41.82	Horizontal
3	10812.666	48.26	39.37	-40.60	47.03	74.00	26.97	Horizontal
4	12476.333	47.35	39.11	-39.57	46.89	74.00	27.11	Horizontal
5	14942.666	45.22	40.21	-37.76	47.66	88.30	40.64	Horizontal
6	17975.333	41.93	44.65	-36.83	49.75	74.00	24.25	Horizontal
7	17918.333	33.45	44.31	-36.94	40.82	54.00	13.18	Horizontal

11a_TX_CH_045_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7889.5	42.66	36.32	-17.70	61.28	88.30	27.02	Vertical
2	8851.6667	52.14	37.24	-43.17	46.21	88.30	42.09	Vertical
3	10042.666	49.03	38.83	-41.63	46.23	88.30	42.07	Vertical
4	11555	47.41	39.44	-39.88	46.97	74.00	27.03	Vertical
5	14403	45.99	40.26	-38.67	47.58	88.30	40.72	Vertical
6	17981	42.39	44.69	-36.82	50.26	74.00	23.74	Vertical
7	17913.666	33.94	44.28	-36.95	41.27	54.00	12.73	Vertical

11a_TX_CH_049_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7845	42.82	36.33	-17.53	61.63	88.30	26.67	Horizontal
2	8882.6667	52.75	37.27	-43.08	46.94	88.30	41.36	Horizontal
3	10759.666	48.05	39.33	-40.76	46.62	74.00	27.38	Horizontal
4	13485	46.61	39.53	-39.32	46.82	88.30	41.48	Horizontal
5	15695.333	44.05	38.95	-37.70	45.30	74.00	28.70	Horizontal
6	17928.666	43.05	44.37	-36.92	50.50	74.00	23.50	Horizontal
7	17979.333	32.93	44.68	-36.82	40.78	54.00	13.22	Horizontal

11a_TX_CH_049_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7906	43.75	36.32	-17.76	62.31	88.30	25.99	Vertical
2	8892	52.63	37.28	-43.05	46.86	88.30	41.44	Vertical
3	10016.666	49.14	38.81	-41.64	46.32	88.30	41.98	Vertical
4	11975.666	47.28	39.40	-39.48	47.20	74.00	26.80	Vertical
5	14398	45.77	40.26	-38.67	47.36	88.30	40.94	Vertical
6	17872.333	43.65	44.03	-37.21	50.47	74.00	23.53	Vertical
7	17921.666	33.07	44.33	-36.94	40.46	54.00	13.54	Vertical

11a_TX_CH_093_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7878.5	42.77	36.32	-17.66	61.44	88.30	26.86	Horizontal
2	8551.3333	52.57	36.91	-43.83	45.65	88.30	42.65	Horizontal
3	10314	48.65	39.02	-41.32	46.35	88.30	41.95	Horizontal
4	12641.666	46.92	39.01	-39.09	46.85	74.00	27.15	Horizontal
5	14915	45.65	40.21	-37.64	48.21	88.30	40.09	Horizontal
6	17969.666	41.96	44.62	-36.84	49.74	74.00	24.26	Horizontal
7	17979	32.77	44.67	-36.82	40.62	54.00	13.38	Horizontal

11a_TX_CH_093_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7938.5	44.46	36.31	-17.89	62.89	88.30	25.41	Vertical
2	8873.3333	52.82	37.26	-43.10	46.98	88.30	41.32	Vertical
3	10033	49.24	38.82	-41.63	46.43	88.30	41.87	Vertical
4	11974.333	47.61	39.40	-39.49	47.52	74.00	26.48	Vertical
5	14788.666	44.15	40.22	-37.86	46.52	88.30	41.78	Vertical
6	17980.333	42.44	44.68	-36.82	50.30	74.00	23.70	Vertical
7	17980.666	33.01	44.68	-36.82	40.88	54.00	13.12	Vertical

11a_TX_CH_097_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7905	42.56	36.32	-17.76	61.12	88.30	27.18	Horizontal
2	8892	51.99	37.28	-43.05	46.22	88.30	42.08	Horizontal
3	10739.666	49.17	39.32	-40.81	47.67	74.00	26.33	Horizontal
4	12368.333	47.27	39.18	-39.33	47.12	74.00	26.88	Horizontal
5	14914.333	44.74	40.21	-37.64	47.31	88.30	40.99	Horizontal
6	17922.333	42.44	44.33	-36.94	49.84	74.00	24.16	Horizontal
7	17909.333	33.40	44.26	-36.96	40.69	54.00	13.31	Horizontal

11a_TX_CH_097_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7953.5	42.40	36.31	-17.94	60.77	88.30	27.53	Vertical
2	8851.3333	52.16	37.24	-43.17	46.23	88.30	42.07	Vertical
3	10783	47.71	39.35	-40.69	46.37	74.00	27.63	Vertical
4	12692.666	46.86	38.98	-39.13	46.71	74.00	27.29	Vertical
5	14847.333	43.60	40.22	-37.71	46.11	88.30	42.19	Vertical
6	17891.333	42.21	44.15	-37.05	49.31	74.00	24.69	Vertical
7	17916	32.65	44.30	-36.95	40.00	54.00	14.00	Vertical

11a_TX_CH_105_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7837	43.19	36.33	-17.49	62.03	88.30	26.27	Horizontal
2	9395	51.64	37.95	-42.87	46.72	74.00	27.28	Horizontal
3	11241.666	47.53	39.48	-40.25	46.76	74.00	27.24	Horizontal
4	13098.666	45.65	38.95	-38.21	46.39	88.30	41.91	Horizontal
5	16304.666	44.19	38.52	-37.53	45.19	88.30	43.11	Horizontal
6	17983.666	42.37	44.70	-36.81	50.26	74.00	23.74	Horizontal
7	17990	32.30	44.74	-36.80	40.24	54.00	13.76	Horizontal

11a_TX_CH_105_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7909.5	42.67	36.32	-17.78	61.21	88.30	27.09	Vertical
2	8837.6667	52.63	37.22	-43.20	46.65	88.30	41.65	Vertical
3	10074	48.98	38.85	-41.63	46.21	88.30	42.09	Vertical
4	12024	47.50	39.39	-39.42	47.47	74.00	26.53	Vertical
5	14352.333	45.84	40.26	-38.61	47.50	88.30	40.80	Vertical
6	17926.333	43.17	44.36	-36.93	50.60	74.00	23.40	Vertical
7	17876.666	33.94	44.06	-37.17	40.83	54.00	13.17	Vertical

11a_TX_CH_113_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7920	43.81	36.32	-17.82	62.31	88.30	25.99	Horizontal
2	9438.3333	51.98	38.01	-42.66	47.33	74.00	26.67	Horizontal
3	11368.333	47.64	39.46	-39.89	47.21	74.00	26.79	Horizontal
4	13484.333	45.95	39.53	-39.32	46.16	88.30	42.14	Horizontal
5	15759.666	44.18	38.83	-37.49	45.53	74.00	28.47	Horizontal
6	17872.666	42.71	44.04	-37.21	49.54	74.00	24.46	Horizontal
7	17912.666	33.30	44.28	-36.95	40.62	54.00	13.38	Horizontal

11a_TX_CH_113_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7926.5	43.03	36.31	-17.84	61.50	88.30	26.80	Vertical
2	8875.3333	52.50	37.26	-43.10	46.66	88.30	41.64	Vertical
3	10650	48.20	39.26	-40.96	46.49	74.00	27.51	Vertical
4	12420.666	46.50	39.15	-39.34	46.31	74.00	27.69	Vertical
5	14949	45.42	40.21	-37.79	47.83	88.30	40.47	Vertical
6	17915.666	42.35	44.29	-36.95	49.70	74.00	24.30	Vertical
7	17926.333	32.74	44.36	-36.93	40.17	54.00	13.83	Vertical

11a_TX_CH_117_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7860.5	43.15	36.33	-17.59	61.89	88.30	26.41	Horizontal
2	8873	52.93	37.26	-43.11	47.08	88.30	41.22	Horizontal
3	10285.666	48.93	39.00	-41.45	46.48	88.30	41.82	Horizontal
4	11819	46.28	39.42	-39.80	45.90	74.00	28.10	Horizontal
5	14387	45.58	40.26	-38.65	47.19	88.30	41.11	Horizontal
6	17978.666	41.59	44.67	-36.82	49.44	74.00	24.56	Horizontal
7	17918	32.91	44.31	-36.94	40.27	54.00	13.73	Horizontal

11a_TX_CH_117_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7985.5	43.12	36.30	-18.06	61.36	88.30	26.94	Vertical
2	8801.6667	53.10	37.18	-43.31	46.98	88.30	41.32	Vertical
3	11200.333	47.20	39.48	-40.52	46.16	74.00	27.84	Vertical
4	13331.666	46.28	39.30	-38.89	46.69	74.00	27.31	Vertical
5	15820	43.37	38.72	-37.46	44.63	74.00	29.37	Vertical
6	17923	42.15	44.34	-36.93	49.55	74.00	24.45	Vertical
7	17871.666	33.51	44.03	-37.22	40.32	54.00	13.68	Vertical

11a_TX_CH_149_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7968	42.69	36.31	-18.00	61.00	88.30	27.30	Horizontal
2	9284.6667	49.68	37.80	-42.62	44.85	88.30	43.45	Horizontal
3	10734.666	47.97	39.31	-40.83	46.45	74.00	27.55	Horizontal
4	13019	46.55	38.83	-39.15	46.23	88.30	42.07	Horizontal
5	14822	44.26	40.22	-37.77	46.71	88.30	41.59	Horizontal
6	17918	42.05	44.31	-36.94	49.41	74.00	24.59	Horizontal
7	17872.333	33.21	44.03	-37.21	40.03	54.00	13.97	Horizontal

11a_TX_CH_149_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7928	43.14	36.31	-17.85	61.61	88.30	26.69	Vertical
2	8848.3333	52.34	37.23	-43.17	46.40	88.30	41.90	Vertical
3	10307.333	47.62	39.02	-41.34	45.30	88.30	43.00	Vertical
4	12154.666	46.49	39.31	-39.64	46.16	74.00	27.84	Vertical
5	14502.666	45.08	40.25	-38.68	46.65	88.30	41.65	Vertical
6	17914.666	42.80	44.29	-36.95	50.14	74.00	23.86	Vertical
7	17987	32.54	44.72	-36.81	40.46	54.00	13.54	Vertical

11a_TX_CH_181_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7910	43.42	36.32	-17.78	61.96	88.30	26.34	Horizontal
2	8809	52.87	37.19	-43.28	46.78	88.30	41.52	Horizontal
3	10551.333	48.61	39.19	-41.14	46.66	88.30	41.64	Horizontal
4	12796	47.05	38.92	-39.07	46.90	88.30	41.40	Horizontal
5	14943	45.11	40.21	-37.76	47.55	88.30	40.75	Horizontal
6	17949.666	42.28	44.50	-36.88	49.90	74.00	24.10	Horizontal
7	17990.333	32.26	44.74	-36.80	40.20	54.00	13.80	Horizontal

11a_TX_CH_181_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7905.5	42.78	36.32	-17.76	61.34	88.30	26.96	Vertical
2	8862	51.97	37.25	-43.14	46.08	88.30	42.22	Vertical
3	10784	48.64	39.35	-40.69	47.30	74.00	26.70	Vertical
4	12366	47.19	39.18	-39.33	47.04	74.00	26.96	Vertical
5	14408.333	44.86	40.26	-38.67	46.45	88.30	41.85	Vertical
6	17918.666	42.30	44.31	-36.94	49.67	74.00	24.33	Vertical
7	17930	33.03	44.38	-36.92	40.49	54.00	13.51	Vertical

11a_TX_CH_185_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7898	43.59	36.32	-17.73	62.18	88.30	26.12	Horizontal
2	8804.6667	52.76	37.19	-43.30	46.65	88.30	41.65	Horizontal
3	10492	48.51	39.14	-41.26	46.39	88.30	41.91	Horizontal
4	12570	46.58	39.06	-39.24	46.40	74.00	27.60	Horizontal
5	14942	44.63	40.21	-37.76	47.08	88.30	41.22	Horizontal
6	17916	42.32	44.30	-36.95	49.67	74.00	24.33	Horizontal
7	17820	33.00	43.72	-37.64	39.08	54.00	14.92	Horizontal

11a_TX_CH_185_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7997.5	42.40	36.30	-18.11	60.59	88.30	27.71	Vertical
2	8857.3333	52.85	37.24	-43.15	46.94	88.30	41.36	Vertical
3	10785	46.93	39.35	-40.68	45.60	74.00	28.40	Vertical
4	12143	46.53	39.31	-39.62	46.22	74.00	27.78	Vertical
5	14439.333	45.70	40.26	-38.68	47.28	88.30	41.02	Vertical
6	17910.666	41.85	44.26	-36.96	49.16	74.00	24.84	Vertical
7	17903.666	33.18	44.22	-36.97	40.43	54.00	13.57	Vertical

11a_TX_CH_189_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7896.5	42.54	36.32	-17.73	61.13	88.30	27.17	Horizontal
2	8851.3333	52.63	37.24	-43.17	46.70	88.30	41.60	Horizontal
3	9899.6667	49.44	38.66	-41.75	46.35	88.30	41.95	Horizontal
4	12032.333	48.73	39.38	-39.43	48.68	74.00	25.32	Horizontal
5	13883.666	44.24	40.13	-38.82	45.55	88.30	42.75	Horizontal
6	17930.333	42.45	44.38	-36.92	49.91	74.00	24.09	Horizontal
7	17867	34.13	44.00	-37.25	40.88	54.00	13.12	Horizontal

11a_TX_CH_189_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7990.5	41.53	36.30	-18.08	59.75	88.30	28.55	Vertical
2	8890.3333	52.82	37.28	-43.06	47.04	88.30	41.26	Vertical
3	10387.333	47.31	39.07	-41.11	45.27	88.30	43.03	Vertical
4	12306	46.52	39.22	-39.48	46.26	74.00	27.74	Vertical
5	14793.333	45.22	40.22	-37.84	47.60	88.30	40.70	Vertical
6	17486	43.14	41.72	-36.85	48.00	88.30	40.30	Vertical
7	17928.666	33.36	44.37	-36.92	40.81	54.00	13.19	Vertical

11a_TX_CH_209_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7920.5	42.74	36.32	-17.82	61.24	88.30	27.06	Horizontal
2	8900.3333	52.07	37.29	-43.03	46.33	88.30	41.97	Horizontal
3	11128	47.36	39.49	-40.40	46.45	74.00	27.55	Horizontal
4	13158.333	45.62	39.04	-38.62	46.04	88.30	42.26	Horizontal
5	15693	43.79	38.95	-37.70	45.04	74.00	28.96	Horizontal
6	17913.333	42.42	44.28	-36.95	49.75	74.00	24.25	Horizontal
7	17973	32.70	44.64	-36.83	40.50	54.00	13.50	Horizontal

11a_TX_CH_209_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7952	42.98	36.31	-17.94	61.35	88.30	26.95	Vertical
2	8786.6667	52.89	37.17	-43.39	46.67	88.30	41.63	Vertical
3	10549	48.31	39.18	-41.14	46.35	88.30	41.95	Vertical
4	12768.333	46.30	38.94	-39.09	46.15	88.30	42.15	Vertical
5	14440.333	45.30	40.26	-38.68	46.88	88.30	41.42	Vertical
6	17994.666	41.64	44.77	-36.79	49.62	74.00	24.38	Vertical
7	17925.333	33.08	44.35	-36.93	40.50	54.00	13.50	Vertical

11a_TX_CH_233_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7872	42.71	36.33	-17.63	61.40	88.30	26.90	Horizontal
2	8687.3333	52.75	37.06	-43.85	45.96	88.30	42.34	Horizontal
3	10277	48.80	38.99	-41.50	46.30	88.30	42.00	Horizontal
4	11950.666	47.29	39.40	-39.60	47.10	74.00	26.90	Horizontal
5	14509.333	44.85	40.25	-38.65	46.45	88.30	41.85	Horizontal
6	17713	43.05	43.08	-37.85	48.27	74.00	25.73	Horizontal
7	17984.333	32.74	44.71	-36.81	40.63	54.00	13.37	Horizontal

11a_TX_CH_233_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7874	43.75	36.33	-17.64	62.44	88.30	25.86	Vertical
2	8811.3333	52.04	37.19	-43.28	45.95	88.30	42.35	Vertical
3	10884.333	47.48	39.42	-40.38	46.52	74.00	27.48	Vertical
4	12545.666	46.64	39.07	-39.39	46.33	74.00	27.67	Vertical
5	14376	45.00	40.26	-38.64	46.62	88.30	41.68	Vertical
6	17869	43.49	44.01	-37.24	50.27	74.00	23.73	Vertical
7	17913.333	33.01	44.28	-36.95	40.34	54.00	13.66	Vertical

11be(EHT20)_TX_CH_001_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7915	43.16	36.32	-17.80	61.68	88.30	26.62	Horizontal
2	8828.3333	52.20	37.21	-43.23	46.18	88.30	42.12	Horizontal
3	10158	48.59	38.91	-41.82	45.68	88.30	42.62	Horizontal
4	12370.666	47.17	39.18	-39.32	47.03	74.00	26.97	Horizontal
5	14617	44.24	40.24	-38.21	46.27	88.30	42.03	Horizontal
6	17915.333	42.91	44.29	-36.95	50.25	74.00	23.75	Horizontal
7	17988	32.72	44.73	-36.80	40.64	54.00	13.36	Horizontal

11be(EHT20)_TX_CH_001_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7805	43.29	36.34	-17.37	62.26	88.30	26.04	Vertical
2	8814.6667	52.17	37.20	-43.27	46.10	88.30	42.20	Vertical
3	10094.333	48.05	38.87	-41.62	45.29	88.30	43.01	Vertical
4	12003.333	46.38	39.40	-39.38	46.40	74.00	27.60	Vertical
5	14291.666	45.72	40.27	-38.52	47.47	88.30	40.83	Vertical
6	17983.666	41.85	44.70	-36.81	49.74	74.00	24.26	Vertical
7	17917.666	33.13	44.31	-36.94	40.49	54.00	13.51	Vertical

11be(EHT20)_TX_CH_045_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7915	43.24	36.32	-17.80	61.76	88.30	26.54	Horizontal
2	8841.3333	53.05	37.23	-43.19	47.08	88.30	41.22	Horizontal
3	10410.666	48.08	39.09	-41.09	46.08	88.30	42.22	Horizontal
4	12952.333	46.63	38.83	-39.39	46.07	88.30	42.23	Horizontal
5	14481	44.57	40.25	-38.69	46.14	74.00	27.86	Horizontal
6	17914.333	42.95	44.29	-36.95	50.28	74.00	23.72	Horizontal
7	17912	32.80	44.27	-36.96	40.12	54.00	13.88	Horizontal

11be(EHT20)_TX_CH_045_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7889.5	42.65	36.32	-17.70	61.27	88.30	27.03	Vertical
2	8853.3333	52.43	37.24	-43.16	46.51	88.30	41.79	Vertical
3	10068.333	48.63	38.85	-41.63	45.85	88.30	42.45	Vertical
4	12028.666	47.28	39.38	-39.42	47.24	74.00	26.76	Vertical
5	14366	45.79	40.26	-38.63	47.43	88.30	40.87	Vertical
6	17923.666	42.92	44.34	-36.93	50.33	74.00	23.67	Vertical
7	17913	33.05	44.28	-36.95	40.37	54.00	13.63	Vertical

11be(EHT20)_TX_CH_049_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7870.5	42.80	36.33	-17.62	61.50	88.30	26.80	Horizontal
2	8833	52.34	37.22	-43.22	46.34	88.30	41.96	Horizontal
3	10090.666	48.69	38.86	-41.62	45.93	88.30	42.37	Horizontal
4	11507.333	46.62	39.45	-39.73	46.34	74.00	27.66	Horizontal
5	13725.666	45.29	39.89	-38.48	46.69	88.30	41.61	Horizontal
6	17906	42.00	44.24	-36.97	49.27	74.00	24.73	Horizontal
7	17920.666	33.26	44.32	-36.94	40.65	54.00	13.35	Horizontal

11be(EHT20)_TX_CH_049_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7875	43.95	36.33	-17.64	62.63	88.30	25.67	Vertical
2	8897.6667	52.44	37.29	-43.04	46.69	88.30	41.61	Vertical
3	10820.666	48.30	39.37	-40.58	47.10	74.00	26.90	Vertical
4	12443	45.80	39.13	-39.43	45.50	74.00	28.50	Vertical
5	14837	43.73	40.22	-37.73	46.22	88.30	42.08	Vertical
6	17925	41.91	44.35	-36.93	49.33	74.00	24.67	Vertical
7	17989.333	32.51	44.74	-36.80	40.44	54.00	13.56	Vertical

11be(EHT20)_TX_CH_093_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7899.5	42.40	36.32	-17.74	60.98	88.30	27.32	Horizontal
2	8826.3333	53.05	37.21	-43.24	47.02	88.30	41.28	Horizontal
3	10321	48.39	39.02	-41.30	46.12	88.30	42.18	Horizontal
4	13371	45.72	39.36	-39.12	45.96	74.00	28.04	Horizontal
5	15080.333	43.79	40.06	-38.10	45.75	88.30	42.55	Horizontal
6	17973.333	41.63	44.64	-36.83	49.44	74.00	24.56	Horizontal
7	17913.333	33.26	44.28	-36.95	40.59	54.00	13.41	Horizontal

11be(EHT20)_TX_CH_093_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7926	43.14	36.31	-17.84	61.62	88.30	26.68	Vertical
2	8942	51.91	37.34	-43.22	46.03	88.30	42.27	Vertical
3	10825.666	47.35	39.38	-40.56	46.17	74.00	27.83	Vertical
4	12530.333	46.64	39.08	-39.48	46.24	74.00	27.76	Vertical
5	14941.333	45.18	40.21	-37.76	47.63	88.30	40.67	Vertical
6	17980	41.33	44.68	-36.82	49.19	74.00	24.81	Vertical
7	17868.333	33.24	44.01	-37.24	40.01	54.00	13.99	Vertical

11be(EHT20)_TX_CH_097_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7899.5	43.06	36.32	-17.74	61.64	88.30	26.66	Horizontal
2	8906	53.36	37.30	-43.06	47.60	88.30	40.70	Horizontal
3	10303.666	48.60	39.01	-41.35	46.26	88.30	42.04	Horizontal
4	12768	46.59	38.94	-39.09	46.44	88.30	41.86	Horizontal
5	15073.333	43.93	40.07	-38.09	45.91	88.30	42.39	Horizontal
6	17925	42.55	44.35	-36.93	49.97	74.00	24.03	Horizontal
7	17917.666	33.99	44.31	-36.94	41.35	54.00	12.65	Horizontal

11be(EHT20)_TX_CH_097_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7840.5	42.82	36.33	-17.51	61.64	88.30	26.66	Vertical
2	8855	52.17	37.24	-43.16	46.25	88.30	42.05	Vertical
3	10603.666	47.99	39.22	-41.00	46.22	74.00	27.78	Vertical
4	12776.666	46.51	38.93	-39.09	46.36	88.30	41.94	Vertical
5	14940	44.52	40.21	-37.75	46.97	88.30	41.33	Vertical
6	17937.666	42.07	44.43	-36.90	49.59	74.00	24.41	Vertical
7	17918.333	33.57	44.31	-36.94	40.94	54.00	13.06	Vertical

11be(EHT20)_TX_CH_105_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7864	42.93	36.33	-17.60	61.66	88.30	26.64	Horizontal
2	8868	52.66	37.25	-43.12	46.80	88.30	41.50	Horizontal
3	10601.333	47.32	39.22	-41.00	45.54	74.00	28.46	Horizontal
4	12117.333	46.57	39.33	-39.58	46.32	74.00	27.68	Horizontal
5	14290.333	46.52	40.27	-38.51	48.28	88.30	40.02	Horizontal
6	17919.666	41.99	44.32	-36.94	49.37	74.00	24.63	Horizontal
7	17920.333	33.13	44.32	-36.94	40.51	54.00	13.49	Horizontal

11be(EHT20)_TX_CH_105_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7916.5	42.53	36.32	-17.80	61.04	88.30	27.26	Vertical
2	8670	52.35	37.04	-43.81	45.58	88.30	42.72	Vertical
3	10678	47.49	39.27	-40.95	45.82	74.00	28.18	Vertical
4	12406.666	46.05	39.16	-39.28	45.93	74.00	28.07	Vertical
5	14901.666	43.89	40.21	-37.59	46.51	88.30	41.79	Vertical
6	17925	42.63	44.35	-36.93	50.05	74.00	23.95	Vertical
7	17912.666	33.38	44.28	-36.95	40.70	54.00	13.30	Vertical

11be(EHT20)_TX_CH_113_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7910	44.04	36.32	-17.78	62.58	88.30	25.72	Horizontal
2	8849	52.97	37.23	-43.17	47.03	88.30	41.27	Horizontal
3	10014.333	49.19	38.81	-41.64	46.36	88.30	41.94	Horizontal
4	11781.333	46.18	39.42	-39.74	45.87	74.00	28.13	Horizontal
5	14406.666	44.64	40.26	-38.67	46.23	88.30	42.07	Horizontal
6	17928	42.22	44.37	-36.92	49.66	74.00	24.34	Horizontal
7	17977	32.67	44.66	-36.83	40.51	54.00	13.49	Horizontal

11be(EHT20)_TX_CH_113_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7900.5	43.24	36.32	-17.74	61.82	88.30	26.48	Vertical
2	8856	51.93	37.24	-43.15	46.02	88.30	42.28	Vertical
3	10954	47.64	39.47	-40.32	46.78	74.00	27.22	Vertical
4	13363	46.17	39.34	-39.07	46.44	74.00	27.56	Vertical
5	14879.666	44.81	40.21	-37.63	47.39	88.30	40.91	Vertical
6	17913.333	43.90	44.28	-36.95	51.23	74.00	22.77	Vertical
7	17922	33.37	44.33	-36.94	40.77	54.00	13.23	Vertical

11be(EHT20)_TX_CH_117_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7867.5	43.16	36.33	-17.61	61.87	88.30	26.43	Horizontal
2	8345.6667	53.02	36.68	-44.06	45.64	74.00	28.36	Horizontal
3	9488.6667	51.51	38.08	-42.37	47.23	74.00	26.77	Horizontal
4	11335	47.16	39.47	-39.88	46.75	74.00	27.25	Horizontal
5	14463.333	44.89	40.25	-38.68	46.46	88.30	41.84	Horizontal
6	17910.333	42.45	44.26	-36.96	49.75	74.00	24.25	Horizontal
7	17926.666	33.27	44.36	-36.93	40.70	54.00	13.30	Horizontal

11be(EHT20)_TX_CH_117_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7998	42.11	36.30	-18.11	60.30	88.30	28.00	Vertical
2	8957.6667	51.31	37.35	-43.29	45.37	88.30	42.93	Vertical
3	11108	46.76	39.49	-40.36	45.89	74.00	28.11	Vertical
4	12787	47.62	38.93	-39.08	47.47	88.30	40.83	Vertical
5	15246.666	43.74	39.76	-37.67	45.82	88.30	42.48	Vertical
6	17934.333	42.06	44.41	-36.91	49.55	74.00	24.45	Vertical
7	17915.666	33.23	44.29	-36.95	40.58	54.00	13.42	Vertical

11be(EHT20)_TX_CH_149_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7959	42.62	36.31	-17.96	60.96	88.30	27.34	Horizontal
2	8794.6667	52.70	37.17	-43.34	46.53	88.30	41.77	Horizontal
3	10101.666	48.62	38.87	-41.63	45.87	88.30	42.43	Horizontal
4	12014	46.54	39.39	-39.40	46.53	74.00	27.47	Horizontal
5	13498.333	45.95	39.55	-39.32	46.18	88.30	42.12	Horizontal
6	17918.333	42.40	44.31	-36.94	49.77	74.00	24.23	Horizontal
7	17873.666	33.27	44.04	-37.20	40.11	54.00	13.89	Horizontal

11be(EHT20)_TX_CH_149_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7846	42.70	36.33	-17.53	61.50	88.30	26.80	Vertical
2	9150.6667	49.82	37.61	-43.09	44.34	74.00	29.66	Vertical
3	10438.666	48.29	39.11	-41.15	46.25	88.30	42.05	Vertical
4	12781	46.97	38.93	-39.08	46.82	88.30	41.48	Vertical
5	14843	44.28	40.22	-37.72	46.78	88.30	41.52	Vertical
6	17925.333	42.48	44.35	-36.93	49.90	74.00	24.10	Vertical
7	17977.666	32.54	44.67	-36.82	40.38	54.00	13.62	Vertical

11be(EHT20)_TX_CH_181_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7908.5	42.95	36.32	-17.77	61.50	88.30	26.80	Horizontal
2	8891.3333	52.23	37.28	-43.05	46.46	88.30	41.84	Horizontal
3	10717.333	47.63	39.30	-40.88	46.05	74.00	27.95	Horizontal
4	12774.666	46.59	38.94	-39.09	46.44	88.30	41.86	Horizontal
5	15124.333	43.74	39.98	-38.04	45.67	88.30	42.63	Horizontal
6	17914.333	42.49	44.29	-36.95	49.82	74.00	24.18	Horizontal
7	17914.333	33.58	44.29	-36.95	40.91	54.00	13.09	Horizontal

11be(EHT20)_TX_CH_181_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7912	42.86	36.32	-17.79	61.39	88.30	26.91	Vertical
2	8886.6667	51.63	37.28	-43.07	45.84	88.30	42.46	Vertical
3	10706	47.17	39.29	-40.91	45.55	74.00	28.45	Vertical
4	12714.333	46.34	38.97	-39.13	46.18	88.30	42.12	Vertical
5	14363.666	45.49	40.26	-38.62	47.13	88.30	41.17	Vertical
6	17976.333	41.91	44.66	-36.83	49.74	74.00	24.26	Vertical
7	17918	32.90	44.31	-36.94	40.26	54.00	13.74	Vertical

11be(EHT20)_TX_CH_185_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7972.5	42.67	36.31	-18.02	60.96	88.30	27.34	Horizontal
2	8885	52.26	37.27	-43.07	46.46	88.30	41.84	Horizontal
3	10242	48.60	38.97	-41.71	45.86	88.30	42.44	Horizontal
4	12351.666	46.19	39.19	-39.37	46.01	74.00	27.99	Horizontal
5	14389.333	45.60	40.26	-38.66	47.20	88.30	41.10	Horizontal
6	17877.333	42.47	44.06	-37.17	49.37	74.00	24.63	Horizontal
7	17912	33.17	44.27	-36.96	40.49	54.00	13.51	Horizontal

11be(EHT20)_TX_CH_185_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7991	42.46	36.30	-18.09	60.68	88.30	27.62	Vertical
2	8809.3333	52.14	37.19	-43.28	46.05	88.30	42.25	Vertical
3	10420.333	48.31	39.09	-41.11	46.29	88.30	42.01	Vertical
4	13349.666	45.50	39.32	-38.99	45.83	74.00	28.17	Vertical
5	14936	44.93	40.21	-37.73	47.40	88.30	40.90	Vertical
6	17918.666	43.00	44.31	-36.94	50.37	74.00	23.63	Vertical
7	17958.666	32.34	44.55	-36.86	40.03	54.00	13.97	Vertical

11be(EHT20)_TX_CH_189_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7892	43.23	36.32	-17.71	61.84	88.30	26.46	Horizontal
2	8595.3333	52.71	36.95	-43.66	46.01	88.30	42.29	Horizontal
3	9686.3333	49.39	38.36	-42.08	45.67	88.30	42.63	Horizontal
4	12240.333	46.58	39.26	-39.62	46.22	74.00	27.78	Horizontal
5	14211.333	43.65	40.28	-38.29	45.64	88.30	42.66	Horizontal
6	17908.666	42.24	44.25	-36.96	49.53	74.00	24.47	Horizontal
7	17923	32.76	44.34	-36.93	40.16	54.00	13.84	Horizontal

11be(EHT20)_TX_CH_189_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7891	42.96	36.32	-17.70	61.58	88.30	26.72	Vertical
2	8818.6667	52.09	37.20	-43.26	46.03	88.30	42.27	Vertical
3	10898.333	47.24	39.43	-40.34	46.33	74.00	27.67	Vertical
4	13296.333	45.27	39.24	-38.71	45.81	74.00	28.19	Vertical
5	15768.666	44.42	38.82	-37.46	45.78	74.00	28.22	Vertical
6	17884.333	43.82	44.11	-37.11	50.82	74.00	23.18	Vertical
7	17888.333	33.12	44.13	-37.08	40.17	54.00	13.83	Vertical

11be(EHT20)_TX_CH_209_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7996	43.87	36.30	-18.10	62.07	88.30	26.23	Horizontal
2	8851.3333	52.65	37.24	-43.17	46.72	88.30	41.58	Horizontal
3	10893.666	46.88	39.43	-40.35	45.96	74.00	28.04	Horizontal
4	13085.333	45.28	38.93	-38.36	45.84	88.30	42.46	Horizontal
5	15201.333	43.78	39.84	-37.80	45.82	88.30	42.48	Horizontal
6	17621.333	43.46	42.53	-37.04	48.95	88.30	39.35	Horizontal
7	17911	33.15	44.27	-36.96	40.46	54.00	13.54	Horizontal

11be(EHT20)_TX_CH_209_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7981.5	42.15	36.30	-18.05	60.40	88.30	27.90	Vertical
2	8708	52.35	37.08	-43.83	45.59	88.30	42.71	Vertical
3	10284.666	48.35	39.00	-41.45	45.90	88.30	42.40	Vertical
4	12801	46.63	38.92	-39.07	46.48	88.30	41.82	Vertical
5	14872	44.52	40.21	-37.65	47.09	88.30	41.21	Vertical
6	17984.666	42.71	44.71	-36.81	50.61	74.00	23.39	Vertical
7	17928.666	32.88	44.37	-36.92	40.33	54.00	13.67	Vertical

11be(EHT20)_TX_CH_233_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7937	42.49	36.31	-17.88	60.92	88.30	27.38	Horizontal
2	8935.3333	51.28	37.33	-43.19	45.42	88.30	42.88	Horizontal
3	10424.333	47.69	39.10	-41.12	45.67	88.30	42.63	Horizontal
4	11870.333	46.92	39.41	-39.82	46.51	74.00	27.49	Horizontal
5	14455.333	44.23	40.25	-38.68	45.80	88.30	42.50	Horizontal
6	17913.666	42.57	44.28	-36.95	49.90	74.00	24.10	Horizontal
7	17922.666	33.22	44.34	-36.93	40.62	54.00	13.38	Horizontal

11be(EHT20)_TX_CH_233_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7963	42.74	36.31	-17.98	61.07	88.30	27.23	Vertical
2	8826	51.94	37.21	-43.24	45.91	88.30	42.39	Vertical
3	10307	47.83	39.01	-41.34	45.51	88.30	42.79	Vertical
4	12040	46.77	39.38	-39.45	46.70	74.00	27.30	Vertical
5	14308.666	45.07	40.27	-38.55	46.79	88.30	41.51	Vertical
6	17913.333	42.13	44.28	-36.95	49.46	74.00	24.54	Vertical
7	17938	33.33	44.43	-36.90	40.85	54.00	13.15	Vertical

11be(EHT40)_TX_CH_003_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7873	42.92	36.33	-17.63	61.61	88.30	26.69	Horizontal
2	8860	52.51	37.25	-43.14	46.61	88.30	41.69	Horizontal
3	10077.666	49.12	38.85	-41.62	46.35	88.30	41.95	Horizontal
4	12058.666	47.14	39.36	-39.48	47.02	74.00	26.98	Horizontal
5	14330.333	45.37	40.27	-38.58	47.06	88.30	41.24	Horizontal
6	17660.666	42.84	42.76	-37.45	48.15	88.30	40.15	Horizontal
7	17919	33.41	44.31	-36.94	40.78	54.00	13.22	Horizontal

11be(EHT40)_TX_CH_003_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7952	42.81	36.31	-17.94	61.18	88.30	27.12	Vertical
2	9686	48.97	38.36	-42.08	45.25	88.30	43.05	Vertical
3	11907.666	46.68	39.41	-39.79	46.29	74.00	27.71	Vertical
4	12724	46.34	38.97	-39.12	46.18	88.30	42.12	Vertical
5	14829.666	44.56	40.22	-37.75	47.03	88.30	41.27	Vertical
6	17876.333	43.12	44.06	-37.18	50.00	74.00	24.00	Vertical
7	17919.333	32.78	44.32	-36.94	40.15	54.00	13.85	Vertical

11be(EHT40)_TX_CH_043_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7946.5	43.84	36.31	-17.92	62.23	88.30	26.07	Horizontal
2	8914.3333	51.58	37.31	-43.09	45.79	88.30	42.51	Horizontal
3	10737.666	48.29	39.32	-40.82	46.79	74.00	27.21	Horizontal
4	13577.666	45.34	39.67	-39.06	45.95	88.30	42.35	Horizontal
5	15326.333	43.97	39.61	-37.64	45.94	88.30	42.36	Horizontal
6	17925	42.68	44.35	-36.93	50.10	74.00	23.90	Horizontal
7	17907.666	32.98	44.25	-36.96	40.26	54.00	13.74	Horizontal

11be(EHT40)_TX_CH_043_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7869	43.06	36.33	-17.62	61.77	88.30	26.53	Vertical
2	8887	51.60	37.28	-43.07	45.81	88.30	42.49	Vertical
3	10691.666	48.02	39.28	-40.94	46.37	74.00	27.63	Vertical
4	11723.666	46.06	39.43	-39.57	45.92	74.00	28.08	Vertical
5	14336.666	45.04	40.27	-38.59	46.72	88.30	41.58	Vertical
6	17970.666	41.88	44.62	-36.84	49.67	74.00	24.33	Vertical
7	17923.666	33.03	44.34	-36.93	40.44	54.00	13.56	Vertical

11be(EHT40)_TX_CH_051_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7911	43.24	36.32	-17.78	61.78	88.30	26.52	Horizontal
2	9438.6667	51.81	38.01	-42.66	47.16	74.00	26.84	Horizontal
3	11588.333	47.22	39.44	-39.98	46.68	74.00	27.32	Horizontal
4	13649.666	45.51	39.77	-38.65	46.63	88.30	41.67	Horizontal
5	15292	43.70	39.67	-37.55	45.82	88.30	42.48	Horizontal
6	17677	42.65	42.86	-37.62	47.89	88.30	40.41	Horizontal
7	17935.333	32.62	44.41	-36.91	40.12	54.00	13.88	Horizontal

11be(EHT40)_TX_CH_051_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7904.5	43.11	36.32	-17.76	61.67	88.30	26.63	Vertical
2	8826.6667	52.27	37.21	-43.24	46.24	88.30	42.06	Vertical
3	9993.3333	48.13	38.79	-41.65	45.27	88.30	43.03	Vertical
4	11430.333	47.26	39.46	-39.84	46.87	74.00	27.13	Vertical
5	14348.333	45.98	40.27	-38.60	47.64	88.30	40.66	Vertical
6	17916.333	42.23	44.30	-36.95	49.58	74.00	24.42	Vertical
7	17940	33.27	44.44	-36.90	40.81	54.00	13.19	Vertical

11be(EHT40)_TX_CH_091_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7838.5	42.98	36.33	-17.50	61.81	88.30	26.49	Horizontal
2	8885	51.90	37.27	-43.07	46.10	88.30	42.20	Horizontal
3	10875	47.21	39.41	-40.41	46.22	74.00	27.78	Horizontal
4	13354	45.74	39.33	-39.02	46.05	74.00	27.95	Horizontal
5	14943.666	44.58	40.21	-37.77	47.02	88.30	41.28	Horizontal
6	17985.333	42.10	44.71	-36.81	50.00	74.00	24.00	Horizontal
7	17920.666	32.93	44.32	-36.94	40.32	54.00	13.68	Horizontal

11be(EHT40)_TX_CH_091_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7807.5	43.02	36.34	-17.38	61.98	88.30	26.32	Vertical
2	8832	52.34	37.22	-43.22	46.33	88.30	41.97	Vertical
3	11069.666	47.42	39.49	-40.34	46.57	74.00	27.43	Vertical
4	12775	46.74	38.93	-39.09	46.59	88.30	41.71	Vertical
5	14940.333	44.47	40.21	-37.75	46.92	88.30	41.38	Vertical
6	17982.666	41.63	44.70	-36.81	49.51	74.00	24.49	Vertical
7	17993	32.15	44.76	-36.79	40.11	54.00	13.89	Vertical

11be(EHT40)_TX_CH_099_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7887.5	42.48	36.32	-17.69	61.11	88.30	27.19	Horizontal
2	8915	52.57	37.31	-43.10	46.78	88.30	41.52	Horizontal
3	11377.333	47.31	39.46	-39.89	46.88	74.00	27.12	Horizontal
4	13554.333	46.01	39.63	-39.14	46.51	88.30	41.79	Horizontal
5	15191.666	44.01	39.85	-37.83	46.04	88.30	42.26	Horizontal
6	17879	43.17	44.07	-37.15	50.09	74.00	23.91	Horizontal
7	17922.666	32.95	44.34	-36.93	40.35	54.00	13.65	Horizontal

11be(EHT40)_TX_CH_099_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7837	42.68	36.33	-17.49	61.52	88.30	26.78	Vertical
2	8828.3333	52.31	37.21	-43.23	46.29	88.30	42.01	Vertical
3	10100	48.16	38.87	-41.62	45.41	88.30	42.89	Vertical
4	12772.333	47.08	38.94	-39.09	46.93	88.30	41.37	Vertical
5	14882.666	43.91	40.21	-37.62	46.50	88.30	41.80	Vertical
6	17922.666	42.65	44.34	-36.93	50.05	74.00	23.95	Vertical
7	17936	32.63	44.42	-36.91	40.14	54.00	13.86	Vertical

11be(EHT40)_TX_CH_107_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7938	42.77	36.31	-17.88	61.20	88.30	27.10	Horizontal
2	9457	52.05	38.04	-42.55	47.54	74.00	26.46	Horizontal
3	11367.333	48.18	39.46	-39.89	47.75	74.00	26.25	Horizontal
4	13620	45.40	39.73	-38.85	46.28	88.30	42.02	Horizontal
5	15755.666	43.98	38.84	-37.50	45.32	74.00	28.68	Horizontal
6	17996.666	41.51	44.78	-36.79	49.50	74.00	24.50	Horizontal
7	17914	32.90	44.28	-36.95	40.23	54.00	13.77	Horizontal

11be(EHT40)_TX_CH_107_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7811	42.97	36.34	-17.39	61.91	88.30	26.39	Vertical
2	8894.6667	52.26	37.28	-43.04	46.50	88.30	41.80	Vertical
3	10275.333	48.28	38.99	-41.51	45.76	88.30	42.54	Vertical
4	12460.333	46.40	39.12	-39.50	46.02	74.00	27.98	Vertical
5	14918.333	44.95	40.21	-37.66	47.50	88.30	40.80	Vertical
6	17921	42.42	44.33	-36.94	49.81	74.00	24.19	Vertical
7	17911	33.02	44.27	-36.96	40.33	54.00	13.67	Vertical

11be(EHT40)_TX_CH_115_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7910	43.01	36.32	-17.78	61.55	88.30	26.75	Horizontal
2	8837.6667	52.38	37.22	-43.20	46.40	88.30	41.90	Horizontal
3	10290	47.99	39.00	-41.42	45.57	88.30	42.73	Horizontal
4	11544.333	46.42	39.45	-39.85	46.02	74.00	27.98	Horizontal
5	13412	45.96	39.42	-39.29	46.08	88.30	42.22	Horizontal
6	17873	42.38	44.04	-37.20	49.21	74.00	24.79	Horizontal
7	17914.333	33.15	44.29	-36.95	40.48	54.00	13.52	Horizontal

11be(EHT40)_TX_CH_115_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7903.5	43.19	36.32	-17.75	61.76	88.30	26.54	Vertical
2	8894.3333	52.47	37.28	-43.05	46.71	88.30	41.59	Vertical
3	10427	47.43	39.10	-41.13	45.40	88.30	42.90	Vertical
4	11463.666	46.66	39.45	-39.78	46.33	74.00	27.67	Vertical
5	14863	44.70	40.21	-37.67	47.24	88.30	41.06	Vertical
6	17982.666	41.93	44.70	-36.81	49.81	74.00	24.19	Vertical
7	17920.333	32.58	44.32	-36.94	39.96	54.00	14.04	Vertical

11be(EHT40)_TX_CH_123_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7895.5	43.30	36.32	-17.72	61.90	88.30	26.40	Horizontal
2	8798.3333	52.30	37.18	-43.32	46.16	88.30	42.14	Horizontal
3	10651.666	48.10	39.26	-40.96	46.39	74.00	27.61	Horizontal
4	12668.666	46.79	39.00	-39.11	46.68	74.00	27.32	Horizontal
5	14911	44.40	40.21	-37.63	46.98	88.30	41.32	Horizontal
6	17911.333	42.24	44.27	-36.96	49.55	74.00	24.45	Horizontal
7	17913.333	33.06	44.28	-36.95	40.39	54.00	13.61	Horizontal

11be(EHT40)_TX_CH_123_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7935.5	42.41	36.31	-17.87	60.85	88.30	27.45	Vertical
2	8800.3333	53.11	37.18	-43.31	46.98	88.30	41.32	Vertical
3	10090.666	48.60	38.86	-41.62	45.84	88.30	42.46	Vertical
4	12034	47.63	39.38	-39.43	47.57	74.00	26.43	Vertical
5	14852.666	44.43	40.21	-37.69	46.95	88.30	41.35	Vertical
6	17993.666	41.47	44.76	-36.79	49.44	74.00	24.56	Vertical
7	17913	33.14	44.28	-36.95	40.46	54.00	13.54	Vertical

11be(EHT40)_TX_CH_147_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7848.5	42.98	36.33	-17.54	61.77	88.30	26.53	Horizontal
2	8835.6667	52.54	37.22	-43.21	46.55	88.30	41.75	Horizontal
3	10418.333	47.95	39.09	-41.11	45.93	88.30	42.37	Horizontal
4	12637	46.53	39.02	-39.08	46.46	74.00	27.54	Horizontal
5	15764.666	44.08	38.82	-37.47	45.43	74.00	28.57	Horizontal
6	17932	42.87	44.39	-36.92	50.35	74.00	23.65	Horizontal
7	17979	32.36	44.67	-36.82	40.21	54.00	13.79	Horizontal

11be(EHT40)_TX_CH_147_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7911	42.98	36.32	-17.78	61.52	88.30	26.78	Vertical
2	8912.6667	51.72	37.30	-43.09	45.94	88.30	42.36	Vertical
3	11483.666	46.78	39.45	-39.74	46.49	74.00	27.51	Vertical
4	13667.333	45.04	39.80	-38.54	46.31	88.30	41.99	Vertical
5	15724.666	43.53	38.90	-37.61	44.82	74.00	29.18	Vertical
6	17987	41.64	44.72	-36.81	49.56	74.00	24.44	Vertical
7	17910.333	33.29	44.26	-36.96	40.59	54.00	13.41	Vertical

11be(EHT40)_TX_CH_179_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7935.5	42.44	36.31	-17.87	60.88	88.30	27.42	Horizontal
2	8850.6667	53.48	37.24	-43.17	47.55	88.30	40.75	Horizontal
3	10671	47.97	39.27	-40.95	46.29	74.00	27.71	Horizontal
4	13168.333	45.89	39.05	-38.69	46.25	88.30	42.05	Horizontal
5	15286	43.39	39.69	-37.57	45.51	88.30	42.79	Horizontal
6	17922.333	42.43	44.33	-36.94	49.83	74.00	24.17	Horizontal
7	17905	33.02	44.23	-36.97	40.28	54.00	13.72	Horizontal

11be(EHT40)_TX_CH_179_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7839	42.75	36.33	-17.50	61.58	88.30	26.72	Vertical
2	9437.3333	51.30	38.01	-42.67	46.64	74.00	27.36	Vertical
3	11322.666	47.10	39.47	-39.88	46.69	74.00	27.31	Vertical
4	12805.333	46.42	38.92	-39.09	46.25	88.30	42.05	Vertical
5	15498.666	44.42	39.30	-38.26	45.47	74.00	28.53	Vertical
6	17981.333	41.99	44.69	-36.82	49.86	74.00	24.14	Vertical
7	17932.666	33.04	44.40	-36.91	40.52	54.00	13.48	Vertical

11be(EHT40)_TX_CH_187_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7831	42.97	36.33	-17.47	61.83	88.30	26.47	Horizontal
2	8873	52.43	37.26	-43.11	46.58	88.30	41.72	Horizontal
3	10637	48.23	39.25	-40.97	46.50	74.00	27.50	Horizontal
4	12784.333	47.64	38.93	-39.08	47.49	88.30	40.81	Horizontal
5	14944	44.73	40.21	-37.77	47.17	88.30	41.13	Horizontal
6	17974.333	42.55	44.65	-36.83	50.36	74.00	23.64	Horizontal
7	17977.666	32.31	44.67	-36.82	40.15	54.00	13.85	Horizontal

11be(EHT40)_TX_CH_187_Vertical



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7871	43.30	36.33	-17.63	62.00	88.30	26.30	Vertical
2	8862.6667	52.15	37.25	-43.13	46.26	88.30	42.04	Vertical
3	10296	47.90	39.01	-41.38	45.52	88.30	42.78	Vertical
4	13698.666	44.84	39.85	-38.33	46.36	88.30	41.94	Vertical
5	14902.666	43.88	40.21	-37.59	46.50	88.30	41.80	Vertical
6	17916.666	43.08	44.30	-36.95	50.43	74.00	23.57	Vertical
7	17915	32.88	44.29	-36.95	40.22	54.00	13.78	Vertical

11be(EHT40)_TX_CH_195_Horizontal



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7979.5	42.56	36.30	-18.04	60.82	88.30	27.48	Horizontal
2	8837.6667	52.79	37.22	-43.20	46.81	88.30	41.49	Horizontal
3	10772.666	47.96	39.34	-40.72	46.58	74.00	27.42	Horizontal
4	14356.333	45.78	40.26	-38.61	47.43	88.30	40.87	Horizontal
5	15827	43.24	38.71	-37.50	44.45	74.00	29.55	Horizontal
6	17922.666	43.46	44.34	-36.93	50.86	74.00	23.14	Horizontal
7	17917.333	32.88	44.30	-36.95	40.24	54.00	13.76	Horizontal