



# **FCC Test Report**

## **FCC ID: XN6-SB3630E6**

**Product:** 36"Sound Bar 3.0 System  
**Trade Mark:** VIZIO  
**Model Number:** SB3630-E6  
**Serial Model:** N/A  
**Report No.:** NTEK- 2017NT02211559F

**Prepared for**

Zylux Acoustic Corporation  
3F, 22, Lane 35, Jihu Road, Neihsu Technology Park, 114 Taipei Taiwan

**Prepared by**

NTEK Testing Technology Co., Ltd.  
1/F, Building E, Fenda Science Park, Sanwei Community,  
Xixiang Street Bao'an District, Shenzhen 518126 P.R. China  
Tel.: +86-755-6115 6588  
Fax.: +86-755-6115 6599  
Website:<http://www.ntek.org.cn>

## TEST RESULT CERTIFICATION

**Applicant's name** ..... : Zylux Acoustic Corporation  
 Address ..... : 3F, 22, Lane 35, Jihu Road, Neihu Technology Park, 114  
 Taipei Taiwan  
**Manufacturer's Name** ..... : Zylux Acoustic Corporation  
 Address ..... : 3F, 22, Lane 35, Jihu Road, Neihu Technology Park, 114  
 Taipei Taiwan  
**Factory's Name** ..... : Zhao Yang Electronic (Shenzhen) Co. , Ltd.  
 Address ..... : Building 2, De Yong Jia Industrial Park, Guang Qiao Road, Yu Lv  
 Community, Gong Ming Street, Guang Ming New District,  
 Shenzhen, 518132, China

### Product description

Product name ..... : 36"Sound Bar 3.0 System

Model and/or type reference : SB3630-E6

FCC Part15B:01 Oct.2016

**Standards** ..... : ANSI C63.4:2014

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with Part 15 of FCC Rules. And it is applicable only to the tested sample identified in the report.


This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personnel only, and shall be noted in the revision of the document.

**Date of Test** .....


Date (s) of performance of tests ..... : 21 Feb. 2017 ~04 Mar. 2017

Date of Issue..... : 04 Mar. 2017

Test Result..... : **Pass**

Testing Engineer :   
 (Lake Xie)

Technical Manager :   
 (Jason Chen)

Authorized Signatory :   
 (Sam Chen)

| Table of Contents                                  | Page |
|----------------------------------------------------|------|
| 1 . TEST SUMMARY                                   | 4    |
| 1.1 TEST FACILITY                                  | 5    |
| 1.2 MEASUREMENT UNCERTAINTY                        | 5    |
| 2 . GENERAL INFORMATION                            | 6    |
| 2.1 GENERAL DESCRIPTION OF EUT                     | 6    |
| 2.2 DESCRIPTION OF TEST SETUP                      | 8    |
| 2.3 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL | 9    |
| 2.4 MEASUREMENT INSTRUMENTS LIST                   | 10   |
| 3 . EMC EMISSION TEST                              | 11   |
| 3.1 CONDUCTED EMISSION MEASUREMENT                 | 11   |
| 3.1.1 POWER LINE CONDUCTED EMISSION                | 11   |
| 3.1.2 TEST PROCEDURE                               | 12   |
| 3.1.3 TEST SETUP                                   | 12   |
| 3.1.4 EUT OPERATING CONDITIONS                     | 12   |
| 3.1.5 TEST RESULTS                                 | 13   |
| 3.2 RADIATED EMISSION MEASUREMENT                  | 17   |
| 3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT      | 17   |
| 3.2.2 TEST PROCEDURE                               | 17   |
| 3.2.3 TEST SETUP                                   | 18   |
| 3.2.4 TEST RESULTS                                 | 19   |
| 3.2.5 TEST RESULTS(1000~25000MHz)                  | 23   |
| 4 . EUT TEST PHOTO                                 | 25   |

## 1. TEST SUMMARY

Test procedures according to the technical standards:

| EMC Emission                         |                    |         |          |        |
|--------------------------------------|--------------------|---------|----------|--------|
| Standard                             | Test Item          | Limit   | Judgment | Remark |
| FCC Part15B:2016<br>ANSI C63.4: 2014 | Conducted Emission | Class B | PASS     |        |
|                                      | Radiated Emission  | Class B | PASS     |        |

### NOTE:

- (1) 'N/A' denotes test is not applicable in this Test Report
- (2) For client's request and manual description, the test will not be executed.

## 1.1 TEST FACILITY

NTEK Testing Technology Co., Ltd

Add. : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen P.R. China.

FCC Registration Number:238937; IC Registration Number:9270A-1

CNAS Registration Number:L5516

## 1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately **95 %**.

### A. Conducted Measurement :

| Test Site | Method | Measurement Frequency Range | U, (dB) | NOTE |
|-----------|--------|-----------------------------|---------|------|
| NTEKC01   | ANSI   | 150 KHz ~ 30MHz             | 3.2     |      |

### B. Radiated Measurement :

| Test Site | Method | Measurement Frequency Range | U, (dB) | NOTE |
|-----------|--------|-----------------------------|---------|------|
| NTEKA01   | ANSI   | 30MHz ~ 1000MHz             | 4.7     |      |
|           |        | 1GHz ~12.4GHz               | 5.0     |      |

## 2. GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

|                     |                                                                                                  |            |  |
|---------------------|--------------------------------------------------------------------------------------------------|------------|--|
| Equipment           | 36"Sound Bar 3.0 System                                                                          |            |  |
| Trade Mark          | VIZIO                                                                                            |            |  |
| Model Name          | SB3630-E6                                                                                        |            |  |
| Serial Model        | N/A                                                                                              |            |  |
| Remark              | The SB3630-E6 have two power sources(AC Power#1 and AC Power#2) to choose, and Please see below. |            |  |
| Product Description | The EUT is a 36"Sound Bar 3.0 System.                                                            |            |  |
|                     | Connecting I/O port:                                                                             | USB, DC in |  |
|                     | Operation Frequency:                                                                             | N/A        |  |
|                     | Modulation Type:                                                                                 | N/A        |  |
| Power Source        | AC Voltage                                                                                       |            |  |
| Power Rating        | AC 120V/60Hz , 60W                                                                               |            |  |
| Adapter             | N/A                                                                                              |            |  |
| Battery             | N/A                                                                                              |            |  |
| HW Version          | N/A                                                                                              |            |  |
| SW Version          | N/A                                                                                              |            |  |

## 2.1.1 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.



| Pretest Mode | Description |
|--------------|-------------|
| Mode 1       | AUX in      |
| Mode 2       | Optical     |
| Mode 3       | HDMI        |
| Mode 4       | USB         |

| For Conducted Test |             |
|--------------------|-------------|
| Final Test Mode    | Description |
| Mode 1             | AUX in      |
| Mode 2             | Optical     |
| Mode 3             | HDMI        |
| Mode 4             | USB         |

| For Radiated Test |             |
|-------------------|-------------|
| Final Test Mode   | Description |
| Mode 1            | AUX in      |
| Mode 2            | Optical     |
| Mode 3            | HDMI        |
| Mode 4            | USB         |

Note: Final Test Mode: Through Pre-scan, find the mode 3 is the worst case. Only the worst case mode is recorded in the report.

## 2.2 DESCRIPTION OF TEST SETUP



## 2.3 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Item | Equipment                | Brand | Model/Type No. | Series No. | Note |
|------|--------------------------|-------|----------------|------------|------|
| E-1  | 36" Sound Bar 3.0 System | N/A   | SB3630-E6      | N/A        | EUT  |
| E-2  | Personal computer        | DELL  | FT4Y23X        | N/A        |      |
| E-3  | Monitor                  | SONY  | KDL-24EX520    | N/A        |      |
| E-4  | Printer                  | Canon | L11121E        | N/A        |      |
| E-5  | Mouse                    | DELL  | MS111-P        | N/A        |      |
| E-6  | Keyboard                 | DELL  | SK-8185        | N/A        |      |
| E-7  | Remote control           | N/A   | N/A            | N/A        |      |
|      |                          |       |                |            |      |
|      |                          |       |                |            |      |
|      |                          |       |                |            |      |

| Item | Cable Type     | Shielded Type | Ferrite Core | Length | Note |
|------|----------------|---------------|--------------|--------|------|
| C-1  | USB Cable      | NO            | NO           | 1.5m   |      |
| C-2  | USB Cable      | NO            | NO           | 1.5m   |      |
| C-3  | HDMI           | NO            | NO           | 0.8m   |      |
| C-4  | Keyboard Cable | NO            | NO           | 1.2m   |      |
| C-5  | Mouse Cable    | NO            | NO           | 1.2m   |      |
|      |                |               |              |        |      |
|      |                |               |              |        |      |
|      |                |               |              |        |      |

### Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) "YES" means "shielded" "with core"; "NO" means "unshielded" "without core".

## 2.4 MEASUREMENT INSTRUMENTS LIST

### Radiation Test equipment

| Item | Kind of Equipment  | Manufacturer | Type No.    | Serial No.   | Last calibration | Calibrated until | Calibration period |
|------|--------------------|--------------|-------------|--------------|------------------|------------------|--------------------|
| 1    | Spectrum Analyzer  | Agilent      | E4407B      | MY45108040   | 2016.07.06       | 2017.07.05       | 1 year             |
| 2    | Test Receiver      | R&S          | ESPI        | 101318       | 2016.06.07       | 2017.06.06       | 1 year             |
| 3    | Bilog Antenna      | TESEQ        | CBL6111D    | 31216        | 2016.07.06       | 2017.07.05       | 1 year             |
| 4    | 50Ω Coaxial Switch | Anritsu      | MP59B       | 6200264416   | 2016.06.07       | 2017.06.06       | 1 year             |
| 5    | Spectrum Analyzer  | ADVANTEST    | R3132       | 150900201    | 2016.06.07       | 2017.06.06       | 1 year             |
| 6    | Horn Antenna       | EM           | EM-AH-10180 | 2011071402   | 2016.07.06       | 2017.07.05       | 1 year             |
| 7    | Horn Ant           | Schwarzbeck  | BBHA 9170   | 9170-181     | 2016.07.06       | 2017.07.05       | 1 year             |
| 8    | Amplifier          | EM           | EM-30180    | 060538       | 2016.07.06       | 2017.07.05       | 1 year             |
| 9    | Loop Antenna       | ARA          | PLA-1030/B  | 1029         | 2016.06.08       | 2017.06.07       | 1 year             |
| 10   | Power Meter        | R&S          | NRVS        | 100696       | 2016.07.06       | 2017.07.05       | 1 year             |
| 11   | Power Sensor       | R&S          | URV5-Z4     | 0395.1619.05 | 2016.07.06       | 2017.07.05       | 1 year             |
| 12   | Test Cable         | N/A          | R-01        | N/A          | 2016.07.06       | 2017.07.05       | 1 year             |
| 13   | Test Cable         | N/A          | R-02        | N/A          | 2016.07.06       | 2017.07.05       | 1 year             |

### Conduction Test equipment

| Item | Kind of Equipment     | Manufacturer | Type No. | Serial No. | Last calibration | Calibrated until | Calibration period |
|------|-----------------------|--------------|----------|------------|------------------|------------------|--------------------|
| 1    | Test Receiver         | R&S          | ESCI     | 101160     | 2016.06.06       | 2017.06.05       | 1 year             |
| 2    | LISN                  | R&S          | ENV216   | 101313     | 2016.08.24       | 2017.08.23       | 1 year             |
| 3    | LISN                  | EMCO         | 3816/2   | 00042990   | 2016.08.24       | 2017.08.23       | 1 year             |
| 4    | 50Ω Coaxial Switch    | Anritsu      | MP59B    | 6200264417 | 2016.06.07       | 2017.06.06       | 1 year             |
| 5    | Passive Voltage Probe | R&S          | ESH2-Z3  | 100196     | 2016.06.07       | 2017.06.06       | 1 year             |
| 6    | Absorbing clamp       | R&S          | MOS-21   | 100423     | 2016.06.08       | 2017.06.07       | 1 year             |
| 7    | Test Cable            | N/A          | C01      | N/A        | 2016.06.08       | 2017.06.07       | 1 year             |
| 8    | Test Cable            | N/A          | C02      | N/A        | 2016.06.08       | 2017.06.07       | 1 year             |
| 9    | Test Cable            | N/A          | C03      | N/A        | 2016.06.08       | 2017.06.07       | 1 year             |

### 3. EMC EMISSION TEST

#### 3.1 CONDUCTED EMISSION MEASUREMENT

##### 3.1.1 POWER LINE CONDUCTED EMISSION (Frequency Range 150KHz-30MHz)

| FREQUENCY (MHz) | Class A (dBuV) |         | Class B (dBuV) |           |
|-----------------|----------------|---------|----------------|-----------|
|                 | Quasi-peak     | Average | Quasi-peak     | Average   |
| 0.15 -0.5       | 79.00          | 66.00   | 66 - 56 *      | 56 - 46 * |
| 0.50 -5.0       | 73.00          | 60.00   | 56.00          | 46.00     |
| 5.0 -30.0       | 73.00          | 60.00   | 60.00          | 50.00     |

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

| Receiver Parameters | Setting  |
|---------------------|----------|
| Attenuation         | 10 dB    |
| Start Frequency     | 0.15 MHz |
| Stop Frequency      | 30 MHz   |
| IF Bandwidth        | 9 kHz    |

### 3.1.2 TEST PROCEDURE

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

### 3.1.3 TEST SETUP



**Note: 1.Support units were connected to second LISN.**

**2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes**

### 3.1.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.


### 3.1.5 TEST RESULTS

|               |                          |                    |           |
|---------------|--------------------------|--------------------|-----------|
| EUT:          | 36"Sound Bar 3.0 System  | Model Name. :      | SB3630-E6 |
| Temperature:  | 26 °C                    | Relative Humidity: | 54%       |
| Pressure:     | 1010hPa                  | Test Date:         | 2017-2-21 |
| Test Mode:    | Mode 3                   | Phase :            | L         |
| Test Voltage: | AC 120V/60Hz(AC Power#1) |                    |           |

| Frequency<br>(MHz) | Reading Level<br>(dBμV) | Correct Factor<br>(dB) | Measure-ment<br>(dBμV) | Limits<br>(dBμV) | Margin<br>(dB) | Remark |
|--------------------|-------------------------|------------------------|------------------------|------------------|----------------|--------|
| 0.15               | 36.83                   | 9.68                   | 46.51                  | 65.99            | -19.48         | QP     |
| 0.15               | 18.22                   | 9.68                   | 27.9                   | 55.99            | -28.09         | AVG    |
| 0.162              | 35.68                   | 9.68                   | 45.36                  | 65.36            | -20            | QP     |
| 0.162              | 17.21                   | 9.68                   | 26.89                  | 55.36            | -28.47         | AVG    |
| 0.1779             | 33.99                   | 9.68                   | 43.67                  | 64.58            | -20.91         | QP     |
| 0.1779             | 16.96                   | 9.68                   | 26.64                  | 54.58            | -27.94         | AVG    |
| 0.4779             | 29.91                   | 9.68                   | 39.59                  | 56.38            | -16.79         | QP     |
| 0.4779             | 20.82                   | 9.68                   | 30.5                   | 46.38            | -15.88         | AVG    |
| 20.858             | 31.64                   | 10.01                  | 41.65                  | 60               | -18.35         | QP     |
| 20.858             | 21.17                   | 10.01                  | 31.18                  | 50               | -18.82         | AVG    |
| 28.57              | 34.55                   | 10.04                  | 44.59                  | 60               | -15.41         | QP     |
| 28.57              | 12.45                   | 10.04                  | 22.49                  | 50               | -27.51         | AVG    |

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




|               |                          |                    |           |
|---------------|--------------------------|--------------------|-----------|
| EUT:          | 36"Sound Bar 3.0 System  | Model Name. :      | SB3630-E6 |
| Temperature:  | 26 °C                    | Relative Humidity: | 54%       |
| Pressure:     | 1010hPa                  | Test Date:         | 2017-2-21 |
| Test Mode:    | Mode 3                   | Phase :            | N         |
| Test Voltage: | AC 120V/60Hz(AC Power#1) |                    |           |

| Frequency | Reading Level | Correct Factor | Measure-ment | Limits | Margin | Remark |
|-----------|---------------|----------------|--------------|--------|--------|--------|
| (MHz)     | (dBμV)        | (dB)           | (dBμV)       | (dBμV) | (dB)   |        |
| 0.158     | 38.44         | 9.68           | 48.12        | 65.56  | -17.44 | QP     |
| 0.158     | 14.34         | 9.68           | 24.02        | 55.56  | -31.54 | AVG    |
| 0.4858    | 30.08         | 9.68           | 39.76        | 56.24  | -16.48 | QP     |
| 0.4858    | 21.08         | 9.68           | 30.76        | 46.24  | -15.48 | AVG    |
| 10.4938   | 31.52         | 9.86           | 41.38        | 60     | -18.62 | QP     |
| 10.4938   | 12.78         | 9.86           | 22.64        | 50     | -27.36 | AVG    |
| 18.6177   | 32.1          | 9.99           | 42.09        | 60     | -17.91 | QP     |
| 18.6177   | 18.14         | 9.99           | 28.13        | 50     | -21.87 | AVG    |
| 22.4618   | 32.83         | 10.01          | 42.84        | 60     | -17.16 | QP     |
| 22.4618   | 20.96         | 10.01          | 30.97        | 50     | -19.03 | AVG    |
| 29.9058   | 32.51         | 10.06          | 42.57        | 60     | -17.43 | QP     |
| 29.9058   | 11.76         | 10.06          | 21.82        | 50     | -28.18 | AVG    |

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




|               |                          |                    |           |
|---------------|--------------------------|--------------------|-----------|
| EUT:          | 36"Sound Bar 3.0 System  | Model Name. :      | SB3630-E6 |
| Temperature:  | 26 °C                    | Relative Humidity: | 54%       |
| Pressure:     | 1010hPa                  | Test Date:         | 2017-2-21 |
| Test Mode:    | Mode 3                   | Phase :            | L         |
| Test Voltage: | AC 120V/60Hz(AC Power#2) |                    |           |

| Frequency | Reading Level | Correct Factor | Measure-ment | Limits | Margin | Remark |
|-----------|---------------|----------------|--------------|--------|--------|--------|
| (MHz)     | (dBμV)        | (dB)           | (dBμV)       | (dBμV) | (dB)   |        |
| 0.15      | 43.56         | 9.58           | 53.14        | 65.99  | -12.85 | QP     |
| 0.15      | 20.02         | 9.58           | 29.6         | 55.99  | -26.39 | AVG    |
| 0.194     | 36.7          | 9.58           | 46.28        | 63.86  | -17.58 | QP     |
| 0.194     | 16.49         | 9.58           | 26.07        | 53.86  | -27.79 | AVG    |
| 0.23      | 33.81         | 9.58           | 43.39        | 62.45  | -19.06 | QP     |
| 0.23      | 13.44         | 9.58           | 23.02        | 52.45  | -29.43 | AVG    |
| 0.4259    | 31.5          | 9.58           | 41.08        | 57.33  | -16.25 | QP     |
| 0.4259    | 22.6          | 9.58           | 32.18        | 47.33  | -15.15 | AVG    |
| 4.4537    | 24.55         | 9.67           | 34.22        | 56     | -21.78 | QP     |
| 4.4537    | 10.83         | 9.67           | 20.5         | 46     | -25.5  | AVG    |
| 4.9058    | 24.59         | 9.69           | 34.28        | 56     | -21.72 | QP     |
| 4.9058    | 9.48          | 9.69           | 19.17        | 46     | -26.83 | AVG    |

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




|               |                          |                    |           |
|---------------|--------------------------|--------------------|-----------|
| EUT:          | 36"Sound Bar 3.0 System  | Model Name. :      | SB3630-E6 |
| Temperature:  | 26 °C                    | Relative Humidity: | 54%       |
| Pressure:     | 1010hPa                  | Test Date:         | 2017-2-21 |
| Test Mode:    | Mode 3                   | Phase :            | N         |
| Test Voltage: | AC 120V/60Hz(AC Power#2) |                    |           |

| Frequency | Reading Level | Correct Factor | Measure-ment | Limits | Margin | Remark |
|-----------|---------------|----------------|--------------|--------|--------|--------|
| (MHz)     | (dBμV)        | (dB)           | (dBμV)       | (dBμV) | (dB)   |        |
| 0.15      | 40.23         | 9.58           | 49.81        | 65.99  | -16.18 | QP     |
| 0.15      | 19.83         | 9.58           | 29.41        | 55.99  | -26.58 | AVG    |
| 0.166     | 38.26         | 9.58           | 47.84        | 65.15  | -17.31 | QP     |
| 0.166     | 18.8          | 9.58           | 28.38        | 55.15  | -26.77 | AVG    |
| 0.2099    | 34.37         | 9.58           | 43.95        | 63.21  | -19.26 | QP     |
| 0.2099    | 14.44         | 9.58           | 24.02        | 53.21  | -29.19 | AVG    |
| 0.33      | 28.13         | 9.57           | 37.7         | 59.45  | -21.75 | QP     |
| 0.33      | 15.33         | 9.57           | 24.9         | 49.45  | -24.55 | AVG    |
| 0.4259    | 30.75         | 9.58           | 40.33        | 57.33  | -17    | QP     |
| 0.4259    | 22.28         | 9.58           | 31.86        | 47.33  | -15.47 | AVG    |
| 4.8658    | 28.63         | 9.69           | 38.32        | 56     | -17.68 | QP     |
| 4.8658    | 16.01         | 9.69           | 25.7         | 46     | -20.3  | AVG    |

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



## 3.2 RADIATED EMISSION MEASUREMENT

### 3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

| FREQUENCY (MHz) | Class A (at 10m) | Class B (at 3m) |
|-----------------|------------------|-----------------|
|                 | dBuV/m           | dBuV/m          |
| 30 ~ 88         | 39.0             | 40.0            |
| 88 ~ 216        | 43.5             | 43.5            |
| 216 ~ 960       | 46.5             | 46.0            |
| Above 960       | 49.5             | 54.0            |

Notes:

- (1) The limit for radiated test was performed according to as following:  
FCC PART 15B /ICES-003.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

### 3.2.2 TEST PROCEDURE

#### Test Arrangement for Radiated Emissions up to 1 GHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at an accredited test facility. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

Note: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for quasi-peak detection (QP) at frequency below 1GHz.

#### Test Arrangement for Radiated Emissions above 1 GHz.


- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at an accredited chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna can be varied from one meter to four meters, the height of adjustment depends on the EUT height and the antenna 3dB beamwidth both, to detect the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

Note: For the hand-held device, the EUT should be measured for all 3 axes and only the worst case is recorded in the report  
During the radiated emission test, the Spectrum Analyzer was set with the following configurations:


| Frequency Band (MHz) | Function             | Resolution bandwidth | Video Bandwidth |
|----------------------|----------------------|----------------------|-----------------|
| 30 to 1000           | QP                   | 120 kHz              | 300 kHz         |
| Above 1000           | Peak                 | 1 MHz                | 1 MHz           |
|                      | PK detector is forAV | 1 MHz                | 10 Hz           |

### 3.2.3 TEST SETUP

For Radiated Emission 30~1000MHz



(B) Radiated Emission Test Set-Up Frequency Above 1GHz



### 3.2.4 TEST RESULTS


#### TEST RESULTS (30~1000 MHz)

|              |                          |                    |            |
|--------------|--------------------------|--------------------|------------|
| EUT:         | 36"Sound Bar 3.0 System  | Model Name:        | SB3630-E6  |
| Temperature: | 24 °C                    | Relative Humidity: | 54%        |
| Pressure:    | 1010 hPa                 | Test Date :        | 2017-2-21  |
| Test Mode :  | Mode 3                   | Polarization :     | Horizontal |
| Test Power : | AC 120V/60Hz(AC Power#1) |                    |            |

| Polar<br>(H/V) | Frequency | Meter<br>Reading | Factor | Emission<br>Level | Limits   | Margin | Remark |
|----------------|-----------|------------------|--------|-------------------|----------|--------|--------|
|                | (MHz)     | (dBuV)           | (dB)   | (dBuV/m)          | (dBuV/m) | (dB)   |        |
| H              | 82.9385   | 23.98            | 9.15   | 33.13             | 40       | -6.87  | QP     |
| H              | 85.8983   | 26.87            | 9.66   | 36.53             | 40       | -3.47  | QP     |
| H              | 92.1388   | 25.06            | 11     | 36.06             | 43.5     | -7.44  | QP     |
| H              | 110.5687  | 24.85            | 12.66  | 37.51             | 43.5     | -5.99  | QP     |
| H              | 135.0319  | 22.17            | 13.13  | 35.3              | 43.5     | -8.2   | QP     |
| H              | 243.3771  | 24.55            | 13.9   | 38.45             | 46       | -7.55  | QP     |

Remark:

Factor = Antenna Factor + Cable Loss - Amplifier.




|              |                          |                    |            |
|--------------|--------------------------|--------------------|------------|
| EUT:         | 36"Sound Bar 3.0 System  | Model Name :       | SB3630-E6  |
| Temperature: | 24 °C                    | Relative Humidity: | 54%        |
| Pressure:    | 1010 hPa                 | Test Date :        | 2016-12-12 |
| Test Mode :  | Mode 3                   | Polarization :     | Vertical   |
| Test Power : | AC 120V/60Hz(AC Power#1) |                    |            |

| Polar<br>(H/V) | Frequency | Meter<br>Reading | Factor | Emission<br>Level | Limits   | Margin | Remark |
|----------------|-----------|------------------|--------|-------------------|----------|--------|--------|
|                | (MHz)     | (dBuV)           | (dB)   | (dBuV/m)          | (dBuV/m) | (dB)   |        |
| V              | 30.9618   | 12.27            | 19.37  | 31.64             | 40       | -8.36  | QP     |
| V              | 36.7661   | 14.84            | 16.45  | 31.29             | 40       | -8.71  | QP     |
| V              | 43.6584   | 17.48            | 12.19  | 29.67             | 40       | -10.33 | QP     |
| V              | 85.8983   | 23.6             | 9.66   | 33.26             | 40       | -6.74  | QP     |
| V              | 159.7844  | 23.33            | 12.19  | 35.52             | 43.5     | -7.98  | QP     |
| V              | 771.4486  | 13.88            | 27.83  | 41.71             | 46       | -4.29  | QP     |

Remark:

Factor = Antenna Factor + Cable Loss - Amplifier.




|              |                          |                    |            |
|--------------|--------------------------|--------------------|------------|
| EUT:         | 36"Sound Bar 3.0 System  | Model Name:        | SB3630-E6  |
| Temperature: | 24 °C                    | Relative Humidity: | 54%        |
| Pressure:    | 1010 hPa                 | Test Date :        | 2017-2-21  |
| Test Mode :  | Mode 3                   | Polarization :     | Horizontal |
| Test Power : | AC 120V/60Hz(AC Power#2) |                    |            |

| Polar<br>(H/V) | Frequency | Meter<br>Reading | Factor | Emission<br>Level | Limits   | Margin | Remark |
|----------------|-----------|------------------|--------|-------------------|----------|--------|--------|
|                | (MHz)     | (dBuV)           | (dB)   | (dBuV/m)          | (dBuV/m) | (dB)   |        |
| H              | 85.8983   | 26.4             | 9.66   | 36.06             | 40       | -3.94  | QP     |
| H              | 92.1388   | 25.42            | 11     | 36.42             | 43.5     | -7.08  | QP     |
| H              | 110.5687  | 22.02            | 12.66  | 34.68             | 43.5     | -8.82  | QP     |
| H              | 188.4123  | 25.69            | 10.66  | 36.35             | 43.5     | -7.15  | QP     |
| H              | 275.1569  | 24.46            | 15.61  | 40.07             | 46       | -5.93  | QP     |
| H              | 771.4486  | 12.29            | 27.83  | 40.12             | 46       | -5.88  | QP     |

Remark:

Factor = Antenna Factor + Cable Loss - Amplifier.




|              |                          |                    |            |
|--------------|--------------------------|--------------------|------------|
| EUT:         | 36"Sound Bar 3.0 System  | Model Name :       | SB3630-E6  |
| Temperature: | 24 °C                    | Relative Humidity: | 54%        |
| Pressure:    | 1010 hPa                 | Test Date :        | 2016-12-12 |
| Test Mode :  | Mode 3                   | Polarization :     | Vertical   |
| Test Power : | AC 120V/60Hz(AC Power#2) |                    |            |

| Polar<br>(H/V) | Frequency | Meter<br>Reading | Factor | Emission<br>Level | Limits   | Margin | Remark |
|----------------|-----------|------------------|--------|-------------------|----------|--------|--------|
|                | (MHz)     | (dBuV)           | (dB)   | (dBuV/m)          | (dBuV/m) | (dB)   |        |
| V              | 30.7454   | 15.3             | 19.49  | 34.79             | 40       | -5.21  | QP     |
| V              | 36.7661   | 13.12            | 16.45  | 29.57             | 40       | -10.43 | QP     |
| V              | 85.8983   | 21.36            | 9.66   | 31.02             | 40       | -8.98  | QP     |
| V              | 275.1569  | 19.3             | 15.61  | 34.91             | 46       | -11.09 | QP     |
| V              | 771.4486  | 14.81            | 27.83  | 42.64             | 46       | -3.36  | QP     |
| V              | 938.8324  | 6.96             | 30.97  | 37.93             | 46       | -8.07  | QP     |

Remark:

Factor = Antenna Factor + Cable Loss - Amplifier.



### 3.2.5 TEST RESULTS(1000~25000MHz)

|              |                          |                    |           |
|--------------|--------------------------|--------------------|-----------|
| EUT:         | 36"Sound Bar 3.0 System  | Model Name :       | SB3630-E6 |
| Temperature: | 24 °C                    | Relative Humidity: | 54%       |
| Pressure:    | 1010 hPa                 | Test Date :        | 2017-2-21 |
| Test Mode :  | Mode 3                   |                    |           |
| Test Power : | AC 120V/60Hz(AC Power#1) |                    |           |

All the modulation modes have been tested, and the worst result was report as below:

| Polar<br>(H/V) | Frequency | Reading  | Correct | Result   | Limit    | Over<br>Limit | Remark |
|----------------|-----------|----------|---------|----------|----------|---------------|--------|
|                | (MHz)     | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)          |        |
| V              | 1559.5    | 64.79    | -13     | 52.29    | 74       | -21.71        | Pk     |
| V              | 1559.5    | 52.9     | -13     | 40.4     | 54       | -13.6         | AV     |
| V              | 2077.2    | 59.67    | -10     | 49.49    | 74       | -24.51        | Pk     |
| V              | 2077.2    | 47.78    | -10     | 37.6     | 54       | -16.4         | AV     |
| V              | 3114.2    | 57.73    | -8.1    | 49.6     | 74       | -24.4         | Pk     |
| V              | 3114.2    | 46.33    | -8.1    | 38.2     | 54       | -15.8         | AV     |
| H              | 1559.5    | 67.23    | -13     | 54.73    | 74       | -19.27        | Pk     |
| H              | 1559.5    | 55.2     | -13     | 42.7     | 54       | -11.3         | AV     |
| H              | 1872.2    | 59.96    | -11     | 49.05    | 74       | -24.95        | Pk     |
| H              | 1872.2    | 48.94    | -11     | 38.03    | 54       | -15.97        | AV     |
| H              | 3119.8    | 56.5     | -8.1    | 48.39    | 74       | -25.61        | Pk     |
| H              | 3119.8    | 45.51    | -8.1    | 37.4     | 54       | -16.6         | AV     |

Remark:

Emission Level = Read Level+Antenna Factor + Cable Loss - Amplifier.

Margin= Emission Level-Limits

Note:

1. Measuring frequencies from 1 GHz to 13GHz.

2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using

Peak detector mode of the emission shown in Actual FS column.

3. The frequency that above 3GHz is mainly from the environment noise

|              |                          |                    |           |
|--------------|--------------------------|--------------------|-----------|
| EUT:         | 36"Sound Bar 3.0 System  | Model Name :       | SB3630-E6 |
| Temperature: | 24 °C                    | Relative Humidity: | 54%       |
| Pressure:    | 1010 hPa                 | Test Date :        | 2017-2-21 |
| Test Mode :  | Mode 3                   |                    |           |
| Test Power : | AC 120V/60Hz(AC Power#2) |                    |           |

All the modulation modes have been tested, and the worst result was report as below:

| Polar<br>(H/V) | Frequency | Reading      | Correct | Result       | Limit        | Over<br>Limit | Remark |
|----------------|-----------|--------------|---------|--------------|--------------|---------------|--------|
|                | (MHz)     | (dBuV/<br>m) | dB/m    | (dBuV/<br>m) | (dBuV/<br>m) | (dB)          |        |
| V              | 1559.5    | 65.79        | -13     | 53.29        | 74           | -20.71        | Pk     |
| V              | 1559.5    | 54.1         | -13     | 41.6         | 54           | -12.4         | AV     |
| V              | 2077.2    | 60.67        | -10     | 50.49        | 74           | -23.51        | Pk     |
| V              | 2077.2    | 49.98        | -10     | 39.8         | 54           | -14.2         | AV     |
| V              | 3114.2    | 58.73        | -8.1    | 50.6         | 74           | -23.4         | Pk     |
| V              | 3114.2    | 48.33        | -8.1    | 40.2         | 54           | -13.8         | AV     |
| H              | 1559.5    | 68.23        | -13     | 55.73        | 74           | -18.27        | Pk     |
| H              | 1559.5    | 55.3         | -13     | 42.8         | 54           | -11.2         | AV     |
| H              | 1872.2    | 59.96        | -11     | 49.05        | 74           | -24.95        | Pk     |
| H              | 1872.2    | 49.31        | -11     | 38.4         | 54           | -15.6         | AV     |
| H              | 3119.8    | 57.5         | -8.1    | 49.39        | 74           | -24.61        | Pk     |
| H              | 3119.8    | 46.01        | -8.1    | 37.9         | 54           | -16.1         | AV     |

Remark:

Emission Level = Read Level+Antenna Factor + Cable Loss - Amplifier.


Margin= Emission Level-Limits

Note:

1. Measuring frequencies from 1 GHz to 13GHz.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode of the emission shown in Actual FS column.
3. The frequency that above 3GHz is mainly from the environment noise

#### 4. EUT TEST PHOTO

**Radiated Measurement Photos**



**Conducted Measurement Photos**

