



RADIO TEST REPORT

FCC ID: XN6-SB3821-C6TX

IC: 8819A-SB3821C6TX

Product : 38" Sound Bar 2.1 System

Trade Name : VIZIO

Model Name : SB3821-C6 Soundbar

Serial Model : N/A

Report No. : NTEK-2014NT1119826F1

Prepared for

Zylux Acoustic Corporation
3F, 22, Lane 35, Jihu Road, Taipei Neihu Technology Park, 114 Taipei
Taiwan-R.O.C

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.
1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street
Bao'an District, Shenzhen P.R. China
Tel.: +86-0755-61156588 Fax.: +86-0755-61156599
Website: www.ntek.org.cn

TEST RESULT CERTIFICATION

Applicant's name : Zylux Acoustic Corporation
Address : 3F,22,Lane 35,Jihu Road,Taipei NeiHu Technology Park,
 114 Taipei Taiwan-R.O.C
Manufacture's Name..... : Zhao Yang Electronic(Shenzhen)Co., Ltd.
Address : Sec.A, 4F, Building 1&2, De Yong Jia Ind. Park, GuangQiao Rd.
 Yu Lv Com., GongMing St. 518100 Guang Ming New Distr.,
 Shenzhen, China

Product description

Product name : 38"Sound Bar 2.1 System
Model and/or type reference : SB3821-C6 Soundbar
Serial Model : N/A


Standards : FCC Part15.247:01 Oct. 2014
 IC RSS-210,Issue 8, December 2010

Test procedure ANSI C63.4-2003
 RSS-Gen ISSUE 4 November 2014


This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements/ the Industry Canada requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personal only, and shall be noted in the revision of the document.

Date of Test :
Date (s) of performance of tests : 19 Nov. 2014 ~28 Nov. 2014
Date of Issue..... : 28 Nov. 2014
Test Result..... : **Pass**

Testing Engineer : 

 Denny Huang

Technical Manager : 

 (Brown Lu)

Authorized Signatory : 

 (Bill Yao)

Table of Contents

	Page
1 . SUMMARY OF TEST RESULTS	5
1.1 TEST FACILITY	6
1.2 MEASUREMENT UNCERTAINTY	6
2 . GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 DESCRIPTION OF TEST MODES	9
2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	9
2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	10
2.5 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	11
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS	12
3 . EMC EMISSION TEST	13
3.1 CONDUCTED EMISSION MEASUREMENT	13
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	13
3.1.2 TEST PROCEDURE	14
3.1.3 DEVIATION FROM TEST STANDARD	14
3.1.4 TEST SETUP	14
3.1.5 EUT OPERATING CONDITIONS	14
3.1.6 TEST RESULTS	15
3.2 RADIATED EMISSION MEASUREMENT	19
3.2.1 RADIATED EMISSION LIMITS	19
3.2.2 TEST PROCEDURE	20
3.2.3 DEVIATION FROM TEST STANDARD	20
3.2.4 TEST SETUP	21
3.2.5 EUT OPERATING CONDITIONS	22
3.2.6 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)	23
3.2.7 TEST RESULTS (ABOVE 1000 MHZ)	27
4 . NUMBER OF HOPPING CHANNEL	30
4.1 APPLIED PROCEDURES / LIMIT	30
4.1.1 TEST PROCEDURE	30
4.1.2 DEVIATION FROM STANDARD	30
4.1.3 TEST SETUP	30
4.1.4 EUT OPERATION CONDITIONS	30
4.1.5 TEST RESULTS	31
5 . AVERAGE TIME OF OCCUPANCY	32
5.1 APPLIED PROCEDURES / LIMIT	32
5.1.1 TEST PROCEDURE	32

Table of Contents

	Page
5.1.2 DEVIATION FROM STANDARD	32
5.1.3 TEST SETUP	33
5.1.4 EUT OPERATION CONDITIONS	33
5.1.5 TEST RESULTS	34
6 . HOPPING CHANNEL SEPARATION MEASUREMENT	40
6.1 APPLIED PROCEDURES / LIMIT	40
6.1.1 TEST PROCEDURE	40
6.1.2 DEVIATION FROM STANDARD	40
6.1.3 TEST SETUP	40
6.1.4 EUT OPERATION CONDITIONS	40
6.1.5 TEST RESULTS	41
7 . BANDWIDTH TEST	47
7.1 APPLIED PROCEDURES / LIMIT	47
7.1.1 TEST PROCEDURE	47
7.1.2 DEVIATION FROM STANDARD	47
7.1.3 TEST SETUP	47
7.1.4 EUT OPERATION CONDITIONS	47
7.1.5 TEST RESULTS	48
8 . PEAK OUTPUT POWER TEST	54
8.1 APPLIED PROCEDURES / LIMIT	54
8.1.1 TEST PROCEDURE	54
8.1.2 DEVIATION FROM STANDARD	54
8.1.3 TEST SETUP	54
8.1.4 EUT OPERATION CONDITIONS	54
8.1.5 TEST RESULTS	55
9 . 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	61
9.1 DEVIATION FROM STANDARD	61
9.2 TEST SETUP	61
9.3 EUT OPERATION CONDITIONS	61
9.4 TEST RESULTS	62
10 . ANTENNA REQUIREMENT	69
10.1 STANDARD REQUIREMENT	69
10.2 EUT ANTENNA	69
11 . EUT TEST PHOTO	70
APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C/ RSS-210 Annex 8			
Standard Section	Test Item	Judgment	Remark
15.207/ RSS-Gen §7.2.4/ RSS-210 §	Conducted Emission	PASS	
15.247(a)(1) / RSS-210 §A8. 2	Hopping Channel Separation	PASS	
15.247(b)(1) / RSS-210 §A8. 4	Peak Output Power	PASS	
15.247(c) / RSS-210 §A8. 5	Radiated Spurious Emission	PASS	
15.247(a)(iii) / RSS-210 §A8. 1	Number of Hopping Frequency	PASS	
15.247(a)(iii) / RSS-210 §A8. 1	Dwell Time	PASS	
15.247(a)(1) / RSS-210 §A8. 1	Bandwidth	PASS	
15.205/ RSS-210 §A8. 5	Band Edge Emission	PASS	
15.203/ RSS-Gen §7.1.2	Antenna Requirement	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

1.1 TEST FACILITY

NTEK Testing Technology Co., Ltd

Add. : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen P.R. China.

FCC Registration No.:238937; IC Registration No.:9270A-1

CNAS Registration No.:L5516

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power,conducted	$\pm 0.16\text{dB}$
3	Spurious emissions,conducted	$\pm 0.21\text{dB}$
4	All emissions,radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	38"Sound Bar 2.1 System	
Trade Name	VIZIO	
Model Name	SB3821-C6 Soundbar	
Serial Model	N/A	
Model Difference	N/A	
Product Description	The EUT is a 38"Sound Bar 2.1 System	
	Operation Frequency:	2402~2480 MHz
	Modulation Type:	BT(1Mbps): GFSK BT EDR(2Mbps): $\pi/4$ -DQPSK BT EDR(3Mbps): 8-DPSK
	Bit Rate of Transmitter	1Mbps/2Mbps/3Mbps
	Number Of Channel	79 CH
	Antenna Designation:	Please see Note 3.
Channel List	Please refer to the Note 2.	
Adapter	Adapter 1: main test Adapter 2: Deputy test	
Battery	N/A	
Connecting I/O Port(s)	Please refer to the User's Manual	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

3.

Table for Filed Antenna

Ant	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	N/A	PCB Antenna	N/A	1.0	BT Antenna

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	CH00
Mode 2	CH39
Mode 3	CH78
Mode 4	Keeping TX mode

For Conducted Emission	
Final Test Mode	Description
Mode 4	Keeping TX mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	CH00
Mode 2	CH39
Mode 3	CH78

Note:


- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The EUT use new battery.
- (3)The data rate was set in 1Mbps for radiated emission due to the highest RF output power.

2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS

Test software Version	Test program: Broadcom		
Frequency	2402 MHz	2441 MHz	2480 MHz
Parameters(1/2/3Mbps)	DEF	DEF	DEF

2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



2.5 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	38"Sound Bar 2.1 System	VIZIO	SB3821-C6 Soundbar	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2014.07.06	2015.07.05	1 year
2	Test Receiver	R&S	ESPI	101318	2014.06.07	2015.06.06	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2014.07.06	2015.07.05	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2014.06.07	2015.06.06	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2014.06.07	2015.06.06	1 year
6	Horn Antenna	EM	EM-AH-10180	2011071402	2014.07.06	2015.07.05	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2014.07.06	2015.07.05	1 year
8	Amplifier	EM	EM-30180	060538	2013.12.22	2014.12.21	1 year
9	Loop Antenna	ARA	PLA-1030/B	1029	2014.06.08	2015.06.07	1 year
10	Power Meter	R&S	NRVS	100696	2014.07.06	2015.07.05	1 year
11	Power Sensor	R&S	URV5-Z4	0395.1619.05	2014.07.06	2015.07.05	1 year

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2014.06.06	2015.06.05	1 year
2	LISN	R&S	ENV216	101313	2014.08.24	2015.08.23	1 year
3	LISN	EMCO	3816/2	00042990	2014.08.24	2015.08.23	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2014.06.07	2015.06.06	1 year
5	Passive Voltage Probe	R&S	ESH2-Z3	100196	2014.06.07	2015.06.06	1 year
6	Absorbing clamp	R&S	MOS-21	100423	2014.06.08	2015.06.07	1 year

1	Attenuation	MCE	24-10-34	BN9258	2014.06.08	2015.06.07	1 year
---	-------------	-----	----------	--------	------------	------------	--------

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC/ RSS-210
0.50 -5.0	73.00	60.00	56.00	46.00	FCC/ RSS-210
5.0 -30.0	73.00	60.00	60.00	50.00	FCC/ RSS-210

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.


3.1.6 TEST RESULTS

EUT :	38"Sound Bar 2.1 System	Model Name :	SB3821-C6 Soundbar
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	L
Test Voltage :	AC 120V/60Hz- Adapter 1	Test Mode :	Mode 4

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.4139	34.42	9.45	43.87	57.57	-13.7	QP
0.4139	25.90	9.45	35.35	47.57	-12.22	AVG
0.5140	34.23	9.47	43.70	56.00	-12.30	QP
0.5140	30.10	9.47	39.57	46.00	-6.43	AVG
1.0260	28.10	9.46	37.56	56.00	-18.44	QP
1.0260	20.97	9.46	30.43	46.00	-15.57	AVG
2.0459	25.37	9.46	34.83	56.00	-21.17	QP
2.0459	15.57	9.46	25.03	46.00	-20.97	AVG
6.1459	22.16	9.45	31.61	60.00	-28.39	QP
6.1459	16.35	9.45	25.80	50.00	-24.20	AVG
27.6499	27.23	9.91	37.14	60.00	-22.86	QP
27.6499	21.80	9.91	31.71	50.00	-18.29	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	38"Sound Bar 2.1 System	Model Name :	SB3821-C6 Soundbar
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	N
Test Voltage :	AC 120V/60Hz- Adapter 1	Test Mode :	Mode 4

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.1580	42.10	9.61	51.71	65.56	-13.85	QP
0.1580	25.58	9.61	35.19	55.56	-20.37	AVG
0.4179	32.37	9.45	41.82	57.49	-15.67	QP
0.4179	24.21	9.45	33.66	47.49	-13.83	AVG
0.5140	32.01	9.47	41.48	56.00	-14.52	QP
0.5140	28.62	9.47	38.09	46.00	-7.91	AVG
1.0260	26.47	9.46	35.93	56.00	-20.07	QP
1.0260	19.05	9.46	28.51	46.00	-17.49	AVG
6.1459	22.62	9.45	32.07	60.00	-27.93	QP
6.1459	15.82	9.45	25.27	50.00	-24.73	AVG
27.6499	28.08	9.91	37.99	60.00	-22.01	QP
27.6499	21.81	9.91	31.72	50.00	-18.28	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	38"Sound Bar 2.1 System	Model Name :	SB3821-C6 Soundbar
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	L
Test Voltage :	AC 120V/60Hz- Adapter 2	Test Mode :	Mode 4

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1580	42.74	9.61	52.35	65.56	-13.21	QP
0.1580	24.36	9.61	33.97	55.56	-21.59	AVG
0.4020	37.17	9.45	46.62	57.81	-11.19	QP
0.4020	27.24	9.45	36.69	47.81	-11.12	AVG
0.5140	30.95	9.47	40.42	56.00	-15.58	QP
0.5140	23.38	9.47	32.85	46.00	-13.15	AVG
1.0260	27.37	9.46	36.83	56.00	-19.17	QP
1.0260	17.31	9.46	26.77	46.00	-19.23	AVG
3.0739	24.07	9.45	33.52	56.00	-22.48	QP
3.0739	17.44	9.45	26.89	46.00	-19.11	AVG
27.6497	29.46	9.91	39.37	60.00	-20.63	QP
27.6497	24.69	9.91	34.60	50.00	-15.40	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	38"Sound Bar 2.1 System	Model Name :	SB3821-C6 Soundbar
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	N
Test Voltage :	AC 120V/60Hz- Adapter 2	Test Mode :	Mode 4

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1580	43.53	9.61	53.14	65.56	-12.42	QP
0.1580	25.50	9.61	35.11	55.56	-20.45	AVG
0.4099	35.07	9.45	44.52	57.65	-13.13	QP
0.4099	26.29	9.45	35.74	47.65	-11.91	AVG
0.5100	29.44	9.47	38.91	56.00	-17.09	QP
0.5100	22.60	9.47	32.07	46.00	-13.93	AVG
0.7539	26.19	9.45	35.64	56.00	-20.36	QP
0.7539	15.48	9.45	24.93	46.00	-21.07	AVG
3.0739	22.75	9.45	32.20	56.00	-23.80	QP
3.0739	15.70	9.45	25.15	46.00	-20.85	AVG
27.6499	33.43	9.91	43.34	60.00	-16.66	QP
27.6499	26.97	9.91	36.88	50.00	-13.12	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a)/ RSS-210 §2.2& A8.5, then the 15.209(a) / RSS-210 & A8.5 limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C/ RSS-Gen.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average , PEAK DETECTOR IS USED FOR BOTH

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 DEVIATION FROM TEST STANDARD


No deviation

3.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz

**3.2.5 EUT OPERATING CONDITIONS**

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


3.2.6 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)

EUT :	38"Sound Bar 2.1 System	Model Name :	SB3821-C6 Soundbar
Temperature :	20 °C	Relative Humidity :	48%
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz- Adapter 1
Test Mode :	TX		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	39.8542	18.77	13.63	32.40	40.00	-7.60	QP
V	46.0164	18.38	11.67	30.05	40.00	-9.95	QP
V	135.0319	18.48	11.65	30.13	43.50	-13.37	QP
V	173.8135	20.59	10.58	31.17	43.50	-12.33	QP
V	324.456	18.19	15.18	33.37	46.00	-12.63	QP
V	348.0274	19.94	16.16	36.10	46.00	-9.90	QP

Remark:


Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	107.8876	20.09	9.74	29.83	43.50	-13.67	QP
H	173.8135	26.58	10.58	37.16	43.50	-6.34	QP
H	180.0165	24.91	10.63	35.54	43.50	-7.96	QP
H	324.4561	21.34	15.18	36.52	46.00	-9.48	QP
H	348.0274	25.78	16.16	41.94	46.00	-4.06	QP
H	372.0045	18.36	17.16	35.52	46.00	-10.48	QP

Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit




EUT :	38"Sound Bar 2.1 System	Model Name :	SB3821-C6 Soundbar
Temperature :	20 °C	Relative Humidity :	48%
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz- Adapter 2
Test Mode :	TX		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	36.0007	19.34	16.06	35.40	40.00	-4.60	QP
V	46.0162	17.96	11.67	29.63	40.00	-10.37	QP
V	59.8588	21.92	7.87	29.79	40.00	-10.21	QP
V	155.9101	16.84	10.45	27.29	43.50	-16.21	QP
V	196.5098	18.28	10.75	29.03	43.50	-14.47	QP
V	348.0274	14.21	16.16	30.37	46.00	-15.63	QP

Remark:


Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	59.8588	16.67	7.87	24.54	40.00	-15.46	QP
H	108.6470	19.82	9.81	29.63	43.50	-13.87	QP
H	173.8135	24.85	10.58	35.43	43.50	-8.07	QP
H	260.1444	19.64	13.70	33.34	46.00	-12.66	QP
H	316.5890	18.93	14.85	33.78	46.00	-12.22	QP
H	348.0274	16.73	16.16	32.89	46.00	-13.11	QP

Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit



3.2.7 TEST RESULTS (ABOVE 1000 MHZ)

EUT :	38"Sound Bar 2.1 System	Model Name :	SB3821-C6 Soundbar
Temperature :	20 °C	Relative Humidity :	48%
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz- Adapter 1
Test Mode :	TX		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Remark	Comment
Low Channel (2402 MHz)-Above 1G							
4804.113	58.92	-3.64	55.28	74.00	-18.72	Pk	Vertical
4804.113	41.15	-3.64	37.51	54.00	-16.49	AV	Vertical
7206.236	52.03	-0.95	51.08	74.00	-22.92	Pk	Vertical
7206.236	37.09	-0.95	36.14	54.00	-17.86	AV	Vertical
4804.302	59.26	-3.64	55.62	74.00	-18.38	Pk	Horizontal
4804.302	41.09	-3.64	37.45	54.00	-16.55	AV	Horizontal
7206.088	53.33	-0.95	52.38	74.00	-21.62	Pk	Horizontal
7206.088	37.02	-0.95	36.07	54.00	-17.93	AV	Horizontal
Mid Channel (2441 MHz)-Above 1G							
4882.148	59.02	-3.68	55.34	74.00	-18.66	Pk	Vertical
4882.148	39.43	-3.68	35.75	54.00	-18.25	AV	Vertical
7323.206	55.49	-0.82	54.67	74.00	-19.33	Pk	Vertical
7323.206	40.32	-0.82	39.50	54.00	-14.50	AV	Vertical
4882.077	58.02	-3.68	54.34	74.00	-19.66	Pk	Horizontal
4882.077	39.16	-3.68	35.48	54.00	-18.52	AV	Horizontal
7323.148	55.39	-0.82	54.57	74.00	-19.43	Pk	Horizontal
7323.148	39.57	-0.82	38.75	54.00	-15.25	AV	Horizontal
High Channel (2480 MHz)- Above 1G							
4960.326	59.05	-3.59	55.46	74.00	-18.54	Pk	Vertical
4960.326	41.89	-3.59	38.30	54.00	-15.70	AV	Vertical
7440.091	53.52	-0.68	52.84	74.00	-21.16	Pk	Vertical
7440.091	37.76	-0.68	37.08	54.00	-16.92	AV	Vertical
4960.126	57.88	-3.59	54.29	74.00	-19.71	Pk	Horizontal
4960.126	40.05	-3.59	36.46	54.00	-17.54	AV	Horizontal
7440.254	53.39	-0.68	52.71	74.00	-21.29	Pk	Horizontal
7440.254	37.25	-0.68	36.57	54.00	-17.43	AV	Horizontal

Remark: "1Mbps" mode is the worst mode.

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Emission Level = Meter Reading + Factor

Margin = Emission Level- Limit

EUT :	38"Sound Bar 2.1 System	Model Name :	SB3821-C6 Soundbar
Temperature :	20 °C	Relative Humidity :	48%
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz- Adapter 2
Test Mode :	TX		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark	Comment
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		
Low Channel (2402 MHz)-Above 1G							
4804.263	58.67	-3.64	55.03	74.00	-18.97	Pk	Vertical
4804.263	40.95	-3.64	37.31	54.00	-16.69	AV	Vertical
7206.145	51.78	-0.95	50.83	74.00	-23.17	Pk	Vertical
7206.145	36.84	-0.95	35.89	54.00	-18.11	AV	Vertical
4804.206	59.01	-3.64	55.37	74.00	-18.63	Pk	Horizontal
4804.206	40.84	-3.64	37.20	54.00	-16.80	AV	Horizontal
7206.112	53.08	-0.95	52.13	74.00	-21.87	Pk	Horizontal
7206.112	36.77	-0.95	35.82	54.00	-18.18	AV	Horizontal
Mid Channel (2441 MHz)-Above 1G							
4882.306	59.27	-3.68	55.59	74.00	-18.41	Pk	Vertical
4882.306	39.68	-3.68	36.00	54.00	-18.00	AV	Vertical
7323.174	55.74	-0.82	54.92	74.00	-19.08	Pk	Vertical
7323.174	40.57	-0.82	39.75	54.00	-14.25	AV	Vertical
4882.185	58.27	-3.68	54.59	74.00	-19.41	Pk	Horizontal
4882.185	39.41	-3.68	35.73	54.00	-18.27	AV	Horizontal
7323.098	55.64	-0.82	54.82	74.00	-19.18	Pk	Horizontal
7323.098	39.82	-0.82	39.00	54.00	-15.00	AV	Horizontal
High Channel (2480 MHz)- Above 1G							
4960.147	58.81	-3.59	55.22	74.00	-18.78	Pk	Vertical
4960.147	41.64	-3.59	38.05	54.00	-15.95	AV	Vertical
7440.185	53.27	-0.68	52.59	74.00	-21.41	Pk	Vertical
7440.185	37.51	-0.68	36.83	54.00	-17.17	AV	Vertical
4960.035	57.63	-3.59	54.04	74.00	-19.96	Pk	Horizontal
4960.035	39.82	-3.59	36.23	54.00	-17.77	AV	Horizontal
7440.148	53.14	-0.68	52.46	74.00	-21.54	Pk	Horizontal
7440.148	37.06	-0.68	36.38	54.00	-17.62	AV	Horizontal

Remark:"1Mbps" mode is the worst mode.

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Emission Level = Meter Reading + Factor

Margin = Emission Level- Limit

Radiated band edge:

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
1Mbps(Non-FHSS) CH00							
2390	55.86	-13.06	42.80	74.00	-31.20	peak	Vertical
2390	56.99	-13.06	43.93	74.00	-30.07	peak	Horizontal
1Mbps(Non-FHSS) CH78							
2483.5	55.97	-12.78	43.19	74.00	-30.81	peak	Vertical
2483.5	58.05	-12.78	45.27	74.00	-28.73	peak	Horizontal
2Mbps(Non-FHSS) CH00							
2390	58.19	-13.06	45.13	74.00	-28.87	peak	Vertical
2390	56.55	-13.06	43.49	74.00	-30.51	peak	Horizontal
2Mbps(Non-FHSS) CH78							
2483.5	59.05	-12.78	46.27	74.00	-27.73	peak	Vertical
2483.5	58.36	-12.78	45.58	74.00	-28.42	peak	Horizontal
3Mbps(Non-FHSS) CH00							
2390	58.63	-13.06	45.57	74.00	-28.43	peak	Vertical
2390	57.79	-13.06	44.73	74.00	-29.27	peak	Horizontal
3Mbps(Non-FHSS) CH78							
2483.5	57.61	-12.78	44.83	74.00	-29.17	peak	Vertical
2483.5	58.46	-12.78	45.68	74.00	-28.32	peak	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
1Mbps(FHSS)							
2390	57.44	-13.06	44.38	74.00	-29.62	peak	Vertical
2390	58.57	-13.06	45.51	74.00	-28.49	peak	Horizontal
2483.5	56.32	-12.78	43.54	74.00	-30.46	peak	Vertical
2483.5	58.63	-12.78	45.85	74.00	-28.15	peak	Horizontal
2Mbps(FHSS)							
2390	55.92	-13.06	42.86	74.00	-31.14	peak	Vertical
2390	57.23	-13.06	44.17	74.00	-29.83	peak	Horizontal
2483.5	57.73	-12.78	44.95	74.00	-29.05	peak	Vertical
2483.5	56.05	-12.78	43.27	74.00	-30.73	peak	Horizontal
3Mbps(FHSS)							
2390	57.52	-13.06	44.46	74.00	-29.54	peak	Vertical
2390	57.73	-13.06	44.67	74.00	-29.33	peak	Horizontal
2483.5	56.48	-12.78	43.70	74.00	-30.30	peak	Vertical
2483.5	59.38	-12.78	46.60	74.00	-27.40	peak	Horizontal

NOTE: When the result(PK) less than AV limite,not record AV result.

4. NUMBER OF HOPPING CHANNEL

4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C/ RSS-210				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(1)(iii)/ RSS-210 §A8. 1	Number of Hopping Channel	≥15	2400-2483.5	PASS

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	= the frequency band of operation
RB	RBW=100kHz
VB	VBW ≥ RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 100kHz, VBW=100kHz, Sweep time = Auto.

4.1.2 DEVIATION FROM STANDARD

No deviation.

4.1.3 TEST SETUP




4.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

4.1.5 TEST RESULTS

EUT :	38"Sound Bar 2.1 System	Model Name :	SB3821-C6 Soundbar
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	Hopping Mode		

Number of Hopping Channel	79
---------------------------	----



5. AVERAGE TIME OF OCCUPANCY

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C/ RSS-210				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(1)(iii)/ RSS-210 §A8. 1	Average Time of Occupancy	0.4sec	2400-2483.5	PASS

5.1.1 TEST PROCEDURE

- The transmitter output (antenna port) was connected to the spectrum analyzer
- Set RBW of spectrum analyzer to 1MHz and VBW to 1MHz.
- Use a video trigger with the trigger level set to enable triggering only on full pulses.
- Sweep Time is more than once pulse time.
- Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- Measure the maximum time duration of one single pulse.
- Set the EUT for DH5, DH3 and DH1 packet transmitting.
- Measure the maximum time duration of one single pulse.
- A Period Time = (channel number)*0.4
 DH1 Time Slot: Reading * (1600/2)*31.6/(channel number)
 DH3 Time Slot: Reading * (1600/4)*31.6/(channel number)
 DH5 Time Slot: Reading * (1600/6)*31.6/(channel number)

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP




5.1.4 EUT OPERATION CONDITIONS



The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

5.1.5 TEST RESULTS

EUT :	38"Sound Bar 2.1 System	Model Name :	SB3821-C6 Soundbar
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	CH39-DH5 ,2DH5,3DH5		


Data Packet	Frequency	Pulse Duration	Dwell Time	Limits
		(ms)	(s)	(s)
DH5	2441 MHz	2.92	0.31	0.4
2DH5	2441 MHz	2.93	0.31	0.4
3DH5	2441 MHz	2.97	0.32	0.4







EUT :	38"Sound Bar 2.1 System	Model Name :	SB3821-C6 Soundbar
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	CH39-DH3,2DH3,3DH3		


Data Packet	Frequency	Pulse Duration	Dwell Time	Limits
		(ms)	(s)	(s)
DH3	2441 MHz	1.68	0.27	0.4
2DH3	2441 MHz	1.70	0.27	0.4
3DH3	2441 MHz	1.70	0.27	0.4







EUT :	38"Sound Bar 2.1 System	Model Name :	SB3821-C6 Soundbar
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	CH39-DH1,2DH1,3DH1		

Data Packet	Frequency	Pulse Duration	Dwell Time	Limits
		(ms)	(s)	(s)
DH1	2441 MHz	0.40	0.13	0.4
2DH1	2441 MHz	0.43	0.14	0.4
3DH1	2441 MHz	0.43	0.14	0.4





6. HOPPING CHANNEL SEPARATION MEASUREMENT

6.1 APPLIED PROCEDURES / LIMIT

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	30 kHz (Channel Separation)
VB	100 kHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


6.1.1 TEST PROCEDURE

- The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
- The resolution bandwidth of 30 kHz and the video bandwidth of 100 kHz were utilised for channel separation measurement.

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS


The EUT was programmed to be in continuously transmitting mode.



6.1.5 TEST RESULTS

EUT :	38"Sound Bar 2.1 System	Model Name :	SB3821-C6 Soundbar
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	CH00 / CH39 /CH78 (1Mbps Mode)		

Frequency	Ch. Separation (MHz)	Result
2402 MHz	1.000	Complies
2441 MHz	1.000	Complies
2480 MHz	1.000	Complies

Ch. Separation Limits: >20dB bandwidth








EUT :	38"Sound Bar 2.1 System	Model Name :	SB3821-C6 Soundbar
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	CH00 / CH39 /CH78 (2Mbps Mode)		

Frequency	Ch. Separation (MHz)	Result
2402 MHz	1.000	Complies
2441 MHz	1.000	Complies
2480 MHz	1.000	Complies

Ch. Separation Limits: >2/3 of 20dB bandwidth








EUT :	38"Sound Bar 2.1 System	Model Name :	SB3821-C6 Soundbar
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	CH00 / CH39 /CH78 (3Mbps Mode)		

Frequency	Ch. Separation (MHz)	Result
2402 MHz	1.000	Complies
2441 MHz	1.000	Complies
2480 MHz	1.000	Complies

Ch. Separation Limits: >2/3 of 20dB bandwidth





7. BANDWIDTH TEST

7.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C/ RSS-210				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(1)/ RSS-210§A8. 1	Bandwidth	(20dB bandwidth)	2400-2483.5	PASS

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	30 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


7.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 30KHz, VBW=100KHz, Sweep time = Auto.

7.1.2 DEVIATION FROM STANDARD

No deviation.

7.1.3 TEST SETUP




7.1.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

7.1.5 TEST RESULTS

EUT :	38"Sound Bar 2.1 System	Model Name :	SB3821-C6 Soundbar
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	CH00 / CH39 /C78(1Mbps)		


Frequency	20dB Bandwidth (kHz)	99% Bandwidth (kHz)	Result
2402 MHz	823.593	796.925	PASS
2441 MHz	817.554	798.587	PASS
2480 MHz	822.866	815.522	PASS






EUT :	38"Sound Bar 2.1 System	Model Name :	SB3821-C6 Soundbar
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	CH00 / CH39 /C78(2Mbps)		


Frequency	20dB Bandwidth (MHz)	99% Bandwidth (MHz)	Result
2402 MHz	1.156	1.097	PASS
2441 MHz	1.152	1.105	PASS
2480 MHz	1.154	1.101	PASS






EUT :	38"Sound Bar 2.1 System	Model Name :	SB3821-C6 Soundbar
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	CH00 / CH39 /C78(3Mbps)		

Frequency	20dB Bandwidth (MHz)	99% Bandwidth (MHz)	Result
2402 MHz	1.121	1.076	PASS
2441 MHz	1.121	1.075	PASS
2480 MHz	1.124	1.083	PASS





8. PEAK OUTPUT POWER TEST

8.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C/ RSS-210				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(i) / RSS-210§A8. 4	Peak Output Power	0.125 w or 20.96dBm	2400-2483.5	PASS

8.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW > the 20 dB bandwidth of the emission being measured
 Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
 VBW ≥ RBW
 Sweep = auto
 Detector function = peak
 Trace = max hold

8.1.2 DEVIATION FROM STANDARD

No deviation.

8.1.3 TEST SETUP




8.1.4 EUT OPERATION CONDITIONS



The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


8.1.5 TEST RESULTS



EUT :	38"Sound Bar 2.1 System	Model Name :	SB3821-C6 Soundbar
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	CH00/ CH39 /CH78 (1M/2M/3Mbps Mode)		


1Mbps			
Test Channel	Frequency (MHz)	Peak Output Power (dBm)	LIMIT (dBm)
CH00	2402	3.98	30
CH39	2441	4.94	30
CH78	2480	4.70	30
2Mbps			
CH00	2402	4.02	30
CH39	2441	4.66	30
CH78	2480	4.56	30
3Mbps			
CH00	2402	3.42	30
CH39	2441	4.25	30
CH78	2480	4.17	30















9. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE

APPLICABLE STANDARD

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

TEST PROCEDURE

- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- Repeat above procedures until all measured frequencies were complete.

9.1 DEVIATION FROM STANDARD

No deviation.

9.2 TEST SETUP



9.3 EUT OPERATION CONDITIONS



The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

9.4 TEST RESULTS



EUT :	38"Sound Bar 2.1 System	Model Name :	SB3821-C6 Soundbar
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	CH00/ CH78 (1M/2M/3Mbps Mode)		



Frequency Band	Delta Peak to band emission (dBc)	> Limit (dBc)	Result
1Mbps Non-hopping			
Left-band	61.25	20	Pass
Right-band	67.89	20	Pass
2Mbps Non-hopping			
Left-band	53.03	20	Pass
Right-band	58.29	20	Pass
3Mbps Non-hopping			
Left-band	48.60	20	Pass
Right-band	58.61	20	Pass
1Mbps hopping			
Left-band	65.08	20	Pass
Right-band	69.50	20	Pass
2Mbps hopping			
Left-band	62.10	20	Pass
Right-band	66.46	20	Pass
3Mbps hopping			
Left-band	63.05	20	Pass
Right-band	69.17	20	Pass



BDR mode (GFSK): Band Edge-Left Side





BDR mode (GFSK): Band Edge-Right Side





EDR mode ($\pi/4$ -DQPSK): Band Edge-Left Side


EDR mode ($\pi/4$ -DQPSK): Band Edge-Right Side


EDR mode(8DPSK): Band Edge-Left Side



EDR mode(8DPSK): Band Edge-Right Side



10. ANTENNA REQUIREMENT

10.1 STANDARD REQUIREMENT



15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

10.2 EUT ANTENNA

The EUT antenna is PCB Antenna. It comply with the standard requirement.

11. EUT TEST PHOTO

Radiated Measurement Photos



CONDUCTED EMISSION Photos

