

FCC Part 15, Subpart C Test Report

FCC ID: XN6-SL714PW1006

Applicant: Zylux Acoustic Corporation

Address: 7F, 70, Rui Guang Road, Neihu District, Taipei 114, Taiwan, Chinese Taipei

Manufacturer: VIZIO INC.

Address: 39 Tesla, Irvine, CA 92618, USA

Product: 7.1.4 Soundbar System

Brand **VIZIO**

Test Model(s): SL714PW-1006

Series Model(s): N/A

Test Date: Nov. 20, 2025 ~ Dec. 02, 2025

Issued Date: Dec. 03, 2025

Issued By: Hwa-Hsing (Dongguan) Testing Co., Ltd.

Address: No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, HuangJiang Town, Dongguan City, People's Republic of China


Test Firm Registration No.: 915896

Designation No.: CN1255

Standards: FCC CFR 47 Part 2, Subpart J
FCC CFR 47 Part 15, Subpart C

The above equipment has been tested by **Hwa-Hsing (Dongguan) Testing Co., Ltd.**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :



Aaron Xiao

Reviewed by :



Approved by :



Scott He

"This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. Our report includes all the tests requested by you and the results thereof based upon the information that you provided to us. The report would be invalid without specific stamp of test institute and the signatures of tester and approver."

Lab: [Hwa-Hsing \(Dongguan\) Testing Co., Ltd.](#)Address: [No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, HuangJiang Town, Dongguan City, People's Republic of China](#)Tel: [0769-85598986](#)Web.: [www.lyns-tci.com](#)E-Mail: [service-hs@lyns-tci.com](#)Release
Ver. 1.5

Table of Contents

Release Control Record	4
1. Summary of Test Results	5
1.1 Measurement Uncertainty	5
1.2 Modification Record	5
2. General Information	6
2.1 General Description of EUT	6
2.2 Description of Test Channels	7
2.3 Test Mode Applicability and Tested Channel Detail	7
2.4 Description of Support Units	9
2.5 Configuration of System under Test	9
3. Test Types and Results	10
3.1 Radiated Emission and Band-edge Measurement	10
3.1.1 Limits of radiated emission and band-edge measurement	10
3.1.2 Test Instruments	11
3.1.3 Test Procedures	12
3.1.4 Deviation from Test Standard	13
3.1.5 Test Setup	14
3.1.6 EUT Operating Conditions	15
3.1.7 Test Results	16
3.2 Conducted Emission Measurement	28
3.2.1 Limits of Conducted Emission Measurement	28
3.2.2 Test Instruments	28
3.2.3 Test Procedures	29
3.2.4 Test Setup	29
3.2.5 EUT Operating Condition	29
3.2.6 Deviation from Test Standard	29
3.2.7 Test Results	30
3.3 6dB Bandwidth Measurement	32
3.3.1 Limits of 6dB Bandwidth Measurement	32
3.3.2 Test Setup	32
3.3.3 Test Instruments	32
3.3.4 Test Procedure	33
3.3.5 Deviation from Test Standard	33
3.3.6 EUT Operating Conditions	33
3.3.7 Test Result	34
3.4 Occupied Bandwidth Measurement	38
3.4.1 Test Setup	38
3.4.2 Test Instruments	38
3.4.3 Test Procedure	38
3.4.4 Deviation from Test Standard	38
3.4.5 EUT Operating Conditions	38
3.4.6 Test Results	39
3.5 Conducted Output Power Measurement	43
3.5.1 Limits of Conducted Output Power Measurement	43
3.5.2 Test Setup	43
3.5.3 Test Instruments	43
3.5.4 Test Procedures	43
3.5.5 Deviation from Test Standard	45
3.5.6 EUT Operating Conditions	45
3.5.7 Test Results	46
3.6 Power Spectral Density Measurement	50

Test Report No.: 25052101-2-RF-US-02

3.6.1	Limits of Power Spectral Density Measurement.....	50
3.6.2	Test Setup	50
3.6.3	Test Instruments	50
3.6.4	Test Procedure	51
3.6.5	Deviation from Test Standard.....	51
3.6.6	EUT Operating Condition	51
3.6.7	Test Results.....	52
3.7	Conducted Out of Band Emission Measurement	56
3.7.1	Limits of Conducted Out of Band Emission Measurement.....	56
3.7.2	Test Setup	56
3.7.3	Test Instruments	56
3.7.4	Test Procedure	57
3.7.5	Deviation from Test Standard.....	57
3.7.6	EUT Operating Condition	57
3.7.7	Test results	58
4.	Pictures of Test Arrangements	69
5.	Test Instruments.....	70
Appendix	- Information on The Testing Laboratories.....	71

Test Report No.: 25052101-2-RF-US-02

Release Control Record

Issue No.	Description	Date Issued
25052101-2-RF-US-02	Original Release	Dec. 03, 2025

1. Summary of Test Results

FCC CFR 47 Part 15, Subpart C			
Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	Pass	Meet the requirement of limit.
15.205 & 209	Radiated Emissions	Pass	Meet the requirement of limit.
15.247(d)	Band Edge Measurement	Pass	Meet the requirement of limit.
15.247(d)	Antenna Port Emission	Pass	Meet the requirement of limit.
15.247(a)(2)	6dB Bandwidth	Pass	Meet the requirement of limit.
---	Occupied Bandwidth Measurement	Pass	Reference only
15.247(b)	Conducted power	Pass	Meet the requirement of limit.
15.247(e)	Power Spectral Density	Pass	Meet the requirement of limit.
15.203	Antenna Requirement	Pass	No antenna connector is used. The device is professionally installed
NOTE1: The above test items were tested in accordance with the C63.10 2020 standard for all the requirements.			
NOTE2: According to FCC OET KDB 558074, the report use radiated measurements in the restricted frequency bands. In addition, the radiated test is also performed to ensure the emissions emanating from the device cabinet also comply with the applicable limits.			

1.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

The listed uncertainties are the worst cases uncertainty for the entire range of measurement. Please note that the uncertainty values are provided for informational purposes only and are not used in determining the PASS/FAIL results.

Measurement	Frequency	Expanded Uncertainty (k=2) ($\pm$)
Radiated Emissions up to 1 GHz	9KHz ~ 30MHz	2.16 dB
	30MHz ~ 1000MHz	3.56 dB
Radiated Emissions above 1 GHz	1GHz ~ 6GHz	4.71 dB
	6GHz~18GHz	4.84 dB
	18GHz ~ 40GHz	5.73 dB

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

1.2 Modification Record

There were no modifications required for compliance.

2. General Information**2.1 General Description of EUT**

Product(s)	7.1.4 Soundbar System
Test Model(s)	SL714PW-1006
Sample No.	HX25052101-2001
Series Model(s)	N/A
Status of EUT	Engineering Prototype
Power Supply Rating	100-240V~ 50/60 Hz 70W
Modulation Type	GFSK for DTS
Transfer Rate	1 Mbps, 2Mbps
Operating Frequency	1M: 2402 ~ 2480MHz 2M: 2404 ~ 2478MHz
Number of Channel	40 for 1Mbps 37 for 2Mbps
Maximum Output Power	12.83dBm (Peak)
Antenna Type and Antenna Gain	FPC Antenna, 4.39dBi
Antenna Connector	N/A
Accessory Device	150CM: 2 AC standard cables, 170CM: 1 HDMI cable, 250CM: 2 adapters

Note:

1. Please refer to the EUT photo document (Reference No.: 25052101-2-01&02&03) for detailed product photo.
2. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.
3. Hwa-Hsing (Dongguan) Testing Co., Ltd. is not responsible for the accuracy of the information provided by the manufacturer.
4. For the test results, the EUT had been tested with all conditions, and only the worst case was shown in the test report.
5. Product(s) uses certified modules, and its FCC: 2BEK7ATM210

2.2 Description of Test Channels

40 channels are provided to BT-LE (1Mbps):

CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

37 channels are provided to BT-LE (2Mbps):

CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)
-	-	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	-	-	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	-	-

2.3 Test Mode Applicability and Tested Channel Detail

EUT Configure Mode	Applicable test items	X-Axis	Y-Axis	Z-Axis	Voltage Supply
Conducted	AC Power Conducted Emission	N/A	N/A	N/A	AC120V 60Hz
Radiated	Radiated Emissions	√	√	√	
Antenna Port Conducted Measurement	Band Edge Measurement	N/A	N/A	N/A	
	Antenna Port Emission	N/A	N/A	N/A	
	6dB Bandwidth	N/A	N/A	N/A	
	Occupied Bandwidth Measurement	N/A	N/A	N/A	
	Conducted power	N/A	N/A	N/A	
	Power Spectral Density	N/A	N/A	N/A	

- *: The EUT had been pre-tested on the positioned of each 3 Axis. The worst case was found when positioned on **Z-plane**.
- "N/A" means no effect.

Test Condition:

Applicable test items	Environmental Conditions	Test Date	Tested by
Radiated Emissions	24.0deg. C, 55%RH	Nov. 27, 2025	Aron
Antenna Port Conducted Measurement	25.5deg. C, 58%RH	Nov. 23, 2025	Yonah Wu

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.
- Following channel(s) was (were) selected for the final test as listed below.

Radiated Emission Test (Above 1GHz):

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type	Data Rate (Mbps)
-	0 to 39	0,19, 39	GFSK	1
-	1 to 38	1,19, 38	GFSK	2

Radiated Emission Test (Below 1GHz):

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type	Data Rate (Mbps)
-	0 to 39	0,19, 39	GFSK	1
-	1 to 38	1,19, 38	GFSK	2

Power Line Conducted Emission Test:

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type	Data Rate (Mbps)
-	0 to 39	19	GFSK	1
-	1 to 38	19	GFSK	2

Antenna Port Conducted Measurement:

*This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type	Data Rate (Mbps)
-	0 to 39	0,19, 39	GFSK	1
-	1 to 38	1,19, 38	GFSK	2


2.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Product	Brand	Model No.	Serial No.	FCC ID
1	Notebook	HUAWEI	NbD-WFH9	EUEPM21725002655	N/A
2	Notebook	DELL	Inspiron 14R Aluminum Edition	6WPG9-63PV4-RBPF2-T6RHW-W9GBP	N/A

No.	Signal Cable Description of The Above Support Units
1.	USB extension cord: Unshielded, Detachable 1.2m;

2.5 Configuration of System under Test



3. Test Types and Results**3.1 Radiated Emission and Band-edge Measurement****3.1.1 Limits of radiated emission and band-edge measurement**

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3
* DTS emissions in non-restricted frequency bands Subclause 11.11 of ANSI C63.10 is applicable.		
* DTS emissions in restricted frequency bands Subclause 11.12 of ANSI C63.10 is applicable.		

Note:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

3.1.2 Test Instruments

Radiated emission below 30MHz:

Equipment	Manufacturer	Model No.	Serial No.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR7	100962	2026-07-23
3m Semi-anechoic Chamber	MAORUI	9m*6m*6m	HS-2018037	2026-03-13*
Test software	FARAD	FARAD	EZ EMCV1.1.4.2	N/A
Loop Antenna	EMCI	HLA 6121	56735	2026-05-19
Antenna Tower	MF	MFA-440H	NA	NA
Turn Table	MF	MFT-201SS	NA	NA
Antenna Tower&Turn Table Controller	MF	MF-7802	NA	NA

Frequency Range below 1GHz:

Equipment	Manufacturer	Model No.	Serial No.	Next Cal.
EMI Test Receiver (9kHz~3GHz)	Rohde&Schwarz	ESPI 7	101978	2026-07-23
Broadband antenna (25MHz~2500MHz)	Schwarzbeck	VULB 9168	937	2026-07-25
3m Semi-anechoic Chamber	MAORUI	9m*6m*6m	HS-2018037	2026-03-13*
Signal Amplifier (30MHz~1000MHz)	Com-power	PAM-103	18020051	2026-07-23
Attenuator	R&S	TS2GA-6dB	18101101	N/A
Test software	FARAD	EZ EMC V1.1.4.2	N/A	N/A
Broadcast test system	R&S	SFU	100410	2026-07-23
Coaxial cable	N/A	N/A	HS-EMC-100	2025-12-12
Coaxial cable	N/A	N/A	HS-EMC-101/102	2025-12-12

Frequency Range above 1GHz:

Equipment	Manufacturer	Model No.	Serial No.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESPI 7	101978	2026-07-23
3m Semi-anechoic Chamber	MAORUI	9m*6m*6m	HS-2018037	2026-03-13*
Test software	FARAD	EZ EMCV1.1.4.2	N/A	N/A
Digital Multimeter	FLUKE	15B+	43512617WS	2026-07-28
Horn Antenna	Schwarzbeck	BBHA 9120 D	1959	2026-08-02
Spectrum Analyzer	Rohde&Schwarz	FSV-40N	101783	2026-07-23
Broadband Coaxial Pre-amplifier	Schwarzbeck	BBV 9718	25	2026-07-23
Pre-Amplifier	EMCI	EMC 184045SE	9870709	2026-07-30
Spectrum	Keysight	N9020A	MY51240612	2026-07-23
Broadcast test system	R&S	SFU	100410	2026-07-23
Antenna Tower	MF	MFA-440H	NA	NA
Turn Table	MF	MFT-201SS	NA	NA
Antenna Tower&Turn Table Controller	MF	MF-7802	NA	NA
Coaxial cable	N/A	N/A	HS-EMC-103	2025-12-12
Coaxial cable	N/A	N/A	HS-EMC-104/105	2025-12-12

Note:

1. The calibration interval of the above test instruments is 12 months or 36 months (*).
2. The test was performed in 966.

3.1.3 Test Procedures

a. Peak emission levels are measured by setting the instrument as follow:

- 1) RBW & VBW setting as a function of frequency:

Frequency	RBW	VBW
9kHz~150kHz	200Hz	600Hz
0.15MHz~30MHz	9kHz	30kHz
30MHz~1000MHz	120kHz	300kHz
>1000MHz	1MHz	3MHz

- 2) Detector = peak.
- 3) Sweep time = auto.
- 4) Trace mode = max hold.
- 5) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be lengthened for low-duty-cycle applications.)

Note: If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement

b. Average emission levels are measured by setting the instrument as follow:**● Trace averaging with continuous EUT transmission at full power**

If the EUT can be configured or modified to transmit continuously ($D \geq 98\%$), then the average emission levels shall be measured using the following method (with EUT transmitting continuously):

- 1) RBW=1 MHz (unless otherwise specified).
- 2) VBW $\geq 3 \times$ RBW.
- 3) Detector =RMS
- 4) Sweep time = auto.
- 5) Perform a trace average of at least 100 traces.

● Trace averaging across ON and OFF times of the EUT transmissions followed by duty cycle correction

If continuous transmission of the EUT ($D \geq 98\%$) cannot be achieved and the duty cycle is constant (duty cycle variations are less than $\pm 2\%$), then the following procedure shall be used

- 1) The EUT shall be configured to operate at the maximum achievable duty cycle.
- 2) Measure the duty cycle D of the transmitter output signal as described in 11.6.
- 3) RBW=1 MHz (unless otherwise specified).
- 4) VBW $\geq 3 \times$ RBW.
- 5) Detector =RMS
- 6) Sweep time = auto.
- 7) Perform a trace average of at least 100 traces.

A correction factor shall be added to the measurement results prior to comparing with the emission limit to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:

*If power averaging (rms) mode was used in step 5). then the applicable correction factor is $[10 \log (1/D)]$, where D is the duty cycle.

**If linear voltage averaging mode was used in step f). then the applicable correction factor is $[20 \log (1/D)]$, where D is the duty cycle.

***If a specific emission is demonstrated to be continuous ($D > 98\%$) rather than turning ON and OFF with the transmit cycle, then no duty cycle correction is required for that.

● Reduced VBW Averaging across ON and OFF times of the EUT transmissions with max hold

If continuous transmission of the EUT ($D > 98\%$) cannot be achieved and the duty cycle is not constant (duty cycle variations exceed $\pm 2\%$), then the following procedure shall be used:

- 1) RBW = 1 MHz
 - 2) VBW $\geq 1/T$.
 - 3) Detector = peak
 - 4) Sweep time = auto.
 - 5) Trace mode = max hold.
 - 6) Allow max hold to run for at least $[50 \times (1/D)]$ traces
- c. The EUT was placed on the top of a rotating table 0.8 meters (below 1GHz) / 1.5 meters (Above 1GHz) above the reference ground. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The EUT was set 3 meters away from the interference-receiving antenna (Below 1GHz) & (Above 1GHz), which was mounted on the top of a variable-height antenna tower.
- e. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- f. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- g. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- h. The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz & 360kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth = 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth = $1/T$ for Average (Duty cycle $< 98\%$) detection at frequency above 1 GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is = 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.

3.1.4 Deviation from Test Standard


No deviation.


3.1.5 Test Setup

Radiated emission below 30MHz:



Frequency Range below 1GHz:



Frequency Range above 1GHz:

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.1.6 EUT Operating Conditions

- Placed the EUT on the testing table.
- Set the EUT under transmission condition continuously at specific channel frequency.

3.1.7 Test Results


The 5.8G AUDIO TRANSCEIVER was kept in transmitting state during all Bluetooth spurious emission tests

9kHz ~ 30MHz Data:

The amplitude of spurious emissions attenuated more than 20dB below the permissible value is not required to be report.

30MHz ~ 1GHz Worst-Case Data:

Test Channel	Channel 0	Frequency Range	30MHz ~ 1GHz
Detector Function	Peak (PK) Quasi-peak (QP)	Tested By	Hua




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Height (cm)	Table Angle (Degree)
1	87.1117	54.41	-19.39	35.02	40.00	-4.98	peak	113	75
2	92.7871	55.41	-19.42	35.99	43.50	-7.51	peak	334	332
3	116.9492	48.60	-16.14	32.46	43.50	-11.04	peak	255	58
4	193.7728	54.95	-16.76	38.19	43.50	-5.31	peak	369	256
5	206.9501	54.09	-17.41	36.68	43.50	-6.82	QP	364	142
6	590.9737	42.56	-5.39	37.17	46.00	-8.83	peak	298	111

Remarks:

1. Emission Level = Read Level + Factor (Antenna Factor + Cable Loss - Preamp Factor)
2. Margin value = Emission level – Limit value

Test Channel	Channel 0	Frequency Range	30MHz ~ 1GHz
Detector Function	Peak (PK) Quasi-peak (QP)	Tested By	Hua




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Height (cm)	Table Angle (Degree)
1	36.5092	50.34	-15.95	34.39	40.00	-5.61	peak	156	212
2	92.7871	54.46	-19.42	35.04	43.50	-8.46	peak	368	99
3	111.3468	52.08	-16.97	35.11	43.50	-8.39	peak	316	90
4	192.4186	54.92	-16.69	38.23	43.50	-5.27	peak	124	16
5	206.9900	54.49	-17.41	37.08	43.50	-6.42	QP	321	0
6	213.7633	56.94	-17.42	39.52	43.50	-3.98	peak	164	113

Remarks:

1. Emission Level = Read Level + Factor (Antenna Factor + Cable Loss - Preamp Factor)
2. Margin value = Emission level – Limit value

Above 1GHz Data:
BLE-1Mbps

Test channel	Channel 0	Frequency Range	Above 1GHz
Detector Function	Peak (PK) Average (AVG)	Tested By	Aron




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Height (cm)	Table Angle (Degree)
1	2372.926	38.98	-1.40	37.58	74.00	-36.42	peak	100	156
2	2372.926	34.02	-1.40	32.62	54.00	-21.38	AVG	100	156
3 #	2401.984	105.32	-1.22	104.10			peak	100	156
4 #	2401.984	105.03	-1.22	103.81			AVG	100	156
5	4804.000	42.26	2.45	44.71	74.00	-29.29	peak	100	220
6	4804.000	38.77	2.45	41.22	54.00	-12.78	AVG	100	220
7	7206.000	30.31	9.90	40.21	74.00	-33.79	peak	100	106
8	7206.000	22.95	9.90	32.85	54.00	-21.15	AVG	100	106

Remarks:

1. Emission Level = Read Level + Factor (Antenna Factor + Cable Loss - Preamp Factor)
2. Margin value = Emission level – Limit value
3. #: Fundamental frequency.

Test channel	Channel 0	Frequency Range	Above 1GHz
Detector Function	Peak (PK) Average (AVG)	Tested By	Aron



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Height (cm)	Table Angle (Degree)
1	2377.936	45.06	-1.36	43.70	74.00	-30.30	peak	100	124
2	2377.936	40.17	-1.36	38.81	54.00	-15.19	AVG	100	124
3 #	2401.784	105.85	-1.22	104.63			peak	100	124
4 #	2401.784	105.16	-1.22	103.94			AVG	100	124
5	4804.000	45.59	2.45	48.04	74.00	-25.96	peak	100	278
6	4804.000	42.77	2.45	45.22	54.00	-8.78	AVG	100	278
7	7206.000	35.76	9.90	45.66	74.00	-28.34	peak	100	58
8	7206.000	29.20	9.90	39.10	54.00	-14.90	AVG	100	58

Remarks:

1. Emission Level = Read Level + Factor (Antenna Factor + Cable Loss - Preamp Factor)
2. Margin value = Emission level – Limit value
3. #: Fundamental frequency.


Test channel	Channel 19	Frequency Range	Above 1GHz
Detector Function	Peak (PK) Average (AVG)	Tested By	Aron

Antennal Polarity& Test Distance: Horizontal at 3m									
No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Height (cm)	Table Angle (Degree)
1#	2441.000	107.16	-0.96	106.20	74.00	32.20	peak	260	111
2#	2441.000	106.70	-0.96	105.74	54.00	51.74	AVG	260	111
3	4882.000	43.46	2.64	46.10	74.00	-27.90	peak	209	51
4	4882.000	39.96	2.64	42.60	54.00	-11.40	AVG	209	51
5	7323.000	32.71	10.21	42.92	74.00	-31.08	peak	222	358
6	7323.000	22.64	10.21	32.85	54.00	-21.15	AVG	222	358
Antennal Polarity& Test Distance: Vertical at 3 M									
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Height (cm)	Table Angle (Degree)
1#	2441.000	105.93	-0.96	104.97	74.00	30.97	peak	232	128
2#	2441.000	105.18	-0.96	104.22	54.00	50.22	AVG	232	128
3	4882.000	46.88	2.64	49.52	74.00	-24.48	peak	100	347
4	4882.000	42.68	2.64	45.32	54.00	-8.68	AVG	100	347
5	7323.000	36.51	10.21	46.72	74.00	-27.28	peak	100	116
6	7323.000	29.70	10.21	39.91	54.00	-14.09	AVG	100	116

Remarks:

1. Emission Level = Read Level + Factor (Antenna Factor + Cable Loss - Preamp Factor)
2. Margin value = Emission level – Limit value
3. #: Fundamental frequency.

Test channel	Channel 39	Frequency Range	Above 1GHz
Detector Function	Peak (PK) Average (AVG)	Tested By	Aron




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Height (cm)	Table Angle (Degree)
1#	2479.820	105.17	-0.72	104.45			peak	164	250
2#	2479.820	104.44	-0.72	103.72			AVG	164	250
3	2485.431	45.19	-0.69	44.50	74.00	-29.50	peak	164	250
4	2485.431	37.80	-0.69	37.11	54.00	-16.89	AVG	164	250
5	4960.000	42.00	2.82	44.82	74.00	-29.18	peak	100	240
6	4960.000	37.56	2.82	40.38	54.00	-13.62	AVG	100	240
7	7440.000	33.06	10.51	43.57	74.00	-30.43	peak	100	15
8	7440.000	25.04	10.51	35.55	54.00	-18.45	AVG	100	15

Remarks:

1. Emission Level = Read Level + Factor (Antenna Factor + Cable Loss - Preamp Factor)
2. Margin value = Emission level – Limit value
3. #: Fundamental frequency.

Test channel	Channel 39	Frequency Range	Above 1GHz
Detector Function	Peak (PK) Average (AVG)	Tested By	Aron




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Height (cm)	Table Angle (Degree)
1#	2479.419	103.61	-0.72	102.89			peak	100	131
2#	2479.419	103.03	-0.72	102.31			AVG	100	131
3	2484.228	50.53	-0.69	49.84	74.00	-24.16	peak	100	131
4	2484.228	43.44	-0.69	42.75	54.00	-11.25	AVG	100	131
5	4960.000	43.68	2.82	46.50	74.00	-27.50	peak	100	150
6	4960.000	38.82	2.82	41.64	54.00	-12.36	AVG	100	150
7	7440.000	36.21	10.51	46.72	74.00	-27.28	peak	100	330
8	7440.000	24.59	10.51	35.10	54.00	-18.90	AVG	100	330

Remarks:

1. Emission Level = Read Level + Factor (Antenna Factor + Cable Loss - Preamp Factor)
2. Margin value = Emission level – Limit value
3. #: Fundamental frequency.

Above 1GHz Data:
BLE-2Mbps

Test channel	Channel 1	Frequency Range	Above 1GHz
Detector Function	Peak (PK) Average (AVG)	Tested By	Aron




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Height (cm)	Table Angle (Degree)
1	2386.353	42.84	-1.32	41.52	74.00	-32.48	peak	100	287
2	2386.353	36.74	-1.32	35.42	54.00	-18.58	AVG	100	287
3 #	2404.188	104.17	-1.20	102.97	74.00	28.97	peak	100	287
4 #	2404.188	103.70	-1.20	102.50	54.00	48.50	AVG	100	287
5	4808.000	43.33	2.47	45.80	74.00	-28.20	peak	100	122
6	4808.000	35.63	2.47	38.10	54.00	-15.90	AVG	100	122
7	7212.000	32.49	9.92	42.41	74.00	-31.59	peak	100	214
8	7212.000	21.95	9.92	31.87	54.00	-22.13	AVG	100	214

Remarks:

1. Emission Level = Read Level + Factor (Antenna Factor + Cable Loss - Preamp Factor)
2. Margin value = Emission level – Limit value
3. #: Fundamental frequency.

Test channel	Channel 1	Frequency Range	Above 1GHz
Detector Function	Peak (PK) Average (AVG)	Tested By	Aron



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Height (cm)	Table Angle (Degree)
1	2380.942	45.06	-1.35	43.71	74.00	-30.29	peak	110	332
2	2380.942	40.56	-1.35	39.21	54.00	-14.79	AVG	110	332
3 #	2403.787	107.75	-1.21	106.54	74.00	32.54	peak	110	332
4 #	2403.787	106.83	-1.21	105.62	54.00	51.62	AVG	110	332
5	4808.000	42.76	2.47	45.23	74.00	-28.77	peak	100	324
6	4808.000	39.03	2.47	41.50	54.00	-12.50	AVG	100	324
7	7212.000	33.68	9.92	43.60	74.00	-30.40	peak	100	128
8	7212.000	25.48	9.92	35.40	54.00	-18.60	AVG	100	128

Remarks:

1. Emission Level = Read Level + Factor (Antenna Factor + Cable Loss - Preamp Factor)
2. Margin value = Emission level – Limit value
3. #: Fundamental frequency.


Test channel	Channel 19	Frequency Range	Above 1GHz
Detector Function	Peak (PK) Average (AVG)	Tested By	Aron

Antennal Polarity& Test Distance: Horizontal at 3m									
No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Height (cm)	Table Angle (Degree)
1#	2440.000	105.31	-0.98	104.33			peak	165	59
2#	2440.000	104.89	-0.98	103.91			AVG	165	59
3	4880.000	44.67	2.63	47.30	74.00	-26.70	peak	110	75
4	4880.000	36.57	2.63	39.20	54.00	-14.80	AVG	110	75
5	7320.000	32.34	10.20	42.54	74.00	-31.46	peak	176	348
6	7320.000	22.04	10.20	32.24	54.00	-21.76	AVG	176	348
Antennal Polarity& Test Distance: Vertical at 3 M									
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Height (cm)	Table Angle (Degree)
1#	2440.000	105.60	-0.98	104.62			peak	205	232
2#	2440.000	104.64	-0.98	103.66			AVG	205	232
3	4880.000	46.49	2.63	49.12	74.00	-24.88	peak	100	174
4	4880.000	39.70	2.63	42.33	54.00	-11.67	AVG	100	174
5	7320.000	33.51	10.20	43.71	74.00	-30.29	peak	100	263
6	7320.000	22.59	10.20	32.79	54.00	-21.21	AVG	100	263

Remarks:

1. Emission Level = Read Level + Factor (Antenna Factor + Cable Loss - Preamp Factor)
2. Margin value = Emission level – Limit value
3. #: Fundamental frequency.

Test channel	Channel 38	Frequency Range	Above 1GHz
Detector Function	Peak (PK) Average (AVG)	Tested By	Aron




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Height (cm)	Table Angle (Degree)
1#	2477.214	106.41	-0.74	105.67	74.00	31.67	peak	100	208
2#	2477.214	105.65	-0.74	104.91	54.00	50.91	AVG	100	208
3	2487.234	42.32	-0.67	41.65	74.00	-32.35	peak	100	208
4	2487.234	44.88	-0.67	44.21	54.00	-9.79	AVG	100	208
5	4956.000	40.59	2.80	43.39	74.00	-30.61	peak	100	110
6	4956.000	33.40	2.80	36.20	54.00	-17.80	AVG	100	110
7	7434.000	34.40	10.50	44.90	74.00	-29.10	peak	100	14
8	7434.000	22.72	10.50	33.22	54.00	-20.78	AVG	100	14

Remarks:

1. Emission Level = Read Level + Factor (Antenna Factor + Cable Loss - Preamp Factor)
2. Margin value = Emission level – Limit value
3. #: Fundamental frequency.

Test channel	Channel 38	Frequency Range	1GHz ~ 25GHz
Detector Function	Peak (PK) Average (AVG)	Tested By	Aron



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Height (cm)	Table Angle (Degree)
1#	2478.016	103.32	-0.72	102.60	74.00	28.60	peak	100	96
2#	2478.016	103.32	-0.72	102.60	54.00	48.60	AVG	100	96
3	2488.637	43.33	-0.66	42.67	74.00	-31.33	peak	100	96
4	2488.637	38.67	-0.66	38.01	54.00	-15.99	AVG	100	96
5	4956.000	41.42	2.80	44.22	74.00	-29.78	peak	100	144
6	4956.000	31.12	2.80	33.92	54.00	-20.08	AVG	100	144
7	7434.000	32.70	10.50	43.20	74.00	-30.80	peak	100	7
8	7434.000	22.76	10.50	33.26	54.00	-20.74	AVG	100	7

Remarks:

1. Emission Level = Read Level + Factor (Antenna Factor + Cable Loss - Preamp Factor)
2. Margin value = Emission level – Limit value
3. #: Fundamental frequency.

3.2 Conducted Emission Measurement**3.2.1 Limits of Conducted Emission Measurement**

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3.2.2 Test Instruments

Equipment	Manufacturer	Model No.	Serial No.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR 7	100962	2026-07-23
Artificial Mains Network	Rohde&Schwarz	ENV216	3560.6550.15	2026-07-23
Test software	FARAD	EZ_EMV V1.1.4.2	N/A	N/A
Broadcast test system	R&S	SFU	100410	2026-07-23


Note: 1. The calibration interval of the above test instruments is 12 months.
2. The test was performed in Shielded Room.

3.2.3 Test Procedures

- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit – 20dB) was not recorded.

Note: All modes of operation were investigated and the worst-case emissions are reported.

3.2.4 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.2.5 EUT Operating Condition


Set the EUT under transmission condition continuously at specific channel frequency.

3.2.6 Deviation from Test Standard

No deviation.

3.2.7 Test Results

Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
-----------------	----------------	--	--------------------------------------




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor dB	Emission Level (dBuV)	Limit (dBuV)	Margin (dB)	Remark Det.
1	0.1500	42.00	10.11	52.11	66.00	-13.89	peak
2	0.1522	16.31	10.10	26.41	55.88	-29.47	AVG
3	0.1882	37.76	10.04	47.80	64.12	-16.32	peak
4	0.2242	15.96	10.02	25.98	52.66	-26.68	AVG
5	0.3750	33.17	9.98	43.15	58.39	-15.24	peak
6	0.3750	28.21	9.98	38.19	48.39	-10.20	AVG
7	0.4965	38.36	10.00	48.36	56.06	-7.70	peak
8	0.4965	26.16	10.00	36.16	46.06	-9.90	AVG
9	0.7507	26.24	9.97	36.21	56.00	-19.79	peak
10	0.7507	19.38	9.97	29.35	46.00	-16.65	AVG
11	7.2846	29.31	7.66	36.97	60.00	-23.03	peak
12	7.5164	16.05	7.66	23.71	50.00	-26.29	AVG

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.

Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
-----------------	----------------	--	--------------------------------------



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor dB	Emission Level (dBuV)	Limit (dBuV)	Margin (dB)	Remark Det.
1	0.1500	42.05	10.11	52.16	66.00	-13.84	peak
2	0.1522	17.96	10.10	28.06	55.88	-27.82	AVG
3	0.1882	39.92	10.05	49.97	64.12	-14.15	peak
4	0.1883	18.24	10.05	28.29	54.11	-25.82	AVG
5	0.2872	34.70	10.03	44.73	60.60	-15.87	peak
6	0.3750	29.65	9.97	39.62	48.39	-8.77	AVG
7	0.4987	25.66	9.99	35.65	46.02	-10.37	AVG
8	0.5032	38.23	9.99	48.22	56.00	-7.78	peak
9	0.7507	27.23	9.97	37.20	56.00	-18.80	peak
10	0.7507	21.51	9.97	31.48	46.00	-14.52	AVG
11	13.9515	27.41	9.69	37.10	60.00	-22.90	peak
12	13.9515	13.86	9.69	23.55	50.00	-26.45	AVG

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.


3.3 6dB Bandwidth Measurement

3.3.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5MHz.

3.3.2 Test Setup

Subclause 11.8 of ANSI C63.10 is applicable.



Spectrum analyzer test configuration

3.3.3 Test Instruments

Refer to section 5 to get information of above instrument.

3.3.4 Test Procedure

Option 1:

- a. Set resolution bandwidth (RBW) = 100kHz
- b. Set the video bandwidth (VBW) $\geq 3 \times$ RBW
- c. Detector = Peak.
- d. Trace mode = max hold.
- e. Sweep = auto couple.
- f. Allow the trace to stabilize.
- g. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

Option 2:

The automatic bandwidth measurement capability of an instrument may be employed using the dB bandwidth mode with X set to 6 dB. if the functionality described in 11.8.1 (i.e. RBW= 100 kHz. VBW $\geq 3 \times$ RBW. and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability. care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB

3.3.5 Deviation from Test Standard

No deviation.


3.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

3.3.7 Test Result

BLE-1Mbps			
Operation Channel	Frequency	6dB Bandwidth (MHz)	
		Result	Limit
0	2402MHz	0.696	>0.5
19	2440MHz	0.696	>0.5
39	2480MHz	0.696	>0.5

BLE-2Mbps			
Operation Channel	Frequency	6dB Bandwidth (MHz)	
		Result	Limit
1	2404MHz	1.160	>0.5
19	2440MHz	1.252	>0.5
38	2478MHz	1.160	>0.5






BLE 1M Ant1 2480




BLE 2M Ant1 2404



3.4 Occupied Bandwidth Measurement

3.4.1 Test Setup



3.4.2 Test Instruments

Refer to section 5 to get information of above instrument.

3.4.3 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with resolution bandwidth in the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth and set the detector to peak. The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 %of the total mean power of a given emission.

3.4.4 Deviation from Test Standard

No deviation.


3.4.5 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.


3.4.6 Test Results


BLE-1Mbps			
Operation Channel	Frequency	Occupied Bandwidth (MHz)	
		Result	Limit
0	2402MHz	1.0723	2400~2483.5
19	2440MHz	1.0719	2400~2483.5
39	2480MHz	1.0521	2400~2483.5

BLE-2Mbps			
Operation Channel	Frequency	Occupied Bandwidth (MHz)	
		Result	Limit
1	2404MHz	2.0294	2400~2483.5
19	2440MHz	2.0317	2400~2483.5
38	2478MHz	2.0261	2400~2483.5



Test Report No.: 25052101-2-RF-US-02






3.5 Conducted Output Power Measurement

3.5.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

3.5.2 Test Setup

- Measurement using a spectrum analyzer (SA) Subclause 11.9.2.2 of ANSI C63.10 is applicable



Spectrum analyzer output power test configuration

3.5.3 Test Instruments

Refer to section 5 to get information of above instrument.

3.5.4 Test Procedures

Measurement using a spectrum analyzer (SA), Selection of test method:

The proper test method is selected based on the following criteria:

- Method AVGSA-1 or method AVGSA-1A (alternative)** shall be applied if either of the following conditions can be satisfied:
 - 1) The EUT transmits continuously (or with a $D > 98\%$).
 - 2) Sweep triggering can be implemented in such a way that the device transmits at the maximum power control level throughout the duration of each of the instrument sweeps to be averaged. This condition can generally be achieved by triggering the instrument's sweep if the duration of the sweep (with the instrument configured as in method AVGSA-1) is equal to or shorter than the duration T of each transmission from the EUT, and if those transmissions exhibit full power throughout their durations.
- Method AVGSA-2 or method AVGSA-2A (alternative)** shall be applied if the conditions of the preceding item a) cannot be achieved and the transmissions exhibit a constant duty cycle during the measurement duration. Duty cycle will be considered to be constant if variations are less than $+2\%$.
- Method AVGSA-3 or method AVGSA-3A (alternative)** shall be applied if the conditions of the preceding item a) and item b) cannot be achieved.

Test Report No.: 25052101-2-RF-US-02

☒ Measurement using a spectrum analyzer (SA), Selection of test method:

☒ Maximum peak conducted output power

The following procedure shall be used when an instrument with a resolution bandwidth that is greater than the DTS bandwidth is available to perform the measurement:

- a) Set the RBW > DTS bandwidth.
- b) Set VBW > [3 x RBW]
- c) Set span > [3 x RBW]
- d) Sweep time = auto couple.
- e) Detector = peak
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

☒ Maximum conducted (average) output power (Method AVGSA-2):

- a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b) Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c) SA Setting:
 - 1* Set span to at least 1.5 times the OBW
 - 2* Set sweep trigger to "free run."
 - 3* Set RBW= 1% to 5% of the OBW. not to exceed 1MHz.
 - 4* Set VBW $\geq 3 \times$ RBW
 - 5* Number of points in sweep $\geq 2 \times$ span /RBW. (This gives bin-to-bin spacing $\leq$ RBW / 2. so that narrowband signals are not lost between frequency bins).
 - 6* Sweep time $\leq$ (number of points in sweep) $\times$ T. where T is defined in 11.6. If this gives a sweep time less than the auto sweep time of the instrument. then method AVGSA-3 shall not be used (use AVGSA-3A). The purpose of this step is so that the averaging time in each bin is less than or equal to the minimum time of a transmission.
 - 7* Detector =RMS (power averaging).
 - 8* Trace mode =max hold.
 - 9* Allow max hold to run for at least 60 s or longer as needed to allow the trace to stabilize.
 - 10* Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function with band limits set equal to the OBW band edges. If the instrument does not have a band power function. then sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW
- d. Measure the captured power within the band and recording the plot.
- e. Repeat above procedures until all frequencies required were complete.

3.5.5 Deviation from Test Standard

No deviation.


3.5.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.


3.5.7 Test Results

BLE-1Mbps					
Peak Power					
Channel	Freq.	RF Output Power		Limit (mW)	Verdict
No.	(MHz)	(dBm)	(mW)		
0	2402	12.83	19.187	<1000	Pass
19	2440	12.24	16.749	<1000	Pass
39	2480	12.28	16.904	<1000	Pass

BLE-2Mbps					
Peak Power					
Channel	Freq.	RF Output Power		Limit (mW)	Verdict
No.	(MHz)	(dBm)	(mW)		
1	2404	12.67	18.493	<1000	Pass
19	2440	12.09	16.181	<1000	Pass
38	2478	12.12	16.293	<1000	Pass



Test Report No.: 25052101-2-RF-US-02




Lab: [Hwa-Hsing \(Dongguan\) Testing Co., Ltd.](#)
Address: [No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, HuangJiang Town, Dongguan City, People's Republic of China](#)

Tel: [0769-85598986](#)
Web.: [www.lyns-tci.com](#)
E-Mail: [service-hs@lyns-tci.com](#)

Release
Ver. 1.5

Test Report No.: 25052101-2-RF-US-02



Lab: [Hwa-Hsing \(Dongguan\) Testing Co., Ltd.](#)
 Address: [No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, HuangJiang Town, Dongguan City, People's Republic of China](#)

Tel: [0769-85598986](tel:0769-85598986)
 Web.: www.lyns-tci.com
 E-Mail: service-hs@lyns-tci.com

Release
 Ver. 1.5


3.6 Power Spectral Density Measurement

3.6.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8dBm/3kHz.

3.6.2 Test Setup

- DTS maximum power spectral density level in the fundamental emission Subclause 11.10 of ANSI C63.10 is applicable



3.6.3 Test Instruments

Refer to section 5 to get information of above instrument.

3.6.4 Test Procedure

- a. **Method AVGPDS-1 or method AVGPDS-1A (alternative)** shall be applied if either of the following conditions can be satisfied:
- 1) The EUT transmits continuously (or with a $D \geq 98\%$).
 - 2) Sweep triggering can be implemented in such a way that the device transmits at the maximum power control level throughout the duration of each of the instrument sweeps to be averaged. This condition can generally be achieved by triggering the instrument's sweep if the duration of the sweep is equal to or shorter than the duration I of each transmission from the EUT, and if those transmissions exhibit full power throughout these durations.
- b. **Method AVGPDS-2 or method AVGPDS-2A (alternative)** shall be applied if the conditions of the preceding item a) cannot be achieved. and the transmissions exhibit a constant duty cycle during the measurement duration. Duty cycle will be considered to be constant if variations are less than $\pm 2\%$.
- c. **Method AVGPDS-3 or method AVGPDS-3A (alternative)** shall be applied if the conditions of the preceding paragraphs a) and b) cannot be achieved.

Method AVGPDS-3:

Method AVGPDS-3 uses mms detection across ON and OFE times of the EUT with max hold. The following procedure is applicable when the EUT cannot be configured to transmit continuously (i.e. $D < 98\%$), when sweep triggering/signal gating cannot be used to measure only when the EUT is transmitting at its maximum power control level. and when the transmission duty cycle is not constant (i.e., duty cycle variations exceed $\pm 2\%$).

SA Setting:

- a. Set the instrument span to a minimum of 1.5 times the OBW.
 - b. Set sweep trigger to "free run."
 - c. Set the RBW = 3 kHz, VBW = 10 kHz,
 - d. Detector = RMS (power averaging).
 - e. Sweep time = Auto couple,
 - f. Allow max hold to run for at least 60 s or longer as needed to allow the trace to stabilize.
 - g. Use the peak marker function to determine the maximum PSD level
- If the measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span to meet the minimum measurement point requirement as the RBW is reduced).

3.6.5 Deviation from Test Standard

No deviation.


3.6.6 EUT Operating Condition

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.


3.6.7 Test Results

BLE-1Mbps	Power Density		
Test Channel	Channel Frequency	Test Result (dBm/3kHz)	Limit (dBm/3kHz)
0	2402MHz	-2.64	<8
19	2440MHz	-3.62	<8
39	2480MHz	-3.34	<8

BLE-2Mbps	Power Density		
Test Channel	Channel Frequency	Test Result (dBm/3kHz)	Limit (dBm/3kHz)
1	2404MHz	-6.02	<8
19	2440MHz	-6.72	<8
38	2478MHz	-6.9	<8




BLE 1M Ant1 2402



BLE 1M Ant1 2440

Test Report No.: 25052101-2-RF-US-02




Lab: [Hwa-Hsing \(Dongguan\) Testing Co., Ltd.](#)
 Address: [No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, Huangjiang Town, Dongguan City, People's Republic of China](#)

Tel: [0769-85598986](tel:0769-85598986)
 Web.: www.lyns-tci.com
 E-Mail: service-hs@lyns-tci.com

Release
 Ver. 1.5

Test Report No.: 25052101-2-RF-US-02



Lab: [Hwa-Hsing \(Dongguan\) Testing Co., Ltd.](#)
 Address: [No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, Huangjiang Town, Dongguan City, People's Republic of China](#)

Tel: [0769-85598986](tel:0769-85598986)
 Web.: www.lyns-tci.com
 E-Mail: service-hs@lyns-tci.com

Release
 Ver. 1.5


3.7 Conducted Out of Band Emission Measurement

3.7.1 Limits of Conducted Out of Band Emission Measurement

- a. **If the maximum peak conducted output power procedure was used to determine compliance as described in 11.9.1**, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).
- b. **If maximum conducted (average) output power was used to determine compliance as described in 11.9.2**, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).

3.7.2 Test Setup

- DTS emissions in non-restricted frequency bands Subclause 11.11 of ANSI C63.10 is applicable.
- DTS emissions in restricted frequency bands Subclause 11.12 of ANSI C63.10 is applicable.



Spectrum analyzer test configuration

3.7.3 Test Instruments

Refer to section 5 to get information of above instrument.

3.7.4 Test Procedure

a. Establish a reference level by using the following procedure:

- 1) Set instrument center frequency to DTS channel center frequency.
- 2) Set the span to 21.5 times the DTS bandwidth)
- 3) Set the RBW= 100 kHz)
- 4) Set the VBW $\geq 3 \times$ RBW
- 5) Detector = peak
- 6) Sweep time = auto coupling
- 7) Trace mode =max hold
- 8) Allow trace to fully stabilize
- 9) Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

b. Establish an emission level by using the following procedure:

- 1) Set the center frequency and span to encompass frequency range to be measured.
- 2) Set the RBW = 100 kHz
- 3) Set the VBW ≥ 300 kHz.
- 4) Detector = peak.
- 5) Sweep time = auto couple.
- 6) Trace mode = max hold.
- 7) Allow trace to fully stabilize.
- 8) Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

3.7.5 Deviation from Test Standard

No deviation.


3.7.6 EUT Operating Condition

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

3.7.7 Test results




Test Report No.: 25052101-2-RF-US-02




Lab: [Hwa-Hsing \(Dongguan\) Testing Co., Ltd.](#)
Address: [No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, Huangjiang Town, Dongguan City, People's Republic of China](#)


Tel: [0769-85598986](#)
Web.: [www.lyns-tci.com](#)
E-Mail: [service-hs@lyns-tci.com](#)

Release
Ver. 1.5










Test Report No.: 25052101-2-RF-US-02




Lab: [Hwa-Hsing \(Dongguan\) Testing Co., Ltd.](#)
Address: [No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, Huangjiang Town, Dongguan City, People's Republic of China](#)


Tel: [0769-85598986](tel:0769-85598986)
Web.: www.lyns-tci.com
E-Mail: service-hs@lyns-tci.com

Release
Ver. 1.5

Test Report No.: 25052101-2-RF-US-02




Test Report No.: 25052101-2-RF-US-02




Lab: [Hwa-Hsing \(Dongguan\) Testing Co., Ltd.](#)
Address: [No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, Huangjiang Town, Dongguan City, People's Republic of China](#)

Tel: [0769-85598986](#)
Web.: [www.lyns-tci.com](#)
E-Mail: [service-hs@lyns-tci.com](#)

Release
Ver. 1.5





Lab: [Hwa-Hsing \(Dongguan\) Testing Co., Ltd.](#)

Address: [No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, Huangjiang Town, Dongguan City, People's Republic of China](#)

Tel: [0769-85598986](#)

Web.: [www.lyns-tci.com](#)

E-Mail: [service-hs@lyns-tci.com](#)

Release

[Ver. 1.5](#)

Test Report No.: 25052101-2-RF-US-02

4. Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

5. Test Instruments

Equipment	Manufacturer	Model No.	Serial No.	Next Cal. Date
Spectrum	Keysight	N9020A	MY51240612	2026-07-23
Power Meter 10Hz~18GHz	Tonscend	JS0806-2	188060126	2026-07-23
Spectrum Analyzer	Rohde&Schwarz	FSV-40N	101783	2026-07-23
Signal generator	Keysight	E4421	GB40051020	2026-05-18
Universal Switch Control Unit	Rohde&Schwarz	CMW500	12010002k50	2026-07-23
Humidity tester	Jingchuang	GSP-8A	CMA22B000592	2026-07-28
Test Software	Tonscend	JS0806-2	188060126	2026-07-23

Note: 1. The calibration interval of the above test instruments is 12 months.
2. The test was performed in RF Chamber.

Appendix – Information on The Testing Laboratories

We, [Hwa-Hsing \(Dongguan\) Testing Co., Ltd.](#), A global provider of TESTING and CERTIFICATION services for consumer products, electronic products and wireless information technology products. Adhering to the core values “HONEST and TRUSTWORTHY, OBJECTIVE and IMPARTIALITY, RIGOROUS and AFFICIENT”, commitment to provide professional, perfect and efficient comprehensive ONE-STOP solution of TESTING and CERTIFICATION services for Manufacturers, Buyers, Traders, Brands, Retailers. Assist client to better manage risk, protect their brands, reduce costs and cut time to over 150 markets in global. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lab Address: [No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, HuangJiang Town, Dongguan City, People's Republic of China](#)

Contact Tel: [0769-85598986](#)

Email: service-hs@lyns-tci.com

Web Site: www.lyns-tci.com

--- END ---