

5

B ① $92.0 \pm 0.2\text{mm}$

 $36 \pm 0.2 \text{ mm}$ 

The label is located on the rear surface of the EUT, near the power supply interface.

PMS Black 6 C

180° 剝離力: $\geq 0.8\text{Kgf}/25\text{mm}$
 標籤需與被貼物進行實驗。

1. IF TOLERANCE FOR EACH DIMENSIONS NOT SHOWN, REFER TO COLUMN B IN TABLE FOR TOLERANCE.
2. UER R=1.0MM FOR ALL RADII NOT SPECIFIED.
3. UNACCEPTABLE CONDITIONS: FLASH, SHRINKAGE, DEFORMATION, AND/OR SPOTS.
4. □ REPRESENTS REVISIONS OR NEW DIMENSIONS.
5. ○ REPRESENTS CRITICAL AREAS TO BE MEASURED. ALL OTHER DIMENSIONS ARE FOU REFERENCE.
6. THE MOULD NUMBER: **NO**
7. TEXTURE NUMBER: **NO**
8. ALL SUBSTANCE NEED TO MEET THE **ROHS/ REACH/PRO65/VOCE** REQUIREMENTS, DETAILS REFER TO ZYLUX'S PROCEDURE "QMI-P40-01".
9. WILL USE $\pm 0.05\text{MM}$ INNER DIMETER FOU THE SCREW WHICH NOT SPECIFIED THE DETAILED DIMENSION.

321

ZYLUX Acoustic Corporation