


FCC RF Exposure Report

FCC ID : XNAWBS09
Equipment : Withings Body Pro
Model No. : WBS09
Brand Name : Withings
Applicant : Withings SA
Address : 2 rue Maurice Hartmann
92130 Issy-Les-Moulineaux
France
Standard : 47 CFR FCC Part 2.1091
Received Date : Feb. 04, 2021
Tested Date : Mar. 09 ~ Apr. 08, 2021

We, International Certification Corporation, would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:


Along Chen / Assistant Manager

Approved by:



Gary Chang / Manager



Table of Contents

1	GENERAL DESCRIPTION	4
1.1	Information.....	4
2	MPE EVALUATION OF MOBILE DEVICES	5
2.1	LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE.....	5
2.2	MPE EVALUATION FORMULA	5
2.3	DEVIATION FROM TEST STANDARD AND MEASUREMENT PROCEDURE	5
2.4	MEASUREMENT UNCERTAINTY	5
2.5	MPE EVALUATION RESULTS	6
2.6	MPE EVALUATION OF SIMULTANEOUS TRANSMISSION.....	6
3	TEST LABORATORY INFORMATION	7

Release Record

Report No.	Version	Description	Issued Date
FA132501	Rev. 01	Initial issue	Apr. 26, 2021

1 General Description

1.1 Information

1.1.1 Test Sample Information

MAC Number of Test Sample	Antenna Port Conducted: 00:24:E4:C7:25:2D
---------------------------	---

2 MPE EVALUATION OF MOBILE DEVICES

2.1 LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE

Frequency Range (MHz)	Power Density (mW /cm ²)	Averaging Time (minutes)
300~1500	F/1500	30
1500~100000	1.0	30

2.2 MPE EVALUATION FORMULA

$$Pd = \frac{Pt}{4 * Pi * R^2}$$

Where

Pd= Power density in mW/cm²

Pt= EIRP in mW

Pi= 3.1416

R= Measurement distance

2.3 DEVIATION FROM TEST STANDARD AND MEASUREMENT PROCEDURE

None

2.4 MEASUREMENT UNCERTAINTY

The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)).

Parameters	Uncertainty
Conducted power	±0.808 dB

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

2.5 MPE EVALUATION RESULTS

BT & WiFi

Frequency Range (MHz)	Maximum Conducted Power (dBm)	Rated Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	*Ratio	Pass / Fail
2412~2462 (Wi-Fi)	14.77	15	2.8	20	0.012	1	0.012	Pass
2402-2480 (BT EDR)	-3.48	-3	2.8	20	0.0002	1	0.0002	Pass
2402-2480 (BT LE)	3.57	4	2.8	20	0.001	1	0.001	Pass

*Ratio = Power density / Limit.

LTE

The device contains a certified module, FCC ID: 2AAGMGM02SA

Frequency Range (MHz)	Rated Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	*Ratio	Pass / Fail
1850~1910 LTE Band 2	25	3.1	20	0.128	1	0.128	Pass
1710~1755 LTE Band 4	25	3.1	20	0.128	1	0.128	Pass
699 ~ 716 LTE Band 12	25	1.6	20	0.091	0.466	0.195	Pass

*Ratio = Power density / Limit.

2.6 MPE EVALUATION OF SIMULTANEOUS TRANSMISSION

Mode	Max Ratio of Each Mode
BT	0.001
LTE	0.195
Sum	0.196
Limit	1
Pass / Fail	Pass

3 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corporation (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No.30-2, Ding Fwu Tsuen, Lin Kou
District, New Taipei City, Taiwan
(R.O.C.)

Kwei Shan

Tel: 886-3-271-8666

No.3-1, Lane 6, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 33381, Taiwan (R.O.C.)

Kwei Shan Site II

Tel: 886-3-271-8640

No.14-1, Lane 19, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 333, Taiwan (R.O.C.)

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==