

Withings

TEST REPORT

SCOPE OF WORK:

FCC Part §2.1091, §2.1093 and §1.1307(b) assessment report

Model:

WPA02

REPORT NUMBER

2502B1019SHA-003

ISSUE DATE

February 26, 2025

DOCUMENT CONTROL NUMBER

TTRFFCCMPE-01_V1 © 2018 Intertek
© 2021 Intertek



Applicant: Withings
2 Rue Maurice Hartmann Issy-les-Moulineaux 92130 France

Manufacturer: Withings
2 Rue Maurice Hartmann Issy-les-Moulineaux 92130 France

Manufacturer Site: YAHORNG (DONGGUAN) ELECTRONIC CO., LTD
Room 201, Building #9, No.84 Gaoyu South Road, Tangxia Town, Dong Guan,
Guangdong, China

Product Name: Withings U-Scan Reader


Type/Model: WPA02

FCC ID: XNAWPA02

SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

KDB447498 D01 General RF Exposure Guidance v06
FCC Part2.1091, FCC Part2.1093, FCC Part1.1307(b)

PREPARED BY:**REVIEWED BY:**

Project Engineer
Dylan Tang

Reviewer
Wakeyou Wang

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Contents

REVISION HISTORY	4
1 GENERAL INFORMATION	5
1.1 DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	5
1.2 TECHNICAL SPECIFICATION	5
1.3 DESCRIPTION OF TEST FACILITY	6
2 RF EXPOSURE EVALUATION	7
2.1 LIMIT	7
2.2 ASSESSMENT RESULTS	8

Revision History

Report No.	Version	Description	Issued Date
2502B1019SHA-003	Rev. 01	Initial issue of report	February 26, 2025

1 GENERAL INFORMATION

1.1 Description of Equipment Under Test (EUT)

Product name:	Withings U-Scan Reader
Type/Model/PMN/HVIN:	WPA02
Description of EUT:	The EUT is Withings U-Scan Reader, it supports NFC functions, there is only one model. We test them and list the worst results in this report.
Rating:	DC 3.8V
EUT type:	☒ Table top ☐ Floor standing
Software Version:	v3101
Hardware Version:	v10a
Sample Identification No.:	A4:7E:FA:3C:C9:04
Sample received date:	January 24, 2025
Date of test:	February 10, 2025 ~ February 21, 2025

Note: SOP document (RF_EMI_STM32WB_test_procedure_v7) for reference in fixed frequency testing.

1.2 Technical Specification

Frequency Range:	13.56MHz-13.56MHZ
Modulation Type:	ASK
Antenna Type:	PCB antenna

1.3 Description of Test Facility

Name:	Intertek Testing Services (Shanghai FTZ) Co., Ltd.
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L21189
	FCC Accredited Lab Designation Number: CN0175
	IC Registration Lab CAB identifier.: CN0014
	VCCI Registration Lab Registration No.: R-14243, G-10845, C-14723, T-12252
	A2LA Accreditation Lab Certificate Number: 3309.02

2 RF Exposure Evaluation

Test result: Pass

2.1 Limit

Based on KDB447498D01v06 4.3.1 c), SAR test exclusion threshold for NFC (13.56MHz) shall be evaluated as below,

Clause 4.3.1 a):

For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR,

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

Clause 4.3.1 b):

For 100 MHz to 6 GHz and test separation distances > 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

- 1) $\{[\text{Power allowed at numeric threshold for 50 mm in 4.3.1 a)}] + [(\text{test separation distance} - 50 \text{ mm}) \cdot (f(\text{MHz})/150)]\}$ mW, for 100 MHz to 1500 MHz
- 2) $\{[\text{Power allowed at numeric threshold for 50 mm in 4.3.1 a)}] + [(\text{test separation distance} - 50 \text{ mm}) \cdot 10]\}$ mW, for > 1500 MHz and ≤ 6 GHz

Clause 4.3.1 c):

For frequencies below 100 MHz, the following may be considered for SAR test exclusion:

- 1) For test separation distances > 50 mm and < 200 mm, the power threshold at the corresponding test separation distance at 100 MHz in 4.3.1 b) is multiplied by $[1 + \log(100/f(\text{MHz}))]$
- 2) For test separation distances ≤ 50 mm, the power threshold determined by the equation in 4.3.1 c) 1) for 50 mm and 100 MHz is multiplied by $\frac{1}{2}$
- 3) SAR measurement procedures are not established below 100 MHz.

Hence, SAR test exclusion threshold is calculated in reverse sequence:

- a): $(3/\sqrt{0.1}) \cdot 50 = 474.3416 \text{ mW}$
- b): $474.3416 - (50 - 50) \cdot (100/150) = 474.3416 \text{ mW}$
- c): $474.3416 \cdot [1 + \log(100/13.56)] = 885.9470 \text{ mW}$
 $885.9470 \cdot 0.5 = 442.974 \text{ mW}$

2.2 Assessment Results

Conversion of measured field strength on 13.56MHz (NFC) from dBuV/m to mW:

$$PG / (4\pi R^2) = E^2 / 120\pi$$

Assuming Antenna Gain=0 dBi and D=3 meters,

$$P/36\pi = E^2 / 120\pi$$

$$P = 0.3 * E^2$$

Measured field strength=50.8 dBuV/m@3m=0.0003467 V/m@3m

$$P = 0.3 * E^2 = 0.3 * (0.0003467)^2 = 3.6 * 10^{-6} \text{ mW}$$

Conclusion:

The 1-g SAR test exclusion power threshold for operation on 13.56MHz, and where the minimum separation distance between the user and the transmitter is ≤ 50 mm, is: 442.974mW

The radiated RF output power of the NFC transmitter is determined as being: $3.6 * 10^{-6}$ mW.

The NFC transmitter is deemed to comply with CFR 47, Part 1.1310 and therefore meets the requirement for portable devices as devices stipulated by CFR 47, Part 2.1093.

***** END *****