

1. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

1.1 General Information

Client Information

Applicant: SHENZHEN QIYUE OPTRONICS COMPANY LIMITED
Address of applicant: Flat3,Tower 3, Excellence Meilin Center Plaza, Zhongkang Road 128, Shangmeilin, Futian District, Shenzhen , China

Manufacturer: SHENZHEN QIYUE OPTRONICS COMPANY LIMITED
BRANCH
Address of manufacturer: SEIYU INDUSTRIAL PARK,DA SAN VILLAGE,DA SHUI KENG,GUANLAN TOWN,LONGHUA NEW DISTRICT,SHENZHEN,P.R.C

General Description of EUT:

Product Name: 58" SMART 4K UHD TV
Trade Name: RCA smarTVirtuoso,RCA, PROSCAN, RCA SCENIUM, TECHNICOLOR, SYLVANIA
Model No.: D58RWB344-U-A-I
RHOS581SM-D, XXXXXXXXXXXXXXXXXXXX58XXXXXXXXXX
Adding Model(s): XXXXXXXXXXXX (Where "X"can be any alphanumeric of A-Z or 0-9 or blank or -, indicates different client)
FCC ID: XOMD58RWB344
Rated Voltage: AC100-120V/60Hz

Technical Characteristics of EUT:

Support Standards: 802.11b, 802.11g, 802.11n
Frequency Range: 2412-2462MHz for 802.11b/g/n(HT20)
2422-2452MHz for 802.11n(HT40)
RF Output Power: 17.28dBm (Conducted)
Type of Modulation: DBPSK,BPSK,DQPSK,QPSK,16QAM,64QAM
Data Rate: 1-11Mbps, 6-54Mbps, up to 300Mbps
Quantity of Channels: 11 for 802.11b/g/n(HT20); 7 for 802.11n(HT40)
Channel Separation: 5MHz
Type of Antenna: Integral Antenna
Antenna Gain: 4.4dBi

1.2 Standard Applicable

According to § 1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

(a) Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz: * = Plane-wave equivalents power density

1.3 MPE Calculation Method

$$S = (30 \cdot P \cdot G) / (377 \cdot R^2)$$

S = power density (in appropriate units, e.g., mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator,
the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

1.4 MPE Calculation Result

Maximum Tune-Up output power: 18(dBm)

Maximum peak output power at antenna input terminal: 63.10(mW)

Prediction distance: >20(cm)

Prediction frequency: 2412 (MHz)

Antenna gain: 4.4(dBi)

Directional gain (numeric gain): 2.75

The worst case is power density at prediction frequency at 20cm: 0.0346(mw/cm²)

MPE limit for general population exposure at prediction frequency: 1 (mw/cm²)

Result: Pass