FCC 47 CFR PART 15 SUBPART C

for

ACCESS POINT

Model: WA1505N,WA1300N,WA505N

Brand: UTT

Test Report Number:
C160419Z04-RP1
Issued Date: June 2, 2016

Issued for

SHANGHAI UTT TECHNOLOGIES CO., LTD.
Room 301, No.9 Building, No.518, Xinzhuan Rd., Songjiang District Shanghai,China

Issued by:

Compliance Certification Services (Shenzhen) Inc.
No.10-1 Mingkeda Logistics park, No.18, Huanguan South Rd.,
Guan Lan Town, Baoan District, Shenzhen, China
TEL: 86-755-28055000
FAX: 86-755-28055221
E-Mail: service@ccssz.com

ACCREDITED
TESTING CERT #2861.01

Note: *This report shall not be reproduced except in full, without the written approval of Compliance Certification Services (Shenzhen) Inc. This document may be altered or revised by Compliance Certification Services (Shenzhen) Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, A2LA, NVLAP, NIST or any government agencies. The test results in the report only apply to the tested sample.*

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	June 2, 2016	Initial Issue	ALL	Amzula Chen

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

TABLE OF CONTENTS

1 TEST CERTIFICATION 4
2 TEST RESULT SUMMARY 4
3 EUT DESCRIPTION 6
4 TEST METHODOLOGY 7
4.1. DESCRIPTION OF TEST MODES 7
5 SETUP OF EQUIPMENT UNDER TEST 8
5.1. DESCRIPTION OF SUPPORT UNITS 8
5.2. CONFIGURATION OF SYSTEM UNDER TEST 8
6 FACILITIES AND ACCREDITATIONS 9
6.1. FACILITIES 9
6.2. ACCREDITATIONS 9
6.3. MEASUREMENT UNCERTAINTY 9
7 FCC PART 15.247 REQUIREMENTS 10
7.1. POWER LINE CONDUCTED EMISSIONS MEASUREMENT 10
7.2. SPURIOUS EMISSIONS MEASUREMENT 15
7.3. 6dB BANDWIDTH MEASUREMENT 65
7.4. ANTENNA GAIN 80
7.5. PEAK OUTPUT POWER 82
7.6. BAND EDGES MEASUREMENT 86
7.7. PEAK POWER SPECTRAL DENSITY MEASUREMENT 112

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

1 TEST CERTIFICATION

Product	ACCESS POINT
Model	WA1505N,WA1300N,WA505N
Brand	UTT
Tested	April 19~June 2, 2016
Applicant	**SHANGHAI UTT TECHNOLOGIES CO., LTD.** Room 301, No.9 Building, No.518, Xinzhuan Rd., Songjiang District Shanghai,China
Manufacturer	**SHANGHAI UTT TECHNOLOGIES CO., LTD.** Room 301, No.9 Building, No.518, Xinzhuan Rd., Songjiang District Shanghai,China

APPLICABLE STANDARDS			
Standard	**Test Type**	**Standard**	**Test Type**
15.207(a)	Power Line Conducted Emissions	15.247(d) 15.209(a)	● Spurious Emissions ● Conducted Measurement ● Radiated Emissions
15.247(a)(2)	6dB Bandwidth Measurement	15.247(b)(3) 15.247(b)(4)	Peak Power Measurement
15.247(d)	Band Edges Measurement	15.247(e)	Peak Power Spectral Density

We hereby certify that:

The above equipment was tested by Compliance Certification Services (Shenzhen) Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in **ANSI C63.10: 2013** and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247.
The test results of this report relate only to the tested sample EUT identified in this report.

Approved by:

Sunday Hu
Supervisor of EMC Dept.
Compliance Certification Services (Shenzhen) Inc.

Reviewed by:

Ruby Zhang
Supervisor of Report Dept.
Compliance Certification Services (Shenzhen) Inc.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

2 TEST RESULT SUMMARY

APPLICABLE STANDARDS			
Standard	**Test Type**	**Result**	**Remark**
15.247(a)(2)	6dB Bandwidth Measurement	Pass	Meet the requirement of limit.
15.247(b)(3) 15.247(b)(4)	Peak Power Measurement	Pass	Meet the requirement of limit.
15.247(d)	Band Edges Measurement	Pass	Meet the requirement of limit.
15.247(e)	Peak Power Spectral Density	Pass	Meet the requirement of limit.
15.247(d) 15.209(a)	● Spurious Emissions ● Conducted Measurement ● Radiated Emissions	Pass	Meet the requirement of limit.
15.207(a)	Power line Conducted Emissions	Pass	Meet the requirement of limit.

Note: 1. The statements of test result on the above are decided by the request of test standard only; the measurement uncertainties are not factored into this compliance determination.
2. The information of measurement uncertainty is available upon the customer's request.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

3 EUT DESCRIPTION

Product	ACCESS POINT
Model Number	WA1505N,WA1300N,WA505N
Brand	UTT
Model Discrepancy	They are identical to each other except for market designation for marketing purpose.
Identify Number	C160419Z04-RP1
Received Date	April 19, 2016
Power Supply	POE or DC4.5V supplied by the adapter
Transmit Power	IEEE 802.11b mode:15.87dBm (Antenna 1) IEEE 802.11b mode: 12.42dBm (Antenna 2) IEEE 802.11g mode: 22.56dBm (Antenna 1) IEEE 802.11g mode: 19.04dBm (Antenna 2) IEEE 802.11n HT20 MHz mode: 23.26dBm(Combine with Antenna 1 and Antenna 2) IEEE 802.11n HT40 MHz mode: 22.96dBm(Combine with Antenna 1 and Antenna 2)
Modulation Technique	IEEE 802.11b mode: DSSS(CCK,QPSK, BPSK) IEEE 802.11g mode: OFDM (BPSK/QPSK/16QAM/64QAM) IEEE 802.11n HT20 MHz mode: OFDM (BPSK/QPSK/16QAM/64QAM) IEEE 802.11n HT40 MHz mode: OFDM (BPSK/QPSK/16QAM/64QAM)
Transmit Data Rate	IEEE 802.11b: 11Mbps(CCK) with fall back rates of 5.5/2/1Mbps IEEE 802.11g: 54Mbps with fall back rates of 48/36/24/18/12/9 /6Mbps IEEE 802.11n HT20: 130Mbps with fall back rates of 130/117/104/ 78/52/39/26/13Mbps IEEE 802.11n HT40: 270Mbps with fall back rates of 270/243/216/ 162/108/81/54/27Mbps
Number of Channels	IEEE 802.11b mode: 11 Channels IEEE 802.11g mode: 11 Channels IEEE 802.11n HT20 MHz mode: 11 Channels IEEE 802.11n HT40 MHz mode: 7 Channels
Antenna Specification	Antenna 1: PCB Antenna with 4dBi gain (Max) Antenna 2: PCB Antenna with 4dBi gain (Max)
Channels Spacing	IEEE 802.11b/g ,802.11n HT20/HT40 : 5MHz
Temperature Range	-10°C ~ +50°C
Hardware Version	MT7620-A
Software Version	WA1505N-ENv2.8.0-160116.bin

Note: *1. The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.*

*2. This submittal(s) (test report) is intended for FCC ID: **XPF-REG09-UTT** filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

4 TEST METHODOLOGY

4.1. DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition.

Software used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Test Item	Test mode	Worse mode
Conducted Emission	**Mode 1:** 100Mbps	☒
Radiated Emission	**Mode 1:** TX	☒

After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz, which worst case was in normal link mode only, and power line conducted emission below 30MHz, which worst case was in normal link mode.

IEEE802.11b mode: Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 1Mbps data rate were chosen for full testing.

IEEE802.11g mode: Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 6Mbps data rate were chosen for full testing.

IEEE 802.11n HT20 MHz mode: Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 13Mbps data rate were chosen for full testing.

IEEE 802.11n HT40 MHz mode: Channel Low (2422MHz), Channel Mid (2437MHz) and Channel High (2452MHz) with 27Mbps data rate were chosen for full testing.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

5 SETUP OF EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Equipment	Model No.	Serial No.	FCC ID	Brand	Data Cable	Power Cord
1	Notebook	E335	N/A	DOC	Thinkpad	Shielded 1.50m	Unshielded 2.00m

Note:

Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

5.2. CONFIGURATION OF SYSTEM UNDER TEST

See test photographs attached in Appendix II for the actual connections between EUT and support equipment.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

6 FACILITIES AND ACCREDITATIONS

6.1. FACILITIES

All measurement facilities used to collect the measurement data are located at **No.10-1 Mingkeda Logistics park, No.18, Huanguan South Rd., Guan Lan Town, Baoan District, Shenzhen, China**

The sites are constructed in conformance with the requirements of ANSI C63.10, ANSI C63.7 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

6.2. ACCREDITATIONS

Our laboratories are accredited and approved by the following accreditation body according to ISO/IEC 17025.

USA	**A2LA**
China	**CNAS**

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

USA	**FCC**
Japan	**VCCI(C-4815,R-4320,T-2317, G-10624)**
Canada	**INDUSTRY CANADA**

Copies of granted accreditation certificates are available for downloading from our web site, http://www.ccssz.com

6.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Parameter	Uncertainty
Radiated Emission, 30 to 200 MHz Test Site : 966(2)	+/-3.6880dB
Radiated Emission, 200 to 1000 MHz Test Site : 966(2)	+/-3.6695dB
Radiated Emission, 1 to 8 GHz	+/-5.1782dB
Radiated Emission, 8 to 18 GHz	+/-5.2173dB
Conducted Emissions	+/-3.6836dB
Band Width	178kHz
Peak Output Power MU	+/-1.906dB
Band Edge MU	+/-0.182dB
Channel Separation MU	416.178Hz
Duty Cycle MU	0.054ms
Frequency Stability MU	226Hz

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.
The measured result is above (below) the specification limit by a margin less than the measurement uncertainty; it is therefore not possible to state compliance based on the 95% level of confidence. However, the result indicates that compliance (non-compliance) is more probable than non-compliance) with the specification limit.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

7 FCC PART 15.247 REQUIREMENTS

7.1. POWER LINE CONDUCTED EMISSIONS MEASUREMENT

7.1.1. LIMITS OF CONDUCTED EMISSIONS MEASUREMENT

According to §15.207(a), except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 µH/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Limits (dBµV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

NOTE:
(1) The lower limit shall apply at the transition frequencies.
(2) The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
(3) All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

7.1.2. TEST INSTRUMENTS

Conducted Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100783	02/21/2016	02/20/2017
LISN(EUT)	ROHDE&SCHWARZ	ENV216	101543-WX	02/21/2016	02/20/2017
LISN	EMCO	3825/2	8901-1459	02/21/2016	02/20/2017
Temp. / Humidity Meter	VICTOR	HTC-1	N/A	02/21/2016	02/20/2017
Test S/W	FARAD	EZ-EMC/ CCS-3A1-CE			

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. N.C.R = No Calibration Request.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

7.1.3. TEST PROCEDURES (please refer to measurement standard)

- The EUT and Support equipment, if needed, was placed on a non-conducted table, which is 0.8m above the ground plane and 0.4m away from the conducted wall.
- The test equipment EUT installed received AC main power, through a Line Impedance Stabilization Network (LISN), which supplied power source and was grounded to the ground plane. All support equipment power received from a second LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- The EUT test program was started. Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.
- The frequency range from 150 kHz to 30 MHz was searched. The test data of the worst-case condition(s) was recorded. Emission levels under limit 20dB were not recorded.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

7.1.4. TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

7.1.5. DATA SAMPLE

Frequency (MHz)	QuasiPeak Reading (dBuV)	Average Reading (dBuV)	Correction Factor (dB)	QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Average Margin (dB)	Remark (Pass/Fail)
X.XXXX	32.69	25.65	11.52	44.21	37.17	65.78	55.79	-21.57	-18.62	Pass

Factor = Insertion loss of LISN + Cable Loss
Result = Quasi-peak Reading/ Average Reading + Factor
Limit = Limit stated in standard
Margin = Result (dBuV) – Limit (dBuV)

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

7.1.6. TEST RESULTS

Model No.	WA1505N	**RBW,VBW**	9 kHz
Environmental Conditions	22°C, 45% RH	**Test Mode**	Mode 1
Tested by	Jack Chen	**Line**	L1
Test Date	April 20, 2016		



Frequency (MHz)	QuasiPeak Reading (dBuV)	Average Reading (dBuV)	Correction Factor (dB)	QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Average Margin (dB)	Remark (Pass/Fail)	**Line (L1/L2)**
0.1660	35.22	23.24	9.78	45.00	33.02	65.15	55.16	-20.15	-22.14	Pass	L1
0.2620	32.42	12.92	9.81	42.23	22.73	61.36	51.37	-19.13	-28.64	Pass	L1
0.2900	34.20	22.65	9.82	44.02	32.47	60.52	50.52	-16.50	-18.05	Pass	L1
1.1620	26.23	14.81	9.91	36.14	24.72	56.00	46.00	-19.86	-21.28	Pass	L1
3.4340	25.74	11.89	10.00	35.74	21.89	56.00	46.00	-20.26	-24.11	Pass	L1
28.6860	32.73	29.41	10.40	43.13	39.81	60.00	50.00	-16.87	-10.19	Pass	L1

REMARKS: *L1 = Line One (Live Line)*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Model No.	WA1505N	**RBW,VBW**	9 kHz
Environmental Conditions	22°C, 45% RH	**Test Mode**	Mode 1
Tested by	Jack Chen	**Line**	L2
Test Date	April 20, 2016		



Frequency (MHz)	QuasiPeak Reading (dBuV)	Average Reading (dBuV)	Correction Factor (dB)	QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Average Margin (dB)	Remark (Pass/Fail)	**Line (L1/L2)**
0.1620	36.85	18.28	9.88	46.73	28.16	65.36	55.36	-18.63	-27.20	Pass	L2
0.2420	32.79	10.74	9.89	42.68	20.63	62.02	52.03	-19.34	-31.40	Pass	L2
0.2860	34.31	23.30	9.89	44.20	33.19	60.64	50.64	-16.44	-17.45	Pass	L2
0.7220	23.12	13.41	9.89	33.01	23.30	56.00	46.00	-22.99	-22.70	Pass	L2
1.1580	24.07	13.43	9.91	33.98	23.34	56.00	46.00	-22.02	-22.66	Pass	L2
29.2340	34.26	30.10	10.40	44.66	40.50	60.00	50.00	-15.34	-9.50	Pass	L2

REMARKS: *L2 = Line Two (Neutral Line)*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

7.2. SPURIOUS EMISSIONS MEASUREMENT

7.2.1. CONDUCTED EMISSIONS MEASUREMENT

7.2.1.1. LIMITS OF CONDUCTED EMISSIONS MEASUREMENT

§15.247(d) specifies that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:
If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to 15.247(b)(3)requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak PSD level.
If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to 15.247(b)(3)requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured in-band average PSD level.
In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

7.2.1.2. TEST INSTRUMENTS

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	N9010A	MY55370330	02/21/2016	02/20/2017

7.2.1.3. TEST PROCEDURE (please refer to measurement standard)

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.
The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.
Measurements are made over the 10MHz to 26GHz range with the transmitter set to the lowest, middle, and highest channels. No emission found between lowest internal used/generated frequency to 10MHz，it is only recorded 10MHz to 26GHz.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

7.2.1.4. TEST RESULTS

Test Plot

IEEE 802.11b mode (Antenna 1)

CH Low (10MHz ~26.5GHz)



CH Low (2.31GHz ~2.43GHz)



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

CH Mid (10MHz ~26.5GHz)



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

CH High (10MHz ~26.5GHz)



CH High (2.45GHz ~2.5GHz)



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

IEEE 802.11b mode (Antenna 2)

CH Low (10MHz ~26.5GHz)



CH Low (2.31GHz ~2.43GHz)



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

CH Mid (10MHz ~26.5GHz)



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

CH High (10MHz ~26.5GHz)



CH High (2.45GHz ~2.5GHz)



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

IEEE 802.11g mode (Antenna 1)

CH Low (10MHz ~26.5GHz)



CH Low (2.31GHz ~2.43GHz)



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

CH Mid (10MHz ~26.5GHz)



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

CH High (10MHz ~26.5GHz)



CH High (2.45GHz ~2.5GHz)



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

IEEE 802.11g mode (Antenna 2)

CH Low (10MHz ~26.5GHz)



CH Low (2.31GHz ~2.43GHz)



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

CH Mid (10MHz ~26.5GHz)



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

CH High (10MHz ~26.5GHz)



CH High (2.45GHz ~2.5GHz)



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

IEEE 802.11n HT20 MHz mode (Antenna 1)

CH Low (10MHz ~26.5GHz)



CH Low (2.31GHz ~2.43GHz)



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

CH Mid (10MHz ~26.5GHz)



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

CH High (10MHz ~26.5GHz)



CH High (2.45GHz ~2.5GHz)



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

IEEE 802.11n HT20 MHz mode (Antenna 2)

CH Low (10MHz ~26.5GHz)



CH Low (2.31GHz ~2.43GHz)



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

CH Mid (10MHz ~26.5GHz)



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

CH High (10MHz ~26.5GHz)



CH High (2.45GHz ~2.5GHz)



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

IEEE 802.11n HT40 MHz mode (Antenna 1)

CH Low (10MHz ~26.5GHz)



CH Low (2.31GHz ~2.45GHz)



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

CH Mid (10MHz ~26.5GHz)



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

CH High (10MHz ~26.5GHz)



CH High (2.43GHz ~2.5GHz)



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

IEEE 802.11n HT40 MHz mode (Antenna 2)

CH Low (10MHz ~26.5GHz)



CH Low (2.31GHz ~2.45GHz)



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

CH Mid (10MHz ~26.5GHz)



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

CH High (10MHz ~26.5GHz)



CH High (2.43GHz ~2.5GHz)



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

7.2.2. RADIATED EMISSIONS MEASUREMENT

7.2.2.1. LIMITS OF RADIATED EMISSIONS MEASUREMENT

According to §15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (mV/m)	Measurement Distance (m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3

Remark: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

1. In the emission table above, the tighter limit applies at the band edges.

Frequency (MHz)	Field Strength (μV/m at 3-meter)	Field Strength (dBμV/m at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

NOTE:(1) The lower limit shall apply at the transition frequencies.
(2) Emission level (dBuV/m) = 20 log Emission level (uV/m).

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

7.2.2.2. TEST INSTRUMENTS

Radiated Emission Test Site 966（2）					
Name of Equipment	**Manufacturer**	**Model Number**	**Serial Number**	**Last Calibration**	**Due Calibration**
PSA Series Spectrum Analyzer	Agilent	E4446A	US44300399	02/21/2016	02/20/2017
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100783	02/21/2016	02/20/2017
Amplifier	EMEC	EM330	060661	03/18/2016	03/17/2017
High Noise Amplifier	Agilent	8449B	3008A01838	02/21/2016	02/20/2017
Loop Antenna	COM-POWER	AL-130	121044	09/25/2015	09/24/2016
Bilog Antenna	SCHAFFNER	CBL6143	5082	02/21/2016	02/20/2017
Horn Antenna	SCHWARZBECK	BBHA9120	D286	02/28/2016	02/27/2017
Board-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170-497	02/28/2016	02/27/2017
Turn Table	N/A	N/A	N/A	N.C.R	N.C.R
Antenna Tower	SUNOL	TLT2	N/A	N.C.R	N.C.R
Controller	Sunol Sciences	SC104V	022310-1	N.C.R	N.C.R
Controller	CT	N/A	N/A	N.C.R	N.C.R
Temp. / Humidity Meter	Anymetre	JR913	N/A	02/21/2016	02/20/2017
Test S/W	FARAD	LZ-RF / CCS-SZ-3A2			

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The FCC Site Registration number is 101879.

3. N.C.R = No Calibration Required.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

7.2.2.3. TEST PROCEDURE (please refer to measurement standard)

1. The EUT is placed on a turntable, which is 0.8m or 1.5m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Set the spectrum analyzer in the following setting as:

   Below 1GHz:

   RBW=100kHz / VBW=300kHz / Sweep=AUTO

   Above 1GHz:

   (a) PEAK: RBW=1MHz,VBW=3MHz / Sweep=AUTO

   (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO

7. Repeat above procedures until the measurements for all frequencies
8. are complete.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

7.2.2.4. TEST SETUP

Below 30MHz



Below 1 GHz



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Above 1 GHz



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

7.2.2.5. DATA SAPLE

Below 1GHz

Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
XXX.XXXX	36.37	-12.20	24.17	40.00	-15.83	V	QP

Frequency (MHz) = Emission frequency in MHz
Reading (dBuV) = Uncorrected Analyzer / Receiver reading
Correct Factor (dB/m) = Antenna factor + Cable loss – Amplifier gain
Result (dBuV/m) = Reading (dBuV) + Corr. Factor (dB/m)
Limit (dBuV/m) = Limit stated in standard
Margin (dB) = Result (dBuV/m) – Limit (dBuV/m)
Q.P. = Quasi-peak Reading

Above 1GHz

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
XXXX.XXXX	62.09	-11.42	50.67	74.00	-23.33	V	Peak
XXXX.XXXX	49.78	-11.42	38.36	54.00	-15.64	V	AVG

Frequency (MHz) = Emission frequency in MHz
Reading (dBuV) = Uncorrected Analyzer / Receiver reading
Correction Factor (dB/m) = Antenna factor + Cable loss – Amplifier gain
Result (dBuV/m) = Reading (dBuV) + Corr. Factor (dB/m)
Limit (dBuV/m) = Limit stated in standard
Margin (dB) = Result (dBuV/m) – Limit (dBuV/m)
Peak = Peak Reading
AVG = Average Reading

Calculation Formula

Margin (dB) = Result (dBuV/m) – Limits (dBuV/m)
Result (dBuV/m) = Reading (dBuV) + Correction Factor

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

7.2.2.6. TEST RESULTS

Below 1 GHz

Test Mode: TX **Tested by:** Jack Chen

Ambient temperature: 24°C **Relative humidity:** 52% RH **Date:** May 13, 2016

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
62.0100	58.59	-24.32	34.27	40.00	-5.73	V	QP
110.5100	55.56	-21.79	33.77	43.50	-9.73	V	QP
312.2700	53.60	-19.12	34.48	46.00	-11.52	V	QP
545.0700	47.39	-13.19	34.20	46.00	-11.80	V	QP
591.6300	46.37	-13.01	33.36	46.00	-12.64	V	QP
822.4900	47.14	-10.44	36.70	46.00	-9.30	V	QP
200.7200	58.42	-22.64	35.78	43.50	-7.72	H	QP
312.2700	55.45	-19.12	36.33	46.00	-9.67	H	QP
512.0900	48.17	-14.22	33.95	46.00	-12.05	H	QP
688.6300	49.71	-12.22	37.49	46.00	-8.51	H	QP
929.1900	47.03	-9.61	37.42	46.00	-8.58	H	QP
946.6500	48.00	-9.50	38.50	46.00	-7.50	H	QP

*****Remark:*** *No emission found between lowest internal used/generated frequency to 30MHz.*

Notes:

1. *Radiated emissions measured in frequency range from 9kHz to 1GHz were made with an instrument using Quasi-peak detector mode.*
2. *Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*
3. *The IF bandwidth of Receiver between 30MHz to 1GHz was 120kHz.*
4. *Frequency (MHz). = Emission frequency in MHz*
   Reading (dBμV/m) = Receiver reading
   Correction Factor (dB) = Antenna factor + Cable loss – Amplifier gain
   Limit (dBμV/m) = Limit stated in standard
   Margin (dB) = Measured (dBμV/m) – Limits (dBμV/m)
   Antenna Pol e(H/V) = Current carrying line of reading

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Above 1 GHz
Antenna 1
Test Mode: TX / IEEE 802.11b(CH Low) **Tested by:** Jack Chen
Ambient temperature: 24°C **Relative humidity:** 52% RH **Date:** May 17, 2016

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1882.000	55.87	-5.75	50.12	74.00	-23.88	V	peak
3214.000	45.29	-1.00	44.29	74.00	-29.71	V	peak
4843.000	42.09	4.47	46.56	74.00	-27.44	V	peak
5572.000	41.50	5.90	47.40	74.00	-26.60	V	peak
6877.000	41.17	7.50	48.67	74.00	-25.33	V	peak
7777.000	41.05	9.22	50.27	74.00	-23.73	V	peak
1882.000	52.30	-5.75	46.55	74.00	-27.45	H	Peak
3214.000	46.92	-1.00	45.92	74.00	-28.08	H	peak
4888.000	41.31	4.61	45.92	74.00	-28.08	H	peak
5986.000	40.95	6.07	47.02	74.00	-26.98	H	peak
6985.000	40.35	7.68	48.03	74.00	-25.97	H	peak
8002.000	40.26	9.65	49.91	74.00	-24.09	H	peak

REMARKS:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.*
3. *Average test would be performed if the peak result were greater than the average limit or as required by the applicant.*
4. *Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*
5. *Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.*
6. *Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode: TX / IEEE 802.11b (CH Mid) **Tested by:** Jack Chen

Ambient temperature: 24°C **Relative humidity:** 52% RH **Date:** May 17, 2016

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1882.000	57.56	-5.75	51.81	74.00	-22.19	V	Peak
4375.000	42.29	2.91	45.20	74.00	-28.80	V	Peak
5239.000	41.12	5.41	46.53	74.00	-27.47	V	Peak
6085.000	42.19	6.22	48.41	74.00	-25.59	V	Peak
7768.000	41.60	9.20	50.80	74.00	-23.20	V	Peak
8020.000	40.42	9.64	50.06	74.00	-23.94	V	Peak
1882.000	53.19	-5.75	47.44	74.00	-26.56	H	Peak
3250.000	46.71	-0.94	45.77	74.00	-28.23	H	Peak
5437.000	39.96	5.76	45.72	74.00	-28.28	H	Peak
6688.000	40.00	7.19	47.19	74.00	-26.81	H	Peak
7228.000	40.99	8.14	49.13	74.00	-24.87	H	Peak
7669.000	40.70	9.00	49.70	74.00	-24.30	H	Peak

REMARKS:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.*
3. *Average test would be performed if the peak result were greater than the average limit or as required by the applicant.*
4. *Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*
5. *Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.*
6. *Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode: TX / IEEE 802.11b (CH High) **Tested by:** Jack Chen

Ambient temperature: 24°C **Relative humidity:** 52% RH **Date:** May 17, 2016

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1882.000	57.81	-5.75	52.06	74.00	-21.94	V	Peak
4348.000	42.86	2.81	45.67	74.00	-28.33	V	Peak
4978.000	41.99	4.91	46.90	74.00	-27.10	V	Peak
5446.000	41.42	5.77	47.19	74.00	-26.81	V	Peak
6922.000	41.17	7.57	48.74	74.00	-25.26	V	Peak
7732.000	41.60	9.13	50.73	74.00	-23.27	V	Peak
1882.000	51.15	-5.75	45.40	74.00	-28.60	H	Peak
3286.000	46.15	-0.88	45.27	74.00	-28.73	H	Peak
4627.000	41.11	3.76	44.87	74.00	-29.13	H	Peak
6220.000	41.75	6.44	48.19	74.00	-25.81	H	Peak
7624.000	40.42	8.92	49.34	74.00	-24.66	H	Peak
7912.000	41.39	9.48	50.87	74.00	-23.13	H	Peak

REMARKS:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.*
3. *Average test would be performed if the peak result were greater than the average limit or as required by the applicant.*
4. *Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*
5. *Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.*
6. *Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Antenna 2

Test Mode: TX / IEEE 802.11b(CH Low) **Tested by:** Jack Chen

Ambient temperature: 24°C **Relative humidity:** 52% RH **Date:** May 17, 2016

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1324.0000	48.82	-7.34	41.48	74.00	-32.52	V	peak
3214.0000	52.51	-1.00	51.51	74.00	-22.49	V	peak
4825.0000	47.69	4.41	52.10	74.00	-21.90	V	peak
5689.0000	41.09	5.95	47.04	74.00	-26.96	V	peak
6940.0000	40.81	7.60	48.41	74.00	-25.59	V	peak
7939.0000	40.56	9.53	50.09	74.00	-23.91	V	peak
1747.0000	54.11	-6.38	47.73	74.00	-26.27	H	Peak
3214.0000	51.80	-1.00	50.80	74.00	-23.20	H	Peak
4825.0000	47.25	4.41	51.66	74.00	-22.34	H	Peak
6805.0000	40.00	7.38	47.38	74.00	-26.62	H	peak
7723.0000	41.33	9.11	50.44	74.00	-23.56	H	peak
8425.0000	41.13	9.42	50.55	74.00	-23.45	H	peak

REMARKS:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.*
3. *Average test would be performed if the peak result were greater than the average limit or as required by the applicant.*
4. *Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*
5. *Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.*
6. *Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode: TX / IEEE 802.11b (CH Mid) **Tested by:** Jack Chen

Ambient temperature: 24°C **Relative humidity:** 52% RH **Date:** May 17, 2016

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
4870.0000	43.51	4.56	48.07	74.00	-25.93	V	Peak
3250.0000	52.92	-0.94	51.98	74.00	-22.02	V	Peak
7750.0000	40.47	9.16	49.63	74.00	-24.37	V	Peak
6949.0000	40.75	7.62	48.37	74.00	-25.63	V	Peak
8722.0000	40.64	9.25	49.89	74.00	-24.11	V	Peak
9496.0000	40.36	10.53	50.89	74.00	-23.11	V	Peak
3250.0000	51.50	-0.94	50.56	74.00	-23.44	H	Peak
4870.0000	45.50	4.56	50.06	74.00	-23.94	H	Peak
5851.0000	40.58	6.02	46.60	74.00	-27.40	H	Peak
6949.0000	40.54	7.62	48.16	74.00	-25.84	H	Peak
7966.0000	40.55	9.58	50.13	74.00	-23.87	H	Peak
8560.0000	40.86	9.34	50.20	74.00	-23.80	H	Peak

REMARKS:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.*
3. *Average test would be performed if the peak result were greater than the average limit or as required by the applicant.*
4. *Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*
5. *Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.*
6. *Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode: TX / IEEE 802.11b (CH High) **Tested by:** Jack Chen

Ambient temperature: 24°C **Relative humidity:** 52% RH **Date:** May 17, 2016

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
3286.0000	52.64	-0.88	51.76	74.00	-22.24	V	Peak
4924.0000	44.28	4.73	49.01	74.00	-24.99	V	Peak
6031.0000	41.37	6.13	47.50	74.00	-26.50	V	Peak
6949.0000	40.99	7.62	48.61	74.00	-25.39	V	Peak
7228.0000	40.59	8.14	48.73	74.00	-25.27	V	Peak
7777.0000	40.78	9.22	50.00	74.00	-24.00	V	Peak
1747.0000	53.25	-6.38	46.87	74.00	-27.13	H	Peak
3286.0000	48.82	-0.88	47.94	74.00	-26.06	H	Peak
4924.0000	46.12	4.73	50.85	74.00	-23.15	H	Peak
6877.0000	41.16	7.50	48.66	74.00	-25.34	H	Peak
7768.0000	41.42	9.20	50.62	74.00	-23.38	H	Peak
8371.0000	40.75	9.45	50.20	74.00	-23.80	H	Peak

REMARKS:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.*
3. *Average test would be performed if the peak result were greater than the average limit or as required by the applicant.*
4. *Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*
5. *Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.*
6. *Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Antenna 1

Test Mode: TX / IEEE 802.11g(CH Low) **Tested by:** Jack Chen

Ambient temperature: 24°C **Relative humidity:** 52% RH **Date:** May 17, 2016

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1882.000	53.44	-5.75	47.69	74.00	-26.31	V	Peak
3214.000	46.22	-1.00	45.22	74.00	-28.78	V	Peak
4825.000	41.64	4.41	46.05	74.00	-27.95	V	Peak
6544.000	40.74	6.96	47.70	74.00	-26.30	V	Peak
6904.000	40.17	7.54	47.71	74.00	-26.29	V	Peak
7696.000	40.80	9.06	49.86	74.00	-24.14	V	Peak
1324.000	50.67	-7.34	43.33	74.00	-30.67	H	Peak
3214.000	45.60	-1.00	44.60	74.00	-29.40	H	Peak
4825.000	42.50	4.41	46.91	74.00	-27.09	H	Peak
5833.000	41.75	6.01	47.76	74.00	-26.24	H	Peak
7651.000	41.47	8.97	50.44	74.00	-23.56	H	Peak
8596.000	41.75	9.32	51.07	74.00	-22.93	H	Peak

REMARKS:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.*
3. *Average test would be performed if the peak result were greater than the average limit or as required by the applicant.*
4. *Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*
5. *Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.*
6. *Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode: TX / IEEE 802.11g (CH Mid) **Tested by:** Jack Chen

Ambient temperature: 24°C **Relative humidity:** 52% RH **Date:** May 17, 2016

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
5113.000	41.27	5.18	46.45	74.00	-27.55	V	Peak
1882.000	54.23	-5.75	48.48	74.00	-25.52	V	Peak
5761.000	41.24	5.98	47.22	74.00	-26.78	V	Peak
6976.000	40.54	7.66	48.20	74.00	-25.80	V	Peak
8236.000	40.58	9.52	50.10	74.00	-23.90	V	Peak
7570.000	41.04	8.81	49.85	74.00	-24.15	V	Peak
1882.000	54.28	-5.75	48.53	74.00	-25.47	H	Peak
3250.000	45.62	-0.94	44.68	74.00	-29.32	H	Peak
5860.000	40.62	6.02	46.64	74.00	-27.36	H	Peak
6409.000	40.78	6.74	47.52	74.00	-26.48	H	Peak
7750.000	40.63	9.16	49.79	74.00	-24.21	H	Peak
8299.000	41.04	9.49	50.53	74.00	-23.47	H	Peak

REMARKS:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.*
3. *Average test would be performed if the peak result were greater than the average limit or as required by the applicant.*
4. *Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*
5. *Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.*
6. *Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode: TX / IEEE 802.11g (CH High) **Tested by:** Jack Chen

Ambient temperature: 24°C **Relative humidity:** 52% RH **Date:** May 17, 2016

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
5590.000	41.76	5.91	47.67	74.00	-26.33	V	Peak
6157.000	41.60	6.33	47.93	74.00	-26.07	V	Peak
6967.000	40.66	7.65	48.31	74.00	-25.69	V	Peak
7228.000	40.74	8.14	48.88	74.00	-25.12	V	Peak
7579.000	40.43	8.83	49.26	74.00	-24.74	V	Peak
8344.000	40.61	9.46	50.07	74.00	-23.93	V	Peak
1882.000	50.80	-5.75	45.05	74.00	-28.95	H	Peak
3286.000	45.47	-0.88	44.59	74.00	-29.41	H	Peak
6535.000	40.13	6.95	47.08	74.00	-26.92	H	Peak
6976.000	41.38	7.66	49.04	74.00	-24.96	H	Peak
7543.000	41.39	8.76	50.15	74.00	-23.85	H	Peak
8209.000	41.18	9.54	50.72	74.00	-23.28	H	Peak

REMARKS:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.*
3. *Average test would be performed if the peak result were greater than the average limit or as required by the applicant.*
4. *Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*
5. *Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.*
6. *Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Antenna 2

Test Mode: TX / IEEE 802.11g(CH Low) **Tested by:** Jack Chen

Ambient temperature: 24°C **Relative humidity:** 52% RH **Date:** May 17, 2016

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
3214.0000	53.37	-1.00	52.37	74.00	-21.63	V	Peak
3214.0000	52.38	-1.00	51.38	54.00	-2.62	V	AVG
4825.0000	46.44	4.41	50.85	74.00	-23.15	V	Peak
6229.0000	40.33	6.45	46.78	74.00	-27.22	V	Peak
6886.0000	40.23	7.52	47.75	74.00	-26.25	V	Peak
7741.0000	40.79	9.14	49.93	74.00	-24.07	V	Peak
8587.0000	41.02	9.33	50.35	74.00	-23.65	V	Peak
3214.0000	52.48	-1.00	51.48	74.00	-22.52	H	Peak
4825.0000	56.56	4.41	60.97	74.00	-13.03	H	Peak
4825.0000	45.90	4.41	50.31	54.00	-3.69	H	AVG
5896.0000	40.50	6.04	46.54	74.00	-27.46	H	Peak
6121.0000	41.16	6.28	47.44	74.00	-26.56	H	Peak
7228.0000	41.94	8.14	50.08	74.00	-23.92	H	Peak
7741.0000	40.89	9.14	50.03	74.00	-23.97	H	Peak

REMARKS:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.*
3. *Average test would be performed if the peak result were greater than the average limit or as required by the applicant.*
4. *Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*
5. *Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.*
6. *Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode: TX / IEEE 802.11g (CH Mid) **Tested by:** Jack Chen

Ambient temperature: 24°C **Relative humidity:** 52% RH **Date:** May 17, 2016

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1882.0000	53.80	-5.75	48.05	74.00	-25.95	V	Peak
3250.0000	53.52	-0.94	52.58	74.00	-21.42	V	Peak
3250.0000	52.50	-0.94	51.56	54.00	-2.44	V	AVG
4942.0000	41.28	4.79	46.07	74.00	-27.93	V	Peak
5320.0000	41.32	5.55	46.87	74.00	-27.13	V	Peak
6265.0000	40.55	6.51	47.06	74.00	-26.94	V	Peak
7624.0000	40.89	8.92	49.81	74.00	-24.19	V	Peak
1324.0000	50.97	-7.34	43.63	74.00	-30.37	H	Peak
3250.0000	55.33	-0.94	54.39	74.00	-19.61	H	Peak
3250.0000	52.31	-0.94	51.37	54.00	-1.69	H	AVG
4141.0000	42.01	2.09	44.10	74.00	-29.90	H	Peak
4870.0000	46.73	4.56	51.29	74.00	-22.71	H	Peak
6175.0000	41.54	6.36	47.90	74.00	-26.10	H	Peak
7660.0000	41.41	8.99	50.40	74.00	-23.60	H	Peak

REMARKS:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.*
3. *Average test would be performed if the peak result were greater than the average limit or as required by the applicant.*
4. *Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*
5. *Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.*
6. *Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode: TX / IEEE 802.11g (CH High) **Tested by:** Jack Chen

Ambient temperature: 24°C **Relative humidity:** 52% RH **Date:** May 17, 2016

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
3286.000	53.10	-0.88	52.22	74.00	-21.78	V	Peak
3286.000	52.25	-0.88	51.37	54.00	-2.63	V	AVG
5023.000	41.63	5.02	46.65	74.00	-27.35	V	Peak
6076.000	40.70	6.20	46.90	74.00	-27.10	V	Peak
6814.000	40.66	7.40	48.06	74.00	-25.94	V	Peak
7534.000	41.30	8.74	50.04	74.00	-23.96	V	Peak
7759.000	41.37	9.18	50.55	74.00	-23.45	V	Peak
3286.000	54.95	-0.88	54.07	74.00	-19.93	H	Peak
3286.000	51.08	-0.88	50.20	54.00	-3.80	H	AVG
4375.000	41.89	2.91	44.80	74.00	-29.20	H	Peak
4924.000	45.06	4.73	49.79	74.00	-24.21	H	Peak
5842.000	40.74	6.01	46.75	74.00	-27.25	H	Peak
6562.000	40.57	6.99	47.56	74.00	-26.44	H	Peak
7750.000	41.25	9.16	50.41	74.00	-23.59	H	Peak

REMARKS:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.*
3. *Average test would be performed if the peak result were greater than the average limit or as required by the applicant.*
4. *Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*
5. *Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.*
6. *Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Combine with Antenna 1 and Antenna 2

Test Mode: TX / IEEE 802.11n HT20 MHz (CH Low) **Tested by:** Jack Chen

Ambient temperature: 24°C **Relative humidity:** 52% RH **Date:** May 17, 2016

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
3214.000	52.93	-1.00	51.93	74.00	-22.07	V	Peak
4816.000	41.79	4.38	46.17	74.00	-27.83	V	Peak
5536.000	41.14	5.89	47.03	74.00	-26.97	V	Peak
7210.000	40.10	8.11	48.21	74.00	-25.79	V	Peak
7705.000	41.16	9.07	50.23	74.00	-23.77	V	Peak
9073.000	42.07	9.31	51.38	74.00	-22.62	V	Peak
1324.000	51.57	-7.34	44.23	74.00	-29.77	H	Peak
3214.000	54.05	-1.00	53.05	74.00	-20.95	H	Peak
3214.000	53.79	-1.00	52.79	54.00	-1.21	H	AVG
4825.000	49.34	4.41	53.75	74.00	-20.25	H	Peak
4825.000	37.02	4.41	41.43	54.00	-12.57	H	AVG
6463.000	41.23	6.83	48.06	74.00	-25.94	H	Peak
7012.000	41.30	7.72	49.02	74.00	-24.98	H	Peak
7786.000	41.51	9.23	50.74	74.00	-23.26	H	Peak

REMARKS:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.*
3. *Average test would be performed if the peak result were greater than the average limit or as required by the applicant.*
4. *Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*
5. *Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.*
6. *Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode: TX / IEEE 802.11n HT20 MHz (CH Mid) **Tested by:** Jack Chen

Ambient temperature: 24°C **Relative humidity:** 52% RH **Date:** May 17, 2016

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1882.000	51.20	-5.75	45.45	74.00	-28.55	V	Peak
3250.000	53.82	-0.94	52.88	74.00	-21.12	V	Peak
3250.000	53.40	-0.94	52.46	54.00	-1.54	V	AVG
4879.000	41.55	4.59	46.14	74.00	-27.86	V	Peak
5329.000	40.88	5.57	46.45	74.00	-27.55	V	Peak
6544.000	41.83	6.96	48.79	74.00	-25.21	V	Peak
8677.000	41.49	9.28	50.77	74.00	-23.23	V	Peak
3250.000	54.83	-0.94	53.89	74.00	-20.11	H	Peak
3250.000	51.30	-0.94	50.36	54.00	-3.64	H	AVG
4870.000	47.19	4.56	51.75	74.00	-22.25	H	Peak
6742.000	41.52	7.28	48.80	74.00	-25.20	H	Peak
7255.000	40.99	8.20	49.19	74.00	-24.81	H	Peak
8137.000	41.20	9.57	50.77	74.00	-23.23	H	Peak
8776.000	41.67	9.22	50.89	74.00	-23.11	H	Peak

REMARKS:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.*
3. *Average test would be performed if the peak result were greater than the average limit or as required by the applicant.*
4. *Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*
5. *Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.*
6. *Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode: TX / EEE 802.11n HT20 MHz (CH High) **Tested by:** Jack Chen

Ambient temperature: 24°C **Relative humidity:** 52% RH **Date:** May 17, 2016

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1882.000	55.03	-5.75	49.28	74.00	-24.72	V	Peak
3286.000	53.64	-0.88	52.76	74.00	-21.24	V	Peak
3286.000	53.19	-0.88	52.31	54.00	-1.69	V	AVG
5059.000	41.18	5.09	46.27	74.00	-27.73	V	Peak
6553.000	41.09	6.98	48.07	74.00	-25.93	V	Peak
7201.000	41.44	8.09	49.53	74.00	-24.47	V	Peak
7795.000	40.47	9.25	49.72	74.00	-24.28	V	Peak
3286.000	53.99	-0.88	53.11	74.00	-20.89	H	Peak
3286.000	53.66	-0.88	52.78	54.00	-1.22	H	AVG
4924.000	44.95	4.73	49.68	74.00	-24.32	H	Peak
5473.000	41.39	5.82	47.21	74.00	-26.79	H	Peak
6814.000	40.02	7.40	47.42	74.00	-26.58	H	Peak
7237.000	41.00	8.16	49.16	74.00	-24.84	H	Peak
8263.000	41.37	9.51	50.88	74.00	-23.12	H	Peak

REMARKS:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.*
3. *Average test would be performed if the peak result were greater than the average limit or as required by the applicant.*
4. *Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*
5. *Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.*
6. *Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Combine with Antenna 1 and Antenna 2

Test Mode: TX/ IEEE 802.11n HT40 MHz (CH Low) **Tested by:** Jack Chen

Ambient temperature: 24°C **Relative humidity:** 52% RH **Date:** May 17, 2016

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1882.000	54.13	-5.75	48.38	74.00	-25.62	V	Peak
3232.000	55.25	-0.97	54.28	74.00	-19.72	V	Peak
3232.000	52.30	-0.97	51.33	54.00	-2.67	V	AVG
4834.000	46.85	4.44	51.29	74.00	-22.71	V	Peak
5752.000	41.69	5.98	47.67	74.00	-26.33	V	Peak
6805.000	41.46	7.38	48.84	74.00	-25.16	V	Peak
8452.000	41.94	9.40	51.34	74.00	-22.66	V	Peak
3232.000	55.77	-0.97	54.80	74.00	-19.20	H	Peak
3232.000	53.65	-0.97	52.68	54.00	-1.32	H	AVG
4843.000	47.35	4.47	51.82	74.00	-22.18	H	Peak
6058.000	40.89	6.17	47.06	74.00	-26.94	H	Peak
6733.000	40.42	7.27	47.69	74.00	-26.31	H	Peak
7651.000	40.99	8.97	49.96	74.00	-24.04	H	Peak
8452.000	40.46	9.40	49.86	74.00	-24.14	H	Peak

REMARKS:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.*
3. *Average test would be performed if the peak result were greater than the average limit or as required by the applicant.*
4. *Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*
5. *Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.*
6. *Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode: TX / IEEE 802.11n HT40 MHz (CH Mid) **Tested by:** Jack Chen

Ambient temperature: 24°C **Relative humidity:** 52% RH **Date:** May 17, 2016

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1882.000	51.25	-5.75	45.50	74.00	-28.50	V	Peak
3250.000	53.32	-0.94	52.38	74.00	-21.62	V	Peak
3250.000	52.96	-0.94	52.02	54.00	-1.98	V	AVG
5068.000	41.33	5.10	46.43	74.00	-27.57	V	Peak
6814.000	40.16	7.40	47.56	74.00	-26.44	V	Peak
7588.000	40.28	8.85	49.13	74.00	-24.87	V	Peak
7750.000	40.85	9.16	50.01	74.00	-23.99	V	Peak
1324.000	49.61	-7.34	42.27	74.00	-31.73	H	Peak
3250.000	55.27	-0.94	54.33	74.00	-19.67	H	Peak
3250.000	52.27	-0.94	51.33	54.00	-2.67	H	AVG
4870.000	43.64	4.56	48.20	74.00	-25.80	H	Peak
5572.000	40.64	5.90	46.54	74.00	-27.46	H	Peak
6733.000	41.19	7.27	48.46	74.00	-25.54	H	Peak
7741.000	40.53	9.14	49.67	74.00	-24.33	H	Peak

REMARKS:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.*
3. *Average test would be performed if the peak result were greater than the average limit or as required by the applicant.*
4. *Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*
5. *Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.*
6. *Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Mode: TX/ IEEE 802.11n HT40 MHz (CH High) **Tested by:** Jack Chen

Ambient temperature: 24°C **Relative humidity:** 52% RH **Date:** May 17, 2016

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1765.000	50.94	-6.35	44.59	74.00	-29.41	V	Peak
3268.000	54.28	-0.91	53.37	74.00	-20.63	V	Peak
3268.000	53.85	-0.91	52.94	54.00	-1.06	V	AVG
4879.000	42.82	4.59	47.41	74.00	-26.59	V	Peak
5545.000	41.33	5.89	47.22	74.00	-26.78	V	Peak
6274.000	41.36	6.52	47.88	74.00	-26.12	V	Peak
6877.000	41.70	7.50	49.20	74.00	-24.80	V	Peak
1765.000	53.64	-6.35	47.29	74.00	-26.71	H	Peak
3268.000	54.86	-0.91	53.95	74.00	-20.05	H	Peak
3268.000	51.99	-0.91	51.08	54.00	-2.92	H	AVG
5320.000	40.73	5.55	46.28	74.00	-27.72	H	Peak
6130.000	41.00	6.29	47.29	74.00	-26.71	H	Peak
6958.000	40.98	7.63	48.61	74.00	-25.39	H	Peak
7939.000	40.38	9.53	49.91	74.00	-24.09	H	Peak

REMARKS:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.*
3. *Average test would be performed if the peak result were greater than the average limit or as required by the applicant.*
4. *Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*
5. *Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.*
6. *Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).*

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

7.3. 6dB BANDWIDTH MEASUREMENT

7.3.1. LIMITS

According to §15.247(a)(2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz. The minimum 6 dB bandwidth shall be at least 500 kHz.

7.3.2. TEST INSTRUMENTS

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Calibration Due
Spectrum Analyzer	Agilent	N9010A	MY55370330	02/21/2016	02/20/2017

7.3.3. TEST PROCEDURES (please refer to measurement standard)

8.1 Option 1:

a) Set RBW = 100 kHz.
b) Set the video bandwidth (VBW) ≥ 3 x RBW.
c) Detector = Peak.
d) Trace mode = max hold.
e) Sweep = auto couple.
f) Allow the trace to stabilize.
g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.3.4. TEST SETUP



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

7.3.5. TEST RESULTS

No non-compliance noted

Test Data

Test mode: IEEE 802.11b (Antenna 1)

Channel	Frequency (MHz)	Bandwidth (kHz)	Limit (kHz)	Test Result
Low	2412	16140	>500	PASS
Mid	2437	16120		PASS
High	2462	15130		PASS

Test mode: IEEE 802.11b (Antenna 2)

Channel	Frequency (MHz)	Bandwidth (kHz)	Limit (kHz)	Test Result
Low	2412	14750	>500	PASS
Mid	2437	14780		PASS
High	2462	14750		PASS

Test mode: IEEE 802.11g (Antenna 1)

Channel	Frequency (MHz)	Bandwidth (kHz)	Limit (kHz)	Test Result
Low	2412	3000	>500	PASS
Mid	2437	3000		PASS
High	2462	19600		PASS

Test mode: IEEE 802.11g (Antenna 2)

Channel	Frequency (MHz)	Bandwidth (kHz)	Limit (kHz)	Test Result
Low	2412	19740	>500	PASS
Mid	2437	19930		PASS
High	2462	19700		PASS

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test mode: IEEE 802.11n HT20 MHz (Antenna 1)

Channel	Frequency (MHz)	Bandwidth (kHz)	Limit (kHz)	Test Result
Low	2412	3000	>500	PASS
Mid	2437	3000		PASS
High	2462	19740		PASS

Test mode: IEEE 802.11n HT20 MHz (Antenna 2)

Channel	Frequency (MHz)	Bandwidth (kHz)	Limit (kHz)	Test Result
Low	2412	20190	>500	PASS
Mid	2437	20220		PASS
High	2462	20160		PASS

Test mode: IEEE 802.11n HT40 MHz (Antenna 1)

Channel	Frequency (MHz)	Bandwidth (kHz)	Limit (kHz)	Test Result
Low	2422	58250	>500	PASS
Mid	2437	51790		PASS
High	2452	56240		PASS

Test mode: IEEE 802.11n HT40 MHz (Antenna 2)

Channel	Frequency (MHz)	Bandwidth (kHz)	Limit (kHz)	Test Result
Low	2422	39360	>500	PASS
Mid	2437	39640		PASS
High	2452	39690		PASS

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test Plot

IEEE 802.11b mode (Antenna 1)

6dB Bandwidth (CH Low)



6dB Bandwidth (CH Mid)



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

6dB Bandwidth (CH High)



IEEE 802.11b mode (Antenna 2)

6dB Bandwidth (CH Low)



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

6dB Bandwidth (CH Mid)



6dB Bandwidth (CH High)



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

IEEE 802.11g mode (Antenna 1)

6dB Bandwidth (CH Low)



6dB Bandwidth (CH Mid)



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

6dB Bandwidth (CH High)



IEEE 802.11g mode (Antenna 2)

6dB Bandwidth (CH Low)



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

6dB Bandwidth (CH Mid)



6dB Bandwidth (CH High



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

IEEE 802.11n HT20 MHz mode (Antenna 1)

6dB Bandwidth (CH Low)



6dB Bandwidth (CH Mid)



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

6dB Bandwidth (CH High)



IEEE 802.11n HT20 MHz mode (Antenna 2)

6dB Bandwidth (CH Low)



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.