RF Test Report

Applicant	:	u-blox AG
Product Name	:	Host-based multiradio module
Trade Name	:	u-blox
Model Number	:	MAYA-W276-00B
Applicable Standard	:	FCC 47 CFR PART 15 SUBPART E ANSI C63.10:2013
Received Date	:	Nov. 09, 2023
Test Period	:	Nov. 23 ~ Dec. 01, 2023
Issued Date	:	Dec. 22, 2023

Issued by

Eurofins E&E Wireless Taiwan Co., Ltd.
No. 140-1, Changan Street, Bade District,
Taoyuan City 334025, Taiwan (R.O.C.)
Tel：+886-3-2710188 / Fax：+886-3-2710190

Taiwan Accreditation Foundation accreditation number: 1330
Frequency Range : 9 kHz to 40 GHz
Test Firm Registration Number: 226252 (Bade test site)
Test Firm Registration Number: 191812 (Wugu test site)

Note:

1.The test results are valid only for samples provided by customers and under the test conditions described in this report.
2.This report shall not be reproduced except in full, without the written approval of Eurofins E&E Wireless Taiwan Co., Ltd.
3.The relevant information is provided by customers in this test report. According to the correctness, appropriateness or completeness of the information provided by the customer, if there is any doubt or error in the information which affects the validity of the test results, the laboratory does not take the responsibility.

Revision History

Rev.	Issued Date	Description	Revised By
00	Dec. 22, 2023	Initial Issue	Abby Huang

Verification of Compliance

Applicant	:	u-blox AG
Product Name	:	Host-based multiradio module
Trade Name	:	u-blox
Model Number	:	MAYA-W276-00B
FCC ID	:	XPYMAYAW2B
Applicable Standard	:	FCC 47 CFR PART 15 SUBPART E ANSI C63.10:2013
Test Result	:	Complied
Performing Lab.	:	Eurofins E&E Wireless Taiwan Co., Ltd. No. 140-1, Changan Street, Bade District, Taoyuan City 334025, Taiwan (R.O.C.) Tel：+886-3-2710188 / Fax：+886-3-2710190 Taiwan Accreditation Foundation accreditation number: 1330

Testing Laboratory 1330

Eurofins E&E Wireless Taiwan Co., Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by Eurofins E&E Wireless Taiwan Co., Ltd. based on interpretations and/or observations of test results. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Approved By :

TABLE OF CONTENTS

1 General Information 5
1.1. Summary of Test Result 5
1.2. Testing Location 6
1.3. Measurement Uncertainty 6
1.4. Test Site Environment 6
2 EUT Description 7
3 Test Methodology 10
3.1. Mode of Operation 10
3.2. EUT Test Step 12
3.3. Configuration of Test System Details 13
3.4. Test Instruments 15
4 Measurement Procedure 18
4.1. AC Power Conducted Emission Measurement 18
4.2. Transmitter Radiated Emissions Measurement 20
4.3. Maximum Conducted Output Power Measurement 25
4.4. 6 dB RF Bandwidth Measurement 26
4.5. Maximum Power Spectral Density Measurement 27
4.6. Automatically discontinue transmission 29
4.7. Antenna Requirement 29
5 Test Results 30
5.1. Conducted Emission 30
5.2. Radiated Emission Measurement 34
5.3. Conducted Test Results 126

Appendix A. Test Data
Appendix B. Test Plots
Appendix C. Test Setup Photographs

1 General Information

1.1. Summary of Test Result

Standard	Item	Result	Remark
15.407(b)(9) 15.207	AC Power Conducted Emission	PASS	---
15.407(b) 15.205 / 15.209	Transmitter Radiated Emissions	PASS	---
15.407(a)	Maximum Conducted Output Power	PASS	---
15.407(e)	6 dB RF Bandwidth	PASS	---
15.407(a)	Maximum Power Spectral Density	PASS	---
15.407(c)	Automatically discontinue transmission	PASS	---
15.407(a) 15.203	Antenna Requirement	PASS	---

Decision Rule

■ Uncertainty is not included.

□ Uncertainty is included.

Standard	Description
CFR47, Part 15, Subpart C	Intentional Radiators
CFR47, Part 15, Subpart E	Unlicensed National Information Infrastructure Devices
ANSI C63. 10: 2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
KDB789033: D02	Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices Part 15, Subpart E
KDB 662911 D01 v02r01	Emissions Testing of Transmitters with Multiple Outputs in the Same Band (e.g., MIMO, Smart Antenna, etc)

1.2. Testing Location

Lab Name: Eurofins E&E Wireless Taiwan Co., Ltd.

Site Address: ☐ No. 140-1, Changan Street, Bade District, Taoyuan City 334025, Taiwan (R.O.C.)

Site Address: ■ No. 2, Wuquan 5th Rd. Wugu Dist., New Taipei City, Taiwan (R.O.C.)

1.3. Measurement Uncertainty

Test Item	Frequency	Uncertainty	
		BD	WG
Conducted Emission	150 kHz ~ 30 MHz	2.7 dB	2.6 dB
Conducted Output Power		1.1 dB	1.1 dB
RF Bandwidth		4.5 %	4.5 %
Power Spectral Density		1.1 dB	1.1 dB
Duty Cycle		1.1 %	1.0 %
Time Occupancy		1.5 %	1.2 %

Test Item	Frequency	Uncertainty			
		96601-BD	96603-BD	96602-WG	96603-WG
Radiated Emission	9 kHz ~ 30 MHz	1.9 dB	1.9 dB	1.6 dB	1.6 dB
	30 MHz ~ 1000 MHz	4.9 dB	4.9 dB	4.8 dB	4.8 dB
	1000 MHz ~ 18000 MHz	4.9 dB	5.0 dB	5.0 dB	5.2 dB
	18000 MHz ~ 26500 MHz	4.3 dB	4.4 dB	4.4 dB	4.5 dB
	26500 MHz ~ 40000 MHz	4.5 dB	4.5 dB	4.6 dB	4.5 dB

1.4. Test Site Environment

Items	Required (IEC 60068-1)	Interval(*)
Temperature (°C)	15-35	20-30
Humidity (%RH)	25-75	45-75

(*)The measurement ambient temperature is within this range.

2 EUT Description

The product specifications of the EUT presented in the report are declared by the manufacturer who shall take full responsibility for the authenticity(except Max. RF Output Power, EIRP).

Applicant	u-blox AG Zürcherstrasse 68, 8800 Thalwil, Switzerland			
Product Name	Host-based multiradio module			
Trade Name	u-blox			
Model Number	MAYA-W276-00B			
FCC ID	XPYMAYAW2B			
Operate Frequency	Frequency Band		Frequency Range (MHz)	
	802.11a	U-NII Band 4 (5850 - 5895 MHz)	5845 – 5885	
	802.11n HT20 / 802.11ac VHT20/ 802.11ax HE20	U-NII Band 4 (5850 - 5895 MHz)	5845 – 5885	
	802.11n HT40 / 802.11ac VHT40/ 802.11ax HE40	U-NII Band 4 (5850 - 5895 MHz)	5835 – 5875	
	802.11ac VHT80 / 802.11ax HE80	U-NII Band 4 (5850 - 5895 MHz)	5855	
Modulation Type	OFDM/OFDMA			
Antenna information	Model	Type	Max. Gain (dBi)	
	ANT-DB1-RAF-SAM	Dipole Antenna	5.1	
	custom	Integrated Antenna	U-NII Band 4	-7.0
Operate Temp. Range	-40 ~ +85 ℃			
EUT Power Rating	3.3 V			

EUT Modify Description：

Modify Description :

1.C44 and C47 shifted down by hundreds of micrometers. Buffer capacitors only. No impact expected on RF Performance / Characteristics.

2.New Module Shield added. Larger cutout on bottom side. No impact expected on RF Performance / Characteristics. No/Low impact on radiated measurements expected.

3.BGA pads on HW Rev C are solder mask defined with exposed copper pads area diameter area of 170um compared to the BGAs pads on HW Rev B which are not solder mask defined with exposed landing pads area diameter of 180um → No impact expected on RF Performance / Characteristics

4.add band4 5850 MHz~5895 MHz

The difference will influence the test results. Therefore, band4 5850 MHz~5895 MHz, all test items need to be re-evaluated.

Frequency Band		Max. RF Output Power (W)
802.11a	U-NII Band 4 (5850 - 5895 MHz)	0.033
802.11n HT20	U-NII Band 4 (5850 - 5895 MHz)	0.032
802.11n HT40	U-NII Band 4 (5850 - 5895 MHz)	0.032
802.11ac VHT20	U-NII Band 4 (5850 - 5895 MHz)	0.032
802.11ac VHT40	U-NII Band 4 (5850 - 5895 MHz)	0.032
802.11ac VHT80	U-NII Band 4 (5850 - 5895 MHz)	0.015
802.11ax HE20	U-NII Band 4 (5850 - 5895 MHz)	0.034
802.11ax HE40	U-NII Band 4 (5850 - 5895 MHz)	0.035
802.11ax HE80	U-NII Band 4 (5850 - 5895 MHz)	0.017

Frequency Band (5.850-5.895 GHz band or spans across 5.725-5.895 GHz)		EIRP (W)
802.11a	U-NII Band 4 (5850 - 5895 MHz)	105.196
802.11n HT20	U-NII Band 4 (5850 - 5895 MHz)	103.039
802.11n HT40	U-NII Band 4 (5850 - 5895 MHz)	103.992
802.11ac VHT20	U-NII Band 4 (5850 - 5895 MHz)	104.232
802.11ac VHT40	U-NII Band 4 (5850 - 5895 MHz)	104.954
802.11ac VHT80	U-NII Band 4 (5850 - 5895 MHz)	49.659
802.11ax HE20	U-NII Band 4 (5850 - 5895 MHz)	111.173
802.11ax HE40	U-NII Band 4 (5850 - 5895 MHz)	112.980
802.11ax HE80	U-NII Band 4 (5850 - 5895 MHz)	53.951

Equipment Type		
Outdoor access point	point-to-point	---
	point-to-multipoint	---
Indoor access point		---
Fixed point-to-point access points		---
Client devices		V

WIFI 5G

5850 MHz ~5895 MHz(UNII-4):

BW 20M	CH	NA	169	173	177
	Freq. (MHz)		5845	5865	5885
BW 40M	CH	167		175	
	Freq. (MHz)	5835		5875	
BW 80M	CH	171			
	Freq. (MHz)	5855			

Note: 5850~5895 MHz is not available for operation in Canada.

3 Test Methodology

3.1. Mode of Operation

Decision of Test Eurofins has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was shown in this test report and defined as:

Pre-Test Mode	Final-Test Mode
Transmit mode	V
802.11a	V
802.11n HT20	
802.11n HT40	
802.11ac VHT20	V
802.11ac VHT40	V
802.11ac VHT80	V
802.11ax HE20	V
802.11ax HE40	V
802.11ax HE80	V

Software used to control the EUT for staying in continuous transmitting mode was programmed.
After verification, all tests were carried out with the worst case test modes.

By preliminary testing and verifying three axis (X, Y and Z) position of EUT transmitted status, it was found that “Z axis” position was the worst, then the final test was executed the worst condition and test data were recorded in this report.

Note 1: Investigation has been done on all the possible configurations for searching the worst cases (VHT20/VHT40 covers HT20/HT40). The table is a list of the test modes show in this test report.
Note 2: PSD Full > PSD Partial, so in this report Full RU Cover Partial RU.

Test Mode	ANT-0
802.11a	V
802.11n HT20	V
802.11n HT40	V
802.11ac VHT20	V
802.11ac VHT40	V
802.11ac VHT80	V
802.11ax HE20	V
802.11ax HE40	V
802.11ax HE80	V

Test Mode	Antenna Delivery	Data Rate (Mbps)	Band	Test Channel
802.11a	1TX	6	U-NII Band 4 (5850 - 5895 MHz)	169, 173, 177
802.11n HT20	1TX	6.5	U-NII Band 4 (5850 - 5895 MHz)	169, 173, 177
802.11n HT40	1TX	13.5	U-NII Band 4 (5850 - 5895 MHz)	167, 175
802.11ac VHT20	1TX	6.5	U-NII Band 4 (5850 - 5895 MHz)	169, 173, 177
802.11ac VHT40	1TX	13.5	U-NII Band 4 (5850 - 5895 MHz)	167, 175
802.11ac VHT80	1TX	29.3	U-NII Band 4 (5850 - 5895 MHz)	171
802.11ax HE20	1TX	MCS 0	U-NII Band 4 (5850 - 5895 MHz)	169, 173, 177
802.11ax HE40	1TX	MCS 0	U-NII Band 4 (5850 - 5895 MHz)	167, 175
802.11ax HE80	1TX	MCS 0	U-NII Band 4 (5850 - 5895 MHz)	171

3.2. EUT Test Step

The EUT is operated in the engineering mode to fix the TX frequency for the purposes of measurement. According to its specifications, the EUT must comply with the requirements of Section 15.407 under the FCC Rules Part 15 Subpart E.

1.	Setup the EUT shown on “Configuration of Test System Details”.
2.	Turn on the power of all equipment.
3.	Turn on TX function.
4.	EUT run test program.

3.3. Configuration of Test System Details

Radiated Emission (Below 1 GHz)



Radiated Emission (Above 1 GHz)



Conduction Emission



Product		Manufacturer	Model Number	Serial Number	Power Cord
(1)	Notebook	Dell	P28S	---	---
(2)	Evaluation Kit for the i.MX 8M Mini Applications Processor	NXP	8MMINILPD4-EVKB	---	---
(3)	USB 5Gbps (USB 3.0, USB 3.x Gen 1. Superspeed) cable USB-A plug to USB-C plug 3,28' (1,00m) shielded.	CUI Devices	CBL-UA-UC-1	---	---
(4)	Power Supply	Gwinstek	PLR60-6	GEV172753	---
(5)	Power Supply	Gwinstek	PLR60-6	GEV172754	---

3.4. Test Instruments

For Conducted
Test Period: Nov. 23 ~ Nov. 28, 2023
Testing Engineer: Ethan Hsu

Test Site		RF03-WG				
Use	Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Cal. Period
☒	Spectrum Analyzer (10 Hz~26.5 GHz)	Keysight	N9010B	MY63460164	Mar. 07, 2023	1 year
☒	Power Sensor	Anritsu	MA24408A	11998	Feb. 07, 2023	1 year

For Conduction Emissions
Test Period: Dec. 01, 2023
Testing Engineer: Marin Lee

Radiation test sites		Conducted Emission Measurement Conduction01-WG				
Use	Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Cal. Period
☒	Test Receiver	R&S	ESR3	102919	Nov 30, 2023	1 year
☒	LISN	R&S	ENV216	101041	Apr 12, 2023	1 year
☒	Current Probe	R&S	EZ-17	101687	Jun 15, 2023	1 year
☒	Cable	EMCI	EMCCFD300-BM-NM-4000	220402	Jun 08, 2023	1 year
☒	Software	ELEKTRA	94.50.4	N.A.	N.C.R.	N.C.R.

Note: N.C.R. = No Calibration Request.

For Radiated Emissions
Test Period: Nov. 27 ~ Nov. 28, 2023
Testing Engineer: Marin Lee

Radiation test sites		Semi Anechoic Room 96603-WG				
Use	Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Cal. Period
☒	LOOP Antenna (9 kHz~30 MHz)	Schwarzbeck Mess-Elektronik	FMZB 1513-60	00031	Feb. 21, 2023	1 year
☒	Trilog Broadband Antenna (30 MHz~1 GHz)	Schwarzbeck Mess-Elektronik	VULB9168	01276	Feb. 09, 2023	1 year
☒	Broadband Horn Antenna (1 GHz~18 GHz)	RF SPIN	DRH18-E	210305A18ES	Feb. 21, 2023	1 year
☒	Broadband Horn Antenna (15 GHz~40 GHz)	Schwarzbeck Mess-Elektronik	BBHA9170	01133	Feb. 13, 2023	1 year
☒	Spectrum Analyzer (10 Hz~44 GHz)	KEYSIGHT	N9020B	MY60112362	Feb. 16, 2023	1 year
☒	Pre-Amplifier	Agilent	8447D	2944A10961	Jul. 10, 2023	1 year
☒	Pre-Amplifier	EMCI	EMC118A45SE	980876	Feb. 13, 2023	1 year
☒	Pre-Amplifier	EMCI	EMC184045SE	980861	Dec. 27, 2022	1 year
☒	Coaxial Cable (10 kHz~3000 MHz)	EMCI	EMCCFD400-NM-NM-2000	211006	Nov. 13, 2023	1 year
☒	Coaxial Cable (10 kHz~3000 MHz)	EMCI	EMCCFD400-NM-NM-2000	211007	Nov. 13, 2023	1 year
☒	Coaxial Cable (10 kHz~3000 MHz)	EMCI	EMCCFD400-NM-NM-6000	211015	Nov. 13, 2023	1 year

Note: N.C.R. = No Calibration Request.

For Radiated Emissions
Test Period: Nov. 27 ~ Nov. 28, 2023
Testing Engineer: Marin Lee

Radiation test sites		Semi Anechoic Room 96603-WG				
Use	Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Cal. Period
☒	Coaxial Cable (1 GHz~18 GHz)	EMCI	EMC104-SM-SM-1000	211026	Nov. 13, 2023	1 year
☒	Coaxial Cable (1 GHz~18 GHz)	EMCI	EMC104-SM-SM-2000	211035	Nov. 13, 2023	1 year
☒	Coaxial Cable (1 GHz~18 GHz)	EMCI	EMC104-SM-SM-8000	211036	Nov. 13, 2023	1 year
☒	Coaxial Cable (18 GHz~40 GHz)	EMCI	EMC101G-KM-KM-600	211211	Jan. 19, 2023	1 year
☒	Coaxial Cable (18 GHz~40 GHz)	EMCI	EMC101G-KM-KM-2000	211210	Jan. 19, 2023	1 year
☒	Coaxial Cable (18 GHz~40 GHz)	EMCI	EMC101G-KM-KM-6000	211209	Jan. 19, 2023	1 year
☒	Highpass Filter	Warison	WFIL-H8000-26000F	001	Nov. 13, 2023	1 year
☒	Software	R_RAM	V1.3	N/A	N.C.R.	---

Note: N.C.R. = No Calibration Request.

4 Measurement Procedure

4.1. AC Power Conducted Emission Measurement

■ **Limit**

Frequency (MHz)	Quasi-peak	Average
0.15 - 0.5	66 to 56	56 to 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

■ **Test Setup**



■ **Test Procedure**

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50 Ω// 50 uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50 Ω// 50 uH coupling impedance with 50 ohm termination.

Tabletop device shall be placed on a non-conducting platform, of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The wall of screened room shall be located 40 cm to the rear of the EUT. Other surfaces of tabletop or floor standing EUT shall be at least 80 cm from any other ground conducting surface including one or more LISNs. For floor-standing device shall be placed under the EUT with a 12 mm insulating material.

Conducted emissions were investigated over the frequency range from 0.15 MHz to 30 MHz using a resolution bandwidth of 9 kHz. The equipment under test (EUT) shall be meet the limits in section 4.1, as applicable, including the average limit and the quasi-peak limit when using respectively, an average detector and quasi-peak detector measured in accordance with the methods described of related standard. When all of peak value were complied with quasi-peak and average limit from 150 kHz to 30 MHz then quasi-peak and average measurement was unnecessary.

The AMN shall be placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for AMNs mounted on top of the ground reference plane. This distance is between the closest points of the AMN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8 m from the AMN. If the mains power cable is longer than 1 m then the cable shall be folded back and forth at the centre of the lead to form a bundle no longer than 0.4 m. All of interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 cm to 40 cm long. All of EUT and AE shall be separate place more than 0.1 m. All 50 Ω ports of the LISN shall be resistively terminated into 50 Ω loads when not connected to the measuring instrument.

If the reading of the measuring receiver shows fluctuations close to the limit, the reading shall be observed for at least 15 s at each measurement frequency; the higher reading shall be recorded with the exception of any brief isolated high reading which shall be ignored

4.2. Transmitter Radiated Emissions Measurement

■ **Limit**

(1)Undesirable emission limits. Except as shown in paragraph (b)(9) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

(e) For transmitters operating solely in the 5.850-5.895 GHz band or operating on a channel that spans across 5.725-5.895 GHz:

Device Type		Limit
☐	indoor access point	(i) all emissions at or above 5.895 GHz shall not exceed an e.i.r.p. of 15 dBm/MHz and shall decrease linearly to an e.i.r.p. of −7 dBm/MHz at or above 5.925 GHz. (ii) all emissions below 5.725 GHz shall not exceed an e.i.r.p. of −27 dBm/MHz at 5.65 GHz increasing linearly to 10 dBm/MHz at 5.7 GHz, and from 5.7 GHz increasing linearly to a level of 15.6 dBm/MHz at 5.72 GHz, and from 5.72 GHz increasing linearly to a level of 27 dBm/MHz at 5.725 GHz.
☐	subordinate	
■	client	(i) all emissions at or above 5.895 GHz shall not exceed an e.i.r.p. of −5 dBm/MHz and shall decrease linearly to an e.i.r.p. of −27 dBm/MHz at or above 5.925 GHz. (ii) all emissions below 5.725 GHz shall not exceed an e.i.r.p. of −27 dBm/MHz at 5.65 GHz increasing linearly to 10 dBm/MHz at 5.7 GHz, and from 5.7 GHz increasing linearly to a level of 15.6 dBm/MHz at 5.72 GHz, and from 5.72 GHz increasing linearly to a level of 27 dBm/MHz at 5.725 GHz.

IRP (dBm)	Field Strength at 3 m(dBuV/m)
-27	68.3

(2)Limits of Radiated Emission Measurement

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequency Range (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	10	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Note: 1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

■ **Setup**

9 kHz ~ 30 MHz



30 MHz ~ 1 GHz



Above 1 GHz



■ **Test Procedure**

Final radiation measurements were made on a three-meter, Semi Anechoic Chamber. The EUT system was placed on a nonconductive turntable which is 0.8 or 1.5 meters height(below 1 GHz use 0.8 m turntable / above 1 GHz use 1.5 m turntable), top surface 1.0 x 1.5 meter. The spectrum was examined from 250 MHz to 2.5 GHz in order to cover the whole spectrum below 10th harmonic which could generate from the EUT. During the test, EUT was set to transmit continuously & Measurements spectrum range from 9 kHz to 40 GHz is investigated.

For measurements below 30 MHz the resolution bandwidth is set to 10 kHz for peak detection measurements or 9 kHz for quasi-peak detection measurements. The video bandwidth is 3 times of the resolution bandwidth.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For restricted measurements above 1 GHz the resolution bandwidth is set to 1 MHz, and then the video bandwidth is set to 3 MHz for peak measurements and 10 Hz for average measurements when Duty cycle > 0.98 / 1/T for average measurements when Duty cycle < 0.98.

For out of band measurements above 1 GHz the resolution bandwidth is set to 1 MHz, and then the video bandwidth is set to 3 MHz for peak measurements.

A nonconductive material surrounded the EUT to supporting the EUT for standing on tree orthogonal planes. At each condition, the EUT was rotated 360 degrees, and the antenna was raised and lowered from one to four meters to find the maximum emission levels. Measurements were taken using both horizontal and vertical antenna polarization.

SCHWARZBECK MESS-ELEKTRONIK Trilog-Broadband Antenna at 3 Meter and the ETS-Lindgren Double-Ridged Waveguide Horn antnna Schwarzbeck Mess-Elektronik Broadband Horn Antenna was used in frequencies 1 – 40 GHz at a distance of 3 meter. The antenna at an angle toward the source of the emission.All test results were extrapolated to equivalent signal at 3 meters utilizing an inverse linear distance extrapolation Factor (20 dB/decade).

For testing above 1 GHz, the emission level of the EUT in peak mode was 20 dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

Appropriate preamplifiers were used for improving sensitivity and precautions were taken to avoid overloading or desensitizing the spectrum analyzer. No post – detector video filters were used in the test.
The spectrum analyzer's 6 dB bandwidth was set to 1 MHz, and the analyzer was operated in the peak detection mode, for frequencies both below and up 1 GHz. The average levels were obtained by subtracting the duty cycle correction factor from the peak readings.

The following procedures were used to convert the emission levels measured in decibels referenced to 1 microvolt (dBuV) into field intensity in micro volts pre meter (uV/m).
The actual field intensity in decibels referenced to 1 microvolt in to field intensity in micro colts per meter (dBuV/m).

Data of measurement within this frequency range without mark in the table above means the reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.

The actual field is intensity in referenced to 1 microvolt per meter (dBuV/m) is determined by algebraically adding the measured reading in dBuV, the antenna factor (dB), and cable loss (dB) and Subtracting the gain of preamplifier (dB) is auto calculate in spectrum analyzer.

(1) Amplitude (dBuV/m) = FI (dBuV) +AF (dBuV) +CL (dBuV)-Gain (dB)
FI= Reading of the field intensity.
AF= Antenna factor.
CL= Cable loss.
P.S Amplitude is auto calculate in spectrum analyzer.

(2) Actual Amplitude (dBuV/m) = Amplitude (dBuV)-Dis(dB)
The FCC specified emission limits were calculated according the EUT operating frequency and by following linear interpolation equations:
(a) For fundamental frequency : Transmitter Output < +30 dBm
(b) For spurious frequency : Spurious emission limits = fundamental emission limit /10

Measuring Instruments and setting

The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	40 GHz
RBW/VBW(Emission in restricted band)	1 MHz / 3 MHz for Peak 1 MHz / (1/T) for Average
RBW/VBW(Emission in non-restricted band)	1 MHz / 3 MHz for Peak

4.3. Maximum Conducted Output Power Measurement

■ **Limit**

Frequency Range (MHz)		5.850 ~ 5.895 GHz or spans across 5.725-5.895 GHz
Device Type		EIRP Limit
☐	indoor access point	The maximum e.i.r.p. over the frequency band of operation must not exceed 36 dBm. Indoor access points operating on a channel that spans the 5.725-5.850 GHz and 5.850-5.895 GHz bands must not exceed an e.i.r.p. of 36 dBm.
☐	subordinate	The maximum e.i.r.p. over the frequency band of operation must not exceed 36 dBm.
■	client	The maximum e.i.r.p. over the frequency band of operation must not exceed 30 dBm. Client devices operating on a channel that spans the 5.725-5.850 GHz and 5.850-5.895 GHz bands must not exceed an e.i.r.p. of 30 dBm.

According FCC KDB 662911 D01 v02r01 – for power measurements on IEEE802.11 devices,

■ **Test Setup**



■ **Test Procedure**

The test is performed in accordance with ANSI C63.10:2013 section 12.3.3.2, Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices
Section (E) Maximum Conducted Output Power
3. Measurement using a Power Meter (PM)
b) Method PM-G (Measurement using a gated RF average power meter)

4.4. 6 dB RF Bandwidth Measurement

■ **Limit**

6 dB RF Bandwidth

Systems using digital modulation techniques may operate in the 5850~5895 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

■ **Test Setup**



■ **Test Procedure**

6 dB RF Bandwidth

The EUT tested to UNII test procedure of ANSI C63.10:2013 section 6.9.2 for compliance to FCC 47CFR 15.407 requirements.

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RES BW was set to 100 kHz. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A peak output reading was taken, a DISPLAY line was drawn 6 dB lower than peak level. The 6 dB bandwidth was determined from where the channel output spectrum intersected the display line.

The test was performed at 3 channels.

4.5. Maximum Power Spectral Density Measurement

■ **Limit**

EIRP spectral density

Frequency Range (MHz)		5.850 ~ 5.895 GHz
Device Type		EIRP spectral density Limit
☐	indoor access point	20 dBm/MHz
☐	subordinate	
■	client	14 dBm/MHz

Note: EIRP spectral density = conducted power spectral density + Directional Gain

According FCC KDB 662911 D01 v02r01 – for power spectral density measurements on IEEE802.11 devices,

■ **Test Setup**



■ **Test Procedure**

The test is performed in accordance with ANSI C63.10:2013 section 12.5, Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices - Part 15, Subpart E.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RBW	1 MHz (5725 ~ 5895 MHz use 100 kHz)
VBW	3 MHz (5725 ~ 5895 MHz use 300 kHz)
Detector	RMS
Trace	AVERAGE
Sweep Time	Auto
Trace Average	100 times
Note: If measurement bandwidth of Maximum PSD is specified in 500 kHz or 1 MHz, add 10 log(500 kHz/100 kHz) or 10 log(1 MHz/100 kHz) to the measured result.	

4.6. Automatically discontinue transmission

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signalling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization a description of how this requirement is met.

■ **Declare**

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving.

The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.

4.7. Antenna Requirement

■ **Requirement**

For intentional device, according to 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.
And According to 15.407 (a), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

■ **Antenna Connector Construction**

See section 2 – antenna information.

■ **Directional Gain Calculated**

Test mode	Band	Transmission Type	Antenna				Directional Gain For Power (dBi)	Directional Gain For PSD (dBi)	Power Limit Reduction (dB)	PSD Limit Reduction (dB)
			Ant-0 (dBi)	Ant-1 (dBi)	Ant-2 (dBi)	Ant-3 (dBi)				
802.11a	Band 4	Ant-0	5.10	-	-	-	5.10	5.10	0.00	0.00
802.11n HT20 802.11n HT40 802.11ac VHT20 802.11ac VHT40 802.11ac VHT80 802.11ax HE20 802.11ax HE40 802.11ax HE80	Band 4	Ant-0	5.10	-	-	-	5.10	5.10	0.00	0.00

5 Test Results

5.1. Conducted Emission

Antenna model number: ANT-DB1-RAF-SAM

Standard:	FCC Part 15.407	Line:	L1
Test item:	Conducted Emission	Power:	AC 120 V/60 Hz
Test Mode:	Transmit mode		
Description:			

Rg	Frequency [MHz]	QP Result [dBµV]	QP Limit [dBµV]	QP Margin [dB]	AV Result [dBµV]	AV Limit [dBµV]	AV Margin [dB]	Correction factor [dB]	Line
1	0.159	48.02	65.52	17.50	30.57	55.52	24.94	9.64	L1
1	0.240	35.48	62.10	26.62	18.33	52.10	33.77	9.64	L1
1	0.416	23.17	57.54	34.36	11.82	47.54	35.71	9.65	L1
1	4.844	26.49	56.00	29.51	20.41	46.00	25.59	9.80	L1
1	14.082	33.04	60.00	26.96	27.51	50.00	22.49	10.01	L1
1	22.880	28.30	60.00	31.70	22.21	50.00	27.79	10.12	L1

Note: 1. Result (dBuV) = Correction factor (dB) + Reading(dBuV).

2. Correction factor (dB) = Cable loss (dB) + L.I.S.N. factor (dB).

Standard:	FCC Part 15.407	Line:	N
Test item:	Conducted Emission	Power:	AC 120 V/60 Hz
Test Mode:	Transmit mode		
Description:			



Rg	Frequency [MHz]	QP Result [dBµV]	QP Limit [dBµV]	QP Margin [dB]	AV Result [dBµV]	AV Limit [dBµV]	AV Margin [dB]	Correction factor [dB]	Line
1	0.150	46.61	66.00	19.39	25.57	56.00	30.43	9.64	N
1	0.222	36.43	62.74	26.31	16.12	52.74	36.62	9.64	N
1	3.489	22.66	56.00	33.34	16.33	46.00	29.67	9.77	N
1	4.709	28.14	56.00	27.86	21.01	46.00	24.99	9.81	N
1	13.767	32.45	60.00	27.55	27.05	50.00	22.95	10.07	N
1	19.482	29.49	60.00	30.51	23.19	50.00	26.81	10.20	N

Note: 1. Result (dBuV) = Correction factor (dB) + Reading(dBuV).

2. Correction factor (dB) = Cable loss (dB) + L.I.S.N. factor (dB).

Antenna model number: custom

Standard:	FCC Part 15.407	Line:	L1
Test item:	Conducted Emission	Power:	AC 120 V/60 Hz
Test Mode:	Transmit mode		
Description:			

Rg	Frequency [MHz]	QP Result [dBµV]	QP Limit [dBµV]	QP Margin [dB]	AV Result [dBµV]	AV Limit [dBµV]	AV Margin [dB]	Correction factor [dB]	Line
1	0.150	48.58	66.00	17.42	29.86	56.00	26.14	9.65	L1
1	0.231	35.81	62.41	26.61	17.38	52.41	35.03	9.64	L1
1	1.842	22.50	56.00	33.50	17.19	46.00	28.81	9.72	L1
1	4.947	27.53	56.00	28.47	20.70	46.00	25.30	9.81	L1
1	13.898	33.34	60.00	26.66	27.80	50.00	22.20	10.00	L1
1	21.899	31.57	60.00	28.43	25.62	50.00	24.38	10.11	L1

Note: 1. Result (dBuV) = Correction factor (dB) + Reading(dBuV).

2. Correction factor (dB) = Cable loss (dB) + L.I.S.N. factor (dB).

Standard:	FCC Part 15.407	Line:	N
Test item:	Conducted Emission	Power:	AC 120 V/60 Hz
Test Mode:	Transmit mode		
Description:			



Rg	Frequency [MHz]	QP Result [dBµV]	QP Limit [dBµV]	QP Margin [dB]	AV Result [dBµV]	AV Limit [dBµV]	AV Margin [dB]	Correction factor [dB]	Line
1	0.159	48.34	65.52	17.17	31.94	55.52	23.58	9.64	N
1	0.303	31.46	60.16	28.70	17.05	50.16	33.11	9.64	N
1	3.606	25.69	56.00	30.31	16.85	46.00	29.15	9.78	N
1	5.010	26.10	60.00	33.90	18.98	50.00	31.02	9.82	N
1	13.979	32.97	60.00	27.03	27.52	50.00	22.48	10.08	N
1	21.989	30.65	60.00	29.35	24.84	50.00	25.16	10.24	N

Note: 1. Result (dBuV) = Correction factor (dB) + Reading(dBuV).

2. Correction factor (dB) = Cable loss (dB) + L.I.S.N. factor (dB).

5.2. Radiated Emission Measurement

Antenna model number: ANT-DB1-RAF-SAM			

Below 1 GHz

Test Site:	96602 - WG	Standard:	Part 15.247
Test Mode:	Normal Operation		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	67.79	47.30	-9.69	37.61	40.00	-2.39	QP
2	100.74	49.52	-12.01	37.51	43.50	-5.99	QP
3	277.10	42.86	-6.95	35.91	46.00	-10.09	QP
4	420.52	40.63	-4.32	36.31	46.00	-9.69	QP
5	624.99	37.36	-0.66	36.70	46.00	-9.30	QP
6	975.77	28.91	4.61	33.52	54.00	-20.48	QP

Test Site:	96602 - WG	Standard:	Part 15.247
Test Mode:	Normal Operation		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	37.53	44.71	-8.55	36.16	40.00	-3.84	QP
2	188.94	50.27	-9.69	40.58	43.50	-2.92	QP
3	332.34	39.33	-5.69	33.64	46.00	-12.36	QP
4	444.75	36.43	-3.66	32.77	46.00	-13.23	QP
5	720.92	33.03	0.98	34.01	46.00	-11.99	QP
6	992.25	29.64	5.09	34.73	54.00	-19.27	QP

Harmonic

Above 1 GHz

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT20 5845 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11690.00	41.41	7.68	49.09	74.00	-24.91	PEAK
2	17535.00	44.25	6.74	50.99	68.20	-17.21	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT20 5845 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11690.00	40.94	7.68	48.62	74.00	-25.38	PEAK
2	17535.00	44.59	6.74	51.33	68.20	-16.87	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT20 5865 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11730.00	41.03	7.67	48.70	74.00	-25.30	PEAK
2	17595.00	44.94	7.06	52.00	68.20	-16.20	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT20 5865 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11730.00	41.26	7.67	48.93	74.00	-25.07	PEAK
2	17595.00	45.07	7.06	52.13	68.20	-16.07	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT20 5885 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11770.00	41.22	7.65	48.87	74.00	-25.13	PEAK
2	17655.00	44.64	6.80	51.45	68.20	-16.76	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT20 5885 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11770.00	48.74	0.00	48.74	74.00	-25.26	PEAK
2	17655.00	44.26	6.80	51.06	68.20	-17.14	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT40 5835 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11670.00	41.30	7.69	48.99	74.00	-25.01	PEAK
2	17505.00	45.38	6.57	51.95	68.20	-16.25	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT40 5835 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11670.00	41.15	7.69	48.84	74.00	-25.16	PEAK
2	17505.00	44.73	6.57	51.30	68.20	-16.90	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT40 5875 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11750.00	40.46	7.66	48.12	74.00	-25.88	PEAK
2	17625.00	45.31	6.95	52.26	68.20	-15.94	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT40 5875 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11750.00	40.89	7.66	48.55	74.00	-25.45	PEAK
2	17625.00	45.47	6.95	52.42	68.20	-15.78	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT80 5855 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11710.00	41.93	7.68	49.61	74.00	-24.39	PEAK
2	17565.00	44.62	6.89	51.51	68.20	-16.69	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT80 5855 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11710.00	41.41	7.68	49.09	74.00	-24.91	PEAK
2	17565.00	44.47	6.89	51.36	68.20	-16.84	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ax HE20 5845 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11690.00	41.75	7.68	49.43	74.00	-24.57	PEAK
2	17535.00	45.86	6.74	52.60	68.20	-15.60	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ax HE20 5845 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11690.00	40.98	7.68	48.66	74.00	-25.34	PEAK
2	17535.00	44.29	6.74	51.03	68.20	-17.17	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ax HE20 5865 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11730.00	41.82	7.67	49.49	74.00	-24.51	PEAK
2	17595.00	45.19	7.06	52.25	68.20	-15.95	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ax HE20 5865 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11730.00	41.01	7.67	48.68	74.00	-25.32	PEAK
2	17595.00	45.18	7.06	52.24	68.20	-15.96	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ax HE20 5885 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11770.00	39.47	7.65	47.12	74.00	-26.88	PEAK
2	17655.00	45.14	6.80	51.94	68.20	-16.26	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ax HE20 5885 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11770.00	39.98	7.65	47.63	74.00	-26.37	PEAK
2	17655.00	44.38	6.80	51.18	68.20	-17.02	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ax HE40 5835 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11670.00	40.63	7.69	48.32	74.00	-25.68	PEAK
2	17505.00	44.64	6.57	51.21	68.20	-16.99	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ax HE40 5835 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11670.00	39.67	7.69	47.36	74.00	-26.64	PEAK
2	17505.00	44.04	6.57	50.61	68.20	-17.59	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ax HE40 5875 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11750.00	39.92	7.66	47.58	74.00	-26.42	PEAK
2	17625.00	45.06	6.95	52.01	68.20	-16.19	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ax HE40 5875 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11750.00	38.89	7.66	46.55	74.00	-27.45	PEAK
2	17625.00	44.98	6.95	51.93	68.20	-16.27	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ax HE80 5855 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11710.00	40.16	7.68	47.84	74.00	-26.16	PEAK
2	17565.00	44.29	6.89	51.18	68.20	-17.02	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ax HE80 5855 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11710.00	39.17	7.68	46.85	74.00	-27.15	PEAK
2	17565.00	44.12	6.89	51.01	68.20	-17.19	PEAK

Band Edge

Peak

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT20 5845 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5842.76	101.02	3.34	104.36	122.20	-17.84	PEAK
2	5925.00	59.80	3.16	62.96	68.20	-5.24	PEAK
3	5929.07	60.63	3.14	63.77	68.20	-4.43	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT20 5845 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5847.55	107.72	3.35	111.07	122.20	-11.13	PEAK
2	5925.00	59.75	3.16	62.91	68.20	-5.29	PEAK
3	6007.39	61.01	3.24	64.25	68.20	-3.95	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT20 5885 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5882.72	98.64	3.30	101.94	122.20	-20.26	PEAK
2	5925.00	59.12	3.16	62.28	68.20	-5.92	PEAK
3	6158.44	59.90	3.93	63.83	68.20	-4.37	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT20 5885 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5883.52	107.61	3.30	110.91	122.20	-11.29	PEAK
2	5925.00	59.22	3.16	62.38	68.20	-5.82	PEAK
3	5950.65	60.22	3.04	63.26	68.20	-4.94	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT40 5835 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5830.77	96.72	3.33	100.05	122.20	-22.15	PEAK
2	5925.00	58.87	3.16	62.03	68.20	-6.17	PEAK
3	5957.84	60.11	3.07	63.18	68.20	-5.02	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT40 5835 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5839.56	106.45	3.34	109.79	122.20	-12.41	PEAK
2	5925.00	59.35	3.16	62.51	68.20	-5.69	PEAK
3	6032.17	60.32	3.41	63.73	68.20	-4.47	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT40 5875 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5869.93	97.17	3.33	100.50	122.20	-21.70	PEAK
2	5925.00	59.68	3.16	62.84	68.20	-5.36	PEAK
3	6118.48	60.14	3.81	63.95	68.20	-4.25	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT40 5875 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5880.32	105.39	3.30	108.69	122.20	-13.51	PEAK
2	5925.00	60.97	3.16	64.13	68.20	-4.07	PEAK
3	5930.67	61.55	3.14	64.69	68.20	-3.51	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT80 5855 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5829.17	91.73	3.33	95.06	122.20	-27.14	PEAK
2	5925.00	58.81	3.16	61.97	68.20	-6.23	PEAK
3	6196.80	59.51	4.16	63.67	68.20	-4.53	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT80 5855 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5822.78	100.54	3.33	103.87	122.20	-18.33	PEAK
2	5925.00	63.13	3.16	66.29	68.20	-1.91	PEAK
3	5929.07	64.04	3.14	67.18	68.20	-1.02	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ax HE20 5845 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5837.16	102.00	3.34	105.34	122.20	-16.86	PEAK
2	5925.00	59.50	3.16	62.66	68.20	-5.54	PEAK
3	6178.42	59.78	4.05	63.83	68.20	-4.37	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ax HE20 5845 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5852.35	110.31	3.35	113.66	122.20	-8.54	PEAK
2	5925.00	58.31	3.16	61.47	68.20	-6.73	PEAK
3	6176.02	59.69	4.04	63.73	68.20	-4.47	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ax HE20 5885 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5883.52	100.49	3.30	103.79	122.20	-18.41	PEAK
2	5925.00	59.31	3.16	62.47	68.20	-5.73	PEAK
3	5994.61	60.91	3.18	64.09	68.20	-4.11	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ax HE20 5885 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5877.12	110.10	3.31	113.41	122.20	-8.79	PEAK
2	5925.00	59.48	3.16	62.64	68.20	-5.56	PEAK
3	5945.85	60.87	3.06	63.93	68.20	-4.27	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ax HE40 5835 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5830.77	100.31	3.33	103.64	122.20	-18.56	PEAK
2	5925.00	59.08	3.16	62.24	68.20	-5.96	PEAK
3	6188.81	59.80	4.11	63.91	68.20	-4.29	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ax HE40 5835 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5829.17	108.26	3.33	111.59	122.20	-10.61	PEAK
2	5925.00	58.76	3.16	61.92	68.20	-6.28	PEAK
3	5976.22	59.93	3.12	63.05	68.20	-5.15	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ax HE40 5875 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5858.74	107.67	3.34	111.01	122.20	-11.19	PEAK
2	5925.00	62.10	3.16	65.26	68.20	-2.94	PEAK
3	5926.67	62.59	3.15	65.74	68.20	-2.46	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ax HE40 5875 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5858.74	107.67	3.34	111.01	122.20	-11.19	PEAK
2	5925.00	62.10	3.16	65.26	68.20	-2.94	PEAK
3	5926.67	62.59	3.15	65.74	68.20	-2.46	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ax HE80 5855 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5840.36	93.43	3.34	96.77	122.20	-25.43	PEAK
2	5925.00	58.52	3.16	61.68	68.20	-6.52	PEAK
3	6058.54	60.14	3.57	63.71	68.20	-4.49	PEAK

Test Site:	96602-WG	Standard:	Part 15.407
Test Mode:	802.11ax HE80 5855 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5817.18	103.34	3.32	106.66	122.20	-15.54	PEAK
2	5925.00	64.64	3.16	67.80	68.20	-0.40	PEAK
3	5928.27	64.40	3.14	67.54	68.20	-0.66	PEAK

Antenna model number: custom

Below 1 GHz

Test Site:	96602 - WG	Standard:	Part 15.247
Test Mode:	Normal Operation		
Polarization:	Horizontal		
ReMark:	in		



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	76.51	49.79	-11.72	38.07	40.00	-1.93	QP
2	156.94	47.34	-7.41	39.93	43.50	-3.57	QP
3	204.43	48.53	-10.21	38.32	43.50	-5.18	QP
4	373.04	39.85	-5.17	34.68	46.00	-11.32	QP
5	720.92	35.66	0.98	36.64	46.00	-9.36	QP
6	984.50	32.31	4.93	37.24	54.00	-16.76	QP

Test Site:	96602 - WG	Standard:	Part 15.247
Test Mode:	Normal Operation		
Polarization:	Vertical		
ReMark:	in		



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	37.75	44.77	-8.58	36.19	40.00	-3.81	QP
2	149.19	46.97	-7.32	39.65	43.50	-3.85	QP
3	268.38	42.69	-7.33	35.36	46.00	-10.64	QP
4	373.04	40.23	-5.17	35.06	46.00	-10.94	QP
5	656.96	33.47	0.00	33.47	46.00	-12.53	QP
6	984.50	30.99	4.93	35.92	54.00	-18.08	QP

Harmonic

Above 1 GHz

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT20 5845 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11690.00	47.11	-1.72	45.39	74.00	-28.61	PEAK
2	17535.00	43.48	4.18	47.66	68.20	-20.54	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT20 5845 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11690.00	47.38	-1.72	45.66	74.00	-28.34	PEAK
2	17535.00	43.27	4.18	47.45	68.20	-20.75	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT20 5865 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11730.00	47.21	-1.94	45.27	74.00	-28.73	PEAK
2	17595.00	44.24	4.55	48.79	68.20	-19.41	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT20 5845 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11730.00	46.79	-1.94	44.86	74.00	-29.14	PEAK
2	17595.00	43.94	4.55	48.49	68.20	-19.71	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT20 5885 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11770.00	47.26	-1.80	45.46	74.00	-28.54	PEAK
2	17655.00	44.08	4.29	48.37	68.20	-19.83	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT20 5885 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11770.00	46.86	-1.80	45.06	74.00	-28.94	PEAK
2	17655.00	43.19	4.29	47.48	68.20	-20.72	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT40 5835 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11670.00	47.01	-1.68	45.33	74.00	-28.67	PEAK
2	17505.00	44.34	3.99	48.33	68.20	-19.87	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT40 5835 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11670.00	47.31	-1.68	45.63	74.00	-28.37	PEAK
2	17505.00	43.68	3.99	47.67	68.20	-20.53	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT40 5875 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11750.00	46.92	-1.90	45.03	74.00	-28.97	PEAK
2	17625.00	43.58	4.52	48.10	68.20	-20.10	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT40 5875 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11750.00	46.80	-1.90	44.91	74.00	-29.09	PEAK
2	17625.00	44.42	4.52	48.94	68.20	-19.26	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT80 5855 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11710.00	47.23	-1.86	45.36	74.00	-28.64	PEAK
2	17565.00	43.86	4.26	48.12	68.20	-20.08	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT80 5855 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11710.00	47.16	-1.86	45.29	74.00	-28.71	PEAK
2	17565.00	44.05	4.26	48.31	68.20	-19.89	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ax HE20 5845 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11710.00	47.23	-1.86	45.36	74.00	-28.64	PEAK
2	17565.00	43.86	4.26	48.12	68.20	-20.08	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ax HE20 5845 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11690.00	47.44	-1.72	45.72	74.00	-28.28	PEAK
2	17535.00	43.60	4.18	47.78	68.20	-20.42	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ax HE20 5865 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11730.00	48.66	-1.94	46.72	74.00	-27.28	PEAK
2	17595.00	45.20	4.55	49.75	68.20	-18.45	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ax HE20 5865 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11730.00	47.23	-1.94	45.30	74.00	-28.70	PEAK
2	17595.00	44.07	4.55	48.62	68.20	-19.58	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ax HE20 5885 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11770.00	48.70	-1.80	46.90	74.00	-27.10	PEAK
2	17655.00	45.33	4.29	49.62	68.20	-18.58	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ax HE20 5885 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11770.00	46.51	-1.80	44.71	74.00	-29.29	PEAK
2	17655.00	44.45	4.29	48.74	68.20	-19.46	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ax HE40 5835 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11670.00	48.85	-1.68	47.17	74.00	-26.83	PEAK
2	17505.00	45.38	3.99	49.37	68.20	-18.83	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ax HE40 5835 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11670.00	47.58	-1.68	45.90	74.00	-28.10	PEAK
2	17505.00	44.29	3.99	48.28	68.20	-19.92	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ax HE40 5875 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11750.00	48.14	-1.90	46.24	74.00	-27.76	PEAK
2	17625.00	45.33	4.52	49.85	68.20	-18.35	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ax HE40 5875 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11750.00	46.84	-1.90	44.95	74.00	-29.05	PEAK
2	17625.00	44.06	4.52	48.58	68.20	-19.62	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ax HE80 5855 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11710.00	49.23	-1.86	47.37	74.00	-26.63	PEAK
2	17565.00	44.88	4.26	49.14	68.20	-19.06	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ax HE80 5855 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	11710.00	47.49	-1.86	45.63	74.00	-28.37	PEAK
2	17565.00	44.50	4.26	48.76	68.20	-19.44	PEAK

Band Edge

Peak

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT20 5845 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5847.55	110.67	-7.85	102.82	122.20	-19.38	PEAK
2	5925.00	61.67	-8.06	53.61	68.20	-14.59	PEAK
3	5997.80	63.03	-8.05	54.98	68.20	-13.22	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT20 5845 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5847.55	103.69	-7.85	95.84	122.20	-26.36	PEAK
2	5925.00	62.52	-8.06	54.46	68.20	-13.74	PEAK
3	6196.00	61.93	-7.23	54.70	68.20	-13.50	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT80 5855 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5838.76	105.83	-7.86	97.97	122.20	-24.24	PEAK
2	5925.00	65.17	-8.06	57.11	68.20	-11.09	PEAK
3	5929.07	68.64	-8.08	60.56	68.20	-7.64	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT80 5855 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5825.17	99.30	-7.86	91.44	122.20	-30.76	PEAK
2	5925.00	62.66	-8.06	54.60	68.20	-13.60	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT20 5885 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5882.72	110.14	-7.91	102.23	122.20	-19.97	PEAK
2	5925.00	61.61	-8.06	53.55	68.20	-14.65	PEAK
3	6152.85	61.99	-7.47	54.52	68.20	-13.68	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT20 5885 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5882.72	102.53	-7.91	94.62	122.20	-27.58	PEAK
2	5925.00	60.60	-8.06	52.54	68.20	-15.66	PEAK
3	6084.12	62.02	-7.61	54.41	68.20	-13.79	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT40 5835 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5841.16	109.38	-7.86	101.52	122.20	-20.68	PEAK
2	5925.00	61.50	-8.06	53.44	68.20	-14.76	PEAK
3	6150.45	62.20	-7.49	54.71	68.20	-13.49	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT40 5835 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5833.17	101.48	-7.86	93.62	122.20	-28.58	PEAK
2	5925.00	60.66	-8.06	52.60	68.20	-15.60	PEAK
3	5937.86	62.60	-8.13	54.47	68.20	-13.73	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT40 5875 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5861.14	107.53	-7.87	99.66	122.20	-22.54	PEAK
2	5925.00	63.88	-8.06	55.82	68.20	-12.38	PEAK
3	5931.47	64.23	-8.09	56.14	68.20	-12.06	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ac VHT40 5875 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5861.14	101.09	-7.87	93.22	122.20	-28.98	PEAK
2	5925.00	61.09	-8.06	53.03	68.20	-15.17	PEAK
3	6172.03	62.12	-7.36	54.76	68.20	-13.44	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ax HE20 5845 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5843.56	112.77	-7.86	104.91	122.20	-17.29	PEAK
2	5925.00	61.63	-8.06	53.57	68.20	-14.63	PEAK
3	6156.84	62.30	-7.45	54.85	68.20	-13.35	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ax HE20 5845 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5852.35	105.20	-7.85	97.35	122.20	-24.85	PEAK
2	5925.00	62.96	-8.06	54.90	68.20	-13.30	PEAK
3	5925.07	63.16	-8.06	55.10	68.20	-13.10	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ax HE20 5885 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5887.51	111.03	-7.92	103.11	122.20	-19.09	PEAK
2	5925.00	61.51	-8.06	53.45	68.20	-14.76	PEAK
3	6079.32	62.36	-7.63	54.73	68.20	-13.47	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ax HE20 5885 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5887.51	104.12	-7.92	96.20	122.20	-26.00	PEAK
2	5925.00	60.93	-8.06	52.87	68.20	-15.33	PEAK
3	6188.81	61.72	-7.28	54.44	68.20	-13.76	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ax HE40 5835 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5826.77	110.82	-7.86	102.96	122.20	-19.24	PEAK
2	5925.00	61.01	-8.06	52.95	68.20	-15.25	PEAK
3	6182.42	61.82	-7.30	54.52	68.20	-13.68	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ax HE40 5835 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5829.17	103.98	-7.87	96.11	122.20	-26.09	PEAK
2	5925.00	61.64	-8.06	53.58	68.20	-14.62	PEAK
3	5983.42	62.20	-8.09	54.11	68.20	-14.09	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ax HE40 5875 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5862.74	110.04	-7.88	102.16	122.20	-20.04	PEAK
2	5925.00	63.92	-8.06	55.86	68.20	-12.34	PEAK
3	5926.67	64.66	-8.07	56.59	68.20	-11.61	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ax HE40 5875 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5859.54	101.96	-7.87	94.09	122.20	-28.11	PEAK
2	5925.00	61.24	-8.06	53.18	68.20	-15.02	PEAK
3	6086.51	62.02	-7.60	54.42	68.20	-13.78	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ax HE80 5855 MHz		
Polarization:	Horizontal		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5824.38	108.12	-7.86	100.26	122.20	-21.94	PEAK
2	5925.00	67.69	-8.06	59.63	68.20	-8.57	PEAK
3	5926.67	69.96	-8.07	61.89	68.20	-6.31	PEAK

Test Site:	96602 - WG	Standard:	Part 15.407
Test Mode:	802.11ax HE80 5855 MHz		
Polarization:	Vertical		
ReMark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	ReMark
1	5833.17	102.96	-7.86	95.11	122.20	-27.10	PEAK
2	5925.00	65.15	-8.06	57.09	68.20	-11.11	PEAK
3	5925.07	65.26	-8.06	57.20	68.20	-11.00	PEAK

5.3. Conducted Test Results

Duty cycle

Reference Appendix A / Appendix B

Maximum Conducted Output Power Measurement

Reference Appendix A

6 dB RF Bandwidth Measurement

Reference Appendix A / Appendix B

Maximum Power Spectral Density and E.I.R.P. Spectral Density Measurement

Reference Appendix A / Appendix B

---END---