

Prüfbericht - Nr.: 14026758 003		Seite 1 von 11	
<i>Test Report No.:</i>		<i>Page 1 of 11</i>	
Auftraggeber: <i>Client:</i>		AvantWave Limited 3 Rd. Floor, Photonics Centre No. 2 Science Park Avenue East Hong Kong Science Park Shatin Hong Kong	
Gegenstand der Prüfung: <i>Test Item:</i>		Bluetooth Module	
Bezeichnung: <i>Identification:</i>	BTR602	Serien-Nr.: <i>Serial No.:</i>	Engineering sample
Wareneingangs-Nr.: <i>Receipt No.:</i>	A000039504-001, A000041708-001	Eingangsdatum: <i>Date of Receipt:</i>	03.03.2014, 19.03.2014
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of test item at delivery:</i>		Test sample(s) is/are not damaged and suitable for testing.	
Prüfört: <i>Testing Location:</i>		Hong Kong Productivity Council HKPC Building, 78 Tat Chee Avenue, Kowloon, Hong Kong TÜV Rheinland Hong Kong Ltd. 8/F., First Group Centre, 14 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong	
Prüfgrundlage: <i>Test Specification:</i>		FCC Part 15 Subpart C ANSI C63.4-2003 CISPR 22:1997	
Prüfergebnis: <i>Test Results:</i>		Das vorstehend beschriebene Gerät wurde geprüft und entspricht oben genannter Prüfgrundlage. The above mentioned product was tested and passed .	
Prüflaboratorium: <i>Testing Laboratory:</i>		TÜV Rheinland Hong Kong Ltd. 8 - 10/F., Goldin Financial Global Square, 7 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong	
geprüft/ tested by:		kontrolliert/ reviewed by:	
09.04.2014	Hugo Wan Senior Project Manager	09.04.2014	Sharon Li Section Manager
Datum <i>Date</i>	Name/Stellung <i>Name/Position</i>	Unterschrift <i>Signature</i>	Datum <i>Date</i>
Sonstiges / Other Aspects: FCCID: XQN-BTR60X			
This test report is issued for "Class II permissive change" of the previously tested EUT of AvantWave model BTR60X in test report number 14026758 002. For details, please refer to "Remark" on page 4.			
Abkürzungen:	P(ass) = entspricht Prüfgrundlage F(ail) = entspricht nicht Prüfgrundlage N/A = nicht anwendbar N/T = nicht getestet	Abbreviations:	P(ass) = passed F(ail) = failed N/A = not applicable N/T = not tested
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any safety mark on this or similar products.</i>			

Table of Content

	Page
Cover Page	1
Table of Content	2
Product information	3
Manufacturers declarations.....	3
Product function and intended use	4
Submitted documents	4
Remark.....	4
Special accessories and auxiliary equipment	4
List of Test and Measurement Instruments.....	5
Results FCC Part 15 – Subpart C	6
Subclause 15.203 – Antenna Information.....	Pass6
Subclause 15.204 – Antenna Information.....	Pass6
Subclause 15.207 – Disturbance Voltage on AC Mains	Pass6
Subclause 15.247 (a)(1) – Carrier Frequency Separation	Pass6
Subclause 15.247 (a)(1)(iii) – Number of hopping channels.....	Pass6
Subclause 15.247 (a)(1)(iii) – Time of Occupancy (Dwell Time).....	Pass6
Subclause 15.247 (a) – 20 dB Bandwidth	Pass7
Subclause 15.247 (a) – Hopping Sequence.....	Pass7
Subclause 15.247 (a) – Equal Hopping Frequency Use	Pass7
Subclause 15.247 (a) – Receiver Input Bandwidth	Pass7
Subclause 15.247 (a) – Receiver Hopping Capability	Pass7
Subclause 15.247 (b)(1) – Peak Output Power.....	Pass8
Subclause 15.247 (d) – Band edge compliance of conducted emissions	Pass8
Subclause 15.205 (a) – Restricted Bands next to Band-edge	Pass9
Subclause 15.247 (d) – Spurious Conducted Emissions.....	Pass9
Subclause 15.247 (c) – Spurious Radiated Emissions	Pass10
Appendix 1 – Test protocols	12 pages
Appendix 2 – Test setup	2 pages
Appendix 3 – Photo documentation	3 pages
Appendix 4 – Product documentation	51 pages

Product information

Manufacturers declarations

	Transceiver
Operating frequency range	2402 - 2480 MHz
Type of modulation	GFSK; Pi/4 DQPSK; 8 DPSK
Number of channels	79
Channel separation	1 MHz
Type of antenna	Integral antenna
Antenna gain (dBi)	-2
Power level	fix
Type of equipment	stand alone radio device
Connection to public utility power line	No
Nominal voltage	V _{nom} : 3.3V
Independent Operation Modes	Page scan Inquiry scan Connection state - ACL Link Connection state - SCO Link

Product function and intended use

The test item is a Bluetooth Module based on the Bluetooth technology.

Bluetooth is a short-range radio link intended to be a cable replacement between portable and/or fixed electronic devices.

Bluetooth operates in the unlicensed ISM Band at 2.4GHz. With the introduction of the enhanced data rate (EDR) feature, the data rates can be up to 3 Mb/s.

An increase in the peak data rate beyond the basic rate of 1 Mb/s is achieved by modulating the RF carrier using phase shift keying (PSK) techniques, resulting in an increase of two to three times the number of bits per symbol. The 2 Mb/s EDR packets use a Pi/4-DQPSK modulation and the 3 Mb/s EDR packets use 8DPSK modulation.

Submitted documents

Circuit Diagram
Block Diagram
Bill of material
User Manual
Label Artwork

Remark

Change as follow:

- PCB manufacturer changed

To show compliance, the following tests were repeated on the modified sample:

Radiated spurious Emission
Peak Output Power
Radiated Emission in Restricted Bands next to Band-edge

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases.

Special accessories and auxiliary equipment

Additional accessory used for testing

The product has been tested together with the following additional accessory:

1. AC/DC Power adaptor
Model number: PSM02R-055
Input: 100-240VAC, 50-60Hz, 0.1A
Output: 5.5VDC 0.35A
2. LPT cable provided by client

List of Test and Measurement Instruments

Hong Kong Productivity Council (FCC Registration number: 90656)

Radiated Emission

Equipment	Manufacturer	Type	S/N	Cal Due Date
Semi-anechoic Chamber	Frankonia	Nil	Nil	12 Apr 2014
EMI Test Receiver	Rohde & Schwarz	ESU40	100190	18 Sep 2014
Biconical Antenna	Rohde & Schwarz	HK116	100241	11 Jun 2015
Log-Periodic Antenna	Rohde & Schwarz	HL223	841516/017	10 Jun 2015
Horn Antenna	EMCO	3115	9002-3347	11 Jun 2015
Coaxial Cable 50ohm	Rosenberger	RTK081-05S-05S-10m	LA2-001-10M / 001	15 Nov 2015
Active Loop Antenna	EMCO	6502	9107-2651	21 Apr 2014

TÜV Rheinland Hong Kong Ltd.

Radio Frequency

Equipment	Manufacturer	Type	S/N	Cal Due Date
Spectrum Analyzer	Rohde & Schwarz	FSP30	100007	03 Dec 2014

Results FCC Part 15 – Subpart C

Subclause 15.203 – Antenna Information**Pass****Remark:** Please refer to test report 14026758 002 for test result.**Subclause 15.204 – Antenna Information****Pass****Remark:** Please refer to test report 14026758 002 for test result.**Subclause 15.207 – Disturbance Voltage on AC Mains****Pass****Remark:** Please refer to test report 14026758 002 for test result.**Subclause 15.247 (a)(1) – Carrier Frequency Separation****Pass****Remark:** Please refer to test report 14026758 002 for test result.**Subclause 15.247 (a)(1)(iii) – Number of hopping channels****Pass****Remark:** Please refer to test report 14026758 002 for test result.**Subclause 15.247 (a)(1)(iii) – Time of Occupancy (Dwell Time)****Pass****Remark:** Please refer to test report 14026758 002 for test result.

Subclause 15.247 (a) – 20 dB Bandwidth**Pass****Remark:** Please refer to test report 14026758 002 for test result.**Subclause 15.247 (a) – Hopping Sequence****Pass****Remark:** Please refer to test report 14026758 002 for test result.**Subclause 15.247 (a) – Equal Hopping Frequency Use****Pass****Remark:** Please refer to test report 14026758 002 for test result.**Subclause 15.247 (a) – Receiver Input Bandwidth****Pass****Remark:** Please refer to test report 14026758 002 for test result.**Subclause 15.247 (a) – Receiver Hopping Capability****Pass****Remark:** Please refer to test report 14026758 002 for test result.

Subclause 15.247 (b)(1) – Peak Output Power					Pass
Test Specification : FCC Part 15 Subpart A – Subclause 15.31 Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz), GFSP, $\pi/4$ -DPSK and 8DPSK Port of testing : Temporary antenna port Detector : Peak RBW/VBW : 3 MHz / 10 MHz Supply voltage : 3.3 VDC Temperature : 23°C Humidity : 50%					
Requirement: For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 Watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 Watts.					
Results: For test protocols please refer to Appendix 1, page 2-7.					
GFSK Modulation					
Frequency (MHz)	Maximum peak output power (dBm)	Cable attenuation (dB)	Output power (dBm)	Limit (W/dBm)	Verdict
2402	-4.40	0.00	-4.40	1 / 30.0	Pass
2441	-3.24	0.00	-3.24	1 / 30.0	Pass
2480	-3.39	0.00	-3.39	1 / 30.0	Pass
$\pi/4$-DPSK Modulation					
Frequency (MHz)	Maximum peak output power (dBm)	Cable attenuation (dB)	Output power (dBm)	Limit (W/dBm)	Verdict
2402	-4.31	0.00	-4.31	0.125 / 21.0	Pass
2441	-3.03	0.00	-3.03	0.125 / 21.0	Pass
2480	-3.27	0.00	-3.27	0.125 / 21.0	Pass
8DPSK Modulation					
Frequency (MHz)	Maximum peak output power (dBm)	Cable attenuation (dB)	Output power (dBm)	Limit (W/dBm)	Verdict
2402	-4.25	0.00	-4.25	0.125 / 21.0	Pass
2441	-3.09	0.00	-3.09	0.125 / 21.0	Pass
2480	-3.24	0.00	-3.24	0.125 / 21.0	Pass
Subclause 15.247 (d) – Band edge compliance of conducted emissions					Pass
Remark: Please refer to test report 14026758 002 for test result.					

Subclause 15.205 (a) – Restricted Bands next to Band-edge		Pass
Test Specification : FCC Part 15 Subpart A – Subclause 15.31 Mode of operation : Tx mode (2402MHz, 2480MHz), GFSK Port of testing : Enclosure Detector : a) Peak, b) Average RBW/VBW : a) 1 MHz / ≤ RBW (Peak), b) 1MHz / 10Hz (Average) Supply voltage : 3.3 VDC Temperature : 23°C Humidity : 50%		
Requirement:	Radiated emissions which fall in the restricted bans, as defined in 15.205 (a), must also comply with the radiated emission limits specified in 15.209(a).	
Results:	Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types. There is no peak found in the restricted bands. For test protocols refer to Appendix 1, page 8-11.	
Subclause 15.247 (d) – Spurious Conducted Emissions		Pass
Remark:	Please refer to test report 14026758 002 for test result.	

Subclause 15.247 (c) – Spurious Radiated Emissions		Pass
Test Specification : ANSI C63.4 – 2003 Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz), 8DPSK Port of testing : Enclosure Detector : Peak / Average* RBW/VBW : 100 kHz / 300 kHz for f < 1 GHz 1 MHz / 3 MHz for f > 1 GHz Supply voltage : 3.3 VDC Temperature : 23°C Humidity : 50%		
*Average reading using duty cycle correction factor on peak measurement: Devices transmitting pulsed emissions and subject to a limit requiring an average detector function for radiated emissions shall initially be measured with an instrument that uses a peak detector. A radiated emission measured with a peak detector may then be corrected to a true average using the appropriate factor for emission duty cycle. This correction factor relates the measured peak level to the average limit and is derived by averaging absolute field strength over one complete pulse train that is 0.1 s, or less, in length. Duty cycle correction factor calculation: Total on time in 100ms = 2.92 ms Number of pulse found in 100ms = 1 Duty cycle factor = 20 x log ((on time in 100ms x no. of pulse) / 100ms) = -30.7 dB		
Requirement:	In any 100kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in section15.205(a), must also comply with the radiated emission limits specified in section 15.205(c).	
Results:	Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types. All three transmit frequency modes comply with the field strength within the restricted bands. There is no spurious found below 30MHz.	
Tx frequency 2402MHz		Vertical Polarization
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
4804.022	68.6	74.0 / PK
4804.022	*37.9	54.0 / AV
Tx frequency 2402MHz		Horizontal Polarization
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
1601.817	48.5	74.0 / PK
1602.010	45.8	54.0 / AV
3203.952	47.5	74.0 / PK
3203.968	39.8	54.0 / AV
4804.070	66.4	74.0 / PK
4804.070	*35.7	54.0 / AV

Tx frequency 2441MHz			Vertical Polarization		
Freq MHz			Level dBuV/m		Limit/ Detector dBuV/m
4881.907			69.4		74.0 / PK
4881.907			*38.7		54.0 / AV
Tx frequency 2441MHz			Horizontal Polarization		
Freq MHz			Level dBuV/m		Limit/ Detector dBuV/m
1626.699			46.9		74.0 / PK
1626.651			41.0		54.0 / AV
4881.987			64.1		74.0 / PK
4881.987			*33.4		54.0 / AV
Tx frequency 2480MHz			Vertical Polarization		
Freq MHz			Level dBuV/m		Limit/ Detector dBuV/m
4960.016			67.8		74.0 / PK
4960.016			*37.1		54.0 / AV
Tx frequency 2480MHz			Horizontal Polarization		
Freq MHz			Level dBuV/m		Limit/ Detector dBuV/m
4959.968			64.6		74.0 / PK
4959.968			*33.9		54.0 / AV
* Duty cycle correction factor applied					