**Shenzhen Global Test Service Co.,Ltd.**
No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

# TEST REPORT

## FCC PART 15 SUBPART C 15.247

| | |
|---|---|
| **Report Reference No.**.....: | **GTS20211120017-1-1** |
| **FCC ID**..... : | **XR3-NOTEAIR2** |
| Compiled by<br>( position+printed name+signature)..: | File administrators Jimmy Wang |
| Supervised by<br>( position+printed name+signature)..: | Test Engineer Aaron Tan |
| Approved by<br>( position+printed name+signature)..: | Manager Jason Hu |
| Date of issue.....: | Nov. 20, 2021 |
| **Representative Laboratory Name**.: | **Shenzhen Global Test Service Co.,Ltd.** |
| Address.....: | No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong, China |
| **Applicant's name**.....: | **ONYX INTERNATIONAL INC.** |
| Address .....: | Room 301-6, 10 Honglou Street, Liwan District, Guangzhou City, Guangdong Province, China |
| **Test specification** .....**:** | |
| Standard .....: | **FCC Part 15.247** |
| TRF Originator.....: | Shenzhen Global Test Service Co.,Ltd. |
| Master TRF.....: | Dated 2014-12 |

**Shenzhen Global Test Service Co.,Ltd. All rights reserved.**
This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Global Test Service Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Global Test Service Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

| | |
|---|---|
| **Test item description** .....**:** | E Ink Tablet, Smart E Ink Tablet, ePaper Tablet, E-bag Tablet, E-book Tablet, E-reader Tablet, Eyes protection E Ink Tablet, E-paper Tablet, Color E Ink Tablet, Color ePaper Tablet |
| Trade Mark .....: | BOOX |
| **Manufacturer**.....: | **ONYX INTERNATIONAL INC.** |
| Model/Type reference.....: | Note Air2 |
| Listed Models .....: | Note Air2 Pro, Note Air2 Lite, Note Air2 Plus, Note Air2 Color, Note Air2 Color Lite, Note Air2 Color Pro, Note Air2 Color Plus, Note Air2 C |
| Ratings .....: | DC 3.85V from battery; Charging input: 5V⎓3A |
| Modulation .....: | 802.11b: DSSS 802.11g/802.11n(H20)/ 802.11n(H40): OFDM |
| Hardware version .....: | BOOX_M4_NOTE_AIR2_V10 |
| Software version .....: | V1.0 |
| Frequency..... | From 2412MHz-2462MHz |
| Result.....: | **PASS** |

# T E S T  R E P O R T

| **Test Report No. :** | **GTS20211120017-1-1** | Nov. 20, 2021<br>Date of issue |
|---|---|---|

| | | |
|---|---|---|
| Equipment under Test | : | E Ink Tablet, Smart E Ink Tablet, ePaper Tablet, E-bag Tablet, E-book Tablet, E-reader Tablet, Eyes protection E Ink Tablet, E-paper Tablet, Color E Ink Tablet, Color ePaper Tablet |
| Model /Type | : | Note Air2 |
| Listed Models | : | Note Air2 Pro, Note Air2 Lite, Note Air2 Plus, Note Air2 Color, Note Air2 Color Lite, Note Air2 Color Pro, Note Air2 Color Plus, Note Air2 C |
| **Applicant** | : | **ONYX INTERNATIONAL INC.** |
| Address | : | Room 301-6, 10 Honglou Street, Liwan District, Guangzhou City, Guangdong Province, China |
| **Manufacturer** | : | **ONYX INTERNATIONAL INC.** |
| Address | : | Building 4, 202 Shiyu Road, Dongchong Town, Nansha District, Guangzhou City, Guangdong Province, China |

| **Test Result**: | **PASS** |
|---|---|

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

# Contents


1 TEST STANDARDS ..... 4

2 SUMMARY ..... 5

2.1 General Remarks 5
2.2 Product Description 5
2.3 Test Sample 5
2.4 Equipment Under Test 5
2.5 Short description of the Equipment under Test (EUT) 5
2.6 EUT operation mode 6
2.7 Block Diagram of Test Setup 6
2.8 Special Accessories 6
2.9 Related Submittal(s) / Grant (s) 6
2.10 Modifications 6

3 TEST ENVIRONMENT ..... 7

3.1 Address of the test laboratory 7
3.2 Test Facility 7
3.3 Environmental conditions 7
3.4 Test Description 8
3.5 Statement of the measurement uncertainty 9
3.6 Equipments Used during the Test 9

4 TEST CONDITIONS AND RESULTS ..... 11

4.1 AC Power Conducted Emission 11
4.2 Radiated Emission 14
4.3 Maximum Conducted Output Power 21
4.4 Power Spectral Density 22
4.5 6dB Bandwidth 25
4.6 Out-of-band Emissions 28
4.7 Antenna Requirement 37

5 TEST SETUP PHOTOS OF THE EUT ..... 38

6 PHOTOS OF THE EUT ..... 39

# 1 TEST STANDARDS

The tests were performed according to following standards:

FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.
ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices
KDB558074 D01 V05r02: Guidance for Compliance Measurements on Digital Transmission Systems (DTS) ,Frequency Hopping Spread Spectrum System(HFSS), and Hybrid System Devices Operating Under §15.247 of The FCC rules.

# 2 SUMMARY

## 2.1 General Remarks

| | | |
|---|---|---|
| Date of receipt of test sample | : | Sep. 25, 2021 |
| | | |
| | | |
| Testing commenced on | : | Sep. 26, 2021 |
| | | |
| | | |
| Testing concluded on | : | Oct. 25, 2021 |

## 2.2 Product Description

| | |
|---|---|
| Product Description: | E Ink Tablet, Smart E Ink Tablet, ePaper Tablet, E-bag Tablet, E-book Tablet, E-reader Tablet, Eyes protection E Ink Tablet, E-paper Tablet, Color E Ink Tablet, Color ePaper Tablet |
| Model/Type reference: | Note Air2 |
| Power supply: | DC 3.85V from battery |
| Sample ID: | GTS20211120017-1-1#/ GTS20211120017-1-2# |
| **WIFI** | |
| Supported type: | 802.11b/802.11g/802.11n(H20)/802.11n(H40) |
| Modulation: | 802.11b: DSSS<br>802.11g/802.11n(H20)/ 802.11n(H40): OFDM |
| Operation frequency: | 802.11b/802.11g/802.11n(H20): 2412MHz~2462MHz<br>802.11n(H40): 2422MHz~2452MHz |
| Channel number: | 802.11b/802.11g/802.11n(H20): 11<br>802.11n(H40): 7 |
| Channel separation: | 5MHz |
| Antenna type: | FPC Antenna |
| Antenna gain: | 2.65dBi |

## 2.3 Test Sample

The application provides 2 samples to meet requirement.

| Sample Number | Description |
|---|---|
| GTS20211120017-1-1# | Engineer sample – continuous transmit |
| GTS20211120017-1-2# | Normal sample – Intermittent transmit |

## 2.4 Equipment Under Test

### Power supply system utilised

| | | | | | |
|---|---|---|---|---|---|
| Power supply voltage | : | ○ | 230V / 50 Hz | ○ | 120V / 60Hz |
| | | ○ | 12 V DC | ○ | 24 V DC |
| | | ● | Other (specified in blank below) | | |

DC 3.85V from battery

## 2.5 Short description of the Equipment under Test (EUT)

This is a Smart E Ink Tablet.

For more details, refer to the user's manual of the EUT.

## 2.6 EUT operation mode

The application provider specific test software(QRCT4) to control sample in continuous TX and RX (Duty Cycle >98%)
for testing meet KDB558074 test requirement.

IEEE 802.11b/g/n: Thirteen channels are provided to the EUT.

| Channel | Frequency(MHz) | Channel | Frequency(MHz) |
|---|---|---|---|
| 1 | 2412 | 8 | 2447 |
| 2 | 2417 | 9 | 2452 |
| 3 | 2422 | 10 | 2457 |
| 4 | 2427 | 11 | 2462 |
| 5 | 2432 | | |
| **6** | 2437 | | |
| 7 | 2442 | | |

## 2.7 Block Diagram of Test Setup




## 2.8 Special Accessories

Follow auxiliary equipment(s) test with EUT that provided by the manufacturer or laboratory is listed as follow:

| Description | Manufacturer | Model | Technical Parameters | Certificate | Provided by |
|---|---|---|---|---|---|
| AC-DC Adapter | MOSO | EP-TA20CBC | Input:AC100-240V-50/60Hz，0.5A<br>Output:DC 5V,3A | FCC | Laboratory |
| / | / | / | / | / | / |
| / | / | / | / | / | / |
| / | / | / | / | / | / |

## 2.9 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for the EUT filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

## 2.10 Modifications

No modifications were implemented to meet testing criteria.

# 3 TEST ENVIRONMENT

## 3.1 Address of the test laboratory

**Shenzhen Global Test Service Co.,Ltd.**
No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

## 3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

### FCC-Registration No.: 165725 Designation Number: CN1234

Shenzhen Global Test Service Co.,Ltd EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

### A2LA-Lab Cert. No.: 4758.01

Shenzhen Global Test Service Co.,Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

### CNAS-Lab Code: L8169

Shenzhen Global Test Service Co.,Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories. Date of Registration: Dec. 11, 2015. Valid time is until Dec. 10, 2024.

## 3.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

| | |
|---|---|
| Temperature: | 15-35 ° C |
| | |
| Humidity: | 30-60 % |
| | |
| Atmospheric pressure: | 950-1050mbar |

## 3.4 Test Description

| Test Specification clause | Test case | Test Sample | Test Mode | Test Channel | Recorded In Report | | Test result |
|---|---|---|---|---|---|---|---|
| §15.247(e) | Power spectral density | GTS2021112 0017-1-1# | 802.11b 802.11g 802.11n(HT)20 802.11n(HT)40 | Lowest Middle Highest | 802.11b 802.11g 802.11n(HT)20 802.11n(HT)40 | Lowest Middle Highest | complies |
| §15.247(a)(2) | Spectrum bandwidth – 6 dB bandwidth | GTS2021112 0017-1-1# | 802.11b 802.11g 802.11n(HT)20 802.11n(HT)40 | Lowest Middle Highest | 802.11b 802.11g 802.11n(HT)20 802.11n(HT)40 | Lowest Middle Highest | complies |
| §15.247(b)(3) | Maximum Conducted output power | GTS2021112 0017-1-1# | 802.11b 802.11g 802.11n(HT)20 802.11n(HT)40 | Lowest Middle Highest | 802.11b 802.11g 802.11n(HT)20 802.11n(HT)40 | Lowest Middle Highest | complies |
| §15.247(d) | Band edge compliance conducted | GTS2021112 0017-1-1# | 802.11b 802.11g 802.11n(HT)20 802.11n(HT)40 | Lowest Highest | 802.11b 802.11g 802.11n(HT)20 802.11n(HT)40 | Lowest Highest | complies |
| §15.205 | Band edge compliance radiated | GTS2021112 0017-1-1# | 802.11b 802.11g 802.11n(HT)20 802.11n(HT)40 | Lowest Highest | 802.11b | Lowest Highest | complies |
| §15.247(d) | TX spurious emissions conducted | GTS2021112 0017-1-1# | 802.11b 802.11g 802.11n(HT)20 802.11n(HT)40 | Lowest Middle Highest | 802.11b 802.11g 802.11n(HT)20 802.11n(HT)40 | Lowest Middle Highest | complies |
| §15.209(a) | TX spurious emissions Radiated above 1GHz | GTS2021112 0017-1-1# | 802.11b 802.11g 802.11n(HT)20 802.11n(HT)40 | Lowest Middle Highest | 802.11b | Lowest Middle Highest | complies |
| §15.209(a) | TX spurious Emissions radiated Below 1GHz | GTS2021112 0017-1-2# | 802.11b 802.11g 802.11n(HT)20 802.11n(HT)40 | Lowest Middle Highest | 802.11b | Lowest | complies |
| §15.107(a) §15.207 | Conducted Emissions < 30 MHz | GTS2021112 0017-1-2# | 802.11b 802.11g 802.11n(HT)20 802.11n(HT)40 | Lowest Middle Highest | 802.11b | Highest | complies |

**Data Rate Used:**

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

| Test Items | Mode | Data Rate | Channel |
|---|---|---|---|
| Maximum Peak Conducted Output Power<br>Power Spectral Density<br>6dB Bandwidth<br>Spurious RF conducted emission<br>Radiated Emission 9KHz~1GHz&<br>Radiated Emission 1GHz~10th Harmonic | 11b/DSSS | 1 Mbps | 1/6/11 |
| | 11g/OFDM | 6 Mbps | 1/6/11 |
| | 11n(20MHz)/OFDM | 6.5Mbps | 1/6/11 |
| | 11n(40MHz)/OFDM | 13.5Mbps | 3/6/9 |
| Band Edge | 11b/DSSS | 1 Mbps | 1/11 |
| | 11g/OFDM | 6 Mbps | 1/11 |
| | 11n(20MHz)/OFDM | 6.5Mbps | 1/11 |
| | 11n(40MHz)/OFDM | 13.5Mbps | 3/9 |

## 3.5 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Global Test Service Co.,Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GTS laboratory is reported:

| Test | Range | Measurement Uncertainty | Notes |
|---|---|---|---|
| Radiated Emission | 30~1000MHz | 4.10 dB | (1) |
| Radiated Emission | 1~18GHz | 4.32 dB | (1) |
| Radiated Emission | 18-40GHz | 5.54 dB | (1) |
| Conducted Disturbance | 0.15~30MHz | 3.12 dB | (1) |

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

## 3.6 Equipments Used during the Test

| Test Equipment | Manufacturer | Model No. | Serial No. | Calibration Date | Calibration Due Date |
|---|---|---|---|---|---|
| LISN | CYBERTEK | EM5040A | E1850400105 | 2021/07/23 | 2022/07/22 |
| LISN | R&S | ESH2-Z5 | 893606/008 | 2021/07/23 | 2022/07/22 |
| EMI Test Receiver | R&S | ESPI3 | 101841-cd | 2021/07/23 | 2022/07/22 |
| EMI Test Receiver | R&S | ESCI7 | 101102 | 2021/09/19 | 2022/09/18 |
| Spectrum Analyzer | Agilent | N9020A | MY48010425 | 2021/09/19 | 2022/09/18 |
| Spectrum Analyzer | R&S | FSV40 | 100019 | 2021/07/23 | 2022/07/22 |
| Vector Signal generator | Agilent | N5181A | MY49060502 | 2021/07/23 | 2022/07/22 |
| Spectrum Analyzer | Agilent | E4421B | 3610AO1069 | 2021/09/19 | 2022/09/18 |
| Climate Chamber | ESPEC | EL-10KA | A20120523 | 2021/09/19 | 2022/09/18 |
| Controller | EM Electronics | Controller EM 1000 | N/A | N/A | N/A |
| Horn Antenna | Schwarzbeck | BBHA 9120D | 01622 | 2020/11/08 | 2021/11/07 |
| Active Loop Antenna | Beijing Da Ze Technology Co.,Ltd. | ZN30900C | 15006 | 2021/10/10 | 2022/10/09 |
| Bilog Antenna | Schwarzbeck | VULB9163 | 000976 | 2021/07/23 | 2022/07/22 |
| Broadband Horn Antenna | SCHWARZBECK | BBHA 9170 | 791 | 2020/11/08 | 2021/11/07 |
| Amplifier | Schwarzbeck | BBV 9743 | #202 | 2021/07/23 | 2022/07/22 |
| Amplifier | Schwarzbeck | BBV9179 | 9719-025 | 2021/07/23 | 2022/07/22 |
| Amplifier | EMCI | EMC051845B | 980355 | 2021/07/23 | 2022/07/22 |
| Temperature/Humidity Meter | Gangxing | CTH-608 | 02 | 2021/07/23 | 2022/07/22 |
| High-Pass Filter | K&L | 9SH10-2700/X12750-O/O | KL142031 | 2021/07/23 | 2022/07/22 |
| High-Pass Filter | K&L | 41H10-1375/U12750-O/O | KL142032 | 2021/07/23 | 2022/07/22 |

| | | | | | |
|---|---|---|---|---|---|
| RF Cable(below 1GHz) | HUBER+SUHNER | RG214 | RE01 | 2021/07/23 | 2022/07/22 |
| RF Cable(above 1GHz) | HUBER+SUHNER | RG214 | RE02 | 2021/07/23 | 2022/07/22 |
| Data acquisition card | Agilent | U2531A | TW53323507 | 2021/07/23 | 2022/07/22 |
| Power Sensor | Agilent | U2021XA | MY5365004 | 2021/07/23 | 2022/07/22 |
| Test Control Unit | Tonscend | JS0806-1 | 178060067 | 2021/07/23 | 2022/07/22 |
| Automated filter bank | Tonscend | JS0806-F | 19F8060177 | 2021/07/23 | 2022/07/22 |
| EMI Test Software | Tonscend | JS1120-1 | Ver 2.6.8.0518 | / | / |
| EMI Test Software | Tonscend | JS1120-3 | Ver 2.5.77.0418 | / | / |
| EMI Test Software | Tonscend | JS32-CE | Ver 2.5 | / | / |
| EMI Test Software | Tonscend | JS32-RE | Ver 2.5.1.8 | / | / |

Note: The Cal.Interval was one year.

# 4 TEST CONDITIONS AND RESULTS

## 4.1 AC Power Conducted Emission

**TEST CONFIGURATION**




**TEST PROCEDURE**

1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2013.
2 Support equipment, if needed, was placed as per ANSI C63.10-2013
3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2013
4 The EUT received DC 12V power from adapter, the adapter received AC120V/60Hz and AC 240V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5 All support equipments received AC power from a second LISN, if any.
6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT.The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
8 During the above scans, the emissions were maximized by cable manipulation.

**AC Power Conducted Emission Limit**

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following：

| Frequency range (MHz) | Limit (dBuV) | |
|---|---|---|
| | Quasi-peak | Average |
| 0.15-0.5 | 66 to 56* | 56 to 46* |
| 0.5-5 | 56 | 46 |
| 5-30 | 60 | 50 |
| * Decreases with the logarithm of the frequency. | | |

**TEST RESULTS**

| Temperature | 22.8℃ | Humidity | 56% |
|---|---|---|---|
| Test Engineer | Moon Tan | Configurations | WLAN2.4G |

Remark:

1. All modes of 802.11b/g/n were tested at Low, Middle, and High channel; only the worst result of 802.11b CH11 was reported as below:
2. Both 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz power supply have been tested, only the worst result of 120 VAC, 60 Hz was reported as below:.

| Power supply: | AC 120V/60Hz(adapter) | Polarization | L |
|---|---|---|---|

**Test Graph**




Suspected List

| NO. | Freq. [MHz] | Reading [dBµV] | Level [dBµV] | Factor [dB] | Limit [dBµV] | Margin [dB] | Detector | Type | Verdict |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 0.1905 | 22.38 | 32.88 | 10.50 | 54.01 | 21.13 | AV | L1 | PASS |
| 2 | 0.195 | 36.16 | 46.66 | 10.50 | 63.82 | 17.16 | PK | L1 | PASS |
| 3 | 0.3795 | 34.12 | 44.62 | 10.50 | 58.29 | 13.67 | PK | L1 | PASS |
| 4 | 0.3885 | 20.16 | 30.66 | 10.50 | 48.10 | 17.44 | AV | L1 | PASS |
| 5 | 0.645 | 37.54 | 48.04 | 10.50 | 56.00 | 7.96 | PK | L1 | PASS |
| 6 | 0.654 | 22.38 | 32.88 | 10.50 | 46.00 | 13.12 | AV | L1 | PASS |
| 7 | 0.987 | 34.13 | 44.63 | 10.50 | 56.00 | 11.37 | PK | L1 | PASS |
| 8 | 1.014 | 21.09 | 31.59 | 10.50 | 46.00 | 14.41 | AV | L1 | PASS |
| 9 | 2.004 | 18.02 | 28.52 | 10.50 | 46.00 | 17.48 | AV | L1 | PASS |
| 10 | 2.0805 | 32.07 | 42.57 | 10.50 | 56.00 | 13.43 | PK | L1 | PASS |
| 11 | 23.1315 | 24.11 | 34.61 | 10.50 | 50.00 | 15.39 | AV | L1 | PASS |
| 12 | 23.9325 | 37.26 | 47.76 | 10.50 | 60.00 | 12.24 | PK | L1 | PASS |

Note:1).Level (dBµV)= Reading (dBµV)+ Factor (dB)
2). Factor (dB)=insertion loss of LISN (dB) + Cable loss (dB)
3). Margin(dB) = Limit (dBµV) - Level (dBµV)

| Power supply: | AC 120V/60Hz(adapter) | Polarization | N |
|---|---|---|---|

**Test Graph**




## Suspected List

| NO. | Freq. [MHz] | Reading [dBµV] | Level [dBµV] | Factor [dB] | Limit [dBµV] | Margin [dB] | Detector | Type | Verdict |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 0.186 | 35.16 | 45.66 | 10.50 | 64.21 | 18.55 | PK | N | PASS |
| 2 | 0.195 | 20.84 | 31.34 | 10.50 | 53.82 | 22.48 | AV | N | PASS |
| 3 | 0.267 | 33.07 | 43.57 | 10.50 | 61.21 | 17.64 | PK | N | PASS |
| 4 | 0.285 | 17.83 | 28.33 | 10.50 | 50.67 | 22.34 | AV | N | PASS |
| 5 | 0.465 | 17.74 | 28.24 | 10.50 | 46.60 | 18.36 | AV | N | PASS |
| 6 | 0.4695 | 32.05 | 42.55 | 10.50 | 56.52 | 13.97 | PK | N | PASS |
| 7 | 0.762 | 32.59 | 43.09 | 10.50 | 56.00 | 12.91 | PK | N | PASS |
| 8 | 0.771 | 18.94 | 29.44 | 10.50 | 46.00 | 16.56 | AV | N | PASS |
| 9 | 1.4415 | 30.59 | 41.09 | 10.50 | 56.00 | 14.91 | PK | N | PASS |
| 10 | 1.473 | 16.10 | 26.60 | 10.50 | 46.00 | 19.40 | AV | N | PASS |
| 11 | 22.8885 | 38.17 | 48.67 | 10.50 | 60.00 | 11.33 | PK | N | PASS |
| 12 | 23.0685 | 23.63 | 34.13 | 10.50 | 50.00 | 15.87 | AV | N | PASS |

Note:1).Level (dBµV)= Reading (dBµV)+ Factor (dB)
2). Factor (dB)=insertion loss of LISN (dB) + Cable loss (dB)
3). Margin(dB) = Limit (dBµV) - Level (dBµV)

## 4.2 Radiated Emission

**TEST CONFIGURATION**

Frequency range 9 KHz – 30MHz




Frequency range 30MHz – 1000MHz




Frequency range above 1GHz-25GHz



**TEST PROCEDURE**

1. The EUT was placed on a turn table which is 0.8m above ground plane when testing frequency range 9 KHz –1GHz;the EUT was placed on a turn table which is 1.5m above ground plane when testing frequency range 1GHz – 25GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. Radiated emission test frequency band from 9KHz to 25GHz.
6. The distance between test antenna and EUT as following table states:

| Test Frequency range | Test Antenna Type | Test Distance |
|---|---|---|
| 9KHz-30MHz | Active Loop Antenna | 3 |
| 30MHz-1GHz | Ultra-Broadband Antenna | 3 |
| 1GHz-18GHz | Double Ridged Horn Antenna | 3 |
| 18GHz-25GHz | Horn Anternna | 1 |

7. Setting test receiver/spectrum as following table states:

| Test Frequency range | Test Receiver/Spectrum Setting | Detector |
|---|---|---|
| 9KHz-150KHz | RBW=200Hz/VBW=3KHz,Sweep time=Auto | QP |
| 150KHz-30MHz | RBW=9KHz/VBW=100KHz,Sweep time=Auto | QP |
| 30MHz-1GHz | RBW=120KHz/VBW=1000KHz,Sweep time=Auto | QP |
| 1GHz-40GHz | Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto<br>Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto | Peak |

**Field Strength Calculation**

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

**FS = RA + AF + CL - AG**

| | |
|---|---|
| Where FS = Field Strength | CL = Cable Attenuation Factor (Cable Loss) |
| RA = Reading Amplitude | AG = Amplifier Gain |
| AF = Antenna Factor | |

Transd=AF +CL-AG

**RADIATION LIMIT**

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission from intentional radiators at a distance of 3 meters shall not exceed the following table. According to § 15.247(d), in any 100kHz bandwidth outside the frequency band in which the EUT is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the100kHz bandwidth within the band that contains the highest level of desired power.

The pre-test have done for the EUT in three axes and found the worst emission at position shown in test setup photos.

| Frequency (MHz) | Distance (Meters) | Radiated (dBμV/m) | Radiated (μV/m) |
|---|---|---|---|
| 0.009-0.49 | 3 | 20log(2400/F(KHz))+40log(300/3) | 2400/F(KHz) |
| 0.49-1.705 | 3 | 20log(24000/F(KHz))+ 40log(30/3) | 24000/F(KHz) |
| 1.705-30 | 3 | 20log(30)+ 40log(30/3) | 30 |
| 30-88 | 3 | 40.0 | 100 |
| 88-216 | 3 | 43.5 | 150 |
| 216-960 | 3 | 46.0 | 200 |
| Above 960 | 3 | 54.0 | 500 |

**TEST RESULTS**

| Temperature | 22.8℃ | Humidity | 56% |
|---|---|---|---|
| Test Engineer | Moon Tan | Configurations | WLAN2.4G |

Remark:

1. This test was performed with EUT in X, Y, Z position and the worse case was found when EUT in X position.
2. All three channels (lowest/middle/highest) of each mode were measured below 1GHz and recorded worst case at 802.11b low channel.
3. All three channels (lowest/middle/highest) of each mode were measured above1GHz and recorded worst case at 802.11b mode.
4. Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.

**For 30MHz-1GHz**

Horizontal

**Test Graph**




**Suspected Data List**

| NO. | Freq. [MHz] | Reading [dBµV/m] | Level [dBµV/m] | Factor [dB] | Limit [dBµV/m] | Margin [dB] | Height [cm] | Angle [°] | Polarity |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 129.546 | 48.82 | 27.55 | -21.27 | 43.50 | 15.95 | 100 | 296 | Horizontal |
| 2 | 302.448 | 49.43 | 32.12 | -17.31 | 46.00 | 13.88 | 100 | 296 | Horizontal |
| 3 | 388.778 | 53.03 | 37.45 | -15.58 | 46.00 | 8.55 | 100 | 41 | Horizontal |
| 4 | 648.011 | 47.91 | 35.99 | -11.92 | 46.00 | 10.01 | 100 | 41 | Horizontal |
| 5 | 734.462 | 50.43 | 39.38 | -11.05 | 46.00 | 6.62 | 100 | 41 | Horizontal |
| 6 | 820.792 | 51.76 | 41.48 | -10.28 | 46.00 | 4.52 | 100 | 296 | Horizontal |

Note:1).Level (dBµV/m)= Reading (dBµV/m)+ Factor (dB/m)
2). Factor(dB/m)=Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB)
3). Margin(dB) = Limit (dBµV/m) - Level (dBµV/m)

Vertical

**Test Graph**




**Suspected Data List**

| NO. | Freq. [MHz] | Reading [dBµV/m] | Level [dBµV/m] | Factor [dB] | Limit [dBµV/m] | Margin [dB] | Height [cm] | Angle [°] | Polarity |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 78.015 | 49.75 | 28.51 | -21.24 | 40.00 | 11.49 | 100 | 63 | Vertical |
| 2 | 129.546 | 60.94 | 39.67 | -21.27 | 43.50 | 3.83 | 100 | 0 | Vertical |
| 3 | 215.997 | 54.43 | 35.50 | -18.93 | 43.50 | 8.00 | 100 | 24 | Vertical |
| 4 | 302.448 | 53.37 | 36.06 | -17.31 | 46.00 | 9.94 | 100 | 0 | Vertical |
| 5 | 734.462 | 52.62 | 41.57 | -11.05 | 46.00 | 4.43 | 100 | 24 | Vertical |
| 6 | 820.792 | 52.23 | 41.95 | -10.28 | 46.00 | 4.05 | 100 | 24 | Vertical |

Note:1).Level (dBµV/m)= Reading (dBµV/m)+ Factor (dB/m)
2). Factor(dB/m)=Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB)
3). Margin(dB) = Limit (dBµV/m) - Level (dBµV/m)

**For 1GHz to 25GHz**

*Note: 802.11b/802.11g/802.11n (H20)/802.11n (H40) all have been tested, only worse case 802.11b mode 1Mbps is reported*

| **Frequency(MHz):** | | | **2412** | | **Polarity:** | | | **HORIZONTAL** | |
|---|---|---|---|---|---|---|---|---|---|
| Frequency (MHz) | Emission Level (dBuV/m) | | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 4824.00 | 49.25 | PK | 74 | 24.75 | 48.46 | 30.28 | 7.01 | 36.50 | 0.79 |
| 4824.00 | -- | AV | 54 | -- | -- | -- | -- | -- | -- |
| 7236.00 | 50.36 | PK | 74 | 23.64 | 40.16 | 36.59 | 8.91 | 35.30 | 10.20 |
| 7236.00 | -- | AV | 54 | -- | -- | -- | -- | -- | -- |

| **Frequency(MHz):** | | | **2412** | | **Polarity:** | | | **VERTICAL** | |
|---|---|---|---|---|---|---|---|---|---|
| Frequency (MHz) | Emission Level (dBuV/m) | | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 4824.00 | 50.45 | PK | 74 | 23.55 | 49.66 | 30.28 | 7.01 | 36.50 | 0.79 |
| 4824.00 | -- | AV | 54 | -- | -- | -- | -- | -- | -- |
| 7236.00 | 51.86 | PK | 74 | 22.14 | 41.66 | 36.59 | 8.91 | 35.30 | 10.20 |
| 7236.00 | -- | AV | 54 | -- | -- | -- | -- | -- | -- |

| **Frequency(MHz):** | | | **2437** | | **Polarity:** | | | **HORIZONTAL** | |
|---|---|---|---|---|---|---|---|---|---|
| Frequency (MHz) | Emission Level (dBuV/m) | | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 4874.00 | 49.88 | PK | 74 | 24.12 | 48.40 | 30.36 | 7.62 | 36.50 | 1.48 |
| 4874.00 | -- | AV | 54 | -- | -- | -- | -- | -- | -- |
| 7311.00 | 50.63 | PK | 74 | 23.37 | 40.48 | 36.61 | 8.84 | 35.30 | 10.15 |
| 7311.00 | -- | AV | 54 | -- | -- | -- | -- | -- | -- |

| **Frequency(MHz):** | | | **2437** | | **Polarity:** | | | **VERTICAL** | |
|---|---|---|---|---|---|---|---|---|---|
| Frequency (MHz) | Emission Level (dBuV/m) | | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 4874.00 | 50.58 | PK | 74 | 23.42 | 49.10 | 30.36 | 7.62 | 36.50 | 1.48 |
| 4874.00 | -- | AV | 54 | -- | -- | -- | -- | -- | -- |
| 7311.00 | 51.33 | PK | 74 | 22.67 | 41.18 | 36.61 | 8.84 | 35.30 | 10.15 |
| 7311.00 | -- | AV | 54 | -- | -- | -- | -- | -- | -- |

| Frequency(MHz): | | | 2462 | | Polarity: | | | HORIZONTAL | |
|---|---|---|---|---|---|---|---|---|---|
| Frequency (MHz) | Emission Level (dBuV/m) | | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 4924.00 | 50.19 | PK | 74 | 23.81 | 48.02 | 30.43 | 7.94 | 36.20 | 2.17 |
| 4924.00 | -- | AV | 54 | -- | -- | -- | -- | -- | -- |
| 7386.00 | 50.79 | PK | 74 | 23.21 | 40.86 | 36.78 | 8.45 | 35.30 | 9.93 |
| 7386.00 | -- | AV | 54 | -- | -- | -- | -- | -- | -- |

| Frequency(MHz): | | | 2462 | | Polarity: | | | VERTICAL | |
|---|---|---|---|---|---|---|---|---|---|
| Frequency (MHz) | Emission Level (dBuV/m) | | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 4924.00 | 50.89 | PK | 74 | 23.11 | 48.72 | 30.43 | 7.94 | 36.20 | 2.17 |
| 4924.00 | -- | AV | 54 | -- | -- | -- | -- | -- | -- |
| 7386.00 | 51.99 | PK | 74 | 22.01 | 42.06 | 36.78 | 8.45 | 35.30 | 9.93 |
| 7386.00 | -- | AV | 54 | -- | -- | -- | -- | -- | -- |

REMARKS:

1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.
6. RBW1MHz VBW3MHz Peak detector is for PK value; RBW 1MHz VBW10Hz Peak detector is for AV value.

***Results of Band Edges Test (Radiated)***

*Note: 802.11b/802.11g/802.11n (H20) /802.11n (H40) all have been tested, only worse case 802.11b is reported*.

| **Frequency(MHz):** | | | **2412** | | **Polarity:** | | | **HORIZONTAL** | |
|---|---|---|---|---|---|---|---|---|---|
| Frequency (MHz) | Emission Level (dBuV/m) | | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 2390.00 | 47.25 | PK | 74 | 26.75 | 52.66 | 27.49 | 3.32 | 36.22 | -5.41 |
| 2390.00 | -- | AV | 54 | -- | -- | -- | -- | -- | -- |
| 2400.00 | 50.36 | PK | 74 | 23.64 | 55.62 | 27.55 | 3.41 | 36.22 | -5.26 |
| 2400.00 | -- | AV | 54 | -- | -- | -- | -- | -- | -- |

| **Frequency(MHz):** | | | **2412** | | **Polarity:** | | | **VERTICAL** | |
|---|---|---|---|---|---|---|---|---|---|
| Frequency (MHz) | Emission Level (dBuV/m) | | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 2390.00 | 49.75 | PK | 74 | 24.25 | 55.16 | 27.49 | 3.32 | 36.22 | -5.41 |
| 2390.00 | -- | AV | 54 | -- | -- | -- | -- | -- | -- |
| 2400.00 | 52.06 | PK | 74 | 21.94 | 57.32 | 27.55 | 3.41 | 36.22 | -5.26 |
| 2400.00 | -- | AV | 54 | -- | -- | -- | -- | -- | -- |

| **Frequency(MHz):** | | | **2462** | | **Polarity:** | | | **HORIZONTAL** | |
|---|---|---|---|---|---|---|---|---|---|
| Frequency (MHz) | Emission Level (dBuV/m) | | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 2483.50 | 49.25 | PK | 74 | 24.75 | 54.76 | 27.45 | 3.38 | 36.34 | -5.51 |
| 2483.50 | -- | AV | 54 | -- | -- | -- | -- | -- | -- |
| 2500.00 | 44.05 | PK | 74 | 29.95 | 49.52 | 27.41 | 3.47 | 36.35 | -5.47 |
| 2500.00 | -- | AV | 54 | -- | -- | -- | -- | -- | -- |

| **Frequency(MHz):** | | | **2462** | | **Polarity:** | | | **VERTICAL** | |
|---|---|---|---|---|---|---|---|---|---|
| Frequency (MHz) | Emission Level (dBuV/m) | | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 2483.50 | 50.85 | PK | 74 | 23.15 | 56.36 | 27.45 | 3.38 | 36.34 | -5.51 |
| 2483.50 | -- | AV | 54 | -- | -- | -- | -- | -- | -- |
| 2500.00 | 46.15 | PK | 74 | 27.85 | 51.62 | 27.41 | 3.47 | 36.35 | -5.47 |
| 2500.00 | -- | AV | 54 | -- | -- | -- | -- | -- | -- |

REMARKS:

1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.
6. RBW1MHz VBW3MHz Peak detector is for PK value; RBW 1MHz VBW10Hz Peak detector is for AV value.

## 4.3 Maximum Conducted Output Power

**Limit**

The Maximum Conducted Output Power Measurement is 30dBm.

**Test Procedure**

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power sensor.

**Test Configuration**




**Test Results**

| Temperature | 22.8℃ | Humidity | 56% |
|---|---|---|---|
| Test Engineer | Moon Tan | Configurations | WLAN2.4G |

**WIFI**

| Type | Channel | Output power AVG (dBm) | Limit (dBm) | Result |
|---|---|---|---|---|
| 802.11b | 01 | 8.88 | 30.00 | Pass |
| | 06 | 9.15 | | |
| | 11 | 9.23 | | |
| 802.11g | 01 | 9.08 | 30.00 | Pass |
| | 06 | 9.32 | | |
| | 11 | 9.27 | | |
| 802.11n(HT20) | 01 | 8.19 | 30.00 | Pass |
| | 06 | 9.18 | | |
| | 11 | 9.15 | | |
| 802.11n(HT40) | 03 | 8.44 | 30.00 | Pass |
| | 06 | 9.45 | | |
| | 09 | 9.25 | | |

Note: 1.The test results including the cable lose.

## 4.4 Power Spectral Density

**Limit**

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

**Test Procedure**

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW ≥ 3 kHz.
3. Set the VBW ≥ 3× RBW.
4. Set the span to 1.5 times the DTS channel bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum power level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
11. The resulting peak PSD level must be 8dBm.

**Test Configuration**




**Test Results**

| Temperature | 22.8℃ | Humidity | 56% |
|---|---|---|---|
| Test Engineer | Moon Tan | Configurations | WLAN2.4G |

**WIFI**

| Type | Channel | Power Spectral Density (dBm/3KHz) | Limit (dBm/3KHz) | Result |
|---|---|---|---|---|
| 802.11b | 01 | -12.22 | 8.00 | Pass |
| | 06 | -12.79 | | |
| | 11 | -12.41 | | |
| 802.11g | 01 | -13.73 | 8.00 | Pass |
| | 06 | -14.14 | | |
| | 11 | -14.92 | | |
| 802.11n(HT20) | 01 | -15.50 | 8.00 | Pass |
| | 06 | -15.53 | | |
| | 11 | -14.97 | | |
| 802.11n(HT40) | 03 | -17.53 | 8.00 | Pass |
| | 06 | -17.66 | | |
| | 09 | -16.44 | | |

Test plot as follows:

| 802.11b | 802.11g |
| --- | --- |
|  |  |
| CH01 | CH01 |
|  |  |
| CH06 | CH06 |
| |  |
| CH11 | CH11 |

| 802.11n(HT20) | 802.11n(HT40) |
|---|---|
|  |  |
| CH01 | CH03 |
|  |  |
| CH06 | CH06 |
|  |  |
| CH11 | CH09 |

## 4.5 6dB Bandwidth

**Limit**

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz

**Test Procedure**

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 KHz RBW and 300 KHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

**Test Configuration**




**Test Results**

| Temperature | 22.8℃ | Humidity | 56% |
|---|---|---|---|
| Test Engineer | Moon Tan | Configurations | WLAN2.4G |

***WIFI***

| Type | Channel | 6dB Bandwidth (MHz) | Limit (KHz) | Result |
|---|---|---|---|---|
| 802.11b | 01 | 7.160 | ≥500 | Pass |
| | 06 | 7.640 | | |
| | 11 | 7.160 | | |
| 802.11g | 01 | 16.120 | ≥500 | Pass |
| | 06 | 16.000 | | |
| | 11 | 15.760 | | |
| 802.11n(HT20) | 01 | 15.560 | ≥500 | Pass |
| | 06 | 16.400 | | |
| | 11 | 16.680 | | |
| 802.11n(HT40) | 03 | 35.840 | ≥500 | Pass |
| | 06 | 35.840 | | |
| | 09 | 35.200 | | |

Test plot as follows:

| 802.11b | 802.11g |
| --- | --- |
| | |
| CH01 | CH01 |
| | |
| CH06 | CH06 |
| | |
| CH11 | CH11 |

| 802.11n(HT20) | 802.11n(HT40) |
|---|---|
| |  |
| CH01 | CH03 |
| |  |
| CH06 | CH06 |
| |  |
| CH11 | CH09 |

## 4.6 Out-of-band Emissions

**Limit**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF con-ducted or a radiated measurement, pro-vided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter com-plies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

**Test Procedure**

Connect the transmitter output to spectrum analyzer using a low loss RF cable, and set the spectrum analyzer to RBW=100 kHz, VBW= 300 kHz, peak detector , and max hold. Measurements utilizing these setting are made of the in-band reference level, bandedge and out-of-band emissions.

**Test Configuration**




**Test Results**

| Temperature | 22.8℃ | Humidity | 56% |
|---|---|---|---|
| Test Engineer | Moon Tan | Configurations | WLAN2.4G |

Remark: The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandage measurement data.

Test plot as follows:

| *802.11b CH01* | *802.11b CH06* |
|---|---|
| | |
| Reference | |
|  |  |
| 30MHz-3GHz | 30MHz-3GHz |
| | |
| 3GHz-25GHz | 3GHz-25GHz |

| *802.11b CH11* | *802.11g CH01* |
|---|---|
| | |
| Reference | Reference |
|  |  |
| 30MHz-3GHz | 30MHz-3GHz |
| | |
| 3GHz-25GHz | 3GHz-25GHz |

| *802.11g CH06* | *802.11g CH11* |
|---|---|
| | |
| Reference | Reference |
|  |  |
| 30MHz-3GHz | 30MHz-3GHz |
| | |
| 3GHz-25GHz | 3GHz-25GHz |

| *802.11n(HT20) CH01* | *802.11n(HT20) CH06* |
|---|---|
| | |
| Reference | |
|  |  |
| 30MHz-3GHz | 30MHz-3GHz |
| | |
| 3GHz-25GHz | 3GHz-25GHz |

| *802.11n(HT20) CH11* | *802.11n(HT40) CH03* |
|---|---|
| | |
| Reference | Reference |
|  |  |
| 30MHz-3GHz | 30MHz-3GHz |
| | |
| 3GHz-25GHz | 3GHz-25GHz |

| *802.11n(HT40) CH06* | *802.11n(HT40) CH09* |
| --- | --- |
| | |
| Reference | Reference |
|  |  |
| 30MHz-3GHz | 30MHz-3GHz |
| | |
| 3GHz-25GHz | 3GHz-25GHz |

***Band-edge Measurements for RF Conducted Emissions:***

| 802.11b | |
|---|---|
|  |  |
| Left bandedge | Right bandedge |

| 802.11g | |
|---|---|
|  |  |
| Left bandedge | Right bandedge |

| 802.11n(HT20) | |
|---|---|
|  |  |
| Left bandedge | Right bandedge |

| *802.11n(HT40)* | |
|---|---|
|  |  |
| Left bandedge | Right bandedge |

## 4.7 Antenna Requirement

**Standard Applicable**

**For intentional device, according to FCC 47 CFR Section 15.203:**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited

**FCC CFR Title 47 Part 15 Subpart C Section 15.247(b):**

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

**Test Result:**

The maximum gain of antenna was 2.65dBi for 2.4GHz WIFI.

# 5 Test Setup Photos of the EUT



# 6 Photos of the EUT

## External Photos of EUT











## Internal Photos








大板
小板





********** End of Report **********