

RF Exposure Exemption Report

Manufacturer: DOMO Tactical Communications
(DTC) Software-Defined Radio (SDR) Module
Model: BluSDR-30-198270-C



**Add value.
Inspire trust.**

In accordance with FCC CFR 47 Pt 1.1307

Prepared for: DOMO Tactical Communications (DTC) Ltd
Fusion 2, 1100 Parkway
Whiteley
Fareham, PO15 7AB

COMMERCIAL-IN-CONFIDENCE

FCC ID: XRF BLUSDR30198270

Document 75964625-04 Issue: 01

SIGNATURE

NAME	JOB TITLE	RESPONSIBLE FOR	ISSUE DATE
Steve Marshall	Senior Engineer	Authorised Signatory	11 December 2025

Signatures in this approval box have checked this document in line with the requirements of TÜV SÜD document control rules.

FCC Accreditation
294497/UK2010 Octagon House, Fareham Test Laboratory

EXECUTIVE SUMMARY

The wireless devices described within this report are compliant with the exemption criteria related to human exposure to electromagnetic fields laid out in FCC CFR Title 47 Part 1.1307. at a distance of 110 mm.



DISCLAIMER AND COPYRIGHT

This non-binding report has been prepared by TÜV SÜD with all reasonable skill and care. The document is confidential to the potential Client and TÜV SÜD. No part of this document may be reproduced without the prior written approval of TÜV SÜD. © 2025 TÜV SÜD. This report relates only to the actual item/items tested.

ACCREDITATION

Our UKAS Accreditation does not cover opinions and interpretations and any expressed are outside the scope of our UKAS Accreditation. Results of tests not covered by our UKAS Accreditation Schedule are marked NUA (Not UKAS Accredited).

TÜV SÜD
is a trading name of TÜV SÜD Ltd
Registered in Scotland at East Kilbride,
Glasgow G75 0QF, United Kingdom
Registered number: SC215164

TÜV SÜD Ltd is a
TÜV SÜD Group Company

Phone: +44 (0) 1489 558100
Fax: +44 (0) 1489 558101
www.tuvsud.com/en

TÜV SÜD
Octagon House
Concorde Way
Fareham
Hampshire PO15 5RL
United Kingdom



Contents

1 Report Summary2

1.1 Report Modification Record.....2

1.2 Introduction.....2

1.3 Brief Summary of Results3

1.4 Product Information4

2 Assessment Details5

2.1 Single RF Source options for determination of exemption.5

2.2 Individual Antenna Port Exposure Results.....6



1 Report Summary

1.1 Report Modification Record

Alterations and additions to this report will be issued to the holders of each copy in the form of a complete document.

Issue	Description of Change	Date of Issue
1	First Issue	11-Dec-2025

Table 1

1.2 Introduction

Applicant	DOMO Tactical Communications (DTC)
Manufacturer	DOMO Tactical Communications (DTC)
Model Number(s)	BluSDR-30-198270-C
Hardware Version(s)	8
Software Version(s)	8.4.1
Specification/Issue/Date	FCC 47 CFR Part 1.1307: 2024
Order Number	PO-071314-1
Date	13 May 2025
Related Document(s)	• KDB 447498 D04 v01 • FCC 47 CFR Part 2.1091: 2024



1.3 Brief Summary of Results

The wireless devices described within this report are compliant with the exemption criteria related to human exposure to electromagnetic fields laid out in FCC CFR Title 47 Part 1.1307.

The calculations shown in this report were made in accordance with the procedures specified in the applied test specification(s).

The calculations shown in this report were made in accordance with the procedures specified in the applied test specification(s).



1.4 Product Information

1.4.1 Technical Description

Small form factor software-defined radio conceived primarily for systems integration into unmanned platforms (including controllers) and into other professional user communications infrastructure.

1.4.2 Transmitter Description

The following radio access technologies and frequency bands are supported by the equipment under test.

Radio Access Technology	Frequency Band (MHz)	Minimum Frequency (MHz)	Output Power (dBm)	Duty Cycle (%)
2.4 GHz WIFI	2400 – 2483.5	2401.875	30.0 *	75

Table 2 – Transmitter Description- FCC

Note: Transmitter power includes upper bounds of uncertainty therefore maximum values are used.

Note *: The BluSDR-30-198270-C is identified as a 2x1W Radio Module. The Power value inserted here is the Maximum Output power declared $2 \times 0.5W = 1W$ max (30dBm).

1.4.3 Antenna Description

The following antennas are supported by the equipment under test.

Radio Access Technology	Antenna Model	Gain (dBi)	Minimum Separation Distance (mm)
2.4 GHz WIFI	Chelton OA2-2.3V/1842	2.9	110

Table 3 – Antenna description

In the case of more than one type of antenna being supported by the equipment, the calculation is based on the maximum of the antenna gains. If other antennas can be used that have greater gains, the minimum separation distances will need to be recalculated.

Note: Antenna gain includes upper bounds of uncertainty therefore maximum values are used.

1.4.4 Equipment Configuration

The device supports the following modes:-

- Single RF Source only.



2 Assessment Details

2.1 Single RF Source options for determination of exemption.

Option	Reference	RF Exposure Test Exemptions for Single Source												
A (1-mW Test Exemption)	FCC 1.1307(b)(3)(i)(A)	The available maximum time averaged power is no more than 1 mW, regardless of separation distance.												
B (SAR-Based Exemption)	FCC 1.1307(b)(3)(i)(B)	The available maximum timeaveraged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by: $P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$ Where $x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$ and $ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$ <i>d</i> = the separation distance (cm);												
C (MPE-Based Exemption)	FCC 1.1307(b)(3)(i)(C)	Or using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least λ/2π, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of λ/4 or if the antenna gain is less than that of a half-wave dipole (1.64 linear value). TABLE 1 TO § 1.1307(b)(3)(i)(C)—SINGLE RF SOURCES SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION <table><tr><th>RF Source frequency (MHz)</th><th>Threshold ERP (watts)</th></tr><tr><td>0.3–1.34</td><td>1,920 R².</td></tr><tr><td>1.34–30</td><td>3,450 R²/f².</td></tr><tr><td>30–300</td><td>3.83 R².</td></tr><tr><td>300–1,500</td><td>0.0128 R²f.</td></tr><tr><td>1,500–100,000</td><td>19.2R².</td></tr></table>	RF Source frequency (MHz)	Threshold ERP (watts)	0.3–1.34	1,920 R ² .	1.34–30	3,450 R ² /f ² .	30–300	3.83 R ² .	300–1,500	0.0128 R ² f.	1,500–100,000	19.2R ² .
RF Source frequency (MHz)	Threshold ERP (watts)													
0.3–1.34	1,920 R ² .													
1.34–30	3,450 R ² /f ² .													
30–300	3.83 R ² .													
300–1,500	0.0128 R ² f.													
1,500–100,000	19.2R ² .													



2.2 Individual Antenna Port Exposure Results

2.2.1 Single Source Calculation of Exposure at Specified Separation Distance FCC 1.1307(b)(3)(i)(B) 'Option B' (SAR Based Exemption)

RAT	Frequency (MHz)	Conducted Power Output (mW)	Duty Cycle %	Time Average Conducted Power Output (mW)	Antenna Gain Ratio	Maximum Power (EIRP) mW	Maximum Power (ERP) mW	Minimum Antenna to User Separation Distance (mm)	Pth (mW) 1.1307 (b)(3)(i)(B)	Greater of Max time averaged conducted power or ERP?	1.1307(b)(3)(i)(B) Exemption (Yes/No) (300 MHz to 6 GHz, 0.5 cm to 20 cm)
2.4 GHz	2401.875	1000	75	750	1.950	1462.5	891.77	110	983.9	891.77	Yes

Table 4 - Transmitter Result

The calculations show that the individual transmitters comply with FCC 1.1307(b)(3)(i)(B) SAR-based exemption at a minimum distance of 110 mm.