



ECL-EMC Test Report No.: 16-091

Equipment under test: **ION-M7P/85P/17EP/19P**
800MHz Path
FCC ID: **XS5-M78517E19P**

Type of test: **FCC 47 CFR Part 90 Subpart S:2016**
Private Land Mobile Repeater

Measurement Procedures: 47 CFR Parts 2:2016 (*Frequency Allocations and Radio Treaty Matters; General Rules and Regulations*),
Part 90:2016 (*Private Land Mobile*),
ANSI/TIA-603-C (2004), *Land Mobile FM or PM Communications Equipment Measurement and Performance Standards*

Test result: **Passed**

Date of issue:	29.04.16	Signature:	
Issue-No.:	01	Author:	 Tom Zahlmann Test engineer Digitally signed by Tom Zahlmann DN: cn=Tom Zahlmann, o=Bureau Veritas CPS, ou=ECL, email=tom.zahlmann@de.bureauveritas.com, c=DE Date: 2016.04.29 10:49:04 +02'00'
Date of delivery:	25.04.16	Checked:	 Frank Tomandl Project manager EMC Digital unterschrieben von Frank Tomandl DN: cn=Frank Tomandl, o=Bureau Veritas CPS, ou=ECL, email=frank.tomandl@de.bureauveritas.com, c=DE Datum: 2016.04.29 11:11:26 +02'00'
Test dates:	24.03.16 – 26.04.16		
Pages:	64		



Manufacturer: ANDREW Wireless Systems GmbH
Industriering 10

D-86675 Buchdorf

Tel.: +49 (0)9099 69 0

Fax: +49 (0)9099 69 140

Test Location: Bureau Veritas Consumer Products Services
Germany GmbH
European Compliance Laboratory (ECL)
Thurn-und-Taxis-Straße 18

D-90411 Nürnberg

Tel.: +49 40 74041 0

Fax: +49 40 74041-2755

General:

The purpose of this report is to show compliance to the FCC regulations for licensed devices operating under section 90 of the Code of Federal Regulations title 47.

This report informs about the results of the RF tests, it only refers to the equipment under test. No part of this report may be reproduced in any form, without written permission.



Table of contents

1	TEST RESULTS SUMMARY	6
2	EQUIPMENT UNDER TEST (E.U.T.)	7
2.1	DESCRIPTION	7
2.1.1	DOWNLINK	7
2.1.2	UPLINK	7
2.1.3	DESCRIPTION OF EUT	8
2.1.4	BLOCK DIAGRAM OF MEASUREMENT REFERENCE POINTS	9
2.1.5	DOWNLINK SYSTEM GAIN AND OUTPUT POWER.....	9
3	TEST SITE (ANDREW BUCHDORF)	10
3.1	TEST ENVIRONMENT	10
3.2	TEST EQUIPMENT	10
3.3	INPUT AND OUTPUT LOSSES	11
3.4	MEASUREMENT UNCERTAINTY	11
4	TEST SITE (BUREAU VERITAS CONSUMER PRODUCTS SERVICES)	11
5	RF POWER OUT: §90.635, §2.1046	12
5.1	LIMIT.....	12
5.2	TEST METHOD	12
5.3	TEST RESULTS.....	13
5.3.1	DOWNLINK.....	14
5.3.1.1	GSM.....	15
5.3.1.2	EDGE.....	15
5.3.1.3	CDMA	16
5.3.1.4	WCDMA.....	16
5.3.1.5	LTE	17
5.3.2	UPLINK	17
5.4	SUMMARY TEST RESULT.....	17
6	OCCUPIED BANDWIDTH: §90.210, §2.1049	18
6.1	LIMIT.....	18
6.2	TEST METHOD	18
6.3	TEST RESULTS	19
6.3.1	DOWNLINK.....	19
6.3.1.1	GSM.....	20
6.3.1.2	EDGE.....	21
6.3.1.3	CDMA	22
6.3.1.4	WCDMA.....	23
6.3.1.5	LTE	24
6.3.2	26dB BANDWIDTH.....	25
6.3.2.1	GSM.....	25
6.3.2.2	EDGE.....	26
6.3.2.3	CDMA	27
6.3.2.4	WCDMA.....	28



6.3.2.5	LTE	29
6.3.3	UPLINK	30
6.4	SUMMARY TEST RESULT	30
7	SPURIOUS EMISSIONS AT ANTENNA TERMINALS: §90.210, §2.1051	31
7.1	LIMIT	31
7.2	TEST METHOD	31
7.3	TEST RESULTS	32
7.3.1	DOWNLINK	32
7.3.1.1	GSM	33
7.3.1.2	EDGE	33
7.3.1.3	CDMA	34
7.3.1.4	WCDMA	34
7.3.1.5	LTE	35
7.3.2	UPLINK	35
7.4	SUMMARY TEST RESULT	35
8	INTERMODULATION: §90.219, §2.1051	36
8.1	LIMIT	36
8.2	TEST METHOD	36
8.3	TEST RESULTS	37
8.3.1	DOWNLINK	37
8.3.1.1	GSM	38
8.3.1.2	EDGE	39
8.3.1.3	CDMA	40
8.3.1.4	WCDMA	41
8.3.1.5	LTE	42
8.3.2	UPLINK	43
8.4	SUMMARY TEST RESULT	43
9	EMISSION MASK: §90.691, §2.1051	44
9.1	LIMIT	44
9.2	TEST METHOD	45
9.3	TEST RESULTS	45
9.3.1	DOWNLINK	45
9.3.1.1	GSM	46
9.3.1.2	EDGE	47
9.3.1.3	CDMA	48
9.3.1.4	WCDMA	49
9.3.1.5	LTE	50
9.3.2	UPLINK	51
9.4	SUMMARY TEST RESULT	51
10	OUT OF BAND REJECTION	52
10.1	LIMIT	52
10.2	TEST METHOD	52
10.3	TEST RESULTS	52
10.3.1	DOWNLINK	53



10.3.2	UPLINK	53
10.4	SUMMARY TEST RESULT	53
11	NOISE.....	54
11.1	LIMIT	55
11.2	TEST METHOD	55
11.3	TEST RESULTS.....	55
11.3.1	DOWNLINK.....	55
11.3.2	UPLINK	55
11.4	SUMMARY TEST RESULT	55
12	FIELD STRENGTH OF SPURIOUS EMISSIONS: §90.210, §2.1053	56
12.1	LIMIT	59
12.2	TEST METHOD ANSI/TIA/EA-603-C.....	59
12.3	CLIMATIC VALUES IN THE LAB.....	59
12.4	TEST RESULTS.....	60
12.4.1	30 MHZ TO 1 GHZ DOWNLINK (BOTTOM – MIDDLE – TOP) SUBPART H.....	60
12.4.2	30 MHZ TO 1 GHZ DOWNLINK (MIDDLE OF ALL PATHS)	61
12.4.3	1 GHZ TO 18 GHZ DOWNLINK (BOTTOM – MIDDLE – TOP) SUBPART H.....	62
12.4.4	1 GHZ TO 18 GHZ DOWNLINK (MIDDLE OF ALL PATHS)	63
13	HISTORY	64



1 Test Results Summary

Name of Test	FCC Para. No.	FCC Method	FCC Spec.	Result
RF Power Output	90.635	2.1046	1000 Watts	Complies
Occupied Bandwidth	90.210	2.1049	Input/Output	Complies
Spurious Emissions at Antenna Terminals	90.210	2.1051	-13dBm	Complies
Intermodulation testing	90.219	KDB 935210 D02 v03r02	-13dBm	Complies
Emission Mask	90.691	2.1051	-13dBm	Complies
Frequency Stability	90.213	2.1055	1 ppm	NA
Out of Band Rejection	KDB 935210 D02 v03r02	KDB 935210 D03 v04	KDB 935210 D03 v04	Complies
Noise	90.219			Complies
Radiated Spurious emission	90.210	2.1053	-13dBm	Complies

Frequency stability is given by: The system gets an electrical analog signal from the BSS which is converted into an analog optical signal, transmitted by the optical links and then reconverted in the Remote Unit into an analog electrical signal. During this process happens no frequency change/modification, so input and output have same frequency what can be seen under clause "Occupied Bandwidth".



2 Equipment under test (E.U.T.)

2.1 Description

Kind of equipment	ION-M7P/85P/17EP/19P
Andrew Ident. Number	7714179-0002
Serial no.(SN)	15
Revision	00
Software version and ID	n. a.
Type of modulation and Designator	GSM (GXW) ☒ GSM EDGE (G7W) ☒ CDMA (F9W) ☒ W-CDMA (F9W) ☒ LTE (G7D) ☒
Frequency Translation	F1-F1 ☒ F1-F2 ☐ N/A ☐
Band Selection	Software ☐ Duplexer ☒ Full band ☐

2.1.1 Downlink

Pass band	Path 862 MHz – 894 MHz
Pass band under test	Path 862 MHz – 869 MHz
Max. composite output power based on one carrier per path (rated)	43 dBm = 20 W
System Gain*	10 dB @ Pout BTS of 33 dBm

*see 2.1.5

2.1.2 Uplink

Pass band	Path 817 MHz – 849 MHz
Maximum rated output power	n. a.
System Gain*	n.a.

*see 2.1.5

Note: The EUT does not transmit over the air in the uplink direction.



2.1.3 Description of EUT

CommScope's ION-M7P/85P/17EP/19P is a multi-band, multi-operator Remote Unit. It is used in conjunction with a Master Unit in the ION optical distribution system. This system transports up to 4 frequency bands simultaneously, providing a cost-effective solution for distributing capacity from one or more base stations.

This Test Report describes only the approval of the 800 MHz Path.

The ION-M7P/85P/17EP/19P Repeater system consists of one 700 MHz path, one 850 MHz path, one 1700/2100 MHz path and one 1900 MHz path with the intended use of simultaneous transmission.

The antenna(s) used with device must be fixed-mounted on permanent structures.

2.1.4 Block diagram of measurement reference points




figure 2.1.4-#1 Block diagram of measurement reference points

Remote Unit (RU) is the EUT

O/E Opticall/Electrical converter
MU Master Unit

Reference point A	MU	UL output,	DL input
Reference point B	Remote Unit	DL output,	UL input
Reference point Z	BTS	DL output,	UL input

Since a signal generator does not supply a good output signal with +33 or +43dBm, for the downlink measurement the MU Attenuation is not used.

That means for downlink measurements the signal generator is connected to measurement point A at the master optical / electrical converter and the analyzer to the measurement point B at the RU.

2.1.5 Downlink System Gain and Output Power

System optimized for BTS power (fixed value) Z	MU Attenuation (manual leveling)	Maximum rated input power at the MU OTRX (fixed value) A	RU Gain (fixed value) A to B	Maximum rated output power at RU Antenna port (fixed value) B
+33 dBm	30 dB	+3 dBm	40 dB	+43.0 dBm @ 1 carrier
System Gain Z to B	+10 dB			
+43 dBm	40 dB	+3 dBm	40 dB	+43.0 dBm @ 1 carrier
System Gain Z to B	0 dB			

table 2.1.5-#1 Equipment under test (E.U.T.) Description Downlink System Gain and Output Power



3 Test site (Andrew Buchdorf)

3.1 Test environment

All tests were performed under the following environmental conditions:

Condition	Minimum value	Maximum value
Barometric pressure	86 kPa	106 kPa
Temperature	15°C	30°C
Relative Humidity	20 %	75 %
Power supply range	±5% of rated voltages	

3.2 Test equipment

ANDREW Inv. No.	Test equipment	Type	Manufacturer	Serial No.	Calibration
9295	Network Analyzer	ZNB20	R&S	101540	11/16
9291	Spectrum Analyzer	FSV30	R&S	103090	06/16
9233	Signal Generator	SMBV100A	R&S	257777	06/16
8849	Signal Generator	SMU200A	R&S	101732	04/16
8671	Power Meter	E4418B	Agilent	GB39513094	06/16
8672	Power Sensor	E9300H	Agilent	US41090179	06/16
7306	Circulator	C25E-1FFF	AEROTEK	12580	CIU
7307	Circulator	C25E-1FFF	AEROTEK	12581	CIU
7408	RF-Cable	2,0m; N-N	Andrew	---	CIU
7409	RF-Cable	2,0m; N-N	Andrew	---	CIU
7410	RF-Cable	1,0m; N-N	Andrew	---	CIU
7411	RF-Cable	2,0m; N-N	Andrew	---	CIU
7373	RF-Cable	Multiflex141	Andrew	---	CIU
7374	RF-Cable	Multiflex141	Andrew	---	CIU
7437	RF-Cable	Multiflex141	Andrew	---	CIU
7438	RF-Cable	Multiflex141	Andrew	---	CIU
7439	RF-Cable	Multiflex141	Andrew	---	CIU
7443	RF-Cable	Multiflex141	Andrew	---	CIU
7444	RF-Cable	Multiflex141	Andrew	---	CIU
7445	RF-Cable	Multiflex141	Andrew	---	CIU
7446	RF-Cable	Multiflex141	Andrew	---	CIU
7447	RF-Cable	Multiflex141	Andrew	---	CIU
7448	RF-Cable	Multiflex141	Andrew	---	CIU
7449	RF-Cable	Multiflex141	Andrew	---	CIU
7450	RF-Cable	Multiflex141	Andrew	---	CIU
7440	RF-Cable	RG-223 0.8m	Andrew	---	CIU
7441	RF-Cable	RG-223 0.8m	Andrew	---	CIU
7453	RF-Cable	RG223 2m SMA.	Andrew	---	CIU
7454	RF-Cable	RG223 2m SMA.	Andrew	---	CIU
7455	RF-Cable	RG223 2m SMA.	Andrew	---	CIU
7144	Attenuator	2N-20dB	Inmet 64671	---	CIU
7336	Power Attenuator	768-20	Narda	---	CIU
7368	Matrix		COMMScope	---	weekly

CIU = Calibrate in use



3.3 Input and output losses

All recorded power levels should be referenced to the input and output connectors of the repeater, unless explicitly stated otherwise.

The test equipment used in this test has to be calibrated, so that the functionality is also checked.

All cables, attenuators, splitter, isolator, circulator and combiner etc. must be measured before testing and used for compensation during testing.

3.4 Measurement uncertainty

The extended measurement uncertainty corresponds to the measurement results from the standard measurement uncertainty multiplied by the coverage factor $k=2$. The true value is located in the corresponding interval with a probability of 95 %.

4 Test site (Bureau Veritas Consumer Products Services)

FCC Test site: 96997

See relevant dates under section 12.

5 RF Power Out: §90.635, §2.1046




figure 5-#1 Test setup: RF Power Out: §90.635, §2.1046

Measurement uncertainty	± 0,38 dB
Test equipment used	9291, 9233, 7444; 7321; 7144; 7454; 7453; 7336; 7449; 7368

5.1 Limit

Minimum standard:

§ 90.635 Limitations on power and antenna height.

(a) The effective radiated power and antenna height for base stations may not exceed 1 kilowatt (30 dBW) and 304 m. (1,000 ft.) above average terrain (AAT), respectively, or the equivalent thereof as determined from the Table. These are maximum values, and applicants will be required to justify power levels and antenna heights requested.

5.2 Test method

§ 2.1046 Measurements required: RF power output.

(a) For transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, power output shall be measured at the RF output terminals when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in § 2.1033(c)(8). The electrical characteristics of the radio frequency load attached to the output terminals when this test is made shall be stated.

(c) For measurements conducted pursuant to paragraphs (a) and (b) of this section, all calculations and methods used by the applicant for determining carrier power or peak envelope power, as appropriate, on the basis of measured power in the radio frequency load attached to the transmitter output terminals shall be shown. Under the test conditions specified, no components of the emission spectrum shall exceed the limits specified in the applicable rule parts as necessary for meeting occupied bandwidth or emission limitations



5.3 Test Results

Detector RMS.

Test signal GSM:

Signal waveform with GMSK modulation in all time slots according to 3GPP TS45.004

Test signal GSM EDGE:

Signal waveform with 8-PSK modulation in all time slots according to 3GPP TS45.004

Test signal CDMA:

Signal waveform according to table 6.2-1 of standard specification 3GPP2 C.p0051-0 v1.0 16.February 2006 pilot, sync, paging, 37 traffics, which is equal to the table 6.5.2.1 of 3GPP2 C.S0010-C v2.0 24.February 2006.

Test signal WCDMA:

Signal waveform according to Test Model 1 of standard specification 3GPP TS25.141. Signal modulated with a combination of PCCPCH, SCCPCH and Dedicated Physical Channels specified as test model 1 64 DPCH.

Test signal LTE:

Signal waveform according to Test Model 1.1, E-TM1.1, clause 6.1.1.1-1, table 6.1.1.1-1 of standard specification 3GPP TS 36.141 V9.3.0 (2010-03).

5.3.1 Downlink

Modulation	Measured at	Carrier /MHz	RBW VBW Span	RF Power (dBm)	RF Power (W)	Plot -
GSM	Middle	865.5 MHz	1MHz 3MHz 10MHz	43.0	20.0	5.3.1.1 #1
EDGE	Middle	865.5 MHz	1MHz 3MHz 10MHz	43.0	20.0	5.3.1.2 #1
CDMA	Middle	865.5 MHz	3MHz 10MHz 15MHz	43.0	20.0	5.3.1.3 #1
WCDMA	Middle	865.5 MHz	10MHz 10MHz 50MHz	42.5	17.8	5.3.1.4 #1
LTE	Middle	865.5 MHz	3MHz 10MHz 15MHz	43.0	20.0	5.3.1.5 #1
Maximum output power = 43.0 dBm = 20 W						
Limit Maximum output power (erp) = 1000 W						

table 5.3.1-#1 RF Power Out: §90.635, §2.1046 Test Results Downlink

The max RF Power out is 43 dBm, so the maximum antenna gain (x) can be calculated as follow:

Limit = 1000W (erp) = 60 dBm

Info: 1000W (erp) = 1640W (eirp)

$60 \text{ dBm} > 43 \text{ dBm} + x \rightarrow x = 60 \text{ dBm} - 43 \text{ dBm} = 17 \text{ dBd}$

$x \text{ dBi} = 17 \text{ dBd} + 2.15 = 19.15 \text{ dBi}$


=> The antenna that will be used for the complete system have to have a gain lower than 19.15 dBi, relative to a dipol.

Modulation	Pin / dBm (Ref. point A)
GSM	2.7
EDGE	2.9
CDMA	2.8
WCDMA	2.3
LTE	2.8

table 5.3.1-#2 RF Power Out: §90.635, §2.1046 Test Results Downlink Input power




5.3.1.1 GSM



plot 5.3.1.1-#1 RF Power Out: \$90.635, \$2.1046; Test Results; Downlink; GSM Middle


5.3.1.2 EDGE



plot 5.3.1.2-#1 RF Power Out: \$90.635, \$2.1046; Test Results; Downlink; EDGE Middle




5.3.1.3 CDMA



plot 5.3.1.3-#1 RF Power Out: \$90.635, \$2.1046; Test Results; Downlink; CDMA Middle


5.3.1.4 WCDMA



plot 5.3.1.4-#1 RF Power Out: \$90.635, \$2.1046; Test Results; Downlink; WCDMA Middle



5.3.1.5 LTE



Date: 24.MAR.2016 12:45:59

plot 5.3.1.5-#1 RF Power Out: \$90.635, \$2.1046; Test Results; Downlink; LTE Middle

5.3.2 Uplink


n.a.

Note: The EUT does not transmit over the air in the uplink direction.

5.4 Summary test result

Test result	complies, according the plots above
Tested by:	M. Leinfelder
Date:	24.03.2016

6 Occupied Bandwidth: §90.210, §2.1049



External Attenuator DL x dB = 20 dB
figure 6-#1 Test setup: Occupied Bandwidth: §90.210, §2.1049

Measurement uncertainty	± 0,38 dB
Test equipment used	9291, 9233, 7444; 7321; 7144; 7454; 7453; 7336; 7449; 7368

6.1 Limit

The spectral shape of the output should look similar to input for all modulations.

6.2 Test method

Para. No.2.1049

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured under the following conditions as applicable:



6.3 Test results

6.3.1 Downlink

Detector PK.


Modulation	Measured at	Carrier /MHz	RBW VBW Span	Occupied Bandwidth	Plot #
GSM	Middle	865.5 MHz	3 kHz 30 kHz 1 MHz	191.4 kHz	6.3.1.1 #1, #2
EDGE	Middle	865.5 MHz	3 kHz 30 kHz 1 MHz	193.4 kHz	6.3.1.2 #1, #2
CDMA	Middle	865.5 MHz	30 kHz 300 kHz 5 MHz	1.17 MHz	6.3.1.3 #1, #2
WCDMA	Middle	865.5 MHz	100 kHz 1 MHz 10 MHz	3.78 MHz	6.3.1.4 #1, #2
LTE	Middle	865.5 MHz	30 kHz 300 kHz 5 MHz	1.05 MHz	6.3.1.5 #1, #2

Modulation	Measured at	Carrier /MHz	RBW VBW Span	26dB Bandwidth	Plot #
GSM	Middle	865.5 MHz	3 kHz 30 kHz 1 MHz	317.3 kHz	6.3.2.1 #1, #2
EDGE	Middle	865.5 MHz	3 kHz 30 kHz 1 MHz	302.4 kHz	6.3.2.2 #1, #2
CDMA	Middle	865.5 MHz	30 kHz 300 kHz 5 MHz	1.42 MHz	6.3.2.3 #1, #2
WCDMA	Middle	865.5 MHz	100 kHz 1 MHz 10 MHz	4.69 MHz	6.3.2.4 #1, #2
LTE	Middle	865.5 MHz	30 kHz 300 kHz 5 MHz	1.3 MHz	6.3.2.5 #1, #2

table 6.3-#1 Occupied Bandwidth: §90.210, §2.1049 Test results




6.3.1.1 GSM



Date: 24.MAR.2016 12:42:22

plot 6.3.1.1-#1 Occupied Bandwidth: \$90.210, \$2.1049; Test results; Downlink; GSM Output




Date: 24.MAR.2016 12:42:45

plot 6.3.1.1-#2 Occupied Bandwidth: \$90.210, \$2.1049; Test results; Downlink; GSM Input




6.3.1.2 EDGE



Date: 24.MAR.2016 12:39:55

plot 6.3.1.2-#1 Occupied Bandwidth: \$90.210, \$2.1049; Test results; Downlink; EDGE Output




Date: 24.MAR.2016 12:40:19

plot 6.3.1.2-#2 Occupied Bandwidth: \$90.210, \$2.1049; Test results; Downlink; EDGE Input




BUREAU
VERITAS

6.3.1.3 CDMA




plot 6.3.1.3-#1 Occupied Bandwidth: §90.210, §2.1049; Test results; Downlink; CDMA Output




plot 6.3.1.3-#2 Occupied Bandwidth: §90.210, §2.1049; Test results; Downlink; CDMA Input



6.3.1.4 WCDMA



plot 6.3.1.4-#1 Occupied Bandwidth: \$90.210, \$2.1049; Test results; Downlink; WCDMA Output




plot 6.3.1.4-#2 Occupied Bandwidth: \$90.210, \$2.1049; Test results; Downlink; WCDMA Input




BUREAU
VERITAS

6.3.1.5 LTE




plot 6.3.1.5-#1 Occupied Bandwidth: \$90.210, \$2.1049; Test results; Downlink; LTE Output



plot 6.3.1.5-#2 Occupied Bandwidth: \$90.210, \$2.1049; Test results; Downlink; LTE Input




6.3.2 26dB Bandwidth
6.3.2.1 GSM



Date: 24.MAR.2016 12:42:33

plot 6.3.2.1-#1 Occupied Bandwidth: \$90.210, \$2.1049; Test results; 26dB Bandwidth; GSM Output




Date: 24.MAR.2016 12:42:56

plot 6.3.2.1-#2 Occupied Bandwidth: \$90.210, \$2.1049; Test results; 26dB Bandwidth; GSM Input


BUREAU
VERITAS

6.3.2.2 EDGE



Date: 24.MAR.2016 12:40:06

plot 6.3.2.2-#1 Occupied Bandwidth: \$90.210, \$2.1049; Test results; 26dB Bandwidth; EDGE Output




Date: 24.MAR.2016 12:40:30

plot 6.3.2.2-#2 Occupied Bandwidth: \$90.210, \$2.1049; Test results; 26dB Bandwidth; EDGE Input




6.3.2.3 CDMA



Date: 24.MAR.2016 12:35:53

plot 6.3.2.3-#1 Occupied Bandwidth: \$90.210, \$2.1049; Test results; 26dB Bandwidth; CDMA Output




Date: 24.MAR.2016 12:36:17

plot 6.3.2.3-#2 Occupied Bandwidth: \$90.210, \$2.1049; Test results; 26dB Bandwidth; CDMA Input




6.3.2.4 WCDMA



Date: 24.MAR.2016 12:48:36

plot 6.3.2.4-#1 Occupied Bandwidth: \$90.210, \$2.1049; Test results; 26dB Bandwidth; WCDMA Output




Date: 24.MAR.2016 12:48:59

plot 6.3.2.4-#2 Occupied Bandwidth: \$90.210, \$2.1049; Test results; 26dB Bandwidth; WCDMA Input




6.3.2.5 LTE



Date: 24.MAR.2016 12:46:27

plot 6.3.2.5-#1 Occupied Bandwidth: \$90.210, \$2.1049; Test results; 26dB Bandwidth; LTE Output



Date: 24.MAR.2016 12:46:51

plot 6.3.2.5-#2 Occupied Bandwidth: \$90.210, \$2.1049; Test results; 26dB Bandwidth; LTE Input



6.3.3 Uplink


n.a.

Note: The EUT does not transmit over the air in the uplink direction.

6.4 Summary test result

Test result	complies, according the plots above
Tested by:	M. Leinfelder
Date:	24.03.2016

7 Spurious Emissions at Antenna Terminals: §90.210, §2.1051



External Attenuator DL x dB = 20 dB

figure 7-#1 Test setup: Spurious Emissions at Antenna Terminals: §90.210, §2.1051

Measurement uncertainty	$\pm 0,54$ dB $\pm 1,2$ dB $\pm 1,5$ dB	9 kHz to 3 GHz 3 GHz to 7 GHz 7 GHz to 26 GHz
Test equipment used	9291, 9233, 7444; 7321; 7144; 7454; 7453; 7336; 7449; 7368	

7.1 Limit

MASK	Spurious Limit
A,B,C,G,H,I	-13dBm

7.2 Test method

Para. No 2.1051 Measurements required: Spurious emissions at antenna terminals.

The radio frequency voltage or powers generated within the equipment and appearing on a spurious frequency shall be checked at the equipment output terminals when properly loaded with a suitable artificial antenna. Curves or equivalent data shall show the magnitude of each harmonic and other spurious emission that can be detected when the equipment is operated under the conditions specified in § 2.1049 as appropriate. The magnitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be specified.

[39 FR 5919, Feb. 15, 1974. Redesignated and amended at 63 FR 36599, July 7, 1998]



7.3 Test results

7.3.1 Downlink

Detector: RMS.


Modulation	Carrier	RBW VBW Span	Max. level (dBm)	Plot -
GSM	865,5 MHz	1MHz 3MHz 30MHz – 10GHz	-20.8	7.3.1.1 #1
EDGE	865,5 MHz	1MHz 3MHz 30MHz – 10GHz	-20.9	7.3.1.2 #1
CDMA	865,5 MHz	1MHz 3MHz 30MHz – 10GHz	-20.6	7.3.1.3 #1
WCDMA	865,5 MHz	1MHz 3MHz 30MHz – 10GHz	-20.8	7.3.1.4 #1
LTE	865,5 MHz	1MHz 3MHz 30MHz – 10GHz	-20.9	7.3.1.5 #1

table 7.3-#1 Spurious Emissions at Antenna Terminals: §90.210, §2.1051 Test results

If the DUT used in MIMO configuration according to KDB 662911, the summed emission (MIMO Max. Level) is calculated (Max. Level) of the output port plus $10 \log(N_{ANT})$. With ($N_{ANT}=2$) the MIMO Max. Level (dBm) equals Max. Level (dBm) plus 3dB.




7.3.1.1 GSM



Date: 24.MAR.2016 12:43:03

plot 7.3.1.1-#1 Spurious Emissions at Antenna Terminals: §90.210, §2.1051; Test results; Downlink; GSM; carrier (865,5MHz) notched

7.3.1.2 EDGE




Date: 24.MAR.2016 12:40:36

plot 7.3.1.2-#1 Spurious Emissions at Antenna Terminals: §90.210, §2.1051; Test results; Downlink; EDGE; carrier (865,5MHz) notched




7.3.1.3 CDMA



Date: 24. MAR 2016 12:36:24

plot 7.3.1.3-#1 Spurious Emissions at Antenna Terminals: §90.210, §2.1051; Test results; Downlink; CDMA; carrier (865,5MHz) notched

7.3.1.4 WCDMA




Date: 24. MAR 2016 12:49:06

plot 7.3.1.4-#1 Spurious Emissions at Antenna Terminals: §90.210, §2.1051; Test results; Downlink; WCDMA; carrier (865,5MHz) notched



7.3.1.5 LTE



Date: 24.MAR.2016 12:46:58

plot 7.3.1.5-#1 Spurious Emissions at Antenna Terminals: §90.210, §2.1051; Test results; Downlink; LTE; carrier (865,5MHz) notched

7.3.2 Uplink


n.a.

Note: The EUT does not transmit over the air in the uplink direction.

7.4 Summary test result

Test result	complies, according the plots above
Tested by:	M. Leinfelder
Date:	24.03.2016

8 Intermodulation: §90.219, §2.1051



External Attenuator DL x dB = 20 dB
figure 8-#1 Test setup: Intermodulation: §90.219, §2.1051

Measurement uncertainty	± 0,54 dB ± 1,2 dB ± 1,5 dB	9 kHz to 3 GHz 3 GHz to 7 GHz 7 GHz to 26 GHz
Test equipment used	9291, 8849; 9233, 7444; 7321; 7326; 7144; 7454; 7453; 7336; 7449; 7368	

8.1 Limit

MASK	Spurious Limit
A,B,C,G,H,I	-13dBm

8.2 Test method

Para. No 2.1051 Measurements required: Spurious emissions at antenna terminals.

The radio frequency voltage or powers generated within the equipment and appearing on a spurious frequency shall be checked at the equipment output terminals when properly loaded with a suitable artificial antenna. Curves or equivalent data shall show the magnitude of each harmonic and other spurious emission that can be detected when the equipment is operated under the conditions specified in § 2.1049 as appropriate. The magnitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be specified.

[39 FR 5919, Feb. 15, 1974. Redesignated and amended at 63 FR 36599, July 7, 1998]



8.3 Test results


8.3.1 Downlink

Detector: RMS.

Modulation	Measured at Band Edge	Carriers	RBW VBW Span	Max. level (dBm)	Plot -
GSM	Lower Edge	862.4 MHz 862.6 MHz	3kHz 30kHz 2MHz	-35.3	8.3.1.1 #1
	Upper Edge	868.4 MHz 868.6 MHz			#2
EDGE	Lower Edge	862.4 MHz 862.6 MHz	3kHz 30kHz 2MHz	-36.5	8.3.1.2 #1
	Upper Edge	868.4 MHz 868.6 MHz			#2
CDMA	Lower Edge	862.775 MHz 864.025 MHz	30kHz 300kHz 6MHz	-24.5	8.3.1.3 #1
	Upper Edge	866.975 MHz 868.225 MHz			#2
WCDMA	Lower Edge	864.6 MHz 869.6 MHz	100kHz 1MHz 15MHz	-26.1	8.3.1.4 #1
	Upper Edge	861.4 MHz 866.4 MHz			#2
LTE	Lower Edge	862.7 MHz 864.1 MHz	30kHz 300kHz 6MHz	-26.5	8.3.1.5 #1
	Upper Edge	866.9 MHz 868.3 MHz			#2


table 8.3-#1 Intermodulation: §90.219, §2.1051 Test results

8.3.1.1 GSM



Date: 24 MAR 2016 12:43:34

plot 8.3.1.1-#1 Intermodulation: §90.219, §2.1051; Test results; Downlink; GSM Lower Band Edge




Date: 24.MAR.2016 12:43:50

plot 8.3.1.1-#2 Intermodulation: §90.219, §2.1051; Test results; Downlink; GSM Upper Band Edge




8.3.1.2 EDGE



Date: 24.MAR.2016 12:41:12

plot 8.3.1.2-#1 Intermodulation: §90.219, §2.1051; Test results; Downlink; EDGE Lower Band Edge




Date: 24.MAR.2016 12:41:28


plot 8.3.1.2-#2 Intermodulation: §90.219, §2.1051; Test results; Downlink; EDGE Upper Band Edge



8.3.1.3 CDMA




plot 8.3.1.3-#1 Intermodulation: §90.219, §2.1051; Test results; Downlink; CDMA Lower Band Edge




plot 8.3.1.3-#2 Intermodulation: §90.219, §2.1051; Test results; Downlink; CDMA Upper Band Edge



8.3.1.4 WCDMA




plot 8.3.1.4-#1 Intermodulation: §90.219, §2.1051; Test results; Downlink; WCDMA Lower Band Edge



plot 8.3.1.4-#2 Intermodulation: §90.219, §2.1051; Test results; Downlink; WCDMA Upper Band Edge




8.3.1.5 LTE



Date: 24.MAR.2016 12:47:24

plot 8.3.1.5-#1 Intermodulation: \$90.219, \$2.1051; Test results; Downlink; LTE Lower Band Edge



Date: 24.MAR.2016 12:47:41

plot 8.3.1.5-#2 Intermodulation: \$90.219, \$2.1051; Test results; Downlink; LTE Upper Band Edge



8.3.2 Uplink

n.a.


Note: The EUT does not transmit over the air in the uplink direction.

8.4 Summary test result

Test result	complies, according the plots above
Tested by:	M. Leinfelder
Date:	24.03.2016



9 Emission Mask: §90.691, §2.1051



External Attenuator DL x dB = 20 dB
figure 9-#1 Test setup: Emission Mask: §90.691, §2.1051

Measurement uncertainty	$\pm 0,54$ dB $\pm 1,2$ dB $\pm 1,5$ dB	9 kHz to 3 GHz 3 GHz to 7 GHz 7 GHz to 26 GHz
Test equipment used	9291, 9233, 7444; 7321; 7144; 7454; 7453; 7336; 7449; 7368	

9.1 Limit

§90.691 Emission mask requirements for EA-based systems.

(a) Out-of-band emission requirement shall apply only to the “outer” channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:

(1) For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $116 \text{ Log}_{10}(f/6.1)$ decibels or $50 + 10 \text{ Log}_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.

(2) For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \text{ Log}_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

(b) When an emission outside of the authorized bandwidth causes harmful interference, the Commission may, at its discretion, require greater attenuation than specified in this section.



9.2 Test method

Para. No 2.1051 Measurements required: Spurious emissions at antenna terminals.

The radio frequency voltage or powers generated within the equipment and appearing on a spurious frequency shall be checked at the equipment output terminals when properly loaded with a suitable artificial antenna. Curves or equivalent data shall show the magnitude of each harmonic and other spurious emission that can be detected when the equipment is operated under the conditions specified in § 2.1049 as appropriate. The magnitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be specified.

[39 FR 5919, Feb. 15, 1974. Redesignated and amended at 63 FR 36599, July 7, 1998]

9.3 Test results

9.3.1 Downlink


Detector: RMS

Modulation	Measured at Band Edge	Carriers	RBW VBW Span	Limit fail / pass	Plot -
GSM	Lower Edge	862.4 MHz	3kHz 30kHz 2MHz	pass	9.3.1.1 #1
	Upper Edge	868.6 MHz			#2
EDGE	Lower Edge	862.4 MHz	3kHz 30kHz 2MHz	pass	9.3.1.2 #1
	Upper Edge	868.6 MHz			#2
CDMA	Lower Edge	862.775 MHz	30kHz 300kHz 6MHz	pass	9.3.1.3 #1
	Upper Edge	868.225 MHz			#2
WCDMA	Lower Edge	864.6 MHz	100kHz 1MHz 15MHz	pass	9.3.1.4 #1
	Upper Edge	866.4 MHz			#2
LTE	Lower Edge	862.7 MHz	30kHz 300kHz 6MHz	pass	9.3.1.5 #1
	Upper Edge	868.3 MHz			#2

table 9.3-#1 Emission Mask: §90.691, §2.1051 Test results <1MHz from Band Edge




9.3.1.1 GSM



Date: 29.MAR.2016 10:25:09

plot 9.3.1.1-#1 Emission Mask: §90.691, §2.1051; Test results; Downlink; GSM Lower Band Edge




Date: 29.MAR.2016 10:32:18


plot 9.3.1.1-#2 Emission Mask: §90.691, §2.1051; Test results; Downlink; GSM Upper Band Edge



9.3.1.2 EDGE




plot 9.3.1.2-#1 Emission Mask: §90.691, §2.1051; Test results; Downlink; EDGE Lower Band Edge



plot 9.3.1.2-#2 Emission Mask: §90.691, §2.1051; Test results; Downlink; EDGE Upper Band Edge




9.3.1.3 CDMA



Date: 29.MAR.2016 11:08:52

plot 9.3.1.3-#1 Emission Mask: §90.691, §2.1051; Test results; Downlink; CDMA Lower Band Edge




Date: 29.MAR.2016 11:35:54

plot 9.3.1.3-#2 Emission Mask: §90.691, §2.1051; Test results; Downlink; CDMA Upper Band Edge




9.3.1.4 WCDMA



Date: 29.MAR.2016 11:51:07

plot 9.3.1.4-#1 Emission Mask: §90.691, §2.1051; Test results; Downlink; WCDMA Lower Band Edge




Date: 29.MAR.2016 11:52:48

plot 9.3.1.4-#2 Emission Mask: §90.691, §2.1051; Test results; Downlink; WCDMA Upper Band Edge



9.3.1.5 LTE



Date: 29.MAR.2016 11:39:54

plot 9.3.1.5-#1 Emission Mask: §90.691, §2.1051; Test results; Downlink; LTE Lower Band Edge



Date: 29.MAR.2016 11:38:41

plot 9.3.1.5-#2 Emission Mask: §90.691, §2.1051; Test results; Downlink; LTE Upper Band Edge



9.3.2 Uplink


n.a.

Note: The EUT does not transmit over the air in the uplink direction.

9.4 Summary test result

Test result	complies, according the plots above
Tested by:	M. Leinfelder
Date:	29.03.2016

10 Out of Band Rejection



External Attenuator DL x dB = 20 dB
figure 10-#1 Test setup: Out of Band Rejection

Measurement uncertainty	± 0,38 dB
Test equipment used	9291, 9233, 7444; 7321; 7144; 7454; 7453; 7336; 7449; 7368

10.1 Limit

KDB 935210 D02 v03r02

Test for rejection of out of band signals. Filter frequency response plots are acceptable.

10.2 Test method


935210 D03 v04

7.1 Authorized frequency band verification test

10.3 Test results

Detector Peak max hold

10.3.1 Downlink



Date: 24.MAR.2016 15:14:19

plot 10.3.1-#1 Out of Band Rejection; Test results; Downlink;

10.3.2 Uplink


n.a.

Note: The EUT does not transmit over the air in the uplink direction.

10.4 Summary test result

Test result	complies, according the plots above
Tested by:	M. Leinfelder
Date:	24.03.2016

11 Noise



External Attenuator DL x dB = 20 dB
figure 11-#1 Test setup: Noise

Measurement uncertainty	± 0,38 dB
Test equipment used	9291, 7321; 7144; 7454; 7453; 7336; 7449; 7368

- The noise power at the output of a RF 2-port is dependent on noise figure NF and gain G; i.e a high NF does not mean necessarily high noise power at the output;
- FCC limits the noise figure NF of a signal booster to max. 9 dB (also in DL)
- FCC defines: “signal boosters” as all manners of amplifiers, repeaters, boosters, *distributed antenna systems* and in-building radiation that serve to amplify signals between a device and a wireless network “;
- Noise figure NF is a useful and common manner for the characterization of a noisy RF 2-port;
- The DUT (DAS) uses also an optical medium (fiber) for signal transport (i.e. not solely RF lines / waveguides); after the photodiode we clearly have a RF 2-port (output photodiode to output remote unit);

→ The DUT is **attenuating** till the position right after the photodiode; only from the position right after the photodiode to the output of the remote the DUT is **amplifying** (this chain of RF components is the only complete and cohesive chain with predominantly **amplifying** stages (including the output port) (output port shall be included, since noise power at the output is of interest));

→ above mentioned FCC definition of signal boosters (“serve to amplify signals”) + definition of “noise figure” for RF 2-ports entail to set the reference planes for determining NF of the DL at the position right after the photodiode and the output of the remote unit;

This means that NF of the DUT in DL has to be determined between these two reference planes (NF of the amplification stages between output of the photodiode and output of the remote unit);

This noise figure is significantly below 9 dB!

To verify this fact, it would be necessary to carry out a second NF measurement with a reference remote OTRx, containing only the photodiode.

Knowing both noise figures (complete DUT + reference remote OTRx), NF of the required amplification stages can be calculated.

Another way to get the NF of the required amplification stages, is to accept line up calculation.

This should be acceptable, since NF of the amplification stages is significant lower than 9 dB.

In addition to that, the output noise level, which is crucial, was measured and is below the limit.

11.1 Limit


§90.219 (d) (6) (ii) In general, the ERP of noise within the passband should not exceed -43 dBm in 10 kHz measurement bandwidth.

11.2 Test method

KDB 935210 D03 v04 7.7

11.3 Test results

11.3.1 Downlink



Date: 29.MAR.2016 13:34:19

plot 11.3.1-#1 Noise; Test results; Downlink;

11.3.2 Uplink

n.a.

Note: The EUT does not transmit over the air in the uplink direction.


11.4 Summary test result

Test result	complies, according the plots above
Tested by:	M. Leinfelder
Date:	29.03.2016


12 Field Strength of Spurious Emissions: §90.210, §2.1053



picture 8.1: label (EUT)



picture 8.3: Test setup: Field Strength Emission 30 M – 1 GHz @10m in the SAC



picture 8.4: Test setup: Field Strength Emission 1 – 18 GHz @3m in the SAC

This clause specifies requirements for the measurement of radiated emission.

Frequency range	Distance: EUT <-> antenna / location	Limit	Test method
30 MHz – 1 GHz	10 metres / SAC	FCC 47 CFR Part §90.210	TIA/EIA-603-C:2004
1 GHz – 18 GHz	3 metres / SAC	IC RSS-131 sec. 4.4	

Test equipment used:

Designation	Type	Manufacturer	Invent.-no.	Cal.-date	due Cal.-date	used
EMI test receiver	ESU40	Rohde & Schwarz	E2025	25.02.2016	25.02.2017	X
Antenna	CBL 6111	Chase	K1026	12.02.2016	12.02.2017	X
RF Cable	RG214	Frankonia	K1121	16.04.2015	16.04.2017	X
Antenna	HL 025	R&S	K1114	09.02.2016	09.02.2017	X
Preamplifier	AFS4-00102000	Miteq	K838	17.06.2015	17.06.2016	X
RF Cable	Sucoflex 100	Suhner	K1760	04.08.2015	04.08.2016	X
Antenna	JXTXLB-42-25-C-KF	A-Info	K1175	09.03.2015	09.03.2017	X

The REMI version 2.135 has been used to maximize radiated emission from the EUT with regards to ANSI C63.4:2009.

Test set-up:

Test location: SAC
 Both, the Fully Anechoic Chamber (FAC) and the Semi Anechoic Chamber (SAC) fulfil the requirements of ANSI C63.4 and CISPR 16-1-4 with regards to NSA and SVSWR.

Test Voltage: 110V / 60 Hz

Type of EUT: Wall mounted

Measurement uncertainty:

Measurement uncertainty expanded (95% or K=2)	± 4,7 dB for ANSI C63.4 measurement ± 0,5 dB for TIA-603 measurement
--	---

12.1 Limit

Para. No.90.210

MASK	Spurious Limit
A,B,C,G,H,I	-13dBm

The limit is -13dBm (e.i.r.p).

12.2 Test method ANSI/TIA/EA-603-C


Measurement procedure. TIA-603-C

The antenna substitution method is used to determine the equivalent radiated power at spurious frequencies. The spurious emissions are measured at a distance of 3 meters. The EUT is then replaced with a reference substitution antenna with a known gain referenced to a dipole. This antenna is fed with a signal at the spurious frequency. The level of the signal is adjusted to repeat the previously measured level. The resulting eirp is the signal level fed to the reference antenna corrected for gain referenced to an isotropic dipole (see Figure 7.2).

From KDB (AMPLIFIER, BOOSTER, AND REPEATER REMINDER SHEET):
Radiated spurs (enclosure) – Use of CW signal (low, mid. and high freq.) is acceptable rather than all modulations.

The maximum RFI field strength was determined during the measurement by rotating the turntable (± 180 degrees) and varying the height of the receive antenna ($h = 1 \dots 4$ m) as like defined in ANSI C63.4. A measurement receiver has been used with a RBW 120 kHz up to 1 GHz and 1 MHz above 1 GHz. Steps with during pre measurement was half the RBW.

Both, the Fully Anechoic Chamber (FAC) and the Semi Anechoic Chamber (SAC) fulfil the requirements of ANSI C63.4 and CISPR 16-1-4 with regards to NSA and SVSWR.



picture 8.3: Substitution method

12.3 Climatic values in the lab

Temperature: 20°
Relative Humidity: 45%
Air-pressure: 1009hPa




12.4 Test results


12.4.1 30 MHz to 1 GHz Downlink (Bottom – Middle – Top) Subpart H

B/M/T: 862 MHz/ 865,5 MHz/ 869 MHz

Vertikal



Horizontal




The RF output power is terminated.




12.4.2 30 MHz to 1 GHz Downlink (Middle of all paths)

F1: 746 MHz; F2: 869 MHz; F3: 1962.5 MHz; F4: 2145 MHz

Vertikal



Horizontal




The RF output power is terminated.




12.4.3 1 GHz to 18 GHz Downlink (Bottom – Middle – Top) Subpart H

B/M/T: 862 MHz/ 865,5 MHz/ 869 MHz

Vertikal



Horizontal




The RF output power is terminated.


12.4.4 1 GHz to 18 GHz Downlink (Middle of all paths)

F1: 746 MHz; F2: 869 MHz; F3: 1962.5 MHz; F4: 2145 MHz

Vertikal



Horizontal



The RF output power is terminated.

Za / 26.04.2016

The radiated spurious emission measurements have been passed!



13 History

Revision	Modification	Date	Name
01.00	Initial Test report	29.04.2016	Tom Zahlmann

***** End of test report *****