

Manufacturer: Andrew Wireless Systems

Model: Radio Module L2 B66

FCC ID: XS5-RML2B66

IC: 2237E-RML2B66

47 CFR 1.1310(e)(1) Maximum Permissible Exposure (MPE) - Limits for General Population/Uncontrolled Exposure

Frequency (f)	Output power (P)	Antenna Gain (G)	Combiner Loss	MIMO Factor	Duty Cycle (DC)	EIRP ¹	EIRP	Distance (R)	Power Density (PD) ²	Power Density Limit	Margin
MHz	dBm	dBi	dB	dB	%	dBm	mW	cm	mW/cm ²	mW/cm ²	dB
2112,5	24,0	9,0	-3,00	3,00	100,0	33,0	1995	20	0,397	1	4,0

Canada RSS-102 Issue 5 (4. Exposure Limits) Table 4: RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)

Frequency (f)	Output power (P)	Antenna Gain (G)	Combiner Loss	MIMO Factor	Duty Cycle (DC)	EIRP ¹	EIRP	Distance (R)	Power Density (PD) ²	Power Density Limit	Margin	Exemption Limit
MHz	dBm	dBi	dB	dB	%	dBm	W	m	W/m ²	W/m ²	dB	W
2112,5	24,0	9,0	-3,00	3,00	100,0	33,0	2,00	0,2	3,969	4,901	0,9	2,45

¹EIRP_{dBm} = P + G + Combiner Loss + MIMO Factor + 10 Log (DC/100)

²PD = EIRP/(4πR²)