



Compliance Testing, LLC

Previously Flom Test Lab

EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268

fax: (480) 926-3598

<http://www.ComplianceTesting.com>

info@ComplianceTesting.com

Test Report

Prepared for: Clear RF

Model: WRE5500

Description: Five-Band Bi-Directional Cellular Amplifier

Serial Number: S2171700

FCC ID: XS7WRE5500

To

FCC Part 1.1310

Date of Issue: February 28, 2017

On the behalf of the applicant:

Clear RF
12825 E. Mirabeau Parkway
Suite 104
Spokane Valley, WA 99216

Attention of:

Shawn Taylor, Chief Operating Officer
Ph: (509)321-9520
Email: shawn.taylor@servatron.com

Prepared By
Compliance Testing, LLC
1724 S. Nevada Way
Mesa, AZ 85204
(480) 926-3100 phone / (480) 926-3598 fax
www.compliancetesting.com
Project No: p16a0013

Greg Corbin
Project Test Engineer

This report may not be reproduced, except in full, without written permission from Compliance Testing
All results contained herein relate only to the sample tested



Test Report Revision History

Revision	Date	Revised By	Reason for Revision
1.0	February 20, 2017	Greg Corbin	Original Document
2.0	February 28, 2017	Greg Corbin	Updated description on page 5 to include mobile applications

ILAC / A2LA

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer joint ISO-ILAC-IAF Communiqué dated January 2009)

The tests results contained within this test report all fall within our scope of accreditation, unless below

Please refer to <http://www.compliancetesting.com/labscope.html> for current scope of accreditation.

Testing Certificate Number: **2152.01**



FCC Site Reg. #349717

IC Site Reg. #2044A-2

Non-accredited tests contained in this report:

N/A

EUT Description

Model: WRE5500

Description: Five-Band Bi-Directional Cellular Amplifier

Firmware: 1.04

Software: N/A

Serial Number: S2171700

Additional Information:

The EUT is a Direct Connect bi-directional amplifier for the boosting of cellular phone signals and data communication devices.

Frequency Band (MHz)					
Uplink	698 - 716	776 – 787 (IC, 777 – 787)	824 - 849	1850 - 1915	1710 – 1755
Downlink	728 - 746	746 – 757 (IC, 746 – 756)	869 - 894	1930 - 1995	2110 - 2155

MPE calculations were performed using the highest measured output power +20% for each band and using an antenna with 3.0 dBi gain.



Average Power calculations

Average Power = Peak Power * duty-cycle%

Tuned Frequency (MHz)	Conducted Peak Output Power (mW)	Duty Cycle (%)	Average Power (mW)
703.19	0.123	100	0.123
781.5	0.074	100	0.074
840.81	0.095	100	0.095
1732.5	0.065	100	0.065
1879.05	0.058	100	0.058



MPE Evaluation

This is a Direct Connect device that is used in both fixed and mobile applications used in Uncontrolled Exposure environment.

Limits Uncontrolled Exposure 47 CFR 1.1310 Table 1, (B)

0.3-1.234 MHz:	Limit [mW/cm ²] = 100
1.34-30 MHz:	Limit [mW/cm ²] = (180/f ²)
30-300 MHz:	Limit [mW/cm ²] = 0.2
300-1500 MHz:	Limit [mW/cm ²] = f/1500
1500-100,000 MHz	Limit [mW/cm ²] = 1.0

Test Data

Test Frequency, MHz	703.19
Power, Conducted, mW (P)	0.148 (measured power + 20%)
Antenna Gain Isotropic	3.0 dBi
Antenna Gain Numeric (G)	2.0
Antenna Type	Omni directional
Distance (R)	20 cm

$S = \frac{P * G}{4\pi r^2}$
Power Density (S) mw/cm ²
0.000059 mw/cm ²

Power Density (S) = 0.000059 mw/cm ²
Limit =(from above table) = 0.469 mw/cm ²

The EUT is below the MPE limit at 20 cm.

Test Frequency, MHz	781.5
Power, Conducted, mW (P)	0.088 (measured power + 20%)
Antenna Gain Isotropic	3.0 dBi
Antenna Gain Numeric (G)	2.0
Antenna Type	Omni directional
Distance (R)	20 cm

$S = \frac{P * G}{4\pi r^2}$
Power Density (S) mw/cm ²
0.000035 mw/cm ²

Power Density (S) =0.000035 mw/cm ²
Limit =(from above table) = 0.521 mw/cm ²

The EUT is below the MPE limit at 20 cm.



Test Frequency, MHz	840.81
Power, Conducted, mW (P)	0.114 (measured power + 20%)
Antenna Gain Isotropic	3.0 dBi
Antenna Gain Numeric (G)	2.0
Antenna Type	Omni directional
Distance (R)	20 cm

$S = \frac{P * G}{4\pi r^2}$
Power Density (S) mw/cm ²
0.000045 mw/cm ²

Power Density (S) = 0.000045 mw/cm ²
Limit =(from above table) = 0.469 mw/cm ²

The EUT is below the MPE limit at 20 cm.

Test Frequency, MHz	1732.5
Power, Conducted, mW (P)	0.078 (measured power + 20%)
Antenna Gain Isotropic	3.0 dBi
Antenna Gain Numeric (G)	2.0
Antenna Type	Omni directional
Distance (R)	20 cm

$S = \frac{P * G}{4\pi r^2}$
Power Density (S) mw/cm ²
0.000031 mw/cm ²

Power Density (S) =0.000031 mw/cm ²
Limit =(from above table) = 1.0 mw/cm ²

The EUT is below the MPE limit at 20 cm.



Test Frequency, MHz	1879.05
Power, Conducted, mW (P)	0.070 (measured power + 20%)
Antenna Gain Isotropic	3.0 dBi
Antenna Gain Numeric (G)	2.0
Antenna Type	Omni directional
Distance (R)	20 cm

$S = \frac{P * G}{4\pi r^2}$
Power Density (S) mw/cm ²
0.000028 mw/cm ²

Power Density (S) = 0.000028 mw/cm ²
Limit =(from above table) = 1.0 mw/cm ²

The EUT is below the MPE limit at 20 cm.

END OF TEST REPORT