

Appendix for the Report

Dosimetric Assessment of the Prodigi Tablet PGI-100 from HumanWare (FCC ID: 0019188978PGITAB) (IC: 8670A-PGITAB)

According to the FCC Requirements SAR Distribution Plots

May 20, 2014

IMST GmbH

Carl-Friedrich-Gauß-Str. 2 - 4
D-47475 Kamp-Lintfort

Customer

HumanWare
445, Rue Du Parc-Industriel
Longueuil, (Quebec)
Canada J4H 3V7

The test results only relate to the items tested.

This report shall not be reproduced except in full without the written approval of the testing laboratory.

1 SAR Distribution Plots

Test Laboratory: Imst GmbH, DASY Yellow (II); File Name: [PGI-100_469_ywhm_dspl_ch6_b.da4](#)

DUT: Humanware Prodigy; Type: PGI-100; Serial: 109000002469

Program Name: IEEE 802.11 b

Communication System: WLAN 2450; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2437$ MHz; $\sigma = 1.98$ mho/m; $\epsilon_r = 52.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3860; ConvF(7.47, 7.47, 7.47); Calibrated: 29.07.2013
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 23.09.2013
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Body Worn/Area Scan (12x11x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.067 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.19 V/m; Power Drift = -0.169 dB

Peak SAR (extrapolated) = 0.152 W/kg

SAR(1 g) = 0.054 mW/g; SAR(10 g) = 0.020 mW/g

Maximum value of SAR (measured) = 0.071 mW/g




Fig. 1: SAR distribution for IEEE 802.11 b, channel 6, front side, gap = 0 mm (May 05, 2014)

Test Laboratory: Imst GmbH, DASY Yellow (II); File Name: [PGI-100_469_ywhm_back_ch6_b.da4](#)

DUT: Humanware Prodigy; Type: PGI-100; Serial: 109000002469

Program Name: IEEE 802.11 b

Communication System: WLAN 2450; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2437$ MHz; $\sigma = 1.98$ mho/m; $\epsilon_r = 52.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3860; ConvF(7.47, 7.47, 7.47); Calibrated: 29.07.2013
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 23.09.2013
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Body Worn/Area Scan (12x11x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (measured) = 0.045 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 4.43 V/m; Power Drift = 0.048 dB

Peak SAR (extrapolated) = 0.086 W/kg

SAR(1 g) = 0.035 mW/g; SAR(10 g) = 0.012 mW/g




Fig. 2: SAR distribution for IEEE 802.11 b, channel 6, back side, gap = 0 mm (May 05, 2014)

Test Laboratory: Imst GmbH, DASY Yellow (II); File Name: [PGI-100_469_ywhm_top_ch6_b.da4](#)

DUT: Humanware Prodigy; Type: PGI-100; Serial: 109000002469

Program Name: IEEE 802.11 b

Communication System: WLAN 2450; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2437$ MHz; $\sigma = 1.98$ mho/m; $\epsilon_r = 52.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3860; ConvF(7.47, 7.47, 7.47); Calibrated: 29.07.2013
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 23.09.2013
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Body Worn/Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.017 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.77 V/m; Power Drift = -0.122 dB

Peak SAR (extrapolated) = 0.108 W/kg

SAR(1 g) = 0.023 mW/g; SAR(10 g) = 0.00587 mW/g

Maximum value of SAR (measured) = 0.026 mW/g




Fig. 3: SAR distribution for IEEE 802.11 b, channel 6, top edge, gap = 0 mm (May 05, 2014)

Test Laboratory: Imst GmbH, DASY Yellow (II); File Name: [PGI-100_469_ywhm_right_ch6_b.da4](#)

DUT: Humanware Prodigy; Type: PGI-100; Serial: 109000002469

Program Name: IEEE 802.11 b

Communication System: WLAN 2450; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2437$ MHz; $\sigma = 1.98$ mho/m; $\epsilon_r = 52.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3860; ConvF(7.47, 7.47, 7.47); Calibrated: 29.07.2013
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 23.09.2013
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Body Worn/Area Scan (7x12x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.061 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 1.71 V/m; Power Drift = 0.090 dB

Peak SAR (extrapolated) = 0.313 W/kg

SAR(1 g) = 0.103 mW/g; SAR(10 g) = 0.026 mW/g

Maximum value of SAR (measured) = 0.138 mW/g




Fig. 4: SAR distribution for IEEE 802.11 b, channel 6, right edge, gap = 0 mm (May 05, 2014)

Test Laboratory: Imst GmbH, DASY Yellow (II); File Name: [PGI-100_469_ywhm_bottom_ch6_b.da4](#)

DUT: Humanware Prodigy; Type: PGI-100; Serial: 109000002469

Program Name: IEEE 802.11 b

Communication System: WLAN 2450; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2437$ MHz; $\sigma = 1.98$ mho/m; $\epsilon_r = 52.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3860; ConvF(7.47, 7.47, 7.47); Calibrated: 29.07.2013
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 23.09.2013
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Body Worn/Area Scan (7x9x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.006 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 1.33 V/m; Power Drift = -5.66 dB

Peak SAR (extrapolated) = 0.002 W/kg

SAR(1 g) = 8.72e-005 mW/g; SAR(10 g) = 1.11e-005 mW/g




Fig. 5: SAR distribution for IEEE 802.11 b, channel 6, bottom edge, gap = 0 mm (May 05, 2014)