

TEST REPORT



DT&C Co., Ltd.

42, Yurim-ro, 154Beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea, 17042
Tel : 031-321-2664, Fax : 031-321-1664

1. Report No : DRTFCC1708-0161
2. Customer
 - Name : TIT ENG Co.,Ltd.
 - Address : 7 Floor, Shin-do B/D. 10, Garak-dong, Songpa-Gu, Seoul, South Korea, 138-160
3. Use of Report : FCC Original Grant
4. Product Name / Model Name : CARD LAMINATOR / NL200
FCC ID : XTNNL200
5. Test Method Used : ANSI C63.10-2013
Test Specification : FCC Part 15.225
6. Date of Test : 2017.07.24 ~ 2017.08.14
7. Testing Environment : Refer to appended test report.
8. Test Result : Refer to the attached test result.

Affirmation	Tested by	Technical Manager
	Name : SunGeun Lee (Signature)	Name : GeunKi Son (Signature)

The test results presented in this test report are limited only to the sample supplied by applicant and the use of this test report is inhibited other than its purpose. This test report shall not be reproduced except in full, without the written approval of DT&C Co., Ltd.

2017 . 08 . 25 .

DT&C Co., Ltd.

If this report is required to confirmation of authenticity, please contact to report@dtnc.net

Test Report Version

Test Report No.	Date	Description
DRTFCC1708-0161	Aug. 25, 2017	Initial issue

CONTENTS

1. General Information.....	4
1.1. Testing Laboratory.....	4
1.2. Testing Environment.....	4
1.3. Measurement Uncertainty	4
1.4. Details of Applicant.....	5
1.5. Description of EUT	5
1.6. EUT CAPABILITIES	5
2. Information about test items.....	6
2.1 Test mode.....	6
2.2 Tested frequency	6
2.3 EMI Suppression Device(s)/Modifications	6
3. Antenna requirements.....	6
4. Test report	7
4.1 Summary of tests	7
4.2 Transmitter requirements.....	8
4.2.1 20dB bandwidth	8
4.2.2 In-band emissions.....	9
4.2.4 Out-of-band emissions	11
4.2.5 Frequency Stability.....	13
4.2.6 AC Line Conducted Emissions	14
APPENDIX	17

1. General Information

1.1. Testing Laboratory

DT&C Co., Ltd.

The 3 m test site and conducted measurement facility used to collect the radiated data are located at the 42, Yurim-ro, 154beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea 17042. The site is constructed in conformance with the requirements.

- FCC MRA Accredited Test Firm No. : KR0034

www.dtc.net

Telephone : + 82-31-321-2664

FAX : + 82-31-321-1664

1.2. Testing Environment

Ambient Condition

▪ Temperature +23 ~ +25 °C

▪ Relative Humidity 42 % ~ 48 %

1.3. Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with requirements of ANSI C 63.4-2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence.

Parameter	Measurement uncertainty
AC conducted emission	± 2.4 dB (The confidence level is about 95 %, $k = 2$)
Radiated Disturbance (Below 1 GHz)	± 5.1 dB (The confidence level is about 95 %, $k = 2$)

1.4. Details of Applicant

Applicant : TIT ENG Co.,Ltd.
Address : 7 Floor, Shin-do B/D. 10, Garak-dong, Songpa-Gu, Seoul, South Korea, 138-160
Contact person : Sang-Joong Lee

1.5. Description of EUT

FCC Equipment Class	Low Power Communications Device Transmitter(DXX)
EUT	CARD LAMINATOR
Model Name	NL200
Add Model Name	NL200U, NL200L, NL200H, L201-D, L201-S, DNALAM2, DNALAM, Jupiter
Serial Number	Identical prototype
Power Supply	AC 120 V
Frequency Band	13.558 MHz
Modulation Type	ASK
Channel(s)	1
Antenna type	Loop Antenna

1.6. EUT CAPABILITIES

This ETU contains the following capabilities: NFC

2. Information about test items

2.1 Test mode

Test mode 1	Continuous transmitting mode (ANT1)
Test mode 2	Continuous transmitting mode (ANT2)

2.2 Tested frequency

Channel	TX Frequency(MHz)
Lowest	13.558
Middle	-
Highest	-

2.3 EMI Suppression Device(s)/Modifications

EMI suppression device(s) added and/or modifications made during testing
→ None

3. Antenna requirements

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

The antenna is permanently printed on PCB. (Refer to Internal photo file.)

Therefore this E.U.T Complies with the requirement of §15.203

4. Test report

4.1 Summary of tests

FCC part section(s)	RSS section(s)	Parameter	Limit	Test condition	Status Note 1
2.1049	-	20 dB Bandwidth	-	Radiated	C ^{Note 3}
-	RSS-Gen [6.6]	Occupied Bandwidth	-		NA
15.225 (a)	RSS-210 [B6(a)]	In-Band Emissions	15,848 $\mu\text{V/m}$ @ 30 m 13.553 – 13.567 MHz		C ^{Note 2}
15.225 (b)	RSS-210 [B6(b)]	In-Band Emissions	334 $\mu\text{V/m}$ @ 30 m 13.410 – 13.553 MHz 13.567 – 13.710 MHz		C ^{Note 2}
15.225 (c)	RSS-210 [B6(c)]	In-Band Emissions	106 $\mu\text{V/m}$ @ 30 m 13.110 – 13.410 MHz 13.710 – 14.010 MHz		C ^{Note 2}
15.225 (d) 15.209	RSS-210 [B6(d)] RSS-GEN [8.9]	Out-of Band Emissions	Emissions outside of the specified band (13.110-14.010 MHz) must meet the radiated limits detailed in 15.209		C ^{Note 2}
15.225 (e)	RSS-210 [B6]	Frequency Stability	± 0.01 % of operating frequency	Temp & Humid Test Chamber	C ^{Note 3}
15.207	RSS-Gen [8.8]	AC Conducted Emissions	FCC Part 15.207	AC Line Conducted	C ^{Note 3}
15.203	-	Antenna Requirements	FCC Part 15.203	-	C

Note 1: **C**=Comply **NC**=Not Comply **NT**=Not Tested **NA**=Not Applicable

Note 2: For radiated emission tests below 30 MHz were performed on semi-anechoic chamber which is correlated with OATS.

Note3: We have done all TX test cases and attached the test result ANT2 mode since ANT2 is the worst case.

4.2 Transmitter requirements

4.2.1 20dB bandwidth


- Procedure:

The 20 dB Bandwidth is measured with a spectrum analyzer connected via a receive antenna placed near the EUT while the EUT is operating in transmission mode.

And spectrum analyzer setting use following test procedure of **ANCSI C63.10-2013 – Section 6.9.2.**

1. Center frequency = EUT channel center frequency
2. Span = 2 ~ 5 times the OBW
3. RBW = 1 % ~ 5 % OBW
4. VBW $\geq 3 \times$ RBW
5. Detector = Peak
6. Trace = Max hold
7. The trace was allowed to stabilize
8. Determine the reference value = Set the spectrum analyzer marker to the highest level of the displayed trace
9. Using the marker-delta function of the instrument, determine the “-xx dB down amplitude” using [(reference value) - xx].
10. Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.


- Measurement Data: **Comply**



- Minimum Standard: NA

4.2.2 In-band emissions

- Test Configuration



- **Procedure:** The radiated emission was tested according to the **section 6.4 of the ANSI C63.10-2013**.

The EUT was placed on a 0.8 m high non-conductive table and it was placed at 3m distance from the antenna. Measurements were performed for each of the three antenna orientations. (ie. parallel, perpendicular, and ground-parallel)

Also, measurements were performed with the EUT oriented in 3 orthogonal axis and rotated 360 degrees to determine worst-case orientation for maximum emissions.

RBW = As specified in below table, VBW $\geq 3 \times$ RBW, Sweep = Auto, Detector = Peak
Trace mode = Max Hold until the trace stabilizes.

Frequency	RBW
9-150 kHz	200-300 Hz
0.15-30 MHz	9-10 kHz
30-1000 MHz	100-120 kHz
> 1000 MHz	1 MHz

- **Minimum Standard: Part 15.225(a), (b), (c) & RSS-210 [B6(a), (b), (c)]**

Frequency Band [MHz]	Limit at 30 m measurement distance	
	[uV/m]	[dBuV/m]
13.553-13.567	15,848	84.00
13.410-13.553 13.567-13.710	334	50.47
13.110-13.410 13.710-14.010	106	40.51

- Measurement Data: Comply

Tested Frequency : 13.558 MHz
Measurement Distance : 3 Meters

Test Mode 1

Frequency Band [MHz]	Freq. [MHz]	EUT Axis.	ANT (Note 1)	Reading Level [dBuV]	T.F [dB/m]	Field Strength @3 m [dBuV/m]	Field Strength @30 m [dBuV/m]	Limit [dBuV/m]	Margin [dB]
13.110 ~ 13.410	13.386	X	P	8.80	20.20	29.00	-11.00	40.50	51.50
13.410 ~ 13.553	13.552	X	P	10.60	20.20	30.80	-9.20	50.50	59.70
13.553 ~ 13.567	13.555	X	P	12.90	20.20	33.10	-6.90	84.00	90.90
13.567 ~ 13.710	13.568	X	P	9.00	20.20	29.20	-10.80	50.50	61.30
13.710 ~ 14.010	13.902	X	P	9.20	20.30	29.50	-10.50	40.50	51.00

Test Mode 2

Frequency Band [MHz]	Freq. [MHz]	EUT Axis.	ANT (Note 1)	Reading Level [dBuV]	T.F [dB/m]	Field Strength @3 m [dBuV/m]	Field Strength @30 m [dBuV/m]	Limit [dBuV/m]	Margin [dB]
13.110 ~ 13.410	13.177	X	P	8.90	20.20	29.10	-10.90	40.50	51.40
13.410 ~ 13.553	13.552	X	P	34.70	20.20	54.90	14.90	50.50	35.60
13.553 ~ 13.567	13.557	X	P	37.40	20.20	57.60	17.60	84.00	66.40
13.567 ~ 13.710	13.568	X	P	25.40	20.20	45.60	5.60	50.50	44.90
13.710 ~ 14.010	13.851	X	P	8.50	20.30	28.80	-11.20	40.50	51.70

Note 1. Loop antenna orientation

“P”: Parallel, “V”: perpendicular, “G”: ground-parallel

Note 2. This test item was performed at 3 m and the data were extrapolated to the specified measurement distance of 30 m using the square of an inverse linear distance extrapolation factor (40 dB/decade) as specified in §15.31(f)2.

▪ Extrapolation Factor = $20 \log_{10}(30/3)^2 = 40 \text{ dB}$

Note 3. All data were recorded using a spectrum analyzer employing a peak detector.

If PK results were meet Quasi-peak limit, Quasi-peak measurements were omitted.

Note 4. Sample Calculation.


Margin = Limit – Field Strength @ 30 m / Field Strength @ 30 m = Field Strength @ 3 m – 40 dB

Field Strength @ 3 m = Reading + T.F / T.F = AF + CL

Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss

4.2.4 Out-of-band emissions

- Test configuration



- **Procedure:** The radiated emission was tested according to the **section 6.4, 6.5 of the ANSI C63.10-2013.**

The EUT was tested from 9 kHz up to the 1 GHz excluding the band 13.110-14.010 MHz.

A The EUT was placed on a 0.8 m high non-conductive table and it was placed at 3m distance from the antenna. For measurements below 30MHz were performed for each of the three antenna orientations. (ie. parallel, perpendicular, and ground-parallel) For measurements above 30MHz were performed for each of the both horizontal and vertical polarizations.

Also, measurements were performed with the EUT oriented in 3 orthogonal axis and rotated 360 degrees to determine worst-case orientation for maximum emissions.

RBW = As specified in below table, VBW $\geq 3 \times$ RBW, Sweep = Auto, Detector = Peak
Trace mode = Max Hold until the trace stabilizes.

Frequency	RBW
9-150 kHz	200-300 Hz
0.15-30 MHz	9-10 kHz
30-1000 MHz	100-120 kHz
> 1000 MHz	1 MHz

- **Minimum Standard: Part 15.209, 225(d) & RSS-210[B6(d)], RSS-GEN[8.9]**

▪ **FCC Part 15.209(a):**

Frequency [MHz]	Field Strength [μ V/m]	Measurement Distance [Meters]
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30	30	30
30 ~ 88	100 **	3
88 ~ 216	150 **	3
216 ~ 960	200 **	3
Above 960	200	3

** Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

▪ **FCC Part 15.209(b):**

In the emission table above, the tighter limit applies at the band edges.

- Measurement Data: Comply

Tested Frequency : 13.558 MHz
Measurement Distance : 3 Meters

Test Mode 1

Frequency [MHz]	EUT Axis.	ANT (Note 1)	Reading [dBuV]	T.F [dB/m]	Distance factor [dB]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
0.044	X	P	44.90	19.6	80	-15.5	34.7	50.2
0.684	X	P	33.20	19.1	40	12.3	30.9	18.6
1.828	X	P	29.40	19.8	40	9.2	29.5	20.3
2.488	X	P	28.40	19.9	40	8.3	29.5	21.2
31.819	X	V	46.10	-18.6	0	27.5	40	12.5
59.343	X	V	45.50	-17.8	0	27.7	40	12.3
86.017	X	V	52.60	-21.9	0	30.7	40	9.3
90.018	X	V	53.20	-21.8	0	31.4	43.5	12.1
216.842	X	V	54.30	-18.9	0	35.4	46	10.6
271.160	X	V	49.30	-16.2	0	33.1	46	12.9
325.357	X	H	45.30	-14.4	0	30.9	46	15.1

Test Mode 2

Frequency [MHz]	EUT Axis.	ANT (Note 1)	Reading [dBuV]	T.F [dB/m]	Distance factor [dB]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
0.044	X	P	44.10	19.60	80	-16.30	34.7	51
0.528	X	P	33.60	18.7	40	12.3	33.2	20.9
0.645	X	P	34.30	19	40	13.3	31.4	18.1
1.852	X	P	28.40	19.8	40	8.2	29.5	21.3
2.405	X	P	27.80	19.9	40	7.7	29.5	21.8
59.585	X	V	45.60	-17.8	0	27.8	40	12.2
80.440	X	H	47.00	-21.5	0	25.5	40	14.5
119.238	X	H	48.90	-18.2	0	30.7	43.5	12.8
166.524	X	V	45.80	-16.3	0	29.5	43.5	14
189.804	X	V	47.20	-18.6	0	28.6	43.5	14.9
216.842	X	V	55.10	-18.9	0	36.2	46	9.8
216.842	X	H	50.70	-18.9	0	31.8	46	14.2
271.039	X	V	49.80	-16.2	0	33.6	46	12.4

Note 1. Loop antenna orientation (30 MHz Below)

“P”= Parallel, “V”= perpendicular, “G”= ground-parallel

Bilog antenna polarization (30 MHz above)

“H”= Horizontal, “V”= Vertical

Note 2. All data were recorded using a spectrum analyzer employing a peak detector.

If PK results were meet Quasi-peak limit, Quasi-peak measurements were omitted.

Note 3. No other spurious and harmonic emissions were reported greater than listed emissions above table.

Note 4. Sample calculation

Margin = Limit – Field Strength

Field Strength = Reading + T.F – Distance factor

T.F = AF + CL – AG

Distance factor = $20\log(\text{Measurement distance} / \text{The measured distance})^2$

Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain

4.2.5 Frequency Stability

- Procedure:

Part 15.225 requires that devices operating in the 13.553 – 13.567 MHz shall maintain the carrier frequency within 0.01 % of the operating frequency over the temperature variation of -20 degrees to + 50 degrees C at normal supply voltage.

- Measurement Data: **Comply**

Operating Frequency : 13,558,000 Hz

VOLTAGE (%)	POWER (V _{DC})	TEMP (°C)	Frequency (Hz)	Freq. Dev. (Hz)	Deviation (%)
100%	120.000	+20(ref)	13,557,086	-914	0.006742
100%		-20	13,557,041	-959	0.007074
100%		-10	13,557,053	-947	0.006985
100%		0	13,557,075	-925	0.006823
100%		+10	13,557,079	-921	0.006793
100%		+20	13,557,086	-914	0.006742
100%		+30	13,557,105	-895	0.006602
100%		+40	13,557,135	-865	0.006380
100%		+50	13,557,143	-857	0.006323
85%	102.000	+20	13,557,091	-909	0.006705
115%	138.000	+20	13,557,080	-920	0.006786
ENDPOINT	100.000	+25	13,557,081	-919	0.006779

- Minimum Standard: Part 15. 225(e) & RSS-210 [B6]

The frequency tolerance of the carrier signal shall be maintained within ± 0.01 % of the operating frequency.

4.2.6 AC Line Conducted Emissions

- Test Requirements and limit

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).

Frequency Range (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

* Decreases with the logarithm of the frequency

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

- Test Configuration

See test photographs for the actual connections between EUT and support equipment.

- Test Procedure

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors – Quasi Peak and Average Detector.

- **Measurement Data:** **Comply** (refer to the next page)

Measurement Data

Results of Conducted Emission

DT&C

Date 2017-08-14



Model NL200
Function
Mode NFC
Test condition

Temp/Humi.
Power Supply
Operator

24 'C 48 %
AC 120 V 60 Hz
S.G LEE

Memo

LIMIT : FCC P15.207 QP
FCC P15.207 AV



Measurement Data

Results of Conducted Emission

DT&C

Date 2017-08-14

Model NL200
 Function
 Mode NFC
 Test condition

Temp/Humi. 24 'C 48 %
 Power Supply AC 120 V 60 Hz
 Operator S.G LEE

Memo

LIMIT : FCC P15.207 QP
 FCC P15.207 AV

NO	FREQ [MHz]	READING		C.FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	CAV [dBuV]		QP [dBuV]	CAV [dBuV]	QP [dBuV]	CAV [dBuV]	QP [dBuV]	CAV [dBuV]	
1	0.16036	42.84	41.58	0.22	43.06	41.80	65.45	55.45	22.39	13.65	N
2	0.24076	39.25	38.28	0.21	39.46	38.49	62.07	52.07	22.61	13.58	N
3	0.32150	38.87	37.52	0.20	39.07	37.72	59.67	49.67	20.60	11.95	N
4	0.40250	41.29	35.02	0.21	41.50	35.23	57.80	47.80	16.30	12.57	N
5	0.56156	42.24	41.29	0.22	42.46	41.51	56.00	46.00	13.54	4.49	N
6	0.78319	34.19	18.38	0.24	34.43	18.62	56.00	46.00	21.57	27.38	N
7	1.10920	40.90	40.96	0.26	41.16	41.22	56.00	46.00	14.84	4.78	N
8	1.28060	41.38	39.61	0.26	41.64	39.87	56.00	46.00	14.36	6.13	N
9	1.84420	36.69	33.45	0.29	36.98	33.74	56.00	46.00	19.02	12.26	N
10	3.32600	34.26	33.74	0.38	34.64	34.12	56.00	46.00	21.36	11.88	N
11	9.12260	34.52	32.38	0.66	35.18	33.04	60.00	50.00	24.82	16.96	N
12	13.55600	32.21	32.03	0.95	33.16	32.98	60.00	50.00	26.84	17.02	N
13	19.63000	21.82	18.93	1.39	23.21	20.32	60.00	50.00	36.79	29.68	N
14	29.40820	13.41	4.70	2.05	15.46	6.75	60.00	50.00	44.54	43.25	N
15	0.16008	40.93	39.71	0.19	41.12	39.90	65.46	55.46	24.34	15.56	L1
16	0.24024	35.83	34.76	0.18	36.01	34.94	62.09	52.09	26.08	17.15	L1
17	0.32050	38.16	36.58	0.19	38.35	36.77	59.69	49.69	21.34	12.92	L1
18	0.40061	41.46	35.90	0.20	41.66	36.10	57.84	47.84	16.18	11.74	L1
19	0.43346	42.37	30.53	0.20	42.57	30.73	57.19	47.19	14.62	16.46	L1
20	0.55967	42.57	41.51	0.21	42.78	41.72	56.00	46.00	13.22	4.28	L1
21	0.80050	39.08	37.01	0.23	39.31	37.24	56.00	46.00	16.69	8.76	L1
22	1.25720	37.86	37.45	0.25	38.11	37.70	56.00	46.00	17.89	8.30	L1
23	1.75780	39.19	35.99	0.29	39.48	36.28	56.00	46.00	16.52	9.72	L1
24	2.29640	33.60	31.91	0.30	33.90	32.21	56.00	46.00	22.10	13.79	L1
25	3.40340	35.16	34.50	0.37	35.53	34.87	56.00	46.00	20.47	11.13	L1
26	9.43980	33.88	33.21	0.77	34.65	33.98	60.00	50.00	25.35	16.02	L1
27	13.55660	42.53	42.85	0.99	43.52	43.84	60.00	50.00	16.48	6.16	L1
28	21.51800	24.49	20.99	1.66	26.15	22.65	60.00	50.00	33.85	27.35	L1

APPENDIX

TEST EQUIPMENT FOR TESTS

Type	Manufacturer	Model	Cal.Date (yy/mm/dd)	Next.Cal.Date (yy/mm/dd)	S/N
Spectrum Analyzer	Agilent Technologies	N9020A	17/07/12	18/07/12	MY46471601
Multimeter	FLUKE	17B	17/04/12	18/04/12	26030065WS
AC Power Supply	DAEKWANG	5KVA	17/01/11	18/01/11	20060321-1
Signal Generator	Rohde Schwarz	SMBV100A	17/01/04	18/01/04	255571
Thermohygrometer	HCT	HCT-1	16/09/09	17/09/09	NONE
Loop Antenna	Schwarzbeck	FMZB1513	16/04/22	18/04/22	1513-128
BILOG ANTENNA	Schwarzbeck	VULB 9160	16/11/11	18/11/11	3151
PreAmplifier	TSJ	MLA-010K01-B01-27	17/03/06	18/03/06	1844539
EMI Test Receiver	Rohde Schwarz	ESR7	17/02/16	18/02/16	101061
EMI Test Receiver	R&S	ESCI	17/02/26	18/02/16	100364
SINGLE-PHASE MASTER	NF	4420	16/09/08	17/09/08	3049354420023
Temp & Humi Test Chamber	SJ Science	SJ-TH-S50	16/09/09	17/09/09	U5542113
Artificial Mains Network	Rohde Schwarz	ESH2-Z5	16/09/08	17/09/08	828739/006

Note: The measurement antennas were calibrated in accordance to the requirements of ANSI C63.5-2006.