

RF Exposure Evaluation Declaration

Product Name : UHD551-L
Trade Name : Vestel
Model No. : UHD551-L
FCC ID. : XU6-UHD551L

Applicant : VESTEL TRADE CO.
Address : Organize Sanayi Bölgesi (45030) Manisa/Türkiye

Date of Receipt : Mar. 28, 2017
Issued Date : Apr. 20, 2017
Report No. : 1740037R-RF-US-EXP
Report Version : V1.0



The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of DEKRA Testing and Certification Co., Ltd.

1. RF Exposure Evaluation

1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

1.3. Test Result of RF Exposure Evaluation

Product	UHD551-L
Test Mode	Transmit_SISO Mode
Test Condition	RF Exposure Evaluation

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber are 2dBi or 1.58 in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

BT2.0 GFSK			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
0	2402	0.7656	0.00024
39	2441	0.7907	0.00025
78	2480	0.7998	0.00025

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

Product	UHD551-L
Test Mode	Transmit_SISO Mode
Test Condition	RF Exposure Evaluation

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber are 2dBi or 1.58 in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

BT4.0			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
0	2402	1.9454	0.00061
19	2440	2.0370	0.00064
39	2480	2.0370	0.00064

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

Product	UHD551-L
Test Mode	Transmit_SISO Mode
Test Condition	RF Exposure Evaluation

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber are 4.5dBi or 2.82 in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11b			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	2412	51.7607	0.02904
6	2437	49.6592	0.02786
11	2462	47.3151	0.02654

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

IEEE 802.11g			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	2412	294.4422	0.16519
6	2437	290.4023	0.16292
11	2462	256.4484	0.14387

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

Product	UHD551-L
Test Mode	Transmit_MIMO Mode
Test Condition	RF Exposure Evaluation

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber are 4.5dBi or 2.82 in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11n (20MHz)			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	2412	246.3770	0.13822
6	2437	201.3713	0.11297
11	2462	206.5368	0.11587

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

IEEE 802.11n (40MHz)			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
3	2422	128.5225	0.07210
6	2437	207.2737	0.11628
9	2452	190.1935	0.10670

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

Product	UHD551-L
Test Mode	Transmit _SISO Mode
Test Condition	RF Exposure Evaluation

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber are 6.75dBi or 4.73 in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11a			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
36	5180	15.1356	0.01424
44	5220	15.3462	0.01444
48	5240	15.5597	0.01464

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

Product	UHD551-L
Test Mode	Transmit_MIMO Mode
Test Condition	RF Exposure Evaluation

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber are 6.75dBi or 4.73 in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11 n(20MHz)			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
36	5180	19.2547	0.01812
44	5220	17.5232	0.01649
48	5240	17.8868	0.01683

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

IEEE 802.11 n(40MHz)			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
38	5190	24.1321	0.02271
46	5230	23.4579	0.02207

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

Product	UHD551-L
Test Mode	Transmit _SISO Mode
Test Condition	RF Exposure Evaluation

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber are 6.75dBi or 4.73 in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11a			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
52	5270	16.0325	0.01509
60	5300	15.4525	0.01454
64	5320	15.1705	0.01428

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

Product	UHD551-L
Test Mode	Transmit_MIMO Mode
Test Condition	RF Exposure Evaluation

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber are 6.75dBi or 4.73 in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11 n(20MHz)			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
52	5270	15.6514	0.01473
60	5300	14.9126	0.01403
64	5320	13.8057	0.01299

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

IEEE 802.11 n(40MHz)			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
54	5270	22.4125	0.02109
62	5310	21.9287	0.02063

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

Product	UHD551-L
Test Mode	Transmit _SISO Mode
Test Condition	RF Exposure Evaluation

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber are 7.5dBi or 5.62 in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11a			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
100	5500	11.2980	0.01263
116	5580	10.6660	0.01193
140	5700	10.1158	0.01131

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

Product	UHD551-L
Test Mode	Transmit_MIMO Mode
Test Condition	RF Exposure Evaluation

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber are 7.5dBi or 5.62 in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11 n(20MHz)			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
100	5500	10.2123	0.01142
116	5580	9.2304	0.01032
140	5700	8.8409	0.00988

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

IEEE 802.11 n(40MHz)			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
102	5510	15.6321	0.01748
110	5550	14.7505	0.01649
134	5670	13.2925	0.01486

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

Product	UHD551-L
Test Mode	Transmit_MIMO Mode
Test Condition	RF Exposure Evaluation

Power Density (WiFi) (mW/cm ²)	Power Density (BT) (mW/cm ²)	Total Power Density (WiFi+BT) (mW/cm ²)	Limit (mW/cm ²)
0.1652	0.00064	0.16584	1