

1		2		3		4		5		6																																																																																																																																																																					
								Remark	Description	Editor	Date																																																																																																																																																																				
1. 以下内容由供应商打印												2. 以下内容由工厂在供应商印刷基础上打印																																																																																																																																																																			
25.5 mm 59.5 mm TRENDnet Power Input: 12V 1.5A US: T1DLO1BTEW816DRM This device complies with Part 15&68 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. Indoor use only Made in China CE RoHS FC 条码扫描内容为LAN MAC信息 TRENDnet Model: TEW-816DRM/EU H/W: XXXX S/N: TWYYWW16XXXX Power Input: 12V 1.5A US: T1DLO1BTEW816DRM This device complies with Part 15&68 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. Indoor use only Made in China CE RoHS FC 3.0 mm 3.0 mm LAN MAC:即系统MAC，见生产信息发布流程 WAN MAC:为LAN MAC+1 <td colspan="12">编号规则:TWYYWW16XXXXX TW:固定，Vendor code,代表同维 YY：年 WW：周 16：固定 XXXXX: 00001 - 99999(按生产流水号) Web password: AAAAAAAA AAAAAAA: 由产测软件生成 TRENDnet816_2.4GHz_NNNN NNNN:由产测软件生成 Wi-Fi Password: 816XXXXXXXXX 816:Model#,固定 XXXXXXXX:SN后8位 FW: XXXX及H/W:XXXX XXXX：均见生产信息发布流程</td>												编号规则:TWYYWW16XXXXX TW:固定，Vendor code,代表同维 YY：年 WW：周 16：固定 XXXXX: 00001 - 99999(按生产流水号) Web password: AAAAAAAA AAAAAAA: 由产测软件生成 TRENDnet816_2.4GHz_NNNN NNNN:由产测软件生成 Wi-Fi Password: 816XXXXXXXXX 816:Model#,固定 XXXXXXXX:SN后8位 FW: XXXX及H/W:XXXX XXXX：均见生产信息发布流程																																																																																																																																																																			
注：条形码使用600DPI打印机进行打印												来料方式：卷装 BARCODE:CODE 128																																																																																																																																																																			
NOTES(技术要求): 1. 黑色印刷，无边框, R0. 5*3,C3*1 (Black printing, no frame, R0. 5*3,C3*1) 2.材料: 50#亮白压花格底PET, 耐85度高温测试不起泡, 过UV油墨, 背胶 (Material:50#Bright white embossing PET,Heat resistant of at least 85 °C,no bubble,UV coated,adhesive) 3. 原材料及后处理工艺均能满足我司《环保技术标准》要求。 (Raw materials and the corresponding post processing should meet requirements defined in the T&W Environmental Protection Technical Standards)												<table><tr><td rowspan="2">DIM</td><td rowspan="2">TOL±</td><td colspan="4"></td><td rowspan="2"></td><td colspan="2">CUSTOMER: Trendnet</td><td colspan="4">T&W 同维 SHANGHAI GONGJIN TELECOM TECHNOLOGY CO.,LTD.</td></tr><tr><td>RANGE</td><td>C1</td><td>C2</td><td>C3</td><td>C4</td><td colspan="2">TITLE: 印刷盒底 标贴</td><td colspan="2">MODEL: TEW-816DRM/EU</td><td colspan="2">PART NO: 61100000XXXX</td></tr><tr><td></td><td></td><td>0~6</td><td>0.1</td><td>0.1</td><td>0.15</td><td>0.2</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td>6~30</td><td>0.2</td><td>0.3</td><td>0.4</td><td>0.5</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td>30~80</td><td>0.25</td><td>0.5</td><td>0.9</td><td>1.2</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td>80~180</td><td>0.3</td><td>0.8</td><td>1.2</td><td>1.5</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td>180~315</td><td>0.5</td><td>1.3</td><td>1.8</td><td>3</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td>315~500</td><td>0.7</td><td>1.5</td><td>2.5</td><td>4</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td>500~800</td><td>0.9</td><td>1.8</td><td>3</td><td>5</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td colspan="2">ANG.TOL±</td><td colspan="2">0°~30°/0.1°</td><td colspan="2">30°~60°/0.3°</td><td colspan="2">60°~90°/0.5°</td><td>FINISH</td><td>N/A</td><td>SHEET</td><td>1 / 1</td><td>PDE</td><td colspan="3">N/A</td></tr></table>												DIM	TOL±						CUSTOMER: Trendnet		T&W 同维 SHANGHAI GONGJIN TELECOM TECHNOLOGY CO.,LTD.				RANGE	C1	C2	C3	C4	TITLE: 印刷盒底 标贴		MODEL: TEW-816DRM/EU		PART NO: 61100000XXXX				0~6	0.1	0.1	0.15	0.2												6~30	0.2	0.3	0.4	0.5												30~80	0.25	0.5	0.9	1.2												80~180	0.3	0.8	1.2	1.5												180~315	0.5	1.3	1.8	3												315~500	0.7	1.5	2.5	4												500~800	0.9	1.8	3	5										ANG.TOL±		0°~30°/0.1°		30°~60°/0.3°		60°~90°/0.5°		FINISH	N/A	SHEET	1 / 1	PDE	N/A		
DIM	TOL±						CUSTOMER: Trendnet		T&W 同维 SHANGHAI GONGJIN TELECOM TECHNOLOGY CO.,LTD.																																																																																																																																																																						
		RANGE	C1	C2	C3		C4	TITLE: 印刷盒底 标贴		MODEL: TEW-816DRM/EU		PART NO: 61100000XXXX																																																																																																																																																																			
		0~6	0.1	0.1	0.15	0.2																																																																																																																																																																									
		6~30	0.2	0.3	0.4	0.5																																																																																																																																																																									
		30~80	0.25	0.5	0.9	1.2																																																																																																																																																																									
		80~180	0.3	0.8	1.2	1.5																																																																																																																																																																									
		180~315	0.5	1.3	1.8	3																																																																																																																																																																									
		315~500	0.7	1.5	2.5	4																																																																																																																																																																									
		500~800	0.9	1.8	3	5																																																																																																																																																																									
ANG.TOL±		0°~30°/0.1°		30°~60°/0.3°		60°~90°/0.5°		FINISH	N/A	SHEET	1 / 1	PDE	N/A																																																																																																																																																																		
1		2		3		4		5		6																																																																																																																																																																					



Label location