


FCC Test Report

FCC ID : XU8TEW820-821
Equipment : Wireless AC Easy-Upgrader
(Please refer to 1.1.1 for more details.)
Model No. : TEW-820AP
(Please refer to 1.1.1 for more details.)
Brand Name : TRENDnet
Applicant : TRENDnet, Inc.
Address : 20675 Manhattan Place, Torrance, CA 90501,
USA
Standard : 47 CFR FCC Part 15.407
Received Date : Mar. 20, 2014
Tested Date : Mar. 21 ~ Mar. 28, 2014

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:



Gary Chang / Manager

Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Local Support Equipment List	8
1.3	Test Setup Chart	8
1.4	The Equipment List	9
1.5	Testing Applied Standards	10
1.6	Measurement Uncertainty	10
2	TEST CONFIGURATION	11
2.1	Testing Condition	11
2.2	The Worst Test Modes and Channel Details	11
3	TRANSMITTER TEST RESULTS.....	12
3.1	Conducted Emissions.....	12
3.2	Emission Bandwidth	15
3.3	RF Output Power	17
3.4	Peak Power Spectral Density	19
3.5	Peak Excursion.....	21
3.6	Transmitter Radiated and Band Edge Emissions	24
3.7	Frequency Stability.....	47
4	TEST LABORATORY INFORMATION	49

Release Record

Report No.	Version	Description	Issued Date
FR432006AN	Rev. 01	Initial issue	May 20, 2014

Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	Conducted Emissions	[dBuV]: 0.156MHz 47.55 (Margin -8.14dB) - AV	Pass
15.407(b)(1)(2)(3) 15.209	Radiated Emissions	[dBuV/m at 3m]: 5150.00MHz 52.51 (Margin -1.49dB) - AV	Pass
15.407(a)(1)(2)(3)	Emission Bandwidth	Meet the requirement of limit	Pass
15.407(a)(1)(2)(3)	RF Output Power	Power [dBm]: 11a: 15.94 HT20: 15.82 HT40: 16.80 VHT20: 15.89 VHT40: 16.86 VHT80: 16.45	Pass
15.407(a)(1)(2)(3)	Peak Power Spectral Density	Meet the requirement of limit	Pass
15.407(a)(6)	Peak Excursion	Meet the requirement of limit	Pass
15.407(g)	Frequency Stability	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

1 General Description

1.1 Information

1.1.1 Product Details

The following models are provided to this EUT.

Brand Name	Model Name	Product Name
TRENDnet	TEW-820AP	Wireless AC Easy-Upgrader
	TEW-821AP	AC433 Wireless Access Point
✦ All models are electrically identical, different model names are for marketing purpose. ✦ The above models, model TEW-820AP was selected as a representative one for the final test and only its data was recorded in this report.		

1.1.2 Specification of the Equipment under Test (EUT)

RF General Information					
IEEE Std. 802.11	Frequency Range (MHz)	Ch. Freq. (MHz)	Channel Number	Transmit Chains (N _{TX})	Data Rate / MCS
a	5150-5250	5180-5240	36-48 [4]	1	6-54 Mbps
n (HT20)	5150-5250	5180-5240	36-48 [4]	1	MCS 0-7
n (HT40)	5150-5250	5190-5230	38-46 [2]	1	MCS 0-7
ac (VHT20)	5150-5250	5180-5240	36-48 [4]	1	MCS 0-8
ac (VHT40)	5150-5250	5190-5230	38-46 [2]	1	MCS 0-9
ac (VHT80)	5150-5250	5210	42 [1]	1	MCS 0-9
Note 1: RF output power specifies that Maximum Conducted Output Power. Note 2: 802.11a/n uses a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM, 256QAM modulation.					

1.1.3 Antenna Details

Ant. No.	Type	Gain (dBi)	Connector	Remark
1	PCB	3	U.FL	---

1.1.4 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	5Vdc from AC adapter
-------------------	----------------------

1.1.5 Accessories

Accessories		
No.	Equipment	Description
1	AC Adapter 1	Brand Name: SHENZHEN FRECOM ELECTRONICS CO., LTD. Model Name: F05W-050100SPAU Power Rating: I/P: 100-240Vac, 50-60Hz, 190mA O/P: 5Vdc, 1.0A Power Line: 1.2m non-shielded cable w/o core

1.1.6 Channel List

802.11 a / HT20 / VHT20		HT40 / VHT40	
Channel	Frequency(MHz)	Channel	Frequency(MHz)
36	5180	38	5190
40	5200	46	5230
44	5220	VHT 80	
48	5240	42	5210

1.1.7 Test Tool and Duty Cycle

Test Tool	MP tool / Version: RTL819x 2.3-13/09/16		
Duty Cycle and Duty Factor	Mode	Duty cycle (%)	Duty factor (dB)
	11a	100%	0.00
	HT20	100%	0.00
	HT40	100%	0.00
	VHT20	100%	0.00
	VHT40	100%	0.00
	VHT80	100%	0.00


1.1.8 Power Setting

Modulation Mode	Test Frequency (MHz)	Power Set
11a	5180	60
11a	5200	59
11a	5240	57
HT20	5180	60
HT20	5200	59
HT20	5240	57
HT40	5190	61
HT40	5230	59
VHT20	5180	60
VHT20	5200	59
VHT20	5240	57
VHT40	5190	61
VHT40	5230	59
VHT80	5210	60

1.2 Local Support Equipment List

Support Equipment List						
No.	Equipment	Brand	Model	S/N	FCC ID	Signal cable / Length (m)
1	Notebook	DELL	E6430	---	---	RJ45, 10m non-shielded w/o core.

1.3 Test Setup Chart



1.4 The Equipment List

Test Item	Conducted Emission				
Test Site	Conduction room 1 / (CO01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
EMC Receiver	R&S	ESCS 30	100169	Oct. 15, 2013	Oct. 14, 2014
LISN	SCHWARZBECK	Schwarzbeck 8127	8127-667	Nov. 23, 2013	Nov. 22, 2014
LISN (Support Unit)	SCHWARZBECK	Schwarzbeck 8127	8127-666	Dec. 04, 2013	Dec. 03, 2014
RF Cable-CON	Woken	CFD200-NL	CFD200-NL-001	Apr. 24, 2013	Apr. 23, 2014
50 ohm terminal (Support Unit)	NA	50	04	Apr. 22, 2013	Apr. 21, 2014
Note: Calibration Interval of instruments listed above is one year.					

Test Item	Radiated Emission				
Test Site	966 chamber 2 / (03CH02-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101499	Feb. 08, 2014	Feb. 07, 2015
Receiver	R&S	ESR3	101657	Jan. 18, 2014	Jan. 17, 2015
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-524	Jan. 08, 2014	Jan. 07, 2015
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1095	Jan. 07, 2014	Jan. 06, 2015
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Dec. 27, 2013	Dec. 26, 2014
Preamplifier	Burgeon	BPA-530	100218	Dec. 09, 2013	Dec. 08, 2014
Preamplifier	Agilent	83017A	MY39501309	Dec. 09, 2013	Dec. 08, 2014
Preamplifier	EM	EM18G40G	060572	Jun. 20, 2013	Jun. 19, 2014
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16140/4	Dec. 17, 2013	Dec. 16, 2014
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16018/4	Dec. 17, 2013	Dec. 16, 2014
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16015/4	Dec. 17, 2013	Dec. 16, 2014
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-003	Dec. 17, 2013	Dec. 16, 2014
LF cable 10M	Woken	CFD400NL-LW	CFD400NL-004	Dec. 17, 2013	Dec. 16, 2014
Note: Calibration Interval of instruments listed above is one year.					

Loop Antenna	R&S	HFH2-Z2	100330	Nov. 15, 2012	Nov. 14, 2014
Note: Calibration Interval of instruments listed above is two year.					

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101063	Feb. 17, 2014	Feb. 16, 2015
TEMP&HUMIDITY CHAMBER	GIANT FORCE	GCT-225-40-SP-SD	MAF1212-002	Dec. 11, 2013	Dec. 10, 2014
Power Meter	Anritsu	ML2495A	1241002	Oct. 24, 2013	Oct. 23, 2014
Power Sensor	Anritsu	MA2411B	1207366	Oct. 24, 2013	Oct. 23, 2014
Note: Calibration Interval of instruments listed above is one year.					

1.5 Testing Applied Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.407

ANSI C63.10-2009

FCC KDB 412172

FCC KDB 789033 D01 General UNII Test procedures v01r03

Note: The EUT has been tested and complied with FCC part 15B requirement. FCC Part 15B test results are issued to another report.

1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	±34.134 Hz
Conducted power	±0.808 dB
Frequency error	±34.134 Hz
Power density	±0.463 dB
Conducted emission	±2.670 dB
AC conducted emission	±2.88 dB
Radiated emission < 1GHz	±3.26 dB
Radiated emission > 1GHz	±4.94 dB
Time	±0.1%
Temperature	±0.6 °C

2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	16°C / 62%	Skys Huang
Radiated Emissions	03CH02-WS	18-24°C / 65-68%	Brad Wu Anderson Hong
RF Conducted	TH01-WS	25°C / 62%	Mark Liao

➤ FCC site registration No.: 657002

➤ IC site registration No.: 10807A-2

2.2 The Worst Test Modes and Channel Details

Test item	Modulation Mode	Test Frequency (MHz)	Data Rate (Mbps) / MCS	Test Configuration
Conducted Emissions	VHT40	5190	MCS 0	---
Radiated Emissions ≤1GHz	VHT40	5190	MCS 0	---
RF Output Power	11a	5180 / 5200 / 5240	6 Mbps	---
	HT20	5180 / 5200 / 5240	MCS 0	
	HT40	5190 / 5230	MCS 0	
	VHT20	5180 / 5200 / 5240	MCS 0	
	VHT40	5190 / 5230	MCS 0	
	VHT80	5210	MCS 0	
Radiated Emissions >1GHz Emission Bandwidth Peak Power Spectral Density	11a	5180 / 5200 / 5240	6 Mbps	---
	HT20	5180 / 5200 / 5240	MCS 0	
	HT40	5190 / 5230	MCS 0	
	VHT80	5210	MCS 0	
Peak Excursion	11a	5240	6 Mbps	---
	HT20	5240	MCS 0	
	HT40	5230	MCS 0	
	VHT20	5240	MCS 0	
	VHT40	5230	MCS 0	
	VHT80	5210	MCS 0	
Frequency Stability	Un-modulation	5240	---	---

3 Transmitter Test Results

3.1 Conducted Emissions

3.1.1 Limit of Conducted Emissions


Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.

3.1.2 Test Procedures

1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
4. This measurement was performed with AC 120V/60Hz

3.1.3 Test Setup



- Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes


3.1.4 Test Result of Conducted Emissions

Modulation	VHT40	Test Freq. (MHz)	5190
Power Phase	Line		

Level (dBuV)

<

Modulation	VHT40	Test Freq. (MHz)	5190
Power Phase	Neutral		



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.166	32.67	55.16	-22.49	32.07	0.50	0.10	Average
2*	0.166	49.00	65.16	-16.16	48.40	0.50	0.10	QP
3	0.191	34.96	53.98	-19.02	34.29	0.51	0.16	Average
4	0.191	47.29	63.98	-16.69	46.62	0.51	0.16	QP
5	0.510	26.81	46.00	-19.19	26.10	0.66	0.05	Average
6	0.510	33.78	56.00	-22.22	33.07	0.66	0.05	QP
7	5.653	12.67	50.00	-37.33	11.13	1.35	0.19	Average
8	5.653	25.21	60.00	-34.79	23.67	1.35	0.19	QP
9	15.083	23.84	50.00	-26.16	21.47	2.24	0.13	Average
10	15.083	32.42	60.00	-27.58	30.05	2.24	0.13	QP
11	22.063	24.12	50.00	-25.88	21.32	2.48	0.32	Average
12	22.063	31.21	60.00	-28.79	28.41	2.48	0.32	QP


Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

3.2 Emission Bandwidth

3.2.1 Test Procedures

1. Set RBW = approximately 1% of the emission bandwidth.
2. Set the VBW > RBW, Detector = Peak.
3. Trace mode = max hold.
4. Measure the maximum width of the emission that is 26 dB down from the peak of the emission.


3.2.2 Test Setup



3.2.3 Test Result of Emission Bandwidth

Emission Bandwidth										
Mode	N _{TX}	Freq. (MHz)	26dB Bandwidth (MHz)			99% Bandwidth (MHz)			Power Limit (dBm)	
			Chain 0	Chain 1	Chain 2	Chain 0	Chain 1	Chain 2	26dB BW	99% BW
11a	1	5180	21.91	---	---	16.86	---	---	17.00	16.27
11a	1	5200	21.68	---	---	16.86	---	---	17.00	16.27
11a	1	5240	21.68	---	---	16.82	---	---	17.00	16.26
VHT20	1	5180	22.26	---	---	17.95	---	---	17.00	16.54
VHT20	1	5200	22.26	---	---	17.95	---	---	17.00	16.54
VHT20	1	5240	22.09	---	---	17.95	---	---	17.00	16.54
VHT40	1	5190	45.68	---	---	37.19	---	---	17.00	17.00
VHT40	1	5230	45.45	---	---	37.05	---	---	17.00	17.00
VHT80	1	5210	94.15	---	---	75.90	---	---	17.00	17.00

Worst Plots



3.3 RF Output Power

3.3.1 Limit of RF Output Power


Frequency Band (GHz)		Limit
☒	5.15~5.25	50mW or 4dBm+10 log B
☐	5.25~5.35	250mW or 11dBm+10 log B
☐	5.47~5.725	250mW or 11dBm+10 log B

Note: "B" is the 26dB emission bandwidth in MHz.

3.3.2 Test Procedures

- ☒ **Power meter**
 - ☒ Measurements is performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required

3.3.3 Test Setup



3.3.4 Test Result of Maximum Conducted Output Power

RF Output Power (dBm)								
Mode	N _{TX}	Freq. (MHz)	Chain 0	Chain 1	Chain 2	Total Power (mW)	Total Power (dBm)	Limit
11a	1	5180	15.94	-	-	39.264	15.94	17.00
11a	1	5200	15.67	-	-	36.898	15.67	17.00
11a	1	5240	15.62	-	-	36.475	15.62	17.00
VHT20	1	5180	15.82	-	-	38.194	15.82	17.00
VHT20	1	5200	15.77	-	-	37.757	15.77	17.00
VHT20	1	5240	15.49	-	-	35.400	15.49	17.00
VHT40	1	5190	16.80	-	-	47.863	16.80	17.00
VHT40	1	5230	16.54	-	-	45.082	16.54	17.00
VHT20	1	5180	15.89	-	-	38.815	15.89	17.00
VHT20	1	5200	15.80	-	-	38.019	15.80	17.00
VHT20	1	5240	15.57	-	-	36.058	15.57	17.00
VHT40	1	5190	16.86	-	-	48.529	16.86	17.00
VHT40	1	5230	16.63	-	-	46.026	16.63	17.00
VHT80	1	5210	16.45	-	-	44.157	16.45	17.00

3.4 Peak Power Spectral Density

3.4.1 Limit of Peak Power Spectral Density

	Frequency Band (GHz)	Limit (dBm)
☒	5.15~5.25	4
☐	5.25~5.35	11
☐	5.47~5.725	11

3.4.2 Test Procedures

☒ Method SA-1

1. Set RBW = 1 MHz, VBW = 3 MHz, Sweep time = auto, Detector = RMS.
2. Trace average 100 traces.
3. Use the peak marker function to determine the maximum amplitude level.


☐ Method SA-2

1. Set RBW = 1 MHz, VBW = 3 MHz, Detector = RMS.
2. Set sweep time $\geq 10 \times (\text{number of points in sweep}) \times (\text{symbol period of the transmitted signal})$.
3. Perform a single sweep.
4. Use the peak marker function to determine the maximum amplitude level.

☐ Method SA-2 Alternative

1. Set RBW = 1 MHz, VBW = 3 MHz, Detector = RMS.
2. Set sweep time $\geq 10 \times (\text{number of points in sweep}) \times (\text{total on/off period of the transmitted signal})$.
3. Perform a single sweep.
4. Use the peak marker function to determine the maximum amplitude level.
5. Add $10 \log(1/x)$, where x is the duty cycle.


3.4.3 Test Setup



3.4.4 Test Result of Peak Power Spectral Density

Condition			Peak Power Spectral Density (dBm)			
Modulation Mode	N _{TX}	Freq. (MHz)	PPSD w/o D.F (dBm)	Duty factor (dB)	PPSD with D.F (dBm)	PPSD Limit (dBm)
11a	1	5180	3.90	0.00	3.90	4
11a	1	5200	3.68	0.00	3.68	4
11a	1	5240	3.09	0.00	3.09	4
VHT20	1	5180	3.78	0.00	3.78	4
VHT20	1	5200	3.25	0.00	3.25	4
VHT20	1	5240	3.15	0.00	3.15	4
VHT40	1	5190	1.41	0.00	1.41	4
VHT40	1	5230	0.85	0.00	0.85	4
VHT80	1	5210	-0.94	0.00	-0.94	4

Note: D.F is duty factor



Note: Power density plot without duty factor

3.5 Peak Excursion


3.5.1 Peak Excursion Limit

Peak excursion of the modulation envelope shall not exceed 13 dB across any 1 MHz bandwidth.

3.5.2 Test Procedures

1. Set RBW = 1 MHz, VBW = 3 MHz, Detector = peak.
2. Trace mode = max-hold. Allow the sweeps to continue until the trace stabilizes.
3. Use the peak search function to find the peak of the spectrum.
4. Use the procedure of section 3.4.2 to measure the PPSD.
5. Compute the ratio of the maximum of the peak-max-hold spectrum to the PPSD

3.5.3 Test Setup




3.5.4 Test Result of Peak Excursion

Frequency band(MHz)		5150~5250					
Mode	Modulation Mode	N _{TX}	Freq. (MHz)	Measured value(dB)	Duty factor (dB)	Peak Excursion (dB)	Limit
11a	BPSK	1	5240	6.7	0.00	6.70	13
11a	QPSK	1	5240	8.66	0.00	8.66	13
11a	16QAM	1	5240	7.96	0.00	7.96	13
11a	64QAM	1	5240	9.18	0.00	9.18	13
VHT20	BPSK	1	5240	7.01	0.00	7.01	13
VHT20	QPSK	1	5240	8.17	0.00	8.17	13
VHT20	16QAM	1	5240	8.14	0.00	8.14	13
VHT20	64QAM	1	5240	9.2	0.00	9.20	13
VHT20	256QAM	1	5240	8.09	0.00	8.09	13
VHT40	BPSK	1	5230	8.5	0.00	8.50	13
VHT40	QPSK	1	5230	7.47	0.00	7.47	13
VHT40	16QAM	1	5230	8.46	0.00	8.46	13
VHT40	64QAM	1	5230	9.16	0.00	9.16	13
VHT40	256QAM	1	5230	8.93	0.00	8.93	13
VHT80	BPSK	1	5210	7.6	0.00	7.60	13
VHT80	QPSK	1	5210	8.13	0.00	8.13	13
VHT80	16QAM	1	5210	8.73	0.00	8.73	13
VHT80	64QAM	1	5210	7.7	0.00	7.70	13
VHT80	256QAM	1	5210	9	0.00	9.00	13

Note: Measured value = Peak-max-hold spectrum to the maximum of the average spectrum for continuous transmission.

Worst Plots



3.6 Transmitter Radiated and Band Edge Emissions

3.6.1 Limit of Transmitter Radiated and Band Edge Emissions

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

Un-restricted band emissions above 1GHz Limit	
Operating Band	Limit
5.15 - 5.25 GHz	e.i.r.p. -27 dBm [68.2 dBuV/m@3m]
5.25 - 5.35 GHz	e.i.r.p. -27 dBm [68.2 dBuV/m@3m]
5.47 - 5.725 GHz	e.i.r.p. -27 dBm [68.2 dBuV/m@3m]
5.725 - 5.825 GHz	5.715 5.725 GHz: e.i.r.p. -17 dBm [78.2 dBuV/m@3m] 5.825 5.835 GHz: e.i.r.p. -17 dBm [78.2 dBuV/m@3m] Other un-restricted band: e.i.r.p. -27 dBm [68.2 dBuV/m@3m]

Note 1: Measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

3.6.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360° . A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at a height of 0.8 m test table above the ground plane.
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360° , the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:


1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

3.6.3 Test Setup

Radiated Emissions below 1 GHz




Radiated Emissions above 1 GHz



3.6.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	VHT40	Test Freq. (MHz)	5190
Polarization	Horizontal		




The graph displays the radiated unwanted emissions for a transmitter. The y-axis represents the Level in dBuV/m, ranging from 0 to 90. The x-axis represents the Frequency in MHz, ranging from 30 to 1000. A red line indicates the FCC CLASS-B limit, which is 40 dBuV/m from 30 MHz to 100 MHz, 45 dBuV/m from 100 MHz to 1000 MHz, and 55 dBuV/m from 1000 MHz to 1100 MHz. Six emission peaks are identified and labeled 1 through 6, with their corresponding frequencies and levels listed in the table below.

	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	215.27	36.23	43.50	-7.27	55.76	-19.53	Peak	---	---
2	240.49	39.30	46.00	-6.70	57.42	-18.12	Peak	---	---
3	318.09	41.11	46.00	-4.89	56.93	-15.82	Peak	---	---
4	393.75	38.10	46.00	-7.90	51.99	-13.89	Peak	---	---
5	580.96	40.45	46.00	-5.55	50.42	-9.97	Peak	---	---
6	774.96	35.68	46.00	-10.32	42.73	-7.05	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	VHT40	Test Freq. (MHz)	5190
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	80.44	36.07	40.00	-3.93	57.70	-21.63	Peak	---	---
2	166.77	38.71	43.50	-4.79	55.94	-17.23	Peak	---	---
3	320.03	40.33	46.00	-5.67	56.11	-15.78	Peak	---	---
4	392.78	40.08	46.00	-5.92	54.00	-13.92	Peak	---	---
5	499.48	36.85	46.00	-9.15	48.56	-11.71	Peak	---	---
6	580.96	38.84	46.00	-7.16	48.81	-9.97	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)


*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

3.6.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 11a


Modulation	11a	Test Freq. (MHz)	5180
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1162.00	34.80	54.00	-19.20	43.51	-8.71	Average	---	---
2	1162.00	46.74	74.00	-27.26	55.45	-8.71	Peak	---	---
3	5150.00	46.98	54.00	-7.02	41.27	5.71	Average	---	---
4	5150.00	61.12	74.00	-12.88	55.41	5.71	Peak	---	---
5	10360.00	61.65	68.20	-6.55	47.21	14.44	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).


Modulation	11a	Test Freq. (MHz)	5180
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1162.00	35.48	54.00	-18.52	44.19	-8.71	Average	---	---
2	1162.00	47.43	74.00	-26.57	56.14	-8.71	Peak	---	---
3	5150.00	46.01	54.00	-7.99	40.30	5.71	Average	---	---
4	5150.00	60.24	74.00	-13.76	54.53	5.71	Peak	---	---
5	10360.00	65.64	68.20	-2.56	51.20	14.44	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).


Modulation	11a	Test Freq. (MHz)	5200
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1162.00	35.31	54.00	-18.69	44.02	-8.71	Average	---	---
2	1162.00	47.29	74.00	-26.71	56.00	-8.71	Peak	---	---
3	10400.00	61.98	68.20	-6.22	47.48	14.50	Peak	---	---
4	15600.00	44.16	54.00	-9.84	28.99	15.17	Average	---	---
5	15600.00	57.48	74.00	-16.52	42.31	15.17	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11a	Test Freq. (MHz)	5200
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1162.00	35.73	54.00	-18.27	44.44	-8.71	Average	---	---
2	1162.00	47.84	74.00	-26.16	56.55	-8.71	Peak	---	---
3	10400.00	65.53	68.20	-2.67	51.03	14.50	Peak	---	---
4	15600.00	44.57	54.00	-9.43	29.40	15.17	Average	---	---
5	15600.00	57.07	74.00	-16.93	41.90	15.17	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11a	Test Freq. (MHz)	5240
Polarization	Horizontal		
Level (dBuV/m) </			

Modulation	11a	Test Freq. (MHz)	5240
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1162.00	35.77	54.00	-18.23	44.48	-8.71	Average	---	---
2	1162.00	47.89	74.00	-26.11	56.60	-8.71	Peak	---	---
3	5350.00	46.56	54.00	-7.44	40.57	5.99	Average	---	---
4	5350.00	59.58	74.00	-14.42	53.59	5.99	Peak	---	---
5	10480.00	66.03	68.20	-2.17	51.40	14.63	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.6.6 Transmitter Radiated Unwanted Emissions (Above 1GHz) for VHT20

Modulation	VHT20	Test Freq. (MHz)	5180
Polarization	Horizontal		


	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1162.00	35.22	54.00	-18.78	43.93	-8.71	Average	---	---
2	1162.00	47.14	74.00	-26.86	55.85	-8.71	Peak	---	---
3	5150.00	47.52	54.00	-6.48	41.81	5.71	Average	---	---
4	5150.00	61.54	74.00	-12.46	55.83	5.71	Peak	---	---
5	10360.00	61.16	68.20	-7.04	46.72	14.44	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).


Modulation	VHT20	Test Freq. (MHz)	5180
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1162.00	36.11	54.00	-17.89	44.82	-8.71	Average	---	---
2	1162.00	47.97	74.00	-26.03	56.68	-8.71	Peak	---	---
3	5150.00	46.86	54.00	-7.14	41.15	5.71	Average	---	---
4	5150.00	60.97	74.00	-13.03	55.26	5.71	Peak	---	---
5	10360.00	65.12	68.20	-3.08	50.68	14.44	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	VHT20	Test Freq. (MHz)	5200
Polarization	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1162.00	35.84	54.00	-18.16	44.55	-8.71	Average	---	---
2	1162.00	47.67	74.00	-26.33	56.38	-8.71	Peak	---	---
3	10400.00	61.43	68.20	-6.77	46.93	14.50	Peak	---	---
4	15600.00	44.36	54.00	-9.64	29.19	15.17	Average	---	---
5	15600.00	57.75	74.00	-16.25	42.58	15.17	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	VHT20	Test Freq. (MHz)	5200
Polarization	Vertical		
 </			


Modulation	VHT20	Test Freq. (MHz)	5240
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1162.00	34.80	54.00	-19.20	43.51	-8.71	Average	---	---
2	1162.00	46.96	74.00	-27.04	55.67	-8.71	Peak	---	---
3	5350.00	46.98	54.00	-7.02	40.99	5.99	Average	---	---
4	5350.00	59.66	74.00	-14.34	53.67	5.99	Peak	---	---
5	10480.00	61.21	68.20	-6.99	46.58	14.63	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	VHT20	Test Freq. (MHz)	5240
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1162.00	36.17	54.00	-17.83	44.88	-8.71	Average	---	---
2	1162.00	48.37	74.00	-25.63	57.08	-8.71	Peak	---	---
3	5350.00	46.94	54.00	-7.06	40.95	5.99	Average	---	---
4	5350.00	60.11	74.00	-13.89	54.12	5.99	Peak	---	---
5	10480.00	65.02	68.20	-3.18	50.39	14.63	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.6.7 Transmitter Radiated Unwanted Emissions (Above 1GHz) for VHT40

Modulation	VHT40	Test Freq. (MHz)	5190
Polarization	Horizontal		
Level (dBuV/m) </			


Modulation	VHT40	Test Freq. (MHz)	5190
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1162.00	36.27	54.00	-17.73	44.98	-8.71	Average	---	---
2	1162.00	48.22	74.00	-25.78	56.93	-8.71	Peak	---	---
3	5150.00	49.74	54.00	-4.26	44.03	5.71	Average	---	---
4	5150.00	64.68	74.00	-9.32	58.97	5.71	Peak	---	---
5	10380.00	63.88	68.20	-4.32	49.42	14.46	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	VHT40	Test Freq. (MHz)	5230
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1162.00	35.78	54.00	-18.22	44.49	-8.71	Average	---	---
2	1162.00	47.34	74.00	-26.66	56.05	-8.71	Peak	---	---
3	5350.00	46.72	54.00	-7.28	40.73	5.99	Average	---	---
4	5350.00	59.91	74.00	-14.09	53.92	5.99	Peak	---	---
5	10460.00	60.61	68.20	-7.59	46.01	14.60	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	VHT40	Test Freq. (MHz)	5230
Polarization	Vertical		
Level (dBuV/m)			

3.6.8 Transmitter Radiated Unwanted Emissions (Above 1GHz) for VHT80

Modulation	VHT80	Test Freq. (MHz)	5210
Polarization	Horizontal		
Level (dBuV/m) </			

Modulation	VHT80	Test Freq. (MHz)	5210
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	5150.00	49.10	54.00	-4.90	43.39	5.71	Average	---	---
2	5150.00	62.94	74.00	-11.06	57.23	5.71	Peak	---	---
3	5350.00	46.34	54.00	-7.66	40.35	5.99	Average	---	---
4	5350.00	59.67	74.00	-14.33	53.68	5.99	Peak	---	---
5	10420.00	61.53	68.20	-6.67	46.99	14.54	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.7 Frequency Stability


3.7.1 Limit of Frequency Stability

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

3.7.2 Test Procedures

1. The EUT is installed in an environment test chamber with external power source.
2. Set the chamber to operate at 50 centigrade and external power source to output at nominal voltage of EUT.
3. A sufficient stabilization period at each temperature is used prior to each frequency measurement.
4. When temperature is stabled, measure the frequency stability.
5. The test shall be performed under -30 to 50 centigrade and 85 to 115 percent of the nominal voltage. Change setting of chamber and external power source to complete all conditions.

3.7.3 Test Setup



3.7.4 Test Result of Frequency Stability

Frequency: 5200 MHz	Frequency Drift (ppm)			
Temperature (°C)	0 minute	2 minutes	5 minutes	10 minutes
T20°C V _{max}	0.14	0.44	-0.30	0.57
T20°C V _{min}	2.87	2.44	3.14	3.35
T50°C V _{nom}	2.13	2.77	2.64	2.73
T40°C V _{nom}	2.39	2.71	2.67	3.19
T30°C V _{nom}	2.97	2.83	2.60	2.71
T20°C V _{nom}	2.13	2.00	1.90	1.54
T10°C V _{nom}	0.13	0.16	0.37	0.81
T0°C V _{nom}	1.27	0.91	0.48	0.95
T-10°C V _{nom}	0.81	0.53	0.42	0.42
T-20°C V _{nom}	-0.23	-0.57	-0.75	-0.96
T-30°C V _{nom}	-0.78	-0.83	-1.33	-1.12
V _{nom} [Vdc]: 110		V _{max} [Vdc]: 126.5		V _{min} [Vdc]: 93.5
T _{nom} [°C]: 20		T _{max} [°C]: 50		T _{min} [°C]: -30

4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp, it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan Hsiang. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan, R.O.C.

Kwei Shan

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==