

## FCC Test Report (Co-Located)

**Report No.:** RF181025C10D-2

**FCC ID:** XU8TEW830MDR

**Test Model:** TEW-830MDR

**Series Model:** TEW-830MDR2K, TEW-830MDR3K (refer to item 3.1 for more details)

**Received Date:** Jun. 21, 2019

**Test Date:** Jul. 07, 2019

**Issued Date:** Jul. 23, 2019

**Applicant:** TRENDnet, Inc.

**Address:** 20675 Manhattan Place, Torrance, CA 90501 U.S.A.

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch  
Lin Kou Laboratories

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

**Test Location:** No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City  
33383, Taiwan

**FCC Registration /  
Designation Number:** 788550 / TW0003



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

## Table of Contents

|                                                                                           |           |
|-------------------------------------------------------------------------------------------|-----------|
| <b>Release Control Record .....</b>                                                       | <b>3</b>  |
| <b>1 Certificate of Conformity.....</b>                                                   | <b>4</b>  |
| <b>2 Summary of Test Results .....</b>                                                    | <b>5</b>  |
| 2.1 Measurement Uncertainty .....                                                         | 5         |
| 2.2 Modification Record .....                                                             | 5         |
| <b>3 General Information.....</b>                                                         | <b>6</b>  |
| 3.1 General Description of EUT .....                                                      | 6         |
| 3.2 Description of Test Modes .....                                                       | 8         |
| 3.2.1 Test Mode Applicability and Tested Channel Detail.....                              | 9         |
| 3.3 Description of Support Units .....                                                    | 10        |
| 3.3.1 Configuration of System under Test .....                                            | 10        |
| 3.4 General Description of Applied Standards .....                                        | 10        |
| <b>4 Test Types and Results .....</b>                                                     | <b>11</b> |
| 4.1 Radiated Emission and Bandedge Measurement.....                                       | 11        |
| 4.1.1 Limits of Radiated Emission and Bandedge Measurement .....                          | 11        |
| 4.1.2 Test Instruments .....                                                              | 12        |
| 4.1.3 Test Procedures.....                                                                | 13        |
| 4.1.4 Deviation from Test Standard .....                                                  | 13        |
| 4.1.5 Test Setup.....                                                                     | 14        |
| 4.1.6 EUT Operating Conditions.....                                                       | 15        |
| 4.1.7 Test Results .....                                                                  | 16        |
| <b>5 Pictures of Test Arrangements.....</b>                                               | <b>20</b> |
| <b>Annex A- Radiated Out of Band Emission (OOBE) Measurement (For U-NII-3 band) .....</b> | <b>21</b> |
| <b>Appendix – Information of the Testing Laboratories .....</b>                           | <b>22</b> |

### Release Control Record

| Issue No.      | Description       | Date Issued   |
|----------------|-------------------|---------------|
| RF181025C10D-2 | Original release. | Jul. 23, 2019 |

## 1 Certificate of Conformity

**Product:** AC2200 WiFi Mesh Router, AC2200 WiFi Mesh Router System

**Brand:** TRENDnet

**Test Model:** TEW-830MDR

**Series Model:** TEW-830MDR2K, TEW-830MDR3K (refer to item 3.1 for more details)

**Sample Status:** Engineering sample

**Applicant:** TRENDnet, Inc.

**Test Date:** Jul. 07, 2019

**Standards:** 47 CFR FCC Part 15, Subpart C (Section 15.247)  
47 CFR FCC Part 15, Subpart E (Section 15.407)  
ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

**Prepared by :** Pettie Chen , **Date:** Jul. 23, 2019  
Pettie Chen / Senior Specialist

**Approved by :** Bruce Chen , **Date:** Jul. 23, 2019  
Bruce Chen / Project Engineer

## 2 Summary of Test Results

| Applied Standard                                           | 47 CFR FCC Part 15, Subpart C (Section 15.247)<br>47 CFR FCC Part 15, Subpart E (Section 15.407) |        |                                                                                   |
|------------------------------------------------------------|--------------------------------------------------------------------------------------------------|--------|-----------------------------------------------------------------------------------|
| FCC Clause                                                 | Test Item                                                                                        | Result | Remarks                                                                           |
| 15.205 / 15.209 /<br>15.247(d)<br>15.407(b)<br>(1/2/3/4/6) | Radiated Emissions                                                                               | Pass   | Meet the requirement of limit.<br>Minimum passing margin is -1.3dB at 5650.00MHz. |

\*For U-NII-3 band compliance with rule part 15.407(b)(4)(i), the OOB test plots were recorded in Annex A.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| Measurement                    | Frequency        | Expanded Uncertainty (k=2) (±) |
|--------------------------------|------------------|--------------------------------|
| Radiated Emissions up to 1 GHz | 9kHz ~ 30MHz     | 3.04 dB                        |
|                                | 30MHz ~ 200MHz   | 3.86 dB                        |
|                                | 200MHz ~ 1000MHz | 3.87 dB                        |
| Radiated Emissions above 1 GHz | 1GHz ~ 18GHz     | 2.29 dB                        |
|                                | 18GHz ~ 40GHz    | 2.29 dB                        |

### 2.2 Modification Record

There were no modifications required for compliance.

### 3 General Information

#### 3.1 General Description of EUT

|                       |                                                                                                                                                                                                                                                                                                                                          |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product               | AC2200 WiFi Mesh Router, AC2200 WiFi Mesh Router System                                                                                                                                                                                                                                                                                  |
| Brand                 | TRENDnet                                                                                                                                                                                                                                                                                                                                 |
| Test Model            | TEW-830MDR                                                                                                                                                                                                                                                                                                                               |
| Series Model          | TEW-830MDR2K, TEW-830MDR3K                                                                                                                                                                                                                                                                                                               |
| Model Difference      | Refer to note                                                                                                                                                                                                                                                                                                                            |
| Sample Status         | Engineering sample                                                                                                                                                                                                                                                                                                                       |
| Power Supply Rating   | 12Vdc (adapter)                                                                                                                                                                                                                                                                                                                          |
| Modulation Type       | CCK, DQPSK, DBPSK for DSSS<br>256QAM, 64QAM, 16QAM, QPSK, BPSK for OFDM                                                                                                                                                                                                                                                                  |
| Modulation Technology | DSSS, OFDM                                                                                                                                                                                                                                                                                                                               |
| Transfer Rate         | 802.11a: 54/48/36/24/18/12/9/6Mbps<br>802.11n: up to 300Mbps<br>802.11ac: up to 867Mbps                                                                                                                                                                                                                                                  |
| Operating Frequency   | 2412~2462MHz, 5180~5240MHz, 5745~5825MHz                                                                                                                                                                                                                                                                                                 |
| Number of Channel     | 2412~2462MHz:<br>802.11b, 802.11g, 802.11n (HT20): 11<br>802.11n (HT40): 7<br>5180~5240MHz:<br>802.11a, 802.11n (HT20), 802.11ac (VHT20): 4<br>802.11n (HT40), 802.11ac (VHT40): 2<br>802.11ac (VHT80): 1<br>5745~5825MHz:<br>802.11a, 802.11n (HT20), 802.11ac (VHT20): 5<br>802.11n (HT40), 802.11ac (VHT40): 2<br>802.11ac (VHT80): 1 |
| Antenna Type          | Refer to Note                                                                                                                                                                                                                                                                                                                            |
| Antenna Connector     | Refer to Note                                                                                                                                                                                                                                                                                                                            |
| Accessory Device      | Adapter                                                                                                                                                                                                                                                                                                                                  |
| Cable Supplied        | NA                                                                                                                                                                                                                                                                                                                                       |

Note:

1. All models are listed as below. Model: TEW-830MDR was chosen for final test.

| Brand    | Model        | Product Name                   | Description           |
|----------|--------------|--------------------------------|-----------------------|
| TRENDnet | TEW-830MDR   | AC2200 WiFi Mesh Router        | For marketing purpose |
|          | TEW-830MDR2K | AC2200 WiFi Mesh Router System |                       |
|          | TEW-830MDR3K | AC2200 WiFi Mesh Router System |                       |

2. The EUT incorporates a MIMO function. Physically, the EUT provides 2 completed transmitters and 2 receivers.

| Modulation Mode  | CDD Mode | Beamforming Mode | Radio                                          |
|------------------|----------|------------------|------------------------------------------------|
| 802.11b          | Support  | Not Support      | Radio 1<br>(IPQ4019 2G)<br>2.4G only           |
| 802.11g          | Support  | Not Support      |                                                |
| 802.11n (HT20)   | Support  | Support          |                                                |
| 802.11n (HT40)   | Support  | Support          |                                                |
| 802.11a          | Support  | Not Support      | Radio 3<br>(QCA9886)<br>5GHz<br>Band 1 only    |
| 802.11n (HT20)   | Support  | Support          |                                                |
| 802.11n (HT40)   | Support  | Support          |                                                |
| 802.11ac (VHT20) | Support  | Support          |                                                |
| 802.11ac (VHT40) | Support  | Support          |                                                |
| 802.11ac (VHT80) | Support  | Support          | Radio 2<br>(IPQ4019 5G)<br>5GHz<br>Band 4 only |
| 802.11a          | Support  | Not Support      |                                                |
| 802.11n (HT20)   | Support  | Support          |                                                |
| 802.11n (HT40)   | Support  | Support          |                                                |
| 802.11ac (VHT20) | Support  | Support          |                                                |
| 802.11ac (VHT40) | Support  | Support          |                                                |
| 802.11ac (VHT80) | Support  | Support          |                                                |

\* The modulation and bandwidth are similar for 802.11n mode for 20MHz/40MHz and 802.11ac mode for 20MHz/40MHz, therefore investigated worst case to representative mode in test report. (Final test mode refer section 3.2.1)

\* For 802.11n and 802.11ac, CDD mode and Beamforming mode are presented in power output test item. For other test items, CDD mode is the worst case for final tests after pretesting.

3. The EUT uses following adapter.

|              |                                                |
|--------------|------------------------------------------------|
| Brand        | JG                                             |
| Model        | ZZU1588-150120-2A                              |
| Input Power  | 100-240Vac~1.5A Max 50-60Hz                    |
| Output Power | 12Vdc, 1.5A                                    |
| Power Line   | 1.5m DC cable without core attached on adapter |

4. The following antennas were provided to the EUT.

| Radio           | 3         |      | 2    |      | 1         |      |
|-----------------|-----------|------|------|------|-----------|------|
| Ant. No.        | 1         | 4    | 2    | 3    | 5         | 6    |
| Frequency (MHz) | 5150-5850 |      |      |      | 2400-2500 |      |
| Peak Gain (dBi) | 4.87      | 5.16 | 5.45 | 5.64 | 3.32      | 4.03 |
| Ant. Type       | PIFA      |      |      |      |           |      |
| Connector       | IPEX      |      |      |      |           |      |

\* The maximum antenna gains of Radio 1, 2, 3 are chosen for final test.

5. Radio 1 & Radio 2 & Radio 3 technologies can transmit at same time.

6. Spurious emission of the simultaneous operation (Radio 1 & Radio 2 & Radio 3) has been evaluated and no non-compliance was found.

### 3.2 Description of Test Modes

#### 2412~2462MHz:

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 1       | 2412MHz   | 7       | 2442MHz   |
| 2       | 2417MHz   | 8       | 2447MHz   |
| 3       | 2422MHz   | 9       | 2452MHz   |
| 4       | 2427MHz   | 10      | 2457MHz   |
| 5       | 2432MHz   | 11      | 2462MHz   |
| 6       | 2437MHz   |         |           |

7 channels are provided for 802.11n (HT40):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 3       | 2422MHz   | 7       | 2442MHz   |
| 4       | 2427MHz   | 8       | 2447MHz   |
| 5       | 2432MHz   | 9       | 2452MHz   |
| 6       | 2437MHz   |         |           |

#### 5180~5240MHz:

4 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 36      | 5180MHz   | 44      | 5220MHz   |
| 40      | 5200MHz   | 48      | 5240MHz   |

2 channels are provided for 802.11n (HT40), 802.11ac (VHT40):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 38      | 5190MHz   | 46      | 5230MHz   |

1 channel is provided for 802.11ac (VHT80):

| Channel | Frequency |
|---------|-----------|
| 42      | 5210MHz   |

#### 5745~5825MHz:

5 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 149     | 5745MHz   | 161     | 5805MHz   |
| 153     | 5765MHz   | 165     | 5825MHz   |
| 157     | 5785MHz   |         |           |

2 channels are provided for 802.11n (HT40), 802.11ac (VHT40):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 151     | 5755MHz   | 159     | 5795MHz   |

1 channel is provided for 802.11ac (VHT80):

| Channel | Frequency |
|---------|-----------|
| 155     | 5775MHz   |

### 3.2.1 Test Mode Applicability and Tested Channel Detail

| EUT Configure Mode | Applicable to |       | Description |
|--------------------|---------------|-------|-------------|
|                    | RE $\geq$ 1G  | RE<1G |             |
| -                  | √             | √     | -           |

Where RE $\geq$ 1G: Radiated Emission above 1GHz & Bandedge Measurement RE<1G: Radiated Emission below 1GHz

Note:

1. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on Z-plane.
2. Radiated emission test items chosen the worst maximum fundamental frequency emission level of 2.4GHz and 5GHz Radio channel.

#### Radiated Emission Test (Above 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure Mode | Radio | Mode             | Tested Channel | Remark |
|--------------------|-------|------------------|----------------|--------|
| -                  | 1     | 802.11g          | 6              | -      |
|                    | 2     | 802.11ac (VHT80) | 155            | -      |
|                    | 3     | 802.11a          | 40             | -      |

#### Radiated Emission Test (Below 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure Mode | Radio | Mode             | Tested Channel | Remark |
|--------------------|-------|------------------|----------------|--------|
| -                  | 1     | 802.11g          | 6              | -      |
|                    | 2     | 802.11ac (VHT80) | 155            | -      |
|                    | 3     | 802.11a          | 40             | -      |

#### Test Condition:

| Applicable to | Environmental Conditions | Input Power  | Tested by  |
|---------------|--------------------------|--------------|------------|
| RE $\geq$ 1G  | 24 deg. C, 64% RH        | 120Vac, 60Hz | Adair Peng |
| RE<1G         | 24 deg. C, 64% RH        | 120Vac, 60Hz | Adair Peng |

### 3.3 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


| ID | Product  | Brand | Model No. | Serial No. | FCC ID           | Remarks |
|----|----------|-------|-----------|------------|------------------|---------|
| A. | Notebook | DELL  | E5410     | 1HC2XM1    | FCC DoC Approved | -       |
| B. | Load     | NA    | NA        | NA         | NA               | -       |
| C. | Flash    | HP    | v250W     | 08         | NA               | -       |

Note:

1. All power cords of the above support units are non-shielded (1.8m).
2. Item A acted as a communication partner to transfer data.

| ID | Descriptions | Qty. | Length (m) | Shielding (Yes/No) | Cores (Qty.) | Remarks |
|----|--------------|------|------------|--------------------|--------------|---------|
| 1. | RJ45, Cat5e  | 1    | 6          | N                  | 0            | -       |
| 2. | RJ45, Cat5e  | 1    | 1.5        | N                  | 0            | -       |

#### 3.3.1 Configuration of System under Test



### 3.4 General Description of Applied Standards

The EUT is a RF Product. According to the specification of the EUT declared by the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C (15.247)**

**FCC Part 15, Subpart E (15.407)**

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

## 4 Test Types and Results

### 4.1 Radiated Emission and Bandedge Measurement

#### 4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 30dB below the highest level of the desired power.

FCC PART 15.209:

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009 ~ 0.490     | 2400/F(kHz)                       | 300                           |
| 0.490 ~ 1.705     | 24000/F(kHz)                      | 30                            |
| 1.705 ~ 30.0      | 30                                | 30                            |
| 30 ~ 88           | 100                               | 3                             |
| 88 ~ 216          | 150                               | 3                             |
| 216 ~ 960         | 200                               | 3                             |
| Above 960         | 500                               | 3                             |

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

Limits of unwanted emission out of the restricted bands

| Applicable To                                                                                    |                                     |                  | Limit                                                                                                                                   |                                                                                                                                             |
|--------------------------------------------------------------------------------------------------|-------------------------------------|------------------|-----------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| 789033 D02 General UNII Test Procedure<br>New Rules v02r01                                       |                                     |                  | Field Strength at 3m                                                                                                                    |                                                                                                                                             |
|                                                                                                  |                                     |                  | PK: 74 (dBµV/m)                                                                                                                         | AV: 54 (dBµV/m)                                                                                                                             |
| Frequency Band                                                                                   | Applicable To                       |                  | EIRP Limit                                                                                                                              | Equivalent Field Strength at 3m                                                                                                             |
| 5150~5250 MHz                                                                                    | 15.407(b)(1)                        |                  | PK: -27 (dBm/MHz)                                                                                                                       | PK: 68.2(dBµV/m)                                                                                                                            |
| 5250~5350 MHz                                                                                    | 15.407(b)(2)                        |                  |                                                                                                                                         |                                                                                                                                             |
| 5470~5725 MHz                                                                                    | 15.407(b)(3)                        |                  |                                                                                                                                         |                                                                                                                                             |
| 5725~5850 MHz                                                                                    | <input checked="" type="checkbox"/> | 15.407(b)(4)(i)  | PK: -27 (dBm/MHz) <sup>*1</sup><br>PK: 10 (dBm/MHz) <sup>*2</sup><br>PK: 15.6 (dBm/MHz) <sup>*3</sup><br>PK: 27 (dBm/MHz) <sup>*4</sup> | PK: 68.2 (dBµV/m) <sup>*1</sup><br>PK: 105.2 (dBµV/m) <sup>*2</sup><br>PK: 110.8 (dBµV/m) <sup>*3</sup><br>PK: 122.2 (dBµV/m) <sup>*4</sup> |
|                                                                                                  | <input type="checkbox"/>            | 15.407(b)(4)(ii) | Emission limits in section 15.247(d)                                                                                                    |                                                                                                                                             |
| <sup>*1</sup> beyond 75 MHz or more above of the band edge.                                      |                                     |                  | <sup>*2</sup> below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above.                                                    |                                                                                                                                             |
| <sup>*3</sup> below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above. |                                     |                  | <sup>*4</sup> from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.                    |                                                                                                                                             |

Note: The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000 \sqrt{30 P}}{3} \mu\text{V/m, where P is the eirp (Watts).}$$

#### 4.1.2 Test Instruments

| Description & Manufacturer               | Model No.                             | Serial No.                                          | Cal. Date                      | Cal. Due                       |
|------------------------------------------|---------------------------------------|-----------------------------------------------------|--------------------------------|--------------------------------|
| Test Receiver<br>ROHDE & SCHWARZ         | ESIB7                                 | 100187                                              | May 30, 2019                   | May 29, 2020                   |
| BILOG Antenna<br>SCHWARZBECK             | VULB9168                              | 9168-171                                            | Nov. 22, 2018                  | Nov. 21, 2019                  |
| HORN Antenna<br>SCHWARZBECK              | 9120D                                 | 209                                                 | Nov. 25, 2018                  | Nov. 24, 2019                  |
| HORN Antenna<br>SCHWARZBECK              | BBHA 9170                             | BBHA9170241                                         | Nov. 25, 2018                  | Nov. 24, 2019                  |
| Loop Antenna<br>TESEQ                    | HLA 6121                              | 45745                                               | Jul. 01, 2019                  | Jun. 30, 2020                  |
| Preamplifier<br>Agilent<br>(Below 1GHz)  | 8447D                                 | 2944A10738                                          | Aug. 21, 2018                  | Aug. 20, 2019                  |
| Preamplifier<br>Agilent<br>(Above 1GHz)  | 8449B                                 | 3008A02465                                          | Mar. 27, 2019                  | Mar. 26, 2020                  |
| RF signal cable<br>HUBER+SUHNER          | SUCOFLEX 104                          | Cable-CH3-03<br>(223653/4)                          | Aug. 21, 2018                  | Aug. 20, 2019                  |
| RF signal cable<br>HUBER+SUHNER&<br>EMCI | SUCOFLEX<br>104&EMC104-SM-SM-8<br>000 | Cable-CH3-03<br>(309224+170907)                     | Aug. 21, 2018                  | Aug. 20, 2019                  |
| RF signal cable<br>WOKEN                 | 8D-FB                                 | Cable-CH3-01                                        | Aug. 21, 2018                  | Aug. 20, 2019                  |
| Software<br>BV ADT                       | ADT_Radiated_<br>V7.6.15.9.5          | NA                                                  | NA                             | NA                             |
| Antenna Tower<br>inn-co GmbH             | MA 4000                               | 013303                                              | NA                             | NA                             |
| Antenna Tower Controller<br>BV ADT       | AT100                                 | AT93021702                                          | NA                             | NA                             |
| Turn Table<br>BV ADT                     | TT100                                 | TT93021702                                          | NA                             | NA                             |
| Turn Table Controller<br>BV ADT          | SC100                                 | SC93021702                                          | NA                             | NA                             |
| Boresight Antenna Fixture                | FBA-01                                | FBA-SIP01                                           | NA                             | NA                             |
| Pre-amplifier<br>(18GHz-40GHz)<br>EMC    | EMC184045B                            | 980175                                              | Nov. 14, 2018                  | Nov. 13, 2019                  |
| USB Wideband Power<br>Sensor<br>KEYSIGHT | U2021XA                               | MY55050005/MY5519<br>0004/MY55190007/MY<br>55210005 | Jul. 17, 2018<br>Jul. 15, 2019 | Jul. 16, 2019<br>Jul. 14, 2020 |

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Chamber 3.

#### 4.1.3 Test Procedures

##### For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

##### For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is  $\geq 1/T$  (Duty cycle < 98%) or 10Hz (Duty cycle  $\geq 98\%$ ) for Average detection (AV) at frequency above 1GHz. (2.4GHz: 802.11g: RBW = 1MHz, VBW = 1kHz; 5GHz: 802.11a: RBW = 1MHz, VBW = 1kHz; 802.11n (HT20): RBW = 1MHz, VBW = 300Hz)
4. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.4 Deviation from Test Standard


No deviation.

#### 4.1.5 Test Setup


##### For Radiated emission below 30MHz



##### For Radiated emission 30MHz to 1GHz



### For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.6 EUT Operating Conditions

- Placed the EUT on the testing table.
- Prepared a notebook to act as a communication partner and placed it outside of testing area.
- The communication partner connected with EUT via a RJ45 cable and ran a test program (provided by manufacturer) to enable EUT under transmission condition continuously at specific channel frequency.
- The communication partner sent data to EUT by command "PING".

#### 4.1.7 Test Results

Above 1GHz data:

Radio 1, 802.11g, CH 6 +

Radio 2, 802.11ac (VHT80), CH 155 +

Radio 3, 802.11a, CH 40

|                 |              |                   |                           |
|-----------------|--------------|-------------------|---------------------------|
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK)<br>Average (AV) |
|-----------------|--------------|-------------------|---------------------------|

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|-----------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 2390.00     | 60.8 PK                 | 74.0           | -13.2       | 1.88 H             | 19                   | 27.8             | 33.0                     |
| 2                                                   | 2390.00     | 48.5 AV                 | 54.0           | -5.5        | 1.88 H             | 19                   | 15.5             | 33.0                     |
| 3                                                   | *2437.00    | 113.7 PK                |                |             | 1.77 H             | 0                    | 80.8             | 32.9                     |
| 4                                                   | *2437.00    | 102.9 AV                |                |             | 1.77 H             | 0                    | 70.0             | 32.9                     |
| 5                                                   | 2483.50     | 60.8 PK                 | 74.0           | -13.2       | 1.79 H             | 15                   | 28.1             | 32.7                     |
| 6                                                   | 2483.50     | 48.2 AV                 | 54.0           | -5.8        | 1.79 H             | 15                   | 15.5             | 32.7                     |
| 7                                                   | 4874.00     | 51.2 PK                 | 74.0           | -22.8       | 1.38 H             | 56                   | 47.9             | 3.3                      |
| 8                                                   | 4874.00     | 41.7 AV                 | 54.0           | -12.3       | 1.38 H             | 56                   | 38.4             | 3.3                      |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |             |                         |                |             |                    |                      |                  |                          |
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 2390.00     | 62.0 PK                 | 74.0           | -12.0       | 2.98 V             | 356                  | 29.0             | 33.0                     |
| 2                                                   | 2390.00     | 49.6 AV                 | 54.0           | -4.4        | 2.98 V             | 356                  | 16.6             | 33.0                     |
| 3                                                   | *2437.00    | 115.3 PK                |                |             | 2.90 V             | 330                  | 82.4             | 32.9                     |
| 4                                                   | *2437.00    | 104.3 AV                |                |             | 2.90 V             | 330                  | 71.4             | 32.9                     |
| 5                                                   | 2483.50     | 62.7 PK                 | 74.0           | -11.3       | 2.99 V             | 342                  | 30.0             | 32.7                     |
| 6                                                   | 2483.50     | 49.7 AV                 | 54.0           | -4.3        | 2.99 V             | 342                  | 17.0             | 32.7                     |
| 7                                                   | 4874.00     | 49.0 PK                 | 74.0           | -25.0       | 2.66 V             | 200                  | 45.7             | 3.3                      |
| 8                                                   | 4874.00     | 39.5 AV                 | 54.0           | -14.5       | 2.66 V             | 200                  | 36.2             | 3.3                      |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |              |                   |                           |
|-----------------|--------------|-------------------|---------------------------|
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK)<br>Average (AV) |
|-----------------|--------------|-------------------|---------------------------|

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|-----------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 5150.00     | 64.3 PK                 | 74.0           | -9.7        | 1.26 H             | 13                   | 60.8             | 3.5                      |
| 2                                                   | 5150.00     | 46.2 AV                 | 54.0           | -7.8        | 1.26 H             | 11                   | 42.7             | 3.5                      |
| 3                                                   | *5200.00    | 113.3 PK                |                |             | 1.29 H             | 29                   | 74.0             | 39.3                     |
| 4                                                   | *5200.00    | 101.3 AV                |                |             | 1.29 H             | 29                   | 62.0             | 39.3                     |
| 5                                                   | 5350.00     | 56.8 PK                 | 74.0           | -17.2       | 1.25 H             | 29                   | 53.1             | 3.7                      |
| 6                                                   | 5350.00     | 43.0 AV                 | 54.0           | -11.0       | 1.25 H             | 29                   | 39.3             | 3.7                      |
| 7                                                   | #5650.00    | 57.6 PK                 | 68.2           | -10.6       | 2.01 H             | 348                  | 53.3             | 4.3                      |
| 8                                                   | *5775.00    | 106.5 PK                |                |             | 1.59 H             | 353                  | 66.5             | 40.0                     |
| 9                                                   | *5775.00    | 95.1 AV                 |                |             | 1.59 H             | 353                  | 55.1             | 40.0                     |
| 10                                                  | #5925.00    | 58.8 PK                 | 68.2           | -9.4        | 1.53 H             | 342                  | 53.9             | 4.9                      |
| 11                                                  | #10400.00   | 57.9 PK                 | 68.2           | -10.3       | 2.09 H             | 303                  | 42.3             | 15.6                     |
| 12                                                  | 11550.00    | 60.4 PK                 | 74.0           | -13.6       | 2.59 H             | 160                  | 43.4             | 17.0                     |
| 13                                                  | 11550.00    | 46.5 AV                 | 54.0           | -7.5        | 2.59 H             | 160                  | 29.5             | 17.0                     |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |             |                         |                |             |                    |                      |                  |                          |
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 5150.00     | 65.2 PK                 | 74.0           | -8.8        | 2.29 V             | 43                   | 61.7             | 3.5                      |
| 2                                                   | 5150.00     | 47.1 AV                 | 54.0           | -6.9        | 2.29 V             | 43                   | 43.6             | 3.5                      |
| 3                                                   | *5200.00    | 116.2 PK                |                |             | 1.90 V             | 12                   | 76.9             | 39.3                     |
| 4                                                   | *5200.00    | 105.1 AV                |                |             | 1.90 V             | 12                   | 65.8             | 39.3                     |
| 5                                                   | 5350.00     | 58.2 PK                 | 74.0           | -15.8       | 1.99 V             | 22                   | 54.5             | 3.7                      |
| 6                                                   | 5350.00     | 44.4 AV                 | 54.0           | -9.6        | 1.99 V             | 22                   | 40.7             | 3.7                      |
| 7                                                   | #5650.00    | <b>66.9 PK</b>          | <b>68.2</b>    | <b>-1.3</b> | <b>1.79 V</b>      | <b>1</b>             | <b>62.6</b>      | <b>4.3</b>               |
| 8                                                   | *5775.00    | 105.5 PK                |                |             | 1.69 V             | 345                  | 65.5             | 40.0                     |
| 9                                                   | *5775.00    | 94.8 AV                 |                |             | 1.49 V             | 345                  | 54.8             | 40.0                     |
| 10                                                  | #5925.00    | 63.5 PK                 | 68.2           | -4.7        | 1.70 V             | 359                  | 58.6             | 4.9                      |
| 11                                                  | #10400.00   | 58.4 PK                 | 68.2           | -9.8        | 2.59 V             | 330                  | 42.8             | 15.6                     |
| 12                                                  | 11550.00    | 59.0 PK                 | 74.0           | -15.0       | 2.82 V             | 266                  | 42.0             | 17.0                     |
| 13                                                  | 11550.00    | 45.4 AV                 | 54.0           | -8.6        | 2.82 V             | 269                  | 28.4             | 17.0                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Below 1GHz data:

Radio 1, 802.11g, CH 6 +

Radio 2, 802.11ac (VHT80), CH 155 +


Radio 3, 802.11a, CH 40

|                 |              |                   |                 |
|-----------------|--------------|-------------------|-----------------|
| Frequency Range | 30MHz ~ 1GHz | Detector Function | Quasi-Peak (QP) |
|-----------------|--------------|-------------------|-----------------|

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|-----------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 70.73       | 26.2 QP                 | 40.0           | -13.8       | 1.99 H             | 329                  | 37.7             | -11.5                    |
| 2                                                   | 94.06       | 24.3 QP                 | 43.5           | -19.2       | 1.99 H             | 283                  | 38.8             | -14.5                    |
| 3                                                   | 261.27      | 26.5 QP                 | 46.0           | -19.5       | 1.50 H             | 106                  | 35.5             | -9.0                     |
| 4                                                   | 321.54      | 26.8 QP                 | 46.0           | -19.2       | 1.00 H             | 139                  | 33.7             | -6.9                     |
| 5                                                   | 605.41      | 29.2 QP                 | 46.0           | -16.8       | 1.50 H             | 314                  | 30.1             | -0.9                     |
| 6                                                   | 842.61      | 33.5 QP                 | 46.0           | -12.5       | 1.99 H             | 59                   | 30.6             | 2.9                      |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20dB below the permissible value to be report.




|                 |              |                   |                 |
|-----------------|--------------|-------------------|-----------------|
| Frequency Range | 30MHz ~ 1GHz | Detector Function | Quasi-Peak (QP) |
|-----------------|--------------|-------------------|-----------------|

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|---------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                               | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                 | 61.01       | 30.6 QP                 | 40.0           | -9.4        | 1.51 V             | 327                  | 40.4             | -9.8                     |
| 2                                                 | 144.61      | 24.1 QP                 | 43.5           | -19.4       | 1.00 V             | 183                  | 33.4             | -9.3                     |
| 3                                                 | 173.78      | 25.5 QP                 | 43.5           | -18.0       | 1.00 V             | 154                  | 35.1             | -9.6                     |
| 4                                                 | 620.96      | 29.7 QP                 | 46.0           | -16.3       | 1.00 V             | 16                   | 30.4             | -0.7                     |
| 5                                                 | 840.67      | 33.7 QP                 | 46.0           | -12.3       | 1.00 V             | 197                  | 30.8             | 2.9                      |
| 6                                                 | 976.77      | 35.6 QP                 | 54.0           | -18.4       | 1.51 V             | 6                    | 30.2             | 5.4                      |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20dB below the permissible value to be report.



## 5 Pictures of Test Arrangements


Please refer to the attached file (Test Setup Photo).

## Annex A- Radiated Out of Band Emission (OOBE) Measurement (For U-NII-3 band)

Radio 1, 802.11g, CH 6 +

Radio 2, 802.11ac (VHT80), CH 155 +

Radio 3, 802.11a, CH 40



## Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

### Linko EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

### Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

### Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---