



SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

FCC RADIO TEST REPORT

Applicant's company	TRENDnet, Inc.
Applicant Address	20675 Manhattan Place, Torrance, CA 90501, USA
FCC ID	XU8THA103AC
Manufacturer's company	TRENDnet, Inc.
Manufacturer Address	20675 Manhattan Place, Torrance, CA 90501, USA

Product Name	AC750 Home Smart Switch with Wireless Extender
Brand Name	TRENDnet
Model No.	THA-103AC
Test Rule Part(s)	47 CFR FCC Part 15 Subpart E § 15.407
Test Freq. Range	5150 ~ 5250 MHz / 5725 ~ 5850 MHz
Received Date	Dec. 03, 2014
Final Test Date	Jan. 16, 2015
Submission Type	Original Equipment

Statement

Test result included is for the IEEE 802.11n and IEEE 802.11a/ac of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.10-2013, 47 CFR FCC Part 15 Subpart E, KDB789033 D02 v01, KDB662911 D01 v02r01, KDB644545 D03 v01.**

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



Table of Contents

1. VERIFICATION OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details.....	3
3.2. Accessories.....	4
3.3. Table for Filed Antenna.....	5
3.4. Table for Carrier Frequencies	6
3.5. Table for Test Modes	7
3.6. Table for Testing Locations.....	9
3.7. Table for Supporting Units	9
3.8. Table for Parameters of Test Software Setting	10
3.9. EUT Operation during Test	10
3.10. Duty Cycle	10
3.11. Test Configurations	11
4. TEST RESULT	14
4.1. AC Power Line Conducted Emissions Measurement.....	14
4.2. 26dB Bandwidth and 99% Occupied Bandwidth Measurement.....	18
4.3. 6dB Spectrum Bandwidth Measurement	29
4.4. Maximum Conducted Output Power Measurement.....	34
4.5. Power Spectral Density Measurement	37
4.6. Radiated Emissions Measurement	46
4.7. Band Edge Emissions Measurement	71
4.8. Frequency Stability Measurement	80
4.9. Antenna Requirements	84
5. LIST OF MEASURING EQUIPMENTS	85
6. MEASUREMENT UNCERTAINTY.....	87
APPENDIX A. TEST PHOTOS	A1 ~ A5
APPENDIX B. MAXIMUM PERMISSIBLE EXPOSURE	B1 ~ B3
APPENDIX C. RADIATED EMISSION CO-LOCATION REPORT	C1 ~ C5


History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR4D0314-02AB	Rev. 01	Initial issue of report	Apr. 07, 2015

1. VERIFICATION OF COMPLIANCE

Product Name : AC750 Home Smart Switch with Wireless Extender
Brand Name : TRENDnet
Model No. : THA-103AC
Applicant : TRENDnet, Inc.
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart E § 15.407

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Dec. 03, 2014 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.



Sam Chen

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart E				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	15.36 dB
4.2	15.407(a)	26dB Spectrum Bandwidth and 99% Occupied Bandwidth	Complies	-
4.3	15.407(e)	6dB Spectrum Bandwidth	Complies	-
4.4	15.407(a)	Maximum Conducted Output Power	Complies	7.72 dB
4.5	15.407(a)	Power Spectral Density	Complies	7.76 dB
4.6	15.407(b)	Radiated Emissions	Complies	3.45 dB
4.7	15.407(b)	Band Edge Emissions	Complies	0.19 dB
4.8	15.407(g)	Frequency Stability	Complies	-
4.9	15.203	Antenna Requirements	Complies	-

3. GENERAL INFORMATION

3.1. Product Details

Items	Description
Product Type	WLAN (2TX, 2RX)
Radio Type	Intentional Transceiver
Power Type	From internal power supply
Modulation	IEEE 802.11a: OFDM IEEE 802.11n/ac: see the below table
Data Modulation	IEEE 802.11a/n: OFDM (BPSK / QPSK / 16QAM / 64QAM) IEEE 802.11ac: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)
Data Rate (Mbps)	IEEE 802.11a: OFDM (6/9/12/18/24/36/48/54) IEEE 802.11n/ac: see the below table
Frequency Range	5150 ~ 5250 MHz / 5725 ~ 5850 MHz
Channel Number	9 for 20MHz bandwidth ; 4 for 40MHz bandwidth 2 for 80MHz bandwidth
Channel Band Width (99%)	Band 1: IEEE 802.11a: 32.56 MHz IEEE 802.11ac MCS0/Nss1 (VHT20): 32.47 MHz IEEE 802.11ac MCS0/Nss1 (VHT40): 39.94 MHz IEEE 802.11ac MCS0/Nss1 (VHT80): 75.83 MHz Band 4: IEEE 802.11a: 33.78 MHz IEEE 802.11ac MCS0/Nss1 (VHT20): 34.47 MHz IEEE 802.11ac MCS0/Nss1 (VHT40): 52.82 MHz IEEE 802.11ac MCS0/Nss1 (VHT80): 76.12 MHz
Maximum Conducted Output Power	Band 1: IEEE 802.11a: 22.28 dBm IEEE 802.11ac MCS0/Nss1 (VHT20): 22.02 dBm IEEE 802.11ac MCS0/Nss1 (VHT40): 20.88 dBm IEEE 802.11ac MCS0/Nss1 (VHT80): 12.69 dBm Band 4: IEEE 802.11a: 21.19 dBm IEEE 802.11ac MCS0/Nss1 (VHT20): 21.13 dBm IEEE 802.11ac MCS0/Nss1 (VHT40): 19.52 dBm IEEE 802.11ac MCS0/Nss1 (VHT80): 14.09 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Items	Description	
Communication Mode	☒ IP Based (Load Based)	☐ Frame Based
Beamforming Function	☐ With beamforming	☒ Without beamforming
Operating Mode	☐ Outdoor access point	
	☒ Indoor access point	
	☐ Fixed point-to-point access points	
	☐ Mobile and portable client devices	

Antenna and Band width

Antenna	Single (TX)		
Band width Mode	20 MHz	40 MHz	80 MHz
IEEE 802.11a	V	X	X
IEEE 802.11n	V	V	X
IEEE 802.11ac	V	V	V

IEEE 11n/ac Spec.

Protocol	Number of Transmit Chains (NTX)	Data Rate / MCS
802.11n (HT20)	1	MCS 0-7
802.11n (HT40)	1	MCS 0-7
802.11ac (VHT20)	1	MCS 0-9/Nss1
802.11ac (VHT40)	1	MCS 0-9/Nss1
802.11ac (VHT80)	1	MCS 0-9/Nss1
Note 1: IEEE Std. 802.11n modulation consists of HT20 and HT40 (HT: High Throughput). Then EUT support HT20 and HT40. Note 2: IEEE Std. 802.11ac modulation consists of VHT20, VHT40, VHT80 and VHT160 (VHT: Very High Throughput). Then EUT support VHT20, VHT40 and VHT80. Note 3: Modulation modes consist of below configuration: HT20/HT40: IEEE 802.11n, VHT20/VHT40/VHT80: IEEE 802.11ac		

3.2. Accessories

N/A

3.3. Table for Filed Antenna

Ant.	Brand	W.Y P/No.	Type	Connector	Gain (dBi)		
					2.4GHz	5GHz Band 1	5GHz Band 4
1	WHA YU	C068-510488-A	Dipole	I-PEX	4.1	-	-
2	WHA YU	C068-510489-A	Dipole	I-PEX	3.5	3.5	4.5

Note: The EUT has two antennas.


Chain 1: Connect to Ant. 1, Chain 2: Connect to Ant. 2.

For 2.4GHz WLAN function (2TX, 2RX):

Chain 1 and Chain 2 could transmit/receive simultaneously.

For 5GHz WLAN function (1TX, 1RX):

Only Chain 2 could transmit/receive simultaneously.



3.4. Table for Carrier Frequencies

There are three bandwidth systems.

For 20MHz bandwidth systems, use Channel 36, 40, 44, 48, 149, 153, 157, 161, 165.

For 40MHz bandwidth systems, use Channel 38, 46, 151, 159.

For 80MHz bandwidth systems, use Channel 42, 155.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
5150~5250 MHz Band 1	36	5180 MHz	44	5220 MHz
	38	5190 MHz	46	5230 MHz
	40	5200 MHz	48	5240 MHz
	42	5210 MHz	-	-
5725~5850 MHz Band 4	149	5745 MHz	157	5785 MHz
	151	5755 MHz	159	5795 MHz
	153	5765 MHz	161	5805 MHz
	155	5775 MHz	165	5825 MHz

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode		Data Rate	Channel	Chain
AC Power Conducted Emission	Normal Link		-	-	-
Max. Conducted Output Power	11a/BPSK	Band 1&4	6Mbps	36/40/48/149/157/165	2
	11ac VHT20	Band 1&4	MCS0/Nss1	36/40/48/149/157/165	2
	11ac VHT40	Band 1&4	MCS0/Nss1	38/46/151/159	2
	11ac VHT80	Band 1&4	MCS0/Nss1	42/155	2
Power Spectral Density	11a/BPSK	Band 1&4	6Mbps	36/40/48/149/157/165	2
	11ac VHT20	Band 1&4	MCS0/Nss1	36/40/48/149/157/165	2
	11ac VHT40	Band 1&4	MCS0/Nss1	38/46/151/159	2
	11ac VHT80	Band 1&4	MCS0/Nss1	42/155	2
26dB Spectrum Bandwidth & 99% Occupied Bandwidth Measurement	11a/BPSK	Band 1&4	6Mbps	36/40/48/149/157/165	2
	11ac VHT20	Band 1&4	MCS0/Nss1	36/40/48/149/157/165	2
	11ac VHT40	Band 1&4	MCS0/Nss1	38/46/151/159	2
	11ac VHT80	Band 1&4	MCS0/Nss1	42/155	2
6dB Spectrum Bandwidth Measurement	11a/BPSK	Band 4	6Mbps	149/157/165	2
	11ac VHT20	Band 4	MCS0/Nss1	149/157/165	2
	11ac VHT40	Band 4	MCS0/Nss1	151/159	2
	11ac VHT80	Band 4	MCS0/Nss1	155	2
Radiated Emission Below 1GHz	Normal Link		-	-	-
Radiated Emission Above 1GHz	11a/BPSK	Band 1&4	6Mbps	36/40/48/149/157/165	2
	11ac VHT20	Band 1&4	MCS0/Nss1	36/40/48/149/157/165	2
	11ac VHT40	Band 1&4	MCS0/Nss1	38/46/151/159	2
	11ac VHT80	Band 1&4	MCS0/Nss1	42/155	2

Band Edge Emission	11a/BPSK	Band 1&4	6Mbps	36/40/48/149/1 57/165	2
	11ac VHT20	Band 1&4	MCS0/Nss1	36/40/48/149/1 57/165	2
	11ac VHT40	Band 1&4	MCS0/Nss1	38/46/151/159	2
	11ac VHT80	Band 1&4	MCS0/Nss1	42/155	2
Frequency Stability	20MHz	Band 1&4	-	40/157	2
	40MHz	Band 1&4	-	38/151	2
	80MHz	Band 1&4	-	42/155	2

Note: VHT20/VHT40 covers HT20/HT40, due to same modulation.

The following test modes were performed for all tests:

For AC Power Line Conducted Emissions test:

Mode 1. EUT (2.4GHz Repeater function with 2.4GHz + 5GHz AP function)

Mode 2. EUT (5GHz Repeater function with 2.4GHz + 5GHz AP function)

Mode 1 is the worst case, so it was selected to record in this test report.

For Radiated Emission below 1GHz test:

There are two modes of EUT, one is EUT standing, and the other is EUT laying, after evaluating, EUT laying has been evaluated to be the worst case, so it was selected to test and record in this test report.

Mode 1. EUT laying (2.4GHz Repeater function with 2.4GHz + 5GHz AP function)

Mode 2. EUT laying (5GHz Repeater function with 2.4GHz + 5GHz AP function)

Mode 1 is the worst case, so it was selected to record in this test report.

For Radiated Emission above 1GHz and Radiated Emission Co-location test:

There are two modes of EUT, one is EUT standing, and the other is EUT laying, after evaluating, EUT standing has been evaluated to be the worst case, so it was selected to test and record in this test report.

For Radiated Emission above 1GHz test:

Mode 1. EUT standing

For Radiated Emission Co-location test:

Mode 1. EUT standing (2.4GHz Repeater function with 2.4GHz + 5GHz AP function)

Mode 2. EUT standing (5GHz Repeater function with 2.4GHz + 5GHz AP function)

For Co-location MPE and Radiated Emission Co-location test:

The EUT could be applied with 2.4GHz Repeater function with 2.4GHz + 5GHz AP function and 5GHz Repeater function with 2.4GHz + 5GHz AP function; therefore Co-location Maximum Permissible Exposure (Please refer to Appendix B) and Radiated Emission Co-location (please refer to Appendix C) tests are added for simultaneously transmit between 2.4GHz Repeater function with 2.4GHz + 5GHz AP function and 5GHz Repeater function with 2.4GHz + 5GHz AP function.

3.6. Table for Testing Locations

Test Site Location					
Address:	No.8, Lane 724, Bo-ai St., Jhubei City, Hsinchu County 302, Taiwan, R.O.C.				
TEL:	886-3-656-9065				
FAX:	886-3-656-9085				
Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH01-CB	SAC	Hsin Chu	262045	IC 4086D	-
CO01-CB	Conduction	Hsin Chu	262045	IC 4086D	-
TH01-CB	OVEN Room	Hsin Chu	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC).

3.7. Table for Supporting Units

For Test Site No: 03CH01-CB (below 1GHz)

Support Unit	Brand	Model	FCC ID
NB	DELL	M1330	DoC
NB	DELL	M1340	DoC
AP	Planex	GW-AP54SGX	KA220030603014-1

For Test Site No: 03CH01-CB (above 1GHz)

Support Unit	Brand	Model	FCC ID
NB	DELL	M1330	DoC
Test fixture	Abocom	PLW522ME	N/A

For Test Site No: CO01-CB

Support Unit	Brand	Model	FCC ID
NB	DELL	E6430	DoC
NB	DELL	E6430	DoC
AP	Planex	GW-AP54SGX	KA220030603014-1

For Test Site No: TH01-CB

Support Unit	Brand	Model	FCC ID
NB	DELL	D420	DoC
Test fixture	Abocom	PLW522ME	N/A

3.8. Table for Parameters of Test Software Setting

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Test Software Version	MT76xxE QA V2.0.2.15							
Mode	Test Frequency (MHz)							
	NCB: 20MHz							
	5180 MHz	5200 MHz	5240 MHz	5745 MHz	5785 MHz	5825 MHz		
802.11a	1B	2B	1E	1B	2B	2B		
802.11ac MCS0/Nss1 VHT20	19	28	1D	1B	2E	1E		
Mode	NCB: 40MHz							
802.11ac MCS0/Nss1 VHT40	5190 MHz		5230 MHz		5755 MHz		5795 MHz	
	11		21		15		22	
Mode	NCB: 80MHz							
802.11ac MCS0/Nss1 VHT80	5210 MHz			5775 MHz				
	0D			13				

3.9. EUT Operation during Test


The EUT was programmed to be in continuously transmitting mode.

3.10. Duty Cycle

Mode	On Time (ms)	On+Off Time (ms)	Duty Cycle (%)	Duty Factor (dB)	1/T Minimum VBW (kHz)
802.11a	1.000	1.000	100.00	0.00	0.01
802.11ac MCS0/Nss1 VHT20	1.000	1.000	100.00	0.00	0.01
802.11ac MCS0/Nss1 VHT40	1.000	1.000	100.00	0.00	0.01
802.11ac MCS0/Nss1 VHT80	1.000	1.000	100.00	0.00	0.01

3.11. Test Configurations


3.11.1. AC Power Line Conduction Emissions Test Configuration



Item	Connection	Shielded	Length
1	Power cable	No	0.8m


3.11.2. Radiation Emissions Test Configuration

Test Configuration: 30MHz~1GHz



Item	Connection	Shielded	Length
1	Power cable	No	1.8m

Test Configuration: above 1GHz



Item	Connection	Shielded	Length
1	Power cable	No	1.8m
2	RJ-45 cable	No	10m

4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product that is designed to connect to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 kHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

4.1.4. Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω . LISN can be placed on top of, or immediately beneath, reference ground plane.
 - (3.1) All other equipment powered from additional LISN(s).
 - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
 - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

4.1.5. Test Deviation


There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	25°C	Humidity	51%
Test Engineer	Kane Liu	Phase	Line
Configuration	Normal Link	Test Mode	Mode 1



	Freq	Level	Over	Limit	Read	LISN	Cable		
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark	Pol/Phase
			dB	dBuV	dBuV	dB	dB		
1	0.15000	34.52	-21.48	56.00	24.59	9.77	0.16	AVERAGE	LINE
2	0.15000	47.71	-18.29	66.00	37.78	9.77	0.16	QP	LINE
3	0.16677	47.73	-17.39	65.12	37.80	9.77	0.16	QP	LINE
4 @	0.16677	39.16	-15.96	55.12	29.23	9.77	0.16	AVERAGE	LINE
5 @	0.19654	47.06	-16.69	63.76	37.12	9.78	0.16	QP	LINE
6 @	0.19654	37.07	-16.68	53.76	27.13	9.78	0.16	AVERAGE	LINE
7	0.36920	27.38	-21.14	48.52	17.43	9.77	0.18	AVERAGE	LINE
8	0.36920	38.55	-19.97	58.52	28.60	9.77	0.18	QP	LINE
9 @	0.46122	39.79	-16.88	56.67	29.84	9.77	0.18	QP	LINE
10 @	0.46122	30.68	-15.99	46.67	20.73	9.77	0.18	AVERAGE	LINE
11	0.48119	36.71	-19.60	56.32	26.76	9.77	0.18	QP	LINE
12	0.48119	26.04	-20.27	46.32	16.09	9.77	0.18	AVERAGE	LINE
13	2.678	21.07	-24.93	46.00	11.07	9.73	0.27	AVERAGE	LINE
14 @	2.678	39.76	-16.24	56.00	29.76	9.73	0.27	QP	LINE

Temperature	25°C	Humidity	51%
Test Engineer	Kane Liu	Phase	Neutral
Configuration	Normal Link	Test Mode	Mode 1



	Freq	Level	Over	Limit	Read	LISN	Cable		
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark	Pol/Phase
			dB	dBuV	dBuV	dB	dB		
1	0.15080	28.44	-27.52	55.96	18.36	9.92	0.16	AVERAGE	NEUTRAL
2	0.15080	45.96	-20.00	65.96	35.88	9.92	0.16	QP	NEUTRAL
3 @	0.16765	48.18	-16.89	65.08	38.10	9.92	0.16	QP	NEUTRAL
4	0.16765	37.21	-17.86	55.08	27.13	9.92	0.16	AVERAGE	NEUTRAL
5 @	0.18838	37.43	-16.67	54.11	27.35	9.92	0.16	AVERAGE	NEUTRAL
6 @	0.18838	48.74	-15.36	64.11	38.66	9.92	0.16	QP	NEUTRAL
7	0.20181	33.91	-19.63	53.54	23.82	9.92	0.17	AVERAGE	NEUTRAL
8 @	0.20181	46.75	-16.79	63.54	36.66	9.92	0.17	QP	NEUTRAL
9	0.28935	41.69	-18.86	60.54	31.60	9.91	0.17	QP	NEUTRAL
10	0.28935	31.51	-19.04	50.54	21.42	9.91	0.17	AVERAGE	NEUTRAL
11	0.30834	30.82	-19.20	50.02	20.73	9.91	0.17	AVERAGE	NEUTRAL
12	0.30834	41.03	-18.99	60.02	30.94	9.91	0.17	QP	NEUTRAL
13	3.058	17.63	-28.37	46.00	7.47	9.88	0.28	AVERAGE	NEUTRAL
14	3.058	34.16	-21.84	56.00	24.00	9.88	0.28	QP	NEUTRAL

Note:

Level = Read Level + LISN Factor + Cable Loss.

4.2. 26dB Bandwidth and 99% Occupied Bandwidth Measurement

4.2.1. Limit

No restriction limits.

4.2.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

26dB Bandwidth	
Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 26dB Bandwidth
RBW	Approximately 1% of the emission bandwidth
VBW	VBW > RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto
99% Occupied Bandwidth	
Spectrum Parameters	Setting
Span	1.5 times to 5.0 times the OBW
RBW	1 % to 5 % of the OBW
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold

4.2.3. Test Procedures

For Radiated 26dB Bandwidth and 99% Occupied Bandwidth Measurement:

1. The transmitter was radiated to the spectrum analyzer in peak hold mode.
2. Measure the maximum width of the emission that is 26 dB down from the peak of the emission.
Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

4.2.4. Test Setup Layout

For Radiated 26dB Bandwidth and 99% Occupied Bandwidth Measurement:

This test setup layout is the same as that shown in section 4.6.4.

4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test


The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of 26dB Bandwidth and 99% Occupied Bandwidth

Temperature	23°C	Humidity	63%
Test Engineer	Mars Lin		


Mode	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
802.11a	5180 MHz	32.87	17.54
	5200 MHz	44.78	32.56
	5240 MHz	35.65	19.80
	5745 MHz	31.74	17.28
	5785 MHz	47.91	33.78
	5825 MHz	47.74	32.91
802.11ac MCS0/Nss1 VHT20	5180 MHz	29.83	17.80
	5200 MHz	48.09	32.47
	5240 MHz	37.48	19.62
	5745 MHz	33.65	18.15
	5785 MHz	49.91	34.47
	5825 MHz	39.57	20.23
802.11ac MCS0/Nss1 VHT40	5190 MHz	42.32	36.76
	5230 MHz	84.20	39.94
	5755 MHz	44.06	36.76
	5795 MHz	98.26	52.82
802.11ac MCS0/Nss1 VHT80	5210 MHz	82.03	75.83
	5775 MHz	100.00	76.12

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11a / Chain 2 / 5180 MHz




Date: 15.JAN.2015 20:09:57

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11a / Chain 2 / 5200 MHz




Date: 15.JAN.2015 20:11:25

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11a / Chain 2 / 5240 MHz




Date: 9 JAN 2015 02:42:15

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11a / Chain 2 / 5745 MHz




Date: 15 JAN 2015 20:12:37

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11a / Chain 2 / 5785 MHz




Date: 15.JAN.2015 20:13:41

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11a / Chain 2 / 5825 MHz




Date: 15.JAN.2015 20:15:01


26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Chain 2 / 5180 MHz



26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Chain 2 / 5200 MHz




26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Chain 2 / 5240 MHz




Date: 9 JAN 2015 02:34:34

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Chain 2 / 5745 MHz




Date: 15 JAN 2015 20:19:47


26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Chain 2 / 5785 MHz




26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Chain 2 / 5825 MHz




26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Chain 2 / 5190 MHz




26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Chain 2 / 5230 MHz




26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Chain 2 / 5755 MHz



26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Chain 2 / 5795 MHz




26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Chain 2 / 5210 MHz



Date: 15.JAN.2015 20:32:21

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Chain 2 / 5775 MHz



Date: 15.JAN.2015 20:33:43

4.3. 6dB Spectrum Bandwidth Measurement

4.3.1. Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

4.3.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer.

6dB Spectrum Bandwidth	
Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RBW	approximately 1% of the emission bandwidth
VBW	VBW > RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.3.3. Test Procedures

For Radiated 6dB Bandwidth Measurement:

1. The transmitter was radiated to the spectrum analyzer in peak hold mode.
2. Test was performed in accordance with KDB789033 D02 v01 for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices - section (C) Emission Bandwidth.
3. Multiple antenna system was performed in accordance with KDB662911 D01 v02r01 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
4. Measured the spectrum width with power higher than 6dB below carrier.

4.3.4. Test Setup Layout

For Radiated 6dB Bandwidth Measurement:

This test setup layout is the same as that shown in section 4.6.4.

4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of 6dB Spectrum Bandwidth


Temperature	23°C	Humidity	63%
Test Engineer	Mars Lin		

Mode	Frequency	6dB Bandwidth (MHz)	Min. Limit (kHz)	Test Result
802.11a	5745 MHz	16.46	500	Complies
	5785 MHz	16.41	500	Complies
	5825 MHz	16.41	500	Complies
802.11ac MCS0/Nss1 VHT20	5745 MHz	17.57	500	Complies
	5785 MHz	17.62	500	Complies
	5825 MHz	17.62	500	Complies
802.11ac MCS0/Nss1 VHT40	5755 MHz	36.41	500	Complies
	5795 MHz	36.41	500	Complies
802.11ac MCS0/Nss1 VHT80	5775 MHz	76.52	500	Complies


Note: All the test values were listed in the report.

For plots, only the channel with worse result was shown.


6 dB Bandwidth Plot on Configuration IEEE 802.11a / Chain 2 / 5785 MHz




6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Chain 2 / 5745 MHz



6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Chain 2 / 5755 MHz



6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Chain 2 / 5775 MHz



4.4. Maximum Conducted Output Power Measurement

4.4.1. Limit

Frequency Band		Limit
☒	5.15~5.25 GHz	
	Operating Mode	
	☐ Outdoor access point	The maximum conducted output power over the frequency band of operation shall not exceed 1 W (30dBm) provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).
	☒ Indoor access point	The maximum conducted output power over the frequency band of operation shall not exceed 1 W (30dBm) provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
	☐ Fixed point-to-point access points	The maximum conducted output power over the frequency band of operation shall not exceed 1 W (30dBm). Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi.
	☐ Mobile and portable client devices	The maximum conducted output power over the frequency band of operation shall not exceed 250 mW (24dBm) provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

☒	5.725~5.85 GHz	The maximum conducted output power over the frequency band of operation shall not exceed 1 W (30dBm). If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power.
---	----------------	--

4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Detector	AVERAGE

4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the power meter.
2. Test was performed in accordance with KDB789033 D02 v01 for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices - section (E) Maximum conducted output power =>3. Measurement using a Power Meter (PM) =>b) Method PM-G (Measurement using a gated RF average power meter).
3. Multiple antenna systems was performed in accordance with KDB662911 D01 v02r01 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
4. When measuring maximum conducted output power with multiple antenna systems, add every result of the values by mathematic formula.

4.4.4. Test Setup Layout



4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of Maximum Conducted Output Power

Temperature	23°C	Humidity	63%
Test Engineer	Mars Lin	Test Date	Jan. 14, 2015

Mode	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
		Chain 2		
802.11a	5180 MHz	18.49	30.00	Complies
	5200 MHz	22.28	30.00	Complies
	5240 MHz	19.76	30.00	Complies
	5745 MHz	17.58	30.00	Complies
	5785 MHz	21.02	30.00	Complies
	5825 MHz	21.19	30.00	Complies
802.11ac MCS0/Nss1 VHT20	5180 MHz	17.78	30.00	Complies
	5200 MHz	22.02	30.00	Complies
	5240 MHz	19.41	30.00	Complies
	5745 MHz	17.65	30.00	Complies
	5785 MHz	21.13	30.00	Complies
	5825 MHz	18.29	30.00	Complies
802.11ac MCS0/Nss1 VHT40	5190 MHz	14.35	30.00	Complies
	5230 MHz	20.88	30.00	Complies
	5755 MHz	15.17	30.00	Complies
	5795 MHz	19.52	30.00	Complies
802.11ac MCS0/Nss1 VHT80	5210 MHz	12.69	30.00	Complies
	5775 MHz	14.09	30.00	Complies

4.5. Power Spectral Density Measurement

4.5.1. Limit

The following table is power spectral density limits and decrease power density limit rule refer to section 4.4.1.

Frequency Band		Limit
☒	5.15~5.25 GHz	
	Operating Mode	
☐	Outdoor access point	17 dBm/MHz
☒	Indoor access point	17 dBm/MHz
☐	Fixed point-to-point access points	17 dBm/MHz
☐	Mobile and portable client devices	11 dBm/MHz
☒	5.725~5.85 GHz	30 dBm/500kHz

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

For 5.15~5.25 GHz

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RBW	1000 kHz
VBW	3000 kHz
Detector	RMS
Trace	AVERAGE
Sweep Time	Auto
Trace Average	100 times

For 5.725~5.85 GHz

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS channel bandwidth.
RBW	$RBW \geq 1/T$
VBW	$VBW \geq 3 RBW$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto couple
Note: If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10\log(500\text{kHz}/RBW)$ to the measured result, whereas $RBW (< 500 \text{ kHz})$ is the reduced resolution bandwidth of the spectrum analyzer set during measurement.	

4.5.3. Test Procedures

For 5.15~5.25 GHz


1. The transmitter output (antenna port) was connected RF switch to the spectrum analyzer.
2. Test was performed in accordance with KDB789033 D02 v01 for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices - section (F) Maximum Power Spectral Density (PSD).
3. Multiple antenna systems was performed in accordance KDB662911 D01 v02r01 in-Band Power Spectral Density (PSD) Measurements (a) Measure and sum the spectra across the outputs.
4. When measuring first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3 and so on up to the Nth output to obtain the value for the first frequency bin of the summed spectrum. The summed spectrum value for each of the other frequency bins is computed in the same way.

For 5.725~5.85 GHz


1. Test procedures refer KDB662911 D01 v02r01 section In-Band Power Spectral Density (PSD) Measurements option (b) Measure and sum spectral maximal across the outputs.
2. Use this procedure when the maximum conducted output power in the fundamental emission is used to demonstrate compliance. The EUT must be configured to transmit continuously at full power over the measurement duration.
3. Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$ (use of a greater number of measurement points than this minimum requirement is recommended).
4. Use the peak marker function to determine the maximum level in any 3 kHz band segment within the fundamental EBW.
5. The measured result of PSD level must add $10\log(500\text{kHz/RBW})$ and the final result should ≤ 30 dBm.

4.5.4. Test Setup Layout

For 5.15~5.25 GHz



For 5.725~5.85 GHz



4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.5.7. Test Result of Power Spectral Density

Temperature	23°C	Humidity	63%
Test Engineer	Mars Lin	Test Date	Jan. 14, 2015

Configuration IEEE 802.11a / Chain 2

Channel	Frequency	Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
36	5180 MHz	5.29	17.00	Complies
40	5200 MHz	9.24	17.00	Complies
48	5240 MHz	6.54	17.00	Complies

Channel	Frequency	Power Density (dBm/MHz)	10log(500kHz/RBW) Factor (dB)	Power Density (dBm/500kHz)	Power Density Limit (dBm/500kHz)	Result
149	5745 MHz	4.20	-3.01	1.19	30.00	Complies
157	5785 MHz	7.60	-3.01	4.59	30.00	Complies
165	5825 MHz	7.79	-3.01	4.78	30.00	Complies

Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Chain 2

Channel	Frequency	Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
36	5180 MHz	4.61	17.00	Complies
40	5200 MHz	8.84	17.00	Complies
48	5240 MHz	6.34	17.00	Complies

Channel	Frequency	Power Density (dBm/MHz)	10log(500kHz/RBW) Factor (dB)	Power Density (dBm/500kHz)	Power Density Limit (dBm/500kHz)	Result
149	5745 MHz	4.16	-3.01	1.15	30.00	Complies
157	5785 MHz	7.92	-3.01	4.91	30.00	Complies
165	5825 MHz	4.83	-3.01	1.82	30.00	Complies

Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Chain 2

Channel	Frequency	Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
38	5190 MHz	-1.75	17.00	Complies
46	5230 MHz	4.82	17.00	Complies

Channel	Frequency	Power Density (dBm/MHz)	10log(500kHz/RBW) Factor (dB)	Power Density (dBm/500kHz)	Power Density Limit (dBm/500kHz)	Result
151	5755 MHz	-1.12	-3.01	-4.13	30.00	Complies
159	5795 MHz	3.18	-3.01	0.17	30.00	Complies

Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Chain 2


Channel	Frequency	Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
42	5210 MHz	-6.69	17.00	Complies

Channel	Frequency	Power Density (dBm/MHz)	10log(500kHz/RBW) Factor (dB)	Power Density (dBm/500kHz)	Power Density Limit (dBm/500kHz)	Result
155	5775 MHz	-5.19	-3.01	-8.20	30.00	Complies


Note: All the test values were listed in the report.

For plots, only the channel with worse result was shown.


Power Density Plot on Configuration IEEE 802.11a / Chain 2 / 5200 MHz




Power Density Plot on Configuration IEEE 802.11a / Chain 2 / 5825 MHz




Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Chain 2 / 5200 MHz




Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Chain 2 / 5785 MHz




Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Chain 2 / 5230 MHz




Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Chain 2 / 5795 MHz



Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Chain 2 / 5210 MHz



Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Chain 2 / 5775 MHz



4.6. Radiated Emissions Measurement

4.6.1. Limit

For transmitters operating in the 5.15-5.25 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

For transmitters operating in the 5.725-5.85 GHz band: all emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an e.i.r.p. of -17 dBm/MHz; for frequencies 10 MHz or greater above or below the band edge, emissions shall not exceed an e.i.r.p. of -27 dBm/MHz.

In addition, In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	40 GHz
RBW / VBW (Emission in restricted band)	1 MHz / 3MHz for Peak, 1 MHz / 1/T for Average
RBW / VBW (Emission in non-restricted band)	1 MHz / 3MHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RBW 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RBW 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RBW 120kHz for QP

4.6.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 1/T VBW for average reading in spectrum analyzer.
7. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
8. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
9. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.6.4. Test Setup Layout


For Radiated Emissions: 9kHz ~30MHz



For Radiated Emissions: 30MHz~1GHz



For Radiated Emissions: Above 1GHz



4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.6.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	26°C	Humidity	68%
Test Engineer	Lucas Huang	Configurations	Normal Link
Test Date	Jan. 06, 2015	Test Mode	Mode 1

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.6.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	26°C	Humidity	68%
Test Engineer	Lucas Huang	Configurations	Normal Link
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna		T/Pos	A/Pos	
	MHz	dBuV/m	dBuV/m	Limit	Level	Loss	Factor	Factor	Pol/Phase	deg	cm	Remark
1	30.00	29.68	40.00	-10.32	41.70	0.41	32.43	20.00	HORIZONTAL	104	300	Peak
2	124.09	30.93	43.50	-12.57	49.89	0.80	32.42	12.66	HORIZONTAL	327	200	Peak
3	289.96	38.17	46.00	-7.83	55.53	1.22	32.28	13.70	HORIZONTAL	56	200	Peak
4	401.51	34.07	46.00	-11.93	48.39	1.43	32.27	16.52	HORIZONTAL	245	100	Peak
5	676.99	34.99	46.00	-11.01	45.96	1.88	32.46	19.61	HORIZONTAL	191	125	Peak
6	819.58	34.36	46.00	-11.64	43.69	2.06	32.19	20.80	HORIZONTAL	155	125	Peak

Vertical



	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna		T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	Limit	Level	Loss	Factor	Factor	Pol/Phase	deg	cm	
1	62.98	35.68	40.00	-4.32	60.82	0.57	32.51	6.80	VERTICAL	145	100	Peak
2	289.96	36.40	46.00	-9.60	53.76	1.22	32.28	13.70	VERTICAL	3	150	Peak
3	320.03	37.91	46.00	-8.09	54.44	1.28	32.28	14.47	VERTICAL	145	100	Peak
4	579.99	36.99	46.00	-9.01	48.84	1.74	32.43	18.84	VERTICAL	137	100	Peak
5	676.99	42.55	46.00	-3.45	53.52	1.88	32.46	19.61	VERTICAL	171	100	Peak
6	814.73	39.92	46.00	-6.08	49.37	2.05	32.25	20.75	VERTICAL	108	150	Peak

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6.9. Results for Radiated Emissions (1GHz~40GHz)

Temperature	26°C	Humidity	68%
Test Engineer	Lucas Huang	Configurations	IEEE 802.11a CH 36 / Chain 2
Test Date	Jan. 08, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	15517.50	45.04	54.00	-8.96	30.66	10.72	34.72	38.38	HORIZONTAL	20	152	Average
2	15546.30	59.35	74.00	-14.65	45.03	10.72	34.73	38.33	HORIZONTAL	20	152	Peak

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	15537.90	59.58	74.00	-14.42	45.24	10.72	34.72	38.34	VERTICAL	310	153	Peak
2	15539.00	46.06	54.00	-7.94	31.72	10.72	34.72	38.34	VERTICAL	310	153	Average

Temperature	26°C	Humidity	68%
Test Engineer	Lucas Huang	Configurations	IEEE 802.11a CH 40 / Chain 2
Test Date	Jan. 08, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	15593.60	59.64	74.00	-14.36	45.36	10.76	34.75	38.27	HORIZONTAL	272	165	Peak
2	15599.30	46.00	54.00	-8.00	31.73	10.76	34.75	38.26	HORIZONTAL	272	165	Average

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	15599.20	47.49	54.00	-6.51	33.21	10.76	34.75	38.27	VERTICAL	360	154	Average
2	15604.10	60.35	74.00	-13.65	46.13	10.76	34.75	38.21	VERTICAL	360	154	Peak

Temperature	26°C	Humidity	68%
Test Engineer	Lucas Huang	Configurations	IEEE 802.11a CH 48 / Chain 2
Test Date	Jan. 08, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	15713.90	44.27	54.00	-9.73	30.17	10.80	34.80	38.10	HORIZONTAL	31	110	Average
2	15723.30	57.85	74.00	-16.15	43.77	10.80	34.80	38.08	HORIZONTAL	31	110	Peak

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	15719.40	46.40	54.00	-7.60	32.32	10.80	34.80	38.08	VERTICAL	360	157	Average
2	15719.80	60.45	74.00	-13.55	46.37	10.80	34.80	38.08	VERTICAL	360	157	Peak

Temperature	26°C	Humidity	68%
Test Engineer	Lucas Huang	Configurations	IEEE 802.11a CH 149 / Chain 2
Test Date	Jan. 08, 2015		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna		T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Pol/Phase	deg	cm	
1	11470.80	41.91	54.00	-12.09	27.95	9.07	35.03	39.92	HORIZONTAL	25	140	Average
2	11482.40	56.00	74.00	-18.00	42.05	9.07	35.03	39.91	HORIZONTAL	25	140	Peak

Vertical

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna		T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Pol/Phase	deg	cm	
1	11469.00	56.27	74.00	-17.73	42.31	9.07	35.03	39.92	VERTICAL	320	122	Peak
2	11471.30	41.88	54.00	-12.12	27.92	9.07	35.03	39.92	VERTICAL	320	122	Average

Temperature	26°C	Humidity	68%
Test Engineer	Lucas Huang	Configurations	IEEE 802.11a CH 157 / Chain 2
Test Date	Jan. 08, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11554.10	55.59	74.00	-18.41	41.73	9.10	35.03	39.79	HORIZONTAL	246	106	Peak
2	11594.40	42.23	54.00	-11.77	28.45	9.10	35.03	39.71	HORIZONTAL	246	106	Average

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11563.60	55.99	74.00	-18.01	42.15	9.10	35.03	39.77	VERTICAL	229	103	Peak
2	11572.20	42.94	54.00	-11.06	29.10	9.10	35.03	39.77	VERTICAL	229	103	Average

Temperature	26°C	Humidity	68%
Test Engineer	Lucas Huang	Configurations	IEEE 802.11a CH 165 / Chain 2
Test Date	Jan. 08, 2015		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna		T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Pol/Phase	deg	cm	
1	11648.70	42.07	54.00	-11.93	28.39	9.12	35.04	39.60	HORIZONTAL	353	102	Average
2	11652.40	56.06	74.00	-17.94	42.39	9.12	35.04	39.59	HORIZONTAL	353	102	Peak

Vertical

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna		T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Pol/Phase	deg	cm	
1	11648.60	42.05	54.00	-11.95	28.34	9.12	35.04	39.63	VERTICAL	36	188	Average
2	11651.40	55.66	74.00	-18.34	42.01	9.12	35.04	39.57	VERTICAL	36	188	Peak

Temperature	26°C	Humidity	68%
Test Engineer	Lucas Huang	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 36 / Chain 2
Test Date	Jan. 08, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	15518.60	44.70	54.00	-9.30	30.33	10.72	34.72	38.37	HORIZONTAL	342	122	Average
2	15541.20	58.81	74.00	-15.19	44.48	10.72	34.73	38.34	HORIZONTAL	342	122	Peak

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	15527.10	44.72	54.00	-9.28	30.38	10.72	34.72	38.34	VERTICAL	4	132	Average
2	15546.50	58.64	74.00	-15.36	44.31	10.72	34.73	38.34	VERTICAL	4	132	Peak

Temperature	26°C	Humidity	68%
Test Engineer	Lucas Huang	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 40 / Chain 2
Test Date	Jan. 08, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	15598.20	45.73	54.00	-8.27	31.46	10.76	34.75	38.26	HORIZONTAL	35	127	Average
2	15599.70	59.14	74.00	-14.86	44.87	10.76	34.75	38.26	HORIZONTAL	35	127	Peak

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	15595.50	47.65	54.00	-6.35	33.37	10.76	34.75	38.27	VERTICAL	356	155	Average
2	15600.00	60.95	74.00	-13.05	46.67	10.76	34.75	38.27	VERTICAL	356	155	Peak

Temperature	26°C	Humidity	68%
Test Engineer	Lucas Huang	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 48 / Chain 2
Test Date	Jan. 08, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	15719.00	44.60	54.00	-9.40	30.51	10.80	34.80	38.09	HORIZONTAL	289	135	Average
2	15729.50	58.34	74.00	-15.66	44.26	10.80	34.80	38.08	HORIZONTAL	289	135	Peak

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	15720.60	46.04	54.00	-7.96	31.96	10.80	34.80	38.08	VERTICAL	360	158	Average
2	15721.30	59.79	74.00	-14.21	45.71	10.80	34.80	38.08	VERTICAL	360	158	Peak

Temperature	26°C	Humidity	68%
Test Engineer	Lucas Huang	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 149 / Chain 2
Test Date	Jan. 08, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11481.60	41.84	54.00	-12.16	27.89	9.07	35.03	39.91	HORIZONTAL	288	149	Average
2	11494.60	55.97	74.00	-18.03	42.03	9.07	35.03	39.90	HORIZONTAL	288	149	Peak

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11471.10	41.86	54.00	-12.14	27.90	9.07	35.03	39.92	VERTICAL	356	116	Average
2	11514.10	55.02	74.00	-18.98	41.08	9.07	35.03	39.90	VERTICAL	356	116	Peak

Temperature	26°C	Humidity	68%
Test Engineer	Lucas Huang	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 157 / Chain 2
Test Date	Jan. 08, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11553.30	55.28	74.00	-18.72	41.42	9.10	35.03	39.79	HORIZONTAL	155	131	Peak
2	11594.40	42.28	54.00	-11.72	28.50	9.10	35.03	39.71	HORIZONTAL	155	131	Average

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11574.80	42.74	54.00	-11.26	28.90	9.10	35.03	39.77	VERTICAL	180	105	Average
2	11576.90	56.33	74.00	-17.67	42.49	9.10	35.03	39.77	VERTICAL	180	105	Peak

Temperature	26°C	Humidity	68%
Test Engineer	Lucas Huang	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 165 / Chain 2
Test Date	Jan. 08, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11648.10	55.84	74.00	-18.16	42.16	9.12	35.04	39.60	HORIZONTAL	287	155	Peak
2	11649.50	42.34	54.00	-11.66	28.66	9.12	35.04	39.60	HORIZONTAL	287	155	Average

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11627.40	41.97	54.00	-12.03	28.26	9.12	35.04	39.63	VERTICAL	359	174	Average
2	11640.00	56.13	74.00	-17.87	42.42	9.12	35.04	39.63	VERTICAL	359	174	Peak

Temperature	26°C	Humidity	68%
Test Engineer	Lucas Huang	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 38 / Chain 2
Test Date	Jan. 08, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	15581.50	55.75	74.00	-18.25	41.49	10.72	34.74	38.28	HORIZONTAL	247	153	Peak
2	15587.40	44.87	54.00	-9.13	30.57	10.76	34.74	38.28	HORIZONTAL	247	153	Average

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	15571.00	59.87	74.00	-14.13	45.62	10.72	34.74	38.27	VERTICAL	194	160	Peak
2	15576.50	44.91	54.00	-9.09	30.66	10.72	34.74	38.27	VERTICAL	194	160	Average

Temperature	26°C	Humidity	68%
Test Engineer	Lucas Huang	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 46 / Chain 2
Test Date	Jan. 08, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	15552.40	59.96	74.00	-14.04	45.64	10.72	34.73	38.33	HORIZONTAL	206	139	Peak
2	15576.30	44.84	54.00	-9.16	30.57	10.72	34.74	38.29	HORIZONTAL	206	139	Average

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	15667.10	44.74	54.00	-9.26	30.61	10.76	34.78	38.15	VERTICAL	297	149	Average
2	15673.90	58.53	74.00	-15.47	44.40	10.76	34.78	38.15	VERTICAL	297	149	Peak

Temperature	26°C	Humidity	68%
Test Engineer	Lucas Huang	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 151 / Chain 2
Test Date	Jan. 08, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11491.50	41.84	54.00	-12.16	27.90	9.07	35.03	39.90	HORIZONTAL	268	120	Average
2	11521.90	55.69	74.00	-18.31	41.79	9.07	35.03	39.86	HORIZONTAL	268	120	Peak

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11504.20	55.61	74.00	-18.39	41.67	9.07	35.03	39.90	VERTICAL	258	126	Peak
2	11513.20	42.79	54.00	-11.21	28.85	9.07	35.03	39.90	VERTICAL	258	126	Average

Temperature	26°C	Humidity	68%
Test Engineer	Lucas Huang	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 159 / Chain 2
Test Date	Jan. 08, 2015		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna		T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	Pol/Phase	deg	cm	
1	11593.90	42.21	54.00	-11.79	28.43	9.10	35.03	39.71	HORIZONTAL	188	151	Average
2	11608.60	55.96	74.00	-18.04	42.21	9.10	35.03	39.68	HORIZONTAL	188	151	Peak

Vertical

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna		T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	Pol/Phase	deg	cm	
1	11599.80	42.24	54.00	-11.76	28.47	9.10	35.03	39.70	VERTICAL	111	160	Average
2	11606.50	56.15	74.00	-17.85	42.38	9.10	35.03	39.70	VERTICAL	111	160	Peak

Temperature	26°C	Humidity	68%
Test Engineer	Lucas Huang	Configurations	IEEE 802.11ac MCS0/Nss1 VHT80 CH 42 / Chain 2
Test Date	Jan. 08, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	15612.20	44.55	54.00	-9.45	30.30	10.76	34.75	38.24	HORIZONTAL	159	141	Average
2	15626.10	58.26	74.00	-15.74	44.04	10.76	34.76	38.22	HORIZONTAL	159	141	Peak

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	15606.40	44.74	54.00	-9.26	30.52	10.76	34.75	38.21	VERTICAL	195	163	Average
2	15607.20	58.96	74.00	-15.04	44.74	10.76	34.75	38.21	VERTICAL	195	163	Peak

Temperature	26°C	Humidity	68%
Test Engineer	Lucas Huang	Configurations	IEEE 802.11ac MCS0/Nss1 VHT80 CH 155 / Chain 2
Test Date	Jan. 08, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11568.10	55.29	74.00	-18.71	41.46	9.10	35.03	39.76	HORIZONTAL	337	161	Peak
2	11574.70	42.13	54.00	-11.87	28.31	9.10	35.03	39.75	HORIZONTAL	337	161	Average

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11566.80	41.99	54.00	-12.01	28.15	9.10	35.03	39.77	VERTICAL	289	113	Average
2	11572.30	55.66	74.00	-18.34	41.82	9.10	35.03	39.77	VERTICAL	289	113	Peak

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.7. Band Edge Emissions Measurement

4.7.1. Limit

For transmitters operating in the 5.15-5.25 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

For transmitters operating in the 5.725-5.85 GHz band: all emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an e.i.r.p. of -17 dBm/MHz; for frequencies 10 MHz or greater above or below the band edge, emissions shall not exceed an e.i.r.p. of -27 dBm/MHz.

In addition, In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.7.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RBW / VBW (Emission in restricted band)	1 MHz / 3MHz for Peak, 1 MHz / 1/T for Average
RBW / VBW (Emission in non-restricted band)	1 MHz / 3MHz for Peak

4.7.3. Test Procedures

- The test procedure is the same as section 4.6.3, only the frequency range investigated is limited to 100MHz around band edges.

4.7.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.6.4.

4.7.5. Test Deviation

There is no deviation with the original standard.

4.7.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.7.7. Test Result of Band Edge and Fundamental Emissions

Temperature	26°C	Humidity	68%
Test Engineer	Lucas Huang	Configurations	IEEE 802.11a CH 36, 40, 48 / Chain 2
Test Date	Jan. 08, 2015		

Channel 36

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5149.86	69.19	74.00	-4.81	64.25	6.13	34.01	35.20	Peak	182	317	VERTICAL
2	5150.00	53.47	54.00	-0.53	48.53	6.13	34.01	35.20	Average	182	317	VERTICAL
3	5182.32	100.11			95.08	6.15	34.08	35.20	Average	182	317	VERTICAL
4	5183.33	109.46			104.43	6.15	34.08	35.20	Peak	182	317	VERTICAL

Item 3, 4 are the fundamental frequency at 5180 MHz.

Channel 40

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5149.13	68.04	74.00	-5.96	63.10	6.13	34.01	35.20	Peak	179	172	VERTICAL
2	5150.00	52.63	54.00	-1.37	47.69	6.13	34.01	35.20	Average	179	172	VERTICAL
3	5201.16	101.50			96.43	6.16	34.11	35.20	Average	179	172	VERTICAL
4	5203.18	111.87			106.80	6.16	34.11	35.20	Peak	179	172	VERTICAL

Item 3, 4 are the fundamental frequency at 5200 MHz.

Channel 48

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5139.58	59.24	74.00	-14.76	54.33	6.13	33.98	35.20	Peak	100	333	VERTICAL
2	5150.00	46.63	54.00	-7.37	41.69	6.13	34.01	35.20	Average	100	333	VERTICAL
3	5240.87	101.40			96.24	6.18	34.18	35.20	Average	100	333	VERTICAL
4	5243.04	110.72			105.54	6.20	34.18	35.20	Peak	100	333	VERTICAL
5	5350.00	47.00	54.00	-7.00	41.52	6.26	34.42	35.20	Average	100	333	VERTICAL
6	5352.17	59.28	74.00	-14.72	53.80	6.26	34.42	35.20	Peak	100	333	VERTICAL

Item 3, 4 are the fundamental frequency at 5240 MHz.

Temperature	26°C	Humidity	68%
Test Engineer	Lucas Huang	Configurations	IEEE 802.11a CH 149, 157, 165 / Chain 2
Test Date	Jan. 08, 2015		

Channel 149

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor		cm	deg	
1	5712.25	65.80	68.20	-2.40	59.69	6.44	34.87	35.20	Peak	171	176	VERTICAL
2	5725.00	77.22	78.20	-0.98	71.08	6.45	34.89	35.20	Peak	171	176	VERTICAL
3	5743.41	107.04			100.89	6.45	34.90	35.20	Peak	171	176	VERTICAL
4	5743.84	98.11			91.96	6.45	34.90	35.20	Average	171	176	VERTICAL

Item 3, 4 are the fundamental frequency at 5745 MHz.

Channel 157

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor		cm	deg	
1	5712.97	60.78	68.20	-7.42	54.67	6.44	34.87	35.20	Peak	203	172	VERTICAL
2	5724.42	62.67	78.20	-15.53	56.53	6.45	34.89	35.20	Peak	203	172	VERTICAL
3	5783.26	109.99			103.80	6.46	34.93	35.20	Peak	203	172	VERTICAL
4	5783.84	100.80			94.61	6.46	34.93	35.20	Average	203	172	VERTICAL
5	5851.74	61.11	78.20	-17.09	54.84	6.49	34.98	35.20	Peak	203	172	VERTICAL
6	5863.18	61.13	68.20	-7.07	54.84	6.50	34.99	35.20	Peak	203	172	VERTICAL

Item 3, 4 are the fundamental frequency at 5785 MHz.

Channel 165

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor		cm	deg	
1	5823.84	100.01			93.78	6.48	34.95	35.20	Average	202	169	VERTICAL
2	5823.99	109.11			102.88	6.48	34.95	35.20	Peak	202	169	VERTICAL
3	5850.14	74.37	78.20	-3.83	68.10	6.49	34.98	35.20	Peak	202	169	VERTICAL
4	5860.00	65.42	68.20	-2.78	59.13	6.50	34.99	35.20	Peak	202	169	VERTICAL

Item 1, 2 are the fundamental frequency at 5825 MHz.

Temperature	26°C	Humidity	68%
Test Engineer	Lucas Huang	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 36, 40, 48 / Chain 2
Test Date	Jan. 08, 2015		

Channel 36

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	5146.09	70.81	74.00	-3.19	66.95	5.92	33.58	31.52	VERTICAL	6	100	Peak
2	5150.00	53.31	54.00	-0.69	49.45	5.92	33.58	31.52	VERTICAL	6	100	Average
3	5176.82	109.00			105.07	5.95	33.57	31.55	VERTICAL	6	100	Peak
4	5177.11	99.28			95.35	5.95	33.57	31.55	VERTICAL	6	100	Average

Item 3, 4 are the fundamental frequency at 5180 MHz.

Channel 40

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	5148.26	70.18	74.00	-3.82	66.32	5.92	33.58	31.52	VERTICAL	2	113	Peak
2	5150.00	53.65	54.00	-0.35	49.79	5.92	33.58	31.52	VERTICAL	2	113	Average
3	5196.82	113.44			109.47	5.97	33.56	31.56	VERTICAL	2	113	Peak
4	5197.11	103.02			99.05	5.97	33.56	31.56	VERTICAL	2	113	Average

Item 3, 4 are the fundamental frequency at 5200 MHz.

Channel 48

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	5147.83	59.73	74.00	-14.27	55.87	5.92	33.58	31.52	VERTICAL	190	112	Peak
2	5150.00	44.91	54.00	-9.09	41.05	5.92	33.58	31.52	VERTICAL	190	112	Average
3	5236.96	112.67			108.64	5.99	33.55	31.59	VERTICAL	190	112	Peak
4	5243.04	102.36			98.33	5.99	33.55	31.59	VERTICAL	190	112	Average
5	5350.00	44.21	54.00	-9.79	39.98	6.06	33.51	31.68	VERTICAL	190	112	Average
6	5350.00	58.44	74.00	-15.56	54.21	6.06	33.51	31.68	VERTICAL	190	112	Peak

Item 3, 4 are the fundamental frequency at 5240 MHz.

Temperature	26°C	Humidity	68%
Test Engineer	Lucas Huang	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 149, 157, 165 / Chain 2
Test Date	Jan. 08, 2015		

Channel 149

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	5712.11	65.03	68.20	-3.17	60.07	6.28	33.38	32.06	VERTICAL	188	102	Peak
2	5725.29	78.00	78.20	-0.20	73.01	6.28	33.37	32.08	VERTICAL	188	102	Peak
3	5742.11	106.55			101.54	6.28	33.37	32.10	VERTICAL	188	102	Peak
4	5744.42	96.65			91.64	6.28	33.37	32.10	VERTICAL	188	102	Average

Item 3, 4 are the fundamental frequency at 5745 MHz.

Channel 157

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	5708.34	66.75	68.20	-1.45	61.81	6.26	33.38	32.06	VERTICAL	184	103	Peak
2	5723.26	67.66	78.20	-10.54	62.67	6.28	33.37	32.08	VERTICAL	184	103	Peak
3	5781.82	112.39			107.30	6.30	33.35	32.14	VERTICAL	184	103	Peak
4	5782.11	101.75			96.66	6.30	33.35	32.14	VERTICAL	184	103	Average
5	5853.18	66.48	78.20	-11.72	61.26	6.33	33.33	32.22	VERTICAL	184	103	Peak
6	5861.45	65.18	68.20	-3.02	59.92	6.35	33.33	32.24	VERTICAL	184	103	Peak

Item 3, 4 are the fundamental frequency at 5785 MHz.

Channel 165

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	5824.42	98.26			93.07	6.33	33.34	32.20	VERTICAL	187	101	Average
2	5825.29	108.52			103.33	6.33	33.34	32.20	VERTICAL	187	101	Peak
3	5850.00	76.92	78.20	-1.28	71.70	6.33	33.33	32.22	VERTICAL	187	101	Peak
4	5861.74	67.39	68.20	-0.81	62.13	6.35	33.33	32.24	VERTICAL	187	101	Peak

Item 1, 2 are the fundamental frequency at 5825 MHz.

Temperature	26°C	Humidity	68%
Test Engineer	Lucas Huang	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 38, 46 / Chain 2
Test Date	Jan. 08, 2015		

Channel 38

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	5150.00	53.81	54.00	-0.19	49.95	5.92	33.58	31.52	VERTICAL	190	126	Average
2	5150.00	68.46	74.00	-5.54	64.60	5.92	33.58	31.52	VERTICAL	190	126	Peak
3	5191.80	92.39			88.43	5.97	33.57	31.56	VERTICAL	190	126	Average
4	5200.20	102.45			98.48	5.97	33.56	31.56	VERTICAL	190	126	Peak

Item 3, 4 are the fundamental frequency at 5190 MHz.

Channel 46

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	5149.00	66.98	74.00	-7.02	63.12	5.92	33.58	31.52	VERTICAL	202	109	Peak
2	5150.00	53.15	54.00	-0.85	49.29	5.92	33.58	31.52	VERTICAL	202	109	Average
3	5228.00	98.50			94.48	5.99	33.55	31.58	VERTICAL	202	109	Average
4	5234.00	108.68			104.65	5.99	33.55	31.59	VERTICAL	202	109	Peak
5	5350.00	45.38	54.00	-8.62	41.15	6.06	33.51	31.68	VERTICAL	202	109	Average
6	5351.00	59.15	74.00	-14.85	54.92	6.06	33.51	31.68	VERTICAL	202	109	Peak

Item 3, 4 are the fundamental frequency at 5230 MHz.

Temperature	26°C	Humidity	68%
Test Engineer	Lucas Huang	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 151, 159 / Chain 2
Test Date	Jan. 08, 2015		

Channel 151

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	5712.00	67.59	68.20	-0.61	62.63	6.28	33.38	32.06	VERTICAL	186	144	Peak
2	5724.00	75.06	78.20	-3.14	70.07	6.28	33.37	32.08	VERTICAL	186	144	Peak
3	5753.00	92.50			87.46	6.30	33.36	32.10	VERTICAL	186	144	Average
4	5765.00	102.73			97.67	6.30	33.36	32.12	VERTICAL	186	144	Peak

Item 3, 4 are the fundamental frequency at 5755 MHz.

Channel 159

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	5713.00	65.79	68.20	-2.41	60.83	6.28	33.38	32.06	VERTICAL	189	128	Peak
2	5724.00	67.14	78.20	-11.06	62.15	6.28	33.37	32.08	VERTICAL	189	128	Peak
3	5794.00	107.25			102.13	6.31	33.35	32.16	VERTICAL	189	128	Peak
4	5797.00	97.06			91.94	6.31	33.35	32.16	VERTICAL	189	128	Average
5	5850.00	73.41	78.20	-4.79	68.19	6.33	33.33	32.22	VERTICAL	189	128	Peak
6	5864.00	67.75	68.20	-0.45	62.49	6.35	33.33	32.24	VERTICAL	189	128	Peak

Item 3, 4 are the fundamental frequency at 5795 MHz.

Temperature	26°C	Humidity	68%
Test Engineer	Lucas Huang	Configurations	IEEE 802.11ac MCS0/Nss1 VHT80 CH 42, 155 / Chain 2
Test Date	Jan. 08, 2015		

Channel 42

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna		T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	Pol/Phase	deg	cm	
1	5148.00	67.00	74.00	-7.00	63.14	5.92	33.58	31.52	VERTICAL	190	113	Peak
2	5150.00	53.42	54.00	-0.58	49.56	5.92	33.58	31.52	VERTICAL	190	113	Average
3	5175.00	87.46			83.53	5.95	33.57	31.55	VERTICAL	190	113	Average
4	5196.00	98.35			94.38	5.97	33.56	31.56	VERTICAL	190	113	Peak
5	5350.00	43.70	54.00	-10.30	39.47	6.06	33.51	31.68	VERTICAL	190	113	Average
6	5386.00	57.66	74.00	-16.34	53.35	6.08	33.49	31.72	VERTICAL	190	113	Peak

Item 3, 4 are the fundamental frequency at 5210 MHz.

Channel 155

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna		T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	Pol/Phase	deg	cm	
1	5709.00	66.72	68.20	-1.48	61.78	6.26	33.38	32.06	VERTICAL	188	129	Peak
2	5721.00	71.38	78.20	-6.82	66.41	6.28	33.37	32.06	VERTICAL	188	129	Peak
3	5740.00	88.68			83.67	6.28	33.37	32.10	VERTICAL	188	129	Average
4	5761.00	99.12			94.06	6.30	33.36	32.12	VERTICAL	188	129	Peak
5	5851.00	64.49	78.20	-13.71	59.27	6.33	33.33	32.22	VERTICAL	188	129	Peak
6	5869.00	63.45	68.20	-4.75	58.18	6.35	33.32	32.24	VERTICAL	188	129	Peak

Item 3, 4 are the fundamental frequency at 5775 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

4.8. Frequency Stability Measurement

4.8.1. Limit

In-band emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

The transmitter center frequency tolerance shall be ± 20 ppm maximum for the 5 GHz band (IEEE 802.11n specification).

4.8.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Entire absence of modulation emissions bandwidth
RBW	10 kHz
VBW	10 kHz
Sweep Time	Auto

4.8.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. EUT have transmitted absence of modulation signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire absence of modulation emissions bandwidth.
4. Set RBW = 10 kHz, VBW = 10 kHz with peak detector and maxhold settings.
5. f_c is declaring of channel frequency. Then the frequency error formula is $(f_c - f)/f_c \times 10^6$ ppm and the limit is less than ± 20 ppm (IEEE 802.11n specification).
6. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value
7. Extreme temperature is $0^\circ\text{C} \sim 40^\circ\text{C}$.

4.8.4. Test Setup Layout



4.8.5. Test Deviation

There is no deviation with the original standard.

4.8.6. EUT Operation during Test

The EUT was programmed to be in continuously un-modulation transmitting mode.

4.8.7. Test Result of Frequency Stability

Temperature	23°C	Humidity	63%
Test Engineer	Mars Lin	Test Date	Jan. 14, 2015

20MHz / Chain 2

Voltage vs. Frequency Stability

Voltage	Measurement Frequency (MHz)	
(V)	5200 MHz	5785 MHz
126.50	5199.9750	5784.9722
110.00	5199.9740	5784.9711
93.50	5199.9730	5784.9700
Max. Deviation (MHz)	0.0270	0.0300
Max. Deviation (ppm)	5.19	5.19

Temperature vs. Frequency Stability

Temperature	Measurement Frequency (MHz)	
(°C)	5200 MHz	5785 MHz
0	5199.9974	5784.9944
10	5199.9851	5784.9823
20	5199.9740	5784.9711
30	5199.9863	5784.9834
40	5199.9986	5784.9957
Max. Deviation (MHz)	0.0260	0.0289
Max. Deviation (ppm)	5.00	5.00

40MHz / Chain 2

Voltage vs. Frequency Stability

Voltage	Measurement Frequency (MHz)	
(V)	5190 MHz	5755 MHz
126.50	5189.9746	5754.9682
110.00	5189.9740	5754.9682
93.50	5189.9730	5754.9672
Max. Deviation (MHz)	0.0270	0.0328
Max. Deviation (ppm)	5.20	5.70

Temperature vs. Frequency Stability

Temperature	Measurement Frequency (MHz)	
(°C)	5190 MHz	5755 MHz
0	5189.9962	5755.0903
10	5189.9851	5754.9793
20	5189.9740	5754.9682
30	5189.9863	5754.9805
40	5190.0093	5754.9928
Max. Deviation (MHz)	0.0260	0.0903
Max. Deviation (ppm)	5.01	15.69

80MHz / Chain 2

Voltage vs. Frequency Stability

Voltage	Measurement Frequency (MHz)	
(V)	5210 MHz	5775 MHz
126.50	5209.9764	5774.9752
110.00	5209.9740	5774.9711
93.50	5209.9728	5774.9702
Max. Deviation (MHz)	0.0272	0.0298
Max. Deviation (ppm)	5.22	5.16

Temperature vs. Frequency Stability

Temperature	Measurement Frequency (MHz)	
(°C)	5210 MHz	5775 MHz
0	5209.9898	5774.9921
10	5209.9808	5774.9812
20	5209.9740	5774.9711
30	5209.9813	5774.9824
40	5209.9944	5774.9934
Max. Deviation (MHz)	0.0260	0.0289
Max. Deviation (ppm)	4.99	5.00

4.9. Antenna Requirements

4.9.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.9.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100355	9kHz ~ 2.75GHz	Apr. 23, 2014	Conduction (CO01-CB)
LISN	Schwarzbeck	NSLK 8127	8127650	9kHz ~ 30MHz	Nov. 17, 2014	Conduction (CO01-CB)
LISN	Schwarzbeck	NSLK 8127	8127478	9kHz ~ 30MHz	Nov. 17, 2014	Conduction (CO01-CB)
COND Cable	Woken	Cable	01	150kHz ~ 30MHz	Dec. 04, 2014	Conduction (CO01-CB)
Software	Audix	E3	5.410e	-	N.C.R.	Conduction (CO01-CB)
Signal analyzer	R&S	FSV40	100979	9kHz~40GHz	Dec.12, 2014	Conducted (TH01-CB)
Temp. and Humidity Chamber	Ten Billion	TTH-D3SP	TBN-931011	-30~100 degree	Jun. 03, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-7	-	1 GHz – 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-8	-	1 GHz – 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-9	-	1 GHz – 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-10	-	1 GHz – 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-11	-	1 GHz – 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
Power Sensor	Anritsu	MA2411B	1126203	300MHz~40GHz	Oct. 06, 2014	Conducted (TH01-CB)
Power Meter	Anritsu	ML2495A	1210004	300MHz~40GHz	Oct. 06, 2014	Conducted (TH01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	May 26, 2014	Radiation (03CH01-CB)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Jul. 28, 2014	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz~18GHz	Oct. 28, 2014	Radiation (03CH01-CB)
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Aug. 22, 2014	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Nov. 15, 2014	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02009	1GHz ~ 26.5GHz	Dec. 17, 2014	Radiation (03CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26GHz ~ 40GHz	Nov. 25, 2014	Radiation (03CH01-CB)
Spectrum Analyzer	R&S	FSP40	100080	9kHz ~ 40GHz	Oct. 15, 2014	Radiation (03CH01-CB)
EMI Test Receiver	R&S	ESR26	101289	9kHz~26GHz	Aug. 22, 2014	Radiation (03CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N.C.R.	Radiation (03CH01-CB)
Antenna Mast	INN CO	CO 2000	N/A	1 m - 4 m	N.C.R.	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz - 1 GHz	Nov. 15, 2014	Radiation (03CH01-CB)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
RF Cable-high	Woken	High Cable-1	N/A	1 GHz – 26.5 GHz	Nov. 15, 2014	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-2	N/A	1 GHz – 26.5 GHz	Nov. 15, 2014	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-3	N/A	1 GHz - 40 GHz	Nov. 15, 2014	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-4	N/A	1 GHz - 40 GHz	Nov. 15, 2014	Radiation (03CH01-CB)

Note: Calibration Interval of instruments listed above is one year.

N.C.R. means Non-Calibration required.

6. MEASUREMENT UNCERTAINTY

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	2.4 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1,000MHz)	3.6 dB	Confidence levels of 95%
Radiated Emission (1GHz ~ 18GHz)	3.7 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	3.5 dB	Confidence levels of 95%
Conducted Emission	1.7 dB	Confidence levels of 95%