

Model: KC.IA.00509**Antenna Specification****1. Application:**

This application shall apply for antenna unit which shall be used such as automotive, conventional communications, smart home, etc..

2. Electrical Specification:

Those specifications were specially defined for customer's model, and all characteristics were measured under the model's handset testing jig .

2-1. Frequency Band:

Frequency Band	MHz
WiFi	2400-2500/5150-5850MHz

2-2. Impedance

50 ohm nominal

2-3. VSWR**2-3-1. Measurement frequency points and VSWR value**


Frequency Band(MHz)	2400	2500	5150	5850
Typical Value: (VSWR)	1.5	1.2	1.9	1.9

UNLESS OTHER SPECIFIED TOLERANCES ON :		 TOXU TECHNOLOGY CO., LTD.
X=±	X.X=±	
ANGLES=±	HOLEDIA=±	
SCALE :	UNIT : mm	Add: No. 52, Xikeng Road, Xinhe Community, Fucheng Street, Longhua District, Shenzhen
DRAWN BY: LI	CHECKED BY: YS	
DESIGNED BY: De wen	APPROVED BY: YS	
TITLE : KC.IA.00509 Antenna Specification		SPEC REV.
		P0

2-3-4 Measuring Method

1. A 50Ω coaxial cable is connected to the antenna. Then this cable is connected to a network analyzer to measure the VSWR.
2. Keeping this jig away from metal at least 20 cm

2-3-5 Picture




UNLESS OTHER SPECIFIED TOLERANCES ON : X=± X.X=± X.XX=± ANGLES=± HOLEDIA=±		TOXU 同讯技术 TOXU TECHNOLOGY CO., LTD. Add: No. 52, Xikeng Road, Xinhe Community, Fucheng Street, Longhua District, Shenzhen
SCALE :	UNIT : mm	
DRAWN BY: LI	CHECKED BY: YS	
DESIGNED BY: De wen	APPROVED BY: YS	
TITLE : KC.IA.00509 Antenna Specification		SPEC REV. P0

2-4. Efficiency and Gain

4-5.1 Measure method

1. Using a low loss coaxial cable to link a standard handset jig
2. Fixed this handset jig on chamber's rotator plane
3. Linking jig into network analyzer port and using a probing horn antenna to collect data.
4. Using another standard gain horn antenna to calibrated those data

4-5.2 Chamber definition






1. An anechoic chamber (7mx4mx3m) which satisfied far-field condition was applied to avoid multi-path effect
2. The quite room region is 40cmx40cmx40cm at the center of rotator
3. The distance between DUT and standard antenna is 4.38 m
4. Probing antenna (9120D horn antenna) and standard gain horn antenna (BBHA9120 LPF 700MHz ~6GHz)

UNLESS OTHER SPECIFIED TOLERANCES ON :		 同讯技术	TOXU TECHNOLOGY CO., LTD.
X=±	X.X=±		
ANGLES=±		HOLEDIA=±	
SCALE :	UNIT : mm	Add: No. 52, Xikeng Road, Xinhe Community, Fucheng Street, Longhua District, Shenzhen	
DRAWN BY: LI	CHECKED BY: YS		
DESIGNED BY: De wen	APPROVED BY: YS		
TITLE : KC.IA.00509 Antenna Specification			SPEC REV.
			P0


2-4-1 Efficiency and Gain and 3D Date

Frequency/Mhz	MaxGain/dBi	Efficiency / %	Frequency/Mhz	MaxGain/dBi	Efficiency / %
2400	1. 81	36. 73	5330	2. 23	59. 02
2410	2. 4	39. 9	5360	2. 21	60. 95
2420	1. 56	36. 98	5390	2. 19	59. 29
2430	1. 9	37. 5	5420	2. 16	58. 88
2440	1. 62	38. 46	5450	2. 2	61. 66
2450	1. 05	36. 81	5480	2. 18	57. 94
2460	0. 75	35. 73	5510	2. 16	62. 23
2470	0. 36	34. 99	5540	2. 16	61. 94
2480	0. 91	35. 65	5570	2. 28	59. 29
2490	0. 15	33. 73	5600	2. 28	55. 85
2500	0. 52	34. 67	5630	2. 26	57. 02
			5660	1. 78	55. 34
5150	1. 34	59. 43	5690	1. 83	53. 95
5180	1. 78	62. 09	5720	2. 24	56. 89
5210	1. 94	60. 95	5750	2. 4	56. 1
5240	1. 75	59. 7	5780	2. 68	58. 61
5270	1. 91	57. 15	5810	2. 82	56. 62
5300	1. 96	58. 08	5840	2. 92	60. 12

UNLESS OTHER SPECIFIED TOLERANCES ON :			TOXU TECHNOLOGY CO., LTD.
X=± X.X=± X.XX=± ANGLES=± HOLEDIA=±			
SCALE :	UNIT : mm	Add: No. 52, Xikeng Road, Xinhe Community, Fucheng Street, Longhua District, Shenzhen	
DRAWN BY: LI	CHECKED BY: YS		
DESIGNED BY: De wen	APPROVED BY: YS		
TITLE : KC.IA.00509 Antenna Specification			SPEC REV.
			P0



天线位置



UNLESS OTHER SPECIFIED TOLERANCES ON :

$X = \pm$ $X.X = \pm$ $X.XX = \pm$

ANGLES = $\pm$ HOLEDIA = $\pm$

SCALE :

UNIT : mm

DRAWN BY: LI

CHECKED BY: YS

DESIGNED BY: De wen

APPROVED BY: YS

TOXU
同讯技术

TOXU TECHNOLOGY CO., LTD.

Add: No. 52, Xikeng Road, Xinhe Community, Fucheng Street, Longhua District, Shenzhen

TITLE : KC.IA.00509 Antenna Specification


SPEC REV.

P0

3. Mechanical Specification:

3-1. Mechanical Configuration (Unit: mm)

The appearance of the antenna is according to drawing




UNLESS OTHER SPECIFIED TOLERANCES ON : X=± X.X=± X.XX=± ANGLES=± HOLEDIA=±		TOXU 同讯技术 TOXU TECHNOLOGY CO., LTD. Add: No. 52, Xikeng Road, Xinhe Community, Fucheng Street, Longhua District, Shenzhen
SCALE :	UNIT : mm	
DRAWN BY: LI	CHECKED BY: YS	
DESIGNED BY: De wen	APPROVED BY: YS	
TITLE : KC.IA.00509 Antenna Specification		SPEC REV. P0

4 .Packaging specification:

Product number: xxxxx			
Product model: xxxxx			
一、 Label requirements:			
Customer	xxx		
supplier	xxxxxx		
Material coding	xx		
Product model	xx		
Number	XXX PCS	Factory date	X X X
Remarks			
二、 Boxing:			
Job description:			
1. Inner packaging:			
XXpcs A bag			
2. External packaging:			
Xx PCS ;			
3. Matters needing attention:			
a. Whether to add partition and pearl cotton;			
b. Label attachments, such as ROHS, etc.;			

PE 袋



纸箱

UNLESS OTHER SPECIFIED TOLERANCES ON :		TOXU 同讯技术	TOXU TECHNOLOGY CO., LTD.
X=±	X.X=±		
ANGLES=±		HOLEDIA=±	
SCALE :	UNIT : mm	Add: No. 52, Xikeng Road, Xinhe Community, Fucheng Street, Longhua District, Shenzhen	
DRAWN BY: LI	CHECKED BY: YS		
DESIGNED BY: De wen	APPROVED BY: YS		
TITLE : KC.IA.00509 Antenna Specification			SPEC REV.
			P0