

FCC ID: XUJTSEN5S

Maximum Permissible Exposure (MPE)

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 * P * G}}{d}$$

$$\text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 * P * G}{377 * D^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

Measurement Result

SRD:

Operation Frequency: FSK: 315 MHz/433.92MHz

Antenna Type: Trapezoidal spring Antenna

Antenna gain: 433.92MHz:-17.15 dBi

315MHz:-19.89 dBi

R=20cm

Transmit power:

Frequency (MHz)	Max Peak level (dBuV/m)	EIRP power (dBm)
433.92	76.37	-18.89
315	69.48	-25.78

$EIRP = E - 104.8 + 20 \log(D)$

Channel Freq. (MHz)	ANT	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result (mW/cm2)	Power density Limits (mW/cm2)
			(dBm)		tune-up power		Gain			
					(dBm)	(mW)	(dBi)	Numeric		
433.92	ANT1	FSK	-18.89	-18±1	-17	0.020	-17.15	0.02	0.00000008	0.29
315	ANT1	FSK	-25.78	-25±1	-24	0.004	-19.89	0.01	0.00000001	0.21

Conclusion:

For the max result : $0.00000008 \leq 0.21$ for Max Power Density, compliance RF exposure.

Signature: 

Date: 2026-01-16

NAME AND TITLE (Please print or type): alex li/Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, People's Republic of China