RADIO TEST REPORT
FCC ID: XUJWO0806A

Product: AUTO Smart Diagnostic Tool

Trade Mark: LAUNCH

Model No.: X-431 PRO ELITE V2

Family Model: X-431 PROS ELITE V2, X-431 PRO STAR V2, OADD-WO0806x(x=A~Z, indicates configuration difference)

Report No.: N26051100109E

Issue Date: Jul. 21, 2026

Prepared for

Launch Tech Co., Ltd.

No.4012, Launch Industrial Park, North Wuhe Rd, Bantian Street, Longgang District, Shenzhen, Guangdong, 518129, China.

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

No. 24 Xinfa East Road Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, China

Tel. 0755-23200050 Website: http://www.ntek.org.cn

TABLE OF CONTENTS

1 TEST RESULT CERTIFICATION 3

2 SUMMARY OF TEST RESULTS 4

3 FACILITIES AND ACCREDITATIONS 5

3.1 FACILITIES 5
3.2 LABORATORY ACCREDITATIONS AND LISTINGS 5
3.3 MEASUREMENT UNCERTAINTY 5

4 GENERAL DESCRIPTION OF EUT 6

5 DESCRIPTION OF TEST MODES 8

6 SETUP OF EQUIPMENT UNDER TEST 9

6.1 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM 9
6.2 SUPPORT EQUIPMENT 10
6.3 EQUIPMENTS LIST FOR ALL TEST ITEMS 11

7 TEST REQUIREMENTS 13

7.1 CONDUCTED EMISSIONS TEST 13
7.2 RADIATED SPURIOUS EMISSION 20
7.3 NUMBER OF HOPPING CHANNEL 42
7.4 HOPPING CHANNEL SEPARATION MEASUREMENT 43
7.5 AVERAGE TIME OF OCCUPANCY (DWELL TIME) 44
7.6 20DB BANDWIDTH TEST 46
7.7 PEAK OUTPUT POWER 47
7.8 CONDUCTED BAND EDGE MEASUREMENT 48
7.9 SPURIOUS RF CONDUCTED EMISSION 49
7.10 ANTENNA APPLICATION 50
7.11 FREQUENCY HOPPING SYSTEM (FHSS) EQUIPMENT REQUIREMENTS 51

8 TEST RESULTS 52

8.1 DWELL TIME 52
8.2 MAXIMUM CONDUCTED OUTPUT POWER 62
8.3 -20DB BANDWIDTH 68
8.4 OCCUPIED CHANNEL BANDWIDTH 74
8.5 CARRIER FREQUENCIES SEPARATION 80
8.6 NUMBER OF HOPPING CHANNEL 86
8.7 BAND EDGE 89
8.8 BAND EDGE(HOPPING) 96
8.9 CONDUCTED RF SPURIOUS EMISSION 103

1 TEST RESULT CERTIFICATION

Applicant's name	Launch Tech Co., Ltd.
Address.....	No.4012, Launch Industrial Park, North Wuhe Rd, Bantian Street, Longgang District, Shenzhen, Guangdong, 518129, China.
Manufacturer's Name	Launch Tech Co., Ltd.
Address.....	No.4012, Launch Industrial Park, North Wuhe Rd, Bantian Street, Longgang District, Shenzhen, Guangdong, 518129, China.
Product description	
Product name	AUTO Smart Diagnostic Tool
Trade Mark.....	LAUNCH
Model and/or type reference	X-431 PRO ELITE V2
Family Model	X-431 PROS ELITE V2, X-431 PRO STAR V2, OADD-WO0806x(x=A~Z, indicates configuration difference)
Test Sample number.....	S2512110207-1# S2605110319-1#
Date (s) of performance of tests .	Dec. 08, 2025 ~ Jan. 05, 2026 May. 11, 2026 ~ Jul. 21, 2026

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD/ TEST PROCEDURE	TEST RESULT
FCC 47 CFR Part 2, Subpart J FCC 47 CFR Part 15, Subpart C ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 KDB 558074 D01 15.247 Meas Guidance v05r02	Complied

This device described above has been tested by Shenzhen NTEK Testing Technology Co., Ltd., and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.
This report shall not be reproduced except in full, without the written approval of Shenzhen NTEK Testing Technology Co., Ltd., this document may be altered or revised by Shenzhen NTEK Testing Technology Co., Ltd., personnel only, and shall be noted in the revision of the document.
The test results of this report relate only to the tested sample identified in this report.

Note: A Part of test data of this report are based on the original test report N25120800412E, dated by Jan. 05, 2026.

Prepared By :	Reviewed By :	Approved By :
Allen Liu	Aaron Cheng	Alex Li
(Project Engineer)	(Supervisor)	(Manager)

2 SUMMARY OF TEST RESULTS

FCC Part15 (15.247), Subpart C			
Standard Section	**Test Item**	**Verdict**	**Remark**
15.207	Conducted Emission	PASS	
15.209 (a) 15.205 (a)	Radiated Spurious Emission	PASS	
15.247(a)(1)	Hopping Channel Separation	PASS	
15.247(b)(1)	Peak Output Power	PASS	
15.247(a)(iii)	Number of Hopping Frequency	PASS	
15.247(a)(iii)	Dwell Time	PASS	
15.247(a)(1)	Bandwidth	PASS	
15.247 (d)	Band Edge Emission	PASS	
15.247 (d)	Spurious RF Conducted Emission	PASS	
15.203	Antenna Requirement	PASS	

Remark:
1. “N/A” denotes test is not applicable in this Test Report.
2. All test items were verified and recorded according to the standards and without any deviation during the test.

3 FACILITIES AND ACCREDITATIONS

3.1 FACILITIES

All measurement facilities used to collect the measurement data are located at
No. 24 Xinfa East Road Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, China.
The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

3.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

CNAS-Lab.	:	The Certificate Registration Number is L5516.
IC-Registration		The Certificate Registration Number is 9270A. CAB identifier:CN0074
FCC- Accredited		Test Firm Registration Number: 463705. Designation Number: CN1184
A2LA-Lab.		The Certificate Registration Number is 4298.01 This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated 8 January 2009).
Name of Firm	:	Shenzhen NTEK Testing Technology Co., Ltd.
Site Location	:	No. 24 Xinfa East Road Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, China.

3.3 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	±2.80dB
2	RF power, conducted	±0.16dB
3	Spurious emissions, conducted	±0.21dB
4	All emissions, radiated(30MHz~1GHz)	±2.64dB
5	All emissions, radiated(1GHz~6GHz)	±2.40dB
6	All emissions, radiated(＞6GHz)	±2.52dB
7	Temperature	±0.5°C
8	Humidity	±2%
9	All emissions, radiated(9KHz~30MHz)	±6dB
10	Occupied bandwidth	±4.7%
11	Dwell time	±5.4%

4 GENERAL DESCRIPTION OF EUT

Product Feature and Specification	
Equipment	AUTO Smart Diagnostic Tool
Trade Mark	LAUNCH
FCC ID	XUJWO0806A
Model No.	X-431 PRO ELITE V2
Family Model	X-431 PROS ELITE V2, X-431 PRO STAR V2, OADD-WO0806x(x=A~Z, indicates configuration difference)
Model Difference	All models are the same circuit and RF module, except for the color of the rubber sleeve or shell.
Operating Frequency	2402MHz~2480MHz
Modulation	GFSK, π/4-DQPSK, 8-DPSK
Number of Channels	79 Channels
Antenna Type	FPC Antenna
Antenna Gain	3.86 dBi
Adapter1	Model: XDJ361R-050500 Input: 100-240V~50/60Hz 0.9A Output: 5.0V⎓5A, 25.0W Manufacturer: Shenzhen Xindejia Electronic Technology Co.. Ltd
Adapter2	Model:GME36F-050500FXR Input: 100-240V~50/60Hz 0.8A Output: 5.0V⎓5A, 25.0W Manufacturer:GME Technology(Shenzhen) Co.,Ltd.
Adapter3	Model: BI36L-050500-I Input: 100-240V~50/60Hz 1.2A Output: 5.0V⎓5A, 25.0W Manufacturer: Dong Guan Royal Intelligent Co., Ltd.
Battery	DC 3.7V, 6000mA, 22.2Wh
Power supply	DC 3.7V from battery or DC 5V from adapter.
HW Version	N/A
SW Version	N/A

Note 1: Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.
Note 2: The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.

Revision History

Report No.	Version	Description	Issued Date
N25120800412E	Rev.01	Initial issue of report	Jan. 05, 2026
N26051100109E	Rev.02	Updated radiation, spurious , band edges data. Updated antenna and C63.10 Version	Jul. 21, 2026

5 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.
The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (1Mbps for GFSK modulation; 2Mbps for π/4-DQPSK modulation; 3Mbps for 8-DPSK modulation) were used for all test.
The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement –X, Y, and Z-plane. The X-plane results were found as the worst case and were shown in this report.

Carrier Frequency and Channel list:

Channel	Frequency(MHz)
0	2402
1	2403
…	…
39	2441
40	2442
…	…
77	2479
78	2480

Note: fc=2402MHz+k×1MHz k=0 to 78
The following summary table is showing all test modes to demonstrate in compliance with the standard.

For AC Conducted Emission	
Final Test Mode	Description
Mode 1	normal link mode

Note: AC power line Conducted Emission was tested under maximum output power.

For Radiated Test Cases	
Final Test Mode	Description
Mode 1	normal link mode
Mode 2	CH00(2402MHz)
Mode 3	CH39(2441MHz)
Mode 4	CH78(2480MHz)

Note: For radiated test cases, the worst mode data rate 3Mbps was reported only, because this data rate has the highest RF output power at preliminary tests, and no other significantly frequencies found in conducted spurious emission.

For Conducted Test Cases	
Final Test Mode	Description
Mode 2	CH00(2402MHz)
Mode 3	CH39(2441MHz)
Mode 4	CH78(2480MHz)
Mode 5	Hopping mode

Note: The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.

6 SETUP OF EQUIPMENT UNDER TEST

6.1 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM

For AC Conducted Emission Mode



For Radiated Test Cases



For Conducted Test Cases



Note: 1. The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

2. EUT built-in battery-powered, the battery is fully-charged.

6.2 SUPPORT EQUIPMENT

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Manufacturer	Model/Type No.	Series No.	Note
AE-1	Adapter	Shenzhen Xindejia Electronic Technology Co., Ltd	XDJ361R-050500	N/A	
AE-1	Adapter	GME Technology(Shenzhen) Co.,Ltd.	GME36F-050500 FXR	N/A	
AE-1	Adapter	Dong Guan Royal Intelligent Co., Ltd.	BI36L-050500-I	N/A	

Item	Cable Type	Shielded Type	Ferrite Core	Length
C-1	DC Cable	NO	NO	1.0m
C-2	RF Cable	YES	NO	0.1m

Notes:

(1) The support equipment was authorized by Declaration of Confirmation.
(2) For detachable type I/O cable should be specified the length in cm in『Length』column.
(3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

6.3 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation& Conducted Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4440A	MY41000130	2025.04.17 2026.04.15	2026.04.16 2027.04.14	1 year
2	Spectrum Analyzer	Agilent	N9020A	MY49100060	2025.04.17 2026.04.15	2026.04.16 2027.04.14	1 year
3	Spectrum Analyzer	R&S	FSV40	101417	2025.04.17 2026.04.15	2026.04.16 2027.04.14	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200983705	2024.04.26	2027.04.25	3 year
5	Horn Antenna	EM	EM-AH-10180	2011071402	2024.05.12	2027.05.11	3 year
6	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	803	2024.05.12	2027.05.11	3 year
7	Amplifier	EMC	EMC051835SE	980246	2025.04.17 2026.04.15	2026.04.16 2027.04.14	1 year
8	Active Loop Antenna	SCHWARZBECK	FMZB 1519 B	055	2024.05.17	2027.05.16	3 year
9	Power Meter	DARE	RPR3006W	15I00041SNO84	2025.04.17 2026.04.15	2026.04.16 2027.04.14	1 year
10	Test Cable (9KHz-30MHz)	N/A	R-01	N/A	2024.05.06	2027.05.05	3 year
11	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2024.05.06	2027.05.05	3 year
12	High Test Cable(1G-40GHz)	N/A	R-03	N/A	2024.05.06	2027.05.05	3 year
13	Filter	TRILTHIC	2400MHz	29	2024.04.26	2027.04.25	3 year

Note:
We will use the temporary antenna connector (soldered on the PCB board) When conducted test
And this temporary antenna connector is listed within the instrument list

AC Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2025.04.17	2026.04.16	1 year
2	LISN	R&S	ENV216	101313	2025.04.16	2026.04.15	1 year
3	LISN	SCHWARZBECK	NNLK 8129	8129245	2025.04.16	2026.04.15	1 year
4	50Ω Coaxial Switch	ANRITSU CORP	MP59B	6200983704	2024.04.26	2027.04.25	3 year
5	Test Cable (9KHz-30MHz)	N/A	C01	N/A	2023.05.06	2026.05.05	3 year
6	Test Cable (9KHz-30MHz)	N/A	C02	N/A	2023.05.06	2026.05.05	3 year
7	Test Cable (9KHz-30MHz)	N/A	C03	N/A	2023.05.06	2026.05.05	3 year

Note: Each piece of equipment is scheduled for calibration once a year except the Aux Equipment & Test Cable which is scheduled for calibration every 2 or 3 years.

Measurement Software

Item	Manufacturer	Software Name	Software Version	Description
1	MWRFtest	MTS 8310 2.4GHz/5GHz	2.0	RF Conducted Test
2	Farad	EZ-EMC_RE	AIT-03A	RadiatedTest
3	raditeq	RadiMation	2023.1.3	RadiatedTest

7 TEST REQUIREMENTS

7.1 CONDUCTED EMISSIONS TEST

7.1.1 Applicable Standard

According to FCC Part 15.207(a)

7.1.2 Conformance Limit

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56*	56-46*
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. *Decreases with the logarithm of the frequency
2. The lower limit shall apply at the transition frequencies
3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

7.1.3 Test Configuration



7.1.4 Test Procedure

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 Conducted emissions the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room.
2. The EUT was placed on a table which is 0.8m above ground plane.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40cm long.
5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
6. LISN at least 80 cm from nearest part of EUT chassis.
7. The frequency range from 150KHz to 30MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth(IF bandwidth=9KHz) with Maximum Hold Mode
9. For the actual test configuration, please refer to the related Item –EUT Test Photos.

7.1.5 Test Results

Pass

7.1.6 Test Results

EUT：	AUTO Smart Diagnostic Tool	Model Name ：	X-431 PRO ELITE V2
Temperature：	23.2℃	Relative Humidity：	47.6%
Pressure：	1010hPa	Phase :	L
Test Voltage ：	DC 5V from Adapter1 AC 120V/60Hz	Test Mode：	Mode 1

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1780	29.38	20.32	49.70	64.58	-14.88	QP
0.1780	24.30	20.32	44.62	54.58	-9.96	AVG
0.3100	25.17	20.40	45.57	59.97	-14.40	QP
0.3100	20.94	20.40	41.34	49.97	-8.63	AVG
0.3740	28.37	20.42	48.79	58.41	-9.62	QP
0.3740	20.65	20.42	41.07	48.41	-7.34	AVG
0.5860	29.31	20.43	49.74	56.00	-6.26	QP
0.5860	18.27	20.43	38.70	46.00	-7.30	AVG
0.6340	27.07	20.43	47.50	56.00	-8.50	QP
0.6340	18.75	20.43	39.18	46.00	-6.82	AVG
17.5300	28.76	22.42	51.18	60.00	-8.82	QP
17.5300	19.96	22.42	42.38	50.00	-7.62	AVG

Remark:
1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



EUT：	AUTO Smart Diagnostic Tool	Model Name ：	X-431 PRO ELITE V2
Temperature：	23.2℃	Relative Humidity：	47.6%
Pressure：	1010hPa	Phase :	N
Test Voltage ：	DC 5V from Adapter1 AC 120V/60Hz	Test Mode：	Mode 1

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1620	26.34	20.30	46.64	65.36	-18.72	QP
0.1620	21.43	20.30	41.73	55.36	-13.63	AVG
0.3339	23.63	20.40	44.03	59.35	-15.32	QP
0.3339	20.06	20.40	40.46	49.35	-8.89	AVG
0.4300	24.45	20.41	44.86	57.25	-12.39	QP
0.4300	17.69	20.41	38.10	47.25	-9.15	AVG
0.5420	25.66	20.43	46.09	56.00	-9.91	QP
0.5420	18.20	20.43	38.63	46.00	-7.37	AVG
0.6020	25.87	20.44	46.31	56.00	-9.69	QP
0.6020	18.11	20.44	38.55	46.00	-7.45	AVG
17.8260	20.30	22.57	42.87	60.00	-17.13	QP
17.8260	12.87	22.57	35.44	50.00	-14.56	AVG

Remark:
1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



EUT：	AUTO Smart Diagnostic Tool	Model Name ：	X-431 PRO ELITE V2
Temperature：	23.2℃	Relative Humidity：	47.6%
Pressure：	1010hPa	Phase :	L
Test Voltage ：	DC 5V from Adapter2 AC 120V/60Hz	Test Mode：	Normal Link

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1660	28.15	19.58	47.73	65.16	-17.43	QP
0.1660	10.38	19.58	29.96	55.16	-25.20	AVG
0.3820	27.21	19.55	46.76	58.24	-11.48	QP
0.3820	14.97	19.55	34.52	48.24	-13.72	AVG
0.4900	23.07	19.56	42.63	56.17	-13.54	QP
0.4900	10.95	19.56	30.51	46.17	-15.66	AVG
1.0180	25.30	19.59	44.89	56.00	-11.11	QP
1.0180	3.46	19.59	23.05	46.00	-22.95	AVG
2.3140	23.17	19.67	42.84	56.00	-13.16	QP
2.3140	7.95	19.67	27.62	46.00	-18.38	AVG
5.7380	18.50	19.91	38.41	60.00	-21.59	QP
5.7380	4.79	19.91	24.70	50.00	-25.30	AVG

Remark:
1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



EUT：	AUTO Smart Diagnostic Tool	Model Name ：	X-431 PRO ELITE V2
Temperature：	23.2℃	Relative Humidity：	47.6%
Pressure：	1010hPa	Phase :	N
Test Voltage ：	DC 5V from Adapter2 AC 120V/60Hz	Test Mode：	Normal Link

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1620	30.75	19.53	50.28	65.36	-15.08	QP
0.1620	10.32	19.53	29.85	55.36	-25.51	AVG
0.2220	26.45	19.53	45.98	62.74	-16.76	QP
0.2220	6.76	19.53	26.29	52.74	-26.45	AVG
0.3820	26.74	19.54	46.28	58.24	-11.96	QP
0.3820	11.26	19.54	30.80	48.24	-17.44	AVG
0.4860	22.42	19.56	41.98	56.24	-14.26	QP
0.4860	8.21	19.56	27.77	46.24	-18.47	AVG
0.8100	20.83	19.63	40.46	56.00	-15.54	QP
0.8100	4.64	19.63	24.27	46.00	-21.73	AVG
2.2940	18.49	19.70	38.19	56.00	-17.81	QP
2.2940	3.87	19.70	23.57	46.00	-22.43	AVG

Remark:
1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



EUT：	AUTO Smart Diagnostic Tool	Model Name ：	X-431 PRO ELITE V2
Temperature：	23.2℃	Relative Humidity：	47.6%
Pressure：	1010hPa	Phase :	L
Test Voltage ：	DC 5V from Adapter3 AC 120V/60Hz	Test Mode：	Normal Link

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1580	35.59	19.59	55.18	65.57	-10.39	QP
0.1580	17.88	19.59	37.47	55.57	-18.10	AVG
0.2100	28.76	19.54	48.30	63.21	-14.91	QP
0.2100	7.64	19.54	27.18	53.21	-26.03	AVG
0.4100	17.18	19.56	36.74	57.65	-20.91	QP
0.4100	8.43	19.56	27.99	47.65	-19.66	AVG
0.5620	15.42	19.57	34.99	56.00	-21.01	QP
0.5620	3.92	19.57	23.49	46.00	-22.51	AVG
1.0460	12.00	19.59	31.59	56.00	-24.41	QP
1.0460	1.04	19.59	20.63	46.00	-25.37	AVG
11.0900	23.20	9.93	33.13	60.00	-26.87	QP
11.0900	12.70	9.93	22.63	50.00	-27.37	AVG

Remark:
1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



EUT：	AUTO Smart Diagnostic Tool	Model Name ：	X-431 PRO ELITE V2
Temperature：	23.2℃	Relative Humidity：	47.6%
Pressure：	1010hPa	Phase :	N
Test Voltage ：	DC 5V from Adapter3 AC 120V/60Hz	Test Mode：	Normal Link

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1700	34.33	19.53	53.86	64.96	-11.10	QP
0.1700	14.48	19.53	34.01	54.96	-20.95	AVG
0.2083	27.75	19.53	47.28	63.27	-15.99	QP
0.2083	6.69	19.53	26.22	53.27	-27.05	AVG
0.4260	19.43	19.55	38.98	57.33	-18.35	QP
0.4260	7.59	19.55	27.14	47.33	-20.19	AVG
0.5260	17.65	19.57	37.22	56.00	-18.78	QP
0.5260	7.71	19.57	27.28	46.00	-18.72	AVG
1.0180	12.38	19.62	32.00	56.00	-24.00	QP
1.0180	0.23	19.62	19.85	46.00	-26.15	AVG
11.1500	24.39	9.21	33.60	60.00	-26.40	QP
11.1500	13.99	9.21	23.20	50.00	-26.80	AVG

Remark:
1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



7.2 RADIATED SPURIOUS EMISSION

7.2.1 Applicable Standard

According to FCC Part 15.247(d) & 15.209 &15.205 and ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024

7.2.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
According to FCC Part15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009~0.490	2400/F(KHz)	20 log (uV/m)	300
0.490~1.705	24000/F(KHz)	20 log (uV/m)	30
1.705~30.0	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Limits of Radiated Emission Measurement(Above 1000MHz)

Frequency(MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Remark :1. Emission level in dBuV/m=20 log (uV/m)
2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
3. For Frequency 9kHz~30MHz:
Distance extrapolation factor =40log(Specific distance/ test distance)(dB);
Limit line=Specific limits(dBuV) + distance extrapolation factor.
For Frequency above 30MHz:
Distance extrapolation factor =20log(Specific distance/ test distance)(dB);
Limit line=Specific limits(dBuV) + distance extrapolation factor.

7.2.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.2.4 Test Configuration

(a) For radiated emissions below 30MHz



(b) For radiated emissions from 30MHz to 1000MHz



(c) For radiated emissions above 1000MHz



7.2.5 Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024. The test distance is 3m.The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 and CAN/CSA-CEI/IEC CISPR 22.
This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT.
Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 1 MHz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
b. The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
c. The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
e. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
f. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
g. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	1 MHz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where RBWCF [dB] =10*lg(100 [kHz]/narrower RBW [kHz]). , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

7.2.6 Test Results

■ Spurious Emission below 30MHz (9KHz to 30MHz)

EUT:	AUTO Smart Diagnostic Tool	Model No.:	X-431 PRO ELITE V2
Temperature:	25 ℃	Relative Humidity:	56%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Allen Liu

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

■ Spurious Emission below 1GHz (30MHz to 1GHz)
All the modulation modes have been tested, and the worst result was report as below:

EUT：	AUTO Smart Diagnostic Tool	Model Name ：	X-431 PRO ELITE V2
Temperature：	25.5℃	Relative Humidity：	55%
Pressure：	1010hPa	Test Mode：	Mode 3(GFSK)
Test Voltage：	DC 5V from Adapter1 AC 120V/60Hz		

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
V	43.9660	14.39	19.35	33.74	40.00	-6.26	peak
V	122.8340	7.92	15.71	23.63	43.50	-19.87	peak
V	155.3640	11.88	14.74	26.62	43.50	-16.88	peak
V	240.8300	8.97	18.85	27.82	46.00	-18.18	peak
V	760.7040	7.56	28.03	35.59	46.00	-10.41	peak
V	948.7610	7.15	30.21	37.36	46.00	-8.64	peak

Remark:
Emission Level= Meter Reading+ Factor, Margin= Emission Level - Limit



Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
H	39.1620	11.70	18.70	30.40	40.00	-9.60	peak
H	46.6980	9.10	19.69	28.79	40.00	-11.21	QP
H	208.5800	12.29	17.49	29.78	43.50	-13.72	peak
H	297.2240	16.11	19.69	35.80	46.00	-10.20	peak
H	766.0570	7.22	28.15	35.37	46.00	-10.63	peak
H	948.7610	7.71	30.21	37.92	46.00	-8.08	peak

Remark:
Emission Level= Meter Reading+ Factor, Margin= Emission Level - Limit



EUT：	AUTO Smart Diagnostic Tool	Model Name ：	X-431 PRO ELITE V2
Temperature：	25.5℃	Relative Humidity：	55%
Pressure：	1010hPa	Test Mode：	Mode 3(GFSK)
Test Voltage：	DC 5V from Adapter2 AC 120V/60Hz		

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
V	39.8540	10.57	18.82	29.39	40.00	-10.61	peak
V	47.9940	9.63	20.17	29.80	40.00	-10.20	peak
V	64.2070	5.81	17.87	23.68	40.00	-16.32	peak
V	97.4560	9.47	17.52	26.99	43.50	-16.51	peak
V	140.8350	11.99	14.76	26.75	43.50	-16.75	peak
V	202.8100	12.48	17.94	30.42	43.50	-13.08	peak

Remark:
Emission Level= Meter Reading+ Factor, Margin= Emission Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	43.5059	6.78	19.55	26.33	40.00	-13.67	peak
H	103.4419	6.38	18.12	24.50	43.50	-19.00	peak
H	205.6750	13.54	18.12	31.66	43.50	-11.84	peak
H	262.8960	9.45	19.82	29.27	46.00	-16.73	peak
H	470.5230	6.46	24.00	30.46	46.00	-15.54	peak
H	734.4910	7.57	28.42	35.99	46.00	-10.01	peak

Remark:
Emission Level= Meter Reading+ Factor, Margin= Emission Level - Limit



EUT：	AUTO Smart Diagnostic Tool	Model Name ：	X-431 PRO ELITE V2
Temperature：	25.5℃	Relative Humidity：	55%
Pressure：	1010hPa	Test Mode：	Mode 3(GFSK)
Test Voltage：	DC 5V from Adapter3 AC 120V/60Hz		

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
V	35.3750	15.81	17.60	33.41	40.00	-6.59	peak
V	50.2320	14.38	19.81	34.19	40.00	-5.81	peak
V	62.4310	12.47	18.43	30.90	40.00	-9.10	peak
V	106.3850	10.66	18.11	28.77	43.50	-14.73	peak
V	144.8420	15.37	14.87	30.24	43.50	-13.26	peak
V	207.1230	11.73	18.13	29.86	43.50	-13.64	peak

Remark:
Emission Level= Meter Reading+ Factor, Margin= Emission Level - Limit



Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
H	46.5030	5.95	19.91	25.86	40.00	-14.14	peak
H	89.9050	10.80	16.37	27.17	43.50	-16.33	peak
H	143.8300	9.55	14.77	24.32	43.50	-19.18	peak
H	212.2690	13.26	18.19	31.45	43.50	-12.05	peak
H	344.3860	6.96	21.83	28.79	46.00	-17.21	peak
H	558.7300	6.18	25.69	31.87	46.00	-14.13	peak

Remark:
Emission Level= Meter Reading+ Factor, Margin= Emission Level - Limit



■ Spurious Emission Above 1GHz (1GHz to 18GHz)

EUT:	AUTO Smart Diagnostic Tool	Model No.:	X-431 PRO ELITE V2
Temperature:	25 ℃	Relative Humidity:	56%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Allen Liu

All the modulation modes have been tested, and the worst result was report as below:

2402

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
V	1121.975	60.05	-18.37	41.68	74.00	-32.32	peak
V	1125.375	51.83	-18.45	33.38	54.00	-20.62	AVG
V	2000.875	48.57	-13.59	34.98	54.00	-19.02	AVG
V	2070.150	55.45	-12.72	42.73	74.00	-31.27	peak
V	3039.150	55.15	-9.58	45.57	74.00	-28.43	peak
V	3050.200	47.22	-9.61	37.61	54.00	-16.39	AVG
V	4822.450	49.70	-6.96	42.74	74.00	-31.26	peak
V	4911.700	43.12	-7.13	35.99	54.00	-18.01	AVG
V	7740.500	50.14	-1.76	48.38	74.00	-25.62	peak
V	7740.500	41.91	-1.76	40.15	54.00	-13.85	AVG
V	14192.850	37.55	5.65	43.20	54.00	-10.80	AVG
V	14306.750	45.49	5.78	51.27	74.00	-22.73	peak

Remark:
Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor
All the modulation modes have been tested, and the worst-case result was 8-DPSK. Only the worst-case mode reported.
Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.
When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
H	1209.525	59.42	-18.30	41.12	74.00	-32.88	peak
H	1244.375	51.42	-17.94	33.48	54.00	-20.52	AVG
H	2012.775	56.11	-13.42	42.69	74.00	-31.31	peak
H	2020.850	47.97	-13.30	34.67	54.00	-19.33	AVG
H	2952.025	54.52	-10.05	44.47	74.00	-29.53	peak
H	3020.025	46.48	-9.52	36.96	54.00	-17.04	AVG
H	4922.750	43.03	-6.80	36.23	54.00	-17.77	AVG
H	4952.075	49.32	-6.02	43.30	74.00	-30.70	peak
H	9212.700	48.09	-0.26	47.83	74.00	-26.17	peak
H	9316.400	39.50	0.17	39.67	54.00	-14.33	AVG
H	14230.675	45.72	5.73	51.45	74.00	-22.55	peak
H	14230.675	37.66	5.73	43.39	54.00	-10.61	AVG

Remark:
Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor
All the modulation modes have been tested, and the worst-case result was 8-DPSK. Only the worst-case mode reported.
Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.
When PK value is lower than the Average value limit, average don't record.



2441

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
V	1222.700	58.94	-18.16	40.78	74.00	-33.22	peak
V	1222.700	52.11	-18.16	33.95	54.00	-20.05	AVG
V	1712.300	56.98	-16.52	40.46	74.00	-33.54	peak
V	1712.300	50.41	-16.52	33.89	54.00	-20.11	AVG
V	3580.600	46.43	-9.46	36.97	54.00	-17.03	AVG
V	3592.925	54.64	-9.20	45.44	74.00	-28.56	peak
V	5944.875	41.48	-4.42	37.06	54.00	-16.94	AVG
V	6327.375	49.22	-4.09	45.13	74.00	-28.87	peak
V	9266.250	39.78	0.29	40.07	54.00	-13.93	AVG
V	9377.175	47.57	0.14	47.71	74.00	-26.29	peak
V	13880.900	45.68	5.23	50.91	74.00	-23.09	peak
V	14192.425	37.67	5.65	43.32	54.00	-10.68	AVG

Remark:
Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor
All the modulation modes have been tested, and the worst-case result was 8-DPSK. Only the worst-case mode reported.
Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.
When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
H	1205.700	59.89	-18.34	41.55	74.00	-32.45	peak
H	1217.175	51.84	-18.21	33.63	54.00	-20.37	AVG
H	1981.325	57.19	-14.02	43.17	74.00	-30.83	peak
H	2024.250	48.48	-13.26	35.22	54.00	-18.78	AVG
H	3594.200	54.48	-9.17	45.31	74.00	-28.69	peak
H	3594.200	46.06	-9.17	36.89	54.00	-17.11	AVG
H	6324.400	51.68	-4.10	47.58	74.00	-26.42	peak
H	6553.050	42.54	-3.35	39.19	54.00	-14.81	AVG
H	9131.100	48.27	-0.25	48.02	74.00	-25.98	peak
H	9242.450	39.28	0.18	39.46	54.00	-14.54	AVG
H	14233.650	38.26	5.73	43.99	54.00	-10.01	AVG
H	14802.725	45.64	5.25	50.89	74.00	-23.11	peak

Remark:
Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor
All the modulation modes have been tested, and the worst-case result was 8-DPSK. Only the worst-case mode reported.
Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.
When PK value is lower than the Average value limit, average don't record.



2480

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
V	1238.000	51.90	-18.00	33.90	54.00	-20.10	AVG
V	1249.900	58.64	-17.88	40.76	74.00	-33.24	peak
V	1989.400	56.40	-13.83	42.57	74.00	-31.43	peak
V	2023.400	48.28	-13.27	35.01	54.00	-18.99	AVG
V	3244.000	45.19	-9.00	36.19	54.00	-17.81	AVG
V	3329.000	53.68	-9.37	44.31	74.00	-29.69	peak
V	4837.750	42.96	-6.90	36.06	54.00	-17.94	AVG
V	5000.100	50.58	-6.41	44.17	74.00	-29.83	peak
V	7704.375	50.01	-1.71	48.30	74.00	-25.70	peak
V	7704.375	41.62	-1.71	39.91	54.00	-14.09	AVG
V	14199.225	46.12	5.70	51.82	74.00	-22.18	peak
V	14199.225	37.50	5.70	43.20	54.00	-10.80	AVG

Remark:
Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor
All the modulation modes have been tested, and the worst-case result was 8-DPSK. Only the worst-case mode reported.
Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.
When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
H	1251.175	59.02	-17.87	41.15	74.00	-32.85	peak
H	1251.175	51.99	-17.87	34.12	54.00	-19.88	AVG
H	1991.950	48.65	-13.78	34.87	54.00	-19.13	AVG
H	2045.925	55.52	-12.95	42.57	74.00	-31.43	peak
H	3596.325	53.62	-9.13	44.49	74.00	-29.51	peak
H	3596.325	46.74	-9.13	37.61	54.00	-16.39	AVG
H	6553.050	42.36	-3.35	39.01	54.00	-14.99	AVG
H	6726.450	50.52	-3.30	47.22	74.00	-26.78	peak
H	9185.925	47.93	-0.28	47.65	74.00	-26.35	peak
H	9378.875	39.61	0.15	39.76	54.00	-14.24	AVG
H	13307.575	37.89	5.26	43.15	54.00	-10.85	AVG
H	13535.375	46.44	5.33	51.77	74.00	-22.23	peak

Remark:
Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor
All the modulation modes have been tested, and the worst-case result was 8-DPSK. Only the worst-case mode reported.
Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.
When PK value is lower than the Average value limit, average don't record.



Spurious Emission Above 1GHz (18GHz to 25GHz)

EUT:	AUTO Smart Diagnostic Tool	Model No.:	X-431 PRO ELITE V2
Temperature:	22.6 ℃	Relative Humidity:	62%
Test Mode:	Mode2/Mode4	Test By:	Allen Liu

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
V	18914.025	59.23	-14.24	44.99	74.00	-29.01	peak
V	18914.025	51.50	-14.24	37.26	54.00	-16.74	AVG
V	20062.375	47.88	-12.56	35.32	54.00	-18.68	AVG
V	20067.975	56.38	-12.57	43.81	74.00	-30.19	peak
V	20983.750	56.73	-12.29	44.44	74.00	-29.56	peak
V	21023.650	49.53	-12.30	37.23	54.00	-16.77	AVG
V	22127.025	50.28	-11.89	38.39	54.00	-15.61	AVG
V	22189.675	57.56	-11.84	45.72	74.00	-28.28	peak
V	22934.650	57.55	-11.79	45.76	74.00	-28.24	peak
V	22975.775	50.11	-11.79	38.32	54.00	-15.68	AVG
V	24453.650	56.65	-11.20	45.45	74.00	-28.55	peak
V	24470.800	49.23	-11.15	38.08	54.00	-15.92	AVG

Remark:
Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor
All the modulation modes have been tested, and the worst-case result was 8-DPSK 2402MHz. Only the worst-case mode reported.
Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.
When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
H	18884.625	57.83	-14.29	43.54	74.00	-30.46	peak
H	18915.775	50.24	-14.23	36.01	54.00	-17.99	AVG
H	19944.250	49.48	-12.59	36.89	54.00	-17.11	AVG
H	20067.800	58.31	-12.57	45.74	74.00	-28.26	peak
H	21029.775	51.48	-12.28	39.20	54.00	-14.80	AVG
H	21046.575	59.40	-12.29	47.11	74.00	-26.89	peak
H	22035.850	51.98	-11.97	40.01	54.00	-13.99	AVG
H	22076.975	59.78	-11.93	47.85	74.00	-26.15	peak
H	22991.700	61.47	-11.79	49.68	74.00	-24.32	peak
H	22998.700	53.45	-11.79	41.66	54.00	-12.34	AVG
H	24569.325	50.53	-11.02	39.51	54.00	-14.49	AVG
H	24580.175	58.03	-11.01	47.02	74.00	-26.98	peak

Remark:
Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor
All the modulation modes have been tested, and the worst-case result was 8-DPSK 2402MHz. Only the worst-case mode reported.
Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.
When PK value is lower than the Average value limit, average don't record.



■ Radiated Spurious at Band Edges

EUT:	AUTO Smart Diagnostic Tool	Model No.:	X-431 PRO ELITE V2
Temperature:	21 ℃	Relative Humidity:	61%
Test Mode:	Mode2/ Mode4	Test By:	Allen Liu

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
V	2390.000	21.27	29.88	51.15	74.00	-22.85	peak
V	2390.000	11.89	29.88	41.77	54.00	-12.23	AVG

Remark:
Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor
All the modulation modes have been tested, and the worst-case result was 8-DPSK 2402MHz. Only the worst-case mode reported.
Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.
When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	2390.000	21.86	29.88	51.74	74.00	-22.26	peak
H	2390.000	11.51	29.88	41.39	54.00	-12.61	AVG

Remark:
Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor
All the modulation modes have been tested, and the worst-case result was 8-DPSK 2402MHz. Only the worst-case mode reported.
Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.
When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	2483.500	21.79	30.69	52.48	74.00	-21.52	peak
V	2483.500	12.41	30.69	43.10	54.00	-10.90	AVG

Remark:
Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor
All the modulation modes have been tested, and the worst-case result was 8-DPSK 2480MHz. Only the worst-case mode reported.
Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.
When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	2483.500	21.34	30.69	52.03	74.00	-21.97	peak
H	2483.500	12.29	30.69	42.98	54.00	-11.02	AVG

Remark:
Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor
All the modulation modes have been tested, and the worst-case result was 8-DPSK 2480MHz. Only the worst-case mode reported.
Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.
When PK value is lower than the Average value limit, average don't record.



7.3 NUMBER OF HOPPING CHANNEL

7.3.1 Applicable Standard

According to FCC Part 15.247(a)(1) (iii)and ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024

7.3.2 Conformance Limit

Frequency hopping systems in the 2400-2483.5MHz band shall use at least 15 channels.

7.3.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.3.4 Test Setup

Please refer to Section 6.1 of this test report.

7.3.5 Test Procedure

The testing follows ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 clause 7.8.3
The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
Set to the maximum power setting and enable the EUT transmit continuously.
The EUT must have its hopping function enabled.
Use the following spectrum analyzer settings:
Span = the frequency band of operation
RBW : To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
VBW ≥ RBW
Sweep = auto
Detector function = peak
Trace = max hold

7.3.6 Test Results

EUT:	AUTO Smart Diagnostic Tool	Model No.:	X-431 PRO ELITE V2
Temperature:	25 ℃	Relative Humidity:	56%
Test Mode:	Mode 5(1Mbps)	Test By:	Allen Liu

Test data reference attachment.

7.4 HOPPING CHANNEL SEPARATION MEASUREMENT

7.4.1 Applicable Standard

According to FCC Part 15.247(a)(1) and ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024

7.4.2 Conformance Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5MHz band shall have hopping channel carrier frequencies that are separated by 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

7.4.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.4.4 Test Setup

Please refer to Section 6.1 of this test report.

7.4.5 Test Procedure

The testing follows ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 clause 7.8.2
The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
Set to the maximum power setting and enable the EUT transmit continuously.
The EUT was operating in controlled its channel.
Use the following spectrum analyzer settings:
Span = Measurement Bandwidth or Channel Separation
RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
VBW ≥ RBW
Sweep = auto
Detector function = peak
Trace = max hold

7.4.6 Test Results

EUT:	AUTO Smart Diagnostic Tool	Model No.:	X-431 PRO ELITE V2
Temperature:	25 ℃	Relative Humidity:	56%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Allen Liu

Test data reference attachment.

7.5 AVERAGE TIME OF OCCUPANCY (DWELL TIME)

7.5.1 Applicable Standard

According to FCC Part 15.247(a)(1)(iii) and ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024

7.5.2 Conformance Limit

The average time of occupancy on any channel shall not be greater than 0.4s within a period of 0.4s multiplied by the number of hopping channels employed.

7.5.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.5.4 Test Setup

Please refer to Section 6.1 of this test report.

7.5.5 Test Procedure

The testing follows ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 clause 7.8.4
The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
Set to the maximum power setting and enable the EUT transmit continuously.
The EUT must have its hopping function enabled.
Use the following spectrum analyzer settings:
Span = zero span, centered on a hopping channel
RBW ≥ 1MHz
VBW ≥ RBW
Sweep = as necessary to capture the entire dwell time per hopping channel
Detector function = peak
Trace = max hold
Measure the maximum time duration of one single pulse.
Set the EUT for DH5, DH3 and DH1 packet transmitting.
Measure the maximum time duration of one single pulse.

7.5.6 Test Results

EUT:	AUTO Smart Diagnostic Tool	Model No.:	X-431 PRO ELITE V2
Temperature:	25 ℃	Relative Humidity:	56%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Allen Liu

Test data reference attachment.

Note:

Period Time = (channel number)*0.4

DH1 Dwell time: Pulse time* Burst Count (Number of hops in the period specified in the requirements)

DH3 Dwell time: Pulse time* Burst Count (Number of hops in the period specified in the requirements)

DH5 Dwell time: Pulse time* Burst Count (Number of hops in the period specified in the requirements)

7.6 20DB BANDWIDTH TEST

7.6.1 Applicable Standard

According to FCC Part 15.247(a)(1) and ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024

7.6.2 Conformance Limit

No limit requirement.

7.6.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.6.4 Test Setup

Please refer to Section 6.1 of this test report.

7.6.5 Test Procedure

The testing follows ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 clause 6.9.2
The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
Set to the maximum power setting and enable the EUT transmit continuously.
The EUT was operating in controlled its channel.
Use the following spectrum analyzer settings:
Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel
RBW shall be in the range of 1% to 5% of the OBW
VBW =3*RBW
Sweep = auto
Detector function = peak
Trace = max hold

7.6.6 Test Results

EUT:	AUTO Smart Diagnostic Tool	Model No.:	X-431 PRO ELITE V2
Temperature:	25 ℃	Relative Humidity:	56%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Allen Liu

Test data reference attachment.

7.7 PEAK OUTPUT POWER

7.7.1 Applicable Standard

According to FCC Part 15.247(b)(1) and ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024

7.7.2 Conformance Limit

The maximum peak conducted output power of the intentional radiator shall not exceed the following: (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts.

7.7.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.7.4 Test Setup

Please refer to Section 6.1 of this test report.

7.7.5 Test Procedure

The testing follows ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 clause 7.8.5.
The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
Set to the maximum power setting and enable the EUT transmit continuously.
The EUT was operating in controlled its channel.
Use the following spectrum analyzer settings:
Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
RBW ≥ the 20 dB bandwidth of the emission being measured
VBW ≥ RBW
Sweep = auto
Detector function = peak
Trace = max hold

7.7.6 Test Results

EUT:	AUTO Smart Diagnostic Tool	Model No.:	X-431 PRO ELITE V2
Temperature:	25 ℃	Relative Humidity:	56%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Allen Liu

Test data reference attachment.

7.8 CONDUCTED BAND EDGE MEASUREMENT

7.8.1 Applicable Standard

According to FCC Part 15.247(d) and ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024

7.8.2 Conformance Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.8.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.8.4 Test Setup

Please refer to Section 6.1 of this test report.

7.8.5 Test Procedure

The testing follows ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 clause 7.8.6.
The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
Set to the maximum power setting and enable the EUT transmit continuously.
The EUT must have its hopping function enabled.
Use the following spectrum analyzer settings:
Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
RBW = 100KHz
VBW = 300KHz
Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
Repeat above procedures until all measured frequencies were complete.

7.8.6 Test Results

EUT:	AUTO Smart Diagnostic Tool	Model No.:	X-431 PRO ELITE V2
Temperature:	25 ℃	Relative Humidity:	56%
Test Mode:	Mode2 /Mode4/ Mode 5	Test By:	Allen Liu

Test data reference attachment.

7.9 SPURIOUS RF CONDUCTED EMISSION

7.9.1 Applicable Standard

According to FCC Part 15.247(d) and ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024.

7.9.2 Conformance Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.9.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.9.4 Test Setup

Please refer to Section 6.1 of this test report.

7.9.5 Test Procedure

Establish an emission level by using the following procedure:
a) Set the center frequency and span to encompass frequency range to be measured.
b) Set the RBW = 100 kHz.
c) Set the VBW ≥ [3 × RBW].
d) Detector = peak.
e) Sweep time = auto couple.
f) Trace mode = max hold.
g) Allow trace to fully stabilize.
h) Use the peak marker function to determine the maximum amplitude level.
Then the limit shall be attenuated by at least 20 dB relative to the maximum amplitude level in 100 kHz.

7.9.6 Test Results

Remark: The measurement frequency range is from 30MHzHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandege measurement data.

Test data reference attachment.

7.10 ANTENNA APPLICATION

7.10.1 Antenna Requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

7.10.2 Result

The EUT antenna is permanent attached FPC Antenna (Gain: 3.86 dBi). It comply with the standard requirement.

7.11 FREQUENCY HOPPING SYSTEM (FHSS) EQUIPMENT REQUIREMENTS

7.11.1 Standard Applicable

According to FCC Part 15.247(a)(1), The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals. (g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section. (h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

7.11.2 Frequency Hopping System

This transmitter device is frequency hopping device, and complies with FCC part 15.247 rule. This device uses Bluetooth radio which operates in 2400-2483.5 MHz band. Bluetooth uses a radio technology called frequency-hopping spread spectrum, which chops up the data being sent and transmits chunks of it on up to 79 bands (1 MHz each; centred from 2402 to 2480 MHz) in the range 2,400-2,483.5 MHz. The transmitter switches hop frequencies 1,600 times per second to assure a high degree of data security. All Bluetooth devices participating in a given piconet are synchronized to the frequency-hopping channel for the piconet. The frequency hopping sequence is determined by the master's device address and the phase of the hopping sequence (the frequency to hop at a specific time) is determined by the master's internal clock. Therefore, all slaves in a piconet must know the master's device address and must synchronize their clocks with the master's clock. Adaptive Frequency Hopping (AFH) was introduced in the Bluetooth specification to provide an effective way for a Bluetooth radio to counteract normal interference. AFH identifies "bad" channels, where either other wireless devices are interfering with the Bluetooth signal or the Bluetooth signal is interfering with another device. The AFH-enabled Bluetooth device will then communicate with other devices within its piconet to share details of any identified bad channels. The devices will then switch to alternative available "good" channels, away from the areas of interference, thus having no impact on the bandwidth used.

This device was tested with an bluetooth system receiver to check that the device maintained hopping synchronization, and the device complied with these requirements for FCC Part 15.247 rule.

7.11.3 EUT Pseudorandom Frequency Hopping Sequence

Pseudorandom Frequency Hopping Sequence Table as below: Channel: 08, 24, 40, 56, 40, 56, 72, 09, 01, 09, 33, 41, 33, 41, 65, 73, 53, 69, 06, 22, 04, 20, 36, 52, 38, 46, 70, 78, 68, 76, 21, 29, 10, 26, 42, 58, 44, 60, 76, 13, 03, 11, 35, 43, 37, 45, 69, 77, 55, 71, 08, 24, 08, 24, 40, 56, 40, 48, 72, 01, 72, 01, 25, 33, 12, 28, 44, 60, 42, 58, 74, 11, 05, 13, 37, 45 etc.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

8 TEST RESULTS

8.1 DWELL TIME

Condition	Mode	Frequency (MHz)	Antenna	Pulse Time (ms)	Total Dwell Time (ms)	Burst Count	Period Time (ms)	Limit (ms)	Verdict
NVNT	1-DH1	2441	Ant1	0.375	78.375	209	31600	400	Pass
NVNT	1-DH3	2441	Ant1	1.63	200.49	123	31600	400	Pass
NVNT	1-DH5	2441	Ant1	2.888	236.816	82	31600	400	Pass
NVNT	2-DH1	2441	Ant1	0.387	78.561	203	31600	400	Pass
NVNT	2-DH3	2441	Ant1	1.635	197.835	121	31600	400	Pass
NVNT	2-DH5	2441	Ant1	2.888	259.92	90	31600	400	Pass
NVNT	3-DH1	2441	Ant1	0.387	79.722	206	31600	400	Pass
NVNT	3-DH3	2441	Ant1	1.635	209.28	128	31600	400	Pass
NVNT	3-DH5	2441	Ant1	2.888	254.144	88	31600	400	Pass

Test Graphs

Dwell NVNT 1-DH1 2441MHz Ant1 One Burst



Dwell NVNT 1-DH1 2441MHz Ant1 Accumulated



Dwell NVNT 1-DH3 2441MHz Ant1 One Burst



Dwell NVNT 1-DH3 2441MHz Ant1 Accumulated



Dwell NVNT 1-DH5 2441MHz Ant1 One Burst



Dwell NVNT 1-DH5 2441MHz Ant1 Accumulated



Dwell NVNT 2-DH1 2441MHz Ant1 One Burst



Dwell NVNT 2-DH1 2441MHz Ant1 Accumulated



Dwell NVNT 2-DH3 2441MHz Ant1 One Burst



Dwell NVNT 2-DH3 2441MHz Ant1 Accumulated



Dwell NVNT 2-DH5 2441MHz Ant1 One Burst



Dwell NVNT 2-DH5 2441MHz Ant1 Accumulated



Dwell NVNT 3-DH1 2441MHz Ant1 One Burst



Dwell NVNT 3-DH1 2441MHz Ant1 Accumulated



Dwell NVNT 3-DH3 2441MHz Ant1 One Burst



Dwell NVNT 3-DH3 2441MHz Ant1 Accumulated



Dwell NVNT 3-DH5 2441MHz Ant1 One Burst



Dwell NVNT 3-DH5 2441MHz Ant1 Accumulated



8.2 MAXIMUM CONDUCTED OUTPUT POWER

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	1-DH5	2402	Ant1	4.5	21	Pass
NVNT	1-DH5	2441	Ant1	4.67	21	Pass
NVNT	1-DH5	2480	Ant1	4.66	21	Pass
NVNT	2-DH5	2402	Ant1	3.76	21	Pass
NVNT	2-DH5	2441	Ant1	3.89	21	Pass
NVNT	2-DH5	2480	Ant1	4.08	21	Pass
NVNT	3-DH5	2402	Ant1	3.87	21	Pass
NVNT	3-DH5	2441	Ant1	3.97	21	Pass
NVNT	3-DH5	2480	Ant1	4.17	21	Pass

Test Graphs

Power NVNT 1-DH5 2402MHz Ant1



Power NVNT 1-DH5 2441MHz Ant1



Power NVNT 1-DH5 2480MHz Ant1



Power NVNT 2-DH5 2402MHz Ant1



Power NVNT 2-DH5 2441MHz Ant1



Power NVNT 2-DH5 2480MHz Ant1



Power NVNT 3-DH5 2402MHz Ant1



Power NVNT 3-DH5 2441MHz Ant1



Power NVNT 3-DH5 2480MHz Ant1



8.3 -20dB Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	-20 dB Bandwidth (MHz)	Verdict
NVNT	1-DH5	2402	Ant1	0.854	Pass
NVNT	1-DH5	2441	Ant1	0.85	Pass
NVNT	1-DH5	2480	Ant1	0.854	Pass
NVNT	2-DH5	2402	Ant1	1.278	Pass
NVNT	2-DH5	2441	Ant1	1.274	Pass
NVNT	2-DH5	2480	Ant1	1.274	Pass
NVNT	3-DH5	2402	Ant1	1.28	Pass
NVNT	3-DH5	2441	Ant1	1.256	Pass
NVNT	3-DH5	2480	Ant1	1.24	Pass

Test Graphs

-20dB Bandwidth NVNT 1-DH5 2402MHz Ant1



-20dB Bandwidth NVNT 1-DH5 2441MHz Ant1



-20dB Bandwidth NVNT 1-DH5 2480MHz Ant1



-20dB Bandwidth NVNT 2-DH5 2402MHz Ant1



-20dB Bandwidth NVNT 2-DH5 2441MHz Ant1



-20dB Bandwidth NVNT 2-DH5 2480MHz Ant1



-20dB Bandwidth NVNT 3-DH5 2402MHz Ant1



-20dB Bandwidth NVNT 3-DH5 2441MHz Ant1



-20dB Bandwidth NVNT 3-DH5 2480MHz Ant1



8.4 OCCUPIED CHANNEL BANDWIDTH

Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	1-DH5	2402	Ant1	0.759
NVNT	1-DH5	2441	Ant1	0.765
NVNT	1-DH5	2480	Ant1	0.773
NVNT	2-DH5	2402	Ant1	1.151
NVNT	2-DH5	2441	Ant1	1.157
NVNT	2-DH5	2480	Ant1	1.169
NVNT	3-DH5	2402	Ant1	1.171
NVNT	3-DH5	2441	Ant1	1.177
NVNT	3-DH5	2480	Ant1	1.163

Test Graphs

OBW NVNT 1-DH5 2402MHz Ant1



OBW NVNT 1-DH5 2441MHz Ant1



OBW NVNT 1-DH5 2480MHz Ant1



OBW NVNT 2-DH5 2402MHz Ant1



OBW NVNT 2-DH5 2441MHz Ant1



OBW NVNT 2-DH5 2480MHz Ant1



OBW NVNT 3-DH5 2402MHz Ant1



OBW NVNT 3-DH5 2441MHz Ant1



OBW NVNT 3-DH5 2480MHz Ant1



8.5 CARRIER FREQUENCIES SEPARATION

Condition	Mode	Antenna	Hopping Freq1 (MHz)	Hopping Freq2 (MHz)	HFS (MHz)	Limit (MHz)	Verdict
NVNT	1-DH5	Ant1	2402.056	2403.056	1	0.569	Pass
NVNT	1-DH5	Ant1	2441.058	2442.162	1.104	0.567	Pass
NVNT	1-DH5	Ant1	2479.056	2480.162	1.106	0.569	Pass
NVNT	2-DH5	Ant1	2402.162	2403.164	1.002	0.852	Pass
NVNT	2-DH5	Ant1	2441.012	2442.164	1.152	0.849	Pass
NVNT	2-DH5	Ant1	2479.076	2480.08	1.004	0.849	Pass
NVNT	3-DH5	Ant1	2402.16	2403.162	1.002	0.853	Pass
NVNT	3-DH5	Ant1	2440.834	2442.014	1.18	0.837	Pass
NVNT	3-DH5	Ant1	2479.012	2480.014	1.002	0.827	Pass

Test Graphs

CFS NVNT 1-DH5 2402MHz Ant1



CFS NVNT 1-DH5 2441MHz Ant1



CFS NVNT 1-DH5 2480MHz Ant1



CFS NVNT 2-DH5 2402MHz Ant1



CFS NVNT 2-DH5 2441MHz Ant1



CFS NVNT 2-DH5 2480MHz Ant1



CFS NVNT 3-DH5 2402MHz Ant1



CFS NVNT 3-DH5 2441MHz Ant1



CFS NVNT 3-DH5 2480MHz Ant1



8.6 NUMBER OF HOPPING CHANNEL

Condition	Mode	Antenna	Hopping Number	Limit	Verdict
NVNT	1-DH5	Ant1	79	15	Pass
NVNT	2-DH5	Ant1	79	15	Pass
NVNT	3-DH5	Ant1	79	15	Pass

Test Graphs

Hopping No. NVNT 1-DH5 2402MHz Ant1



Hopping No. NVNT 2-DH5 2402MHz Ant1



Hopping No. NVNT 3-DH5 2402MHz Ant1



8.7 BAND EDGE

Condition	Mode	Frequency (MHz)	Antenna	Hopping Mode	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH5	2402	Ant1	No-Hopping	-53.54	-20	Pass
NVNT	1-DH5	2480	Ant1	No-Hopping	-55.12	-20	Pass
NVNT	2-DH5	2402	Ant1	No-Hopping	-51.09	-20	Pass
NVNT	2-DH5	2480	Ant1	No-Hopping	-52.02	-20	Pass
NVNT	3-DH5	2402	Ant1	No-Hopping	-53.91	-20	Pass
NVNT	3-DH5	2480	Ant1	No-Hopping	-55.65	-20	Pass

Test Graphs

Band Edge NVNT 1-DH5 2402MHz Ant1 No-Hopping Ref



Band Edge NVNT 1-DH5 2402MHz Ant1 No-Hopping Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.40215 GHz	3.83 dBm		
M2		1	2.4 GHz	-54.10 dBm		
M3		1	2.39 GHz	-54.08 dBm		
M4		1	2.3408 GHz	-49.80 dBm		

Band Edge NVNT 1-DH5 2480MHz Ant1 No-Hopping Ref



Band Edge NVNT 1-DH5 2480MHz Ant1 No-Hopping Emission



Band Edge NVNT 2-DH5 2402MHz Ant1 No-Hopping Ref



Band Edge NVNT 2-DH5 2402MHz Ant1 No-Hopping Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.40205 GHz	3.13 dBm		
M2		1	2.4 GHz	-54.93 dBm		
M3		1	2.39 GHz	-55.64 dBm		
M4		1	2.3414 GHz	-49.48 dBm		

Band Edge NVNT 2-DH5 2480MHz Ant1 No-Hopping Ref



Band Edge NVNT 2-DH5 2480MHz Ant1 No-Hopping Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.48005 GHz	1.82 dBm		
M2		1	2.4835 GHz	-55.31 dBm		
M3		1	2.5 GHz	-53.40 dBm		
M4		1	2.4899 GHz	-50.63 dBm		

Band Edge NVNT 3-DH5 2402MHz Ant1 No-Hopping Ref



Band Edge NVNT 3-DH5 2402MHz Ant1 No-Hopping Emission



Band Edge NVNT 3-DH5 2480MHz Ant1 No-Hopping Ref



Band Edge NVNT 3-DH5 2480MHz Ant1 No-Hopping Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.47985 GHz	2.09 dBm		
M2		1	2.4835 GHz	-55.07 dBm		
M3		1	2.5 GHz	-53.67 dBm		
M4		1	2.4871 GHz	-52.28 dBm		

8.8 BAND EDGE(HOPPING)

Condition	Mode	Frequency (MHz)	Antenna	Hopping Mode	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH5	2402	Ant1	Hopping	-52.59	-20	Pass
NVNT	1-DH5	2480	Ant1	Hopping	-55.59	-20	Pass
NVNT	2-DH5	2402	Ant1	Hopping	-52.25	-20	Pass
NVNT	2-DH5	2480	Ant1	Hopping	-54.47	-20	Pass
NVNT	3-DH5	2402	Ant1	Hopping	-52.48	-20	Pass
NVNT	3-DH5	2480	Ant1	Hopping	-54.7	-20	Pass

Test Graphs

Band Edge(Hopping) NVNT 1-DH5 2402MHz Ant1 Hopping Ref

Band Edge(Hopping) NVNT 1-DH5 2402MHz Ant1 Hopping Emission



Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.40395 GHz	3.72 dBm		
M2		1	2.4 GHz	-53.97 dBm		
M3		1	2.39 GHz	-53.41 dBm		
M4		1	2.3494 GHz	-48.51 dBm		

Band Edge(Hopping) NVNT 1-DH5 2480MHz Ant1 Hopping Ref



Band Edge(Hopping) NVNT 1-DH5 2480MHz Ant1 Hopping Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.47795 GHz	4.02 dBm		
M2		1	2.4835 GHz	-53.29 dBm		
M3		1	2.5 GHz	-52.79 dBm		
M4		1	2.4907 GHz	-51.38 dBm		

Band Edge(Hopping) NVNT 2-DH5 2402MHz Ant1 Hopping Ref



Band Edge(Hopping) NVNT 2-DH5 2402MHz Ant1 Hopping Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.40595 GHz	3.32 dBm		
M2		1	2.4 GHz	-54.69 dBm		
M3		1	2.39 GHz	-52.66 dBm		
M4		1	2.3491 GHz	-49.25 dBm		

Band Edge(Hopping) NVNT 2-DH5 2480MHz Ant1 Hopping Ref



Band Edge(Hopping) NVNT 2-DH5 2480MHz Ant1 Hopping Emission



Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.47685 GHz	2.55 dBm		
M2		1	2.4835 GHz	-52.92 dBm		
M3		1	2.5 GHz	-53.44 dBm		
M4		1	2.4955 GHz	-50.57 dBm		

Band Edge(Hopping) NVNT 3-DH5 2402MHz Ant1 Hopping Ref



Band Edge(Hopping) NVNT 3-DH5 2402MHz Ant1 Hopping Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.40315 GHz	3.79 dBm		
M2		1	2.4 GHz	-52.99 dBm		
M3		1	2.39 GHz	-54.06 dBm		
M4		1	2.3486 GHz	-48.75 dBm		

Band Edge(Hopping) NVNT 3-DH5 2480MHz Ant1 Hopping Ref



Band Edge(Hopping) NVNT 3-DH5 2480MHz Ant1 Hopping Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.47615 GHz	1.26 dBm		
M2		1	2.4835 GHz	-51.79 dBm		
M3		1	2.5 GHz	-53.18 dBm		
M4		1	2.4973 GHz	-51.01 dBm		

8.9 CONDUCTED RF SPURIOUS EMISSION

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH5	2402	Ant1	-54.36	-20	Pass
NVNT	1-DH5	2441	Ant1	-54.92	-20	Pass
NVNT	1-DH5	2480	Ant1	-54.48	-20	Pass
NVNT	2-DH5	2402	Ant1	-54.21	-20	Pass
NVNT	2-DH5	2441	Ant1	-53.74	-20	Pass
NVNT	2-DH5	2480	Ant1	-53.81	-20	Pass
NVNT	3-DH5	2402	Ant1	-52.91	-20	Pass
NVNT	3-DH5	2441	Ant1	-54.1	-20	Pass
NVNT	3-DH5	2480	Ant1	-53.13	-20	Pass

Test Graphs

Tx. Spurious NVNT 1-DH5 2402MHz Ant1 Ref



Tx. Spurious NVNT 1-DH5 2402MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.40207 GHz	3.25 dBm		
M2		1	15.941117 GHz	-50.48 dBm		
M3		1	5.003713 GHz	-55.09 dBm		
M4		1	7.00661 GHz	-54.20 dBm		
M5		1	9.757725 GHz	-55.02 dBm		

Tx. Spurious NVNT 1-DH5 2441MHz Ant1 Ref



Tx. Spurious NVNT 1-DH5 2441MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.4409 GHz	3.75 dBm		
M2		1	15.720534 GHz	-50.95 dBm		
M3		1	4.683426 GHz	-54.55 dBm		
M4		1	7.378954 GHz	-54.78 dBm		
M5		1	9.94478 GHz	-54.99 dBm		

Tx. Spurious NVNT 1-DH5 2480MHz Ant1 Ref



Tx. Spurious NVNT 1-DH5 2480MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.47972 GHz	3.73 dBm		
M2		1	16.391107 GHz	-50.58 dBm		
M3		1	5.055771 GHz	-54.66 dBm		
M4		1	7.407189 GHz	-54.24 dBm		
M5		1	10.085953 GHz	-54.47 dBm		

Tx. Spurious NVNT 2-DH5 2402MHz Ant1 Ref



Tx. Spurious NVNT 2-DH5 2402MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.40207 GHz	-0.45 dBm		
M2		1	17.213442 GHz	-50.97 dBm		
M3		1	4.802541 GHz	-54.70 dBm		
M4		1	7.124842 GHz	-54.10 dBm		
M5		1	9.772725 GHz	-55.28 dBm		

Tx. Spurious NVNT 2-DH5 2441MHz Ant1 Ref



Tx. Spurious NVNT 2-DH5 2441MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.4409 GHz	-2.98 dBm		
M2		1	22.765965 GHz	-49.99 dBm		
M3		1	5.035477 GHz	-54.75 dBm		
M4		1	7.389542 GHz	-54.06 dBm		
M5		1	9.836253 GHz	-53.33 dBm		

Tx. Spurious NVNT 2-DH5 2480MHz Ant1 Ref



Tx. Spurious NVNT 2-DH5 2480MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.47972 GHz	3.54 dBm		
M2		1	20.136612 GHz	-49.96 dBm		
M3		1	4.951655 GHz	-55.22 dBm		
M4		1	7.538657 GHz	-54.18 dBm		
M5		1	10.105364 GHz	-54.68 dBm		

Tx. Spurious NVNT 3-DH5 2402MHz Ant1 Ref



Tx. Spurious NVNT 3-DH5 2402MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.40207 GHz	-1.84 dBm		
M2		1	17.362556 GHz	-49.83 dBm		
M3		1	4.641074 GHz	-55.55 dBm		
M4		1	7.025139 GHz	-53.53 dBm		
M5		1	9.551259 GHz	-55.14 dBm		

Tx. Spurious NVNT 3-DH5 2441MHz Ant1 Ref



Tx. Spurious NVNT 3-DH5 2441MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.4409 GHz	1.83 dBm		
M2		1	22.811847 GHz	-50.21 dBm		
M3		1	5.040771 GHz	-54.74 dBm		
M4		1	7.313662 GHz	-54.80 dBm		
M5		1	9.779783 GHz	-55.23 dBm		

Tx. Spurious NVNT 3-DH5 2480MHz Ant1 Ref



Tx. Spurious NVNT 3-DH5 2480MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.47972 GHz	-0.60 dBm		
M2		1	15.595242 GHz	-50.90 dBm		
M3		1	5.061065 GHz	-54.48 dBm		
M4		1	7.249251 GHz	-55.16 dBm		
M5		1	9.954485 GHz	-54.58 dBm		

END OF REPORT