



Prüfbericht-Nr.: Test Report No.:	17040437 005	Auftrags-Nr.: Order No.:	164014360	Seite 1 von 26 Page 1 of 26	
Kunden-Referenz-Nr.: Client Reference No.:	N/A	Auftragsdatum: Order date:	20.05.2014		
Auftraggeber: Client:	KEEN HIGH TECHNOLOGIES LTD. Block A1 & A2, Ze Da Li Industrial Park, Tangwei Area, Fuyong, Bao'an, Shenzhen, Guangdong, China				
Prüfgegenstand: Test item:	Tablet				
Bezeichnung / Typ-Nr.: Identification / Type No.:	NS-15AT10				
Auftrags-Inhalt: Order content:	FCC/IC Certification				
Prüfgrundlage: Test specification:	CFR47 FCC Part 15: Subpart B Section 15.107 CFR47 FCC Part 15: Subpart B Section 15.109 ICES-003 Issue 5 August 2012				
Wareneingangsdatum: Date of receipt:	25.05.2014				
Prüfmuster-Nr.: Test sample No.:	A000073356-003				
Prüfzeitraum: Testing period:	25.05.2014 - 08.06.2014				
Ort der Prüfung: Place of testing:	Accurate Technology Co., Ltd. Shenzhen Academy of Metrology and Quality Inspection				
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (Shenzhen) Co., Ltd.				
Prüfergebnis*: Test result*:	Pass				
geprüft von / tested by:			kontrolliert von / reviewed by:		
 13.06.2014 Owen Tian/Project Manager Datum Name / Stellung Unterschrift Date Name / Position Signature			 13.06.2014 Sam Lin/Technical Certifier Datum Name / Stellung Unterschrift Date Name / Position Signature		
Sonstiges / Other:					
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:			Prüfmuster vollständig und unbeschädigt Test item complete and undamaged		
* Legende: 1 = sehr gut 2 = gut 3 = befriedigend 4 = ausreichend 5 = mangelhaft P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet Legend: 1 = very good 2 = good 3 = satisfactory 4 = sufficient 5 = poor P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested					
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.					

Prüfbericht - Nr.: 17040437 005
Test Report No.

Seite 2 von 26
Page 2 of 26

TEST SUMMARY

5.1.1 CONDUCTED EMISSIONS

RESULT: Pass

5.2.1 RADIATED EMISSION

RESULT: Pass

CONTENTS

1.	GENERAL REMARKS	4
1.1	COMPLEMENTARY MATERIALS	4
2.	TEST SITES	4
2.1	TEST FACILITIES.....	4
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	5
2.3	TRACEABILITY	6
2.4	CALIBRATION	6
2.5	MEASUREMENT UNCERTAINTY	6
2.6	LOCATION OF ORIGINAL DATA	6
2.7	STATUS OF FACILITY USED FOR TESTING.....	7
2.8	TEST SETUP DIAGRAM.....	8
3.	GENERAL PRODUCT INFORMATION	9
3.1	PRODUCT FUNCTION AND INTENDED USE.....	9
3.2	RATINGS AND SYSTEM DETAILS	9
3.3	INDEPENDENT OPERATION MODES	9
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS	9
3.5	SUBMITTED DOCUMENTS	9
4.	TEST SET-UP AND OPERATION MODES	10
4.1	PRINCIPLE OF CONFIGURATION SELECTION	10
4.2	TEST OPERATION AND TEST SOFTWARE.....	10
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	10
4.4	COUNTERMEASURES TO ACHIEVE ERM COMPLIANCE	10
5.	TEST RESULTS EMISSION	11
5.1	EMISSION IN THE FREQUENCY RANGE UP TO 30 MHz	11
5.1.1	<i>Conducted emissions.....</i>	<i>11</i>
5.2	EMISSION IN THE FREQUENCY RANGE ABOVE 30 MHz.....	14
5.2.1	<i>Radiated Emission</i>	<i>14</i>
6.	PHOTOGRAPHS OF THE TEST SET-UP.....	23
7.	LIST OF TABLES	26
8.	LIST OF PHOTOGRAPHS	26

1. General Remarks

1.1 Complementary Materials

None.

2. Test Sites

2.1 Test Facilities

Accurate Technology Co., Ltd.

(FCC Registration No.: 752051)

(Test site Industry Canada No.: 5077A-2)

F1, Bldg. A, Changyuan New Material Port
Keyuan Rd., Science & Industry Park, Nanshan
Shenzhen, P.R. China

Shenzhen Academy of Metrology and Quality Inspection

(FCC Registration No.: 979748)

(Test site Industry Canada No.: 144376)

NETC Building, No. 4 Tongfa Rd., Xili, Nanshan, Shenzhen, China

The tests at the test sites have been conducted under the supervision of a TÜV engineer.

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

Kind of Equipment	Manufacturer	Type	S/N	Calibrated until
Conducted Emission				
Test Receiver	Rohde & Schwarz	ESCS30	100307	2015-01-11
L.I.S.N.	Schwarzbeck	NLSK8126	8126431	2015-01-11
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100815	2015-01-11
50Ω Coaxial Switch	Anritsu Corp	MP59B	6200283933	2015-01-11
Radiated Emission				
Spectrum Analyzer	Agilent	E7405A	MY45115511	2015-01-11
Test Receiver	Rohde & Schwarz	ESCS30	100307	2015-01-11
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	2015-01-11
Loop Antenna	Schwarzbeck	FMZB1516	1516131	2015-01-11
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	2015-01-11
50 Coaxial Switch	Anritsu Corp	MP59B	6200506474	2015-01-11
Pre-Amplifier	Rohde & Schwarz	CBLU118354 0-01	3791	2015-01-11
RF Coaxial Cable (966 Chamber) (for below 1GHz test)	Suhner	N-3m	No.8	2015-01-11
RF Coaxial Cable (966 Chamber) (for below 1GHz test)	Resenberger	N-3.5m	No.9	2015-01-11
RF Coaxial Cable (966 Chamber) (for below 1GHz test)	Suhner	N-6m	No.10	2015-01-11
RF Coaxial Cable (966 Chamber) (for above 1GHz test)	Resenberger	N-12m	No.11	2015-01-11
RF Coaxial Cable (966 Chamber) (for above 1GHz test)	Resenberger	N-0.5m	No.12	2015-01-11
Radiated Emission (SMQ) (for 26.5 - 40GHz)				
EMI Receiver	Rohde & Schwarz	ESU40	SB8501/09	2015-05-14
Horn Antenna	Rohde & Schwarz	3160-10	SB8501/12	2014-08-15

2.3 Traceability

All measurement equipment calibrations are traceable to NIST or where calibration is performed outside the United States, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO/IEC 17025 are:

Table 2: Measurement Uncertainty

Items		Extended Uncertainty
Conducted Emission (0.15 - 30MHz)	Disturbance Voltage (dBuV)	$U=\pm 2.23\text{dB}$, $k=2$, $\sigma=95\%$
Radiated Emission (30 - 1000MHz)	Field strength (dBuV/m)	$U=\pm 4.42\text{dB}$, $k=2$, $\sigma=95\%$
Radiated Emission (1 - 26.5GHz)	Field strength (dBuV/m)	$U=\pm 4.06\text{dB}$, $k=2$, $\sigma=95\%$
Radiated Emission (26.5 - 40GHz)	Field strength (dBuV/m)	$U=\pm 5.54\text{dB}$, $k=2$, $\sigma=95\%$

2.6 Location of Original Data

The original copies of all test data taken during actual testing were retained in the TÜV Rheinland (Shenzhen) file for certification follow-up purposes.

Prüfbericht - Nr.: 17040437 005
*Test Report No.***Seite 7 von 26**
Page 7 of 26

2.7 Status of Facility Used for Testing

Accurate Technology Co., Ltd. test facility located at F1, Bldg. A, Changyuan New Material Port Keyuan Rd., Science & Industry Park, Nanshan, Shenzhen, P.R. China and Shenzhen Academy of Metrology and Quality Inspection test facility located at NETC Building, No. 4 Tongfa Rd., Xili, Nanshan, Shenzhen, China are listed on the US Federal Communications Commission list of facilities approved to perform measurements.

2.8 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test





Diagram of Measurement Equipment Configuration for Conduction Measurement



3. General Product Information

3.1 Product Function and Intended Use

The EUT is 10" tablet with Wi-Fi, Bluetooth & GPS function.
For details refer to the User Manual and Circuit Diagram.

3.2 Ratings and System Details

Table 3: Technical Specification of EUT

Technical Specification	Value
Kind of Equipment	Tablet
Type Designation	NS-15AT10
FCC ID	XUZNS-15AT10
IC	10558A-NS15AT10
Extreme Temperature Range	-30~+75°C
Operation Voltage	DC 3.7V (via built in battery)
	DC 5V (via AC/DC adapter)

3.3 Independent Operation Modes

The basic operation modes are:

- A. On, connecting to PC
- B. Standby
- C. Off

3.4 Noise Generating and Noise Suppressing Parts

Refer to the Circuit Diagram.

3.5 Submitted Documents

- Bill of Material
- Constructional Drawing
- PCB Layout
- Photo Document
- Circuit Diagram
- Instruction Manual
- Rating Label

4. Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

The equipment under test (EUT) was configured to measure its maximum power level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All testing were performed according to the procedures in ANSI C63.4: 2003.

4.3 Special Accessories and Auxiliary Equipment

The EUT was tested together with the following accessories:

Description	Manufacturer	Part No.	S/N
Notebook PC	Lenovo	4290-RT8	R9-FW93G
Printer	HP	HP laserjet 1015	CNFG030424

The EUT was tested with following cables:

Interface(s)/Port(s):	Max. cable length, shielding	Cable classification
Micro USB port	4 cores, non-shielded port, 3m	DC Power Input

4.4 Countermeasures to Achieve ERM Compliance

The test sample which has been tested contained the noise suppression parts as described in the Technical Construction File (TCF). No additional measures were employed to achieve compliance.

5. Test Results EMISSION

5.1 Emission in the Frequency Range up to 30 MHz

5.1.1 Conducted emissions

RESULT:**Pass**

Date of testing	:	2014-05-26
Test standard	:	FCC Part 15.107 (a) ICES-003 Issue 5 August 2012
Basic standard	:	ANSI C63.4: 2003
Frequency range	:	0.15 – 30MHz
Limits	:	FCC Part 15.107(a) ICES-003 Issue 5 August 2012
Kind of test site	:	Shield room

Test setup

Input Voltage	:	AC 120V, 60Hz
Operation Mode	:	A
Earthing	:	Not Connected
Ambient temperature	:	25°C
Relative humidity	:	52%
Atmospheric pressure	:	101kPa


For details refer to following test plot.

ACCURATE TECHNOLOGY CO.,LTD
CONDUCTED EMISSION STANDARD FCC PART 15 B

EUT: Tablet M/N:NS-15AT10
 Manufacturer: Keen High
 Operating Condition: Transfer data
 Test Site: 1#Shielding Room
 Operator: LAN
 Test Specification: L 120V/60Hz
 Comment:
 Start of Test: 5/26/2014 / 9:26:35AM

SCAN TABLE: "V 150K-30MHz fin"

Short Description: _SUB_STD_VTERM2 1.70
 Start Stop Step Detector Meas. IF Transducer
 Frequency Frequency Width Time Bandw.
 150.0 kHz 30.0 MHz 4.5 kHz QuasiPeak 1.0 s 9 kHz NSLK8126 2008
 Average


MEASUREMENT RESULT: "A-0526-09_fin"

5/26/2014 9:36AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.178803	55.80	10.5	65	8.7	QP	L1	GND
0.230851	47.70	10.6	62	14.7	QP	L1	GND
2.877655	37.40	11.0	56	18.6	QP	L1	GND

MEASUREMENT RESULT: "A-0526-09_fin2"

5/26/2014 9:36AM


Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.193664	35.20	10.5	54	18.7	AV	L1	GND
0.233633	31.20	10.6	52	21.1	AV	L1	GND
3.055234	28.60	11.1	46	17.4	AV	L1	GND

ACCURATE TECHNOLOGY CO.,LTD
CONDUCTED EMISSION STANDARD FCC PART 15 B

EUT: Tablet M/N:NS-15AT10
 Manufacturer: Keen High
 Operating Condition: Transfer data
 Test Site: 1#Shielding Room
 Operator: LAN
 Test Specification: N 120V/60Hz
 Comment:
 Start of Test: 5/26/2014 / 9:37:18AM

SCAN TABLE: "V 150K-30MHz fin"

Short Description: _SUB_STD_VTERM2 1.70
 Start Stop Step Detector Meas. IF Transducer
 Frequency Frequency Width Time Bandw.
 150.0 kHz 30.0 MHz 4.5 kHz QuasiPeak 1.0 s 9 kHz NSLK8126 2008
 Average


MEASUREMENT RESULT: "A-0526-10_fin"

5/26/2014 9:45AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.177381	55.20	10.5	65	9.4	QP	N	GND
0.189837	53.20	10.5	64	10.8	QP	N	GND
3.443942	38.20	11.1	56	17.8	QP	N	GND

MEASUREMENT RESULT: "A-0526-10_fin2"

5/26/2014 9:45AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.181681	38.20	10.5	54	16.2	AV	N	GND
0.192124	34.70	10.5	54	19.2	AV	N	GND
3.154381	29.00	11.1	46	17.0	AV	N	GND

5.2 Emission in the Frequency Range above 30 MHz

5.2.1 Radiated Emission

RESULT:**Pass**

Date of testing	:	2014-06-08
Test standard	:	FCC Part 15.109 (a) ICES-003 Issue 5 August 2012
Test procedure	:	ANSI C63.4: 2003
Frequency range	:	30 - 40000MHz
Equipment Classification	:	Class B
Limits	:	FCC Part 15.109(a) ICES-003 Issue 5 August 2012
Kind of test site	:	3m Semi-Anechoic Chamber

Test setup

Input Voltage	:	AC 120V, 60Hz
Operation mode	:	A
Earthing	:	Not connected
Ambient temperature	:	25°C
Relative humidity	:	52%
Atmospheric pressure	:	101kPa

For details refer to following test plot.


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel: +86-0755-26503290

Fax: +86-0755-26503396

Job No.: LAN2014 #144

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Tablet

Mode: Transfer data

Model: NS-15AT10

Manufacturer: Keen High

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 2014/05/26

Time:

Engineer Signature: PEI

Distance:

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	171.4043	53.30	-13.67	39.63	43.50	-3.87	QP			
2	242.7927	44.52	-10.82	33.70	46.00	-12.30	QP			
3	446.1299	40.34	-5.84	34.50	46.00	-11.50	QP			


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LAN2014 #143

Polarization: Vertical

Standard: FCC Class B 3M Radiated

Power Source: AC 120V/60Hz

Test item: Radiation Test

Date: 2014/05/26

Temp.(C)/Hum.(%) 23 C / 48 %

Time:

EUT: Tablet

Engineer Signature: PEI


Mode: Transfer data

Distance:

Model: NS-15AT10

Manufacturer: Keen High

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	46.2180	49.44	-12.63	36.81	40.00	-3.19	QP			
2	171.4380	52.31	-13.67	38.64	43.50	-4.86	QP			
3	703.7314	36.75	-1.68	35.07	46.00	-10.93	QP			


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LAN2014 #146

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Tablet

Mode: Transfer data

Model: NS-15AT10

Manufacturer: Keen High

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 2014/05/25

Time:

Engineer Signature: PEI

Distance:

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	12257.686	9.70	38.16	47.86	74.00	-26.14	peak			
2	12257.686	0.69	38.16	38.85	54.00	-15.15	AVG			


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel: +86-0755-26503290

Fax: +86-0755-26503396

Job No.: LAN2014 #145

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Tablet

Mode: Transfer data

Model: NS-15AT10

Manufacturer: Keen High

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2014/05/25

Time:

Engineer Signature: PEI

Distance:

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	12222.059	9.72	38.12	47.84	74.00	-26.16	peak			
2	12222.059	0.27	38.12	38.39	54.00	-15.61	AVG			


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China


Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: PZ #524	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/06/08/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: Tablet	Engineer Signature: PEI
Mode: Transfer data	Distance:
Model: NS-15AT10	
Manufacturer: Keen High	

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	25961.241	33.81	18.71	52.52	74.00	-21.48	peak			
2	25961.241	20.64	18.71	39.35	54.00	-14.65	AVG			


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China


Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: PZ #523	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/06/08/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: Tablet	Engineer Signature: PEI
Mode: Transfer data	Distance:
Model: NS-15AT10	
Manufacturer: Keen High	

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26021.678	33.99	18.73	52.72	74.00	-21.28	peak			
2	26021.678	20.35	18.73	39.08	54.00	-14.92	AVG			

Test

1 / 1

Radiated Emission


EUT Information

EUT Model Name:	Tablet M/N: NS-15AT10
Operation mode:	Transfer data
Test Voltage:	AC 120V/60Hz
Comment:	

Common Information

Test Site:	SMQ EMC Lab.
Environment Conditions:	
Antenna Polarization:	Horizontal
Operator Name:	
Comment:	

Copy of FCC Electric Field Strength 26.5-40GHz



Test

1 / 1

Radiated Emission


EUT Information

EUT Model Name:	Tablet M/N: NS-15AT10
Operation mode:	Transfer data
Test Voltage:	AC 120V/60Hz
Comment:	

Common Information

Test Site:	SMQ EMC Lab.
Environment Conditions:	
Antenna Polarization:	Vertical
Operator Name:	
Comment:	

Copy of FCC Electric Field Strength 26.5-40GHz




6. Photographs of the Test Set-Up


Photograph 1: Set-up for Conducted Emission




Photograph 2: Set-up for Radiated Emission of below 1GHz




Photograph 3: Set-up for Radiated Emission of 1 - 18GHz



Photograph 4: Set-up for Radiated Emission of 18 - 26.5GHz



Photograph 5: Set-up for Radiated Emission of 26.5 - 40GHz



7. List of Tables

Table 1: List of Test and Measurement Equipment.....	5
Table 2: Measurement Uncertainty	6
Table 3: Technical Specification of EUT.....	9

8. List of Photographs

Photograph 1: Set-up for Conducted Emission	23
Photograph 2: Set-up for Radiated Emission of below 1GHz	23
Photograph 3: Set-up for Radiated Emission of 1 - 18GHz.....	24
Photograph 4: Set-up for Radiated Emission of 18 - 26.5GHz	24
Photograph 5: Set-up for Radiated Emission of 26.5 - 40GHz	25