

APPROVAL SHEET

MESSRS. (주)아이디로

ITEM : Ceramic Patch Antenna


PART NAME : MPAC34SC922SS-TA

MODEL NAME : IDROWC-100

REVISION : 0

ISSUE DATE : February 29, 2024

LAST SAVED : February 29, 2024

BUYER : (주)아이디로	SUPPLIER : MAC technologies Inc.		
ACKNOWLEDGED BY	DRAWN	CHECKED	APPROVED
			



615, 530, Jikji-daero,

Heungdeok-gu, Cheongju-si, Chungbuk, KOREA, 28578

Tel : +82 43 275 2485 Fax : +82 43 275 2487

Title	RFID Ceramic Patch Ant. Specification
Document Number	MAC-08-02-05-24002
Revision & Date	0 & February 29, 2024
Issue Date	February 29, 2024

Table of Contents

	Page
1. Scope	4
2. Part Name Information	4
3. Composition and Materials	4
4. Mechanical Dimensions	5
5. Electrical Specifications	6
6. Test Fixture	6
7. S11 Measurement Data	7
8. Environmental Specifications	8
9. Radiation Patterns	9~11
10. Remark	12

Title	RFID Ceramic Patch Ant. Specification
Document Number	MAC-08-02-05-24002
Revision & Date	0 & February 29, 2024
Issue Date	February 29, 2024

1. Scope.

This specification covers the characteristics of the ceramic patch antenna element for the ISM band.

2. Part Name Information.

Part Name : **M PA C 34S C 922 SS - TA**
 ① ② ③ ④ ⑤ ⑥ ⑦ ⑧

- ① : MAC technologies Inc.
- ② : Patch Antenna
- ③ : Hole Location - Center type (D : Diagonal type)
- ④ : 34 mm Square (Size)
- ⑤ : 4 mm Thickness (A : 2 mm, B : 3 mm, C : 4 mm, D : 5 mm ...)
- ⑥ : Center Frequency : 922 MHz ($\pm$ 2 MHz)
- ⑦ : Ground Plane – SS : 78 x 78 **S**pecial Ground, **S**pecial Characteristic Graph
- ⑧ : Assembly – PCB


3. Composition and Materials.

- 3-1. Ceramic Substrate : $\epsilon_r = 37.0 \pm 1.5$
- 3-2. Electrode Plating : Silver
- 3-3. Terminal pin : Brass with Silver coating
- 3-4. Antenna Color : Ceramics antenna color alteration is possible


Title	RFID Ceramic Patch Ant. Specification
Document Number	MAC-08-02-05-24002
Revision & Date	0 & February 29, 2024
Issue Date	February 29, 2024

4. Mechanical Dimensions. (unit : mm)

4-1. Antenna Element (The color of ceramic substrates can be changed.)



4-2. PCB Ass'y




Title	RFID Ceramic Patch Ant. Specification
Document Number	MAC-08-02-05-24002
Revision & Date	0 & February 29, 2024
Issue Date	February 29, 2024

5. Electrical Specifications.

NO.	Parameter	Spec.		Unit	Remark
		Ant. Element (@ 78×78 GND Plane)	Set Ass'y		
1	Center Frequency	922.0 ± 2	919.0 ± 2	MHz	
2	Peak Gain	typ.	-2.5 typ.	dBiL	@ Set Ass,y
		typ.	0 typ.	dBiC	
3	Polarization	RHCP	RHCP		
4	Beam Width	typ.	120 typ.	Deg.	@ -3 dB B.W
5	Band Width	typ.	8 typ.	MHz	@ -5 dB R.L
6	VSWR	max.	2.0 : 1 max.	Ratio	
7	Impedance	50	50	Ohm	


6. Test Fixture.




Title	RFID Ceramic Patch Ant. Specification
Document Number	MAC-08-02-05-24002
Revision & Date	0 & February 29, 2024
Issue Date	February 29, 2024

7. S11 Measurement Data.

7-1. 78x78 mm Ground Plane



7-2. Set Ass'y



Title	RFID Ceramic Patch Ant. Specification
Document Number	MAC-08-02-05-24002
Revision & Date	0 & February 29, 2024
Issue Date	February 29, 2024

8. Environmental Specifications.

** Operation conditions : Temperature range : -30 °C ~ +85 °C

Humidity range : 45 ~ 85 % RH

The device should satisfy the electrical characteristics specified in paragraph 5 after the following tests.

Measurements should be done after putting in the typical condition (20~30 °C / 55~75 % RH) for 2 hours minimum.

8-1. Temperature Characteristics

The device should satisfy the electrical characteristics specified in paragraph 5 at the temperature range of -30 °C ~ +85 °C.

8-2. Heat Proof

The device should satisfy the electrical characteristics specified in paragraph 5 after exposed to the temperature 85 ± 2 °C for 72 hours.

8-3. Cold Proof

The device should satisfy the electrical characteristics specified in paragraph 5 after exposed to the temperature -30 ± 2 °C for 72 hours.


8-4. Moisture Proof

The device should satisfy the electrical characteristics specified in paragraph 5 after exposed to the temperature 40 ± 2 °C and the humidity 95 % RH for 72 hours.


Title	RFID Ceramic Patch Ant. Specification
Document Number	MAC-08-02-05-24002
Revision & Date	0 & February 29, 2024
Issue Date	February 29, 2024

9. Radiation Patterns after Set Ass'y

9-1. H-pol (Frequency 917.0, 919.0, 921.0, 923.0 MHz)



9-2. V-pol (Frequency 917.0, 919.0, 921.0, 923.0 MHz)



Title	RFID Ceramic Patch Ant. Specification
Document Number	MAC-08-02-05-24002
Revision & Date	0 & February 29, 2024
Issue Date	February 29, 2024

9-5. List of Equipments (MAC technologies Inc.)

NO	Equipments	Maker	Model No.	S/N	Specification	Note
1	Anechoic Chamber	MTG	Mobile Chamber		4.0 m X 2.5 m X 2.5 m (0.4 ~ 3 GHz)	
2	Network Analyzer	Agilent	8753ES	US39173213	30 KHz ~ 6 GHz	
3	Dual-Polarization Horn Antenna with RF Switch	MTG	QRH-004060/ RSW-001060		0.4 GHz ~ 6 GHz	Source
4	Calibration Antenna	Schwarzbeck Mess - Elektronik	BBHA 9120 A	1201	0.8 GHz ~ 5 GHz	Reference
5	Absorber Installation	EMERSON & CUMING	SABS-003 18"		Reflectivity : -25 dB @ 0.8 GHz -30 dB @ 1.0 GHz	

Title	RFID Ceramic Patch Ant. Specification
Document Number	MAC-08-02-05-24002
Revision & Date	0 & February 29, 2024
Issue Date	February 29, 2024

10. Remark.

- If there is any doubt in this specification and product, it should be resolved between made and manufacture.
- Don't handling by unarmed.
- No responsibility is assumed by us for any consequence resulting from any wrong or improper use or operation, etc. of the product.
- No part of the contents contained herein may be reprinted or re-produced without our prior permission.