

TCB**GRANT OF EQUIPMENT
AUTHORIZATION****TCB****Certification****Issued Under the Authority of the
Federal Communications Commission****By:****SGS North America, Inc.
620 Old Peachtree Road NW Suite 100
Suwanee, GA 30024****Date of Grant: 11/07/2016****Application Dated: 11/07/2016****LM Technologies Ltd.****Sierra Quebec Bravo, 2nd Floor, 77 Marsh Wall****London, E14 9SH****United Kingdom****Attention: Penelope Victoria , CEO****NOT TRANSFERABLE**

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is
VALID ONLY for the equipment identified hereon for use under the Commission's
Rules and Regulations listed below.

FCC IDENTIFIER: VVX-LM811-04XX**Name of Grantee: LM Technologies Ltd.****Equipment Class: Part 15 Spread Spectrum Transmitter****Notes: LM811****Modular Type: Single Modular**

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
	15C	2402.0 - 2480.0	0.0033		

Power Output listed is conducted. Single Modular Approval. This module can only be used with a host antenna circuit trace layout design in strict compliance with the OEM instructions provided. This device is to be used only for mobile and fixed application. The antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter, except in accordance with FCC multi-transmitter evaluation procedures as documented in this filing. End-Users must be provided with transmitter operation conditions for satisfying RF exposure compliance. OEM integrators must insure that the end user has no manual instructions to remove or install this module. For mobile and fixed operating configurations the antenna gain, including cable loss, must not exceed 6 dBi for satisfying RF exposure compliance according to as defined in 2.1091.